

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

BEVERLY EAVES PERDUE GOVERNOR EUGENE A. CONTI, JR. SECRETARY

December 20, 2011

NOTICE TO: All Prequalified Contractors and Subcontractors

FROM: R.A. Garris, PE

State Contract Officer

SUBJECT: Davis-Bacon Wage Determinations

On September 30, 2011, the U.S. Department of Labor (USDOL) published and put into effect new Davis-Bacon Wage Determinations. Please pay close attention to these wage determinations as significant changes have been made to the rates. The following projects advertised in the January 17, 2012 highway letting include the new Davis-Bacon Wage Determinations:

| B-4090 | Cumberland | C202724 | BP-5300N | Haywood | C202899 |
|---------|------------|---------|-----------|----------------|---------|
| B-4415 | Beaufort | C202727 | BP-5300R | Guilford | C202806 |
| B-4456 | Catawba | C202729 | I-5307, | Wake | C202875 |
| | | | I-5310 | | |
| B-4463 | Chowan | C202908 | R-2309AB, | Guilford | C200800 |
| | | | R-2413C | (8-week Ad) | |
| B-4473 | Columbus | C202737 | R-2554BB, | Wayne | C202771 |
| | | | R-2554C | (Design Build) | |
| B-4503 | Edgecombe | C202730 | R-5102 | Jackson | C202876 |
| B-4514 | Franklin | C202747 | R-5103 | Jackson | C202877 |
| B-4551 | Hyde | C202910 | R-5517 | Currituck | C202808 |
| B-4556, | Johnston | C202739 | U-624 | Orange | C202156 |
| B-4560 | | | | | |
| B-4647 | Tyrrell | C202750 | U-3326A, | Rockingham | C202652 |
| | | | U-3326B | | |
| B-4657 | Wake | C202733 | U-3812 | Ashe | C202744 |
| BK-5128 | Carteret | C202873 | U-4909 | Forsyth | C202745 |
| BK-5129 | Brunswick | C202874 | U-5168 | Onslow | C202576 |

TELEPHONE: 919-707-6900

FAX: 919-250-4119

WEBSITE: www.NCDOT.ORG

In the proposal, the wage rates provision appears before the Proposal Item Sheets.



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

BEVERLY EAVES PERDUE
GOVERNOR

EUGENE A. CONTI, JR. SECRETARY

December 20, 2011

NOTICE TO: All Prequalified Bidders

FROM: R. A. Garris, P.E.

State Contract Engineer

SUBJECT: Revision of the "Mechanically Stabilized Earth Retaining

Walls" Project Special Provision

Beginning with the January 17, 2012 letting, the above subject Project Special Provision (PSP) is to be effective on State and Federal funded contracts with mechanically stabilized earth (MSE) retaining walls.

The MSE retaining walls provision has been completely revised for the 2012 *Standard Specifications for Roads and Structures*, traffic impact analysis, fine aggregate and other issues. The Department encourages you to read the PSP as there are numerous and extensive changes.

The most significant changes are associated with the use of fine aggregate instead of coarse aggregate for critical MSE retaining walls. The Department will now allow fine aggregate in the reinforced zone of some critical walls with the required fine aggregate sampling and testing and carbon steel corrosion rates. Attached for your convenience is a copy of this PSP.

If you have any questions about the MSE Retaining Walls PSP, contact Scott Hidden, P.E. or Njoroge Wainaina, P.E. of the Geotechnical Engineering Unit at 919-707-6850.

Attachment

1.0 GENERAL

Construct mechanically stabilized earth (MSE) retaining walls consisting of steel or geogrid reinforcements in the reinforced zone connected to vertical facing elements. The facing elements may be precast concrete panels or segmental retaining wall (SRW) units unless required otherwise in the plans or the *NCDOT Policy for Mechanically Stabilized Earth Retaining Walls* prohibits the use of SRW units. At the Contractor's option, use coarse or fine aggregate in the reinforced zone of MSE retaining walls except do not use fine aggregate for walls subject to scour, walls that support or are adjacent to railroads or walls with design heights greater than 35 ft or internal acute corners less than 45°. Provide reinforced concrete coping as required. Design and construct MSE retaining walls based on actual elevations and wall dimensions in accordance with the contract and accepted submittals. Use a prequalified MSE Wall Installer to construct MSE retaining walls.

Define "MSE wall" as a mechanically stabilized earth retaining wall and "MSE Wall Vendor" as the vendor supplying the chosen MSE wall system. Define a "segmental retaining wall" as an MSE wall with SRW units and an "abutment wall" as an MSE wall with bridge foundations in the reinforced zone. Define "reinforcement" as steel or geogrid reinforcement and "aggregate" as coarse or fine aggregate. Define "panel" as a precast concrete panel and "coping" as precast or cast-in-place concrete coping.

Use an approved MSE wall system in accordance with the plans, NCDOT MSE wall policy and any NCDOT restrictions for the chosen system. Value engineering proposals for other MSE wall systems will not be considered. Do not use segmental retaining walls or MSE wall systems with an "approved for provisional use" status code for critical walls or MSE walls connected to critical walls. Critical walls are defined in the NCDOT MSE wall policy. The list of approved MSE wall systems and NCDOT MSE wall policy are available from:

www.ncdot.org/doh/preconstruct/highway/geotech/msewalls

2.0 MATERIALS

Refer to the Standard Specifications.

| Item | Section |
|--------------------------------|---------|
| Aggregate | 1014 |
| Anchor Pins | 1056-2 |
| Curing Agents | 1026 |
| Geotextiles | 1056 |
| Joint Materials | 1028 |
| Portland Cement Concrete | 1000 |
| Precast Retaining Wall Coping | 1077 |
| Reinforcing Steel | 1070 |
| Retaining Wall Panels | 1077 |
| Segmental Retaining Wall Units | 1040-4 |
| Shoulder Drain Materials | 816-2 |

Wire Staples 1060-8(D)

Provide Type 2 geotextile for filtration and separation geotextiles. Use Class A concrete for cast-in-place coping, leveling concrete and pads.

Provide panels and SRW units produced by a manufacturer approved or licensed by the MSE Wall Vendor. Unless required otherwise in the contract, produce panels with a smooth flat final finish that meets Article 1077-11 of the *Standard Specifications*. Accurately locate and secure reinforcement connectors in panels and maintain required concrete cover. Produce panels within 1/4" of the panel dimensions shown in the accepted submittals.

Damaged panels or SRW units with excessive discoloration, chips or cracks as determined by the Engineer will be rejected. Do not damage reinforcement connection devices or mechanisms in handling or storing panels and SRW units.

Store steel materials on blocking at least 12" above the ground and protect it at all times from damage; and when placing in the work make sure it is free from dirt, dust, loose mill scale, loose rust, paint, oil or other foreign materials. Handle and store geogrids in accordance with Article 1056-2 of the *Standard Specifications*. Load, transport, unload and store MSE wall materials so materials are kept clean and free of damage.

A. Aggregate

Use standard size No. 57, 57M, 67 or 78M that meets Table 1005-1 of the *Standard Specifications* for coarse aggregate except do not use No. 57 or 57M stone in the reinforced zone of MSE walls with geogrid reinforcement. Use the following for fine aggregate:

- 1. Standard size No. 1S, 2S, 2MS or 4S that meets Table 1005-2 of the *Standard Specifications* or
- 2. Gradation that meets Class III, Type 3 select material in accordance with Article 1016-3 of the *Standard Specifications*.

Fine aggregate is exempt from mortar strength and siliceous particle content referenced in Subarticles 1014-1(E) and 1014-1(H) of the *Standard Specifications*. Provide fine aggregate that meets the following requirements:

FINE AGGREGATE REQUIREMENTS

| Reinforcement or Connector Material | pН | Resistivity | Chlorides | Sulfates | Organics |
|-------------------------------------|------|--------------------------------|------------------------|----------------|-------------|
| Steel | 5-10 | \geq 3,000 $\Omega \cdot cm$ | $\leq 100 \text{ ppm}$ | \leq 200 ppm | ≤1% |
| Geogrid | 5-8 | N/A* | N/A* | N/A* | ≤1 % |

^{*} Resistivity, chlorides and sulfates are not applicable to geogrid.

Use fine aggregate from a source that meets the Mechanically Stabilized Earth Wall Fine Aggregate Sampling and Testing Manual. Perform organic content tests in

accordance with AASHTO T 267 instead of Subarticle 1014-1(D) of the *Standard Specifications*. Perform electrochemical tests in accordance with the following test procedures:

| Property | Test Method |
|-------------|--------------|
| pH | AASHTO T 289 |
| Resistivity | AASHTO T 288 |
| Chlorides | AASHTO T 291 |
| Sulfates | AASHTO T 290 |

B. Reinforcement

Provide steel or geogrid reinforcement supplied by the MSE Wall Vendor or a manufacturer approved or licensed by the vendor. Use approved reinforcement for the chosen MSE wall system. The list of approved reinforcement for each MSE wall system is available from the website shown elsewhere in this provision.

1. Steel Reinforcement

Provide Type 1 material certifications in accordance with Article 106-3 of the *Standard Specifications* for steel reinforcement. Use welded wire grid reinforcement ("mesh", "mats" and "ladders") that meet Article 1070-3 of the *Standard Specifications* and metallic strip reinforcement ("straps") that meet ASTM A572 or A1011. Galvanize steel reinforcement in accordance with Section 1076 of the *Standard Specifications*.

2. Geogrid Reinforcement

Define "machine direction" (MD) for geogrids in accordance with ASTM D4439. Provide Type 1 material certifications for geogrid strengths in the MD in accordance with Article 1056-3 of the *Standard Specifications*. Test geogrids in accordance with ASTM D6637.

C. Bearing Pads

Use bearing pads that meet Section 3.6.1.a of the FHWA Design and Construction of Mechanically Stabilized Earth Walls and Reinforced Soil Slopes – Volume I (Publication No. FHWA-NHI-10-024).

D. Miscellaneous Components

Miscellaneous components may include connectors (e.g., anchors, bars, clamps, pins, plates, ties, etc.), fasteners (e.g., bolts, nuts, washers, etc.) and any other MSE wall components not included above. Galvanize steel components in accordance with Section 1076 of the *Standard Specifications*. Provide approved miscellaneous components for the chosen MSE wall system. The list of approved miscellaneous components for each MSE wall system is available from the website shown elsewhere in this provision.

3.0 PRECONSTRUCTION REQUIREMENTS

A. MSE Wall Surveys

The Retaining Wall Plans show a plan view, typical sections, details, notes and an elevation or profile view (wall envelope) for each MSE wall. Before beginning MSE wall design, survey existing ground elevations shown in the plans and other elevations in the vicinity of MSE wall locations as needed. Based on these elevations, finished grades and actual MSE wall dimensions and details, submit revised wall envelopes for acceptance. Use accepted wall envelopes for design.

B. MSE Wall Designs

Submit 11 copies of working drawings and 3 copies of design calculations and a PDF copy of each for MSE wall designs at least 30 days before the preconstruction meeting. Do not begin MSE wall construction until a design submittal is accepted.

Use a prequalified MSE Wall Design Consultant to design MSE walls. Provide designs sealed by a Design Engineer approved as a Geotechnical Engineer (key person) for the MSE Wall Design Consultant.

Design MSE walls in accordance with the plans, AASHTO LRFD Bridge Design Specifications and any NCDOT restrictions for the chosen MSE wall system unless otherwise required. Design MSE walls for seismic if walls are located in seismic zone 2 in accordance with Figure 2-1 of the Structure Design Manual. Use a uniform reinforcement length throughout the wall height of at least 0.7H with H as defined for the embedment requirements in this provision or 6 ft, whichever is greater, unless shown otherwise in the plans. Extend the reinforced zone at least 6" beyond end of reinforcement. Do not locate drains, the reinforced zone or leveling pads outside right-of-way or easement limits.

Use the simplified method for determining maximum reinforcement loads and approved design parameters for the chosen MSE wall system or default values in accordance with the AASHTO LRFD specifications. Design steel components including reinforcement and connectors for the design life noted in the plans and aggregate type in the reinforced zone. Use corrosion loss rates for galvanizing in accordance with the AASHTO LRFD specifications for nonaggressive backfill and carbon steel corrosion rates in accordance with the following:

CARBON STEEL CORROSION RATES

| Aggregate Type | Corrosion Loss Rate | | |
|------------------------------|------------------------|--|--|
| (in the reinforced zone) | (after zinc depletion) | | |
| Coarse | 0.47 mil/year | | |
| Fine (except abutment walls) | 0.58 mil/year | | |
| Fine (abutment walls) | 0.70 mil/year | | |

For geogrid reinforcement and connectors, use approved geogrid properties for the

design life noted in the plans and aggregate type in the reinforced zone.

When noted in the plans, design MSE walls for a live load (traffic) surcharge of 250 lb/sf in accordance with Figure C11.5.5-3(b) of the AASHTO LRFD specifications. For steel beam guardrail with 8 ft posts or concrete barrier rail above MSE walls, analyze top 2 reinforcement layers for traffic impact loads in accordance with Section 7.2 of the FHWA MSE wall manual shown elsewhere in this provision except use the following for geogrid reinforcement rupture:

| | | $\phi T_{al} R_c \ge T_{max} + (T_I / RF_{CR})$ |
|------------------|---|--|
| Where, | | |
| ф | | resistance factor for tensile resistance in accordance with Section 7.2.1 of the FHWA MSE wall manual, |
| T_{al} | = | long-term geogrid design strength approved for chosen MSE wall system, |
| R_c | = | reinforcement coverage ratio = 1 for continuous geogrid reinforcement, |
| T_{max} | = | factored static load in accordance with Section 7.2 of the FHWA MSE wall manual, |
| T_{I} | = | factored impact load in accordance with Section 7.2 of the FHWA MSE wall manual, and |
| RF_{CR} | = | creep reduction factor approved for chosen MSE wall system. |

If existing or future obstructions such as foundations, guardrail, fence or handrail posts, moment slabs, pavements, pipes, inlets or utilities will interfere with reinforcement, maintain a clearance of at least 3" between obstructions and reinforcement unless otherwise approved. Locate reinforcement layers so all of reinforcement length is within 3" of corresponding connection elevations.

Use 6" thick cast-in-place unreinforced concrete leveling pads beneath panels and SRW units that are continuous at steps and extend at least 6" in front of and behind bottom row of panels or SRW units. Unless required otherwise in the plans, embed top of leveling pads in accordance with the following requirements:

EMBEDMENT REQUIREMENTS

| Front Slope ¹ (H:V) | Minimum Embedment Depth ² (whichever is greater) | | |
|--|---|--|--|
| 6:1 or flatter (except abutment walls) | H/20 | 1 ft for $H \le 10$ ft 2 ft for $H > 10$ ft | |
| 6:1 or flatter (abutment walls) | H/10 | 2 ft | |
| > 6:1 to < 3:1 | H/10 | 2 ft | |
| 3:1 to 2:1 | H/7 | 2 ft | |

- 1. Front slope shown in the plans.
- 2. Define "H" as the maximum design height plus embedment per wall with the design height and embedment as shown in the plans.

When noted in the plans, locate a continuous aggregate shoulder drain along base of

reinforced zone behind aggregate. Provide wall drainage systems consisting of drains and outlet components in accordance with Standard Drawing No. 816.02 of the Roadway Standard Drawings.

For MSE walls with panels, place at least 2 bearing pads in each horizontal panel joint so the final horizontal joint opening is between 5/8" and 7/8". Additional bearing pads may be required for panels wider than 5 ft as determined by the Engineer. Cover joints at back of panels with filtration geotextiles at least 12" wide.

For segmental retaining walls, fill SRW unit core spaces with coarse aggregate and between and behind SRW units with coarse aggregate for a horizontal distance of at least 18".

Separation geotextiles are required between aggregate and overlying fill or pavement sections except when concrete pavement, full depth asphalt or cement treated base is placed directly on aggregate. Separation geotextiles may also be required between coarse aggregate and backfill or natural ground as determined by the Engineer.

Unless required otherwise in the plans, use reinforced concrete coping at top of walls. Extend coping at least 6" above where the grade intersects back of coping unless required otherwise in the plans. Use coping dimensions shown in the plans and cast-in-place concrete coping for segmental retaining walls and when noted in the plans. At the Contractor's option, connect cast-in-place concrete coping to panels and SRW units with dowels or extend coping down back of MSE walls. Also, connect cast-in-place leveling concrete for precast concrete coping to panels with dowels. When concrete barrier rail is required above MSE walls, use concrete barrier rail with moment slab as shown in the plans.

Submit working drawings and design calculations for acceptance in accordance with Article 105-2 of the Standard Specifications. Submit working drawings showing plan views, wall profiles with required resistances, typical sections with reinforcement and connection details, aggregate locations and types, geotextile locations and details of leveling pads, panels or SRW units, coping, bin walls, slip joints, etc. If necessary, include details on working drawings for concrete barrier rail with moment slab, geogrid splices if allowed for the chosen MSE wall system, reinforcement connected to end bent caps and obstructions extending through walls or interfering with reinforcement, leveling pads, barriers or moment slabs. Submit design calculations for each wall section with different surcharge loads, geometry or material parameters. At least one analysis is required for each wall section with different reinforcement lengths. When designing MSE walls with computer software other than MSEW, use MSEW version 3.0 with update 14.2 or later, manufactured by ADAMA Engineering, Inc. to verify the design. At least one MSEW analysis is required per 100 ft of wall length with at least one MSEW analysis for the wall section with the longest reinforcement length. Submit electronic MSEW input files and PDF output files with design calculations.

C. Preconstruction Meeting

Before starting MSE wall construction, hold a preconstruction meeting to discuss the construction and inspection of the MSE walls. Schedule this meeting after all MSE wall submittals have been accepted. The Resident or Bridge Maintenance Engineer, Bridge Construction Engineer, Geotechnical Operations Engineer, Contractor and MSE Wall Installer Superintendent will attend this preconstruction meeting.

4.0 Corrosion Monitoring

Corrosion monitoring is required for MSE walls with steel reinforcement. The Engineer will determine the number of monitoring locations and where to install the instrumentation. Contact the Materials and Tests (M&T) Unit before beginning wall construction. M&T will provide the corrosion monitoring instrumentation kits and if necessary, assistance with installation.

5.0 SITE ASSISTANCE

Unless otherwise approved, provide an MSE Wall Vendor representative to assist and guide the MSE Wall Installer on-site for at least 8 hours when the first panels or SRW units and reinforcement layer are placed. If problems are encountered during construction, the Engineer may require the vendor representative to return to the site for a time period determined by the Engineer.

6.0 Construction Methods

Control drainage during construction in the vicinity of MSE walls. Direct run off away from MSE walls, aggregate and backfill. Contain and maintain aggregate and backfill and protect material from erosion.

Excavate as necessary for MSE walls in accordance with the accepted submittals. If applicable and at the Contractor's option, use temporary shoring for wall construction instead of temporary slopes to construct MSE walls. Define "temporary shoring for wall construction" as temporary shoring not shown in the plans or required by the Engineer including shoring for OSHA reasons or the Contractor's convenience.

Unless required otherwise in the plans, install foundations located in the reinforced zone before placing aggregate or reinforcement. Notify the Engineer when foundation excavation is complete. Do not place leveling pad concrete, aggregate or reinforcement until excavation dimensions and foundation material are approved.

Construct cast-in-place concrete leveling pads at elevations and with dimensions shown in the accepted submittals and in accordance with Section 420 of the *Standard Specifications*. Cure leveling pads at least 24 hours before placing panels or SRW units.

Erect and support panels and stack SRW units with no negative batter (wall face leaning forward) so the final wall position is as shown in the accepted submittals. Place SRW units with a maximum vertical joint width of 3/8".

Set panels with a vertical joint width of 3/4". Place bearing pads in horizontal panel joints

and cover all panel joints with filtration geotextiles as shown in the accepted submittals. Attach filtration geotextiles to back of panels with adhesives, tapes or other approved methods.

Stagger panels and SRW units to create a running bond by centering panels or SRW units over joints in the row below as shown in the accepted submittals. Construct MSE walls with the following tolerances:

- A. SRW units are level from front to back and between units when checked with a 3 ft long level,
- B. Final wall face is within 3/4" of horizontal and vertical alignment shown in the accepted submittals when measured along a 10 ft straightedge, and
- C. Final wall plumbness (batter) is within 0.5° of vertical unless otherwise approved.

Place reinforcement at locations and elevations shown in the accepted submittals and within 3" of corresponding connection elevations. Install reinforcement with the direction shown in the accepted submittals. Place reinforcement in slight tension free of kinks, folds, wrinkles or creases. Do not splice steel reinforcement. Geogrids may be spliced once per reinforcement length if shown in the accepted submittals. Use geogrid pieces at least 6 ft long. Contact the Engineer when unanticipated existing or future obstructions such as foundations, guardrail, fence or handrail posts, pavements, pipes, inlets or utilities will interfere with reinforcement. To avoid obstructions, deflect, skew or modify reinforcement as shown in the accepted submittals.

Place aggregate in the reinforced zone in 8" to 10" thick lifts. Compact fine aggregate in accordance with Subarticle 235-3(C) of the *Standard Specifications*. Use only hand operated compaction equipment to compact aggregate within 3 ft of panels or SRW units. At a distance greater than 3 ft, compact aggregate with at least 4 passes of an 8 ton to 10 ton vibratory roller in a direction parallel to the wall face. Smooth wheeled or rubber tired rollers are also acceptable for compacting aggregate. Do not use sheepsfoot, grid rollers or other types of compaction equipment with feet. Do not displace or damage reinforcement when placing and compacting aggregate. End dumping directly on geogrids is not permitted. Do not operate heavy equipment on reinforcement until it is covered with at least 8" of aggregate. Replace any damaged reinforcement to the satisfaction of the Engineer.

Backfill for MSE walls outside the reinforced zone in accordance with Article 410-8 of the *Standard Specifications*. If a drain is required, install wall drainage systems as shown in the accepted submittals and in accordance with Section 816 of the *Standard Specifications*.

Place and construct coping and leveling concrete as shown in the accepted submittals. Construct leveling concrete in accordance with Section 420 of the *Standard Specifications*. Construct cast-in-place concrete coping in accordance with Subarticle 452-3(C) of the *Standard Specifications*. When single faced precast concrete barrier is required in front of and against MSE walls, stop coping just above barrier so coping does not interfere with placing barrier up against wall faces.

When separation geotextiles are required, overlap adjacent geotextiles at least 18" and hold separation geotextiles in place with wire staples or anchor pins as needed. Seal joints above and behind MSE walls between coping and ditches or concrete slope protection with silicone sealant.

7.0 MEASUREMENT AND PAYMENT

MSE Retaining Walls will be measured and paid in square feet. MSE walls will be measured as the square feet of exposed wall face area with the height equal to the difference between top and bottom of wall elevations. Define "top of wall" as top of coping or top of panels or SRW units for MSE walls without coping. Define "bottom of wall" as shown in the plans and no measurement will be made for portions of MSE walls embedded below bottom of wall elevations.

The contract unit price for MSE Retaining Walls will be full compensation for providing designs, submittals, labor, tools, equipment and MSE wall materials, excavating, backfilling, hauling and removing excavated materials and supplying site assistance, leveling pads, panels, SRW units, reinforcement, aggregate, wall drainage systems, geotextiles, bearing pads, coping, miscellaneous components and any incidentals necessary to construct MSE walls. The contract unit price for MSE Retaining Walls will also be full compensation for reinforcement connected to and aggregate behind end bent caps in the reinforced zone, if required.

No separate payment will be made for temporary shoring for wall construction. Temporary shoring for wall construction will be incidental to the contract unit price for MSE Retaining Walls.

The contract unit price for MSE Retaining Walls does not include the cost for ditches, fences, handrails, barrier or guardrail associated with MSE walls as these items will be paid for elsewhere in the contract.

Where it is necessary to provide backfill material behind the reinforced zone from sources other than excavated areas or borrow sources used in connection with other work in the contract, payment for furnishing and hauling such backfill material will be paid as extra work in accordance with Article 104-7 of the *Standard Specifications*. Placing and compacting such backfill material is not considered extra work but is incidental to the work being performed.

Payment will be made under:

Pay ItemMSE Retaining Walls

Pay Unit Square Foot



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

BEVERLY EAVES PERDUE
GOVERNOR

EUGENE A. CONTI, JR. SECRETARY

October 18, 2011

NOTICE TO: To all Prequalified Contractors

FROM: R.A. Garris, PE

State Contract Officer

SUBJECT: 2012 Standard Specifications and 2012 Roadway Standard Drawings

The subject publications will be effective with the January 2012 let and are currently available for purchase on the following website: **http://www.ncdot.gov/business/order/puborder.html.** If you have questions concerning ordering these publications, please contact Rick Montanez at (919) 707-6944.



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

BEVERLY EAVES PERDUE
GOVERNOR

EUGENE A. CONTI, JR. SECRETARY

September 20, 2011

NOTICE TO: All Prequalified Bidders

FROM: R.A. Garris, P.E.

State Contract Engineer

SUBJECT: Revision of the "Disadvantaged Business Enterprise" and the

"Minority Business Enterprise and Women Business

Enterprise" Project Special Provisions

Beginning with the November 15, 2011 letting, the above subject project special provisions are to be effective on all Federal and State funded contracts.

Over the past year, the North Carolina Department of Transportation has been working with the contracting industry and the Federal Highway Administration on revisions to the "Disadvantaged Business Enterprise" special provision to make clarifications and enhancements. Likewise, these revisions are mirrored in the "Minority Business Enterprise and Women Business Enterprise" special provision. Attached for your convenience are copies of these provisions.

The Department encourages you to read the special provisions as there are changes to the way DBE or MBE and WBE participation is submitted with the bid and how they are considered toward the advertised goal. Please review the changes to the good faith effort requirements, the addition of the joint check and the replacement forms, how to count disadvantaged prime contractors toward the goal, the clarification of the use of leases in trucking, the addition of new forms such as the SAF (Subcontractor Approval Form) and Subcontractor Quote Comparison Sheet in good faith efforts, and the use of the DBE@ncdot.gov e-mail address for submittals.

It should be noted that with the changes to the special provisions, there will also be changes to the way that the DBE, MBE, and WBE firms are keyed in the Expedite bid system. At the time of bid, bidders shall submit all DBE or MBE and WBE participation that they anticipate to use during the life of the contract. Additional DBE or MBE and WBE participation submitted at the time of bid will be used toward the

Department's overall race-neutral goals, may be used for MBE/WBE banking, and may later be used to replace a committed firm of the same category which is terminated for good cause.

Commitment to use the firm comes at the time that the bidder submits their Letter of Intent to use that firm on the project. When Letters of Intent are submitted, it must be for the same cost as what was submitted at time of bid. Letters of Intent for DBE goals will not commit participation greater than the advertised goal. Letters of Intent for MBE/WBE goals may exceed the goal to bank participation in accordance with the special provision but will not commit participation greater than the advertised goal.

If you have any questions on the special provision, you can contact Mr. Michael McKoy or Ms. Terry Canales, P.E. at 919-733-7174.

Attachments

(10-16-07)(Rev 11-15-11) SPI G61

Description

The purpose of this Special Provision is to carry out the U.S. Department of Transportation's policy of ensuring nondiscrimination in the award and administration of contracts financed in whole or in part with Federal funds. This provision is guided by 49 CFR Part 26.

Definitions

Additional DBE Subcontractors - Any DBE submitted at the time of bid that will <u>not</u> be used to meet the DBE goal. No submittal of a Letter of Intent is required.

Committed DBE Subcontractor - Any DBE submitted at the time of bid that is being used to meet the DBE goal by submission of a Letter of Intent. Or any DBE used as a replacement for a previously committed DBE firm.

Contract Goal Requirement - The approved DBE participation at time of award, but not greater than the advertised contract goal.

DBE Goal - A portion of the total contract, expressed as a percentage, that is to be performed by committed DBE subcontractor(s).

Disadvantaged Business Enterprise (DBE) - A firm certified as a Disadvantaged Business Enterprise through the North Carolina Unified Certification Program.

Goal Confirmation Letter - Written documentation from the Department to the bidder confirming the Contractor's approved, committed DBE participation along with a listing of the committed DBE firms.

Manufacturer - A firm that operates or maintains a factory or establishment that produces on the premises, the materials or supplies obtained by the Contractor.

Regular Dealer - A firm that owns, operates, or maintains a store, warehouse, or other establishment in which the materials or supplies required for the performance of the contract are bought, kept in stock, and regularly sold to the public in the usual course of business. A regular dealer engages in, as its principal business and in its own name, the purchase and sale or lease of the products in question. A regular dealer in such bulk items as steel, cement, gravel, stone, and petroleum products need not keep such products in stock, if it owns and operates distribution equipment for the products. Brokers and packagers are not regarded as manufacturers or regular dealers within the meaning of this section.

North Carolina Unified Certification Program (NCUCP) - A program that provides comprehensive services and information to applicants for DBE certification, such that an applicant is required to apply only once for a DBE certification that will be honored by all

recipients of USDOT funds in the state and not limited to the Department of Transportation only. The Certification Program is in accordance with 49 CFR Part 26.

United States Department of Transportation (USDOT) - Federal agency responsible for issuing regulations (49 CFR Part 26) and official guidance for the DBE program.

Forms and Websites Referenced in this Provision

DBE Payment Tracking System - On-line system in which the Contractor enters the payments made to DBE subcontractors who have performed work on the project. https://apps.dot.state.nc.us/Vendor/PaymentTracking/

DBE-IS Subcontractor Payment Information - Form for reporting the payments made to all DBE firms working on the project. This form is for paper bid projects only. http://www.ncdot.org/doh/forms/files/DBE-IS.xls

RF-1 DBE Replacement Request Form - Form for replacing a committed DBE. https://apps.dot.state.nc.us/_includes/download/external.html?pdf=http%3A//www.ncdot.gov/doh/forms/files/RF-1.pdf

SAF Subcontract Approval Form - Form required for approval to sublet the contract. http://www.ncdot.org/doh/operations/dp_chief_eng/constructionunit/saf.xls

JC-1 Joint Check Notification Form - Form and procedures for joint check notification. The form acts as a written joint check agreement among the parties providing full and prompt disclosure of the expected use of joint checks.

https://apps.dot.state.nc.us/_includes/download/external.html?pdf=http%3A//www.ncdot.gov/doh/forms/files/JC-1.pdf

Letter of Intent - Form signed by the Contractor and the DBE subcontractor, manufacturer or regular dealer that affirms that a portion of said contract is going to be performed by the signed DBE for the amount listed at the time of bid.

http://www.ncdot.org/doh/preconstruct/ps/contracts/letterofintent.pdf

Listing of DBE Subcontractors Form - Form for entering DBE subcontractors on a project that will meet this DBE goal. This form is for paper bids only. http://www.ncdot.gov/doh/preconstruct/ps/word/MISC2.doc

Subcontractor Quote Comparison Sheet - Spreadsheet for showing all subcontractor quotes in the work areas where DBEs quoted on the project. This sheet is submitted with good faith effort packages.

http://www.ncdot.gov/business/ocs/goodfaith/excel/Ex_Subcontractor_Quote_Comparison.xls

DBE Goal

The following DBE goal for participation by Disadvantaged Business Enterprises is established for this contract:

Disadvantaged Business Enterprises [number to the nearest tenth] %

- (A) If the DBE goal is more than zero, the Contractor shall exercise all necessary and reasonable steps to ensure that DBEs participate in at least the percent of the contract as set forth above as the DBE goal.
- (B) If the DBE goal is zero, the Contractor shall make an effort to recruit and use DBEs during the performance of the contract. Any DBE participation obtained shall be reported to the Department.

Directory of Transportation Firms (Directory)

Real-time information is available about firms doing business with the Department and firms that are certified through NCUCP in the Directory of Transportation Firms. Only firms identified in the Directory as DBE certified shall be used to meet the DBE goal. The Directory can be found at the following link. https://partner.ncdot.gov/VendorDirectory/default.html

The listing of an individual firm in the directory shall not be construed as an endorsement of the firm's capability to perform certain work.

Listing of DBE Subcontractors

At the time of bid, bidders shall submit <u>all</u> DBE participation that they anticipate to use during the life of the contract. Only those identified to meet the DBE goal will be considered committed, even though the listing shall include both committed DBE subcontractors and additional DBE subcontractors. Additional DBE subcontractor participation submitted at the time of bid will be used toward the Department's overall race-neutral goal. Only those firms with current DBE certification at the time of bid opening will be acceptable for listing in the bidder's submittal of DBE participation. The Contractor shall indicate the following required information:

(A) Electronic Bids

Bidders shall submit a listing of DBE participation in the appropriate section of Expedite, the bidding software of Bid Express[®].

(1) Submit the names and addresses of DBE firms identified to participate in the contract. If the bidder uses the updated listing of DBE firms shown in Expedite, the bidder may use the dropdown menu to access the name and address of the DBE firm.

- (2) Submit the contract line numbers of work to be performed by each DBE firm. When no figures or firms are entered, the bidder will be considered to have no DBE participation.
- (3) The bidder shall be responsible for ensuring that the DBE is certified at the time of bid by checking the Directory of Transportation Firms. If the firm is not certified at the time of the bid-letting, that DBE's participation will not count towards achieving the DBE goal.

(B) Paper Bids

Blank forms will not be deemed to represent zero participation. Bids submitted that do not have DBE participation indicated on the appropriate form will not be read publicly during the opening of bids. The Department will not consider these bids for award and the proposal will be rejected.

- (1) If the DBE goal is more than zero,
 - (a) Bidders, at the time the bid proposal is submitted, shall submit a listing of DBE participation, including the names and addresses on *Listing of DBE Subcontractors* contained elsewhere in the contract documents in order for the bid to be considered responsive. Bidders shall indicate the total dollar value of the DBE participation for the contract.
 - (b) If bidders have no DBE participation, they shall indicate this on the Listing of DBE Subcontractors by entering the word "None" or the number "0." This form shall be completed in its entirety.
 - (c) The bidder shall be responsible for ensuring that the DBE is certified at the time of bid by checking the Directory of Transportation Firms. If the firm is not certified at the time of the bid-letting, that DBE's participation will not count towards achieving the DBE goal.
- (2) If the DBE goal is zero, bidders, at the time the bid proposal is submitted, shall enter the word "None"; or the number "0"; or if there is participation, add the value on the Listing of DBE Subcontractors contained elsewhere in the contract documents.

DBE Prime Contractor

When a certified DBE firm bids on a contract that contains a DBE goal, the DBE firm is responsible for meeting the goal or making good faith efforts to meet the goal, just like any other bidder. In most cases, a DBE bidder on a contract will meet the DBE goal by virtue of the work it performs on the contract with its own forces. However, all the work that is performed by the DBE bidder and any other DBE subcontractors will count toward the DBE goal. The DBE bidder shall list itself along with any DBE subcontractors, if any, in order to receive credit toward the DBE goal.

For example, if the DBE goal is 45% and the DBE bidder will only perform 40% of the contract work, the prime will list itself at 40%, and the additional 5% shall be obtained through additional DBE participation with DBE subcontractors or documented through a good faith effort.

DBE prime contractors shall also follow Sections A and B listed under Listing of DBE Subcontractor just as a non-DBE bidder would.

Written Documentation - Letter of Intent

The bidder shall submit written documentation for each DBE that will be used to meet the DBE goal of the contract, indicating the bidder's commitment to use the DBE in the contract. This documentation shall be submitted on the Department's form titled *Letter of Intent*.

The documentation shall be received in the office of the State Contractor Utilization Engineer or at DBE@ncdot.gov no later than 12:00 noon of the sixth calendar day following opening of bids, unless the sixth day falls on an official state holiday. In that situation, it is due in the office of the State Contractor Utilization Engineer no later than 12:00 noon on the next official state business day.

If the bidder fails to submit the Letter of Intent from each committed DBE to be used toward the DBE goal, or if the form is incomplete (i.e. both signatures are not present), the DBE participation will not count toward meeting the DBE goal. If the lack of this participation drops the commitment below the DBE goal, the Contractor shall submit evidence of good faith efforts, completed in its entirety, to the State Contractor Utilization Engineer or DBE@ncdot.gov no later than 12:00 noon on the eighth calendar day following opening of bids, unless the eighth day falls on an official state holiday. In that situation, it is due in the office of the State Contractor Utilization Engineer no later than 12:00 noon on the next official state business day.

Submission of Good Faith Effort

If the bidder fails to meet or exceed the DBE goal the apparent lowest responsive bidder shall submit to the Department documentation of adequate good faith efforts made to reach the DBE goal.

A hard copy and an electronic copy of this information shall be received in the office of the State Contractor Utilization Engineer or at DBE@ncdot.gov no later than 12:00 noon of the sixth calendar day following opening of bids unless the sixth day falls on an official state holiday. In that situation, it would be due in the office of the State Contractor Utilization Engineer the next official state business day. If the contractor cannot send the information electronically, then one complete set and 9 copies of this information shall be received under the same time constraints above.

Note: Where the information submitted includes repetitious solicitation letters, it will be acceptable to submit a representative letter along with a distribution list of the firms that were solicited. Documentation of DBE quotations shall be a part of the good faith effort submittal.

This documentation may include written subcontractor quotations, telephone log notations of verbal quotations, or other types of quotation documentation.

Consideration of Good Faith Effort for Projects with DBE Goals More Than Zero

Adequate good faith efforts mean that the bidder took all necessary and reasonable steps to achieve the goal which, by their scope, intensity, and appropriateness, could reasonably be expected to obtain sufficient DBE participation. Adequate good faith efforts also mean that the bidder actively and aggressively sought DBE participation. Mere *pro forma* efforts are not considered good faith efforts.

The Department will consider the quality, quantity, and intensity of the different kinds of efforts a bidder has made. Listed below are examples of the types of actions a bidder will take in making a good faith effort to meet the goal and are not intended to be exclusive or exhaustive, nor is it intended to be a mandatory checklist.

- (A) Soliciting through all reasonable and available means (e.g. attendance at pre-bid meetings, advertising and/or written notices through the use of the NCDOT Directory of Transportation Firms) the interest of all certified DBEs who have the capability to perform the work of the contract. The bidder must solicit this interest within at least 10 days prior to bid opening to allow the DBEs to respond to the solicitation. Solicitation shall provide the opportunity to DBEs within the Division and surrounding Divisions where the project is located. The bidder must determine with certainty if the DBEs are interested by taking appropriate steps to follow up initial solicitations.
- (B) Selecting portions of the work to be performed by DBEs in order to increase the likelihood that the DBE goals will be achieved. This includes, where appropriate, breaking out contract work items into economically feasible units to facilitate DBE participation, even when the prime contractor might otherwise prefer to perform these work items with its own forces.
- (C) Providing interested DBEs with adequate information about the plans, specifications, and requirements of the contract in a timely manner to assist them in responding to a solicitation.
- (D) (1) Negotiating in good faith with interested DBEs. It is the bidder's responsibility to make a portion of the work available to DBE subcontractors and suppliers and to select those portions of the work or material needs consistent with the available DBE subcontractors and suppliers, so as to facilitate DBE participation. Evidence of such negotiation includes the names, addresses, and telephone numbers of DBEs that were considered; a description of the information provided regarding the plans and specifications for the work selected for subcontracting; and evidence as to why additional agreements could not be reached for DBEs to perform the work.

- A bidder using good business judgment would consider a number of factors in negotiating with subcontractors, including DBE subcontractors, and would take a firm's price and capabilities as well as contract goals into consideration. However, the fact that there may be some additional costs involved in finding and using DBEs is not in itself sufficient reason for a bidder's failure to meet the contract DBE goal, as long as such costs are reasonable. Also, the ability or desire of a prime contractor to perform the work of a contract with its own organization does not relieve the bidder of the responsibility to make good faith efforts. Bidding contractors are not, however, required to accept higher quotes from DBEs if the price difference is excessive or unreasonable.
- (E) Not rejecting DBEs as being unqualified without sound reasons based on a thorough investigation of their capabilities. The bidder's standing within its industry, membership in specific groups, organizations, or associates and political or social affiliations (for example, union vs. non-union employee status) are not legitimate causes for the rejection or non-solicitation of bids in the bidder's efforts to meet the project goal.
- (F) Making efforts to assist interested DBEs in obtaining bonding, lines of credit, or insurance as required by the recipient or bidder.
- (G) Making efforts to assist interested DBEs in obtaining necessary equipment, supplies, materials, or related assistance or services.
- (H) Effectively using the services of available minority/women community organizations; minority/women contractors' groups; Federal, State, and local minority/women business assistance offices; and other organizations as allowed on a case-by-case basis to provide assistance in the recruitment and placement of DBEs. Contact within 7 days from the bid opening the Business Development Manager in the Business Opportunity and Work Force Development Unit to give notification of the bidder's inability to get DBE quotes.
- (I) Any other evidence that the bidder submits which shows that the bidder has made reasonable good faith efforts to meet the DBE goal.

In addition, the Department may take into account the following:

- (1) Whether the bidder's documentation reflects a clear and realistic plan for achieving the DBE goal.
- (2) The bidders' past performance in meeting the DBE goals.
- (3) The performance of other bidders in meeting the DBE goal. For example, when the apparent successful bidder fails to meet the DBE goal, but others meet it, you may reasonably raise the question of whether, with additional reasonable efforts the apparent successful bidder could have met the goal. If the apparent successful bidder fails to meet the DBE goal, but meets or exceeds the average DBE participation obtained by other bidders, the Department may view this,

in conjunction with other factors, as evidence of the apparent successful bidder having made a good faith effort.

If the Department does not award the contract to the apparent lowest responsive bidder, the Department reserves the right to award the contract to the next lowest responsive bidder that can satisfy to the Department that the DBE goal can be met or that an adequate good faith effort has been made to meet the DBE goal.

Non-Good Faith Appeal

The State Contractor Utilization Engineer will notify the contractor verbally and in writing of non-good faith. A contractor may appeal a determination of non-good faith made by the Goal Compliance Committee. If a contractor wishes to appeal the determination made by the Committee, they shall provide written notification to the State Contractual Services Engineer or at DBE@ncdot.gov. The appeal shall be made within 2 business days of notification of the determination of non-good faith.

Counting DBE Participation Toward Meeting DBE Goal

(A) Participation

The total dollar value of the participation by a committed DBE will be counted toward the contract goal requirement. The total dollar value of participation by a committed DBE will be based upon the value of work actually performed by the DBE and the actual payments to DBE firms by the Contractor.

(B) Joint Checks

Prior notification of joint check use shall be required when counting DBE participation for services or purchases that involves the use of a joint check. Notification shall be through submission of Form JC-1 (Joint Check Notification Form) and the use of joint checks shall be in accordance with the Department's Joint Check Procedures.

(C) Subcontracts (Non-Trucking)

A DBE may enter into subcontracts. Work that a DBE subcontracts to another DBE firm may be counted toward the contract goal requirement. Work that a DBE subcontracts to a non-DBE firm does <u>not</u> count toward the contract goal requirement. If a DBE contractor or subcontractor subcontracts a significantly greater portion of the work of the contract than would be expected on the basis of standard industry practices, it shall be presumed that the DBE is not performing a commercially useful function. The DBE may present evidence to rebut this presumption to the Department. The Department's decision on the rebuttal of this presumption is subject to review by the Federal Highway Administration but is not administratively appealable to USDOT.

(D) Joint Venture

When a DBE performs as a participant in a joint venture, the Contractor may count toward its contract goal requirement a portion of the total value of participation with the DBE in the joint venture, that portion of the total dollar value being a distinct clearly defined portion of work that the DBE performs with its forces.

(E) Suppliers

A contractor may count toward its DBE requirement 60 percent of its expenditures for materials and supplies required to complete the contract and obtained from a DBE regular dealer and 100 percent of such expenditures from a DBE manufacturer.

(F) Manufacturers and Regular Dealers

A contractor may count toward its DBE requirement the following expenditures to DBE firms that are not manufacturers or regular dealers:

- (1) The fees or commissions charged by a DBE firm for providing a *bona fide* service, such as professional, technical, consultant, or managerial services, or for providing bonds or insurance specifically required for the performance of a DOT-assisted contract, provided the fees or commissions are determined to be reasonable and not excessive as compared with fees and commissions customarily allowed for similar services.
- (2) With respect to materials or supplies purchased from a DBE, which is neither a manufacturer nor a regular dealer, count the entire amount of fees or commissions charged for assistance in the procurement of the materials and supplies, or fees or transportation charges for the delivery of materials or supplies required on a job site (but not the cost of the materials and supplies themselves), provided the fees are determined to be reasonable and not excessive as compared with fees customarily allowed for similar services.

Commercially Useful Function

(A) DBE Utilization

The Contractor may count toward its contract goal requirement only expenditures to DBEs that perform a commercially useful function in the work of a contract. A DBE performs a commercially useful function when it is responsible for execution of the work of the contract and is carrying out its responsibilities by actually performing, managing, and supervising the work involved. To perform a commercially useful function, the DBE shall also be responsible with respect to materials and supplies used on the contract, for negotiating price, determining quality and quantity, ordering the material and installing (where applicable) and paying for the material itself. To determine whether a DBE is performing a commercially useful function, the Department will

evaluate the amount of work subcontracted, industry practices, whether the amount the firm is to be paid under the contract is commensurate with the work it is actually performing and the DBE credit claimed for its performance of the work, and any other relevant factors.

(B) DBE Utilization in Trucking

The following factors will be used to determine if a DBE trucking firm is performing a commercially useful function.

- (1) The DBE shall be responsible for the management and supervision of the entire trucking operation for which it is responsible on a particular contract, and there shall not be a contrived arrangement for the purpose of meeting DBE goals.
- (2) The DBE shall itself own and operate at least one fully licensed, insured, and operational truck used on the contract.
- (3) The DBE receives credit for the total value of the transportation services it provides on the contract using trucks it owns, insures, and operates using drivers it employs.
- (4) The DBE may subcontract the work to another DBE firm, including an owner-operator who is certified as a DBE. The DBE who subcontracts work to another DBE receives credit for the total value of the transportation services the subcontracted DBE provides on the contract.
- (5) The DBE may also subcontract the work to a non-DBE firm, including from an owner-operator. The DBE who subcontracts the work to a non-DBE is entitled to credit for the total value of transportation services provided by the non-DBE subcontractor not to exceed the value of transportation services provided by DBE-owned trucks on the contract. Additional participation by non-DBE subcontractors receives credit only for the fee or commission it receives as a result of the subcontract arrangement. The value of services performed under subcontract agreements between the DBE and the Contractor will not count towards the DBE contract requirement.
- (6) A DBE may lease truck(s) from an established equipment leasing business open to the general public. The lease must indicate that the DBE has exclusive use of and control over the truck. This requirement does not preclude the leased truck from working for others during the term of the lease with the consent of the DBE, so long as the lease gives the DBE absolute priority for use of the leased truck. This type of lease may count toward the DBE's credit as long as the driver is under the DBE's payroll.

(7) Subcontracted/leased trucks shall display clearly on the dashboard the name of the DBE that they are subcontracted/leased to and their own company name if it is not identified on the truck itself. Magnetic door signs are not permitted.

DBE Replacement

When a Contractor has relied on a commitment to a DBE firm (or an approved substitute DBE firm) to meet all or part of a contract goal requirement, the contractor shall not terminate the DBE for convenience. This includes, but is not limited to, instances in which the Contractor seeks to perform the work of the terminated subcontractor with another DBE subcontractor, a non-DBE subcontractor, or with the Contractor's own forces or those of an affiliate. A DBE may only be terminated after receiving the Engineer's written approval based upon a finding of good cause for the termination.

All requests for replacement of a committed DBE firm shall be submitted to the Engineer for approval on Form RF-1 (DBE Replacement Request). If the Contractor fails to follow this procedure, the Contractor may be disqualified from further bidding for a period of up to 6 months.

The Contractor shall comply with the following for replacement of a committed DBE:

(A) Performance Related Replacement

When a committed DBE is terminated for good cause as stated above, an additional DBE that was submitted at the time of bid may be used to fulfill the DBE commitment. A good faith effort will only be required for removing a committed DBE if there were no additional DBEs submitted at the time of bid to cover the same amount of work as the DBE that was terminated.

If a replacement DBE is not found that can perform at least the same amount of work as the terminated DBE, the Contractor shall submit a good faith effort documenting the steps taken. Such documentation shall include, but not be limited to, the following:

- (1) Copies of written notification to DBEs that their interest is solicited in contracting the work defaulted by the previous DBE or in subcontracting other items of work in the contract.
- (2) Efforts to negotiate with DBEs for specific subbids including, at a minimum:
 - (a) The names, addresses, and telephone numbers of DBEs who were contacted.
 - (b) A description of the information provided to DBEs regarding the plans and specifications for portions of the work to be performed.
- (3) A list of reasons why DBE quotes were not accepted.

(4) Efforts made to assist the DBEs contacted, if needed, in obtaining bonding or insurance required by the Contractor.

(B) Decertification Replacement

- (1) When a committed DBE is decertified by the Department after the SAF (Subcontract Approval Form) has been received by the Department, the Department will not require the Contractor to solicit replacement DBE participation equal to the remaining work to be performed by the decertified firm. The participation equal to the remaining work performed by the decertified firm will count toward the contract goal requirement.
- (2) When a committed DBE is decertified prior to the Department receiving the SAF (Subcontract Approval Form) for the named DBE firm, the Contractor shall take all necessary and reasonable steps to replace the DBE subcontractor with another DBE subcontractor to perform at least the same amount of work to meet the DBE goal requirement. If a DBE firm is not found to do the same amount of work, a good faith effort must be submitted to NCDOT (see A herein for required documentation).

Changes in the Work

When the Engineer makes changes that result in the reduction or elimination of work to be performed by a committed DBE, the Contractor will not be required to seek additional participation. When the Engineer makes changes that result in additional work to be performed by a DBE based upon the Contractor's commitment, the DBE shall participate in additional work to the same extent as the DBE participated in the original contract work.

When the Engineer makes changes that result in extra work, which has more than a minimal impact on the contract amount, the Contractor shall seek additional participation by DBEs unless otherwise approved by the Engineer.

When the Engineer makes changes that result in an alteration of plans or details of construction, and a portion or all of the work had been expected to be performed by a committed DBE, the Contractor shall seek participation by DBEs unless otherwise approved by the Engineer.

When the Contractor requests changes in the work that result in the reduction or elimination of work that the Contractor committed to be performed by a DBE, the Contractor shall seek additional participation by DBEs equal to the reduced DBE participation caused by the changes.

Reports and Documentation

A SAF (Subcontract Approval Form) shall be submitted for all work which is to be performed by a DBE subcontractor. The Department reserves the right to require copies of actual subcontract agreements involving DBE subcontractors.

When using transportation services to meet the contract commitment, the Contractor shall submit a proposed trucking plan in addition to the SAF. The plan shall be submitted prior to beginning construction on the project. The plan shall include the names of all trucking firms proposed for use, their certification type(s), the number of trucks owned by the firm, as well as the individual truck identification numbers, and the line item(s) being performed.

Within 30 calendar days of entering into an agreement with a DBE for materials, supplies or services, not otherwise documented by the SAF as specified above, the Contractor shall furnish the Engineer a copy of the agreement. The documentation shall also indicate the percentage (60% or 100%) of expenditures claimed for DBE credit.

Reporting Disadvantaged Business Enterprise Participation

The Contractor shall provide the Engineer with an accounting of payments made to all DBE firms, including material suppliers and contractors at all levels (prime, subcontractor, or second tier subcontractor). This accounting shall be furnished to the Engineer for any given month by the end of the following month. Failure to submit this information accordingly may result in the following action:

- (A) Withholding of money due in the next partial pay estimate; or
- (B) Removal of an approved contractor from the prequalified bidders' list or the removal of other entities from the approved subcontractors list.

While each contractor (prime, subcontractor, 2nd tier subcontractor) is responsible for accurate accounting of payments to DBEs, it shall be the prime contractor's responsibility to report all monthly and final payment information in the correct reporting manner.

Failure on the part of the Contractor to submit the required information in the time frame specified may result in the disqualification of that contractor and any affiliate companies from further bidding until the required information is submitted.

Failure on the part of any subcontractor to submit the required information in the time frame specified may result in the disqualification of that contractor and any affiliate companies from being approved for work on future DOT projects until the required information is submitted.

Contractors reporting transportation services provided by non-DBE lessees shall evaluate the value of services provided during the month of the reporting period only.

At any time, the Engineer can request written verification of subcontractor payments.

(A) Electronic Bids Reporting

The Contractor shall report the accounting of payments through the Department's DBE Payment Tracking System.

(B) Paper Bids Reporting

The Contractor shall report the accounting of payments on the Department's DBE-IS (Subcontractor Payment Information) with each invoice. Invoices will not be processed for payment until the DBE-IS is received.

Failure to Meet Contract Requirements

Failure to meet contract requirements in accordance with Subarticle 102-16(J) of the 2006 Standard Specifications may be cause to disqualify the Contractor from further bidding for a specified length of time.

MINORITY BUSINESS ENTERPRISE AND WOMEN BUSINESS ENTERPRISE:

(10-16-07)(Rev 11-15-11) SP1 G67

Description

The purpose of this Special Provision is to carry out the North Carolina Department of Transportation's policy of ensuring nondiscrimination in the award and administration of contracts financed in whole or in part with State funds.

Definitions

Additional MBE/WBE Subcontractors - Any MBE/WBE submitted at the time of bid that will <u>not</u> be used to meet either the MBE or WBE goal. No submittal of a Letter of Intent is required, unless the additional participation is used for banking purposes.

Committed MBE/WBE Subcontractor - Any MBE/WBE submitted at the time of bid that is being used to meet either the MBE or WBE goal by submission of a Letter of Intent. Or any MBE or WBE used as a replacement for a previously committed MBE or WBE firm.

Contract Goals Requirement - The approved MBE and WBE participation at time of award, but not greater than the advertised contract goals for each.

Goal Confirmation Letter - Written documentation from the Department to the bidder confirming the Contractor's approved, committed MBE and WBE participation along with a listing of the committed MBE and WBE firms.

Manufacturer - A firm that operates or maintains a factory or establishment that produces on the premises, the materials or supplies obtained by the Contractor.

MBE Goal - A portion of the total contract, expressed as a percentage, that is to be performed by committed MBE subcontractor(s).

Minority Business Enterprise (MBE) - A firm certified as a Disadvantaged Minority-Owned Business Enterprise through the North Carolina Unified Certification Program.

Regular Dealer - A firm that owns, operates, or maintains a store, warehouse, or other establishment in which the materials or supplies required for the performance of the contract are bought, kept in stock, and regularly sold to the public in the usual course of business. A regular dealer engages in, as its principal business and in its own name, the purchase and sale or lease of the products in question. A regular dealer in such bulk items as steel, cement, gravel, stone, and petroleum products need not keep such products in stock, if it owns and operates distribution equipment for the products. Brokers and packagers are not regarded as manufacturers or regular dealers within the meaning of this section.

North Carolina Unified Certification Program (NCUCP) - A program that provides comprehensive services and information to applicants for MBE/WBE certification.

The MBE/WBE program follows the same regulations as the federal Disadvantaged Business Enterprise (DBE) program in accordance with 49 CFR Part 26.

United States Department of Transportation (USDOT) - Federal agency responsible for issuing regulations (49 CFR Part 26) and official guidance for the DBE program.

WBE Goal - A portion of the total contract, expressed as a percentage, that is to be performed by committed WBE subcontractor(s).

Women Business Enterprise (WBE) - A firm certified as a Disadvantaged Women-Owned Business Enterprise through the North Carolina Unified Certification Program.

Forms and Websites Referenced in this Provision

Payment Tracking System - On-line system in which the Contractor enters the payments made to MBE and WBE subcontractors who have performed work on the project. https://apps.dot.state.nc.us/Vendor/PaymentTracking/

DBE-IS Subcontractor Payment Information - Form for reporting the payments made to all MBE/WBE firms working on the project. This form is for paper bid projects only. http://www.ncdot.org/doh/forms/files/DBE-IS.xls

RF-1 *MBE/WBE Replacement Request Form* - Form for replacing a committed MBE or WBE. https://apps.dot.state.nc.us/_includes/download/external.html?pdf=http%3A//www.ncdot.gov/doh/forms/files/RF-1.pdf

SAF Subcontract Approval Form - Form required for approval to sublet the contract. http://www.ncdot.org/doh/operations/dp_chief_eng/constructionunit/saf.xls

JC-1 Joint Check Notification Form - Form and procedures for joint check notification. The form acts as a written joint check agreement among the parties providing full and prompt disclosure of the expected use of joint checks.

https://apps.dot.state.nc.us/_includes/download/external.html?pdf=http%3A//www.ncdot.gov/doh/forms/files/JC-1.pdf

Letter of Intent - Form signed by the Contractor and the MBE/WBE subcontractor, manufacturer or regular dealer that affirms that a portion of said contract is going to be performed by the signed MBE/WBE for the amount listed at the time of bid.

http://www.ncdot.org/doh/preconstruct/ps/contracts/letterofintent.pdf

Listing of MBE and WBE Subcontractors Form - Form for entering MBE/WBE subcontractors on a project that will meet this MBE and WBE goals. This form is for paper bids only. http://www.ncdot.gov/doh/preconstruct/ps/word/MISC3.doc

Subcontractor Quote Comparison Sheet - Spreadsheet for showing all subcontractor quotes in the work areas where MBEs and WBEs quoted on the project. This sheet is submitted with good faith effort packages.

http://www.ncdot.gov/business/ocs/goodfaith/excel/Ex_Subcontractor_Quote_Comparison.xls

MBE and WBE Goal

The following goals for participation by Minority Business Enterprises and Women Business Enterprises are established for this contract:

- (A) Minority Business Enterprises [number to the nearest tenth] %
 - (1) If the MBE goal is more than zero, the Contractor shall exercise all necessary and reasonable steps to ensure that MBEs participate in at least the percent of the contract as set forth above as the MBE goal.
 - (2) If the MBE goal is zero, the Contractor shall make an effort to recruit and use MBEs during the performance of the contract. Any MBE participation obtained shall be reported to the Department.
- (B) Women Business Enterprises [number to the nearest tenth] %
 - (1) If the WBE goal is more than zero, the Contractor shall exercise all necessary and reasonable steps to ensure that WBEs participate in at least the percent of the contract as set forth above as the WBE goal.
 - (2) If the WBE goal is zero, the Contractor shall make an effort to recruit and use WBEs during the performance of the contract. Any WBE participation obtained shall be reported to the Department.

Directory of Transportation Firms (Directory)

Real-time information is available about firms doing business with the Department and firms that are certified through NCUCP in the Directory of Transportation Firms. Only firms identified in the Directory as MBE and WBE certified shall be used to meet the MBE and WBE goals respectively. The Directory can be found at the following link. https://partner.ncdot.gov/VendorDirectory/default.html

The listing of an individual firm in the directory shall not be construed as an endorsement of the firm's capability to perform certain work.

Listing of MBE/WBE Subcontractors

At the time of bid, bidders shall submit <u>all</u> MBE and WBE participation that they anticipate to use during the life of the contract. Only those identified to meet the MBE goal and the WBE goal will be considered committed, even though the listing shall include both committed

MBE/WBE subcontractors and additional MBE/WBE subcontractors. Any additional MBE/WBE subcontractor participation above the goal for which letters of intent are received will follow the banking guidelines found elsewhere in this provision. All other additional MBE/WBE subcontractor participation submitted at the time of bid will be used toward the Department's overall race-neutral goals. Only those firms with current MBE and WBE certification at the time of bid opening will be acceptable for listing in the bidder's submittal of MBE and WBE participation. The Contractor shall indicate the following required information:

(A) Electronic Bids

Bidders shall submit a listing of MBE and WBE participation in the appropriate section of Expedite, the bidding software of Bid Express[®].

- (1) Submit the names and addresses of MBE and WBE firms identified to participate in the contract. If the bidder uses the updated listing of MBE and WBE firms shown in Expedite, the bidder may use the dropdown menu to access the name and address of the firms.
- (2) Submit the contract line numbers of work to be performed by each MBE and WBE firm. When no figures or firms are entered, the bidder will be considered to have no MBE or WBE participation.
- (3) The bidder shall be responsible for ensuring that the MBE and WBE are certified at the time of bid by checking the Directory of Transportation Firms. If the firm is not certified at the time of the bid-letting, that MBE's or WBE's participation will not count towards achieving either the MBE or WBE goal.

(B) Paper Bids

Blank forms will not be deemed to represent zero participation. Bids submitted that do not have MBE and WBE participation indicated on the appropriate form will not be read publicly during the opening of bids. The Department will not consider these bids for award and the proposal will be rejected.

- (1) If either the MBE or WBE goal is more than zero,
 - (a) Bidders, at the time the bid proposal is submitted, shall submit a listing of MBE/WBE participation, including the names and addresses on *Listing of MBE and WBE Subcontractors* contained elsewhere in the contract documents in order for the bid to be considered responsive. Bidders shall indicate the total dollar value of the MBE and WBE participation for the contract.
 - (b) If bidders have no MBE or WBE participation, they shall indicate this on the *Listing of MBE and WBE Subcontractors* by entering the word "None" or the number "0." This form shall be completed in its entirety.

- (c) The bidder shall be responsible for ensuring that the MBE/WBE is certified at the time of bid by checking the Directory of Transportation Firms. If the firm is not certified at the time of the bid-letting, that MBE's or WBE's participation will not count towards achieving the corresponding goal.
- (2) If either the MBE or WBE goal is zero, bidders, at the time the bid proposal is submitted, shall enter the word "None"; or the number "0"; or if there is participation, add the value on the Listing of MBE and WBE Subcontractors contained elsewhere in the contract documents.

MBE or WBE Prime Contractor

When a certified MBE or WBE firm bids on a contract that contains MBE and WBE goals, the firm is responsible for meeting the goals or making good faith efforts to meet the goals, just like any other bidder. In most cases, a MBE or WBE bidder on a contract will meet one of the goals by virtue of the work it performs on the contract with its own forces. However, all the work that is performed by the MBE or WBE bidder and any other similarly certified subcontractors will count toward the goal. The MBE or WBE bidder shall list itself along with any MBE or WBE subcontractors, if any, in order to receive credit toward the goals.

For example, on a proposed contract, the WBE goal is 10%, and the MBE goal is 8%. A WBE bidder puts in a bid where they will perform 40% of the contract work and have a WBE subcontractor which will perform another 5% of the work. Together the two WBE firms submit on the *Listing of MBE and WBE Subcontractors* a value of 45% of the contract which fulfills the WBE goal. The 8% MBE goal shall be obtained through MBE participation with MBE certified subcontractors or documented through a good faith effort. It should be noted that you cannot combine the two goals to meet an overall value. The two goals shall remain separate.

MBE/WBE prime contractors shall also follow Sections A and B listed under Listing of MBE and WBE Subcontractor just as a non-MBE/WBE bidder would.

Written Documentation - Letter of Intent

The bidder shall submit written documentation for each MBE/WBE that will be used to meet the MBE and WBE goals of the contract, indicating the bidder's commitment to use the MBE/WBE in the contract. This documentation shall be submitted on the Department's form titled Letter of Intent.

The documentation shall be received in the office of the State Contractor Utilization Engineer or at DBE@ncdot.gov no later than 12:00 noon of the sixth calendar day following opening of bids, unless the sixth day falls on an official state holiday. In that situation, it is due in the office of the State Contractor Utilization Engineer no later than 12:00 noon on the next official state business day.

If the bidder fails to submit the Letter of Intent from each committed MBE and WBE to be used toward the MBE and WBE goals, or if the form is incomplete (i.e. both signatures are not present), the MBE/WBE participation will not count toward meeting the MBE/WBE goal. If the lack of this participation drops the commitment below either the MBE or WBE goal, the Contractor shall submit evidence of good faith efforts for the goal not met, completed in its entirety, to the State Contractor Utilization Engineer or DBE@ncdot.gov no later than 12:00 noon on the eighth calendar day following opening of bids, unless the eighth day falls on an official state holiday. In that situation, it is due in the office of the State Contractor Utilization Engineer no later than 12:00 noon on the next official state business day.

Submission of Good Faith Effort

If the bidder fails to meet or exceed either the MBE or the WBE goal the apparent lowest responsive bidder shall submit to the Department documentation of adequate good faith efforts made to reach that specific goal(s).

A hard copy and an electronic copy of this information shall be received in the office of the State Contractor Utilization Engineer or at DBE@ncdot.gov no later than 12:00 noon of the sixth calendar day following opening of bids unless the sixth day falls on an official state holiday. In that situation, it would be due in the office of the State Contractor Utilization Engineer the next official state business day. If the contractor cannot send the information electronically, then one complete set and 9 copies of this information shall be received under the same time constraints above.

Note: Where the information submitted includes repetitious solicitation letters, it will be acceptable to submit a representative letter along with a distribution list of the firms that were solicited. Documentation of MBE/WBE quotations shall be a part of the good faith effort submittal. This documentation may include written subcontractor quotations, telephone log notations of verbal quotations, or other types of quotation documentation.

Consideration of Good Faith Effort for Projects with MBE/WBE Goals More Than Zero

Adequate good faith efforts mean that the bidder took all necessary and reasonable steps to achieve the goal which, by their scope, intensity, and appropriateness, could reasonably be expected to obtain sufficient MBE/WBE participation. Adequate good faith efforts also mean that the bidder actively and aggressively sought MBE/WBE participation. Mere *pro forma* efforts are not considered good faith efforts.

The Department will consider the quality, quantity, and intensity of the different kinds of efforts a bidder has made. Listed below are examples of the types of actions a bidder will take in making a good faith effort to meet the goals and are not intended to be exclusive or exhaustive, nor is it intended to be a mandatory checklist.

(A) Soliciting through all reasonable and available means (e.g. attendance at pre-bid meetings, advertising and/or written notices through the use of the NCDOT Directory of Transportation Firms) the interest of all certified MBEs/WBEs who have the capability to

perform the work of the contract. The bidder must solicit this interest within at least 10 days prior to bid opening to allow the MBEs/WBEs to respond to the solicitation. Solicitation shall provide the opportunity to MBEs/WBEs within the Division and surrounding Divisions where the project is located. The bidder must determine with certainty if the MBEs/WBEs are interested by taking appropriate steps to follow up initial solicitations.

- (B) Selecting portions of the work to be performed by MBEs/WBEs in order to increase the likelihood that the MBE and WBE goals will be achieved. This includes, where appropriate, breaking out contract work items into economically feasible units to facilitate MBE/WBE participation, even when the prime contractor might otherwise prefer to perform these work items with its own forces.
- (C) Providing interested MBEs/WBEs with adequate information about the plans, specifications, and requirements of the contract in a timely manner to assist them in responding to a solicitation.
- (D) (1) Negotiating in good faith with interested MBEs/WBEs. It is the bidder's responsibility to make a portion of the work available to MBE/WBE subcontractors and suppliers and to select those portions of the work or material needs consistent with the available MBE/WBE subcontractors and suppliers, so as to facilitate MBE/WBE participation. Evidence of such negotiation includes the names, addresses, and telephone numbers of MBEs/WBEs that were considered; a description of the information provided regarding the plans and specifications for the work selected for subcontracting; and evidence as to why additional agreements could not be reached for MBEs/WBEs to perform the work.
 - (2) A bidder using good business judgment would consider a number of factors in negotiating with subcontractors, including MBE/WBE subcontractors, and would take a firm's price and capabilities as well as contract goals into consideration. However, the fact that there may be some additional costs involved in finding and using MBEs/WBEs is not in itself sufficient reason for a bidder's failure to meet the contract MBE or WBE goals, as long as such costs are reasonable. Also, the ability or desire of a prime contractor to perform the work of a contract with its own organization does not relieve the bidder of the responsibility to make good faith efforts. Bidding contractors are not, however, required to accept higher quotes from MBEs/WBEs if the price difference is excessive or unreasonable.
- (E) Not rejecting MBEs/WBEs as being unqualified without sound reasons based on a thorough investigation of their capabilities. The bidder's standing within its industry, membership in specific groups, organizations, or associates and political or social affiliations (for example, union vs. non-union employee status) are not legitimate causes for the rejection or non-solicitation of bids in the bidder's efforts to meet the project goal.

- (F) Making efforts to assist interested MBEs/WBEs in obtaining bonding, lines of credit, or insurance as required by the recipient or bidder.
- (G) Making efforts to assist interested MBEs/WBEs in obtaining necessary equipment, supplies, materials, or related assistance or services.
- (H) Effectively using the services of available minority/women community organizations; minority/women contractors' groups; Federal, State, and local minority/women business assistance offices; and other organizations as allowed on a case-by-case basis to provide assistance in the recruitment and placement of MBEs/WBEs. Contact within 7 days from the bid opening the Business Development Manager in the Business Opportunity and Work Force Development Unit to give notification of the bidder's inability to get MBE or WBE quotes.
- (I) Any other evidence that the bidder submits which shows that the bidder has made reasonable good faith efforts to meet the MBE and WBE goal.

In addition, the Department may take into account the following:

- (1) Whether the bidder's documentation reflects a clear and realistic plan for achieving the MBE and WBE goals.
- (2) The bidders' past performance in meeting the MBE and WBE goals.
- (3) The performance of other bidders in meeting the MBE and WBE goals. For example, when the apparent successful bidder fails to meet the goals, but others meet it, you may reasonably raise the question of whether, with additional reasonable efforts the apparent successful bidder could have met the goals. If the apparent successful bidder fails to meet the MBE and WBE goals, but meets or exceeds the average MBE and WBE participation obtained by other bidders, the Department may view this, in conjunction with other factors, as evidence of the apparent successful bidder having made a good faith effort.

If the Department does not award the contract to the apparent lowest responsive bidder, the Department reserves the right to award the contract to the next lowest responsive bidder that can satisfy to the Department that the MBE and WBE goals can be met or that an adequate good faith effort has been made to meet the MBE and WBE goals.

Non-Good Faith Appeal

The State Contractor Utilization Engineer will notify the contractor verbally and in writing of non-good faith. A contractor may appeal a determination of non-good faith made by the Goal Compliance Committee. If a contractor wishes to appeal the determination made by the Committee, they shall provide written notification to the State Contractual Services Engineer or at DBE@ncdot.gov. The appeal shall be made within 2 business days of notification of the determination of non-good faith.

Counting MBE/WBE Participation Toward Meeting MBE/WBE Goals

(A) Participation

The total dollar value of the participation by a committed MBE/WBE will be counted toward the contract goal requirements. The total dollar value of participation by a committed MBE/WBE will be based upon the value of work actually performed by the MBE/WBE and the actual payments to MBE/WBE firms by the Contractor.

(B) Joint Checks

Prior notification of joint check use shall be required when counting MBE/WBE participation for services or purchases that involves the use of a joint check. Notification shall be through submission of Form JC-1 (Joint Check Notification Form) and the use of joint checks shall be in accordance with the Department's Joint Check Procedures.

(C) Subcontracts (Non-Trucking)

A MBE/WBE may enter into subcontracts. Work that a MBE subcontracts to another MBE firm may be counted toward the MBE contract goal requirement. The same holds for work that a WBE subcontracts to another WBE firm. Work that a MBE subcontracts to a non-MBE firm does <u>not</u> count toward the MBE contract goal requirement. Again, the same holds true for the work that a WBE subcontracts to a non-WBE firm. If a MBE or WBE contractor or subcontractor subcontracts a significantly greater portion of the work of the contract than would be expected on the basis of standard industry practices, it shall be presumed that the MBE or WBE is not performing a commercially useful function. The MBE/WBE may present evidence to rebut this presumption to the Department. The Department's decision on the rebuttal of this presumption may be subject to review by the Office of Inspector General, NCDOT.

(D) Joint Venture

When a MBE or WBE performs as a participant in a joint venture, the Contractor may count toward its contract goal requirement a portion of the total value of participation with the MBE or WBE in the joint venture, that portion of the total dollar value being a distinct clearly defined portion of work that the MBE or WBE performs with its forces.

(E) Suppliers

A contractor may count toward its MBE or WBE requirement 60 percent of its expenditures for materials and supplies required to complete the contract and obtained from a MBE or WBE regular dealer and 100 percent of such expenditures from a MBE or WBE manufacturer.

(F) Manufacturers and Regular Dealers

A contractor may count toward its MBE or WBE requirement the following expenditures to MBE/WBE firms that are not manufacturers or regular dealers:

- (1) The fees or commissions charged by a MBE/WBE firm for providing a bona fide service, such as professional, technical, consultant, or managerial services, or for providing bonds or insurance specifically required for the performance of a DOT-assisted contract, provided the fees or commissions are determined to be reasonable and not excessive as compared with fees and commissions customarily allowed for similar services.
- (2) With respect to materials or supplies purchased from a MBE/WBE, which is neither a manufacturer nor a regular dealer, count the entire amount of fees or commissions charged for assistance in the procurement of the materials and supplies, or fees or transportation charges for the delivery of materials or supplies required on a job site (but not the cost of the materials and supplies themselves), provided the fees are determined to be reasonable and not excessive as compared with fees customarily allowed for similar services.

Commercially Useful Function

(A) MBE/WBE Utilization

The Contractor may count toward its contract goal requirement only expenditures to MBEs and WBEs that perform a commercially useful function in the work of a contract. A MBE/WBE performs a commercially useful function when it is responsible for execution of the work of the contract and is carrying out its responsibilities by actually performing, managing, and supervising the work involved. To perform a commercially useful function, the MBE/WBE shall also be responsible with respect to materials and supplies used on the contract, for negotiating price, determining quality and quantity, ordering the material and installing (where applicable) and paying for the material itself. To determine whether a MBE/WBE is performing a commercially useful function, the Department will evaluate the amount of work subcontracted, industry practices, whether the amount the firm is to be paid under the contract is commensurate with the work it is actually performing and the MBE/WBE credit claimed for its performance of the work, and any other relevant factors.

(B) MBE/WBE Utilization in Trucking

The following factors will be used to determine if a MBE or WBE trucking firm is performing a commercially useful function.

(1) The MBE/WBE shall be responsible for the management and supervision of the entire trucking operation for which it is responsible on a particular contract, and

- there shall not be a contrived arrangement for the purpose of meeting the MBE or WBE goal.
- (2) The MBE/WBE shall itself own and operate at least one fully licensed, insured, and operational truck used on the contract.
- (3) The MBE/WBE receives credit for the total value of the transportation services it provides on the contract using trucks it owns, insures, and operates using drivers it employs.
- (4) The MBE may subcontract the work to another MBE firm, including an owner-operator who is certified as a MBE. The same holds true that a WBE may subcontract the work to another WBE firm, including an owner-operator who is certified as a WBE. When this occurs, the MBE or WBE who subcontracts work receives credit for the total value of the transportation services the subcontracted MBE or WBE provides on the contract. It should be noted that every effort shall be made by MBE and WBE contractors to subcontract to the same certification (i.e., MBEs to MBEs and WBEs to WBEs), in order to fulfill the goal requirement. This, however, may not always be possible due to the limitation of firms in the area. If the MBE or WBE firm shows a good faith effort has been made to reach out to similarly certified transportation service providers and there is no interest or availability, and they can get assistance from other certified providers, the Engineer will not hold the prime liable for meeting the goal.
- (5) The MBE/WBE may also subcontract the work to a non-MBE/WBE firm, including from an owner-operator. The MBE/WBE who subcontracts the work to a non-MBE/WBE is entitled to credit for the total value of transportation services provided by the non-MBE/WBE subcontractor not to exceed the value of transportation services provided by MBE/WBE-owned trucks on the contract. Additional participation by non-MBE/WBE subcontractors receives credit only for the fee or commission it receives as a result of the subcontract arrangement. The value of services performed under subcontract agreements between the MBE/WBE and the Contractor will not count towards the MBE/WBE contract requirement.
- (6) A MBE/WBE may lease truck(s) from an established equipment leasing business open to the general public. The lease must indicate that the MBE/WBE has exclusive use of and control over the truck. This requirement does not preclude the leased truck from working for others during the term of the lease with the consent of the MBE/WBE, so long as the lease gives the MBE/WBE absolute priority for use of the leased truck. This type of lease may count toward the MBE/WBE's credit as long as the driver is under the MBE/WBE's payroll.

(7) Subcontracted/leased trucks shall display clearly on the dashboard the name of the MBE/WBE that they are subcontracted/leased to and their own company name if it is not identified on the truck itself. Magnetic door signs are not permitted.

Banking MBE/WBE Credit

If the bid of the lowest responsive bidder exceeds \$500,000 and if the committed MBE/WBE participation submitted by Letter of Intent exceeds the algebraic sum of the MBE or WBE goal by \$1,000 or more, the excess will be placed on deposit by the Department for future use by the bidder. Separate accounts will be maintained for MBE and WBE participation and these may accumulate for a period not to exceed 24 months.

When the apparent lowest responsive bidder fails to submit sufficient participation by MBE firms to meet the contract goal, as part of the good faith effort, the Department will consider allowing the bidder to withdraw funds to meet the MBE goal as long as there are adequate funds available from the bidder's MBE bank account.

When the apparent lowest responsive bidder fails to submit sufficient participation by WBE firms to meet the contract goal, as part of the good faith effort, the Department will consider allowing the bidder to withdraw funds to meet the WBE goal as long as there are adequate funds available from the bidder's WBE bank account.

MBE/WBE Replacement

When a Contractor has relied on a commitment to a MBE or WBE firm (or an approved substitute MBE or WBE firm) to meet all or part of a contract goal requirement, the contractor shall not terminate the MBE/WBE for convenience. This includes, but is not limited to, instances in which the Contractor seeks to perform the work of the terminated subcontractor with another MBE/WBE subcontractor, a non-MBE/WBE subcontractor, or with the Contractor's own forces or those of an affiliate. A MBE/WBE may only be terminated after receiving the Engineer's written approval based upon a finding of good cause for the termination.

All requests for replacement of a committed MBE/WBE firm shall be submitted to the Engineer for approval on Form RF-1 (Replacement Request). If the Contractor fails to follow this procedure, the Contractor may be disqualified from further bidding for a period of up to 6 months.

The Contractor shall comply with the following for replacement of a committed MBE/WBE:

(A) Performance Related Replacement

When a committed MBE is terminated for good cause as stated above, an additional MBE that was submitted at the time of bid may be used to fulfill the MBE commitment. The same holds true if a committed WBE is terminated for good cause, an additional WBE that was submitted at the time of bid may be used to fulfill the WBE goal. A good faith effort will only be required for removing a committed MBE/WBE if there were no

additional MBEs/WBEs submitted at the time of bid to cover the same amount of work as the MBE/WBE that was terminated.

If a replacement MBE/WBE is not found that can perform at least the same amount of work as the terminated MBE/WBE, the Contractor shall submit a good faith effort documenting the steps taken. Such documentation shall include, but not be limited to, the following:

- (1) Copies of written notification to MBEs/WBEs that their interest is solicited in contracting the work defaulted by the previous MBE/WBE or in subcontracting other items of work in the contract.
- (2) Efforts to negotiate with MBEs/WBEs for specific subbids including, at a minimum:
 - (a) The names, addresses, and telephone numbers of MBEs/WBEs who were contacted.
 - (b) A description of the information provided to MBEs/WBEs regarding the plans and specifications for portions of the work to be performed.
- (3) A list of reasons why MBE/WBE quotes were not accepted.
- (4) Efforts made to assist the MBEs/WBEs contacted, if needed, in obtaining bonding or insurance required by the Contractor.

(B) Decertification Replacement

- (1) When a committed MBE/WBE is decertified by the Department after the SAF (Subcontract Approval Form) has been received by the Department, the Department will not require the Contractor to solicit replacement MBE/WBE participation equal to the remaining work to be performed by the decertified firm. The participation equal to the remaining work performed by the decertified firm will count toward the contract goal requirement.
- When a committed MBE/WBE is decertified prior to the Department receiving the SAF (Subcontract Approval Form) for the named MBE/WBE firm, the Contractor shall take all necessary and reasonable steps to replace the MBE/WBE subcontractor with another similarly certified MBE/WBE subcontractor to perform at least the same amount of work to meet the MBE/WBE goal requirement. If a MBE/WBE firm is not found to do the same amount of work, a good faith effort must be submitted to NCDOT (see A herein for required documentation).

Changes in the Work

When the Engineer makes changes that result in the reduction or elimination of work to be performed by a committed MBE/WBE, the Contractor will not be required to seek additional participation. When the Engineer makes changes that result in additional work to be performed by a MBE/WBE based upon the Contractor's commitment, the MBE/WBE shall participate in additional work to the same extent as the MBE/WBE participated in the original contract work.

When the Engineer makes changes that result in extra work, which has more than a minimal impact on the contract amount, the Contractor shall seek additional participation by MBEs/WBEs unless otherwise approved by the Engineer.

When the Engineer makes changes that result in an alteration of plans or details of construction, and a portion or all of the work had been expected to be performed by a committed MBE/WBE, the Contractor shall seek participation by MBEs/WBEs unless otherwise approved by the Engineer.

When the Contractor requests changes in the work that result in the reduction or elimination of work that the Contractor committed to be performed by a MBE/WBE, the Contractor shall seek additional participation by MBEs/WBEs equal to the reduced MBE/WBE participation caused by the changes.

Reports and Documentation

A SAF (Subcontract Approval Form) shall be submitted for all work which is to be performed by a MBE/WBE subcontractor. The Department reserves the right to require copies of actual subcontract agreements involving MBE/WBE subcontractors.

When using transportation services to meet the contract commitment, the Contractor shall submit a proposed trucking plan in addition to the SAF. The plan shall be submitted prior to beginning construction on the project. The plan shall include the names of all trucking firms proposed for use, their certification type(s), the number of trucks owned by the firm, as well as the individual truck identification numbers, and the line item(s) being performed.

Within 30 calendar days of entering into an agreement with a MBE/WBE for materials, supplies or services, not otherwise documented by the SAF as specified above, the Contractor shall furnish the Engineer a copy of the agreement. The documentation shall also indicate the percentage (60% or 100%) of expenditures claimed for MBE/WBE credit.

Reporting Minority and Women Business Enterprise Participation

The Contractor shall provide the Engineer with an accounting of payments made to all MBE and WBE firms, including material suppliers and contractors at all levels (prime, subcontractor, or second tier subcontractor). This accounting shall be furnished to the Engineer for any given month by the end of the following month. Failure to submit this information accordingly may result in the following action:

- (A) Withholding of money due in the next partial pay estimate; or
- (B) Removal of an approved contractor from the prequalified bidders' list or the removal of other entities from the approved subcontractors list.

While each contractor (prime, subcontractor, 2nd tier subcontractor) is responsible for accurate accounting of payments to MBEs/WBEs, it shall be the prime contractor's responsibility to report all monthly and final payment information in the correct reporting manner.

Failure on the part of the Contractor to submit the required information in the time frame specified may result in the disqualification of that contractor and any affiliate companies from further bidding until the required information is submitted.

Failure on the part of any subcontractor to submit the required information in the time frame specified may result in the disqualification of that contractor and any affiliate companies from being approved for work on future DOT projects until the required information is submitted.

Contractors reporting transportation services provided by non-MBE/WBE lessees shall evaluate the value of services provided during the month of the reporting period only.

At any time, the Engineer can request written verification of subcontractor payments.

(A) Electronic Bids Reporting

The Contractor shall report the accounting of payments through the Department's Payment Tracking System.

(B) Paper Bids Reporting

The Contractor shall report the accounting of payments on the Department's DBE-IS (Subcontractor Payment Information) with each invoice. Invoices will not be processed for payment until the DBE-IS is received.

Failure to Meet Contract Requirements

Failure to meet contract requirements in accordance with Subarticle 102-16(J) of the 2006 Standard Specifications may be cause to disqualify the Contractor from further bidding for a specified length of time.



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

BEVERLY EAVES PERDUE GOVERNOR EUGENE A. CONTI, JR.
SECRETARY

September 20, 2011

Notice To:

Prospective Bidders, Material Suppliers, and Subcontractors

From:

R.A. Garris, P.E.

State Contract Officer

Subject:

2006 Metric Standard Specifications for Roads and Structures and 2006

Metric Roadway Standard Drawings

In 1999, the North Carolina Department of Transportation elected to return to the English measurement system when developing project plans as a result of the elimination of the FHWA metric requirement in the 1998 TEA 21 legislation. However, design efforts had already begun on approximately sixty projects utilizing the metric measurement system. Of those, some remained metric and were let under the 2002 Specifications and Standards, and some were reengineered (converted) to English plans. Currently, there are fourteen projects that will be designed, let and constructed utilizing the 2006 Metric Specifications and Standards. See attached list for project information and tentative let dates.

The Metric Specifications Book is a mirror image of the 2006 (English) Specifications Book, except for the conversion to metric units and dimensions. The 2006 Metric Standard Drawings is a mirror image of the 2006 (English) Standard Drawings, except that Standards 840.25 and 700.01 have been updated to match Details 840D25 and 700D01. The Specifications and Standards are available in .pdf on the Contract Standards and Development Unit's Website at: http://www.ncdot.org/doh/preconstruct/ps/contracts/default.html

The 2006 Metric Specifications and Standards are being printed within the Department and are available for purchase. Due to the small number of metric projects to be let over the next several years, a limited number will be printed. Therefore we ask that you review the attached list of projects and not order immediately if projects of interest to you are further out in the future. This will allow us to manage the printing demands much more efficiently. The 2006 Metric Standard Specifications for Roads and Structures and the 2006 Metric Roadway Standard Drawings are \$25.00 each plus 6.75% North Carolina sales tax. To request a copy, please contact Rick Montanez at 919-707-6944, or place your order electronically at the following Website: http://www.ncdot.org/business/order/puborder.html

If you have any questions, I can be reached at (919) 707-6900.

UPDATED September 20, 2011

| TIP# | DIVISION | COUNTY | DESCRIPTION | TENTATIVE LET DATE |
|---------|----------|---------|---|-----------------------|
| B-4183 | 13 | MADISON | BRIDGE 29 OVER MIDDLE FORK CREEK ON SR 1526 AND BRIDGE 28 OVER CROOKED CREEK ON SR 1526 | DECEMBER 20, 2011 |
| R-2414B | 1 | CAMDEN | US 158/NC 34 FROM NORTH OF SR 1257 TO EAST OF NC 34 IN BELCROSS | FEBRUARY 21, 2012 |
| R-2554A | 4 | WAYNE | US 70 (GOLDSBORO BYPASS) FROM WEST OF NC 581 TO SR 1300 (SALEM CHURCH ROAD) | JUNE 19, 2012 |



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

BEVERLY EAVES PERDUE
GOVERNOR

EUGENE A. CONTI, JR.
SECRETARY

May 24, 2011

Notice To

All Prequalified Contractors

From:

R.A. Garris, P.E.

State Contract Officer

Subject:

Directory of Transportation Firms

The NCDOT has updated its Transportation Directory to include additional items such as the SBE work codes, engineering disciplines, queries based on the physical address, and other reporting options. With the update, a new web address was created for the Directory. The old Directory address is still working, but we encourage the use of the new Directory for your outreach efforts. The new Directory address is https://partner.ncdot.gov/VendorDirectory/default.html.

If you have any problems or have questions regarding the Directory please contact Mr. Mickey Biedell at 919-733-7174.

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION INVITATION TO BID

ELECTRONIC BIDS (UNLESS OTHERWISE SPECIFIED IN THE PROJECT SPECIAL PROVISION) FOR THE CONSTRUCTION OF THE FOLLOWING PROJECTS WILL BE PUBLICLY READ IN ROOM 156-A/B, THE CONTRACT STANDARDS AND DEVELOPMENT UNIT LARGE CONFERENCE ROOM, LOCATED IN BUILDING B AT 1020 BIRCH RIDGE DRIVE, RALEIGH, N.C. AT **2:00 PM** ON JANUARY 17, 2011. NO ELECTRONIC BIDS WILL BE RECEIVED AFTER 2.00 PM.

- 1. THE BIDDER SHALL PURCHASE A PROPOSAL FOR EACH PROJECT FOR WHICH HE INTENDS TO SUBMIT A BID IN RESPONSE TO THIS INVITATION TO BID.
- 2. A BID BOND OR BID DEPOSIT IN THE AMOUNT OF 5% OF THE TOTAL AMOUNT BID WILL BE REQUIRED. THE BIDDER SHALL SUBMIT AN ELECTRONIC BID BOND WITH EACH ELECTRONIC BID SUBMITTAL UNLESS HE ELECTS TO FURNISH A BID DEPOSIT.
- 3. UPON RECEIPT OF AWARD LETTER, THE SUCCESSFUL BIDDER SHALL FURNISH A PROPERLY EXECUTED EXECUTION OF CONTRACT, NON-COLLUSION AFFIDAVIT AND DEBARMENT CERTIFICATION, AND EXECUTED PAYMENT AND PERFORMANCE BONDS FOR EACH CONTRACT. AFFIDAVIT FORMS AND BOND FORMS ARE AVAILABLE AS PART OF THE CONTRACT EXECUTION FORMS AT THE FOLLOWING WEBSITE http://www.ncdot.gov/doh/preconstruct/ps/contracts/letting.html.

ALL QUESTIONS RELATED TO PROJECTS DURING THE ADVERTISEMENT PERIOD SHALL BE ADDRESSED TO THE STATE CONTRACT OFFICER AT 919-707-6900.

THE MINIMUM WAGE FOR LABOR WILL BE SHOWN IN THE PROPOSAL FORM FOR FEDERAL AID PROJECTS.

CONTRACTOR'S LICENSE: A GENERAL CONTRACTOR'S LICENSE IS REQUIRED IN ORDER TO SUBMIT A BID ON ANY NON-FEDERAL AID PROJECT WHERE THE BID IS \$30,000.00 OR MORE, EXCEPT FOR CERTAIN SPECIALTY WORK AS DETERMINED BY THE LICENSING BOARD. FOR ADDITIONAL INFORMATION OR TO MAKE APPLICATION FOR A LICENSE, APPLY TO THE EXECUTIVE SECRETARY OF THE CONTRACTOR LICENSING BOARD, P.O. BOX 17187, RALEIGH, NC 27619, (919-571-4183).

PREQUALIFYING TO BID: ALL PROSPECTIVE BIDDERS SHALL BE PREQUALIFIED WITH THE DEPARTMENT OF TRANSPORTATION PRIOR TO SUBMITTING A BID. CONTRACTORS WHO ARE NOT PREQUALIFIED MAY OBTAIN INFORMATION AND FORMS FOR PREQUALIFYING FROM THE CONTRACTUAL SERVICES UNIT, DIVISION OF HIGHWAYS, DEPARTMENT OF TRANSPORTATION, 1509 MAIL SERVICE CENTER, RALEIGH, N. C., . ALL REQUIRED PREQUALIFICATION STATEMENTS AND DOCUMENTS SHALL BE FILED WITH THE CONTRACTUAL SERVICES UNIT AT LEAST FOUR WEEKS PRIOR TO THE DATE OF OPENING BIDS.

THE DEPARTMENT OF TRANSPORTATION HEREBY NOTIFIES ALL BIDDERS THAT IT WILL AFFIRMATIVELY INSURE THAT IN ANY CONTRACT ENTERED INTO PURSUANT TO THIS INVITATION TO BID, MINORITY BUSINESS ENTERPRISES WILL BE AFFORDED FULL OPPORTUNITY TO SUBMIT BIDS IN RESPONSE TO THIS INVITATION AND WILL NOT BE DISCRIMINATED AGAINST ON THE GROUNDS OF RACE, COLOR, SEX, OR NATIONAL ORIGIN IN COMPENSATION TO THIS AWARD.

PROPOSAL FORMS AT \$25.00 EACH, PLANS (SMALL SIZE) AT \$40.00 PER SET, PLANS (LARGE SIZE) AT \$100.00 PER SET, AND CROSS-SECTIONS AT \$40.00 PER SET, PLUS SALES TAX FOR N.C. RESIDENTS, MAY BE OBTAINED BY TELEPHONING (919-707-6925), FAXING (919-250-4127), OR WRITING TO: PLANS AND PROPOSALS, CONTRACT STANDARDS AND DEVELOPMENT UNIT, DEPARTMENT OF TRANSPORTATION, 1591 MAIL SERVICE CENTER, RALEIGH, N.C., 27699-1591. THESE CHARGES ARE NOT DEPOSITS AND WILL NOT BE REFUNDED. ALL ORDERS FOR PROPOSAL FORMS, PLANS AND CROSS-SECTIONS DELIVERED IN NORTH CAROLINA ARE SUBJECT TO 6.75% SALES TAX. ORDERS MAILED TO OUT OF STATE CONTRACTORS ARE NOT SUBJECT TO SALES TAX. MAKE ALL CHECKS PAYABLE TO THE "N.C. DEPARTMENT OF TRANSPORTATION".

THE RIGHT IS RESERVED TO REJECT ANY OR ALL BIDS.

TODAY'S DATE IS DECEMBER 20, 2011.

BY ORDER OF THE DEPARTMENT OF TRANSPORTATION
(THE WORK WILL CONSIST APPROXIMATELY AS SHOWN ON THE FOLLOWING SHEETS)

(Revised on 14Jul2011)

REVIEW OF PLANS AND PROPOSALS IN DIVISION OFFICE

IN ORDER TO FACILITATE AND ENCOURAGE THE INVOLVEMENT OF MINORITY BUSINESS ENTERPRISES IN THE HIGHWAY CONSTRUCTION PROCESS, IT IS THE POLICY OF THE DEPARTMENT OF TRANSPORTATION, DIVISION OF HIGHWAYS, THAT A SET OF PLANS AND PROPOSAL FOR EACH PROJECT TO BE LET WILL BE MAINTAINED FOR REVIEW BY ANY CONTRACTOR INTERESTED IN BIDDING UPON OR QUOTING WORK IN AN ADVERTISED PROJECT.

THE PROPOSALS AND PLANS WILL BE AVAILABLE FOR REVIEW BEGINNING TWO WEEKS PRIOR TO THE DATE OF BID OPENING IN THE DIVISION OFFICE WHICH WILL ADMINISTER THE CONTRACT. THE DEPARTMENT WILL, UPON REQUEST, MAKE AVAILABLE FROM ITS STAFF A PERSON TO EXPLAIN THE PROPOSED PROJECT AND TO ANSWER GENERAL QUESTIONS RELATING TO THE PROJECT. THE PLANS AND PROPOSALS CAN BE REVIEWED ANY TIME MONDAY THRU FRIDAY, EXCLUDING HOLIDAYS, BETWEEN THE HOURS OF 8:00 A.M. AND 4:30 P.M. IN THE DIVISION OFFICE. IN ORDER TO HAVE A MEMBER OF THE STAFF EXPLAIN THE PROJECT AND/OR ANSWER GENERAL QUESTIONS PERTAINING TO THE PROJECT, PRIOR APPOINTMENTS MUST BE MADE BY CALLING THE APPROPRIATE DIVISION OFFICE.

FOLLOWING ARE THE LOCATIONS AND TELEPHONE NUMBERS OF THE OFFICES IN WHICH THE PLANS AND PROPOSALS WILL BE MADE AVAILABLE, REFERENCE SHOULD BE MADE TO THE SHEETS CONTAINING THE INDIVIDUAL PROJECT QUANTITIES TO DETERMINE WHICH DIVISION OFFICE WILL ADMINISTER THE CONTRACT

| DIV NO 00001 | <u>DIVISION ENGINEER</u> Jerry Jennings, PE | LOCATION 113 AIRPORT DRIVE, SUITE 100 | TOWN EDENTON | TELEPHONE (252) 482-7977 |
|---------------------|---|--|------------------|---------------------------------|
| 00002 | C. E. Lassiter, Jr., PE | PO BOX 1587 | GREENVILLE | (252) 830-3490 |
| 00003 | H. Allen Pope, PE | 5501 BARBADOS BLVD | CASTLE HAYNE | (910) 341-2000 |
| 00004 | John W Rouse, PE | PO BOX 3165 | WILSON | (252) 237-6164 |
| 00005 | J. Wally Bowman, PE | 2612 NORTH DUKE STREET | DURHAM | (919) 220-4600 |
| 00006 | Gregory W Burns, PE | PO BOX 1150 | FAYETTEVILLE | (910) 486-1493 |
| 00007 | James M Mills, PE | PO BOX 14996 | GREENSBORO | (336) 334-3192 |
| 00008 | Tim Johnson, PE | PO BOX 1067 | ABERDEEN | (910) 944-2344 |
| 00009 | S. Pat Ivey, PE | 375 SILAS CREEK PARKWAY | WINSTON-SALEM | (336) 703-6500 |
| 00010 | Barry S Moose, PE | 716 WEST MAIN STREET | ALBEMARLE | (704) 983-4400 |
| 00011 | Michael A Pettyjohn, PE | PO BOX 250 | NORTH WILKESBORO | (336) 667-9111 |
| 00012 | Michael L Holder, PE | PO BOX 47 | SHELBY | (704) 480-5400 |
| 00013 | Jay J Swain, PE | PO BOX 3279 | ASHEVILE | (828) 251-6171 |
| 00014 | Joel B Setzer, PE | 253 WEBSTER ROAD | SYLVA | (828) 586-2141 |
| | | | | |

| Bid I | Letting Numl | ber L120117 | | | |
|-------|--------------|------------------|----------------------------------|-----------|--|
| RPN | Contract Id | WBS | County | Length | JobType |
| 001 | C202908 | 33713.3.1 | CHOWAN | 0.071 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURE. |
| 002 | C202746 | 33730.3.1 | CURRITUCK | 0.109 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURE. |
| 003 | C202910 | 33764.3.1 | HYDE | 0.214 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURE. |
| 004 | C202750 | 33813.3.1 | TYRRELL | 0.434 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURE. |
| 005 | C202808 | 45458.3.1 | CURRITUCK | 24.250 MI | MILLING, RESURFACING, SHOULDER RECONST, AND RUMBLE STRIPS. |
| 006 | C202897 | 1C.048061 ETC. | HYDE, TYRRELL | 19.000 MI | RESURFACING. |
| 007 | C202911 | 1C.058054 ETC. | MARTIN | 22.900 MI | WIDENING, AND RESURFACING. |
| 008 | C202913 | 1CR.10081.19 ETC | BERTIE, HERTFORD, NORTHAMPTON | 50.400 MI | MILLING AND RESURFACING. |
| 009 | C202898 | 1C.021027 ETC. | CHOWAN, WASHINGTON | 20.300 MI | RESURFACING. |
| 010 | C202727 | 33691.3.1 | BEAUFORT | 0.147 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURE. |
| 011 | C202748 | 33751.3.1 | GREENE, PITT | 0.379 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURES. |
| 012 | C202873 | 47064.3.1 | CARTERET | 0.000 MI | REMOVAL AND REPLACEMENT OF FENDER SYSTEM. |
| 013 | C202919 | 2CR.10741.10 | PITT | 1.340 MI | MILLING, AND RESURFACING. |
| *014 | C202576 | 45241.3.1 | ONSLOW | 0.000 MI | COMPUTERIZED SIGNAL SYSTEM. |
| 015 | C202874 | 47065.3.1 | BRUNSWICK | 0.000 MI | REMOVAL AND REPLACEMENT OF FENDER SYSTEM. |
| 016 | C202916 | 3CR.10101.114 ET | BRUNSWICK, NEW HANOVER | 37.240 MI | MILLING, RESURFACING, MILLED RUMBLE STRIPS & SHLDR RECONST. |
| 017 | C202859 | 3CR.10311.115 ET | DUPLIN, SAMPSON | 11.890 MI | WIDENING, MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION. |
| 018 | C202927 | 3CR.10671.117 ET | ONSLOW, PENDER | 25.110 MI | WIDENING, MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION. |
| 019 | C202730 | 33734.3.1 | EDGECOMBE | 0.180 MI | GRADING, DRAINAGE, PAVING, SIGNALS AND STRUCTURE. |
| 020 | C202739 | 33768.3.1 | JOHNSTON | | GRADING, DRAINAGE, PAVING, AND STRUCTURE. |
| 021 | C202749 | 33788.3.1 | NASH | 0.161 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURE. |
| 022 | C202747 | 33739.3.1 | FRANKLIN | 0.170 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURE. |
| 023 | C202733 | 33820.3.1 | WAKE | 0.257 MI | GRADING, DRAINAGE, PAVING, SIGNALS, AND STRUCTURES. |
| 024 | C202751 | 33823.3.1 | WAKE | 0.143 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURE. |
| 025 | C202875 | 47030.3.1 ETC. | WAKE, DURHAM | 17.133 MI | MILLING, RESURFACING, SHOULDER RECONST, AND STR REHAB. |
| 026 | C202928 | 5CR.10321.22 ETC | DURHAM | 13.570 MI | WIDENING, MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION. |
| 027 | C202918 | 5CR.20321.21 | DURHAM | 6.090 MI | MILLING, RESURFACING & SHOULDER RECONSTRUCTION. |
| 028 | C202724 | 33448.2.2 | CUMBERLAND | 0.227 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURES. |
| 029 | C202737 | 33721.3.1 | COLUMBUS | 0.209 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURES. |
| 030 | C202156 | 34762.3.4 | ORANGE | 0.748 MI | WIDENING, GRADING, DRAINAGE, PAVING, AND SIGNALS. |

| | SUMMARY OF PROPOSALS | |
|--|----------------------|--|
|--|----------------------|--|

| Bid Letting Num | ber L120117 | | | |
|-----------------|--------------------|----------------------|-----------|--|
| RPN Contract Id | l WBS | County | Length | JobType |
| *031 C202652 | 34924.3.1 | ROCKINGHAM | 6.052 MI | WIDENING, GRADING, DRAINAGE, PAVING, RET WALL, & STRUCTURES. |
| 032 C202806 | 45438.3.15 | GUILFORD | 0.000 MI | DECK REHABILITATION. |
| 033 C202920 | 30001.38 ETC. | MOORE, LEE | 8.274 MI | MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION. |
| 034 C202745 | 40278.3.1 | FORSYTH | 4.163 MI | GRADING, DRAINAGE, PAVING, SIGNALS, AND STRUCTURES. |
| 035 C202925 | 9CR.10291.9 ETC. | DAVIDSON | 29.473 MI | MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION. |
| 036 C202926 | 9CR.10341.9 ETC. | FORSYTH, STOKES | 40.733 MI | MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION. |
| 037 C202725 | 33632.3.1 | UNION | 0.157 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURE. |
| 038 C202744 | 34977.3.1 | ASHE | 1.492 MI | GRADING, DRAINAGE, PAVING, SIGNALS, AND CULVERT. |
| 039 C202729 | 33708.3.1 | CATAWBA | 0.222 MI | GRADING, DRAINAGE, PAVING, AND STRUCTURES. |
| 040 C202876 | 41892.3.1 | JACKSON | 3.500 MI | PAVEMENT REHABILITATION. |
| 041 C202877 | 41893.3.1 | JACKSON | 5.000 MI | PAVEMENT REHABILITATION. |
| 042 C202899 | 45438.3.13 | HAYWOOD | 0.270 MI | BRIDGE PRESERVATION. |
| Bid Letting Num | ber L120221 | | | |
| RPN Contract Id | l WBS | County | Length | JobType |
| *001 C200800 | 34418.3.5 ETC. | GUILFORD, ROCKINGHAM | 13.231 MI | WIDENING, GRADING, DRAINAGE, PAVING, SIGNALS, & STRUCTURES. |

^{*}NOTE: PLANS FOR JANUARY'S RPN 14 & 31 AND FEBRUARY'S RPN 1 ARE PRICED AS FOLLOWS: SMALL PLANS \$60 LARGE PLANS \$200

Page: 1 of 62

L120117 001

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202908 33713.3.1 DIV OFFICE EDENTON LENGTH = 0.071 MI

COUNTY : CHOWAN

GRADING, DRAINAGE, PAVING, AND STRUCTURE.

 180
 LF
 TEMPORARY SILT FENCE

 225
 TON
 STONE FOR EROSION CONTROL, CLASS A

 30
 TON
 STONE FOR EROSION CONTROL, CLASS B

 320
 TON
 SEDIMENT CONTROL STONE

 1
 ACR
 TEMPORARY MULCHING

 50
 LB
 SEED FOR TEMPORARY SEEDING

 0.25
 TON
 FERTILIZER FOR TEMPORARY SEEDING

 200
 LF
 TEMPORARY SLOPE DRAINS

DBE GOAL 6.0% COMPLETION DATE: SEP 07 2012

BRIDGE OVER QUEEN ANNE CREEK AND APPROACHES ON NC-32.

| | | ROADWAY ITEMS | 4 | EA | INLET PROTECTION AT TEMPORARY SLOPE DRAINS |
|------------|----------|--|--------------|-----------|---|
| | | | 1,700 | LF | SAFETY FENCE |
| Lump Sum | LS | MOBILIZATION | 40 | CY | SILT EXCAVATION |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- | 1,550 | SY | MATTING FOR EROSION CONTROL |
| | | BING | 1,600 90 | LF SY | 1/4" HARDWARE CLOTH FLOATING TURBIDITY CURTAIN |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH | 1.5 | ACR | SEEDING & MULCHING |
| | | FILL, STATION ************************************ | 0.5 | | MOWING |
| Lump Sum | LS | GRADING | 50 | LB | SEED FOR REPAIR SEEDING |
| 400 | CY | UNDERCUT EXCAVATION | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| 400 | CY | SELECT GRANULAR MATERIAL | 50 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| 400 | SY | FABRIC FOR SOIL STABILIZATION | 0.5 | TON | FERTILIZER TOPDRESSING |
| 69 | TON | FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS | 10 25 | MHR EA | SPECIALIZED HAND MOWING RESPONSE FOR EROSION CONTROL |
| 2,132 | SY | FOUNDATION CONDITIONING FABRIC | | | |
| 16 | LF | 15" DRAINAGE PIPE | | | |
| 25 | TON | INCIDENTAL STONE BASE | | | |
| 770 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (1-1/2") | | | STRUCTURE ITEMS |
| 120 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE AT STATION ********** |
| 120 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0B | 1 | EA | (21+24.00-L-) PDA TESTING |
| 260 | TON | ASPHALT CONC SURFACE COURSE, | 1 | EA | PDA ASSISTANCE |
| | | TYPE S9.5B | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| 30 | TON | ASPHALT BINDER FOR PLANT MIX | 1 | | TION AT STATION ******* |
| 15 | TON | ASPHALT PLANT MIX, PAVEMENT REPAIR | 40.4 | | (21+24.00-L-) |
| 23 | CY | SUBDRAIN EXCAVATION | 68.6 | CY | CLASS AA CONCRETE (BRIDGE) |
| 17 | CY | SUBDRAIN FINE AGGREGATE | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| 100 | LF | 6" PERFORATED SUBDRAIN PIPE | | | (21+24.00-L-) |
| 1 | EA | SUBDRAIN PIPE OUTLETS | 8,571 | LB | EPOXY COATED REINFORCING STEEL |
| 6 | LF | 6" OUTLET PIPE (SUBDRAINS) | | | (BRIDGE) |
| 1 | EA | MASONRY DRAINAGE STRUCTURES | 1,035 | LF | HP14X73 STEEL PILES |
| 1 | EA | FRAME WITH TWO GRATES, STD | 18 106.02 | EA LF | PILE REDRIVES TWO BAR METAL RAIL |
| 14 | LF | 840.29 SHOULDER BERM GUTTER | 121.43 | LF | 1'-**"X *****" CONCRETE PARA- |
| 625 | LF | STEEL BM GUARDRAIL | 121.43 | 1.1 | PET |
| 5 | EA | ADDITIONAL GUARDRAIL POSTS | | | (1'-2" X 2'-7 1/2") |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE | Lump Sum | LS | ELASTOMERIC BEARINGS |
| 4 | EA | III GUARDRAIL ANCHOR UNITS, TYPE | 910.7 | LF | 3'-0" X 2'-0" PRESTRESSED CONC CORED SLABS |
| 7 | LA | 350 | 7,645 | SF | GENERIC STRUCTURE ITEM |
| 1 | TON | RIP RAP, CLASS B | | | (18" STEEL SHEET PILES) |
| 455 | SY | FILTER FABRIC FOR DRAINAGE | | | |
| 386 | SF | WORK ZONE SIGNS (STATIONARY) | | | |
| 96 | SF | WORK ZONE SIGNS (PORTABLE) | | | |
| 119 | SF | WORK ZONE SIGNS (BARRICADE MOUNTED) | | | |
| 20 | EA | CONES | | | |
| 640 | LF | BARRICADES (TYPE III) | | | |
| 640 | HR | FLAGGER THERMORI A STIC DAVIEMENT MADKING | | | |
| 747 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) | | | |
| 747 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) | | | |
| 10 | EA | PERMANENT RAISED PAVEMENT MARKERS | | | |
| 638 | LF | 6" WATER LINE | | | |
| 2 | EA | 6" VALVE | | | |
| 541 423 | LF LF | ABANDON 6" UTILITY PIPE TRENCHLESS INSTALLATION OF 6" | | | |
| 423 | LF LF | IN SOIL TRENCHLESS INSTALLATION OF 6" | | | |
| 4/ | LF | NOT IN SOIL | | | |

Page: 2 of 62

L120117 002

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

DIV OFFICE EDENTON **CONTRACT ID: C202746** 33730.3.1 LENGTH = 0.109 MI

COUNTY : CURRITUCK

> Lump Sum Lump Sum

GRADING, DRAINAGE, PAVING, AND STRUCTURE.

BING

DBE GOAL 6.0% COMPLETION DATE: NOV 15 2012

BRIDGE OVER TULLS CREEK AND APPROACHES ON SR-1232.

| | DO A DAMA SZ JEDENICO | 1.5 | ΔCR | MOWING |
|----|----------------------------|------|-------------|-------------------------------|
| | ROADWAY ITEMS | 50 | | SEED FOR REPAIR SEEDING |
| | | 50 | LD | SEED FOR REPAIR SEEDING |
| | | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| LS | MOBILIZATION | 50 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| LS | REINFORCED BRIDGE APPROACH | 0.75 | TON | FERTILIZER TOPDRESSING |
| | FILL STATION ********* | 10 | MHR | SPECIALIZED HAND MOWING |

(14+49.00 -L-) 18 EA RESPONSE FOR EROSION CONTROL Lump Sum LS GRADING 1 ACR SUPPLEMENTARY CLEARING & GRUB-

STRUCTURE ITEMS UNDERCUT EXCAVATION 500 CY SELECT GRANULAR MATERIAL 500 CY 500 SY GEOTEXTILE FOR SOIL STABILIZA-REMOVAL OF EXISTING STRUCTURE Lump Sum LS

2,150 TON ROCK EMBANKMENTS (14+49.00-L-) GENERIC GRADING ITEM 1 980 SY FILTER FABRIC FOR ROCK 1 EA PDA TESTING Lump Sum LS EMBANKMENTS UNCLASSIFIED STRUCTURE EXCAVA-

190 SYGENERIC GRADING ITEM TION AT STATION ****** ROCK PLATING FOUNDATION CONDITIONING MATE-CLASS AA CONCRETE (BRIDGE) 50.6 CY 5

TON BRIDGE APPROACH SLABS, STATION RIAL, MINOR STRUCTURES Lump Sum LS FOUNDATION CONDITIONING GEO-20 SY (14+49.00-L-) TEXTILE

EPOXY COATED REINFORCING STEEL 15" RC PIPE CULVERTS, CLASS IV 8,542 LB (BRIDGE) EA PIPE CLEAN-OUT

12" PRESTRESSED CONCRETE PILES 500 LF 380 TON #57 STONE 16" PRESTRESSED CONCRETE PILES 600 LF ASPHALT CONC BASE COURSE, TYPE 210 TON

12 EA PILE REDRIVES ASPHALT CONC SURFACE COURSE, 239.75 LF VERTICAL CONCRETE BARRIER RAIL 240 TON TYPE SF9.5A 126 TON RIP RAP, CLASS **

CLASS I (2'-0" THICK) ASPHALT BINDER FOR PLANT MIX 30 TON GEOTEXTILE FOR DRAINAGE 22.4 CY SUBDRAIN EXCAVATION 141 SY

SUBDRAIN FINE AGGREGATE Lump Sum LS ELASTOMERIC BEARINGS 16.8 CY1,315.88 LF 3'-0" X 1'-6" PRESTRESSED CONC 6" PERFORATED SUBDRAIN PIPE 100 LF CORED SLABS SUBDRAIN PIPE OUTLET 1

EA 6 LF 6" OUTLET PIPE 1 EA MASONRY DRAINAGE STRUCTURES

SHOULDER BERM GUTTER 100 LF

1 EA MODIFIED CONCRETE FLUME

337.5 LF STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS EA

2 EA GUARDRAIL ANCHOR UNITS, TYPE

FRAME WITH TWO GRATES, STD

(350 TL-2)

840.29

GUARDRAIL ANCHOR UNITS, TYPE 4 EA

2 EA GUARDRAIL ANCHOR UNITS, TYPE

EA

5 TON RIP RAP, CLASS B

GEOTEXTILE FOR DRAINAGE 465

DISPOSAL OF SIGN SYSTEM, WOOD 6 EA

WORK ZONE SIGNS (STATIONARY) 270 SF WORK ZONE SIGNS (BARRICADE 94 SF

MOUNTED)

80 LF BARRICADES (TYPE III)

PAINT PAVEMENT MARKING LINES LF 4,600

1,255 TEMPORARY SILT FENCE

STONE FOR EROSION CONTROL, 225 TON

CLASS A

25 TON STONE FOR EROSION CONTROL, CLASS B

SEDIMENT CONTROL STONE 85 TON

ACR TEMPORARY MULCHING 1.5

50 SEED FOR TEMPORARY SEEDING LB

0.25 TON FERTILIZER FOR TEMPORARY SEED-

ING

200 LF TEMPORARY SLOPE DRAINS

LF SAFETY FENCE 475

30 CY SILT EXCAVATION

1,500 SY MATTING FOR EROSION CONTROL

1/4" HARDWARE CLOTH 370 LF

FLOATING TURBIDITY CURTAIN 150 SY COIR FIBER BAFFLE 10 LF

1.5 ACR SEEDING & MULCHING

Page: 3 of 62

L120117 003

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202910 33764.3.1 DIV OFFICE EDENTON LENGTH = 0.214 MI

COUNTY : HYDE

GRADING, DRAINAGE, PAVING, AND STRUCTURE.

DBE GOAL 6.0% COMPLETION DATE: DEC 31 2013

BRIDGE #45 OVER A CANAL AND APPROACHES ON US-264.

| | | ROADWAY ITEMS | 4 | EA | GENERIC TRAFFIC CONTROL ITEM WARNING FLAGS |
|----------------------|------------|--|------------|------------|--|
| Lump Sum | 1.0 | MOBILIZATION | 270 | DAY | GENERIC TRAFFIC CONTROL ITEM TEMPORARY TRAFFIC SIGNAL |
| Lump Sum Lump Sum | LS LS | CONSTRUCTION SURVEYING | 40 | EA | SYSTEM TEMPORARY RAISED PAVEMENT |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | 2,565 | LF | MARKERS THERMOPLASTIC PAVEMENT MARKING |
| Lump Sum | LS | (22+60.00) GRADING | 2,532 | LF | LINES (4", 90 MILS) THERMOPLASTIC PAVEMENT MARKING |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- BING | 44 | LF | LINES (4", 120 MILS) |
| 400 | CY | UNDERCUT EXCAVATION | 44 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 4 20 | EA CY | EMBANKMENT SETTLEMENT GAUGES DRAINAGE DITCH EXCAVATION | 15,500 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 400 | CY | SELECT GRANULAR MATERIAL | 90 | LF | PAINT PAVEMENT MARKING LINES |
| 500 699 | SY SF | FABRIC FOR SOIL STABILIZATION TEMPORARY SHORING | 4,234 | LF | (24") REMOVAL OF PAVEMENT MARKING |
| 450 | SY | GENERIC GRADING ITEM | 60 | LF | LINES (4") REMOVAL OF PAVEMENT MARKING |
| | | FABRIC FOR EMBANKMENT STABILI- ZATION | 00 | | LINES (24") |
| 31 | TON | FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS | 16 | EA | PERMANENT RAISED PAVEMENT MARKERS |
| 860 32 | SY LF | FOUNDATION CONDITIONING FABRIC 15" DRAINAGE PIPE | 165 97 | LF LF | 4" WATER LINE 6" WATER LINE |
| 56 | LF | 18" DRAINAGE FIPE | 2 | EA | 6" VALVE |
| 24 | LF | 18" SIDE DRAIN PIPE | 1 235 | EA LF | FIRE HYDRANT ABANDON **" UTILITY PIPE |
| 68 | LF | 15" RC PIPE CULVERTS, CLASS III | | | (4") |
| 42 | LF | PIPE REMOVAL | 18 1 | LF EA | ABANDON 6" UTILITY PIPE REMOVE FIRE HYDRANT |
| 180 40 | TON TON | AGGREGATE BASE COURSE INCIDENTAL STONE BASE | 2,100 | LF | TEMPORARY SILT FENCE |
| 1,330 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B | 350 | TON | STONE FOR EROSION CONTROL, CLASS A |
| 830 | TON | ASPHALT CONC SURFACE COURSE, TYPE 59.5B | 100 | TON | STONE FOR EROSION CONTROL, CLASS B |
| 80 | TON | ASPHALT CONC SURFACE COURSE, | 70 3 | TON ACR | SEDIMENT CONTROL STONE TEMPORARY MULCHING |
| 115 | TON | TYPE SF9.5A ASPHALT BINDER FOR PLANT MIX | 100 | LB | SEED FOR TEMPORARY SEEDING |
| 20 | TON | ASPHALT PLANT MIX, PAVEMENT REPAIR | 1.5 | TON | FERTILIZER FOR TEMPORARY SEED-ING |
| 22.4 | CY | SUBDRAIN EXCAVATION | 600 12 | LF EA | TEMPORARY SLOPE DRAINS INLET PROTECTION AT TEMPORARY |
| 16.8 100 | CY LF | SUBDRAIN FINE AGGREGATE 6" PERFORATED SUBDRAIN PIPE | 12 | EA | SLOPE DRAINS |
| 1 | EA | SUBDRAIN PIPE OUTLETS | 900 270 | LF CY | SAFETY FENCE SILT EXCAVATION |
| 6 | LF EA | 6" OUTLET PIPE (SUBDRAINS) MASONRY DRAINAGE STRUCTURES | 1,865 | SY | MATTING FOR EROSION CONTROL |
| 2 | EA | FRAME WITH TWO GRATES, STD | 300 | SY | COIR FIBER MAT |
| 1 | EA | 840.29 FRAME WITH COVER, STD 840.54 | 250 500 | LF SY | 1/4" HARDWARE CLOTH FLOATING TURBIDITY CURTAIN |
| 50 | LF | SHOULDER BERM GUTTER | 450 | LF | WATTLE |
| 75 | LF | STEEL BM GUARDRAIL | 50 | LB | POLYACRYLAMIDE (PAM) |
| 125 | LF | STEEL BM GUARDRAIL, SHOP CURVED | 175 2 | LF EA | COIR FIBER BAFFLE **" SKIMMER |
| 5 | EA | ADDITIONAL GUARDRAIL POSTS | 2 | ı CD | (1-1/2") |
| 2 | EA | GUARDRAIL ANCHOR UNITS, TYPE AT-1 | 3 | ACR | SEEDING & MULCHING MOWING |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 50 | LB | SEED FOR REPAIR SEEDING |
| 2 | EA | III GUARDRAIL ANCHOR UNITS, TYPE | 0.25 75 | TON LB | FERTILIZER FOR REPAIR SEEDING SEED FOR SUPPLEMENTAL SEEDING |
| 510.5 | LE | 350 TEMPORARY STEEL BM GUARDRAIL | 2 | TON | FERTILIZER TOPDRESSING |
| 512.5 162.5 | LF LF | TEMPORARY STEEL BM GUARDRAIL TEMPORARY STEEL BM GUARDRAIL | | | SPECIALIZED HAND MOWING |
| 4 | EA | (SHOP CURVED) GUARDRAIL ANCHOR UNITS, TYPE | 18 0.1 | EA ACR | RESPONSE FOR EROSION CONTROL REFORESTATION |
| 6 | EA | ******* TEMPORARY (III MODIFIED) GUARDRAIL ANCHOR UNITS, TYPE | | | |
| 5 | TON | 350 TEMPORARY RIP RAP, CLASS B | | | STRUCTURE ITEMS |
| 714 | SY | FILTER FABRIC FOR DRAINAGE | I G | 1.0 | DEMOVAL OF EVICTING CADITION IN |
| 244 192 | SF SF | WORK ZONE SIGNS (STATIONARY) WORK ZONE SIGNS (POPTABLE) | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE AT STATION ********** |
| 40 | SF | WORK ZONE SIGNS (PORTABLE) WORK ZONE SIGNS (BARRICADE | 2 | EA | (22+60.00 -L-) PDA TESTING |
| | | MOUNTED) | 2 2 | EA | PDA ASSISTANCE |
| 90 80 | EA LF | DRUMS BARRICADES (TYPE III) | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| 960 | HR | FLAGGER | | | TION AT STATION ******* (22+60.00 -L-) |
| 15 | EA | SKINNY DRUM | 70.8 | CY | CLASS AA CONCRETE (BRIDGE) |

| Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
|----------|-----|--------------------------------|
| | | (22+60.00 -L-) |
| 10,760 | LB | EPOXY COATED REINFORCING STEEL |
| | | (BRIDGE) |
| 560 | LF | 12" PRESTRESSED CONC PILES |
| 800 | LF | 16" PRESTRESSED CONC PILES |
| 16 | EA | PILE REDRIVES |
| 232.63 | LF | ONE BAR METAL RAIL |
| 247.63 | LF | 1'-**"X *****" CONCRETE PARA- |
| | | PET |
| | | (1'-2" X 2'-7 3/4") |
| 225 | TON | RIP RAP CLASS II (2'-0" THICK) |
| 251 | SY | FILTER FABRIC FOR DRAINAGE |
| Lump Sum | LS | ELASTOMERIC BEARINGS |
| 1,853.44 | LF | 3'-0" X 1'-9" PRESTRESSED CONC |
| | | CORED SLABS |
| | | |

Page: 5 of 62 L120117 004

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202750 33813.3.1 DIV OFFICE EDENTON LENGTH = 0.434 MI

COUNTY : TYRRELL

GRADING, DRAINAGE, PAVING, AND STRUCTURE.

DBE GOAL 7.0% COMPLETION DATE: DEC 31 2013

BRIDGE #6 OVER NORTHWEST FORK AND APPROACHES ON NC-94.

| | | ROADWAY ITEMS | 1,900 1,200 | LF LF | ABANDON 6" UTILITY PIPE TRENCHLESS INSTALLATION OF 6" IN SOIL |
|------------|------------|--|----------------|------------|---|
| Lump Sum | LS | MOBILIZATION | 125 | LF | TRENCHLESS INSTALLATION OF 6" NOT IN SOIL |
| Lump Sum | LS | CONSTRUCTION SURVEYING | 5,595 | LF | TEMPORARY SILT FENCE |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | 225 | TON | STONE FOR EROSION CONTROL, CLASS A |
| 1,375 | CY | (26+90) UNDERCUT EXCAVATION | 60 | TON | STONE FOR EROSION CONTROL, CLASS B |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- | 135 | TON | SEDIMENT CONTROL STONE |
| Lump Sum | LS | BING GRADING | 3.5 | ACR | TEMPORARY MULCHING |
| 4,010 | CY | BORROW EXCAVATION | 150 | LB | SEED FOR TEMPORARY SEEDING |
| 2,900 | CY | SELECT GRANULAR MATERIAL, CLASS III | 1 | TON | FERTILIZER FOR TEMPORARY SEED- ING |
| 1,300 | SY | GEOTEXTILE FOR SOIL STABILIZA- | 200 4,300 | LF LF | TEMPORARY SLOPE DRAINS SAFETY FENCE |
| 1,500 | SF | TION TEMPORARY SHORING | 500 | CY | SILT EXCAVATION |
| 77 | TON | FOUNDATION CONDITIONING MATE- | 1,515 | SY | MATTING FOR EROSION CONTROL |
| | | RIAL, MINOR STRUCTURES | 770 | SY | COIR FIBER MAT |
| 210 | SY | FOUNDATION CONDITIONING GEO- TEXTILE | 560 500 | LF SY | 1/4" HARDWARE CLOTH FLOATING TURBIDITY CURTAIN |
| 44 | LF | 15" DRAINAGE PIPE | 75 | LF | COIR FIBER WATTLE |
| 60 | LF | 15" RC PIPE CULVERTS, CLASS | 220 | LF | COIR FIBER BAFFLE |
| 2 | TON | III | 2 | EA | **" SKIMMER |
| 1,620 | TON TON | AGGREGATE BASE COURSE ASPHALT CONC BASE COURSE, TYPE | 3 | ACR | (1-1/2") SEEDING & MULCHING |
| 1,020 | 1011 | B25.0B | 3 | ACR | MOWING |
| 750 | TON | ASPHALT CONC SURFACE COURSE, | 50 | LB | SEED FOR REPAIR SEEDING |
| 125 | TON | TYPE SF9.5A ASPHALT BINDER FOR PLANT MIX | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| 20 | TON | ASPHALT PLANT MIX, PAVEMENT | 75 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| | | REPAIR | 2 10 | TON MHR | FERTILIZER TOPDRESSING SPECIALIZED HAND MOWING |
| 112 | CY | SUBDRAIN EXCAVATION | 18 | EA | RESPONSE FOR EROSION CONTROL |
| 84 500 | CY LF | SUBDRAIN FINE AGGREGATE 6" PERFORATED SUBDRAIN PIPE | 0.52 | ACR | WETLAND REFORESTATION |
| 1 | EA | SUBDRAIN PIPE OUTLET | 0.52 | ACR | GENERIC EROSION CONTROL ITEM |
| 6 | LF | 6" OUTLET PIPE | 0.52 | ACR | DISKING GENERIC EROSION CONTROL ITEM |
| 1.4 | CY | ENDWALLS | 0.52 | | RIPPING |
| 2 2 | EA EA | MASONRY DRAINAGE STRUCTURES FRAME WITH TWO GRATES, STD | | | |
| 2 | LA | 840.29 | | | |
| 2 | EA | **" SLUICE GATE | | | STRUCTURE ITEMS |
| 40 | LF | (15") SHOULDER BERM GUTTER | | | |
| 600 | LF | STEEL BM GUARDRAIL | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE |
| 5 | EA | ADDITIONAL GUARDRAIL POSTS | • | | AT STATION ************************************ |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE III | 2 | EA | (26+90.00-L-) PDA TESTING |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| | | 350 | • | | TION AT STATION ******* |
| 275 2 | LF EA | TEMPORARY STEEL BM GUARDRAIL TEMPORARY GUARDRAIL ANCHOR | 115.5 | CY | (26+90.00-L-) CLASS AA CONCRETE (BRIDGE) |
| 2 | LA | UNITS, TYPE ********* | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| | | (III MOD) | | | ************ |
| 2 | EA | TEMPORARY GUARDRAIL ANCHOR UNITS, TYPE 350 | 22,717 | LB | (26+90.00-L-) EPOXY COATED REINFORCING STEEL |
| 5 | TON | RIP RAP, CLASS B | ==,, | | (BRIDGE) |
| 465 | SY | GEOTEXTILE FOR DRAINAGE | 930 | LF | HP12X53 STEEL PILES |
| 284 | SF | WORK ZONE SIGNS (STATIONARY) | 12 54 | EA EA | PIPE PILE PLATES PILE REDRIVES |
| 96 45 | SF EA | WORK ZONE SIGNS (PORTABLE) DRUMS | 720.5 | LF | TWO BAR METAL RAIL |
| 60 | | FLAGGER | 735.5 | LF | 1'-**"X *****" CONCRETE PARA- |
| 2 | EA | TEMPORARY CRASH CUSHIONS | | | PET (1'-2" X 2'-7 1/2") |
| 2 | EA | RESET TEMPORARY CRASH CUSHION | 231 | TON | RIP RAP CLASS II (2'-0" THICK) |
| 525 200 | LF LF | PORTABLE CONCRETE BARRIER RESET PORTABLE CONCRETE BAR- | 257 | SY | GEOTEXTILE FOR DRAINAGE |
| 200 | LI | RIER | Lump Sum | LS | ELASTOMERIC BEARINGS |
| 365 | DAY | GENERIC TRAFFIC CONTROL ITEM TEMPORARY TRAFFIC SIGNAL | 4,402.5 | LF | 3'-0" X 1'-9" PRESTRESSED CONC CORED SLABS |
| 166 | EA | SYSTEM TEMPORARY RAISED PAVEMENT MARKERS | 2,670 | LF | GENERIC STRUCTURE ITEM HP 14 X 73 METALLIZED STEEL PI LES |
| 25,140 | LF | PAINT PAVEMENT MARKING LINES | 1,080 | LF | GENERIC STRUCTURE ITEM PP 24 X 0.50 METALLIZED STEEL |
| 2,000 | LF | (4") REMOVAL OF PAVEMENT MARKING LINES (4") | | | PILES |
| 1,940 | LF | 6" WATER LINE | | | |
| 2 | EA | 6" VALVE | | | |

Page: 6 of 62

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

L120117 005

CONTRACT ID: C202808 45458.3.1 DIV OFFICE EDENTON

LENGTH = 24.250 MI

: CURRITUCK

MILLING, RESURFACING, SHOULDER RECONST, AND RUMBLE STRIPS.

DBE GOAL 5.0% COMPLETION DATE: NOV 02 1012

US-158 FROM US-168 TO THE WRIGHT MEMORIAL BRIDGE.

| Lump Sum | LS | MOBILIZATION |
|------------|----------|--|
| 210 120 | CY SY | BORROW EXCAVATION REMOVAL OF EXISTING ASPHALT |
| 120 | 51 | PAVEMENT |
| 22 | TON | FOUNDATION CONDITIONING MATERIAL, MINOR STRS |
| 50 | SY | FOUNDATION CONDITIONING FABRIC |
| 60 | LF | 24" RC PIPE CULVERTS, CLASS III |
| 88 | LF | 30" RC PIPE CULVERTS, CLASS |
| 155 | TON | INCIDENTAL STONE BASE |
| 39.5 | SMI | SHOULDER RECONSTRUCTION |
| 949,252 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (1-1/2") |
| 949,252 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (3/4") |
| 311 | SY | INCIDENTAL MILLING |
| 130 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B |
| 87,369 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5C |
| 5,160 | TON | ASPHALT BINDER FOR PLANT MIX |
| 2,646 | TON | POLYMER MODIFIED ASPHALT BIN- DER FOR PLANT MIX |
| 43,372 | TON | OPEN-GRADED ASPHALT FRICTION COURSE, TYPE FC-2 MODIFIED |
| 63 | TON | ASPHALT PLANT MIX, PAVEMENT REPAIR |
| 256,108 | LF | MILLED RUMBLE STRIPS (ASPHALT CEMENT CONCRETE) |
| 7 | EA | GENERIC DRAINAGE ITEM REPAIR MASONRY DRAINAGE STRUC- TURE |
| 5 | EA | ADJUSTMENT OF METER BOXES OR VALVE BOXES |
| Lump Sum | LS | GENERIC TRAFFIC CONTROL ITEM TRAFFIC CONTROL |
| 683 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 28 | EA | THERMOPLASTIC PAVEMENT MARKING CHARACTER (120 MILS) |
| 2,097,404 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 1,483 | LF | PAINT PAVEMENT MARKING LINES (24") |
| 581,975 | LF | POLYUREA PAVEMENT MARKING LINES (6", ********) |
| 877 | EA | (HIGHLY REFLECTIVE ELEMENTS) POLYUREA PAVEMENT MARKING SYMBOL (**********) |
| 11,250 | LF | (HIGHLY REFLECTIVE ELEMENTS) REMOVAL OF PAVEMENT MARKING LINES (6") |
| 5,472 | EA | PERMANENT RAISED PAVEMENT MARKERS |
| 4,032 | LF | TEMPORARY SILT FENCE |
| 661 | SY | MATTING FOR EROSION CONTROL |
| 1,653 | LF | WATTLE |
| 144 | LB | POLYACRYLAMIDE (PAM) |
| 28.7 | ACR | SEEDING & MULCHING |
| 300 | LF | UNPAVED TRENCHING (*******) (1,2") |
| 12 | EA | JUNCTION BOX (STANDARD SIZE) |
| 2,246 | LF | INDUCTIVE LOOP SAWCUT |
| 600 | LF | LEAD-IN CABLE (************) (14-2) |
| | | |

Page: 7 of 62

L120117 006

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202897 1C.048061 DIV OFFICE EDENTON LENGTH = 19.000 MI

COUNTY: HYDE, TYRRELL

RESURFACING.

MBE GOAL 3.0% WBE 3.0% COMPLETION DATE: SEP 07 2012

1 SECTION OF NC-45 AND 7 SECTIONS OF SECONDARY ROADS.

| Lump Sum | LS | MOBILIZATION |
|----------|-----|---|
| 24,640 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (2") |
| 548 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B |
| 2,790 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 17,672 | TON | ASPHALT CONC SURFACE COURSE, TYPE SF9.5A |
| 1,345 | TON | ASPHALT BINDER FOR PLANT MIX |
| Lump Sum | LS | TEMPORARY TRAFFIC CONTROL |
| 659,680 | LF | PAINT PAVEMENT MARKING LINES (4") |

Page: 8 of 62

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

L120117 007

CONTRACT ID : C202911 1C.058054 DIV OFFICE EDENTON LENGTH = 22.900 MI

COUNTY : MARTIN

WIDENING, AND RESURFACING.

MBE GOAL 3.0% WBE 3.0% COMPLETION DATE : OCT 05 2012

NC-125 FROM NC-903 TO HAMILTON CITY LIMITS, AND 9 SECTIONS OF SECONDARY ROADS.

ROADWAY ITEMS

 Lump Sum
 LS
 MOBILIZATION

 1,260
 TON
 ASPHALT CONC BASE COURSE, TYPE B25.0B

 4,078
 TON
 ASPHALT CONC SURFACE COURSE, TYPE S9.5B

 20,428
 TON
 ASPHALT CONC SURFACE COURSE, TYPE S79.5A

 1,671
 TON
 ASPHALT BINDER FOR PLANT MIX

 Lump Sum
 LS
 TEMPORARY TRAFFIC CONTROL

 795,088
 LF
 PAINT PAVEMENT MARKING LINES

Page: 9 of 62

LENGTH = 50.400 MI

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

L120117 008

DIV OFFICE EDENTON

: BERTIE, HERTFORD, NORTHAMPTON

1CR.10081.19

MILLING AND RESURFACING.

CONTRACT ID: C202913

MBE GOAL 3.0% WBE 3.0% COMPLETION DATE: JUL 31 2012

VARIOUS SECTIONS OF US-13, US-13 BUS, US-17 BUS, NC-46, NC-48, NC-305 & NC-308 AND 17 SECTIONS OF SECONDARY ROADS.

| I C | 1.0 | MODIL 17 ATION |
|----------|------|--|
| Lump Sum | LS | MOBILIZATION |
| 37,000 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH |
| | | (1-1/2") |
| 7,200 | SY | MILLING ASPHALT PAVEMENT, ***" |
| 7,200 | 51 | DEPTH |
| | | (2-1/2") |
| 2,425 | SY | INCIDENTAL MILLING |
| 3,065 | TON | ASPHALT CONC BASE COURSE, TYPE |
| | | B25.0B |
| 1,000 | TON | ASPHALT CONC INTERMEDIATE |
| | | COURSE, TYPE I19.0B |
| 20,625 | TON | ASPHALT CONC SURFACE COURSE, |
| | | TYPE S9.5B |
| 32,525 | TON | ASPHALT CONC SURFACE COURSE, |
| | moss | TYPE SF9.5A |
| 325 | TON | ASPHALT CONC SURFACE COURSE, |
| 2 (22 | TON | TYPE SF9.5A (LEVELING COURSE) ASPHALT BINDER FOR PLANT MIX |
| 3,623 | TON | |
| 150 | LF | 2'-6" CONCRETE CURB & GUTTER |
| 13 | EA | RETROFIT EXISTING CURB RAMP |
| 17 | EA | ADJUSTMENT OF MANHOLES |
| 16 | EA | ADJUSTMENT OF METER BOXES OR |
| | | VALVE BOXES |
| Lump Sum | LS | TEMPORARY TRAFFIC CONTROL |
| 897,548 | LF | PAINT PAVEMENT MARKING LINES |
| 100 | | (4") |
| 100 | LF | PAINT PAVEMENT MARKING LINES (16") |
| 250 | LF | PAINT PAVEMENT MARKING LINES |
| 230 | LF | (24") |
| 16 | EA | PAINT PAVEMENT MARKING CHARAC- |
| 10 | 271 | TER |
| 150 | LF | INDUCTIVE LOOP SAWCUT |
| 25 | LF | LEAD-IN CABLE (************) |
| 25 | | (14-2) |
| | | |

Page: 10 of 62

L120117 009

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202898 1C.021027 DIV OFFICE EDENTON LENGTH = 20.300 MI

COUNTY : CHOWAN, WASHINGTON

RESURFACING.

MBE GOAL 3.0% WBE 3.0% COMPLETION DATE: SEP 28 2012

1 SECTION OF NC-32 AND 3 SECTIONS OF SECONDARY ROADS.

| Lump Sum | LS | MOBILIZATION |
|----------|-----|--|
| 35,200 | SY | MILLING ASPHALT PAVEMENT, ***" TO ******" (0" TO 6") |
| 717 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B |
| 15,404 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 8,895 | TON | ASPHALT CONC SURFACE COURSE, TYPE SF9.5A |
| 1,551 | TON | ASPHALT BINDER FOR PLANT MIX |
| Lump Sum | LS | TEMPORARY TRAFFIC CONTROL |
| 704,816 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 200 | LF | PAINT PAVEMENT MARKING LINES (6") |
| 200 | LF | PAINT PAVEMENT MARKING LINES (8") |

Page: 11 of 62

L120117 010

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

DIV OFFICE GREENVILLE CONTRACT ID: C202727 33691.3.1 LENGTH = 0.147 MI

: BEAUFORT

GRADING, DRAINAGE, PAVING, AND STRUCTURE.

LINES (4") 870 LF 12" WATER LINE

DBE GOAL 7.0% COMPLETION DATE: DEC 31 2012

BRIDGE OVER PUNGO CREEK AND APPROACHES ON NC-32.

| | | DO A DAWA W FEELING | 2 | EA | 12" VALVE |
|-------------|----------|---|---------------|-----------|---|
| | | ROADWAY ITEMS | 866 | LF | ABANDON 12" UTILITY PIPE |
| | | | 693 | LF | TRENCHLESS INSTALLATION OF 12" IN SOIL |
| Lump Sum | LS | MOBILIZATION | 77 | LF | TRENCHLESS INSTALLATION OF 12" |
| Lump Sum | LS | CONSTRUCTION SURVEYING | | | NOT IN SOIL |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL. STATION *********** | 2,875 | LF | TEMPORARY SILT FENCE |
| | | (16+22) | 360 | TON | STONE FOR EROSION CONTROL, |
| Lump Sum | LS | GRADING | 275 | TON | CLASS A |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- | 275 | TON | STONE FOR EROSION CONTROL, CLASS B |
| | | BING | 300 | TON | SEDIMENT CONTROL STONE |
| 300 | CY | UNDERCUT EXCAVATION | 3 | ACR | TEMPORARY MULCHING |
| 300 | CY SY | SELECT GRANULAR MATERIAL FABRIC FOR SOIL STABILIZATION | 150 | LB | SEED FOR TEMPORARY SEEDING |
| 3,220 84 | TON | FOUNDATION CONDITIONING MATE- | 0.5 | TON | FERTILIZER FOR TEMPORARY SEED- |
| 04 | 1011 | RIAL, MINOR STRS | 2.5 | | ING |
| 190 | SY | FOUNDATION CONDITIONING FABRIC | 365 | LF EA | TEMPORARY SLOPE DRAINS |
| 40 | LF | 15" DRAINAGE PIPE | 11 | EA | INLET PROTECTION AT TEMPORARY SLOPE DRAINS |
| 52 | LF | 18" DRAINAGE PIPE | 200 | LF | SAFETY FENCE |
| 160 | LF | 24" DRAINAGE PIPE | 460 | CY | SILT EXCAVATION |
| 316 | LF | 36" DRAINAGE PIPE | 2,300 | SY | MATTING FOR EROSION CONTROL |
| 2 | EA | **" DRAINAGE PIPE ELBOWS (15") | 10 | SY | COIR FIBER MAT |
| 189 | LF | PIPE REMOVAL | 755 | LF | 1/4" HARDWARE CLOTH |
| 400 | TON | STABILIZER AGGREGATE | 200 | SY | FLOATING TURBIDITY CURTAIN |
| 939 | TON | AGGREGATE BASE COURSE | 150 | LF | COIR FIBER WATTLE |
| 100 | TON | INCIDENTAL STONE BASE | 40 | LB | POLYACRYLAMIDE (PAM) |
| 683.2 | GAL | PRIME COAT | 115 | LF ACR | COIR FIBER BAFFLE SEEDING & MULCHING |
| 440 | TON | ASPHALT CONC BASE COURSE, TYPE | 3 | ACR | MOWING |
| 920 | TON | B25.0B | 50 | LB | SEED FOR REPAIR SEEDING |
| 820 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| 70 | TON | ASPHALT BINDER FOR PLANT MIX | 100 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| 22.4 | CY | SUBDRAIN EXCAVATION | 3 | TON | FERTILIZER TOPDRESSING |
| 16.8 | CY | SUBDRAIN FINE AGGREGATE | 10 | MHR | SPECIALIZED HAND MOWING |
| 100 | LF | 6" PERFORATED SUBDRAIN PIPE | 25 | EA | RESPONSE FOR EROSION CONTROL |
| 1 | EA | SUBDRAIN PIPE OUTLETS | 0.75 | ACR | REFORESTATION |
| 6 | LF | 6" OUTLET PIPE (SUBDRAINS) | | | |
| 1 | EA | TEMPORARY STEEL PLATE COVERS FOR MASONRY DRAINAGE | | | |
| | | STRUCTURE | | | STRUCTURE ITEMS |
| 5 | EA | MASONRY DRAINAGE STRUCTURES | | | |
| 2.02 | LF | MASONRY DRAINAGE STRUCTURES | | | |
| 2 | EA | FRAME WITH TWO GRATES, STD | Lump Sum | LS | CONSTRUCTION, MAINTENANCE, & |
| 2 | E.A | 840.24 | | | REMOVAL OF TEMP STRUCTURE AT STA ********* |
| 2 | EA | FRAME WITH TWO GRATES, STD 840.29 | | | (16+22.00-L-) |
| 126 | LF | SHOULDER BERM GUTTER | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE |
| 600 | LF | STEEL BM GUARDRAIL | | | AT STATION ************************************ |
| 5 | EA | ADDITIONAL GUARDRAIL POSTS | 1 | EA | PDA TESTING |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 1 | EA | PDA ASSISTANCE |
| | | 350 | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE B-77 | | | TION AT STATION ******* |
| 325 | LF | TEMPORARY STEEL BM GUARDRAIL | | | (16+22.00-L-) |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 3,836 | SF | CONCRETE WEARING SURFACE |
| | | ****** TEMPORARY | 4,891 51.8 | SF CY | GROOVING BRIDGE FLOORS CLASS A CONCRETE (BRIDGE) |
| _ | | (B-77) | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| 5 | EA | GUARDRAIL ANCHOR UNITS, TYPE 350 TEMPORARY | Eurip Suiii | Lo | ****** |
| 60 | TON | RIP RAP, CLASS I | | | (16+22.00-L-) |
| 520 | SY | FILTER FABRIC FOR DRAINAGE | 7,854 | LB | REINFORCING STEEL (BRIDGE) |
| 1 | EA | PREFORMED SCOUR HOLES WITH | 600 | LF | HP12X53 STEEL PILES |
| | | LEVEL SPREADER APRON | 960 | LF EA | HP14X73 GALVANIZED STEEL PILES |
| 224 | SF | WORK ZONE SIGNS (STATIONARY) | 12 235.5 | EA LF | PILE REDRIVES CONCRETE BARRIER RAIL |
| 96 | SF | WORK ZONE SIGNS (PORTABLE) | 455 | | RIP RAP CLASS II (2'-0" THICK) |
| 42 | SF | WORK ZONE SIGNS (BARRICADE MOUNTED) | 505 | SY | FILTER FABRIC FOR DRAINAGE |
| 30 | EA | DRUMS | Lump Sum | LS | ELASTOMERIC BEARINGS |
| 48 | LF | BARRICADES (TYPE III) | Lump Sum | LS | EVAZOTE JOINT SEALS |
| 42 | MD | FLAGGER | 1,410.02 | LF | 3'-0" X 1'-9" PRESTRESSED CONC |
| 151 | EA | TEMPORARY RAISED PAVEMENT | | | CORED SLABS |
| A. 20 : | | MARKERS | | | |
| 31,686 | LF | PAINT PAVEMENT MARKING LINES (4") | | | |
| 8,250 | LF | REMOVAL OF PAVEMENT MARKING | | | |
| 0,230 | 1-1 | LINES (4") | | | |

Page: 12 of 62

L120117 011

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202748 33751.3.1 DIV OFFICE GREENVILLE LENGTH = 0.379 MI

COUNTY : GREENE, PITT

GRADING, DRAINAGE, PAVING, AND STRUCTURES.

 200
 LB
 SEED FOR TEMPORARY SEEDING

 1.75
 TON
 FERTILIZER FOR TEMPORARY SEEDING

 200
 LF
 TEMPORARY SLOPE DRAINS

 500
 LF
 SAFETY FENCE

280 CY SILT EXCAVATION
1,800 SY MATTING FOR EROSION CONTROL
10 SY COIR FIBER MAT

DBE GOAL 7.0% COMPLETION DATE: SEE SPECIAL PROVISIONS

BRIDGES #35 AND 36 OVER LITTLE CONTENTEA CREEK AND AP-PROACHES ON SR-1343.

| | | ROADWAY ITEMS | 285 | SY | PERMANENT SOIL REINFORCEMENT MAT |
|------------|------------|--|----------|----------|--|
| | | | 1,125 | LF | 1/4" HARDWARE CLOTH |
| Lump Sum | LS | MOBILIZATION | 360 | LF | WATTLE |
| Lump Sum | LS | CONSTRUCTION SURVEYING | 115 | LB | POLYACRYLAMIDE (PAM) |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH | 115 | LF | COIR FIBER BAFFLE |
| | | FILL, STATION ********* | 1 | EA | **" SKIMMER (1-1/2") |
| | | (14+92.50) | 6 | ACR | SEEDING & MULCHING |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ********** | 3 | ACR | MOWING |
| | | (30+70.00) | 50 | LB | SEED FOR REPAIR SEEDING |
| Lump Sum | LS | GRADING | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- | 125 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| | | BING | 3.25 | TON | FERTILIZER TOPDRESSING |
| 300 | CY | UNDERCUT EXCAVATION | 10 | MHR | |
| 300 | CY | SELECT GRANULAR MATERIAL | 18 | EA | RESPONSE FOR EROSION CONTROL |
| 400 | SY | GEOTEXTILE FOR SOIL STABILIZA- TION | 0.1 | ACR | REFORESTATION |
| 20 | TON | FOUNDATION CONDITIONING MATE- | | | |
| | | RIAL, MINOR STRUCTURES | | | |
| 70 | SY | FOUNDATION CONDITIONING GEO- | | | STRUCTURE ITEMS |
| | | TEXTILE | | | |
| 68 | LF | 15" DRAINAGE PIPE | | | |
| 24 | LF | 15" SIDE DRAIN PIPE | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE |
| 92 | LF | 15" RC PIPE CULVERTS, CLASS III | | | AT STATION ************************************ |
| 50 | TON | AGGREGATE BASE COURSE | Lump Sum | LS | (30+70.00-L-) REMOVAL OF EXISTING STRUCTURE |
| 100 | TON | INCIDENTAL STONE BASE | Lump Sum | Lo | AT STATION ********* |
| 1,260 | TON | ASPHALT CONC BASE COURSE, TYPE | | | (14+92.50-L-) |
| | | B25.0B | 2 | EA | PDA TESTING |
| 1,030 | TON | ASPHALT CONC SURFACE COURSE, | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| 105 | TON | TYPE SF9.5A | | | TION AT STATION ************************************ |
| 125 | TON TON | ASPHALT BINDER FOR PLANT MIX | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| 100 | TON | ASPHALT PLANT MIX, PAVEMENT REPAIR | Lump Sum | Lo | TION AT STATION ******* |
| 22.4 | CY | SUBDRAIN EXCAVATION | | | (30+70.00-L-) |
| 16.8 | CY | SUBDRAIN FINE AGGREGATE | 104.8 | CY | CLASS A CONCRETE (BRIDGE) |
| 100 | LF | 6" PERFORATED SUBDRAIN PIPE | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| 1 | EA | SUBDRAIN PIPE OUTLET | | | (14+92.50-L-) |
| 6 | LF | 6" OUTLET PIPE | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| 5 | EA | MASONRY DRAINAGE STRUCTURES | r | | ****** |
| 4 | EA | FRAME WITH GRATE, STD 840.29 | | | (30+70.00-L-) |
| 1 | EA | FRAME WITH COVER, STD 840.54 | 18,066 | LB | REINFORCING STEEL (BRIDGE) |
| 70 | LF | SHOULDER BERM GUTTER | 1,470 | LF | HP12X53 STEEL PILES |
| 1 | EA | ADJUSTMENT OF METER BOXES OR VALVE BOXES | 2,800 | LF | HP14X73 GALVANIZED STEEL PILES |
| 162.5 | LF | STEEL BM GUARDRAIL | 16 60 | EA EA | STEEL PILE POINTS PILE REDRIVES |
| 5 | EA | ADDITIONAL GUARDRAIL POSTS | 571.5 | LF | VERTICAL CONCRETE BARRIER RAIL |
| 8 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 590 | TON | RIP RAP CLASS II (2'-0" THICK) |
| | | III | 650 | SY | GEOTEXTILE FOR DRAINAGE |
| 8 | EA | GUARDRAIL ANCHOR UNITS, TYPE | Lump Sum | LS | ELASTOMERIC BEARINGS |
| 414 | LF | 350 REMOVE EVICTING CHARDRAIL | 2,465 | LF | 3'-0" X 1'-9" PRESTRESSED CONC |
| 414 2.2 | TON | REMOVE EXISTING GUARDRAIL RIP RAP. CLASS B | | | CORED SLABS |
| 517 | SY | GEOTEXTILE FOR DRAINAGE | 840 | LF | 3'-0" X 2'-0" PRESTRESSED CONC |
| 411 | SF | WORK ZONE SIGNS (STATIONARY) | | | CORED SLABS |
| 48 | SF | WORK ZONE SIGNS (PORTABLE) | | | |
| 94 | SF | WORK ZONE SIGNS (BARRICADE | | | |
| | | MOUNTED) | | | |
| 10 | EA | CONES | | | |
| 64 | LF | BARRICADES (TYPE III) | | | |
| 80 | HR | FLAGGER | | | |
| 4,200 | LF | TEMPORARY SILT FENCE | | | |
| 225 | ION | STONE FOR EROSION CONTROL, CLASS A | | | |
| 265 | TON | STONE FOR EROSION CONTROL, | | | |
| 203 | | CLASS B | | | |
| 310 | TON | SEDIMENT CONTROL STONE | | | |
| 5 | ACR | TEMPORARY MULCHING | | | |

Page: 13 of 62

L120117 012

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202873 47064.3.1 DIV OFFICE GREENVILLE LENGTH = 0.000 MI

: CARTERET

REMOVAL AND REPLACEMENT OF FENDER SYSTEM.

DBE GOAL 0.0% COMPLETION DATE: SEP 30 2012

BRIDGE #6 ON NC-58 OVER ATLANTIC INTERCOASTAL WATERWAY BETWEEN NC-24 AND EMERALD ISLE.

STRUCTURE ITEMS

Lump Sum LS MOBILIZATION (STRUCTURES)

1,568 LF PP ** X **** STEEL PILES

(14 X 0.50)

5,656 LF PP ** X **** STEEL PILES (16 X 0.50)

Lump Sum LS GENERIC STRUCTURE ITEM PLASTIC AND COMPOSITE LUMBER

Lump Sum LS GENERIC STRUCTURE ITEM REMOVAL OF EXISTING FENDER

SYSTEM

Page: 14 of 62

L120117 013

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202919 2CR.10741.10 DIV OFFICE GREENVILLE LENGTH = 1.340 MI

COUNTY : PITT

MILLING, AND RESURFACING.

MBE GOAL 3.0% WBE 3.0% COMPLETION DATE: SEP 30 2012

NC-11 FROM END OF TAR RIVER BRIDGE TO US-13.

| Lump Sum | LS | MOBILIZATION |
|----------|-----|--|
| 62,891 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (2") |
| 7,411 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 445 | TON | ASPHALT BINDER FOR PLANT MIX |
| Lump Sum | LS | TEMPORARY TRAFFIC CONTROL |
| 14,418 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 8,844 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 1,458 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 120 MILS) |
| 260 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (16", 120 MILS) |
| 290 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 20 | EA | THERMOPLASTIC PAVEMENT MARKING CHARACTER (120 MILS) |
| 115 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 23,262 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 1,458 | LF | PAINT PAVEMENT MARKING LINES (8") |
| 360 | LF | PAINT PAVEMENT MARKING LINES (16") |
| 340 | LF | PAINT PAVEMENT MARKING LINES (24") |
| 8 | EA | PAINT PAVEMENT MARKING CHARACTER |
| 115 | EA | PAINT PAVEMENT MARKING SYMBOL |
| 550 | EA | SNOWPLOWABLE PAVEMENT MARKERS |
| Lump Sum | LS | PORTABLE LIGHTING |
| 3,528 | LF | INDUCTIVE LOOP SAWCUT |

Page: 15 of 62

L120117 014

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202576 45241.3.1 DIV OFFICE CASTLE HAYNE LENGTH = 0.000 MI

COUNTY : ONSLOW

COMPUTERIZED SIGNAL SYSTEM.

DBE GOAL 5.0% COMPLETION DATE: JUL 01 2014

JACKSONVILLE.

| | | ROADWAY ITEMS | 1 | EA | FURNISH FIBER-OPTIC POWER METER |
|-------------|-----------|---|-----|----|--|
| | | | 1 | EA | FURNISH OPTICAL LIGHT GENERA- TOR |
| Lump Sum | LS | MOBILIZATION | 35 | EA | NEW ELECTRICAL SERVICE |
| 50 1,900 | SY LF | 4" CONCRETE SIDEWALK STEEL BM GUARDRAIL | 10 | EA | CABLE TRANSFER |
| 50 | LF | STEEL BM GUARDRAIL, SHOP | 1 | EA | SIGNAL PEDESTAL WITH FOUNDA- TION |
| | | CURVED | 1 | EA | SIGN FOR SIGNALS |
| 10 | EA EA | ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE | 7 | EA | SIGNAL CABINET FOUNDATION |
| 0 | LA | CAT-1 | 32 | EA | CONDUIT ENTRANCE INTO EXISTING FOUNDATION |
| 11 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 5 | EA | MODIFY FOUNDATION FOR CONTROL- |
| 468 | SF | 350 WORK ZONE SIGNS (PORTABLE) | | | LER CABINET |
| 40 | SF | WORK ZONE SIGNS (BARRICADE | 140 | EA | DETECTOR CARD (*********) (MODEL 222) |
| | Б.4 | MOUNTED) | 10 | EA | CABINET BASE EXTENDER |
| 1 60 | EA DAY | FLASHING ARROW PANELS, TYPE C CHANGEABLE MESSAGE SIGN (SHORT | 2 | EA | CABINET BASE ADAPTER |
| 00 | D/11 | TERM) | 4 | EA | GENERIC SIGNAL ITEM 2.4/5.8 GHZ WIRELESS ETHERNET |
| 50 | EA | DRUMS | | | RADIO SYSTEM |
| 25 80 | EA LF | CONES BARRICADES (TYPE III) | 8 | EA | GENERIC SIGNAL ITEM 2.4/5.8 GHZ WIRELESS ETHERNET |
| 225 | HR | FLAGGER | | | REPEATER STANDALONE RADIO |
| 400 | HR | LAW ENFORCEMENT | 40 | | SYSTEM |
| 30 | EA | PEDESTRIAN SIGNAL HEAD (**", | 10 | EA | GENERIC SIGNAL ITEM AUXILIARY OUTPUT FILE |
| | | ** SECTION) (16", 1 SECTION W/ COUNTDOWN) | 1 | EA | GENERIC SIGNAL ITEM |
| 11,800 | LF | SIGNAL CABLE | 41 | EA | BACKUP STORAGE SERVER GENERIC SIGNAL ITEM |
| 25 | EA | VEHICLE SIGNAL HEAD (12", 3 SECTION) | 41 | EA | CCTV CAMERA ASSEMBLY |
| 20 | EA | VEHICLE SIGNAL HEAD (12", 4 | 3 | EA | GENERIC SIGNAL ITEM |
| | | SECTION) | 1 | EA | CCTV CONTROL PANEL GENERIC SIGNAL ITEM |
| 1 | EA | MODIFY EXISTING VEHICLE SIGNAL HEAD | 1 | EA | CCTV VIDEO SERVER |
| 136,100 | LF | MESSENGER CABLE (1/4") | 37 | EA | GENERIC SIGNAL ITEM |
| 46,600 | LF | TRACER WIRE | | | CCTV WOOD POLE (MT HGHT 30' - 35') |
| 900 | LF | PAVED TRENCHING (********) (1, 2") | 4 | EA | GENERIC SIGNAL ITEM |
| 1,100 | LF | PAVED TRENCHING (********) | | | CCTV WOOD POLE (MT HGHT 45' - 60') |
| | | (2, 2") | 6 | EA | GENERIC SIGNAL ITEM |
| 800 | LF | UNPAVED TRENCHING (********) (1, 1") | | | CELLULAR MODEM |
| 7,300 | LF | UNPAVED TRENCHING (********) | 3 | EA | GENERIC SIGNAL ITEM COMPUTER WORKSTATION |
| 0.700 | LE | (1, 2") | 8 | EA | GENERIC SIGNAL ITEM |
| 9,700 | LF | UNPAVED TRENCHING (********) (2, 2") | 5 | EA | CONFLICT MONITOR GENERIC SIGNAL ITEM |
| 3,400 | LF | DIRECTIONAL DRILL (********) | 5 | LA | CONTROLLER WITH CABINET (TYPE |
| 28,600 | LF | (1, 2") DIRECTIONAL DRILL (*********) | | | 2070L) (332 BASE MOUNTED WITH AUX FILE) |
| 20,000 | LI | (2, 2") | 7 | EA | GENERIC SIGNAL ITEM |
| 19 | EA | JUNCTION BOX (**************) | | | CONTROLLER WITH CABINET (TYPE |
| 76 | EA | (SPECIAL OVERSIZED HEAVY DUTY) JUNCTION BOX (STANDARD SIZE) | 6 | EA | 2070L) (332 BASE MOUNTED) GENERIC SIGNAL ITEM |
| 173 | EA | JUNCTION BOX (OVER-SIZED, HEA- | Ü | | CONTROLLER WITH CABINET (TYPE |
| | Б.4 | VY DUTY) | 5 | EA | 2070L) (336S POLE MOUNTED) GENERIC SIGNAL ITEM |
| 4 164 | EA EA | WOOD POLE GUY ASSEMBLY | 5 | LA | DMS ACCESS LADDER |
| 78 | EA | 2" RISER WITH WEATHERHEAD | 1 | EA | GENERIC SIGNAL ITEM |
| 9 | EA | HEAT SHRINK TUBING RETROFIT | 16 | EA | DMS SERVER GENERIC SIGNAL ITEM |
| 144 | EA | KIT 2" RISER WITH HEAT SHRINK | 10 | | EMERGENCY GENERATOR PROVISIONS |
| 144 | LA | TUBING | 2 | EA | GENERIC SIGNAL ITEM FIBER-OPTIC TRANSMITTER & |
| 6,300 | LF | INDUCTIVE LOOP SAWCUT | | | RECEIVER UNIT |
| 34,400 | LF | LEAD-IN CABLE (*********) (14-2) | 96 | EA | GENERIC SIGNAL ITEM FIELD ETHERNET SWITCH |
| 143,600 | LF | COMMUNICATIONS CABLE (**FIBER) | 41 | EA | GENERIC SIGNAL ITEM |
| 276 900 | LF | (12) COMMUNICATIONS CABLE (**FIBER) | | | FIELD VIDEO CODEC UNIT |
| 276,800 | LF | (24) | 4 | EA | GENERIC SIGNAL ITEM FRONT ACCESS ENCLOSURE DMS |
| 17,800 | LF | COMMUNICATIONS CABLE (**FIBER) | 3 | EA | GENERIC SIGNAL ITEM |
| 1,600 | LF | (48) COMMUNICATIONS CABLE (**FIBER) | | | FURNISH 2070L CONTROLLER |
| 1,000 | LI | (72) | 2 | EA | GENERIC SIGNAL ITEM FURNISH 332 CABINET |
| 127 | EA | SPLICE ENCLOSURE | 1 | EA | GENERIC SIGNAL ITEM |
| 76 116 | EA EA | INTERCONNECT CENTER DELINEATOR MARKER | = | г. | FURNISH 336 CABINET |
| 116 1 | EA EA | FURNISH FIBER-OPTIC RESTORA- | 3 | EA | GENERIC SIGNAL ITEM FURNISH AC ISOLATOR CARD |
| • | | TION KIT | 2 | EA | GENERIC SIGNAL ITEM |
| | | | | | FURNISH CCTV ASSEMBLY |
| | | | | | |

Page: 16 of 62

1 EA GENERIC SIGNAL ITEM REMOTE ACCESS SERVER

| | | | 1 | LA | REMOTE ACCESS SERVER |
|----|------|--|-------------|----|--|
| | | | 1 | EA | GENERIC SIGNAL ITEM SIGNAL SYSTEM COMMUNICATIONS |
| 1 | EA | GENERIC SIGNAL ITEM FURNISH CCTV TEST CABINET | | | SERVER |
| 1 | EA | GENERIC SIGNAL ITEM | 1 | EA | GENERIC SIGNAL ITEM SIGNAL SYSTEM PROCESSING |
| | | FURNISH CCTV TEST MONITOR | | | SERVER |
| 3 | EA | GENERIC SIGNAL ITEM FURNISH CONFLICT MONITOR | 3 | EA | GENERIC SIGNAL ITEM SOLAR POWER ASSEMBLY |
| 1 | EA | GENERIC SIGNAL ITEM | 5 | EA | GENERIC SIGNAL ITEM |
| 3 | EA | FURNISH CONTROLLER TESTER GENERIC SIGNAL ITEM | | | TERMINAL SPLICE BOX |
| 3 | LA | FURNISH DC ISOLATOR CARD | 6 | EA | GENERIC SIGNAL ITEM VIDEO MONITOR PROCESSOR UNIT |
| 6 | EA | GENERIC SIGNAL ITEM FURNISH DETECTOR CARD | 1 | EA | GENERIC SIGNAL ITEM |
| 2 | EA | GENERIC SIGNAL ITEM | 1 | EA | VIDEO PROJECTION UNIT GENERIC SIGNAL ITEM |
| _ | | FURNISH DMS CONTROLLER | 1 | LA | VPN FIREWALL |
| 5 | EA | GENERIC SIGNAL ITEM FURNISH FIBER OPTIC INTER- | 5 | EA | GENERIC SIGNAL ITEM WALK-IN ENCLOSURE DMS |
| | | CONNECT CENTER | Lump Sum | LS | GENERIC SIGNAL ITEM |
| 8 | EA | GENERIC SIGNAL ITEM FURNISH FIELD ETHERNET SWITCH | | | CCTV SYSTEM SOFTWARE |
| 4 | EA | GENERIC SIGNAL ITEM | Lump Sum | LS | GENERIC SIGNAL ITEM COMPUTER HARDWARE INTEGRATION |
| 2 | EA | FURNISH FLASH TRANSFER RELAY GENERIC SIGNAL ITEM | Lump Sum | LS | GENERIC SIGNAL ITEM |
| 2 | LA | FURNISH FLASHER MODULE | Lump Sum | LS | LAN INTEGRATION GENERIC SIGNAL ITEM |
| 5 | EA | GENERIC SIGNAL ITEM | Zump Bum | 20 | PUBLIC SAFETY COMPLEX FIBER |
| 5 | EA | FURNISH HEAT SHRINK TUBING GENERIC SIGNAL ITEM | Lump Sum | LS | OPTIC CABLE TERMINATION GENERIC SIGNAL ITEM |
| | | FURNISH HEAT SHRINK TUBING | Lump Sum | Lo | PUBLIC SERVICES COMPLEX FIBER |
| 3 | EA | RETROFIT KIT GENERIC SIGNAL ITEM | I vana Cvan | LS | OPTIC CABLE TERMINATION GENERIC SIGNAL ITEM |
| | 2 | FURNISH LOAD SWITCH | Lump Sum | LS | SIGNAL SYSTEM SOFTWARE |
| 1 | EA | GENERIC SIGNAL ITEM FURNISH OPTICAL PREEMPTION | Lump Sum | LS | GENERIC SIGNAL ITEM |
| | | PHASE SELECTOR | Lump Sum | LS | SYSTEM SUPPORT SOFTWARE GENERIC SIGNAL ITEM |
| 1 | EA | GENERIC SIGNAL ITEM FURNISH OPTICAL PREEMPTION | • | | TRAINING |
| | | DETECTOR | 33,700 | LF | GENERIC SIGNAL ITEM DROP CABLE (6 FIBER) |
| 8 | EA | GENERIC SIGNAL ITEM FURNISH SC JUMPERS | 3,300 | LF | GENERIC SIGNAL ITEM |
| 8 | EA | GENERIC SIGNAL ITEM | 4 400 | | ETHERNET CABLE (OUTDOOR RATED) |
| | | FURNISH SC PIGTAILS | 4,400 | LF | GENERIC SIGNAL ITEM FURNISH COMMUNICATIONS CABLE |
| 8 | EA | GENERIC SIGNAL ITEM FURNISH SC SPLICE CONNECTOR | 0.400 | | (12 FIBER) |
| 8 | EA | GENERIC SIGNAL ITEM | 8,400 | LF | GENERIC SIGNAL ITEM FURNISH COMMUNICATIONS CABLE |
| 1 | EA | FURNISH SC-ST JUMPERS GENERIC SIGNAL ITEM | 500 | | (24 FIBER) |
| • | Lit | FURNISH SIGNAL MONITOR TESTER | 600 | LF | GENERIC SIGNAL ITEM FURNISH COMMUNICATIONS CABLE |
| 2 | EA | GENERIC SIGNAL ITEM FURNISH SPLICE ENCLOSURE | 400 | | (48 FIBER) |
| 8 | EA | GENERIC SIGNAL ITEM | 100 | LF | GENERIC SIGNAL ITEM FURNISH COMMUNICATIONS CABLE |
| 0 | E.4 | FURNISH ST JUMPERS | 4.400 | | (72 FIBER) |
| 8 | EA | GENERIC SIGNAL ITEM FURNISH ST PIGTAILS | 1,100 | LF | GENERIC SIGNAL ITEM FURNISH DROP CABLE (6 FIBER) |
| 8 | EA | GENERIC SIGNAL ITEM | 500 | SF | GENERIC SIGNAL ITEM |
| 20 | EA | FURNISH ST SPLICE CONNECTOR GENERIC SIGNAL ITEM | 90 | CY | BRICK PAVERS GENERIC SIGNAL ITEM |
| 20 | Lit | FURNISH SURGE PROTECTOR | 70 | CI | FOOTINGS FOR DMS STRUCTURE |
| 1 | EA | GENERIC SIGNAL ITEM FURNISH TEST CABINET/ | | | |
| | | CONTROLLER | | | |
| 2 | EA | GENERIC SIGNAL ITEM FURNISH VIDEO CODEC UNIT | | | |
| 2 | EA | GENERIC SIGNAL ITEM | | | |
| | | FURNISH WIRELESS RADIO TRANS- CEIVER | | | |
| 26 | EA | GENERIC SIGNAL ITEM | | | |
| | | GENERATOR ANCHOR INTO EXISTING FOUNDATION | | | |
| 5 | EA | GENERIC SIGNAL ITEM | | | |
| 1. | E. A | LCD VIDEO MONITOR GENERIC SIGNAL ITEM | | | |
| 11 | EA | MODIFY EXISTING ELECTRICAL | | | |
| | | SERVICE | | | |
| 24 | EA | GENERIC SIGNAL ITEM MODIFY EXISTING INTERCONNECT | | | |
| | | CENTER OR SPLICE ENCLOSURE | | | |
| 1 | EA | GENERIC SIGNAL ITEM NETWORK VIDEO RECORDER | | | |
| 3 | EA | GENERIC SIGNAL ITEM | | | |
| 26 | EA | NOTEBOOK COMPUTER GENERIC SIGNAL ITEM | | | |
| 36 | LA | OPTICAL PREEMPTION DETECTOR | | | |
| 14 | EA | GENERIC SIGNAL ITEM | | | |
| | | OPTICAL PREEMPTION PHASE SELECTOR | | | |
| 4 | EA | GENERIC SIGNAL ITEM | | | |
| | | PEDESTAL STRUCTURE FOR FRONT ACCESS DMS | | | |
| 5 | EA | GENERIC SIGNAL ITEM | | | |
| | | PEDESTAL STRUCTURE FOR WALK-IN DMS | | | |
| 13 | EA | GENERIC SIGNAL ITEM | | | |
| | | POWER FROM EXISTING ELECTRICAL SERVICE | | | |
| | | | | | |

Page: 17 of 62

L120117 015

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202874 47065.3.1 DIV OFFICE CASTLE HAYNE LENGTH = 0.000 MI

: BRUNSWICK

REMOVAL AND REPLACEMENT OF FENDER SYSTEM.

DBE GOAL 0.0% COMPLETION DATE: SEP 30 2012

BRIDGE #14 ON NC-133 OVER ATLANTIC INTERCOASTAL WATERWAY BETWEEN SOUTHPORT AND OAK ISLAND.

STRUCTURE ITEMS

Lump Sum LS MOBILIZATION (STRUCTURES)

1,624 LF PP ** X **** STEEL PILES

(14 X 0.50)

5,864 LF PP ** X **** STEEL PILES (16 X 0.50)

Lump Sum LS GENERIC STRUCTURE ITEM PLASTIC AND COMPOSITE LUMBER

Lump Sum LS GENERIC STRUCTURE ITEM REMOVAL OF EXISTING FENDER

SYSTEM

Page: 18 of 62

L120117 016

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202916 3CR.10101.114 DIV OFFICE CASTLE HAYNE LENGTH = 37.240 MI

COUNTY : BRUNSWICK, NEW HANOVER

MILLING, RESURFACING, MILLED RUMBLE STRIPS & SHLDR RECONST.

MBE GOAL 3.0% WBE 4.0% COMPLETION DATE: NOV 16 2012

1 SECTION OF US-17, US-17 BUS, US-74/76 & NC-221 AND 10 SECTIONS OF SECONDARY ROADS.

| | | ROADWAY ITEMS |
|-------------------|------------|---|
| | | |
| Lump Sum | LS | MOBILIZATION |
| 4,108 | CY | BORROW EXCAVATION |
| 1,170 38.64 | TON SMI | INCIDENTAL STONE BASE SHOULDER RECONSTRUCTION |
| 391,744 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH |
| 54,348 | SY | (1-1/2") MILLING ASPHALT PAVEMENT, ***" DEPTH |
| 5,635 | SY | (2-1/2") INCIDENTAL MILLING |
| 7,043 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B |
| 8,667 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE I19.0C |
| 36,189 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 29,873 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5C |
| 6,429 | TON | ASPHALT CONC SURFACE COURSE, TYPE SF9.5A |
| 5,094 | TON | ASPHALT BINDER FOR PLANT MIX |
| 163,470 | LF | MILLED RUMBLE STRIPS (ASPHALT CONCRETE) |
| 935 | TON | GENERIC PAVING ITEM PATCHING EXISTING PAVEMENT |
| 3,750 | TON | (FULL DEPTH) GENERIC PAVING ITEM PATCHING EXISTING PAVEMENT (MILL) |
| 19 | EA | GENERIC DRAINAGE ITEM CONCRETE APRON |
| 5 | EA | RETROFIT EXISTING CURB RAMP |
| 10 5 | EA EA | CONCRETE CURB RAMP ADJUSTMENT OF MANHOLES |
| 6 | EA | ADJUSTMENT OF MAINFIOLES ADJUSTMENT OF METER BOXES OR VALVE BOXES |
| 2 | EA | FLASHING ARROW BOARD |
| 2 | EA | PORTABLE CHANGEABLE MESSAGE SIGN |
| 2 | EA | TMA |
| 192,611 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 98,063 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 7,007 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 90 MILS) |
| 392 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 4 | EA | THERMOPLASTIC PAVEMENT MARKING CHARACTER (120 MILS) |
| 820 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 6 | EA | HEATED-IN-PLACE THERMOPLASTIC PAVEMENT MARKING CHARACTER (120 MILS) |
| 26 | EA | HEATED-IN-PLACE THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 1,260,229 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 8,106 | LF | PAINT PAVEMENT MARKING LINES (8") |
| 400 | LF | PAINT PAVEMENT MARKING LINES (16") |
| 720 | LF | PAINT PAVEMENT MARKING LINES (24") |
| 48 | EA | PAINT PAVEMENT MARKING CHARACTER |
| 268 | EA | PAINT PAVEMENT MARKING SYMBOL |
| 1,841 | EA | PERMANENT RAISED PAVEMENT MARKERS |
| 4,226 | EA | SNOWPLOWABLE PAVEMENT MARKERS |
| Lump Sum 1,950 | LS LF | PORTABLE LIGHTING TEMPORARY SILT FENCE |
| 491 | TON | STONE FOR EROSION CONTROL, |
| | | CLASS B |

| 491 | TON | SEDIMENT CONTROL STONE |
|-------|-----|-------------------------------------|
| 19.5 | ACR | TEMPORARY MULCHING |
| 155 | SY | MATTING FOR EROSION CONTROL |
| 977 | LF | 1/4" HARDWARE CLOTH |
| 320 | LF | WATTLE |
| 28.69 | ACR | SEEDING & MULCHING |
| 977 | LB | SEED FOR REPAIR SEEDING |
| 4.87 | TON | FERTILIZER FOR REPAIR SEEDING |
| 3,900 | LF | INDUCTIVE LOOP SAWCUT |
| 850 | LF | LEAD-IN CABLE (************) (14-2) |
| | | |

Page: 19 of 62

L120117 017

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202859 3CR.10311.115 DIV OFFICE CASTLE HAYNE LENGTH = 11.890 MI

COUNTY : DUPLIN, SAMPSON

Lump Sum LS MOBILIZATION

WIDENING, MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION.

MBE GOAL 5.0% WBE 5.0% COMPLETION DATE: NOV 16 2012

1 SECTION OF US-117, US-13, NC-41, AND NC-50/403.

| Lump Sum | Lo | MODILIZATION |
|----------|------|--------------------------------|
| 4,808 | CY | BORROW EXCAVATION |
| 200 | SY | GENERIC GRADING ITEM |
| 200 | 31 | |
| | | REMOVE ASPHALT ISLAND |
| 550 | TON | INCIDENTAL STONE BASE |
| 20.08 | SMI | SHOULDER RECONSTRUCTION |
| | | |
| 72,208 | SY | MILLING ASPHALT PAVEMENT, ***" |
| | | DEPTH |
| | | (1-1/2") |
| 12 422 | 037 | |
| 13,423 | SY | MILLING ASPHALT PAVEMENT, ***" |
| | | DEPTH |
| | | (2") |
| 123,048 | SY | MILLING ASPHALT PAVEMENT, ***" |
| 123,040 | 51 | DEPTH |
| | | |
| | | (2-1/2") |
| 4,535 | SY | INCIDENTAL MILLING |
| 7,758 | TON | ASPHALT CONC BASE COURSE, TYPE |
| 7,750 | 1011 | B25.0B |
| | | |
| 19,458 | TON | ASPHALT CONC INTERMEDIATE |
| | | COURSE, TYPE I19.0B |
| 26,257 | TON | ASPHALT CONC SURFACE COURSE, |
| 20,237 | ION | |
| | | TYPE S9.5B |
| 2,854 | TON | ASPHALT BINDER FOR PLANT MIX |
| 250 | TON | GENERIC PAVING ITEM |
| 230 | 1011 | PATCHING EXISTING PAVEMENT |
| | | |
| | | (FULL DEPTH) |
| 785 | TON | GENERIC PAVING ITEM |
| | | PATCHING EXISTING PAVEMENT |
| | | |
| | | (MILL) |
| 60 | SY | 4" CONCRETE SIDEWALK |
| 13 | EA | RETROFIT EXISTING CURB RAMP |
| | | |
| 23 | EA | CONCRETE CURB RAMP |
| 200 | SY | 5" MONOLITHIC CONCRETE ISLANDS |
| | | (SURFACE MOUNTED) |
| | | |
| 75 | SY | GENERIC PAVING ITEM |
| | | INCIDENTAL CONCRETE |
| 85 | SY | GENERIC PAVING ITEM |
| | | REMOVE & REPLACE SIDEWALK |
| | | |
| 210 | LF | GENERIC PAVING ITEM |
| | | REMOVE AND REPLACE 2'-0" CURB |
| | | & GUTTER |
| 000 | LF | GENERIC PAVING ITEM |
| 900 | LF | |
| | | REMOVE AND REPLACE 2'-6" CURB |
| | | & GUTTER |
| 19 | EA | GENERIC PAVING ITEM |
| • / | | REMOVE AND REPLACE CURB RAMPS |
| | | |
| 37 | EA | ADJUSTMENT OF MANHOLES |
| 44 | EA | ADJUSTMENT OF METER BOXES OR |
| | | VALVE BOXES |
| _ | | |
| 2 | EA | GUARDRAIL ANCHOR UNITS, TYPE |
| | | 350 |
| 1 | EA | FLASHING ARROW BOARD |
| | | |
| 1 | EA | PORTABLE CHANGEABLE MESSAGE |
| | | SIGN |
| 1 | EA | TMA |
| - | | |
| 106,710 | LF | THERMOPLASTIC PAVEMENT MARKING |
| | | LINES (4", 90 MILS) |
| 181,026 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 101,020 | | LINES (4", 120 MILS) |
| | | |
| 1,400 | LF | THERMOPLASTIC PAVEMENT MARKING |
| | | LINES (8", 90 MILS) |
| 50 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 30 | LI. | |
| | | LINES (8", 120 MILS) |
| 150 | LF | THERMOPLASTIC PAVEMENT MARKING |
| | | LINES (16", 120 MILS) |
| 1 411 | 1.17 | |
| 1,411 | LF | THERMOPLASTIC PAVEMENT MARKING |
| | | LINES (24", 120 MILS) |
| 14 | EA | THERMOPLASTIC PAVEMENT MARKING |
| • • | | CHARACTER (120 MILS) |
| | ъ. | |
| 141 | EA | THERMOPLASTIC PAVEMENT MARKING |
| | | SYMBOL (90 MILS) |
| 294,228 | LF | PAINT PAVEMENT MARKING LINES |
| ,0 | | (4") |
| | | |
| 900 | LF | PAINT PAVEMENT MARKING LINES |
| | | (8") |
| 150 | LF | PAINT PAVEMENT MARKING LINES |
| 150 | | (16") |
| | | (10) |
| | | |

| 1,387 LF PAINT PAVEMENT MARKING LINES (24") 14 EA PAINT PAVEMENT MARKING CHARACTER 141 EA PAINT PAVEMENT MARKING SYMBOL 1,851 EA SNOWPLOWABLE PAVEMENT MARKERS 1,223 LF TEMPORARY SILT FENCE 307 TON STONE FOR EROSION CONTROL, CLASS B 307 TON SEDIMENT CONTROL STONE 12,23 ACR TEMPORARY MULCHING 110 SY MATTING FOR EROSION CONTROL 619 LF 1/4" HARDWARE CLOTH 210 LF WATTLE 14,71 ACR SEEDING & MULCHING 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | | | |
|--|-------|-----|--|
| TER 141 EA PAINT PAVEMENT MARKING SYMBOL 1,851 EA SNOWPLOWABLE PAVEMENT MARKERS 1,223 LF TEMPORARY SILT FENCE 307 TON STONE FOR EROSION CONTROL, CLASS B 307 TON SEDIMENT CONTROL STONE 12.23 ACR TEMPORARY MULCHING 110 SY MATTING FOR EROSION CONTROL 619 LF 1/4" HARDWARE CLOTH 210 LF WATTLE 14.71 ACR SEEDING & MULCHING 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 1,387 | LF | |
| 1,851 | 14 | EA | TIME TITE DAMES TO THE METER TO COMMUNIC |
| 1,223 LF TEMPORARY SILT FENCE 307 TON STONE FOR EROSION CONTROL, CLASS B 307 TON SEDIMENT CONTROL STONE 12,23 ACR TEMPORARY MULCHING 110 SY MATTING FOR EROSION CONTROL 619 LF 1/4" HARDWARE CLOTH 210 LF WATTLE 14,71 ACR SEEDING & MULCHING 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 141 | EA | PAINT PAVEMENT MARKING SYMBOL |
| 307 TON STONE FOR EROSION CONTROL, CLASS B 307 TON SEDIMENT CONTROL STONE 12.23 ACR TEMPORARY MULCHING 110 SY MATTING FOR EROSION CONTROL 619 LF 1/4" HARDWARE CLOTH 210 LF WATTLE 14.71 ACR SEEDING & MULCHING 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 1,851 | EA | SNOWPLOWABLE PAVEMENT MARKERS |
| CLASS B 307 TON SEDIMENT CONTROL STONE 12.23 ACR TEMPORARY MULCHING 110 SY MATTING FOR EROSION CONTROL 619 LF 1/4" HARDWARE CLOTH 210 LF WATTLE 14.71 ACR SEEDING & MULCHING 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 1,223 | LF | TEMPORARY SILT FENCE |
| 12.23 ACR TEMPORARY MULCHING 110 SY MATTING FOR EROSION CONTROL 619 LF 1/4" HARDWARE CLOTH 210 LF WATTLE 14.71 ACR SEEDING & MULCHING 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 307 | TON | |
| 110 SY MATTING FOR EROSION CONTROL 619 LF 1/4" HARDWARE CLOTH 210 LF WATTLE 14.71 ACR SEEDING & MULCHING 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 307 | TON | SEDIMENT CONTROL STONE |
| 619 LF 1/4" HARDWARE CLOTH 210 LF WATTLE 14.71 ACR SEEDING & MULCHING 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 12.23 | ACR | TEMPORARY MULCHING |
| 210 LF WATTLE 14.71 ACR SEEDING & MULCHING 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 110 | SY | MATTING FOR EROSION CONTROL |
| 14.71 ACR SEEDING & MULCHING 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 619 | LF | 1/4" HARDWARE CLOTH |
| 612 LB SEED FOR REPAIR SEEDING 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 210 | LF | WATTLE |
| 3.07 TON FERTILIZER FOR REPAIR SEEDING 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 14.71 | ACR | SEEDING & MULCHING |
| 5 EA JUNCTION BOX (STANDARD SIZE) 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 612 | LB | SEED FOR REPAIR SEEDING |
| 2,020 LF INDUCTIVE LOOP SAWCUT 3,425 LF LEAD-IN CABLE (************************************ | 3.07 | TON | FERTILIZER FOR REPAIR SEEDING |
| 3,425 LF LEAD-IN CABLE (*************) | 5 | EA | JUNCTION BOX (STANDARD SIZE) |
| | 2,020 | LF | INDUCTIVE LOOP SAWCUT |
| | 3,425 | LF | , |

Page: 20 of 62

L120117 018

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202927 3CR.10671.117 DIV OFFICE CASTLE HAYNE LENGTH = 25.110 MI

COUNTY : ONSLOW, PENDER

WIDENING, MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION.

MBE GOAL 4.0% WBE 5.0% COMPLETION DATE: NOV 16 2012

NC-24 BUS FROM BEG OF DIVIDED HWY TO W OF US-17, NC-210 FROM ICW BRG TO PENDER CO, AND 7 SECTIONS OF SECONDARY ROADS.

ROADWAY ITEMS

| | | ROADWAY ITEMS |
|------------------|----------|--|
| Lump Sum | LS | MOBILIZATION |
| 13,481 | CY | BORROW EXCAVATION |
| 1,225 | TON | INCIDENTAL STONE BASE |
| 46.26 | SMI | SHOULDER RECONSTRUCTION |
| 434 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH |
| 64,289 | SY | (1") MILLING ASPHALT PAVEMENT, ***" DEPTH (1-1/2") |
| 9,382 | SY | INCIDENTAL MILLING |
| 900 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B |
| 16,297 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE I19.0B |
| 40,675 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 3,264 | TON | ASPHALT BINDER FOR PLANT MIX |
| 175 | TON | GENERIC PAVING ITEM PATCHING EXISTING PAVEMENT (FULL DEPTH) |
| 975 | TON | GENERIC PAVING ITEM PATCHING EXISTING PAVEMENT (MILL) S9.5B |
| 11 | EA | CONCRETE CURB RAMP |
| 165 | SY | GENERIC PAVING ITEM REMOVE & REPLACE SIDEWALK |
| 40 | SY | GENERIC PAVING ITEM INCIDENTAL CONCRETE |
| 180 | LF | GENERIC PAVING ITEM 2'-6" CURB & GUTTER, REMOVE & REPLACE |
| 10 | EA | ADJUSTMENT OF MANHOLES |
| 52 | EA | ADJUSTMENT OF METER BOXES OR VALVE BOXES |
| 1,720 | LF | STEEL BM GUARDRAIL |
| 2 | EA | GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 1 820 | EA | GUARDRAIL ANCHOR UNITS, TYPE B-83 |
| 1,820 193,827 | LF LF | REMOVE EXISTING GUARDRAIL THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 222,570 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 2,303 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 90 MILS) |
| 588 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 24 119 | EA EA | THERMOPLASTIC PAVEMENT MARKING CHARACTER (120 MILS) THERMOPLASTIC PAVEMENT MARKING |
| 6 | EA | SYMBOL (90 MILS) HEATED-IN-PLACE THERMOPLASTIC |
| | 2 | PAVEMENT MARKING CHARACTER (120 MILS) |
| 114 | EA | HEATED-IN-PLACE THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 684,494 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 2,303 | LF | PAINT PAVEMENT MARKING LINES (8") |
| 588 | LF | PAINT PAVEMENT MARKING LINES (24") |
| 120 | EA | PAINT PAVEMENT MARKING CHARAC- TER |
| 120 2,543 | EA EA | PAINT PAVEMENT MARKING SYMBOL PERMANENT RAISED PAVEMENT |
| 620 | EA | MARKERS SNOWPLOWABLE PAVEMENT MARKERS |
| 620 Lump Sum | LS | PORTABLE LIGHTING |
| 1,686 | LF | TEMPORARY SILT FENCE |
| 425 | TON | STONE FOR EROSION CONTROL, CLASS B |
| 425 | TON | SEDIMENT CONTROL STONE |

16.86 ACR TEMPORARY MULCHING

| 140 | SY | MATTING FOR EROSION CONTROL |
|-------|-----|-------------------------------|
| 845 | LF | 1/4" HARDWARE CLOTH |
| 280 | LF | WATTLE |
| 40.73 | ACR | SEEDING & MULCHING |
| 845 | LB | SEED FOR REPAIR SEEDING |
| 4.22 | TON | FERTILIZER FOR REPAIR SEEDING |
| 5 | EA | JUNCTION BOX (STANDARD SIZE) |
| 4,950 | LF | INDUCTIVE LOOP SAWCUT |
| 1,000 | LF | LEAD-IN CABLE (*********) |
| | | (14-2) |
| | | |

Page: 21 of 62

L120117 019

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202730 33734.3.1 DIV OFFICE WILSON LENGTH = 0.180 MI

COUNTY : **EDGECOMBE**

GRADING, DRAINAGE, PAVING, SIGNALS AND STRUCTURE.

DBE GOAL 9.0% COMPLETION DATE: DEC 31 2012

1,861 LF THERMOPLASTIC PAVEMENT MARKING

114.7 CY CLASS A CONCRETE (BRIDGE)

BRIDGE OVER TAR RIVER AND APPROACHES ON SR-1250.

| | | | ROADWAY ITEMS | 1,001 | LI | LINES (4", 90 MILS) |
|---|--|---|--|--|--|--|
| | | | | 2,156 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 1 | Lump Sum | LS | MOBILIZATION | | | LINES (4", 120 MILS) |
| | Lump Sum | LS | BRIDGE APPROACH FILL - SUB | 26 | LF | THERMOPLASTIC PAVEMENT MARKING |
| | Zump Jum | 20 | REGIONAL TIER, STATION ******* | 22 | LE | LINES (8", 90 MILS) |
| | | | (21+11.00) | 32 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| | 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- | 140 | LF | 6" WATER LINE |
| | | | BING | 2 | EA | RELOCATE FIRE HYDRANT |
| | 300 | CY | UNDERCUT EXCAVATION | 1 | EA | ABANDON UTILITY MANHOLE |
|] | Lump Sum | LS | GRADING | 1 | EA | GENERIC UTILITY ITEM |
| | 4,125 | CY | BORROW EXCAVATION | | | 6" CHECK VALVE ASSEMBLY |
| | 101 | CY | DRAINAGE DITCH EXCAVATION | 1,050 | LF | TEMPORARY SILT FENCE |
| | 300 | CY | SELECT GRANULAR MATERIAL | 225 | TON | STONE FOR EROSION CONTROL, |
| | 400 | SY | FABRIC FOR SOIL STABILIZATION FOUNDATION CONDITIONING MATE | | | CLASS A |
| | 45 | TON | FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS | 150 | TON | STONE FOR EROSION CONTROL, CLASS B |
| | 440 | SY | FOUNDATION CONDITIONING FABRIC | 390 | TON | SEDIMENT CONTROL STONE |
| | 140 | LF | 15" DRAINAGE PIPE | 3 | ACR | TEMPORARY MULCHING |
| | 36 | LF | 72" RC PIPE CULVERTS, CLASS | 100 | LB | SEED FOR TEMPORARY SEEDING |
| | | | III | 1.5 | TON | FERTILIZER FOR TEMPORARY SEED- |
| | 84 | LF | 15" CS PIPE CULVERTS, 0.064" | 1.5 | 1011 | ING |
| | | | THICK | 280 | LF | TEMPORARY SLOPE DRAINS |
| | 4 | EA | **" CS PIPE ELBOWS, *****" THICK | 7 | EA | INLET PROTECTION AT TEMPORARY |
| | | | (15", 0.064") | | | SLOPE DRAINS |
| | 23 | LF | PIPE REMOVAL | 800 | LF | SAFETY FENCE |
| | 200 | SY | MILLING ASPHALT PAVEMENT, ***" | 400 | CY | SILT EXCAVATION |
| | | | DEPTH | 2,000 | SY | MATTING FOR EROSION CONTROL |
| | | | (1-1/2") | 40 | SY | COIR FIBER MAT |
| | 780 | TON | ASPHALT CONC BASE COURSE, TYPE | 70 | SY | PERMANENT SOIL REINFORCEMENT MAT |
| | 2.00 | TON | B25.0B | 820 | LF | 1/4" HARDWARE CLOTH |
| | 260 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0B | 130 | SY | FLOATING TURBIDITY CURTAIN |
| | 610 | TON | ASPHALT CONC SURFACE COURSE, | 8 | EA | SPECIAL STILLING BASINS |
| | | | TYPE S9.5B | 20 | LB | POLYACRYLAMIDE (PAM) |
| | 85 | TON | ASPHALT BINDER FOR PLANT MIX | 200 | LF | COIR FIBER BAFFLE |
| | 9 | EA | RIGHT OF WAY MARKERS | 4 | EA | **" SKIMMER |
| | 22.4 | CY | SUBDRAIN EXCAVATION | | | (1-1/2") |
| | 16.8 | CY | SUBDRAIN FINE AGGREGATE | 4 | ACR | SEEDING & MULCHING |
| | 100 | LF | 6" PERFORATED SUBDRAIN PIPE | 3 | ACR | MOWING |
| | 1 | EA | SUBDRAIN PIPE OUTLETS | 50 | LB | SEED FOR REPAIR SEEDING |
| | 6 | LF | 6" OUTLET PIPE (SUBDRAINS) | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| | 14.2 | CY | REINFORCED ENDWALLS | 75 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| | 5 | EA | MASONRY DRAINAGE STRUCTURES | 2 | TON | FERTILIZER TOPDRESSING |
| | 18.4 | CY | MASONRY DRAINAGE STRUCTURES | 10 | | SPECIALIZED HAND MOWING |
| | 4 | EA | FRAME WITH TWO GRATES, STD 840.29 | 16 | EA | RESPONSE FOR EROSION CONTROL |
| | | | 040.27 | | | REFORESTATION |
| | 1 | FΔ | FRAME WITH COVER STD 840 54 | 0.5 | ACR | MODIEW EVICENIC VEHICLE CICNAL |
| | 1 15 | EA LF | FRAME WITH COVER, STD 840.54 2'-6" CONCRETE CURB & GUTTER | 0.5 | ACR EA | MODIFY EXISTING VEHICLE SIGNAL |
| | 15 | LF | 2'-6" CONCRETE CURB & GUTTER | 2 | EA | HEAD |
| | 15 60 | LF LF | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER | | | |
| | 15 | LF | 2'-6" CONCRETE CURB & GUTTER | 2 | EA | HEAD UNPAVED TRENCHING (*******) |
| | 15 60 50 | LF LF LF | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL | 2 20 | EA LF | HEAD UNPAVED TRENCHING (********) (1, 2") |
| | 15 60 50 3 | LF LF LF EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS | 2 20 1 | EA LF EA | HEAD UNPAVED TRENCHING (********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (***********) |
| | 15 60 50 3 | LF LF LF EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE | 2 20 1 200 | EA LF EA LF | HEAD UNPAVED TRENCHING (********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT |
| | 15 60 50 3 4 | LF LF EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 | 2 20 1 200 | EA LF EA LF | HEAD UNPAVED TRENCHING (********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (***********) |
| | 15 60 50 3 4 4 | LF LF LF EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B | 2 20 1 200 | EA LF EA LF | HEAD UNPAVED TRENCHING (********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (***********) |
| | 15 60 50 3 4 4 1 1,055 | LF LF LF EA EA TON SY | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE | 2 20 1 200 | EA LF EA LF | HEAD UNPAVED TRENCHING (*********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (*********) (14-2) |
| | 15 60 50 3 4 4 | LF LF LF EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH | 2 20 1 200 | EA LF EA LF | HEAD UNPAVED TRENCHING (********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (***********) |
| | 15 60 50 3 4 4 1 1,055 | LF LF EA EA TON SY EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON | 2 20 1 200 | EA LF EA LF | HEAD UNPAVED TRENCHING (*********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (*********) (14-2) |
| | 15 60 50 3 4 4 1 1,055 | LF LF LF EA EA TON SY | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL | 2 20 1 200 | EA LF EA LF | HEAD UNPAVED TRENCHING (*********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (*********) (14-2) |
| | 15 60 50 3 4 4 1 1,055 1 | LF LF EA EA TON SY EA LF | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON | 2 20 1 200 400 | EA LF EA LF LF | HEAD UNPAVED TRENCHING (*********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (*********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA |
| | 15 60 50 3 4 4 1 1,055 1 | LF LF EA EA TON SY EA LF EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE **** (GROUND MOUNTED) | 2 20 1 200 400 | EA LF EA LF LF | HEAD UNPAVED TRENCHING (*********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (**********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************** |
| | 15 60 50 3 4 4 1 1,055 1 51 1 | LF LF EA EA TON SY EA LF EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE ***** (GROUND MOUNTED) (E) | 2 20 1 200 400 | EA LF EA LF LF | HEAD UNPAVED TRENCHING (*********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (**********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************************************ |
| | 15 60 50 3 4 4 1 1,055 1 | LF LF EA EA TON SY EA LF EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE ***** (GROUND MOUNTED) (E) DISPOSAL OF SIGN SYSTEM, U- | 2 20 1 200 400 | EA LF EA LF LF | HEAD UNPAVED TRENCHING (*********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (**********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************** |
| | 15 60 50 3 4 4 1 1,055 1 51 1 7 | LF LF EA EA TON SY EA LF EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE **** (GROUND MOUNTED) (E) DISPOSAL OF SIGN SYSTEM, U-CHANNEL | 2 20 1 200 400 | EA LF EA LF LF | HEAD UNPAVED TRENCHING (**********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (**********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA **************** (21+11.00-L-) REMOVAL OF EXISTING STRUCTURE |
| | 15 60 50 3 4 4 1 1,055 1 51 1 1 | LF LF EA EA TON SY EA LF EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-18 STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE **** (GROUND MOUNTED) (E) DISPOSAL OF SIGN SYSTEM, U-CHANNEL DISPOSAL OF SIGN SYSTEM, WOOD | 2 20 1 200 400 | EA LF EA LF LF | HEAD UNPAVED TRENCHING (*********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (**********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************************************ |
| | 15 60 50 3 4 4 1 1.055 1 51 1 1 | LF LF EA EA TON SY EA LF EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE ***** (GROUND MOUNTED) (E) DISPOSAL OF SIGN SYSTEM, U-CHANNEL DISPOSAL OF SIGN SYSTEM, WOOD DISPOSAL OF SUPPORT, U-CHANNEL | 2 20 1 200 400 400 Lump Sum 201.34 | EA LF EA LF LF LS LS | HEAD UNPAVED TRENCHING (**********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (***********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************************************ |
| | 15 60 50 3 4 4 1 1,055 1 51 1 1 | LF LF EA EA TON SY EA LF EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE ***** (GROUND MOUNTED) (E) DISPOSAL OF SIGN SYSTEM, U-CHANNEL UISPOSAL OF SIGN SYSTEM, WOOD DISPOSAL OF SURPORT, U-CHANNEL UISPOSAL OF SURPORT, U-CHANNEL WORK ZONE SIGNS (STATIONARY) | 2 20 1 200 400 Lump Sum | EA LF EA LF LF | HEAD UNPAVED TRENCHING (************) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (************) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************************************ |
| | 15 60 50 3 4 4 1 1,055 1 51 1 1 | LF LF LF EA EA TON SY EA LF EA EA EA | 2'-6" CONCRETE CURB & GUTTER SHOUL DER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE **** (GROUND MOUNTED) (E) DISPOSAL OF SIGN SYSTEM, U-CHANNEL DISPOSAL OF SIGN SYSTEM, WOOD DISPOSAL OF SUPPORT, U-CHANNEL WORK ZONE SIGNS (STATIONARY) WORK ZONE SIGNS (STATIONARY) | 2 20 1 200 400 Lump Sum Lump Sum 201.34 77.34 | EA LF LF LS LS LF LF LF | HEAD UNPAVED TRENCHING (***********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (***********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************************************ |
| | 15 60 50 3 4 4 1 1,055 1 51 1 1 7 7 | LF LF LF EA EA TON SY EA LF EA EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE ***** (GROUND MOUNTED) (E) DISPOSAL OF SIGN SYSTEM, U-CHANNEL UISPOSAL OF SIGN SYSTEM, WOOD DISPOSAL OF SURPORT, U-CHANNEL UISPOSAL OF SURPORT, U-CHANNEL WORK ZONE SIGNS (STATIONARY) | 2 20 1 200 400 Lump Sum Lump Sum 201.34 77.34 | EA LF LF LS LS LS LF LF LF | HEAD UNPAVED TRENCHING (***********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (***********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************************************ |
| | 15 60 50 3 4 4 1 1,055 1 51 1 1 7 7 | LF LF LF EA EA TON SY EA LF EA EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE **** (GROUND MOUNTED) (E) DISPOSAL OF SIGN SYSTEM, U-CHANNEL DISPOSAL OF SIGN SYSTEM, WOOD DISPOSAL OF SUPPORT, U-CHANNEL WORK ZONE SIGNS (STATIONARY) WORK ZONE SIGNS (PORTABLE) | 2 20 1 200 400 Lump Sum Lump Sum 201.34 77.34 2 2 | EA LF EA LF LF LS LS | HEAD UNPAVED TRENCHING (*********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (***********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************************************ |
| | 15 60 50 3 4 4 1 1,055 1 51 1 1 7 1 492 144 89 | LF LF LF EA EA TON SY EA LF EA EA EA EA EA EA EA | 2'-6" CONCRETE CURB & GUTTER SHOUL DER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE **** (GROUND MOUNTED) (E) DISPOSAL OF SIGN SYSTEM, U-CHANNEL DISPOSAL OF SIGN SYSTEM, WOOD DISPOSAL OF SUPPORT, U-CHANNEL WORK ZONE SIGNS (STATIONARY) WORK ZONE SIGNS (BARRICADE MOUNTED) DRUMS BARRICADES (TYPE III) | 2 20 1 200 400 Lump Sum Lump Sum 201.34 77.34 | EA LF LF LS LS LS LF LF LF | HEAD UNPAVED TRENCHING (**********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (***********) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************************************ |
| | 15 60 50 3 4 4 1 1,055 1 51 1 1 7 7 1 1 492 144 89 | LF LF LF EA EA TON SY EA LF EA EA EA EA | 2'-6" CONCRETE CURB & GUTTER SHOULDER BERM GUTTER STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 RIP RAP, CLASS B FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D SIGN ERECTION, RELOCATE, TYPE ***** (GROUND MOUNTED) (E) DISPOSAL OF SIGN SYSTEM, U-CHANNEL DISPOSAL OF SIGN SYSTEM, WOOD DISPOSAL OF SIGN SYSTEM, WOOD DISPOSAL OF SIGNS (STATIONARY) WORK ZONE SIGNS (STATIONARY) WORK ZONE SIGNS (BARRICADE MOUNTED) DRUMS | 2 20 1 200 400 Lump Sum Lump Sum 201.34 77.34 2 2 | EA LF EA LF LF LS LS | HEAD UNPAVED TRENCHING (************) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (************) (14-2) STRUCTURE ITEMS CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP ACCESS AT STA ************************************ |

Page: 22 of 62

| Lump Sum | LS | BRIDGE APPROACH SLABS, STATION ************************************ |
|----------|-----|---|
| 37,715 | LB | REINFORCING STEEL (BRIDGE) |
| 8,044 | LB | SPIRAL COLUMN REINFORCING STEEL (BRIDGE) |
| 690 | LF | HP12X53 STEEL PILES |
| 520.5 | LF | TWO BAR METAL RAIL |
| 535.5 | LF | 1'-**"X *****" CONCRETE PARA- |
| | | PET (1'-2" X 2'-7 3/4") |
| 400 | TON | RIP RAP CLASS II (2'-0" THICK) |
| 444 | SY | FILTER FABRIC FOR DRAINAGE |
| Lump Sum | LS | ELASTOMERIC BEARINGS |
| 3,210 | LF | 3'-0" X 2'-9" PRESTRESSED CONC |
| | | BOX BEAMS |
| 1 | EA | GENERIC STRUCTURE ITEM CSL TESTING |

Page: 23 of 62

L120117 020

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202739 33768.3.1 DIV OFFICE WILSON LENGTH = 0.613 MI

COUNTY : JOHNSTON

GRADING, DRAINAGE, PAVING, AND STRUCTURE.

ROADWAY ITEMS

DBE GOAL 11.0% COMPLETION DATE: DEC 31 2013

450 $\,$ TON $\,$ STONE FOR EROSION CONTROL,

BRIDGES #74 & 102 OVER BLACK CREEK AND APPROACHES ON NC-50 AND SR-1331.

| | | ROADWAY ITEMS | 430 | 1011 | CLASS A |
|--------------|-------|---|---------------|-----------|--|
| | | | 410 | TON | STONE FOR EROSION CONTROL, |
| Lump Sun | n LS | MOBILIZATION | | | CLASS B |
| Lump Sun | | REINFORCED BRIDGE APPROACH | 915 | TON | SEDIMENT CONTROL STONE |
| r | | FILL, STATION ******** | 6.5 | ACR | TEMPORARY MULCHING |
| | | (16+44.00) | 300 | LB TON | SEED FOR TEMPORARY SEEDING FERTILIZER FOR TEMPORARY SEED- |
| Lump Sun | n LS | BRIDGE APPROACH FILL - SUB REGIONAL TIER, STATION ****** | 2 | TON | ING |
| | | (17+87.50-L-) | 720 | LF | TEMPORARY SLOPE DRAINS |
| 2 | 2 ACR | SUPPLEMENTARY CLEARING & GRUB- | 15 | EA | INLET PROTECTION AT TEMPORARY |
| | | BING | 4.000 | | SLOPE DRAINS |
| 500 | | UNDERCUT EXCAVATION | 1,200 | LF | SAFETY FENCE |
| Lump Sun | | GRADING POPPOW EYCAVATION | 750 4,900 | CY SY | SILT EXCAVATION MATTING FOR EROSION CONTROL |
| 8,800 500 | | BORROW EXCAVATION SELECT GRANULAR MATERIAL | 4,500 | SY | COIR FIBER MAT |
| 79: | | FABRIC FOR SOIL STABILIZATION | 3,100 | LF | 1/4" HARDWARE CLOTH |
| 72 | | FOUNDATION CONDITIONING MATE- | 200 | SY | FLOATING TURBIDITY CURTAIN |
| | | RIAL, MINOR STRS | 8 | EA | SPECIAL STILLING BASINS |
| 140 |) SY | FOUNDATION CONDITIONING FABRIC | 40 | LB | POLYACRYLAMIDE (PAM) |
| 300 | | 15" DRAINAGE PIPE | 230 | LF | COIR FIBER BAFFLE |
| (| 5 EA | **" DRAINAGE PIPE ELBOWS (15") | 2 | EA | **" SKIMMER |
| 90 | 5 LF | 15" RC PIPE CULVERTS, CLASS | 7 | ACR | (1-1/2") SEEDING & MULCHING |
| , | , 11 | III | 5.5 | ACR | MOWING |
| 90 | 5 TON | AGGREGATE BASE COURSE | 100 | LB | SEED FOR REPAIR SEEDING |
| 50 | TON | INCIDENTAL STONE BASE | 0.5 | TON | FERTILIZER FOR REPAIR SEEDING |
| 500 | | INCIDENTAL MILLING | 175 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| 1,290 |) TON | ASPHALT CONC BASE COURSE, TYPE B25.0B | 4.75 | TON | FERTILIZER TOPDRESSING |
| 525 | TON | ASPHALT CONC INTERMEDIATE | 20 | MHR | SPECIALIZED HAND MOWING |
| 32. | 1011 | COURSE, TYPE I19.0B | 32 | EA | RESPONSE FOR EROSION CONTROL |
| 690 | 5 TON | ASPHALT CONC SURFACE COURSE, | 0.35 | ACR | REFORESTATION |
| | | TYPE S9.5B | | | |
| 510 |) TON | ASPHALT CONC SURFACE COURSE, TYPE SF9.5A | | | |
| 162 | 2 TON | ASPHALT BINDER FOR PLANT MIX | | | STRUCTURE ITEMS |
| 22 | | RIGHT OF WAY MARKERS | | | |
| 22.4 | | SUBDRAIN EXCAVATION | | | |
| 16.8 | | SUBDRAIN FINE AGGREGATE | Lump Sum | LS | CONSTRUCTION, MAINTENANCE, & |
| 100 |) LF | 6" PERFORATED SUBDRAIN PIPE | | | REMOVAL OF TEMP ACCESS AT STA |
| | I EA | SUBDRAIN PIPE OUTLETS | | | (17+87.50-L-) |
| (| | 6" OUTLET PIPE (SUBDRAINS) | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE |
| 1 | | MASONRY DRAINAGE STRUCTURES | | | AT STATION ************************************ |
| 6.3 | | MASONRY DRAINAGE STRUCTURES | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE |
| 1 | I EA | FRAME WITH TWO GRATES, STD 840.29 | r | | AT STATION ******** |
| 1,42 | 7 LF | SHOULDER BERM GUTTER | | | (17+87.50-L-) |
| 2,162.5 | 5 LF | STEEL BM GUARDRAIL | 123 | LF | **'-**" DIA DRILLED PIERS (3'-6") |
| 10 |) EA | ADDITIONAL GUARDRAIL POSTS | 79.6 | LF | PERMANENT STEEL CASING FOR |
| 4 | ‡ EA | GUARDRAIL ANCHOR UNITS, TYPE | ,,,,, | | 3'-6" DIA DRILLED PIER |
| | D F.A | III | 1 | EA | SID INSPECTION |
| • | B EA | GUARDRAIL ANCHOR UNITS, TYPE 350 | 1 | EA | SPT TESTING |
| 4 | 4 EA | GUARDRAIL ANCHOR UNITS, TYPE | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| | | B-77 | | | TION AT STATION ******* (16+44.00-L-) |
| 499.70 | 5 LF | REMOVE EXISTING GUARDRAIL | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| 10 | | RIP RAP, CLASS B | | | TION AT STATION ******* |
| 1,554 | | FILTER FABRIC FOR DRAINAGE | 2.050 | ar. | (17+87.50-L-) |
| 30 | | SUPPORTS, 3-LB STEEL U-CHANNEL | 3,878 | SF | REINFORCED CONCRETE DECK SLAB GROOVING BRIDGE FLOORS |
| | EA EA | SIGN ERECTION, TYPE D DISPOSAL OF SIGN SYSTEM, U- | 4,435 97.8 | SF CY | CLASS A CONCRETE (BRIDGE) |
| , |) LA | CHANNEL | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| 783 | 3 SF | WORK ZONE SIGNS (STATIONARY) | Zump Sum | 2.0 | ******* |
| 238 | 3 SF | WORK ZONE SIGNS (BARRICADE | | | (16+44.00-L-) |
| | | MOUNTED) | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| 192 | | BARRICADES (TYPE III) | | | (17+87.50-L-) |
| 2,180 |) LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) | 24,420 | LB | REINFORCING STEEL (BRIDGE) |
| 2,180 |) LF | THERMOPLASTIC PAVEMENT MARKING | 2,916 | LB | SPIRAL COLUMN REINFORCING |
| _, | | LINES (4", 120 MILS) | | | STEEL (BRIDGE) |
| 440 |) LF | COLD APPLIED PLASTIC PAVEMENT | 107,700 | LS | APPROX LBS STRUCTURAL |
| | | MARKING LINES, TYPE ** (4") | 530 | LF | STEEL HP12X53 STEEL PILES |
| 8,400 |) LF | (II) PAINT PAVEMENT MARKING LINES | 530 | EA | PILE REDRIVES |
| 0,400 | , LI | (4") | 216.67 | LF | CONCRETE BARRIER RAIL |
| 246 | 5 LF | 16" WATER LINE | 345.5 | LF | VERTICAL CONCRETE BARRIER RAIL |
| 238 | B LF | ABANDON 16" UTILITY PIPE | 745 | TON | RIP RAP CLASS II (2'-0" THICK) |
| 3,700 |) LF | TEMPORARY SILT FENCE | | | |
| | | | | | |

Page: 24 of 62

826 SY FILTER FABRIC FOR DRAINAGE

Lump Sum LS ELASTOMERIC BEARINGS

LIMP SUM LS EVAZOTE JOINT SEALS

1,725 LF 3'-0" X 2'-0" PRESTRESSED CONC CORED SLABS

1 EA GENERIC STRUCTURE ITEM CSL TESTING

Page: 25 of 62

L120117 021

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202749 33788.3.1 DIV OFFICE WILSON LENGTH = 0.161 MI

COUNTY: NASH

GRADING, DRAINAGE, PAVING, AND STRUCTURE.

325 TON SEDIMENT CONTROL STONE

DBE GOAL 11.0% COMPLETION DATE: DEC 31 2012

BRIDGE OVER STONEY CREEK AND APPROACHES ON SR-1670.

| | | ROADWAY ITEMS | 2.5 | ACR | TEMPORARY MULCHING |
|-----------------|------------|--|----------------------|-----------|--|
| | | | 100 1.5 | LB TON | SEED FOR TEMPORARY SEEDING FERTILIZER FOR TEMPORARY SEED- |
| Lump Sum | LS | MOBILIZATION | | | ING |
| Lump Sum | LS | BRIDGE APPROACH FILL - SUB | 200 700 | LF LF | TEMPORARY SLOPE DRAINS SAFETY FENCE |
| | | REGIONAL TIER, STATION ******* (15+85) | 170 | CY | SILT EXCAVATION |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- | 2,400 | SY | MATTING FOR EROSION CONTROL |
| *** | | BING | 30 | SY | COIR FIBER MAT |
| 200 Lump Sum | CY LS | UNDERCUT EXCAVATION GRADING | 800 | LF SY | 1/4" HARDWARE CLOTH FLOATING TURBIDITY CURTAIN |
| 2,600 | CY | BORROW EXCAVATION | 45 | EA | SPECIAL STILLING BASINS |
| 200 | CY | SELECT GRANULAR MATERIAL | 50 | LF | WATTLE |
| 1,110 | SY | GEOTEXTILE FOR SOIL STABILIZA- TION | 10 | LB | POLYACRYLAMIDE (PAM) |
| 37 | TON | FOUNDATION CONDITIONING MATE- | 100 | LF EA | COIR FIBER BAFFLE **" SKIMMER |
| | | RIAL, MINOR STRUCTURES | 3 | EA | (1-1/2") |
| 10 | SY | FOUNDATION CONDITIONING GEO- TEXTILE | 2.5 | ACR | SEEDING & MULCHING |
| 24 | LF | 15" DRAINAGE PIPE | 2.5 | ACR | MOWING |
| 2 | EA | **" DRAINAGE PIPE ELBOWS | 50 0.25 | LB TON | SEED FOR REPAIR SEEDING FERTILIZER FOR REPAIR SEEDING |
| 50 | TOM | (15") | 50 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| 50 50 | TON TON | AGGREGATE BASE COURSE INCIDENTAL STONE BASE | 1.5 | TON | FERTILIZER TOPDRESSING |
| 700 | TON | ASPHALT CONC BASE COURSE, TYPE | 10 | MHR | SPECIALIZED HAND MOWING |
| | | B25.0B | 16 0.15 | EA | RESPONSE FOR EROSION CONTROL REFORESTATION |
| 520 | TON | ASPHALT CONC SURFACE COURSE, TYPE SF9.5A | 0.13 | ACK | REPORESTATION |
| 70 | TON | ASPHALT BINDER FOR PLANT MIX | | | |
| 10 | EA | RIGHT OF WAY MARKERS | | | STRUCTURE ITEMS |
| 1 | EA | MASONRY DRAINAGE STRUCTURES | | | STRUCTURE ITEMS |
| 1 | EA | FRAME WITH TWO GRATES, STD 840.29 | | | |
| 330 | LF | 2'-6" CONCRETE CURB & GUTTER | Lump Sum | LS | CONSTRUCTION, MAINTENANCE, & |
| 25 | LF | SHOULDER BERM GUTTER | | | REMOVAL OF TEMP ACCESS AT STA |
| 180 | SY | 4" CONCRETE SIDEWALK | | | (15+85.00-L-) |
| 200 | EA LF | CONCRETE CURB RAMP STEEL BM GUARDRAIL | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE AT STATION ************************************ |
| 37.5 | LF | STEEL BM GUARDRAIL, SHOP | | | (15+85.00-L-) |
| _ | | CURVED | 41 | LF | 3'-6" DIA DRILLED PIERS IN SOIL |
| 5 1 | EA EA | ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE | 16 | LF | 3'-6" DIA DRILLED PIERS NOT IN |
| 1 | LA | AT-1 | | | SOIL |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE III | 24 | LF | PERMANENT STEEL CASING FOR 3'-6" DIA DRILLED PIER |
| 3 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 1 | EA | SID INSPECTIONS |
| | | 350 | 1 | EA | CSL TESTING |
| | TON | RIP RAP, CLASS B | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- TION AT STATION ******* |
| 1,010 95 | SY LF | GEOTEXTILE FOR DRAINAGE SUPPORTS, 3-LB STEEL U-CHANNEL | | | (15+85.00-L-) |
| 2 | EA | SIGN ERECTION, TYPE D | 28.7 | CY | CLASS AA CONCRETE (BRIDGE) |
| 1 | EA | SIGN ERECTION, TYPE E | 62.9 | CY | CLASS A CONCRETE (BRIDGE) |
| 1 | EA | SIGN ERECTION, RELOCATE, TYPE **** (GROUND MOUNTED) | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION ************************************ |
| | | (E) | | | (15+85.00-L-) |
| 6 | EA | DISPOSAL OF SIGN SYSTEM, U- | 15,679 1,462 | LB LB | REINFORCING STEEL (BRIDGE) EPOXY COATED REINFORCING STEEL |
| 2 | EA | CHANNEL DISPOSAL OF SIGN SYSTEM, WOOD | 1,402 | LD | (BRIDGE) |
| 1 | EA | DISPOSAL OF SUPPORT, U-CHANNEL | 1,729 | LB | SPIRAL COLUMN REINFORCING |
| 465 | SF | WORK ZONE SIGNS (STATIONARY) | 280 | LF | STEEL (BRIDGE) HP12X53 STEEL PILES |
| 94 | SF | WORK ZONE SIGNS (BARRICADE MOUNTED) | 140.25 | LF | TWO BAR METAL RAIL |
| 64 | LF | BARRICADES (TYPE III) | 140.25 | LF | THREE BAR METAL RAIL |
| 6,176 | LF | PAINT PAVEMENT MARKING LINES | 147.75 | LF | 1'-**"X *****" CONCRETE PARA- PET |
| 657 | LF | (4") 6" WATER LINE | | | (1'-2" X 2'-7 1/2 ") |
| 3 | EA | 6" VALVE | 410 | TON | RIP RAP CLASS II (2'-0" THICK) |
| 1 | EA | RECONNECT WATER METER | 460 | SY | GEOTEXTILE FOR DRAINAGE ELASTOMERIC BEARINGS |
| 588 | LF | ABANDON 6" UTILITY PIPE | Lump Sum 2,066,75 | LS LF | 3'-0" X 2'-9" PRESTRESSED CONC |
| 155 | LF | TRENCHLESS INSTALLATION OF 6" IN SOIL | 2,000.75 | | BOX BEAMS |
| 155 | LF | TRENCHLESS INSTALLATION OF 6" | | | |
| | | NOT IN SOIL | | | |
| 2,010 305 | LF TON | TEMPORARY SILT FENCE STONE FOR EROSION CONTROL, | | | |
| 303 | ION | CLASS A | | | |
| 75 | TON | | | | |
| 325 | TON | CLASS B SEDIMENT CONTROL STONE | | | |

Page: 26 of 62

L120117 022

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID : C202747 33739.3.1 **DIV OFFICE DURHAM LENGTH = 0.170 MI**

COUNTY : FRANKLIN

GRADING, DRAINAGE, PAVING, AND STRUCTURE.

50 LB SEED FOR TEMPORARY SEEDING 1.25 TON FERTILIZER FOR TEMPORARY SEED-ING

DBE GOAL 7.0% COMPLETION DATE: DEC 31 2012

BRIDGE OVER TAR RIVER AND APPROACHES ON SR-1003 (SIMS BRIDGE RD).

| | | ROADWAY ITEMS | 320 | LF | TEMPORARY SLOPE DRAINS |
|-------------------|-----------|--|-------------|------------|---|
| | | ROADWATTIEWS | 600 | LF | SAFETY FENCE |
| | | | 260 | CY | SILT EXCAVATION |
| Lump Sum | LS | MOBILIZATION | 6,000 | SY | MATTING FOR EROSION CONTROL |
| Lump Sum | LS | BRIDGE APPROACH FILL - SUB | 10 1,300 | SY LF | COIR FIBER MAT 1/4" HARDWARE CLOTH |
| | | REGIONAL TIER, STATION ******* (26+67.50) | 50 | SY | FLOATING TURBIDITY CURTAIN |
| 200 | CY | UNDERCUT EXCAVATION | 8 | EA | SPECIAL STILLING BASINS |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- | 100 | LF | WATTLE |
| T 0 | T C | BING | 25 | LB | POLYACRYLAMIDE (PAM) |
| Lump Sum 4,600 | LS CY | GRADING BORROW EXCAVATION | 70 | LF | COIR FIBER BAFFLE |
| 200 | CY | SELECT GRANULAR MATERIAL | 1 | EA | **" SKIMMER (1-1/2") |
| 300 | SY | GEOTEXTILE FOR SOIL STABILIZA- | 2 | ACR | SEEDING & MULCHING |
| | | TION | 2 | ACR | MOWING |
| 10 | TON | FOUNDATION CONDITIONING MATE- RIAL, MINOR STRUCTURES | 50 | LB | SEED FOR REPAIR SEEDING |
| 30 | SY | FOUNDATION CONDITIONING GEO- | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| 30 | 5. | TEXTILE | 50 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| 36 | LF | 15" DRAINAGE PIPE | 1.25 10 | TON MHR | FERTILIZER TOPDRESSING SPECIALIZED HAND MOWING |
| 2 | EA | **" DRAINAGE PIPE ELBOWS | 16 | EA | RESPONSE FOR EROSION CONTROL |
| 28 | LF | (15") 15" RC PIPE CULVERTS, CLASS IV | 0.25 | | REFORESTATION |
| 100 | TON | INCIDENTAL STONE BASE | | | |
| 390 | TON | ASPHALT CONC BASE COURSE, TYPE | | | |
| | | B25.0B | | | STRUCTURE ITEMS |
| 250 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0B | | | STREETERE ITEMS |
| 520 | TON | ASPHALT CONC SURFACE COURSE, | | | |
| 320 | 1011 | TYPE S9.5B | Lump Sum | LS | CONSTRUCTION, MAINTENANCE, & |
| 60 | TON | ASPHALT BINDER FOR PLANT MIX | | | REMOVAL OF TEMP ACCESS AT STA |
| 8 | EA | RIGHT OF WAY MARKERS | | | (26+67.50-L-) |
| 44.8 | CY | SUBDRAIN EXCAVATION | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE |
| 33.6 | CY | SUBDRAIN FINE AGGREGATE | | | AT STATION ************************************ |
| 200 | LF EA | 6" PERFORATED SUBDRAIN PIPE SUBDRAIN PIPE OUTLET | 152 | LF | (26+67.50-L-) **'-**" DIA DRILLED PIERS |
| 6 | LF | 6" OUTLET PIPE | 132 | Li | (4'-6") |
| 2 | EA | MASONRY DRAINAGE STRUCTURES | 36 | LF | PERMANENT STEEL CASING FOR |
| 2 | EA | FRAME WITH TWO GRATES, STD | | | **'-**" DIA DRILLED PIER (4'-6") |
| 20 | LE | 840.29 | 2 | EA | SID INSPECTIONS |
| 38 912.5 | LF LF | SHOULDER BERM GUTTER STEEL BM GUARDRAIL | 2 | EA | SPT TESTING |
| 5 | EA | ADDITIONAL GUARDRAIL POSTS | 1 | EA | CSL TESTING |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| | | III | | | TION AT STATION ************************************ |
| 2 | EA | GUARDRAIL ANCHOR UNITS, TYPE 350 | 116.3 | CY | CLASS A CONCRETE (BRIDGE) |
| 1,102 | LF | REMOVE EXISTING GUARDRAIL | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| 260 | TON | RIP RAP, CLASS II | | | ************************************** |
| 80 | TON | RIP RAP, CLASS B | 31,381 | LB | (26+67.50-L-) REINFORCING STEEL (BRIDGE) |
| 1,280 | SY | GEOTEXTILE FOR DRAINAGE | 6,599 | LB | SPIRAL COLUMN REINFORCING |
| 1 | EA | PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON | | | STEEL (BRIDGE) |
| 82 | LF | SUPPORTS, 3-LB STEEL U-CHANNEL | 555 | LF | HP12X53 STEEL PILES |
| 2 | EA | SIGN ERECTION, TYPE D | 564.81 | LF | VERTICAL CONCRETE BARRIER RAIL |
| 1 | EA | SIGN ERECTION, TYPE E | 700 785 | TON SY | RIP RAP CLASS II (2'-0" THICK) GEOTEXTILE FOR DRAINAGE |
| 5 | EA | DISPOSAL OF SIGN SYSTEM, U- | Lump Sum | LS | ELASTOMERIC BEARINGS |
| 740 | CE | CHANNEL WORK ZONE SIGNS (STATIONARY) | 3,106.47 | LF | 3'-0" X 3'-3" PRESTRESSED CONC |
| 740 116 | SF SF | WORK ZONE SIGNS (STATIONARY) WORK ZONE SIGNS (BARRICADE | | | BOX BEAMS |
| 110 | 51 | MOUNTED) | | | |
| 80 | LF | BARRICADES (TYPE III) | | | |
| 1,790 | LF | THERMOPLASTIC PAVEMENT MARKING | | | |
| 1,790 | LF | LINES (4", 90 MILS) THERMOPLASTIC PAVEMENT MARKING | | | |
| 1,770 | | LINES (4", 120 MILS) | | | |
| 11 | EA | PERMANENT RAISED PAVEMENT | | | |
| 1 450 | I F | MARKERS TEMPORARY SHIT FENCE | | | |
| 1,450 225 | LF TON | TEMPORARY SILT FENCE STONE FOR EROSION CONTROL, | | | |
| 223 | 1011 | CLASS A | | | |
| 150 | TON | | | | |
| 40= | TON | CLASS B | | | |
| | | SEDIMENT CONTROL STONE TEMPORARY MULCHING | | | |
| 1.5 | ACK | TEMPORARY MULCHING | | | |

Page: 27 of 62

L120117 023

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID : C202733 33820.3.1 **DIV OFFICE DURHAM LENGTH = 0.257 MI**

COUNTY : WAKE

GRADING, DRAINAGE, PAVING, SIGNALS, AND STRUCTURES.

DBE GOAL 10.0% COMPLETION DATE : SEE SPECIAL PROVISIONS

BRIDGE OVER NORFOLK SOUTHERN RAILROAD AND APPROACHES ON SR-1101.

| | | ROADWAY ITEMS | 15 | EA | DISPOSAL OF SIGN SYSTEM, U-CHANNEL |
|----------|------|--|--------|------|--|
| | | | 328 | SF | WORK ZONE SIGNS (STATIONARY) |
| Lump Sum | LS | MOBILIZATION | 192 | SF | WORK ZONE SIGNS (PORTABLE) |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH | 52 | SF | WORK ZONE SIGNS (BARRICADE |
| Zump Jum | 20 | FILL, STATION ********* | | | MOUNTED) |
| | | (17+68.30) | 50 | EA | DRUMS |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- | 50 | EA | CONES |
| | | BING | 96 | LF | BARRICADES (TYPE III) |
| 200 | CY | UNDERCUT EXCAVATION | 640 | HR | FLAGGER |
| Lump Sum | LS | GRADING | 50 | EA | SKINNY DRUM |
| 19,400 | CY | BORROW EXCAVATION | 22 | EA | TEMPORARY RAISED PAVEMENT |
| 20 | CY | DRAINAGE DITCH EXCAVATION | | | MARKERS |
| 200 | CY | SELECT GRANULAR MATERIAL | 2,428 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 200 | SY | FABRIC FOR SOIL STABILIZATION | 2 429 | T.E. | LINES (4", 90 MILS) |
| 90 | TON | FOUNDATION CONDITIONING MATE- | 2,428 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| | | RIAL, MINOR STRS | 23 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 260 | SY | FOUNDATION CONDITIONING FABRIC | 23 | | LINES (24", 120 MILS) |
| 164 | LF | 15" DRAINAGE PIPE | 564 | LF | COLD APPLIED PLASTIC PAVEMENT |
| 80 | LF | 24" DRAINAGE PIPE | | | MARKING LINES, TYPE ** (4") |
| 404 | LF | 15" RC PIPE CULVERTS, CLASS | | | (II) |
| | | Ш | 13,600 | LF | PAINT PAVEMENT MARKING LINES |
| 56 | LF | 24" RC PIPE CULVERTS, CLASS | | | (4") |
| | | III | 96 | LF | PAINT PAVEMENT MARKING LINES |
| 60 | LF | 15" CS PIPE CULVERTS, 0.064" THICK | | | (24") |
| 4 | EA | | 24 | LF | REMOVAL OF PAVEMENT MARKING |
| 4 | EA | **" CS PIPE ELBOWS, *****" THICK | 10 | г. | LINES (24") |
| | | (15", 0.064") | 18 | EA | PERMANENT RAISED PAVEMENT MARKERS |
| 244 | LF | PIPE REMOVAL | 93 | LF | 2" WATER LINE |
| 809 | TON | AGGREGATE BASE COURSE | 130 | LF | 6" WATER LINE |
| 200 | TON | INCIDENTAL STONE BASE | | | |
| 578 | GAL | PRIME COAT | 1 | EA | 2" BLOW OFF |
| 290 | SY | INCIDENTAL MILLING | 4,100 | LF | TEMPORARY SILT FENCE |
| 1,020 | TON | ASPHALT CONC BASE COURSE, TYPE | 270 | TON | STONE FOR EROSION CONTROL, CLASS A |
| 1,020 | 1011 | B25.0B | 440 | TON | STONE FOR EROSION CONTROL, |
| 860 | TON | ASPHALT CONC INTERMEDIATE | 440 | ION | CLASS B |
| | | COURSE, TYPE I19.0B | 340 | TON | SEDIMENT CONTROL STONE |
| 1,080 | TON | ASPHALT CONC SURFACE COURSE, | 2.5 | ACR | TEMPORARY MULCHING |
| | | TYPE S9.5B | 100 | LB | SEED FOR TEMPORARY SEEDING |
| 155 | TON | ASPHALT BINDER FOR PLANT MIX | 0.25 | TON | FERTILIZER FOR TEMPORARY SEED- |
| 7 | TON | ASPHALT PLANT MIX, PAVEMENT | 0.23 | 1011 | ING |
| | | REPAIR | 300 | LF | TEMPORARY SLOPE DRAINS |
| 5 | EA | RIGHT OF WAY MARKERS | 6 | EA | INLET PROTECTION AT TEMPORARY |
| 10 | EA | MASONRY DRAINAGE STRUCTURES | | | SLOPE DRAINS |
| 3.86 | LF | MASONRY DRAINAGE STRUCTURES | 200 | LF | SAFETY FENCE |
| 1 | EA | FRAME WITH TWO GRATES, STD | 700 | CY | SILT EXCAVATION |
| | | 840.16 | 4,000 | SY | MATTING FOR EROSION CONTROL |
| 1 | EA | FRAME WITH TWO GRATES, STD | 800 | LF | 1/4" HARDWARE CLOTH |
| - | Б. | 840.24 | 300 | LF | COIR FIBER BAFFLE |
| 7 | EA | FRAME WITH TWO GRATES, STD 840.29 | 3.6 | ACR | SEEDING & MULCHING |
| 1 | EA | | 2.5 | ACR | MOWING |
| 1 | LA | FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** | 50 | LB | SEED FOR REPAIR SEEDING |
| | | (G) | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| 80 | LF | **"X **" CONCRETE CURB | 75 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| | | (9" X 12") | 2.25 | | FERTILIZER TOPDRESSING |
| 170 | LF | 2'-6" CONCRETE CURB & GUTTER | | | SPECIALIZED HAND MOWING |
| 614 | LF | SHOULDER BERM GUTTER | 18 | EA | RESPONSE FOR EROSION CONTROL |
| 10 | SY | 6" CONCRETE DRIVEWAY | 550 | LF | SIGNAL CABLE |
| 140 | SY | 4" CONCRETE ISLAND COVERS | 8 | EA | VEHICLE SIGNAL HEAD (12", 3 |
| 220 | LF | STEEL BM GUARDRAIL | o o | Lar | SECTION) |
| 25 | LF | STEEL BM GUARDRAIL, SHOP | 270 | LF | MESSENGER CABLE (3/8") |
| | | CURVED | 50 | LF | PAVED TRENCHING (********) |
| 5 | EA | ADDITIONAL GUARDRAIL POSTS | | | (1, 2") |
| 1 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 1,210 | LF | UNPAVED TRENCHING (*******) |
| | | AT-1 | | | (1, 2") |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 9 | EA | JUNCTION BOX (STANDARD SIZE) |
| | | III | 2 | EA | WOOD POLE |
| 3 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 8 | EA | GUY ASSEMBLY |
| 205 | , - | 350 | 1 | EA | 1" RISER WITH WEATHERHEAD |
| 380 | LF | GENERIC GUARDRAIL ITEM STEEL BEAM GUARDRAIL WITH 8' | 5 | EA | 2" RISER WITH WEATHERHEAD |
| | | POST | 480 | LF | INDUCTIVE LOOP SAWCUT |
| 10 | TON | RIP RAP, CLASS B | 1,790 | LF | LEAD-IN CABLE (**********) |
| 485 | SY | FILTER FABRIC FOR DRAINAGE | | | (14-2) |
| 64 | LF | SUPPORTS, 3-LB STEEL U-CHANNEL | 1 | EA | CONTROLLER WITH CABINET (TYPE |
| 2 | EA | SIGN ERECTION, TYPE E | | | 2070L, POLE MOUNTED) |
| 2 | EA | SIGN ERECTION, TYPE F | 4 | EA | DETECTOR CARD (TYPE 2070L) |
| 2 | ĿА | SIGN EXECTION, THE P | | | |

Page: 28 of 62

1 EA TRAFFIC SIGNAL REMOVAL

WALL ITEMS

3,710 SF MSE RETAINING WALLS

STRUCTURE ITEMS

| Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE |
|----------|-----|---|
| | | AT STATION ************************************ |
| | | (17+64.30-L-) |
| 1 | EA | PDA TESTING |
| 1 | EA | PDA ASSISTANCE |
| Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| | | TION AT STATION ****** |
| | | (17+64.30-L-) |
| 5,370 | SF | REINFORCED CONCRETE DECK SLAB |
| 5,354 | SF | GROOVING BRIDGE FLOORS |
| 76.2 | CY | CLASS A CONCRETE (BRIDGE) |
| Lump Sum | LS | BRIDGE APPROACH SLABS, STATION ************* |
| | | (17+64.30-L-) |
| 11,824 | LB | REINFORCING STEEL (BRIDGE) |
| 687.08 | LF | 45" PRESTRESSED CONCRETE GIR- DERS |
| 675 | LF | HP12X53 STEEL PILES |
| 920 | LF | PP 18 X 0.50 GALVANIZED STEEL |
| 920 | LF | PILES |
| 14 | EA | PILE REDRIVES |
| 263.67 | LF | TWO BAR METAL RAIL |
| 139.33 | LF | 1'-**"X *****" CONCRETE PARA- |
| | | PET |
| | | (1'-2" X 2'-10") |
| 139.33 | LF | 1'-**"X *****" CONCRETE PARA- |
| | | PET |
| | | (1'-2" X 3'-6 3/4") |
| Lump Sum | LS | ELASTOMERIC BEARINGS |
| Lump Sum | LS | EVAZOTE JOINT SEALS |
| 1,500 | DOL | CONTRACT TIME |
| | | |

Page: 29 of 62

L120117 024

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID : C202751 33823.3.1 **DIV OFFICE DURHAM LENGTH = 0.143 MI**

COUNTY : WAKE

GRADING, DRAINAGE, PAVING, AND STRUCTURE.

100 LB SEED FOR TEMPORARY SEEDING 2.25 TON FERTILIZER FOR TEMPORARY SEED-

ING 200 LF TEMPORARY SLOPE DRAINS

700 LF SAFETY FENCE

DBE GOAL 10.0% COMPLETION DATE: SEE SPECIAL PROVISIONS

BRIDGE OVER POWELL CREEK AND APPROACHES ON SR-2227.

| ID GE O | | OVERE CHERITING III I NOI | TOTAL OF THE TAXABLE PROPERTY. | | |
|------------|----------|---|--------------------------------|-----------|---|
| | | ROADWAY ITEMS | 170 | CY | SILT EXCAVATION |
| | | ROADWATTEMS | 3,000 | SY | MATTING FOR EROSION CONTROL |
| | | | 20 | SY | COIR FIBER MAT |
| Lump Sum | LS | MOBILIZATION | 1,300 | LF | 1/4" HARDWARE CLOTH |
| Lump Sum | LS | BRIDGE APPROACH FILL - SUB | 655 | SY | FLOATING TURBIDITY CURTAIN |
| | | REGIONAL TIER, STATION ****** | 150 | LF | WATTLE |
| Lumn Sum | LS | (24+50) GRADING | 50 | LB | POLYACRYLAMIDE (PAM) |
| Lump Sum 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- | 75 2 | LF EA | COIR FIBER BAFFLE **" SKIMMER |
| 1 | ACK | BING | 2 | LA | (1-1/2") |
| 200 | CY | UNDERCUT EXCAVATION | 1.5 | ACR | SEEDING & MULCHING |
| 40 | CY | DRAINAGE DITCH EXCAVATION | 1.5 | ACR | MOWING |
| 200 | CY | SELECT GRANULAR MATERIAL | 50 | LB | SEED FOR REPAIR SEEDING |
| 300 | SY | GEOTEXTILE FOR SOIL STABILIZA- TION | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| 340 | TON | ROCK EMBANKMENTS | 50 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| 330 | SY | ROCK PLATING | 1 | TON | FERTILIZER TOPDRESSING |
| 150 | SY | GENERIC GRADING ITEM | 10 18 | MHR EA | SPECIALIZED HAND MOWING RESPONSE FOR EROSION CONTROL |
| | | FILTER FABRIC FOR ROCK EMBANKMENT | 0.1 | | REFORESTATION |
| 30 | TON | FOUNDATION CONDITIONING MATE- | | | |
| | | RIAL, MINOR STRUCTURES | | | |
| 90 | SY | FOUNDATION CONDITIONING GEO- | | | STRUCTURE ITEMS |
| 06 | T.F. | TEXTILE | | | |
| 96 156 | LF LF | 15" SIDE DRAIN PIPE 15" RC PIPE CULVERTS, CLASS IV | | | |
| 80 | TON | #57 STONE | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE |
| 100 | TON | INCIDENTAL STONE BASE | | | AT STATION ************************************ |
| 490 | TON | ASPHALT CONC BASE COURSE, TYPE | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- |
| | | B25.0B | Lump Sum | LO | TION AT STATION ******* |
| 345 | TON | ASPHALT CONC INTERMEDIATE | | | (24+50.00-L-) |
| 165 | TON | COURSE, TYPE 119.0B ASPHALT CONC SURFACE COURSE, | 50.2 | CY | CLASS A CONCRETE (BRIDGE) |
| 465 | ION | TYPE S9.5B | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| 66 | TON | ASPHALT BINDER FOR PLANT MIX | | | (24+50.00-L-) |
| 5 | EA | RIGHT OF WAY MARKERS | 8,582 | LB | REINFORCING STEEL (BRIDGE) |
| 2 | EA | MASONRY DRAINAGE STRUCTURES | 280 | LF | HP12X53 STEEL PILES |
| 1 | EA | FRAME WITH TWO GRATES, STD 840.29 | 440 | LF | HP14X73 GALVANIZED STEEL PILES |
| 16 | LF | SHOULDER BERM GUTTER | 16 | EA | STEEL PILE POINTS |
| 1 | EA | ADJUSTMENT OF MANHOLES | 245.5 260.5 | LF LF | TWO BAR METAL RAIL 1'-**"X *****" CONCRETE PARA- |
| 225 | LF | STEEL BM GUARDRAIL | 200.5 | Li | PET |
| 5 | EA | ADDITIONAL GUARDRAIL POSTS | | | (1'-2" X 2'-10") |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 245 | TON | RIP RAP CLASS II (2'-0" THICK) |
| | EA | III | 280 | SY | GEOTEXTILE FOR DRAINAGE |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE 350 | Lump Sum 1,430 | LS LF | ELASTOMERIC BEARINGS 3'-0" X 1'-9" PRESTRESSED CONC |
| 157 | TON | RIP RAP, CLASS B | 1,430 | LI | CORED SLABS |
| 972 | SY | GEOTEXTILE FOR DRAINAGE | | | |
| 2 | EA | PREFORMED SCOUR HOLES WITH | | | |
| 77 | | LEVEL SPREADER APRON | | | |
| 77 2 | LF EA | SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE D | | | |
| 1 | EA | SIGN ERECTION, TYPE B | | | |
| 16 | EA | DISPOSAL OF SIGN SYSTEM, U- | | | |
| | | CHANNEL | | | |
| 408 | SF | WORK ZONE SIGNS (STATIONARY) | | | |
| 104 | SF | WORK ZONE SIGNS (BARRICADE | | | |
| 27 | EA | MOUNTED) DRUMS | | | |
| 80 | LF | BARRICADES (TYPE III) | | | |
| 754 | LF | THERMOPLASTIC PAVEMENT MARKING | | | |
| 1,508 | LF | LINES (4", 90 MILS) THERMOPLASTIC PAVEMENT MARKING | | | |
| | | LINES (4", 120 MILS) | | | |
| 9 | EA | PERMANENT RAISED PAVEMENT MARKERS | | | |
| 725 | LF | TEMPORARY SILT FENCE | | | |
| 225 | TON | STONE FOR EROSION CONTROL, CLASS A | | | |
| 100 | TON | | | | |
| | merr | CLASS B | | | |
| | TON | SEDIMENT CONTROL STONE TEMPORARY MULICHING | | | |
| 1.5 | ACK | TEMPORARY MULCHING | | | |

Page: 30 of 62

L120117 025

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID : C202875 47030.3.1 **DIV OFFICE DURHAM LENGTH = 17.133 MI**

COUNTY: WAKE, DURHAM

MILLING, RESURFACING, SHOULDER RECONST, AND STR REHAB.

(HIGHLY REFLECTIVE ELEMENTS)

LINES (6")

REMOVAL OF PAVEMENT MARKING

5,226 LF

DBE GOAL 10.0% COMPLETION DATE: NOV 15 2012

I-540 FROM I-40 OVERPASS TO TRIANGLE TOWN BLVD, AND TRIANGLE TOWN BLVD FROM I-540 TO NEW ASPHALT PAVEMENT JOINT.

| PHALIP | AVL | MENI JOINI. | | | |
|-------------------|------------|---|----------------|----------|---|
| | | ROADWAY ITEMS | 222 | LF | REMOVAL OF PAVEMENT MARKING LINES (8") |
| | | | 66 | LF | REMOVAL OF PAVEMENT MARKING LINES (24") |
| Lump Sum 4,020 | LS CY | MOBILIZATION BORROW EXCAVATION | 8 | EA | REMOVAL OF PAVEMENT MARKING SYMBOLS & CHARACTERS |
| 69.96 | SMI | GENERIC GRADING ITEM SHOULDER GRADING | 185 | EA | GENERIC PAVEMENT MARKING ITEM REPLACE EXISTING BARRIER |
| 8,825 | TON | AGGREGATE BASE COURSE | *** | | DELINEATOR |
| 3,303 3.8 | TON SMI | INCIDENTAL STONE BASE SHOULDER RECONSTRUCTION | 117 | EA | PERMANENT RAISED PAVEMENT MARKERS |
| 695,818 | SY | MILLING ASPHALT PAVEMENT, ***" | 4,994 | EA | SNOWPLOWABLE PAVEMENT MARKERS |
| 0,5,010 | | DEPTH | 90 | EA | FLEXIBLE DELINEATORS (CRYSTAL) |
| 22 525 | CXZ | (2") | 90 | EA | FLEXIBLE DELINEATORS (YELLOW) |
| 33,727 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH | Lump Sum | LS | PORTABLE LIGHTING |
| | | (3") | 3,029 2,840 | LF SY | TEMPORARY SILT FENCE MATTING FOR EROSION CONTROL |
| 1,467 | SY | MILLING ASPHALT PAVEMENT, ***" | 3,600 | LF | WATTLE |
| | | DEPTH (4-1/2") | 264 | LB | POLYACRYLAMIDE (PAM) |
| 714 | SY | MILLING ASPHALT PAVEMENT, ***" | 51.17 | ACR | SEEDING & MULCHING |
| | | DEPTH | 150 | LF | UNPAVED TRENCHING (********) |
| 466 | TON | (6") ASPHALT CONC INTERMEDIATE | 2,556 | LF | (1, 1") INDUCTIVE LOOP SAWCUT |
| 400 | 1011 | COURSE, TYPE I19.0C | 2,330 | LF | GENERIC STRUCTURE ITEM |
| 886 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B | | _ | EXPANSION JOINT EPDM OR |
| 84,839 | TON | ASPHALT CONC SURFACE COURSE, | | | NEOPRENE GLAND ELASTOMERIC RE- PLACEMENT |
| £ 001 | TON | TYPE S9.5C | 500 | LF | GENERIC STRUCTURE ITEM FILLED EXPANSION JOINT |
| 5,081 11,771 | TON LB | ASPHALT BINDER FOR PLANT MIX SEALING EXISTING PAVEMENT | | | REPLACEMENT |
| 11,771 | 22 | CRACKS & JOINTS | 1,624 | LF | GENERIC STRUCTURE ITEM |
| 150 | TON | PATCHING EXISTING PAVEMENT | 570 | LE | FOAM JOINT SEALS |
| 435,017 | SY | GENERIC PAVING ITEM FOG SEAL | 570 | LF | GENERIC STRUCTURE ITEM MODULAR EXPANSION JOINT |
| Lump Sum | LS | TEMPORARY TRAFFIC CONTROL | 155 | | ELASTOMERIC SEAL |
| 2,000 | HR | LAW ENFORCEMENT | 155 | LF | GENERIC STRUCTURE ITEM PREFORMED COMPRESSION JOINT |
| 6,336 | LF | THERMOPLASTIC PAVEMENT MARKING | | | SEAL |
| 2,212 | LF | LINES (4", 90 MILS) THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) | 587,420.4 | SF | GENERIC STRUCTURE ITEM PLACEMENT OF CRACK/DECK SEALER |
| 321,150 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (6", 90 MILS) | | | |
| 79,411 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (6", 120 MILS) | | | |
| 285 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 90 MILS) | | | |
| 102 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 120 MILS) | | | |
| 22,187 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (12", 90 MILS) | | | |
| 461 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) | | | |
| 146 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) | | | |
| 66 | LF | COLD APPLIED PLASTIC PAVEMENT MARKING LINES, TYPE ** (24") (II) | | | |
| 5 | EA | COLD APPLIED PLASTIC PAVEMENT MARKING CHARACTER, TYPE ** (III) | | | |
| 4 | EA | COLD APPLIED PLASTIC PAVEMENT MARKING SYMBOL, TYPE ** (II) | | | |
| 17,108 | LF | PAINT PAVEMENT MARKING LINES (4") | | | |
| 102 | LF | PAINT PAVEMENT MARKING LINES (8") | | | |
| 841 | LF | PAINT PAVEMENT MARKING LINES (12") | | | |
| 120 | LF | PAINT PAVEMENT MARKING LINES (24") | | | |
| 26 | EA | PAINT PAVEMENT MARKING SYMBOL | | | |
| 5,226 | LF | POLYUREA PAVEMENT MARKING LINES (6", ************) | | | |
| 1,567 | LF | (HIGHLY REFLECTIVE ELEMENTS) POLYUREA PAVEMENT MARKING LINES (S". ************) | | | |

Page: 31 of 62

L120117 026

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202928 5CR.10321.22 DIV OFFICE DURHAM LENGTH = 13.570 MI

COUNTY : DURHAM

WIDENING, MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION.

MBE GOAL 5.0% WBE 5.0% COMPLETION DATE: NOV 09 2012

NC-54 FROM NC-55 TO WEST OF DAVIS DR AND 10 SECTIONS OF SECONDARY ROADS.

| Lump Sum | LS | MOBILIZATION |
|----------|-----|--|
| 2,311 | CY | BORROW EXCAVATION |
| 1,162 | TON | INCIDENTAL STONE BASE |
| 23.23 | SMI | SHOULDER RECONSTRUCTION |
| 57,067 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (1-1/2") |
| 141,072 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (2-1/2") |
| 2,432 | SY | MILLING ASPHALT PAVEMENT, ***" TO ******" (0" TO 1-1/2") |
| 4.223 | SY | INCIDENTAL MILLING |
| 1,462 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B |
| 23,394 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE I19.0B |
| 20,353 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 2,409 | TON | ASPHALT BINDER FOR PLANT MIX |
| 1,485 | TON | PATCHING EXISTING PAVEMENT |
| 38 | EA | ADJUSTMENT OF MANHOLES |
| 10 | EA | ADJUSTMENT OF METER BOXES OR VALVE BOXES |
| 110,829 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 161,047 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 1,010 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 90 MILS) |
| 300 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 120 MILS) |
| 350 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (16", 120 MILS) |
| 990 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 30 | EA | THERMOPLASTIC PAVEMENT MARKING CHARACTER (120 MILS) |
| 134 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 237,631 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 810 | LF | PAINT PAVEMENT MARKING LINES (8") |
| 350 | LF | PAINT PAVEMENT MARKING LINES (16") |
| 820 | LF | PAINT PAVEMENT MARKING LINES (24") |
| 18 | EA | PAINT PAVEMENT MARKING CHARACTER |
| 112 | EA | PAINT PAVEMENT MARKING SYMBOL |
| 1,632 | EA | PERMANENT RAISED PAVEMENT MARKERS |
| 1,839 | LF | TEMPORARY SILT FENCE |
| 4,630 | LF | WATTLE |
| 18.39 | ACR | SEEDING & MULCHING |
| 2,574 | LF | INDUCTIVE LOOP SAWCUT |
| 500 | LF | LEAD-IN CABLE (*************) (18-4) |

Page: 32 of 62

L120117 027

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202918 5CR.20321.21 DIV OFFICE DURHAM LENGTH = 6.090 MI

COUNTY : DURHAM

MILLING, RESURFACING & SHOULDER RECONSTRUCTION.

MBE GOAL 5.0% WBE 6.0% COMPLETION DATE: JUN 29 2012

5 SECTIONS OF SECONDARY ROADS.

| Lump Sum | LS | MOBILIZATION |
|----------------|-----------|---|
| 1,201 | CY | BORROW EXCAVATION |
| 597 | TON | INCIDENTAL STONE BASE |
| 12.01 | SMI | SHOULDER RECONSTRUCTION |
| 62,452 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (2-1/2") |
| 1,112 | SY | MILLING ASPHALT PAVEMENT, ***" TO ******" |
| 2 249 | CXZ | (0" TO 1-1/2") |
| 2,348 9,390 | SY TON | INCIDENTAL MILLING ASPHALT CONC INTERMEDIATE |
| 9,390 | ION | COURSE, TYPE I19.0B |
| 7,139 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 879 | TON | ASPHALT BINDER FOR PLANT MIX |
| 945 | TON | PATCHING EXISTING PAVEMENT |
| 7 | EA | ADJUSTMENT OF MANHOLES |
| 3 | EA | ADJUSTMENT OF METER BOXES OR VALVE BOXES |
| 62,064 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 63,046 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 100 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 90 MILS) |
| 106 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 17 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 2,560 | LF | COLD APPLIED PLASTIC PAVEMENT MARKING LINES, TYPE ** (4") (III) |
| 101,676 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 100 | LF | PAINT PAVEMENT MARKING LINES (8") |
| 35 | LF | PAINT PAVEMENT MARKING LINES (24") |
| 11 | EA | PAINT PAVEMENT MARKING SYMBOL |
| 2,560 | LF | REMOVAL OF PAVEMENT MARKING LINES (4") |
| 469 | EA | PERMANENT RAISED PAVEMENT MARKERS |
| 867 | LF | TEMPORARY SILT FENCE |
| 2,180 | LF | WATTLE |
| 8.67 | ACR | SEEDING & MULCHING |
| 302 | LF | INDUCTIVE LOOP SAWCUT |
| | | |

Page: 33 of 62

L120117 028

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202724 33448.2.2 DIV OFFICE FAYETTEVILLE LENGTH = 0.227 MI

COUNTY : CUMBERLAND

GRADING, DRAINAGE, PAVING, AND STRUCTURES.

DBE GOAL 10.0% COMPLETION DATE: DEC 31 2013

BRIDGE OVER CROSS CREEK & APPROACHES ON NC-24 IN FAYETTEVILLE.

| | | | 4 | ΕA | TMIA |
|----------------|-----------|--|---------------|------------|--|
| | | ROADWAY ITEMS | 4 940 | EA LF | TMIA PORTABLE CONCRETE BARRIER |
| | | | 700 | LF | PORTABLE CONCRETE BARRIER (ANCHORED) |
| Lump Sum | LS | MOBILIZATION | 180 | LF | PORTABLE CONCRETE BARRIER |
| Lump Sum | LS | CONSTRUCTION SURVEYING | | | (DRAINAGE) |
| Lump Sum 1 | LS ACR | CLEARING & GRUBBING ACRE(S) SUPPLEMENTARY CLEARING & GRUB- | 760 | LF | RESET PORTABLE CONCRETE BAR- RIER |
| 14,200 | CY | BING UNCLASSIFIED EXCAVATION | 180 | LF | RESET PORTABLE CONCRETE BAR- RIER (DRAINAGE) |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH | 180 | HR | LAW ENFORCEMENT |
| | | FILL, STATION ************************************ | 64 | EA | SKINNY DRUM |
| 300 | CY | UNDERCUT EXCAVATION | 341 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 20,400 15 | CY CY | BORROW EXCAVATION DRAINAGE DITCH EXCAVATION | 3,152 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 4,100 | SY | REMOVAL OF EXISTING ASPHALT | 95 | LF | LINES (4", 120 MILS) THERMOPLASTIC PAVEMENT MARKING |
| 300 | CY | PAVEMENT SELECT GRANULAR MATERIAL | 0 | Б. | LINES (8", 90 MILS) |
| 2,050 | SY | FABRIC FOR SOIL STABILIZATION | 8 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 730 | SF | TEMPORARY SHORING | 690 | LF | COLD APPLIED PLASTIC PAVEMENT |
| 20 | TON | FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS | | | MARKING LINES, TYPE ** (4") (III) |
| 40 | SY | FOUNDATION CONDITIONING FABRIC | 1,323 | LF | COLD APPLIED PLASTIC PAVEMENT |
| 96 | LF | 24" CS PIPE CULVERTS, 0.064" | | | MARKING LINES, TYPE ** (4") |
| | | THICK | 29,984 | LF | (IV) PAINT PAVEMENT MARKING LINES |
| 64 Lump Sum | LF LS | PIPE REMOVAL FINE GRADING | 2,,,,,,,,,, | | (4") |
| 1,762 | TON | AGGREGATE BASE COURSE | 432 | LF | PAINT PAVEMENT MARKING LINES |
| 380 | SY | INCIDENTAL MILLING | 340 | LF | (8") PAINT PAVEMENT MARKING LINES |
| 260 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0C | | | (24") |
| 250 | TON | ASPHALT CONC INTERMEDIATE | 24 | EA | PAINT PAVEMENT MARKING CHARAC- TER |
| 500 | TON | COURSE, TYPE 119.0C ASPHALT CONC SURFACE COURSE, | 104 11,762 | EA LF | PAINT PAVEMENT MARKING SYMBOL REMOVAL OF PAVEMENT MARKING |
| 245 | TON | TYPE S9.5B | 11,702 | LI | LINES (4") |
| 245 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5C | 633 | LF | REMOVAL OF PAVEMENT MARKING LINES (8") |
| 70 1 | TON CY | ASPHALT BINDER FOR PLANT MIX PIPE COLLARS | 25 | EA | REMOVAL OF PAVEMENT MARKING |
| 600 | LF | 2'-6" CONCRETE CURB & GUTTER | 472 | EA | SYMBOLS & CHARACTERS PERMANENT RAISED PAVEMENT |
| 300 | SY | 4" CONCRETE SIDEWALK | 172 | | MARKERS |
| 110 | SY | 5" MONOLITHIC CONCRETE ISLANDS | Lump Sum | LS | PORTABLE LIGHTING |
| 1 | EA | (KEYED IN) GENERIC PAVING ITEM | 3,370 225 | LF TON | TEMPORARY SILT FENCE STONE FOR EROSION CONTROL, |
| | | CONCRETE CURB RAMPS | 223 | ION | CLASS A |
| 1 | EA | ADJUSTMENT OF CATCH BASINS | 380 | TON | STONE FOR EROSION CONTROL, |
| 225 | LF EA | STEEL BM GUARDRAIL ADDITIONAL GUARDRAIL POSTS | 165 | TON | CLASS B |
| 5 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 465 5 | TON ACR | SEDIMENT CONTROL STONE TEMPORARY MULCHING |
| 7 | LA | III | 200 | LB | SEED FOR TEMPORARY SEEDING |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE 350 | 1.75 | TON | FERTILIZER FOR TEMPORARY SEED-ING |
| 300 | LF | CHAIN LINK FENCE, **" FABRIC | 800 | LF | TEMPORARY SLOPE DRAINS |
| 25 | EA | (120") METAL LINE POSTS FOR **" CHAIN | 10 | EA | INLET PROTECTION AT TEMPORARY |
| 23 | LA | LINK FENCE | 000 | IE | SLOPE DRAINS |
| | | (120") | 900 440 | LF CY | SAFETY FENCE SILT EXCAVATION |
| 5 | EA | METAL TERMINAL POSTS FOR **" CHAIN LINK FENCE | 6,500 | SY | MATTING FOR EROSION CONTROL |
| | | (120") | 1,050 | SY | COIR FIBER MAT |
| 43 | TON | RIP RAP, CLASS I | 1,400 | SY | PERMANENT SOIL REINFORCEMENT |
| 1,149 | SY | FILTER FABRIC FOR DRAINAGE | 300 | LF | MAT 1/4" HARDWARE CLOTH |
| 97 | LF | SUPPORTS, 3-LB STEEL U-CHANNEL | 2 | EA | SPECIAL STILLING BASINS |
| 12 13 | EA EA | SIGN ERECTION, TYPE E DISPOSAL OF SIGN SYSTEM, U- | 100 | LF | WATTLE |
| 13 | LA | CHANNEL | 25 | LB | POLYACRYLAMIDE (PAM) |
| 853 | SF | WORK ZONE SIGNS (STATIONARY) | 240 | LF | COIR FIBER BAFFLE |
| 514 | SF | WORK ZONE SIGNS (PORTABLE) | 1 | EA | **" SKIMMER (1-1/2") |
| 44 | SF | WORK ZONE SIGNS (BARRICADE MOUNTED) | 6 | ACR | SEEDING & MULCHING |
| 4 | EA | FLASHING ARROW PANELS, TYPE C | | | MOWING |
| 4 | EA | CHANGEABLE MESSAGE SIGN | | LB | SEED FOR REPAIR SEEDING |
| 105 | EA | DRUMS | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| 64 | EA | CONES | 150 | | SEED FOR SUPPLEMENTAL SEEDING |
| 80 | LF | BARRICADES (TYPE III) | 4.5 | | FERTILIZER TOPDRESSING |
| 56 | HR | FLAGGER TEMPORARY CRASH CUSHIONS | 100 30 | MHR EA | SPECIALIZED HAND MOWING RESPONSE FOR EROSION CONTROL |
| 4 | EA EA | TEMPORARY CRASH CUSHIONS RESET TEMPORARY CRASH CUSHIONS | 30 | ĿA | REST ONSE FOR EROSION CONTROL |
| 7 | | | | | |

Page: 34 of 62

0.4 ACR REFORESTATION

WALL ITEMS

1,595 SF SOLDIER PILE RETAINING WALLS

STRUCTURE ITEMS

| Lump Sum | LS | CONSTRUCTION, MAINTENANCE, & REMOVAL OF TEMP STRUCTURE AT STA ******************************** |
|----------|-----|--|
| Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE AT STATION ************************************ |
| 2 | EA | PDA TESTING |
| 2 | EA | PDA ASSISTANCE |
| Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA TION AT STATION ******* (18+55.00-L-) |
| 20,181 | SF | REINFORCED CONCRETE DECK SLAB |
| 16,345 | SF | GROOVING BRIDGE FLOORS |
| 191.2 | CY | CLASS A CONCRETE (BRIDGE) |
| Lump Sum | LS | BRIDGE APPROACH SLABS, STATION ************************************ |
| | | (18+55.00-L-) |
| 27,590 | LB | REINFORCING STEEL (BRIDGE) |
| 2,047.5 | LF | 45" PRESTRESSED CONCRETE GIR- DERS |
| 1,210 | LF | HP12X53 STEEL PILES |
| 1,650 | LF | PP ** X **** GALVANIZED STEEL PILES (24 X 0.625) |
| 30 | EA | PILE REDRIVES |
| 485 | TON | RIP RAP CLASS II (2'-0" THICK) |
| 540 | SY | FILTER FABRIC FOR DRAINAGE |
| Lump Sum | LS | ELASTOMERIC BEARINGS |
| Lump Sum | LS | EVAZOTE JOINT SEALS |
| 462.17 | LF | GENERIC STRUCTURE ITEM CLASSIC CONCRETE BRIDGE RAIL |

Page: 35 of 62

L120117 029

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

DIV OFFICE FAYETTEVILLE **CONTRACT ID: C202737** 33721.3.1 LENGTH = 0.209 MI

: COLUMBUS

GRADING, DRAINAGE, PAVING, AND STRUCTURES.

DBE GOAL 8.0% COMPLETION DATE: SEE SPECIAL PROVISIONS

BRIDGES #76 & 78 OVER GRISSETT SWAMP AND APPROACHES ON SR-1006.

ROADWAY ITEMS

| Lump Sum | LS | MOBILIZATION |
|----------|-----|--|
| Lump Sum | LS | CONSTRUCTION SURVEYING |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ |
| Lump Sum | LS | GRADING |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- BING |
| 400 | CY | UNDERCUT EXCAVATION |
| 400 | CY | SELECT GRANULAR MATERIAL |
| 400 | SY | FABRIC FOR SOIL STABILIZATION |
| 10 | TON | FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS |
| 30 | SY | FOUNDATION CONDITIONING FABRIC |
| 32 | LF | 15" DRAINAGE PIPE |
| 56 | LF | 15" RC PIPE CULVERTS, CLASS IV |
| 190 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B |
| 310 | TON | ASPHALT CONC SURFACE COURSE, TYPE SF9.5A |
| 30 | TON | ASPHALT BINDER FOR PLANT MIX |
| 22.4 | CY | SUBDRAIN EXCAVATION |
| 16.8 | CY | SUBDRAIN FINE AGGREGATE |
| 100 | LF | 6" PERFORATED SUBDRAIN PIPE |
| 1 | EA | SUBDRAIN PIPE OUTLETS |
| 6 | LF | 6" OUTLET PIPE (SUBDRAINS) |
| 4 | EA | MASONRY DRAINAGE STRUCTURES |
| 4 | EA | FRAME WITH TWO GRATES, STD 840.29 |
| 115 | LF | SHOULDER BERM GUTTER |
| 150 | LF | STEEL BM GUARDRAIL |
| 5 | EA | ADDITIONAL GUARDRAIL POSTS |
| 8 | EA | GUARDRAIL ANCHOR UNITS, TYPE III |
| 8 | EA | GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 2 | TON | RIP RAP, CLASS B |
| 385 | SY | FILTER FABRIC FOR DRAINAGE |
| | | |

435 SF WORK ZONE SIGNS (STATIONARY) 63 SF WORK ZONE SIGNS (BARRICADE MOUNTED) 64 LF BARRICADES (TYPE III)

2,210 LF THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) 2,210 LF THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) 14 EA PERMANENT RAISED PAVEMENT MARKERS 1,875 LF TEMPORARY SILT FENCE 160 TON STONE FOR EROSION CONTROL, CLASS A 5 TON STONE FOR EROSION CONTROL, CLASS B 45 TON SEDIMENT CONTROL STONE 1 ACR TEMPORARY MULCHING 50 LB SEED FOR TEMPORARY SEEDING 0.25 TON FERTILIZER FOR TEMPORARY SEED-

ING 200 LF TEMPORARY SLOPE DRAINS 4 EA INLET PROTECTION AT TEMPORARY SLOPE DRAINS

1,300 LF SAFETY FENCE 10 CY SILT EXCAVATION

0.5 ACR MOWING

140 SY

165 LF

2,400 SY MATTING FOR EROSION CONTROL

COIR FIBER WATTLE 1.5 ACR SEEDING & MULCHING

COIR FIBER MAT 220 LF 1/4" HARDWARE CLOTH

50 LB SEED FOR REPAIR SEEDING 0.25 TON FERTILIZER FOR REPAIR SEEDING 50 LB SEED FOR SUPPLEMENTAL SEEDING

| 0.75 | TON | FERTILIZER TOPDRESSING |
|------|-----|------------------------------|
| 25 | MHR | SPECIALIZED HAND MOWING |
| 20 | EA | RESPONSE FOR EROSION CONTROL |

STRUCTURE ITEMS

| Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE AT STATION ************************************ |
|----------|----|---|
| Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE AT STATION ************************************ |
| 2 | EA | PDA TESTING |
| Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- TION AT STATION ******** (12+65.75-L-) |
| Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVATION AT STATION ************************************ |
| 88.4 | CY | CLASS A CONCRETE (BRIDGE) |
| Lump Sum | LS | BRIDGE APPROACH SLABS, STATION ************************************ |
| | | (12+65.75-L-) |
| Lump Sum | LS | BRIDGE APPROACH SLABS, STATION ************************************ |
| | | (20+14.00-L-) |
| 11,274 | LB | REINFORCING STEEL (BRIDGE) |
| 1,215 | LF | HP14X73 STEEL PILES |
| 24 | EA | PILE REDRIVES |
| 240.5 | LF | VERTICAL CONCRETE BARRIER RAIL |
| Lump Sum | LS | ELASTOMERIC BEARINGS |
| 550 | LF | 3'-0" X 1'-9" PRESTRESSED CONC CORED SLABS |
| 770 | LF | 3'-0" X 2'-0" PRESTRESSED CONC CORED SLABS |
| 2,804 | SF | GENERIC STRUCTURE ITEM 18" STEEL SHEET PILES |

Page: 36 of 62

L120117 030

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202156 34762.3.4 DIV OFFICE GREENSBORO LENGTH = 0.748 MI

COUNTY : ORANGE

WIDENING, GRADING, DRAINAGE, PAVING, AND SIGNALS.

DBE GOAL 13.0% COMPLETION DATE: JUL 01 2013

NC-86 (S COLUMBIA ST) FROM SR-1906 (PUREFOY RD) TO SR-1902 (MANNING DR).

| | | ROADWAY ITEMS | 1.009 0.882 | CY CY | PIPE COLLARS PIPE PLUGS |
|--------------|----------|--|----------------|----------|--|
| | | | 40.3 | CY | FLOWABLE FILL |
| Lump Sum | LS | MOBILIZATION | 76 | EA | MASONRY DRAINAGE STRUCTURES |
| 3,500 | CY | SHALLOW UNDERCUT | 31.6 | LF | MASONRY DRAINAGE STRUCTURES |
| Lump Sum | LS | GRADING | 15 | EA | FRAME WITH TWO GRATES, STD |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- BING | 1 | EA | 840.16 FRAME WITH TWO GRATES, STD |
| 350 | CY | UNDERCUT EXCAVATION | | | 840.24 |
| 8,500 | TON | CLASS IV SUBGRADE STABILIZA- | 2 | EA | FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** |
| 1,720 | CY | TION DRAINAGE DITCH EXCAVATION | | | (E) |
| 375 | CY | SELECT GRANULAR MATERIAL | 26 | EA | FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** |
| 9,825 | SY | FABRIC FOR SOIL STABILIZATION | | | (F) |
| 100 | CY | GENERIC GRADING ITEM | 23 | EA | FRAME WITH GRATE & HOOD, STD |
| | | EXCAVATION AND STOCKPILING CONTAMINATED SOIL | | | 840.03, TYPE ** |
| 740 | TON | FOUNDATION CONDITIONING MATE- | 7 | EA | (G) FRAME WITH COVER, STD 840.54 |
| 740 | 1011 | RIAL, MINOR STRS | 120 | LF | **"X **" CONCRETE CURB |
| 1,680 | SY | FOUNDATION CONDITIONING FABRIC | | | (9" X 18") |
| 76 | LF | 15" RC PIPE CULVERTS, CLASS | 7,830 | LF | 2'-6" CONCRETE CURB & GUTTER |
| 36 | LF | III 30" RC PIPE CULVERTS, CLASS | 30 | LF | CONCRETE EXPRESSWAY GUTTER |
| 30 | LI | III | 3,410 | SY | 4" CONCRETE SIDEWALK |
| 172 | LF | 42" RC PIPE CULVERTS, CLASS | 180 70 | SY SY | 6" CONCRETE DRIVEWAY 5" MONOLITHIC CONCRETE ISLANDS |
| | | III | 70 | 51 | (KEYED IN) |
| 1,932 | LF | 15" RC PIPE CULVERTS, CLASS IV | 720 | SY | GENERIC PAVING ITEM |
| 358 1,420 | LF LF | 18" RC PIPE CULVERTS, CLASS IV 24" RC PIPE CULVERTS, CLASS IV | | | REMOVE AND RESET BRICK SIDE- WALK |
| 556 | LF | 30" RC PIPE CULVERTS, CLASS IV | 38 | EA | GENERIC PAVING ITEM |
| 16 | LF | 15" CS PIPE CULVERTS, 0.064" | 36 | LA | CONCRETE CURB RAMPS |
| | | THICK | 1 | EA | GENERIC PAVING ITEM |
| 52 | LF | 24" CS PIPE CULVERTS, 0.064" | 40 | | RETROFIT EXISTING CURB RAMP |
| 332 | LF | THICK 30" CS PIPE CULVERTS, 0.079" | 10 2,000 | EA LF | ADJUSTMENT OF MANHOLES GENERIC FENCING ITEM |
| 332 | LI | THICK | 2,000 | LF | TEMPORARY 72" CHAIN LINK FENCE |
| 2 | EA | **" CS PIPE ELBOWS, *****" | 360 | TON | RIP RAP, CLASS I |
| | | THICK | 20 | TON | RIP RAP, CLASS B |
| 2 | EA | (15", 0.064") **" CS PIPE ELBOWS, *****" | 3,230 | SY | FILTER FABRIC FOR DRAINAGE |
| ~ | Lit | THICK | 890 | LF | SUPPORTS, 3-LB STEEL U-CHANNEL |
| | | (24", 0.064") | 1 44 | EA EA | SIGN ERECTION, TYPE D SIGN ERECTION, TYPE E |
| 2 | EA | **" CS PIPE ELBOWS, *****" THICK | 5 | EA | SIGN ERECTION, TYPE F |
| | | (30", 0.079") | 61 | EA | DISPOSAL OF SIGN SYSTEM, U- |
| 40 | LF | **" WELDED STEEL PIPE, ****" | | | CHANNEL |
| | | THICK, GRADE ** IN SOIL (42", 0.109", B) | 675 | SF | WORK ZONE SIGNS (STATIONARY) |
| 40 | LF | **" WELDED STEEL PIPE, ****" | 890 61 | SF SF | WORK ZONE SIGNS (PORTABLE) WORK ZONE SIGNS (BARRICADE |
| | | THICK, GRADE ** NOT IN SOIL | 01 | эг | MOUNTED) |
| 22 | | (42", 0.109", B) | 2 | EA | FLASHING ARROW PANELS, TYPE C |
| 32 | LF | GENERIC PIPE ITEM TEMPORARY 12" PLASTIC | 4 | EA | CHANGEABLE MESSAGE SIGN |
| | | CORRUGATED PIPE | 58 | EA | DRUMS |
| 920.4 | LF | PIPE REMOVAL | 356 | LF | BARRICADES (TYPE III) |
| 40 | TON | #57 STONE | 660 | MD EA | FLAGGER TMIA |
| 500 | | STABILIZER AGGREGATE | 2,211 | LF | WATER FILLED BARRIER |
| 1,500 | SY | INCIDENTAL STONE BASE MILLING ASPHALT PAVEMENT, ***" | 3,887 | LF | RESET WATER FILLED BARRIER |
| 880 | 31 | DEPTH | 270 | EA | SKINNY DRUM |
| | | (1-1/2") | 7,380 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 4,210 | SY | MILLING ASPHALT PAVEMENT, ***" | | | LINES (4", 90 MILS) |
| | | TO ****** DEPTH (0" TO 3") | 11,560 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 280 | SY | INCIDENTAL MILLING | 500 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 4,210 | TON | ASPHALT CONC BASE COURSE, TYPE | | | LINES (8", 90 MILS) |
| 4.100 | mon. | B25.0B | 2,180 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 4,100 | ION | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0B | 33 | EA | LINES (24", 120 MILS) THERMOPLASTIC PAVEMENT MARKING |
| 3,120 | TON | ASPHALT CONC SURFACE COURSE, | 33 | LA | CHARACTER (120 MILS) |
| | | TYPE S9.5B | 142 | EA | THERMOPLASTIC PAVEMENT MARKING |
| 640 | | ASPHALT BINDER FOR PLANT MIX | a | | SYMBOL (90 MILS) |
| 405 | TON | ASPHALT PLANT MIX, PAVEMENT REPAIR | 63,200 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 112 | CY | SUBDRAIN EXCAVATION | 1,430 | LF | PAINT PAVEMENT MARKING LINES |
| 84 | CY | SUBDRAIN FINE AGGREGATE | | | (8") |
| 500 | LF | 6" PERFORATED SUBDRAIN PIPE | 2,650 | LF | PAINT PAVEMENT MARKING LINES |
| 1 | EA | SUBDRAIN PIPE OUTLETS | 57 | EA | (24") PAINT PAVEMENT MARKING CHARAC- |
| 6 | LF | 6" OUTLET PIPE (SUBDRAINS) | 3/ | ĿА | TER |
| 4.5 | CY | ENDWALLS | | | |

| 201 | EA | PAINT PAVEMENT MARKING SYMBOL |
|--------|----|-------------------------------|
| 10,900 | LF | REMOVAL OF PAVEMENT MARKING |
| | | LINES (4") |

- 100 LF REMOVAL OF PAVEMENT MARKING LINES (8")
- REMOVAL OF PAVEMENT MARKING 70 LF
- REMOVAL OF PAVEMENT MARKING 25 EA SYMBOLS & CHARACTERS
- 93 LF 2" WATER LINE
- 859 LF 8" WATER LINE
- 3,956 LF 12" WATER LINE
- 8" VALVE 11 EA
- 12" VALVE 23 EA
- 34 EA RELOCATE WATER METER
- 1 EA RECONNECT WATER METER
- 6 EΑ RELOCATE FIRE HYDRANT
- SANITARY SEWER CLEAN-OUT
- ABANDON 8" UTILITY PIPE 3,063 LF
- 1,580 ABANDON 12" UTILITY PIPE LF
- TRENCHLESS INSTALLATION OF 8" 100 LF
- 100 LF TRENCHLESS INSTALLATION OF 8" NOT IN SOIL
- 88 LF TRENCHLESS INSTALLATION OF 12" IN SOIL
- TRENCHLESS INSTALLATION OF 12" 88 LF NOT IN SOIL
- 8,000 TEMPORARY SILT FENCE
- STONE FOR EROSION CONTROL, TON 2,700
- CLASS A 400 TON STONE FOR EROSION CONTROL,
- CLASS B
- 1,200 TON SEDIMENT CONTROL STONE 9 TEMPORARY MULCHING ACR
- SEED FOR TEMPORARY SEEDING 300 LB
- 2.25 TON FERTILIZER FOR TEMPORARY SEED-
- 65 TEMPORARY SLOPE DRAINS
- 100 LF SAFETY FENCE
- 2.100 CY SILT EXCAVATION
- MATTING FOR EROSION CONTROL 13.250 SY
 - 15 SY COIR FIBER MAT
- PERMANENT SOIL REINFORCEMENT 3.225 SY
- MAT 4,700 LF 1/4" HARDWARE CLOTH
- COIR FIBER BAFFLE 1.200 LF
 - 1 EA **" SKIMMER (2")
- 9 ACR SEEDING & MULCHING
 - 9 ACR MOWING
- 150 LB SEED FOR REPAIR SEEDING
- 0.25 TON FERTILIZER FOR REPAIR SEEDING
- 225 SEED FOR SUPPLEMENTAL SEEDING
- FERTILIZER TOPDRESSING 6.25 TON
- 10 MHR SPECIALIZED HAND MOWING
- 150 RESPONSE FOR EROSION CONTROL EA
- PEDESTRIAN SIGNAL HEAD (**", 8 EΑ * SECTION)
 - (16", 1 SECTION W/ COUNTDOWN)
- 3.310 LF SIGNAL CABLE
 - 9 VEHICLE SIGNAL HEAD (12", 3 EA
 - SECTION) VEHICLE SIGNAL HEAD (12", 4 2 EA
 - SECTION) VEHICLE SIGNAL HEAD (12", 5
 - EA 3
- 250 LF MESSENGER CABLE (1/4")
- MESSENGER CABLE (3/8") 420 LF
- UNPAVED TRENCHING (********) 375 LF
- 30 LF UNPAVED TRENCHING (********)
- (3, 2")JUNCTION BOX (STANDARD SIZE)
- 7 EA
- 4 EA WOOD POLE GUY ASSEMBLY 9 EA
- 2 1" RISER WITH WEATHERHEAD EA
- 2" RISER WITH WEATHERHEAD 16 EA
- 1 EA 2" RISER WITH HEAT SHRINK TUBING
- 3,835 INDUCTIVE LOOP SAWCUT LF
- LEAD-IN CABLE (*************) 7,905 LF
 - EA INTERCONNECT CENTER
 - CABLE TRANSFER 2 EA
 - 3 EA SIGN FOR SIGNALS
 - CONTROLLER WITH CABINET (TYPE 1 EA 2070L, POLE MOUNTED)
 - 7 DETECTOR CARD (TYPE 2070L) EA

GENERIC SIGNAL ITEM 16 EA

APS DETECTOR STATIONS GENERIC SIGNAL ITEM

CENTRAL CONTROL UNITS FOR APS

Page: 37 of 62

DETECTOR STATIONS

16 EA GENERIC SIGNAL ITEM PUSH BUTTON POSTS

Page: 38 of 62

L120117 031

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202652 34924.3.1 DIV OFFICE GREENSBORO LENGTH = 6.052 MI

COUNTY : ROCKINGHAM

WIDENING, GRADING, DRAINAGE, PAVING, RET WALL, & STRUCTURES.

DBE GOAL 13.0% COMPLETION DATE: OCT 01 2015

US-29 BUS (FREEWAY DR) FROM SR-2670 (S SCALES ST) TO NC-14 IN REIDSVILLE.

| | | ROADWAY ITEMS | 29 | EA | **" CS PIPE ELBOWS, *****" THICK (15") |
|---------------------|-----------|--|----------------|------------|---|
| Lump Sum | LS | MOBILIZATION | 15 | EA | **" CS PIPE ELBOWS, *****" THICK |
| Lump Sum | LS | CONSTRUCTION SURVEYING | | | (18") |
| Lump Sum 2 | LS ACR | CLEARING & GRUBBING ACRE(S) SUPPLEMENTARY CLEARING & GRUB- | 6 | EA | **" CS PIPE ELBOWS, *****" THICK |
| 247 200 | CY | BING | 138 | LF | (24") **" WELDED STEEL PIPE, ****" |
| 347,300 Lump Sum | LS | UNCLASSIFIED EXCAVATION REINFORCED BRIDGE APPROACH | 130 | LI | THICK, GRADE ** IN SOIL |
| | | FILL, STATION ************************************ | 88 | LF | 36" WSP, 0.5" THICK, GRADE B **" WELDED STEEL PIPE, ****" THICK, GRADE ** IN SOIL |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | 82 | LF | 42" WSP, 0.625" THICK, GRADE B **" WELDED STEEL PIPE. ****" |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | | | THICK, GRADE ** IN SOIL 48" WSP, 0.625" THICK, GRADE B |
| Lump Sum | LS | (203+08.04 -L- EBL) REINFORCED BRIDGE APPROACH | 30 | LF | **" WELDED STEEL PIPE, ****" THICK, GRADE ** NOT IN SOIL |
| Lump Sum | Lo | FILL, STATION ************************************ | 20 | LF | 36" WSP, 0.5" THICK, GRADE B **" WELDED STEEL PIPE, ****" |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | | | THICK, GRADE ** NOT IN SOIL 42" WSP, 0.625" THICK, GRADE B |
| | | (24+49.6 -Y10-) | 18 | LF | **" WELDED STEEL PIPE, ****" THICK, GRADE ** NOT IN SOIL |
| 5,905 | CY | UNDERCUT EXCAVATION | | | 48" WSP, 0.625" THICK, GRADE B |
| 1,970 | CY | SHALLOW UNDERCUT | 116 | LF | GENERIC PIPE ITEM |
| 3,750 | TON | CLASS IV SUBGRADE STABILIZA- TION | 400 | LE | 36" RC PIPE CULVERTS, CLASS V |
| 256,000 | CY | BORROW EXCAVATION | 408 | LF | GENERIC PIPE ITEM 54" WELDED STEEL PIPE LINER |
| 3,124 1,145 | CY LF | DRAINAGE DITCH EXCAVATION BERM DITCH CONSTRUCTION | 372 | LF | GENERIC PIPE ITEM 60" RC PIPE CULVERTS, CLASS V |
| 98,900 | SY | REMOVAL OF EXISTING ASPHALT PAVEMENT | 168 | LF | GENERIC PIPE ITEM 60" WELDED STEEL PIPE LINER |
| 6,200 | SY | BREAKING OF EXISTING ASPHALT PAVEMENT | 128 | LF | GENERIC PIPE ITEM 66" RC PIPE CULVERTS, CLASS V |
| 5,000 | CY | SELECT GRANULAR MATERIAL | 8,376 | LF | PIPE REMOVAL |
| 10,000 | SY | FABRIC FOR SOIL STABILIZATION | Lump Sum | LS | FINE GRADING |
| 13,165 | SF EA | TEMPORARY SHORING GENERIC GRADING ITEM | 1,000 | TON | STABILIZER AGGREGATE |
| 1 | EA | HAZARDOUS SPILL BASIN | 15,900 | TON TON | AGGREGATE BASE COURSE INCIDENTAL STONE BASE |
| 7,390 | TON | FOUNDATION CONDITIONING MATE- | 5,000 5,750 | GAL | PRIME COAT |
| 18,460 | SY | RIAL, MINOR STRS FOUNDATION CONDITIONING FABRIC | 2,000 | SY | MILLING ASPHALT PAVEMENT, ***" TO ******" DEPTH |
| 12 | LF | **" SIDE DRAIN PIPE (12") | 7,700 | SY | (0" TO 1-1/2") MILLING ASPHALT PAVEMENT, ***" |
| 936 | LF | **" SIDE DRAIN PIPE (30") | | | TO *****" DEPTH (0" TO 3") |
| 628 | LF | **" SIDE DRAIN PIPE (36") | 700 20,200 | SY TON | INCIDENTAL MILLING ASPHALT CONC BASE COURSE, TYPE |
| 120 | LF | **" SIDE DRAIN PIPE (42") | | | B25.0B |
| 28 | LF | **" SIDE DRAIN PIPE (48") | 80,750 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0C |
| 5,036 | LF | 15" SIDE DRAIN PIPE | 10,650 | ION | ASPHALT CONC INTERMEDIATE COURSE, TYPE I19.0B |
| 2,404 | LF | 18" SIDE DRAIN PIPE | 52,700 | TON | ASPHALT CONC INTERMEDIATE |
| 1,616 2,668 | LF LF | 24" SIDE DRAIN PIPE 15" RC PIPE CULVERTS, CLASS | 14,600 | TON | COURSE, TYPE 119.0C ASPHALT CONC SURFACE COURSE, |
| 4,084 | LF | III 18" RC PIPE CULVERTS, CLASS | | | TYPE S9.5B ASPHALT CONC SURFACE COURSE, |
| 2,292 | LF | III 24" RC PIPE CULVERTS, CLASS | 4,200 | TON | TYPE S9.5C ASPHALT CONC SURFACE COURSE, |
| 1,524 | LF | III 30" RC PIPE CULVERTS, CLASS | | TON | TYPE SF9.5A ASPHALT BINDER FOR PLANT MIX |
| 92 | LF | III 36" RC PIPE CULVERTS, CLASS III | 1,775 | TON | ASPHALT PLANT MIX, PAVEMENT REPAIR |
| 80 | LF | 42" RC PIPE CULVERTS, CLASS III | 330 896 | EA CY | RIGHT OF WAY MARKERS SUBDRAIN EXCAVATION |
| 144 | LF | 54" RC PIPE CULVERTS, CLASS III | 4,000 | CY LF | SUBDRAIN FINE AGGREGATE 6" PERFORATED SUBDRAIN PIPE |
| 164 | LF | 66" RC PIPE CULVERTS, CLASS III | 8 48 | EA LF | SUBDRAIN PIPE OUTLETS 6" OUTLET PIPE (SUBDRAINS) |
| 26,172 | LF | 15" RC PIPE CULVERTS, CLASS IV | 75 | EA | TEMPORARY STEEL PLATE COVERS |
| 1,632 | LF | 18" RC PIPE CULVERTS, CLASS IV | | | FOR MASONRY DRAINAGE STRUCTURE |
| 2,616 | LF | 24" RC PIPE CULVERTS, CLASS IV | 16 | CY | ENDWALLS |
| 1,104 | LF | 30" RC PIPE CULVERTS, CLASS IV | 42 | CY | REINFORCED ENDWALLS |
| 912 | LF | 15" CS PIPE CULVERTS, 0.064" THICK | 30 | CY | PIPE COLLARS |
| 100 | LF | 24" CS PIPE CULVERTS, 0.064" | 1 40 | CY CY | PIPE PLUGS FLOWABLE FILL |
| | | THICK | 40 | CI | I DO MADLE I ILL |

| | | | 1,900 | SY | GENERIC EROSION CONTROL ITEM |
|-----------------|----------|--|----------------|----------|--|
| | | | 12 | CY | REINFORCED SOIL SLOPES REINFORCED CONCRETE SIGN FOUN- |
| 586 | EA | MASONRY DRAINAGE STRUCTURES | 3 | CY | DATIONS PLAIN CONCRETE SIGN FOUNDA- |
| 46 213 | CY LF | MASONRY DRAINAGE STRUCTURES MASONRY DRAINAGE STRUCTURES | 40 | CIV. | TIONS |
| 2 | EA | FRAME WITH GRATE, STD 840.24 | 48 2,874 | CY LB | OVERHEAD FOOTING SUPPORTS, BREAKAWAY STEEL BEAM |
| 71 | EA | FRAME WITH TWO GRATES, STD | 7,577 | LB | SUPPORTS, SIMPLE STEEL BEAM |
| 10 | EA | 840.16 FRAME WITH TWO GRATES, STD | 7,875 | LF | SUPPORTS, 3-LB STEEL U-CHANNEL |
| 10 | LA | 840.22 | Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- TURE AT STA ***** |
| 83 | EA | FRAME WITH TWO GRATES, STD 840.24 | | | (A ON US-29 NBL) |
| 40 | EA | FRAME WITH TWO GRATES, STD 840.29 | Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- TURE AT STA ****** (B ON US-29 SBL) |
| 31 | EA | FRAME WITH GRATE & HOOD, STD | 33 | EA | SIGN ERECTION, TYPE D |
| | | 840.03, TYPE ** (E) | 143 | EA | SIGN ERECTION, TYPE E |
| 149 | EA | FRAME WITH GRATE & HOOD, STD | 89 | EA | SIGN ERECTION, TYPE F |
| | | 840.03, TYPE ** (F) | 21 | EA | SIGN ERECTION, TYPE *** (GROUND MOUNTED) |
| 146 | EA | FRAME WITH GRATE & HOOD, STD | 2 | EA | (A) SIGN ERECTION, RELOCATE, TYPE |
| | | 840.03, TYPE ** (G) | | | **** (GROUND MOUNTED) |
| 30 | EA | FRAME WITH COVER, STD 840.54 | 3 | EA | (D) SIGN ERECTION, RELOCATE, TYPE |
| 9 | EA | STEEL FRAME WITH TWO GRATES, STD 840.37 | | | **** (GROUND MOUNTED) (E) |
| 56 | EA | CONCRETE TRANSITIONAL SECTION FOR CATCH BASIN | 1 | EA | DISPOSAL OF SIGN SYSTEM, STEEL |
| 35 | EA | CONCRETE TRANSITIONAL SECTION | 287 | EA | BEAM DISPOSAL OF SIGN SYSTEM, U- |
| 1 | EA | FOR DROP INLETS **" SLUICE GATE | | | CHANNEL |
| • | Lil | (24") | 5 | EA | DISPOSAL OF SUPPORT IL CHANNEL |
| 32,100 | LF | 1'-6" CONCRETE CURB & GUTTER | 12 7 | EA EA | DISPOSAL OF SUPPORT, U-CHANNEL DISPOSAL OF SIGN, A OR B |
| 51,300 1,300 | LF LF | 2'-6" CONCRETE CURB & GUTTER | • | | (GROUND MOUNTED) |
| 3,160 | LF | SHOULDER BERM GUTTER CONCRETE EXPRESSWAY GUTTER | 10 | EA | DISPOSAL OF SIGN, D, E OR F |
| 5,400 | SY | 4" CONCRETE SIDEWALK | 2,982 1,895 | SF SF | WORK ZONE SIGNS (STATIONARY) WORK ZONE SIGNS (PORTABLE) |
| 1,800 | SY | 6" CONCRETE DRIVEWAY | 811 | SF | WORK ZONE SIGNS (FORTABLE) WORK ZONE SIGNS (BARRICADE |
| 240 | SY | 4" CONCRETE PAVED DITCH | 011 | 51 | MOUNTED) |
| 8,800 | SY | 5" MONOLITHIC CONCRETE ISLANDS (KEYED IN) | 4 | EA | FLASHING ARROW PANELS, TYPE C |
| 700 | LF | PRECAST REINFORCED CONCRETE | 4 1,644 | EA EA | CHANGEABLE MESSAGE SIGN DRUMS |
| 2.4 | E.4 | BARRIER, SINGLE FACED | 200 | EA | CONES |
| 24 | EA | GENERIC PAVING ITEM CONCRETE CURB RAMP | 568 | LF | BARRICADES (TYPE III) |
| 27 | EA | ADJUSTMENT OF MANHOLES | 16,000 | HR | FLAGGER |
| 21 | EA | ADJUSTMENT OF METER BOXES OR VALVE BOXES | 10 6 | EA EA | TEMPORARY CRASH CUSHIONS RESET TEMPORARY CRASH CUSHIONS |
| 1 | EA | CONVERT EXISTING CATCH BASIN | 4 | EA | TMIA |
| | | TO JUNCTION BOX | 2,060 | LF | PORTABLE CONCRETE BARRIER |
| 1 | EA | CONVERT EXISTING DROP INLET TO JUNCTION BOX | 810 | LF | RESET PORTABLE CONCRETE BAR- RIER |
| 2 | EA | CONVERT EXISTING DROP INLET TO CATCH BASIN | 10,000 | LF | WATER FILLED BARRIER |
| 2 | EA | IMPACT ATTENUATOR UNIT, TYPE | 9,925 340 | LF EA | RESET WATER FILLED BARRIER SKINNY DRUM |
| | | 350 | 3,400 | EA | TEMPORARY RAISED PAVEMENT |
| 13,875 225 | LF LF | STEEL BM GUARDRAIL STEEL BM GUARDRAIL, SHOP | 100.110 | | MARKERS |
| | | CURVED | 108,440 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 2 | EA | STEEL BM GUARDRAIL TERMINAL SECTIONS | 58,209 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 40 | EA | ADDITIONAL GUARDRAIL POSTS | 1,300 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 30 | EA | GUARDRAIL ANCHOR UNITS, TYPE CAT-1 | 254 | LF | LINES (8", 90 MILS) THERMOPLASTIC PAVEMENT MARKING |
| 4 | EA | GUARDRAIL ANCHOR UNITS, TYPE III | | | LINES (8", 120 MILS) |
| 42 | EA | GUARDRAIL ANCHOR UNITS, TYPE | 5,400 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (12", 90 MILS) |
| 8 | EA | 350 GUARDRAIL ANCHOR UNITS, TYPE | 500 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 0 | LA | M-350 | 5 | EA | LINES (24", 120 MILS) THERMOPLASTIC PAVEMENT MARKING |
| 12 | EA | GUARDRAIL ANCHOR UNITS, TYPE B-77 | 107 | г. | CHARACTER (120 MILS) |
| 4,900 | LF | REMOVE EXISTING GUARDRAIL | 437 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 750 | LF | TEMPORARY STEEL BM GUARDRAIL | 1,185 | LF | COLD APPLIED PLASTIC PAVEMENT |
| 1 | EA | GUARDRAIL ANCHOR UNITS, TYPE ******** TEMPORARY | | | MARKING LINES, TYPE ** (4") (II) |
| | | (CAT-1) | 2,217 | LF | COLD APPLIED PLASTIC PAVEMENT |
| 3 | EA | GUARDRAIL ANCHOR UNITS, TYPE 350 TEMPORARY | | | MARKING LINES, TYPE ** (4") (IV) |
| 4 | EA | CABLE GUIDERAIL ANCHOR UNITS | 200 | LF | COLD APPLIED PLASTIC PAVEMENT MARKING LINES, TYPE ** (8") |
| 975 | LF | GENERIC GUARDRAIL ITEM REMOVE CABLE GUIDERAIL | | | (II) |
| 21,140 | LF | WOVEN WIRE FENCE, 47" FABRIC | 200 | LF | COLD APPLIED PLASTIC PAVEMENT MARKING LINES, TYPE ** (8") |
| 1,270 | EA | 4" TIMBER FENCE POSTS, 7'-6" LONG | | | (IV) |
| 470 | EA | 5" TIMBER FENCE POSTS, 8'-0" | 4 | EA | COLD APPLIED PLASTIC PAVEMENT MARKING SYMBOL, TYPE ** |
| 919 | TON | LONG RIP RAP, CLASS I | | | (IV) |
| 231 | | RIP RAP, CLASS II | 760,532 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 1,501 | TON | RIP RAP, CLASS B | 17,658 | LF | PAINT PAVEMENT MARKING LINES |
| 19,192 9 | SY EA | FILTER FABRIC FOR DRAINAGE PREFORMED SCOUR HOLES WITH | 5,864 | LF | (8") PAINT PAVEMENT MARKING LINES |
| | 1 | LEVEL SPREADER APRON | 3,004 | 1-1 | (24") |
| | | | | | |

Page: 40 of 62

| | | | 380 19,251 | SY SY | COIR FIBER MAT PERMANENT SOIL REINFORCEMENT MAT |
|-----------------|-----------|--|----------------|------------|--|
| 72 | EA | PAINT PAVEMENT MARKING CHARACTER | 20,000 450 | LF LF | 1/4" HARDWARE CLOTH **" TEMPORARY PIPE |
| 1,352 63,510 | EA LF | PAINT PAVEMENT MARKING SYMBOL REMOVAL OF PAVEMENT MARKING | 185 | CY | (15") STILLING BASINS |
| 1,464 | LF | LINES (4") REMOVAL OF PAVEMENT MARKING | 6,000 6,800 | LF LB | COIR FIBER WATTLE POLYACRYLAMIDE (PAM) |
| 1,343 | LF | LINES (8") REMOVAL OF PAVEMENT MARKING LINES (24") | 7,000 27 | LF EA | COIR FIBER BAFFLE **" SKIMMER (1-1/2") |
| 36 | EA | REMOVAL OF PAVEMENT MARKING SYMBOLS & CHARACTERS | 1 | EA | **" SKIMMER (2") |
| 9 | EA | PERMANENT RAISED PAVEMENT MARKERS | 150 150 | ACR ACR | SEEDING & MULCHING MOWING |
| 977 Lump Sum | EA LS | SNOWPLOWABLE PAVEMENT MARKERS PORTABLE LIGHTING | 2,200 6.25 | LB TON | SEED FOR REPAIR SEEDING FERTILIZER FOR REPAIR SEEDING |
| 225 | LF | **" WATER LINE (1") | 3,450 103.5 | LB TON | SEED FOR SUPPLEMENTAL SEEDING FERTILIZER TOPDRESSING |
| 1,745 2,113 | LF LF | 6" WATER LINE 8" WATER LINE | 500 | LF | IMPERVIOUS DIKE |
| 9,466 | LF | 12" WATER LINE | 100 125 | MHR EA | SPECIALIZED HAND MOWING RESPONSE FOR EROSION CONTROL |
| 632 | LF | 16" WATER LINE | 10 | | REFORESTATION |
| 3 | EA | 6" VALVE | 2 | EA | PEDESTRIAN SIGNAL HEAD (**", |
| 9 | EA | 8" VALVE 12" VALVE | | | ** SECTION) (16", 1 SECTION W/ COUNTDOWN) |
| 10 1 | EA EA | 16" VALVE | 18,270 | LF | SIGNAL CABLE |
| 1 | EA | 12" TAPPING VALVE | 4 | EA | VEHICLE SIGNAL HEAD (12", 1 |
| 2 | EA | 2" AIR RELEASE VALVE | 122 | Б. | SECTION) |
| 4 | EA | 4" AIR RELEASE VALVE | 132 | EA | VEHICLE SIGNAL HEAD (12", 3 SECTION) |
| 50 | EA | RELOCATE WATER METER | 32 | EA | VEHICLE SIGNAL HEAD (12", 4 |
| 16 26 | EA EA | RECONNECT WATER METER RELOCATE FIRE HYDRANT | | | SECTION) |
| 97 | LF | 4" SANITARY GRAVITY SEWER | 23 | EA | VEHICLE SIGNAL HEAD (12", 5 SECTION) |
| 40 | LF | 6" SANITARY GRAVITY SEWER | 4 | EA | RELOCATE EXISTING VEHICLE SIG- |
| 2,405 | LF | 8" SANITARY GRAVITY SEWER | | | NAL HEAD |
| 288 | LF | 16" SANITARY GRAVITY SEWER | 600 | LF | MESSENGER CABLE (1/4") |
| 2,224 | LF LF | 24" SANITARY GRAVITY SEWER **" FORCE MAIN SEWER | 9,800 | LF | MESSENGER CABLE (3/8") |
| 6,455 | LF | (18") | 500 | LF | PAVED TRENCHING (********) (1, 2") |
| 1,055 | LF | **" FORCE MAIN SEWER (2-1/2") | 7,400 | LF | UNPAVED TRENCHING (********) (1, 2") |
| 20 | LF | 2" FORCE MAIN SEWER | 131 | EA | JUNCTION BOX (STANDARD SIZE) |
| 70 | LF | 4" FORCE MAIN SEWER | 25 | EA | WOOD POLE |
| 2,074 | LF EA | 8" FORCE MAIN SEWER SANITARY SEWER CLEAN-OUT | 54 | EA EA | GUY ASSEMBLY 1" RISER WITH WEATHERHEAD |
| 18 | EA | 4' DIA UTILITY MANHOLE | 31 | EA | 2" RISER WITH WEATHERHEAD |
| 10 | EA | 5' DIA UTILITY MANHOLE | 1 | EA | HEAT SHRINK TUBING RETROFIT |
| 2 | EA | 6' DIA UTILITY MANHOLE | | | KIT |
| 80 | LF | UTILITY MANHOLE WALL, 4' DIA | 6 | EA | 2" RISER WITH HEAT SHRINK TUBING |
| 56 17 | LF LF | UTILITY MANHOLE WALL, 5' DIA UTILITY MANHOLE WALL, 6' DIA | 16,090 | LF | INDUCTIVE LOOP SAWCUT |
| 362 | LF | ABANDON 8" UTILITY PIPE | 38,370 | LF | LEAD-IN CABLE (**********) |
| 283 | LF | ABANDON 16" UTILITY PIPE | 15 | EA | (14-2) SITE SURVEY |
| 8,473 | LF | ABANDON 18" UTILITY PIPE | 15 | EA EA | LUMINAIRE ARM FOR VIDEO SYSTEM |
| 5 | EA | REMOVE WATER METER | 36 | EA | CAMERA WITHOUT INTERNAL LOOP |
| 26 4 | EA EA | ABANDON UTILITY MANHOLE REMOVE UTILITY MANHOLE | | | EMULATOR PROCESSING UNIT |
| 60 | LF | **" ENCASEMENT PIPE | 6 | EA | EXTERNAL LOOP EMULATOR PRO- CESSING UNIT |
| 180 | LF | (42") 30" ENCASEMENT PIPE | 34 | EA | RELOCATE CAMERA SENSOR UNIT |
| 30 | LF | TRENCHLESS INSTALLATION OF **" | 6 | EA | 900MHZ WIRELESS RADIO SYSTEM METAL STRAIN SIGNAL POLE |
| | | IN SOIL | 52 52 | EA EA | SOIL TEST |
| 30 | LF | (42") TRENCHLESS INSTALLATION OF **" | 364 | CY | DRILLED PIER FOUNDATION |
| 50 | 1-1 | NOT IN SOIL | 1 | EA | SIGNAL PEDESTAL WITH FOUNDA- |
| 90 | LF | (42") TRENCHLESS INSTALLATION OF 30" | 20 | EA | TION SIGN FOR SIGNALS |
| 90 | LI | IN SOIL | 3 | EA | RELOCATE EXISTING SIGN |
| 90 | LF | TRENCHLESS INSTALLATION OF 30" | 12 | EA | SIGNAL CABINET FOUNDATION |
| Lump Sum | LS | NOT IN SOIL SANITARY SEWER PUMP STATION | 12 | EA | CONTROLLER WITH CABINET (TYPE 2070L, BASE MOUNTED) |
| Lump Sum 1 | EA | GENERIC UTILITY ITEM | 2 | EA | CONTROLLER WITH CABINET (TYPE |
| | | ABANDON EXISTING SANITARY SEW- | | | 2070L, POLE MOUNTED) |
| 20,000 | LF | ER PUMP STATION TEMPORARY SILT FENCE | 85 | EA | DETECTOR CARD (TYPE 2070L) |
| 14,800 | TON | STONE FOR EROSION CONTROL, | 12 | EA EA | CABINET BASE EXTENDER BEACON CONTROLLER ASSEMBLY & |
| 12,700 | TON | CLASS A STONE FOR EROSION CONTROL, | 1 | LA | CABINET (*******) (F1) |
| | | CLASS B | 2 | EA | GENERIC SIGNAL ITEM |
| 12,000 | TON | SEDIMENT CONTROL STONE | | | FURNISH WIRELESS LIGHTNING AR- RESTORS |
| 150 4,850 | ACR LB | TEMPORARY MULCHING SEED FOR TEMPORARY SEEDING | 2 | EA | GENERIC SIGNAL ITEM |
| 21 | TON | FERTILIZER FOR TEMPORARY SEED- | - | - | FURNISH WIRELESS RADIO MODEMS |
| | | ING | | | |
| 10,000 | LF | TEMPORARY SLOPE DRAINS | | | |
| 150 | EA | INLET PROTECTION AT TEMPORARY SLOPE DRAINS | | | |
| 100 | LF | SAFETY FENCE | | | |
| 30,600 | CY | SILT EXCAVATION | | | |
| 130,000 | SY | MATTING FOR EROSION CONTROL | | | |
| | | | | | |

Page: 41 of 62

CULVERT ITEMS

Lump Sum LS CULVERT EXCAVATION, STA ****** (225+82.25-L-) CULVERT EXCAVATION, STA ****** Lump Sum LS (250+30.41-L-) CULVERT EXCAVATION, STA ***** Lump Sum LS Lump Sum LS CULVERT EXCAVATION, STA ***** (324+72.83-L-) FOUNDATION CONDITIONING MATER-279 TON IAL, BOX CULVERT 575.1 CY CLASS A CONCRETE (CULVERT) 79,200 LB REINFORCING STEEL (CULVERT)

WALL ITEMS

5,050 SF MSE RETAINING WALLS 5,465 SF SOIL NAIL RETAINING WALLS 1,410 SF SOLDIER PILE RETAINING WALLS 4 EA SOIL NAIL VERIFICATION TESTS 12 EA SOIL NAIL PROOF TESTS

STRUCTURE ITEMS

Lump Sum LS REMOVAL OF EXISTING STRUCTURE AT STATION (113+47.50-L-) Lump Sum LS REMOVAL OF EXISTING STRUCTURE AT STATION *** (203+04.30-L-RT) REMOVAL OF EXISTING STRUCTURE Lump Sum LS AT STATION ******* (262+51.60-L-) Lump Sum LS REMOVAL OF EXISTING STRUCTURE AT STATION **** (303+93.67-L-) Lump Sum LS FOUNDATION EXCAVATION FOR BENT * AT STATION ** (1,113+47.50-L-) Lump Sum LS FOUNDATION EXCAVATION FOR BENT ** AT STATION **** (1.262+51.60-L-) 110 LF PILE EXCAVATION IN SOIL PILE EXCAVATION NOT IN SOIL 205 LF 52.25 LF 3'-6" DIA DRILLED PIERS IN SOIL 3'-6" DIA DRILLED PIERS NOT IN 28 LF SOIL SID INSPECTION EA REINFORCED CONCRETE DECK SLAB 42,112 SF 42,377 GROOVING BRIDGE FLOORS SF CLASS A CONCRETE (BRIDGE) 688 CYLump Sum LS BRIDGE APPROACH SLABS, STATION (113+47.50-L-) Lump Sum LS BRIDGE APPROACH SLABS, STATION (203+04.30-L-LT) BRIDGE APPROACH SLABS, STATION Lump Sum LS (203+04.30-L-RT) Lump Sum LS BRIDGE APPROACH SLABS, STATION Lump Sum LS BRIDGE APPROACH SLABS, STATION (303+93.67-L-) 106,831 LB REINFORCING STEEL (BRIDGE) SPIRAL COLUMN REINFORCING 5,362 LB STEEL (BRIDGE) 4,448.62 MODIFIED 63" PRESTRESSED CONC LF 5,800 LF HP12X53 STEEL PILES 845 LF HP14X73 STEEL PILES 342.46 LF TWO BAR METAL RAIL THREE BAR METAL RAIL 533.37 LF CONCRETE BARRIER RAIL 662.59 LF 188.33 LF 1'-**"X *****" CONCRETE PARA-PET (1'-2" X 2'-6") 169.31 LF 1'-**"X *****" CONCRETE PARA-PET (1'-2" X 2'-8") 1,819 SY 4" SLOPE PROTECTION Lump Sum LS ELASTOMERIC BEARINGS

EVAZOTE JOINT SEALS

EXPANSION JOINT SEALS

Lump Sum LS

Lump Sum LS

EA GENERIC STRUCTURE ITEM CSL TESTING

Page: 42 of 62

L120117 032

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202806 45438.3.15 DIV OFFICE GREENSBORO LENGTH = 0.000 MI

COUNTY : GUILFORD

DECK REHABILITATION.

DBE GOAL 4.0% COMPLETION DATE: NOV 15 2012

BRIDGES # 1, 136, AND 470 ON SR-2254 (WENDOVER AVE), #287, 217, 259, AND 274 ON US-220 (WENDOVER AVE).

| Lump Sum | LS | MOBILIZATION |
|----------|-----|--|
| 650 | TON | ASPHALT CONC SURFACE COURSE, |
| | | TYPE S9.5B |
| 39 | TON | ASPHALT BINDER FOR PLANT MIX |
| 537 | LF | 2'-6" CONCRETE CURB & GUTTER |
| 128 | SF | WORK ZONE SIGNS (STATIONARY) |
| 811 | SF | WORK ZONE SIGNS (PORTABLE) |
| 24 | SF | WORK ZONE SIGNS (BARRICADE MOUNTED) |
| 5 | EA | FLASHING ARROW PANELS, TYPE C |
| 4 | EA | CHANGEABLE MESSAGE SIGN |
| 500 | EA | DRUMS |
| 40 | LF | BARRICADES (TYPE III) |
| 2 | EA | TMIA |
| 22,125 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 61,613 | SF | GROOVING BRIDGE FLOORS |
| Lump Sum | LS | EVAZOTE JOINT SEALS |
| 424.7 | CY | GENERIC STRUCTURE ITEM LATEX MOD CONC OVERLAY - VERY EARLY STRENGTH |
| 7,566.2 | SY | GENERIC STRUCTURE ITEM HYDRO-DEMOLITION OF BRIDGE DECK |
| 7,566.2 | SY | GENERIC STRUCTURE ITEM PLACING & FINISHING LATEX MOD CONC OVERLAY - VERY EARLY STRENGTH |
| 13,728.6 | SY | GENERIC STRUCTURE ITEM SCARIFYING BRIDGE DECK |

Page: 43 of 62

L120117 033

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202920 30001.38 DIV OFFICE ABERDEEN LENGTH = 8.274 MI

COUNTY : MOORE, LEE

MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION.

MBE GOAL 4.0% WBE 5.0% COMPLETION DATE: AUG 31 2012

NC-24/27 FROM NC-22 TO SR-1261 AND 11 SECTIONS OF SECONDARY ROADS.

| Lump Sum | LS | MOBILIZATION |
|----------|-----|--|
| 229 | CY | BORROW EXCAVATION |
| 650 | SY | REMOVAL OF EXISTING ASPHALT PAVEMENT |
| 3,980 | TON | AGGREGATE BASE COURSE |
| 8.96 | MSY | CONDITIONING EXISTING BASE |
| 285 | TON | INCIDENTAL STONE BASE |
| 11.5 | SMI | SHOULDER RECONSTRUCTION |
| 17,300 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (1-1/2") |
| 850 | SY | MILLING ASPHALT PAVEMENT, ***" TO ******" (0" TO 2") |
| 2,645 | SY | INCIDENTAL MILLING |
| 200 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B |
| 7,535 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 7,287 | TON | ASPHALT CONC SURFACE COURSE, TYPE SF9.5A |
| 949 | TON | ASPHALT BINDER FOR PLANT MIX |
| 820 | TON | PATCHING EXISTING PAVEMENT |
| 450 | TON | GENERIC PAVING ITEM JOINT REPAIR |
| 24 | EA | ADJUSTMENT OF MANHOLES |
| 12 | EA | ADJUSTMENT OF METER BOXES OR VALVE BOXES |
| Lump Sum | LS | TEMPORARY TRAFFIC CONTROL |
| 40,000 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 28,230 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 980 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 120 MILS) |
| 4 | EA | THERMOPLASTIC PAVEMENT MARKING CHARACTER (120 MILS) |
| 16 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 68,750 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 250 | EA | PERMANENT RAISED PAVEMENT MARKERS |
| 675 | LF | TEMPORARY SILT FENCE |
| 95 | TON | STONE FOR EROSION CONTROL, CLASS B |
| 95 | TON | SEDIMENT CONTROL STONE |
| 150 | LF | WATTLE |
| 8.35 | ACR | SEEDING & MULCHING |

Page: 44 of 62

L120117 034

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202745 40278.3.1 DIV OFFICE WINSTON-SALEM LENGTH = 4.163 MI

COUNTY : FORSYTH

GRADING, DRAINAGE, PAVING, SIGNALS, AND STRUCTURES.

DBE GOAL 14.0% COMPLETION DATE: SEP 15 2015

SR-2643 (UNION CROSS RD) FROM SR-2691 (WALLBURG RD) TO SR-2632 (SEDGE GARDEN RD).

| | | ROADWAY ITEMS | 12,770 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0B |
|----------------------|-----------|--|------------------|----------|---|
| | | | 51,370 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0C |
| Lump Sum Lump Sum | LS LS | MOBILIZATION CONSTRUCTION SURVEYING | 15,570 | TON | ASPHALT CONC SURFACE COURSE, |
| Lump Sum | LS | FIELD OFFICE | 41,790 | TON | TYPE S9.5B ASPHALT CONC SURFACE COURSE, |
| Lump Sum 4 | LS EA | CLEARING & GRUBBING ACRE(S) SEALING ABANDONED WELLS | 1,040 | TON | TYPE S9.5C ASPHALT CONC SURFACE COURSE, |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH | | | TYPE SF9.5A |
| | | FILL, STATION ************************************ | 630 | TON | ASPHALT PLANT MIX, PAVEMENT REPAIR |
| 1,000 5,000 | CY CY | UNDERCUT EXCAVATION SHALLOW UNDERCUT | 270 336 | EA CY | RIGHT OF WAY MARKERS SUBDRAIN EXCAVATION |
| 2 | ACR | SUPPLEMENTARY CLEARING & GRUB- | 168 | CY | SUBDRAIN FINE AGGREGATE |
| 10,000 | TON | BING CLASS IV SUBGRADE STABILIZA- | 1,000 | LF EA | 6" PERFORATED SUBDRAIN PIPE SUBDRAIN PIPE OUTLETS |
| | | TION | 12 | LF | 6" OUTLET PIPE (SUBDRAINS) |
| 4,420 36,960 | CY SY | DRAINAGE DITCH EXCAVATION REMOVAL OF EXISTING ASPHALT | 3 | CY | ENDWALLS |
| 30,700 | 51 | PAVEMENT PAVEMENT | 5.2 | CY CY | REINFORCED ENDWALLS PIPE COLLARS |
| 6,640 | SY | REMOVAL OF EXISTING CONCRETE PAVEMENT | 2 | CY | PIPE COLLARS PIPE PLUGS |
| 3,770 | SY | BREAKING OF EXISTING ASPHALT | 5 | CY | FLOWABLE FILL |
| *** | | PAVEMENT | 311 | EA | MASONRY DRAINAGE STRUCTURES |
| 300 | SY | BREAKING OF EXISTING CONCRETE PAVEMENT | 81 52 | LF EA | MASONRY DRAINAGE STRUCTURES FRAME WITH TWO GRATES, STD |
| 16,100 | SY | FABRIC FOR SOIL STABILIZATION | | . | 840.16 |
| 720 420 | SF TON | TEMPORARY SHORING GENERIC GRADING ITEM | 14 | EA | FRAME WITH TWO GRATES, STD 840.22 |
| 420 | ION | EXCAVATION AND STOCKPILING CONTAMINATED SOIL | 5 | EA | FRAME WITH TWO GRATES, STD 840.24 |
| 2,820 | TON | FOUNDATION CONDITIONING MATERIAL, MINOR STRS | 5 | EA | FRAME WITH TWO GRATES, STD 840.29 |
| 8,850 | SY | FOUNDATION CONDITIONING FABRIC | 40 | EA | FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** |
| 5,264 1,592 | LF LF | 15" DRAINAGE PIPE 18" DRAINAGE PIPE | | | (E) |
| 920 | LF | 24" DRAINAGE PIPE | 102 | EA | FRAME WITH GRATE & HOOD, STD |
| 416 | LF | 30" DRAINAGE PIPE | | | 840.03, TYPE ** (F) |
| 204 | LF | 36" DRAINAGE PIPE | 86 | EA | FRAME WITH GRATE & HOOD, STD |
| 16 | EA | **" DRAINAGE PIPE ELBOWS (15") | | | 840.03, TYPE ** (G) |
| 2 | EA | **" DRAINAGE PIPE ELBOWS (24") | 8 36 | EA EA | FRAME WITH COVER, STD 840.54 CONCRETE TRANSITIONAL SECTION |
| 2 | EA | **" DRAINAGE PIPE ELBOWS (30") | 28 | EA | FOR CATCH BASIN CONCRETE TRANSITIONAL SECTION |
| 976 | LF | 15" SIDE DRAIN PIPE | | | FOR DROP INLETS |
| 68 752 | LF | 18" SIDE DRAIN PIPE | 25,650 | LF | 1'-6" CONCRETE CURB & GUTTER |
| 752 | LF | 15" RC PIPE CULVERTS, CLASS III | 49,330 16,060 | LF SY | 2'-6" CONCRETE CURB & GUTTER 4" CONCRETE SIDEWALK |
| 148 | LF | 18" RC PIPE CULVERTS, CLASS | 2,500 | SY | 6" CONCRETE DRIVEWAY |
| 248 | LF | III 24" RC PIPE CULVERTS, CLASS | 9 | SY | 4" CONCRETE PAVED DITCH |
| | | III | 4,000 | SY | 5" MONOLITHIC CONCRETE ISLANDS (KEYED IN) |
| 28 | LF | 30" RC PIPE CULVERTS, CLASS III | 490 | LF | PRECAST REINFORCED CONCRETE BARRIER, SINGLE FACED |
| 12,392 1,332 | LF LF | 15" RC PIPE CULVERTS, CLASS IV 18" RC PIPE CULVERTS, CLASS IV | 130 | EA | GENERIC PAVING ITEM |
| 2,412 | | 24" RC PIPE CULVERTS, CLASS IV | 1 | EA | CONCRETE CURB RAMPS ADJUSTMENT OF CATCH BASINS |
| 56 | LF | 30" RC PIPE CULVERTS, CLASS IV | 1 | EA | CONVERT EXISTING DROP INLET TO |
| 40 | LF | 36" RC PIPE CULVERTS, CLASS IV | | | JUNCTION BOX WITH MANHOLE COVER |
| 1 | EA | **" PIPE END SECTION (15") | 2 | EA | IMPACT ATTENUATOR UNIT, TYPE |
| 1 | EA | **" PIPE END SECTION | | | 350 |
| 26 | LF | (18") **" CS PIPE CULVERTS, *****" | 5,787.5 50 | LF LF | STEEL BM GUARDRAIL STEEL BM GUARDRAIL, SHOP |
| | | THICK (54", 0.109") | | | CURVED |
| 5,400 | LF | PIPE REMOVAL | 10 | EA EA | ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE |
| Lump Sum | LS | FINE GRADING | 2 | LA | AT-1 |
| 21,437.5 | | PRIME COAT | 9 | EA | GUARDRAIL ANCHOR UNITS, TYPE |
| 32,400 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (2-1/2") | 19 | EA | CAT-1 GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 5,640 | SY | MILLING ASPHALT PAVEMENT, ***" TO ******" DEPTH | 17 | EA | GUARDRAIL ANCHOR UNITS, TYPE B-77 |
| | | (0" TO 2-1/2") | 3,270 | LF | REMOVE EXISTING GUARDRAIL |
| 14,950 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B | 7,700 | LF | WOVEN WIRE FENCE, 47" FABRIC |
| | | | 480 | EA | 4" TIMBER FENCE POSTS, 7'-6" LONG |

| | | | 7 | EA | COLD APPLIED PLASTIC PAVEMENT MARKING SYMBOL, TYPE ** |
|-------------------|----------|--|------------|----------|--|
| 130 | EA | 5" TIMBER FENCE POSTS, 8'-0" | 440,465 | LF | (III) PAINT PAVEMENT MARKING LINES |
| 120 | TON | LONG RIP RAP, CLASS I | 14,862 | LF | (4") PAINT PAVEMENT MARKING LINES |
| 470 | TON | RIP RAP, CLASS B | 5,352 | LF | (8") PAINT PAVEMENT MARKING LINES |
| 8,260 7 | SY CY | FILTER FABRIC FOR DRAINAGE REINFORCED CONCRETE SIGN FOUN- | 172 | EA | (24") PAINT PAVEMENT MARKING CHARAC- |
| 3 | CY | DATIONS PLAIN CONCRETE SIGN FOUNDA- | 576 | EA | TER PAINT PAVEMENT MARKING SYMBOL |
| 120 | CY | TIONS OVERHEAD FOOTING | 155,832 | LF | POLYUREA PAVEMENT MARKING LINES (4", *********) |
| 9,045 | LB | SUPPORTS, BREAKAWAY STEEL BEAM | 4,000 | I F | (HIGHLY REFLECTIVE ELEMENTS) |
| 4,232 Lump Sum | LF LS | SUPPORTS, 3-LB STEEL U-CHANNEL SUPPORTS, OVERHEAD SIGN STRUC- TURE AT STA ****** | 4,900 | LF | POLYUREA PAVEMENT MARKING LINES (6", *********) (HIGHLY REFLECTIVE ELEMENTS) |
| Lump Sum | LS | ("A" AT 18+00 -Y15RPC-) SUPPORTS, OVERHEAD SIGN STRUC- | 12,836 | LF | POLYUREA PAVEMENT MARKING LINES (8", *********) |
| Lump Jum | Lo | TURE AT STA ****** ("B" AT 18+00 -Y15RPA-) | 46,647 | LF | (HIGHLY REFLECTIVE ELEMENTS) REMOVAL OF PAVEMENT MARKING |
| Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- TURE AT STA ****** | 17 | LF | LINES (4") REMOVAL OF PAVEMENT MARKING LINES (6") |
| Lump Sum | LS | ("C" AT 152+75 -L-) SUPPORTS, OVERHEAD SIGN STRUC- TURE AT STA ****** | 166 | LF | REMOVAL OF PAVEMENT MARKING LINES (8") |
| I C | 1.0 | ("D" AT 164+25 -L-) | 238 | LF | REMOVAL OF PAVEMENT MARKING LINES (24") |
| Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- TURE AT STA ****** ("E" AT 160+50 -L-) | 38 | EA | REMOVAL OF PAVEMENT MARKING SYMBOLS & CHARACTERS |
| Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- TURE AT STA ****** | 157 | EA | SNOWPLOWABLE PAVEMENT MARKERS |
| | | ("F" AT 156+75 -L-) | 140 116 | EA EA | FLEXIBLE DELINEATORS (CRYSTAL) FLEXIBLE DELINEATORS (YELLOW) |
| 270 | EA | SIGN ERECTION, TYPE E | 1 | EA | PORTABLE DRIVE UNIT |
| 15 12 | EA EA | SIGN ERECTION, TYPE F SIGN ERECTION, TYPE *** (OVER- | 28 | CY | HIGH MOUNT FOUNDATIONS |
| | | HEAD) (A) | 24 | EA | HIGH MOUNT LUMINAIRES ******** (750W HPS) |
| 12 | EA | SIGN ERECTION, TYPE *** (GROUND MOUNTED) | 22 | EA | LIGHT STANDARD, TYPE MTLT *********************************** |
| 6 | EA | (A) SIGN ERECTION, RELOCATE, TYPE | 22 | EA | (45' SA 15') STANDARD FOUNDATION ******** (TYPE R1) |
| | | **** (GROUND MOUNTED) (A) | 22 | EA | LIGHT STANDARD LUMINAIRES, TYPE ********** |
| 2 | EA | SIGN ERECTION, RELOCATE, TYPE **** (GROUND MOUNTED) | 1 | EA | (RDW 250W HPS) ELECTRIC SERVICE POLE **** |
| 6 | EA | (D) SIGN ERECTION, RELOCATE, TYPE | | | ******* (30' CLASS 4) |
| 6 | EA | **** (GROUND MOUNTED) (E) DISPOSAL OF SUPPORT, STEEL | 50 | LF | ELECTRIC SERVICE LATERAL ************************************ |
| 3 | EA | BEAM DISPOSAL OF SIGN SYSTEM, STEEL | 330 | LF | (3,#1/0 USE) ELECTRICAL DUCT, TYPE BD, SIZE |
| 162 | EA | BEAM DISPOSAL OF SIGN SYSTEM, U- | 860 | LF | ***** (2") ELECTRICAL DUCT, TYPE JA, SIZE |
| 1,792 | SF | CHANNEL WORK ZONE SIGNS (STATIONARY) | 800 | LI | **** |
| 976 | SF | WORK ZONE SIGNS (PORTABLE) | 270 | LF | (3") ELECTRICAL DUCT, TYPE JA, SIZE |
| 666 | SF | WORK ZONE SIGNS (BARRICADE MOUNTED) | | | ***** (4") |
| 4 | EA EA | FLASHING ARROW PANELS, TYPE C CHANGEABLE MESSAGE SIGN | 260 | LF | ** #6 W/G FEEDER CIRCUIT (2) |
| 1,500 | EA | DRUMS | 370 | LF | ** #4 W/G FEEDER CIRCUIT |
| 125 | EA | CONES | 370 | LF | (2) ** #2 W/G FEEDER CIRCUIT |
| 2,424 1,560 | LF MD | BARRICADES (TYPE III) FLAGGER | 370 | LI | (2) |
| 10 | EA | TEMPORARY CRASH CUSHIONS | 3,365 | LF | ** #8 W/G FEEDER CIRCUIT IN *****" CONDUIT |
| 2 | EA | RESET TEMPORARY CRASH CUSHIONS | | | (2, 1-1/2") |
| 4 6,680 | EA LF | TMIA PORTABLE CONCRETE BARRIER | 6,070 | LF | ** #6 W/G FEEDER CIRCUIT IN *****" CONDUIT |
| 2,230 | LF | PORTABLE CONCRETE BARRIER | 1,000 | | (2, 1-1/2") |
| 2,210 | LF | (DRAINAGE) RESET PORTABLE CONCRETE BAR- RIER | 1,090 | LF | ** #4 W/G FEEDER CIRCUIT IN *****" CONDUIT (2, 1-1/2") |
| 750 | LF | RESET PORTABLE CONCRETE BAR- RIER (DRAINAGE) | 3,310 | LF | ** #2 W/G FEEDER CIRCUIT IN *****" CONDUIT |
| 160 | HR | LAW ENFORCEMENT | Lump Sum | LS | (2, 1-1/2") PORTABLE LIGHTING |
| 50 2,285 | EA EA | SKINNY DRUM TEMPORARY RAISED PAVEMENT | 4 | EA | GENERIC LIGHTING ITEM 100' HIGH MOUNT STANDARD |
| 1,536 | LF | MARKERS THERMOPLASTIC PAVEMENT MARKING | 24 | EA | GENERIC LIGHTING ITEM ELECTRICAL JUNCTION BOX (PC18) |
| 4,060 | LF | LINES (8", 90 MILS) THERMOPLASTIC PAVEMENT MARKING | 4 | EA | GENERIC LIGHTING ITEM ELECTRICAL JUNCTION BOX (PC30) |
| 88 | LF | LINES (8", 120 MILS) THERMOPLASTIC PAVEMENT MARKING | 2 | EA | GENERIC LIGHTING ITEM ELECTRICAL JUNCTION BOX (PC36) |
| 3,215 | LF | LINES (16", 120 MILS) THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) | 1 | EA | GENERIC LIGHTING ITEM LIGHT CONTROL EQUIPMENT, RW, |
| 98 | EA | THERMOPLASTIC PAVEMENT MARKING | 48 | LF | 240/480V, 150A 6" WATER LINE |
| 321 | EA | CHARACTER (120 MILS) THERMOPLASTIC PAVEMENT MARKING | 705 | LF | 8" WATER LINE |
| | | SYMBOL (90 MILS) | 78 212 | LF LF | 12" WATER LINE 16" WATER LINE |
| 12 | EA | COLD APPLIED PLASTIC PAVEMENT MARKING CHARACTER, TYPE ** | 584 | LF | 20" WATER LINE |
| | | (III) | 749 | LF | 24" WATER LINE |

Page: 46 of 62

| | | | | | 1 age . |
|------------------|------------|--|------------------|--------------|---|
| | | | 10,000 |) LF | REMOVE EXISTING COMMUNICATIONS CABLE |
| | | | 36 | 5 EA | METAL STRAIN SIGNAL POLE |
| 1 | EA | 8" VALVE | 2 | 2 EA | METAL POLE WITH SINGLE MAST ARM |
| 1 | EA | 12" VALVE | 2 | 2 EA | METAL POLE WITH DUAL MAST ARM |
| 3 | EA EA | 20" VALVE 24" VALVE | 40 |) EA | SOIL TEST |
| 95 | EA | RELOCATE WATER METER | 252 | | DRILLED PIER FOUNDATION |
| 1 | EA | RECONNECT WATER METER | 10 |) EA | SIGNAL PEDESTAL WITH FOUNDA- TION |
| 33 | EA EA | FIRE HYDRANT RELOCATE FIRE HYDRANT | 4 | 4 EA | MAST ARM WITH METAL POLE DE- SIGN |
| 2 | EA | 24" LINE STOP | 63 | 3 EA | SIGN FOR SIGNALS |
| 2 | EA | 20" LINE STOP WITH BYPASS | 13 | B EA | SIGNAL CABINET FOUNDATION |
| 1 242 | LF LF | ABANDON 6" UTILITY PIPE | 13 | B EA | CONTROLLER WITH CABINET (TYPE 2070L, BASE MOUNTED) |
| 1,242 69 | LF | ABANDON 8" UTILITY PIPE ABANDON 12" UTILITY PIPE | 91 | l EA | DETECTOR CARD (TYPE 2070L) |
| 207 | LF | ABANDON 16" UTILITY PIPE | 13 | | CABINET BASE EXTENDER |
| 448 | LF LF | ABANDON 20" UTILITY PIPE | 1 | I EA 5 EA | TRAFFIC SIGNAL REMOVAL GENERIC SIGNAL ITEM |
| 533 25 | EA | ABANDON 24" UTILITY PIPE REMOVE WATER METER | ` | , 1,1 | MODIFY RADIO INSTALLATION |
| 135 | LF | 36" ENCASEMENT PIPE | | | |
| 68 | LF | TRENCHLESS INSTALLATION OF 24" IN SOIL | | | ****** BEGIN SCHEDULE AA ****** |
| 67 | LF | TRENCHLESS INSTALLATION OF 24" | | | ****** (3 ALTERNATES) ****** |
| 90,000 | LE | NOT IN SOIL | 262,000 | | UNCLASSIFIED EXCAVATION |
| 80,000 7,000 | LF TON | TEMPORARY SILT FENCE STONE FOR EROSION CONTROL, | 44,080 17,900 | | AGGREGATE BASE COURSE SHOULDER BORROW |
| | | CLASS A | 60,340 | | |
| 4,200 | TON | STONE FOR EROSION CONTROL, CLASS B | 0.077 | TON: | B25.0C |
| 7,000 | TON | SEDIMENT CONTROL STONE | 9,875 | 5 TON | ASPHALT BINDER FOR PLANT MIX *** OR *** |
| 130 | ACR | TEMPORARY MULCHING | 257,000 |) CY | UNCLASSIFIED EXCAVATION |
| 3,750 16 | LB TON | SEED FOR TEMPORARY SEEDING FERTILIZER FOR TEMPORARY SEED- | 9,000 |) CY | BORROW EXCAVATION |
| | | ING | 9,120 | | |
| 1,500 25 | LF EA | TEMPORARY SLOPE DRAINS INLET PROTECTION AT TEMPORARY | 75,640 |) TON | ASPHALT CONC BASE COURSE, TYPE B25.0C |
| 23 | EA | SLOPE DRAINS | 10,550 | TON | |
| 500 | LF | SAFETY FENCE | 200,000 | OV. | *** OR *** |
| 14,000 72,800 | CY SY | SILT EXCAVATION MATTING FOR EROSION CONTROL | 260,000 9,120 | | UNCLASSIFIED EXCAVATION AGGREGATE BASE COURSE |
| 200 | SY | COIR FIBER MAT | 42,530 | | AGGREGATE FOR CEMENT TREATED |
| 900 | SY | PERMANENT SOIL REINFORCEMENT | 1,720 |) TON | BASE COURSE PORTLAND CEMENT FOR CEMENT |
| 26,000 | LF | MAT 1/4" HARDWARE CLOTH | 1,720 |) TON | TREATED BASE COURSE |
| 8,500 | LF | COIR FIBER WATTLE | 11,390 | | |
| 6,700 | LB | POLYACRYLAMIDE (PAM) | 17,300 45,240 | | SHOULDER BORROW ASPHALT CONC BASE COURSE, TYPE |
| 2,000 12 | LF EA | COIR FIBER BAFFLE **" SKIMMER | | | B25.0C |
| | | (1-1/2") | 9,210 20 | | |
| 105 120 | ACR ACR | SEEDING & MULCHING MOWING | 20 | , 101 | BEOTTING SAND |
| 2,000 | LB | SEED FOR REPAIR SEEDING | | | *** END SCHEDULE AA *** |
| 5.25 | TON | FERTILIZER FOR REPAIR SEEDING | | | WALL ITEMS |
| 2,600 | LB TON | SEED FOR SUPPLEMENTAL SEEDING FERTILIZER TOPDRESSING | | | |
| 100 | MHR | SPECIALIZED HAND MOWING | 4,253 | 3 SF | MSE RETAINING WALLS |
| 150 | EA | RESPONSE FOR EROSION CONTROL | 4,23. | 31. | MSE RETAINING WALLS |
| 30 | EA | PEDESTRIAN SIGNAL HEAD (**", ** SECTION) | | | |
| | | (16", 1 SECTION WITH COUNT- | | | STRUCTURE ITEMS |
| 28,135 | LF | DOWN) SIGNAL CABLE | | | |
| 154 | EA | VEHICLE SIGNAL HEAD (12", 3 | Lump Sun | . 10 | EQUIDATION EVCAVATION FOR DENT |
| 20 | EA | SECTION) VEHICLE SIGNAL HEAD (12", 4 | Lump Sun | n LS | FOUNDATION EXCAVATION FOR BENT ** AT STATION ************************************ |
| 20 | LA | SECTION) | 8,287 | 7 SF | (158+24.63 -L_NB-) REINFORCED CONCRETE DECK SLAB |
| 24 | EA | VEHICLE SIGNAL HEAD (12", 5 SECTION) | 8,198 | | GROOVING BRIDGE FLOORS |
| 9,100 | LF | MESSENGER CABLE (1/4") | 147 | | CLASS A CONCRETE (BRIDGE) |
| 10,545 | LF | MESSENGER CABLE (3/8") | Lump Sun | n LS | BRIDGE APPROACH SLABS, STATION ************************************ |
| 610 | LF | PAVED TRENCHING (********) (1, 2") | | | (158+24.63 -L_NB-) |
| 17,215 | LF | UNPAVED TRENCHING (*******) | 23,599 1,172 | | REINFORCING STEEL (BRIDGE) SPIRAL COLUMN REINFORCING |
| 660 | LF | (1, 2") UNPAVED TRENCHING (********) | 1,172 | 2 LD | STEEL (BRIDGE) |
| 660 | LF | (2, 2") | 974.25 | 5 LF | 54" PRESTRESSED CONCRETE GIR- DERS |
| 1,025 | LF | DIRECTIONAL DRILL (*******) | 735 | 5 LF | HP12X53 STEEL PILES |
| 130 | LF | (1, 2") DIRECTIONAL DRILL (********) | 865 | 5 LF | HP12X53 GALVANIZED STEEL PILES |
| | | (2, 2") | 156.35 | | TWO BAR METAL RAIL |
| 204 | EA EA | JUNCTION BOX (STANDARD SIZE) | 164.36 164.36 | | CONCRETE BARRIER RAIL 1'-**"X *****" CONCRETE PARA- |
| 38 95 | EA EA | WOOD POLE GUY ASSEMBLY | 104.30 | | PET |
| 9 | EA | 1" RISER WITH WEATHERHEAD | 28 | 8 SY | (1'-2" X 2'-6") 4" SLOPE PROTECTION |
| 50 27 185 | EA | 2" RISER WITH WEATHERHEAD | Lump Sun | | ELASTOMERIC BEARINGS |
| 27,185 75,235 | LF LF | INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (**********) | Lump Sun | n LS | EVAZOTE JOINT SEALS |
| | | (14-2) | | | |
| 5 14 | EA EA | MICROWAVE VEHICLE DETECTOR 900MHZ WIRELESS RADIO SYSTEM | | | |
| 14 | | , | | | |

Page: 47 of 62

L120117 035

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202925 9CR.10291.9 DIV OFFICE WINSTON-SALEM LENGTH = 29.473 MI

COUNTY : DAVIDSON

MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION.

MBE GOAL 5.0% WBE 6.0% COMPLETION DATE : OCT 31 2012

NC-109 FROM NC-109 / RANDOLPH ST RR CROSSING TO SR-2067 AND 11 SECTIONS OF SECONDARY ROADS.

| Lump Sum | LS | MOBILIZATION |
|----------|-----|--|
| 3,357 | CY | BORROW EXCAVATION |
| 1,561 | TON | INCIDENTAL STONE BASE |
| 56.41 | SMI | SHOULDER RECONSTRUCTION |
| 9,353 | SY | MILLING ASPHALT PAVEMENT. ***" |
| 9,333 | 31 | DEPTH (1-1/2") |
| 14,689 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (2") |
| 31,148 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (3-1/2") |
| 17,122 | SY | MILLING ASPHALT PAVEMENT, ***" TO ******" |
| | | (0" TO 1-1/2") |
| 578 | SY | MILLING ASPHALT PAVEMENT, ***" TO ******" (0" TO 3-1/2") |
| 1,854 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE I19.0B |
| 3,906 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0C |
| 35,744 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 5,058 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5C |
| 2,718 | TON | ASPHALT BINDER FOR PLANT MIX |
| 1 | EA | ADJUSTMENT OF DROP INLETS |
| 3 | EA | ADJUSTMENT OF MANHOLES |
| 54 | EA | ADJUSTMENT OF METER BOXES OR VALVE BOXES |
| 303,253 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 320,440 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 355 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (6", 90 MILS) |
| 175 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (6", 120 MILS) |
| 186 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 120 MILS) |
| 350 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (16", 120 MILS) |
| 1,680 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 54 | EA | THERMOPLASTIC PAVEMENT MARKING CHARACTER (120 MILS) |
| 102 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 17,356 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 326 | EA | SNOWPLOWABLE PAVEMENT MARKERS |
| 11,684 | LF | TEMPORARY SILT FENCE |
| 1,100 | LF | WATTLE |

Page: 48 of 62

L120117 036

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C202926 9CR.10341.9 DIV OFFICE WINSTON-SALEM LENGTH = 40.733 MI

COUNTY : FORSYTH, STOKES

MILLING, RESURFACING, AND SHOULDER RECONSTRUCTION.

MBE GOAL 4.0% WBE 4.0% COMPLETION DATE : OCT 31 2012

1 SECTION OF US-158, US-311, NC-66, AND NC-67, AND 11 SECTIONS OF SECONDARY ROADS.

| Lump Sum | LS | MOBILIZATION |
|----------|-----|---|
| 4,277 | CY | BORROW EXCAVATION |
| 1,459 | TON | INCIDENTAL STONE BASE |
| 69.88 | SMI | SHOULDER RECONSTRUCTION |
| 10,330 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (1-1/2") |
| 13,667 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (2") |
| 69,433 | SY | MILLING ASPHALT PAVEMENT, ***" TO ******" (0" TO 1-1/2") |
| 489 | SY | MILLING ASPHALT PAVEMENT, ***" TO ******" |
| 534 | SY | (0" TO 2") MILLING ASPHALT PAVEMENT, ***" TO ****** |
| 1,173 | SY | (1-1/2" TO 3-1/2") MILLING ASPHALT PAVEMENT, ***" TO ******" [1-1/2" TO 5") |
| 958 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B |
| 122 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0B |
| 1,734 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE I19.0C |
| 52,140 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 16,090 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5C |
| 4,209 | TON | ASPHALT BINDER FOR PLANT MIX |
| 95 | EA | ADJUSTMENT OF MANHOLES |
| 99 | EA | ADJUSTMENT OF METER BOXES OR VALVE BOXES |
| Lump Sum | LS | TEMPORARY TRAFFIC CONTROL |
| 300 | HR | LAW ENFORCEMENT |
| 411,647 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 501,688 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 2,587 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 90 MILS) |
| 3,845 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 120 MILS) |
| 3,372 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 28 | EA | THERMOPLASTIC PAVEMENT MARKING CHARACTER (120 MILS) |
| 475 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 2,220 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 28 | LF | PAINT PAVEMENT MARKING LINES (24") |
| 8 | EA | PAINT PAVEMENT MARKING SYMBOL |
| 1,277 | EA | SNOWPLOWABLE PAVEMENT MARKERS |
| Lump Sum | LS | PORTABLE LIGHTING |
| 16,292 | LF | TEMPORARY SILT FENCE |
| 1,400 | LF | WATTLE |
| 30,000 | LF | INDUCTIVE LOOP SAWCUT |

Page: 49 of 62

L120117 037

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202725 33632.3.1 DIV OFFICE ALBEMARLE LENGTH = 0.157 MI

COUNTY : UNION

GRADING, DRAINAGE, PAVING, AND STRUCTURE.

112 LF BARRICADES (TYPE III)
1,400 LF TEMPORARY SILT FENCE
225 TON STONE FOR EROSION CONTROL,
CLASS A
205 TON STONE FOR EROSION CONTROL,
CLASS B
125 TON SEDIMENT CONTROL STONE
3 ACR TEMPORARY MULCHING
100 LB SEED FOR TEMPORARY SEEDING
1.5 TON FERTILIZER FOR TEMPORARY SEEDING
350 LF TEMPORARY SLOPE DRAINS
5 EA INLET PROTECTION AT TEMPORARY
\$LOPE DRAINS
400 LF SAFETY FENCE

DBE GOAL 10.0% COMPLETION DATE: SEE SPECIAL PROVISIONS

BRIDGE OVER WAXHAW CREEK AND APPROACHES ON SR-1113.

| | | ROADWAY ITEMS | 1 | EA ACR | **" SKIMMER (1-1/2") SEEDING & MULCHING |
|-----|--|--|---|------------------------------|---|
| | 1.0 | MODIL 17 ATION | 3 | ACR | MOWING |
| | | | 50 | LB | SEED FOR REPAIR SEEDING |
| | | | 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| um | Lo | REGIONAL TIER, STATION ****** | 75 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| | | (18+79.00-L-) | 2 | TON | FERTILIZER TOPDRESSING |
| 75 | CY | SHALLOW UNDERCUT | | | SPECIALIZED HAND MOWING |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- BING | 18 | EA | RESPONSE FOR EROSION CONTROL |
| 250 | CY | UNDERCUT EXCAVATION | | | |
| um | LS | GRADING | | | CEDITORIDE LEEVE |
| 350 | TON | CLASS IV SUBGRADE STABILIZA- TION | | | STRUCTURE ITEMS |
|)75 | CY | BORROW EXCAVATION | | | |
| 35 | CY | DRAINAGE DITCH EXCAVATION | Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE |
| 500 | SY | FABRIC FOR SOIL STABILIZATION | | | AT STATION ************************************ |
| 3 | TON | FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS | Lump Sum | LS | UNCLASSIFIED STRUCTURE EXCAVA- TION AT STATION ******* |
| 10 | SY | FOUNDATION CONDITIONING FABRIC | | | (18+79.00-L-) |
| 24 | LF | 15" DRAINAGE PIPE | 34.4 | CY | CLASS A CONCRETE (BRIDGE) |
| 2 | EA | **" DRAINAGE PIPE ELBOWS (15") | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| 00 | TON | INCIDENTAL STONE BASE | | | (18+79.00-L-) |
| 120 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B | 5,076 360 | LB | REINFORCING STEEL (BRIDGE) HP12X53 STEEL PILES |
| 170 | TON | ASPHALT CONC SURFACE COURSE, TYPE SF9.5A | 195.5 | LF | VERTICAL CONCRETE BARRIER RAIL |
| 50 | TON | ASPHALT BINDER FOR PLANT MIX | | | RIP RAP CLASS II (2'-0" THICK) |
| 56 | CY | SUBDRAIN EXCAVATION | | | FILTER FABRIC FOR DRAINAGE ELASTOMERIC BEARINGS |
| 42 | CY | SUBDRAIN FINE AGGREGATE | | | 3'-0" X 3'-3" PRESTRESSED CONC |
| 250 | LF | 6" PERFORATED SUBDRAIN PIPE | 711.5 | Li | BOX BEAMS |
| 1 | | | | | |
| 6 | | | | | |
| - | | | | | |
| 1 | | FRAME WITH TWO GRATES, STD 840.29 | | | |
| 30 | | SHOULDER BERM GUTTER | | | |
| | | | | | |
| | | | | | |
| 6 | EA | ******* | | | |
| 4 | E.A | | | | |
| | | III | | | |
| | | | | | |
| | | | | | |
| - | | LEVEL SPREADER APRON | | | |
| | SF | WORK ZONE SIGNS (STATIONARY) | | | |
| 14 | SF | WORK ZONE SIGNS (BARRICADE MOUNTED) | | | |
| | 250 aum 350 35 35 3600 3 10 24 2 100 420 470 56 42 250 1 6 1 1 | um LS um LS um LS 175 CY 1 ACR 250 CY um LS 1850 TON 175 CY 35 CY 500 SY 3 TON 10 SY 24 LF 2 EA 100 TON 170 TO | um LS MOBILIZATION um LS CONSTRUCTION SURVEYING um LS BRIDGE APPROACH FILL - SUB REGIONAL TIER, STATION ******** (18+79.00-L-) 175 CY SHALLOW UNDERCUT 1 ACR SUPPLEMENTARY CLEARING & GRUBBING 250 CY UNDERCUT EXCAVATION um LS GRADING 350 TON CLASS IV SUBGRADE STABILIZATION 175 CY BORROW EXCAVATION 35 CY DRAINAGE DITCH EXCAVATION 360 SY FABRIC FOR SOIL STABILIZATION 37 TON FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS 10 SY FOUNDATION CONDITIONING FABRIC 24 LF 15" DRAINAGE PIPE ELBOWS (15") 160 TON INCIDENTAL STONE BASE 120 TON ASPHALT CONC BASE COURSE, TYPE B25.0B 170 TON ASPHALT CONC SURFACE COURSE, TYPE SF9.5A ASPHALT BINDER FOR PLANT MIX 25 CY SUBDRAIN FINE AGGREGATE 26 LF 6" PERFORATED SUBDRAIN PIPE 1 EA SUBDRAIN PIPE OUTLETS 6 LF 6" OUTLET PIPE (SUBDRAINS) 1 EA MASONRY DRAINAGE STRUCTURES 1 EA FRAME WITH TWO GRATES, STD 840.29 30 LF SHOULDER BERM GUTTER 50 LF STEEL BM GUARDRAIL 5 EA ADDITIONAL GUARDRAIL 5 EA ADDITIONAL GUARDRAIL 5 EA GUARDRAIL ANCHOR UNITS, TYPE III 75 TON RIP RAP, CLASS I FILTER FABRIC FOR DRAINAGE 1 EA PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON 556 SF WORK ZONE SIGNS (STATIONARY) 5510 WORK ZONE SIGNS (STATIONARY) 5510 WORK ZONE SIGNS (BARRICADE | MIN LS MOBILIZATION 50 | MOBILIZATION |

Page: 50 of 62

L120117 038

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202744 34977.3.1 DIV OFFICE NORTH WILKESBORO LENGTH = 1.492 MI

COUNTY : ASHE

GRADING, DRAINAGE, PAVING, SIGNALS, AND CULVERT.

DBE GOAL 10.0% COMPLETION DATE: OCT 01 2013

NC-88 FROM NC-194 TO US-221 BUS IN JEFFERSON.

| | | ROADWAY ITEMS | 5 | EA | FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** (E) |
|----------|------|--|---------|-----|---|
| | | | 14 | EA | FRAME WITH GRATE & HOOD, STD |
| Lump Sum | LS | MOBILIZATION | | | 840.03, TYPE ** |
| 1 | EA | SEALING ABANDONED WELLS | | | (F) |
| 17,500 | CY | UNCLASSIFIED EXCAVATION | 8 | EA | FRAME WITH GRATE & HOOD, STD |
| 1,000 | CY | SHALLOW UNDERCUT | | | 840.03, TYPE ** |
| 1 | ACR | SUPPLEMENTARY CLEARING & GRUB- | | | (G) |
| | | BING | 2 | EA | GENERIC DRAINAGE ITEM |
| 1,425 | CY | UNDERCUT EXCAVATION | | | BICYCLE SAFE STEEL GRATE AND FRAME |
| Lump Sum | LS | GRADING | 870 | LF | **"X **" CONCRETE CURB |
| 1,900 | TON | CLASS IV SUBGRADE STABILIZA- | 870 | LI | (9" X 12") |
| | | TION | 4,640 | LF | 2'-6" CONCRETE CURB & GUTTER |
| 410 | CY | DRAINAGE DITCH EXCAVATION | 425 | LF | SHOULDER BERM GUTTER |
| 2,300 | CY | SELECT GRANULAR MATERIAL | 1,380 | SY | 4" CONCRETE SIDEWALK |
| 2,400 | SY | FABRIC FOR SOIL STABILIZATION | 400 | SY | 6" CONCRETE DRIVEWAY |
| 330 | SF | TEMPORARY SHORING | 220 | SY | 4" CONCRETE PAVED DITCH |
| 100 | CY | GENERIC GRADING ITEM | 16 | EA | GENERIC PAVING ITEM |
| | | STOCKPILING OF CONTAMINATED | 10 | Lit | CONCRETE CURB RAMPS |
| 1 200 | CV | SOIL CENERIC CRADING ITEM | 1,362.5 | LF | STEEL BM GUARDRAIL |
| 1,200 | SY | GENERIC GRADING ITEM GEOTEXTILE FOR PAVEMENT STABI- | 250 | LF | STEEL BM GUARDRAIL, SHOP |
| | | LIZATION | | | CURVED |
| 590 | TON | FOUNDATION CONDITIONING MATE- | 10 | EA | ADDITIONAL GUARDRAIL POSTS |
| 270 | 1011 | RIAL, MINOR STRS | 3 | EA | GUARDRAIL ANCHOR UNITS, TYPE |
| 2,383 | SY | FOUNDATION CONDITIONING FABRIC | _ | | AT-1 |
| 2,312 | LF | 15" DRAINAGE PIPE | 11 | EA | GUARDRAIL ANCHOR UNITS, TYPE |
| 600 | LF | 18" DRAINAGE PIPE | | | 350 |
| 480 | LF | 24" DRAINAGE PIPE | 250 | LF | REMOVE EXISTING GUARDRAIL |
| 176 | LF | 36" DRAINAGE PIPE | 480 | LF | GENERIC FENCING ITEM |
| 80 | LF | 15" SIDE DRAIN PIPE | | | BLACK VINYL COATED CHAIN LINK |
| 56 | LF | 18" SIDE DRAIN PIPE | | | FENCE, 48" FABRIC ON RETAINING |
| | LF | **" CS PIPE CULVERTS, *****" | | | WALL |
| 136 | LI | THICK | 40 | EA | GENERIC FENCING ITEM BLACK VINYL COATED METAL LINE |
| | | (60", 0.168") | | | POSTS FOR 48" CHAIN LINK FENCE |
| 36 | LF | 15" CS PIPE CULVERTS, 0.064" | 2 | EA | GENERIC FENCING ITEM |
| | | THICK | 2 | LA | BLACK VINYL COATED METAL TER- |
| 8 | LF | 18" CS PIPE CULVERTS, 0.064" | | | MINAL POSTS FOR 48" CHAIN LINK |
| | | THICK | | | FENCE |
| 44 | LF | 24" CS PIPE CULVERTS, 0.064" | 42 | TON | RIP RAP, CLASS B |
| | | THICK | 1,415 | SY | FILTER FABRIC FOR DRAINAGE |
| 2 | EA | **" CS PIPE ELBOWS, *****" | 2 | EA | PREFORMED SCOUR HOLES WITH |
| | | THICK | | | LEVEL SPREADER APRON |
| | | (15", 0.064") | 901 | LF | SUPPORTS, 3-LB STEEL U-CHANNEL |
| 2 | EA | **" CS PIPE ELBOWS, *****" | 4 | EA | SIGN ERECTION, TYPE D |
| | | THICK (24", 0.064") | 22 | EA | SIGN ERECTION, TYPE E |
| 500 | LF | PIPE REMOVAL | 11 | EA | SIGN ERECTION, TYPE F |
| 500 | TON | STABILIZER AGGREGATE | 39 | EA | DISPOSAL OF SIGN SYSTEM, U- |
| 150 | TON | INCIDENTAL STONE BASE | | | CHANNEL |
| 9,150 | SY | MILLING ASPHALT PAVEMENT, ***" | 15 | EA | DISPOSAL OF SIGN SYSTEM, WOOD |
| 9,130 | 31 | DEPTH | 617 | SF | WORK ZONE SIGNS (STATIONARY) |
| | | (1-1/2") | 211 | SF | WORK ZONE SIGNS (PORTABLE) |
| 4,200 | TON | ASPHALT CONC BASE COURSE, TYPE | 209 | SF | WORK ZONE SIGNS (BARRICADE |
| ., | | B25.0B | | | MOUNTED) |
| 3,000 | TON | ASPHALT CONC INTERMEDIATE | 2 | EA | CHANGEABLE MESSAGE SIGN |
| | | COURSE, TYPE I19.0B | 250 | EA | DRUMS |
| 6,100 | TON | ASPHALT CONC SURFACE COURSE, | 25 | EA | CONES |
| | | TYPE S9.5B | 160 | LF | BARRICADES (TYPE III) |
| 695 | TON | ASPHALT BINDER FOR PLANT MIX | 360 | MD | FLAGGER |
| 175 | TON | ASPHALT PLANT MIX, PAVEMENT | 1 | EA | TMIA |
| | | REPAIR | 500 | LF | WATER FILLED BARRIER |
| 67.2 | CY | SUBDRAIN EXCAVATION | 16 | HR | LAW ENFORCEMENT |
| 50.4 | CY | SUBDRAIN FINE AGGREGATE | 40 | EA | SKINNY DRUM |
| 300 | LF | 6" PERFORATED SUBDRAIN PIPE | 170 | EA | TEMPORARY RAISED PAVEMENT |
| 1 | EA | SUBDRAIN PIPE OUTLETS | 170 | Lit | MARKERS |
| 6 | LF | 6" OUTLET PIPE (SUBDRAINS) | 190 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 4 | CY | ENDWALLS | | | LINES (8", 90 MILS) |
| 8.3 | CY | REINFORCED ENDWALLS | 109 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 1 | CY | PIPE COLLARS | | | LINES (8", 120 MILS) |
| 44 | CY | FLOWABLE FILL | 176 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 50 | EA | MASONRY DRAINAGE STRUCTURES | | | LINES (24", 120 MILS) |
| 13 | LF | MASONRY DRAINAGE STRUCTURES | 91,600 | LF | PAINT PAVEMENT MARKING LINES |
| 16 | EA | FRAME WITH TWO GRATES, STD | | | (4") |
| 10 | | 840.24 | 400 | LF | PAINT PAVEMENT MARKING LINES |
| 3 | EA | FRAME WITH TWO GRATES, STD | | | (8") |
| | | 840.29 | 30 | LF | PAINT PAVEMENT MARKING LINES (24") |
| | | | 1.5 | EΑ | |
| | | | 15 | EA | PAINT PAVEMENT MARKING SYMBOL |

Page: 51 of 62

CULVERT ITEMS

| 42,408 | LF | POLYUREA PAVEMENT MARKING |
|--|-------------------------------|--|
| | | LINES (4", *********) (HIGHLY REFLECTIVE ELEMENTS) |
| 1,000 | LF | REMOVAL OF PAVEMENT MARKING |
| 210 | EA | LINES (4") |
| 38 | LF | SNOWPLOWABLE PAVEMENT MARKERS 2" WATER LINE |
| 3,187 | LF | 6" WATER LINE |
| 1 | EA | 2" VALVE |
| 13 | EA | 6" VALVE |
| 7 | EA EA | RELOCATE WATER METER |
| 6 4 | EA | RECONNECT WATER METER RELOCATE FIRE HYDRANT |
| 50 | LF | 8" SANITARY GRAVITY SEWER |
| 1 | EA | 4' DIA UTILITY MANHOLE |
| 2,895 | LF | ABANDON 6" UTILITY PIPE |
| 13,000 | LF TON | TEMPORARY SILT FENCE STONE FOR EROSION CONTROL, |
| 1,200 | TON | CLASS A |
| 660 | TON | STONE FOR EROSION CONTROL, |
| 1,170 | TON | CLASS B SEDIMENT CONTROL STONE |
| 9.5 | ACR | TEMPORARY MULCHING |
| 250 | LB | SEED FOR TEMPORARY SEEDING |
| 2 | TON | FERTILIZER FOR TEMPORARY SEED- |
| 900 | LF | ING |
| 18 | EA | TEMPORARY SLOPE DRAINS INLET PROTECTION AT TEMPORARY |
| 10 | Lit | SLOPE DRAINS |
| 1,100 | LF | SAFETY FENCE |
| 1,850 13,000 | CY | SILT EXCAVATION MATTING FOR EROSION CONTROL |
| 1,575 | SY SY | COIR FIBER MAT |
| 650 | SY | PERMANENT SOIL REINFORCEMENT |
| | | MAT |
| 3,125 | LF | 1/4" HARDWARE CLOTH |
| 100 | LF | **" TEMPORARY PIPE (24") |
| 220 | SY | FLOATING TURBIDITY CURTAIN |
| 8 | EA | SPECIAL STILLING BASINS |
| 1,500 | LF LB | COIR FIBER WATTLE POLYACRYLAMIDE (PAM) |
| 650 460 | LF | COIR FIBER BAFFLE |
| 6 | EA | **" SKIMMER |
| | | (1-1/2") |
| 9 | ACR ACR | SEEDING & MULCHING MOWING |
| 100 | LB | SEED FOR REPAIR SEEDING |
| 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| 175 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| 4.75 | TON | FERTILIZER TOPDRESSING |
| 160 100 | LF MHR | IMPERVIOUS DIKE SPECIALIZED HAND MOWING |
| 100 | EA | RESPONSE FOR EROSION CONTROL |
| 0.25 | ACR | REFORESTATION |
| 2 | EA | PEDESTRIAN SIGNAL HEAD (**", |
| | | ** SECTION) (16", 1 SECTION WITH COUNT- |
| | | DOWN) |
| 1,805 | LF | SIGNAL CABLE |
| 13 | EA | VEHICLE SIGNAL HEAD (12", 3 |
| _ | | SECTION) |
| 2 | EA | VEHICLE SIGNAL HEAD (12", 4 |
| | | VEHICLE SIGNAL HEAD (12", 4 SECTION) |
| 2 | EA EA | VEHICLE SIGNAL HEAD (12", 4 |
| | | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 |
| 2 | EA | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (************) |
| 2 695 85 | EA LF | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (************************************ |
| 2 695 85 735 | EA LF LF LF | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (*************) (1, 2") UNPAVED TRENCHING (************) (1, 2") |
| 2 695 85 735 | EA LF LF LF | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (************) (1, 2") UNPAVED TRENCHING (***********) (1, 2") JUNCTION BOX (STANDARD SIZE) |
| 2 695 85 735 10 1,495 | EA LF LF LF EA LF | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (************) (1, 2") UNPAVED TRENCHING (***********) JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT |
| 2 695 85 735 | EA LF LF LF | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (************) (1, 2") UNPAVED TRENCHING (***********) (1, 2") JUNCTION BOX (STANDARD SIZE) |
| 2 695 85 735 10 1,495 2,660 | EA LF LF EA LF LF EA | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (*************) (1, 2") UNPAVED TRENCHING (************) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (*************) (14-2) METAL STRAIN SIGNAL POLE |
| 2 695 85 735 10 1,495 2,660 8 8 | EA LF LF EA LF LF EA LF LF | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (*************) (1, 2") UNPAVED TRENCHING (************) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (************) (14-2) METAL STRAIN SIGNAL POLE SOIL TEST |
| 2 695 85 735 10 1,495 2,660 8 8 8 | EA LF LF EA LF LF EA CY | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (************) (1, 2") UNPAVED TRENCHING (***********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (************) (14-2) METAL STRAIN SIGNAL POLE SOIL TEST DRILLED PIER FOUNDATION |
| 2 695 85 735 10 1,495 2,660 8 8 | EA LF LF EA LF LF EA LF LF | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (*************) (1, 2") UNPAVED TRENCHING (************) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (************) (14-2) METAL STRAIN SIGNAL POLE SOIL TEST |
| 2 695 85 735 10 1,495 2,660 8 8 8 48 2 2 | EA LF LF EA LF LF EA CY EA EA | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (*************) (1, 2") UNPAVED TRENCHING (************) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (************) (14-2) METAL STRAIN SIGNAL POLE SOIL TEST DRILLED PIER FOUNDATION SIGNAL CABINET FOUNDATION CONTROLLER WITH CABINET (TYPE 2070L, BASE MOUNTED) |
| 2 695 85 735 10 1,495 2,660 8 8 48 2 | EA LF LF EA LF LF CY EA | VEHICLE SIGNAL HEAD (12", 4 SECTION) VEHICLE SIGNAL HEAD (12", 5 SECTION) MESSENGER CABLE (3/8") PAVED TRENCHING (*************) (1, 2") UNPAVED TRENCHING (***********) (1, 2") JUNCTION BOX (STANDARD SIZE) INDUCTIVE LOOP SAWCUT LEAD-IN CABLE (************) (14-2) METAL STRAIN SIGNAL POLE SOIL TEST DRILLED PIER FOUNDATION SIGNAL CABINET FOUNDATION CONTROLLER WITH CABINET (TYPE |

4,320 SF SOLDIER PILE RETAINING WALLS

Page: 52 of 62

L120117 039

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID : C202729 33708.3.1 **DIV OFFICE SHELBY LENGTH = 0.222 MI**

COUNTY : CATAWBA

GRADING, DRAINAGE, PAVING, AND STRUCTURES.

DBE GOAL 10.0% COMPLETION DATE: NOV 15 2012

BRIDGE OVER I-40 AND APPROACHES ON NC-16.

| Lump Sum LS MOBILIZATION Lump Sum LS CONSTRUCTION SURVEYING Lump Sum LS BRIDGE APPROACH FILL - SUB REGIONAL TIER, STATION ******** (24+46.07-L-) 100 CY SHALLOW UNDERCUT Lump Sum LS GRADING 1 ACR SUPPLEMENTARY CLEARING & GRUBBING 250 CY UNDERCUT EXCAVATION CLASS IV SUBGRADE STABILIZATION CLASS IV SUBGRADE STABILIZATION 540 CY DRAINAGE DITCH EXCAVATION 950 SY FABRIC FOR SOIL STABILIZATION 143 TON FOUNDATION CONDITIONING MATERIAL, MINOR STRS 450 SY FOUNDATION CONDITIONING FABRIC 196 LF 15" SIDE DRAIN PIPE 244 LF **** RC PIPE CULVERTS, CLASS ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK 120 LF 18" CS PIPE CULVERTS, 0.064" | 4 3 3 1,570 830 150 1,537.5 1,537.5 5 2 4 6 4 2,582 6 | EA EA LF SY LF LF LF EA EA EA EA LF EA | (E) FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** (F) FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** (G) FRAME WITH COVER, STD 840.54 2'-6" CONCRETE CURB & GUTTER 4" CONCRETE SIDEWALK PRECAST REINFORCED CONCRETE BARRIER, SINGLE FACED STEEL BM GUARDRAIL STEEL BM GUARDRAIL, DOUBLE FACED ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 GUARDRAIL ANCHOR UNITS, TYPE 350 GUARDRAIL ANCHOR UNITS, TYPE |
|---|---|--|--|
| Lump Sum | 3 1,570 830 150 1,537.5 1,537.5 2 4 6 4 2,582 | EA LF SY LF LF EA EA EA | (F) FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** (G) FRAME WITH COVER, STD 840.54 2'-6" CONCRETE CURB & GUTTER 4" CONCRETE SIDEWALK PRECAST REINFORCED CONCRETE BARRIER, SINGLE FACED STEEL BM GUARDRAIL STEEL BM GUARDRAIL STEEL BM GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| Lump Sum | 3 1,570 830 150 1,537.5 1,537.5 2 4 6 4 2,582 | EA LF SY LF LF EA EA EA | FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** (G) FRAME WITH COVER, STD 840.54 2'-6" CONCRETE CURB & GUTTER 4" CONCRETE SIDEWALK PRECAST REINFORCED CONCRETE BARRIER, SINGLE FACED STEEL BM GUARDRAIL STEEL BM GUARDRAIL, DOUBLE FACED ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 100 | 1,570 830 150 1,537.5 1,537.5 5 2 4 6 4 2,582 | LF SY LF LF EA EA EA | FRAME WITH COVER, STD 840.54 2'-6" CONCRETE CURB & GUTTER 4" CONCRETE SIDEWALK PRECAST REINFORCED CONCRETE BARRIER, SINGLE FACED STEEL BM GUARDRAIL STEEL BM GUARDRAIL, DOUBLE FACED ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| Lump Sum | 1,570 830 150 1,537.5 1,537.5 5 2 4 6 4 2,582 | LF SY LF LF EA EA EA | 2'-6" CONCRETE CURB & GUTTER 4" CONCRETE SIDEWALK PRECAST REINFORCED CONCRETE BARRIER, SINGLE FACED STEEL BM GUARDRAIL STEEL BM GUARDRAIL, DOUBLE FACED ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 1 ACR SUPPLEMENTARY CLEARING & GRUBBING 250 CY UNDERCUT EXCAVATION 200 TON CLASS IV SUBGRADE STABILIZATION 540 CY DRAINAGE DITCH EXCAVATION 950 SY FABRIC FOR SOIL STABILIZATION 143 TON FOUNDATION CONDITIONING MATERIAL, MINOR STRS 450 SY FOUNDATION CONDITIONING FABRIC 196 LF 15" SIDE DRAIN PIPE 244 LF **** RC PIPE CULVERTS, CLASS ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | 830 150 1,537.5 1,537.5 5 2 4 6 4 2,582 | SY LF LF EA EA EA | 4" CONCRETE SIDEWALK PRECAST REINFORCED CONCRETE BARRIER, SINGLE FACED STEEL BM GUARDRAIL STEEL BM GUARDRAIL, DOUBLE FACED ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 250 CY UNDERCUT EXCAVATION 200 TON CLASS IV SUBGRADE STABILIZATION 540 CY DRAINAGE DITCH EXCAVATION 950 SY FABRIC FOR SOIL STABILIZATION 143 TON FOUNDATION CONDITIONING MATERIAL, MINOR STRS 450 SY FOUNDATION CONDITIONING FABRIC 196 LF 15" SIDE DRAIN PIPE 244 LF **** RC PIPE CULVERTS, CLASS ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | 1,537.5 1,537.5 5 2 4 6 4 2,582 | LF LF EA EA EA | BARRIER, SINGLE FACED STEEL BM GUARDRAIL STEEL BM GUARDRAIL, DOUBLE FACED ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 200 TON CLASS IV SUBGRADE STABILIZA- TION 540 CY DRAINAGE DITCH EXCAVATION 950 SY FABRIC FOR SOIL STABILIZATION 143 TON FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS 450 SY FOUNDATION CONDITIONING FABRIC 196 LF 15" SIDE DRAIN PIPE 244 LF **** RC PIPE CULVERTS, CLASS ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, CLASS IV 15" CS PIPE CULVERTS, CLASS IV 15T CS PIPE CULVERTS, CLASS IV | 1,537.5 5 2 4 6 4 2,582 | EA EA EA | STEEL BM GUARDRAIL STEEL BM GUARDRAIL, DOUBLE FACED ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| TION 540 CY DRAINAGE DITCH EXCAVATION 950 SY FABRIC FOR SOIL STABILIZATION 143 TON FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS 450 SY FOUNDATION CONDITIONING FABRIC 196 LF 15" SIDE DRAIN PIPE 244 LF **** RC PIPE CULVERTS, CLASS ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, CLASS IV THICK | 1,537.5 5 2 4 6 4 2,582 | EA EA EA | STEEL BM GUARDRAIL, DOUBLE FACED ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 950 SY FABRIC FOR SOIL STABILIZATION 143 TON FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS 450 SY FOUNDATION CONDITIONING FABRIC 196 LF 15" SIDE DRAIN PIPE 244 LF **** RC PIPE CULVERTS, CLASS ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | 5 2 4 6 4 2,582 | EA EA EA EA | FACED ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 143 TON FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS 450 SY FOUNDATION CONDITIONING FABRIC 196 LF 15" SIDE DRAIN PIPE 244 LF **** RC PIPE CULVERTS, CLASS ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, CLASS IV THICK | 2 4 6 4 2,582 | EA EA EA | GUARDRAIL ANCHOR UNITS, TYPE CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| RIAL, MINOR STRS 450 SY FOUNDATION CONDITIONING FABRIC 196 LF 15" SIDE DRAIN PIPE 244 LF **** RC PIPE CULVERTS, CLASS ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | 4 6 4 2,582 | EA EA | CAT-1 GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 450 SY FOUNDATION CONDITIONING FABRIC 196 LF 15" SIDE DRAIN PIPE 244 LF ***" RC PIPE CULVERTS, CLASS ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | 6 4 2,582 | EA EA | GUARDRAIL ANCHOR UNITS, TYPE III GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 244 LF ***" RC PIPE CULVERTS, CLASS ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | 4 2,582 | EA | GUARDRAIL ANCHOR UNITS, TYPE 350 |
| ****** (18", V) 84 LF 15" RC PIPE CULVERTS, CLASS III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | 4 2,582 | EA | 350 |
| 84 LF 15" RC PIPE CULVERTS, CLASS III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | 2,582 | | |
| III 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | | IE | |
| 204 LF 18" RC PIPE CULVERTS, CLASS IV 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | | | B-77 |
| 392 LF 24" RC PIPE CULVERTS, CLASS IV 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | 0 | EA | REMOVE EXISTING GUARDRAIL |
| 92 LF 15" CS PIPE CULVERTS, 0.064" THICK | | EA | GUARDRAIL ANCHOR UNITS, TYPE 350 TEMPORARY |
| | 9 | TON | RIP RAP, CLASS B |
| 120 TE 18" CS PIPE CTIL VERTS 0.064" | 495 | SY | FILTER FABRIC FOR DRAINAGE |
| THICK | 105 3 | LF EA | SUPPORTS, 3-LB STEEL U-CHANNEL SIGN ERECTION, TYPE E |
| 16 LF 24" CS PIPE CULVERTS, 0.064" | 4 | EA | SIGN ERECTION, TYPE E |
| THICK | 9 | EA | DISPOSAL OF SIGN SYSTEM, U- |
| 2 EA **" CS PIPE ELBOWS, *****" THICK | | | CHANNEL |
| (15", 0.064") | 404 558 | SF SF | WORK ZONE SIGNS (STATIONARY) WORK ZONE SIGNS (PORTABLE) |
| 2 EA **" CS PIPE ELBOWS, *****" THICK | 157 | SF | WORK ZONE SIGNS (FORTABLE) WORK ZONE SIGNS (BARRICADE |
| (18", 0.064") | | | MOUNTED) |
| 2 EA **" CS PIPE ELBOWS, *****" | 2 | EA | FLASHING ARROW PANELS, TYPE C |
| THICK (24", 0.064") | 240 | DAY | CHANGEABLE MESSAGE SIGN (SHORT TERM) |
| 1,069 LF PIPE REMOVAL | 510 | EA | DRUMS |
| 2 EA PIPE CLEAN-OUT | 115 | LF | BARRICADES (TYPE III) |
| 100 TON INCIDENTAL STONE BASE 710 TON ASPHALT CONC BASE COURSE, TYPE | 2 2 | EA EA | TEMPORARY CRASH CUSHIONS TMIA |
| 710 TON ASPHALT CONC BASE COURSE, TYPE B25.0B | 670 | LF | PORTABLE CONCRETE BARRIER |
| 2,420 TON ASPHALT CONC BASE COURSE, TYPE | 480 | HR | LAW ENFORCEMENT |
| B25.0C 520 TON ASPHALT CONC INTERMEDIATE | 52 | EA | TEMPORARY RAISED PAVEMENT |
| COURSE, TYPE 119.0B | 18,452 | LF | MARKERS PAINT PAVEMENT MARKING LINES |
| 1,010 TON ASPHALT CONC INTERMEDIATE | , | | (6") |
| COURSE, TYPE 119.0C 510 TON ASPHALT CONC SURFACE COURSE, | 4,650 | LF | POLYUREA PAVEMENT MARKING LINES (4", ********) |
| TYPE S9.5B | | | (HIGHLY REFLECTIVE ELEMENTS) |
| 600 TON ASPHALT CONC SURFACE COURSE, | 4,612 | LF | |
| TYPE S9.5C 780 TON ASPHALT CONC SURFACE COURSE, | | | LINES (6", *********) (HIGHLY REFLECTIVE ELEMENTS) |
| TYPE S9.5D | 4,612 | LF | REMOVAL OF PAVEMENT MARKING |
| 280 TON ASPHALT BINDER FOR PLANT MIX | 02 | EA | LINES (6") |
| 45 TON POLYMER MODIFIED ASPHALT BIN- DER FOR PLANT MIX | 93 2,650 | EA LF | SNOWPLOWABLE PAVEMENT MARKERS TEMPORARY SILT FENCE |
| 800 SY GENERIC PAVING ITEM | | TON | STONE FOR EROSION CONTROL, |
| MILLING CONCRETE PAVEMENT, 0" TO 1-1/2" DEPTH | | | CLASS A |
| 56 CY SUBDRAIN EXCAVATION | 290 | TON | STONE FOR EROSION CONTROL, CLASS B |
| 42 CY SUBDRAIN FINE AGGREGATE | 320 | TON | SEDIMENT CONTROL STONE |
| 250 LF 6" PERFORATED SUBDRAIN PIPE | | | TEMPORARY MULCHING |
| 1 EA SUBDRAIN PIPE OUTLETS 6 LF 6" OUTLET PIPE (SUBDRAINS) | 200 | LB | SEED FOR TEMPORARY SEEDING |
| 1.79 CY PIPE COLLARS | 1.75 | ION | FERTILIZER FOR TEMPORARY SEED- ING |
| 21 EA MASONRY DRAINAGE STRUCTURES | 500 | LF | TEMPORARY SLOPE DRAINS |
| 7.48 LF MASONRY DRAINAGE STRUCTURES | 8 | EA | INLET PROTECTION AT TEMPORARY |
| 2 EA FRAME WITH TWO GRATES, STD 840.16 | 1,000 | LF | SLOPE DRAINS SAFETY FENCE |
| 7 EA FRAME WITH TWO GRATES, STD | 550 | CY | SILT EXCAVATION |
| 840.22 | 5,500 | SY | MATTING FOR EROSION CONTROL |
| | 10 | SY | COIR FIBER MAT |

| 800 | SY | PERMANENT SOIL REINFORCEMENT MAT |
|------|-----|----------------------------------|
| 950 | LF | 1/4" HARDWARE CLOTH |
| 525 | LF | WATTLE |
| 140 | LB | POLYACRYLAMIDE (PAM) |
| 130 | LF | COIR FIBER BAFFLE |
| 1 | EA | **" SKIMMER |
| | | (1-1/2") |
| 6 | ACR | SEEDING & MULCHING |
| 3 | ACR | MOWING |
| 50 | LB | SEED FOR REPAIR SEEDING |
| 0.25 | TON | FERTILIZER FOR REPAIR SEEDING |
| 125 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| 3.75 | TON | FERTILIZER TOPDRESSING |
| 30 | MHR | SPECIALIZED HAND MOWING |
| 30 | EA | RESPONSE FOR EROSION CONTROL |
| | | |

WALL ITEMS

5,728 SF MSE RETAINING WALLS

STRUCTURE ITEMS

| Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE AT STATION ********* |
|----------|----|---|
| | | (24+46.07-L-) |
| Lump Sum | LS | FOUNDATION EXCAVATION FOR BENT |
| | | ** AT STATION ******** |
| | | (1,24+46.07-L-) |
| 3 | EA | PDA TESTING |
| 3 | EA | PDA ASSISTANCE |
| 10,332 | SF | REINFORCED CONCRETE DECK SLAB |
| 7,864 | SF | GROOVING BRIDGE FLOORS |
| 229.1 | CY | CLASS A CONCRETE (BRIDGE) |
| Lump Sum | LS | BRIDGE APPROACH SLABS, STATION ************************************ |
| | | (24+46.07-L-) |
| 33,941 | LB | REINFORCING STEEL (BRIDGE) |
| 1,650 | LB | SPIRAL COLUMN REINFORCING |
| | | STEEL (BRIDGE) |
| 1,103.75 | LF | MODIFIED 63" PRESTRESSED CONC GIRDERS |
| 1,850 | LF | HP12X53 STEEL PILES |
| 40 | EA | PILE REDRIVES |
| 435.385 | LF | THREE BAR METAL RAIL |
| 40 | SY | 4" SLOPE PROTECTION |
| Lump Sum | LS | ELASTOMERIC BEARINGS |
| Lump Sum | LS | EVAZOTE JOINT SEALS |
| - | | |

Page: 54 of 62

L120117 040

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202876 41892.3.1 DIV OFFICE SYLVA LENGTH = 3.500 MI

COUNTY : JACKSON

PAVEMENT REHABILITATION.

DBE GOAL 11.0% COMPLETION DATE: OCT 15 2012

US-23/441 FROM EAST OF SR-1310 TO SR-1365.

| Lump Sum | LS | MOBILIZATION |
|----------|-----|--|
| 14 | SMI | SHOULDER RECONSTRUCTION |
| 91,135 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (2-1/2") |
| 124,128 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (4") |
| 29,927 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0C |
| 22,326 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5C |
| 2,626 | TON | ASPHALT BINDER FOR PLANT MIX |
| 14 | EA | GENERIC DRAINAGE ITEM REPLACE CONCRETE APRON |
| 33 | EA | GENERIC DRAINAGE ITEM SEAL EXISTING DROP INLET |
| 9,500 | LF | STEEL BM GUARDRAIL |
| 175 | LF | STEEL BM GUARDRAIL, SHOP CURVED |
| 5 | EA | ADDITIONAL GUARDRAIL POSTS |
| 16 | EA | GUARDRAIL ANCHOR UNITS, TYPE CAT-1 |
| 2 | EA | GUARDRAIL ANCHOR UNITS, TYPE III |
| 17 | EA | GUARDRAIL ANCHOR UNITS, TYPE 350 |
| 9,656.25 | LF | REMOVE EXISTING GUARDRAIL |
| 288 | SF | WORK ZONE SIGNS (STATIONARY) |
| 96 | SF | WORK ZONE SIGNS (PORTABLE) |
| 1 | EA | FLASHING ARROW BOARD |
| 2 | EA | PORTABLE CHANGEABLE MESSAGE SIGN |
| 80 | EA | DRUMS |
| 1 | EA | TMA |
| 220 | EA | SKINNY DRUM |
| 80,028 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 9,706 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 380 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 54 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 84,630 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 846 | EA | SNOWPLOWABLE PAVEMENT MARKERS |

Page: 55 of 62

L120117 041

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202877 41893.3.1 DIV OFFICE SYLVA LENGTH = 5.000 MI

COUNTY : JACKSON

PAVEMENT REHABILITATION.

DBE GOAL 9.0% COMPLETION DATE: OCT 15 2012

US-23/74 FROM US-23 BUS TO SR-1705 PAVEMENT REHAB.

| Lump Sum | LS | MOBILIZATION |
|----------|-----|---|
| 21.84 | SMI | SHOULDER RECONSTRUCTION |
| 104,960 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (3") |
| 83,894 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (4") |
| 9,019 | SY | MILLING ASPHALT PAVEMENT, ***" DEPTH (8") |
| 4,211 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0B |
| 1,656 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0B |
| 36,820 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0C |
| 1,419 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5B |
| 24,576 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5C |
| 3,561 | TON | ASPHALT BINDER FOR PLANT MIX |
| 105,600 | LF | MILLED RUMBLE STRIPS (ASPHALT CONCRETE) |
| 432 | SF | WORK ZONE SIGNS (STATIONARY) |
| 96 | SF | WORK ZONE SIGNS (PORTABLE) |
| 2 | EA | FLASHING ARROW BOARD |
| 3 | EA | PORTABLE CHANGEABLE MESSAGE SIGN |
| 100 | EA | DRUMS |
| 2 | EA | TMA |
| 600 | EA | SKINNY DRUM |
| 113,379 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 13,200 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 1,011 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (8", 90 MILS) |
| 480 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (24", 120 MILS) |
| 84 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) |
| 117,478 | LF | PAINT PAVEMENT MARKING LINES (4") |
| 340 | LF | PAINT PAVEMENT MARKING LINES (8") |
| 752 | EA | SNOWPLOWABLE PAVEMENT MARKERS |
| Lump Sum | LS | PORTABLE LIGHTING |

Page: 56 of 62

L120117 042

FEDERAL AID PROPOSAL, CONTRACTOR LICENSE NOT REQUIRED TO BID

CONTRACT ID: C202899 45438.3.13 DIV OFFICE SYLVA LENGTH = 0.270 MI

COUNTY: HAYWOOD BRIDGE PRESERVATION.

DBE GOAL 0.0% COMPLETION DATE: SEE SPECIAL PROVISIONS

BRIDGES #124, 142, 171, 205, AND 208 ON I-40.

| Lump Sum | LS | MOBILIZATION |
|----------|----|--|
| 224 | SF | WORK ZONE SIGNS (PORTABLE) |
| 1 | EA | FLASHING ARROW BOARD |
| 2 | EA | PORTABLE CHANGEABLE MESSAGE SIGN |
| 60 | EA | DRUMS |
| 240 | HR | FLAGGER |
| 1 | EA | TMA |
| Lump Sum | LS | GENERIC STRUCTURE ITEM BRIDGE JACKING |
| Lump Sum | LS | GENERIC STRUCTURE ITEM CLEANING AND REPAINTING BRIDGE #124 |
| Lump Sum | LS | GENERIC STRUCTURE ITEM CLEANING AND REPAINTING BRIDGE #142 |
| Lump Sum | LS | GENERIC STRUCTURE ITEM CLEANING AND REPAINTING BRIDGE #171 |
| Lump Sum | LS | GENERIC STRUCTURE ITEM CLEANING AND REPAINTING BRIDGE #205 |
| Lump Sum | LS | GENERIC STRUCTURE ITEM CLEANING AND REPAINTING BRIDGE #208 |
| Lump Sum | LS | GENERIC STRUCTURE ITEM DECK DRAIN MODIFICATION |
| Lump Sum | LS | GENERIC STRUCTURE ITEM POLLUTION CONTROL |
| Lump Sum | LS | GENERIC STRUCTURE ITEM UNDERSTRUCTURE WORK PLATFORM |
| 476 | LF | GENERIC STRUCTURE ITEM EPOXY RESIN INJECTION |
| 143 | CF | GENERIC STRUCTURE ITEM CONCRETE REPAIRS |
| 408 | CF | GENERIC STRUCTURE ITEM SHOTCRETE REPAIRS |
| 5,785 | LB | GENERIC STRUCTURE ITEM STRUCTURAL STEEL REPAIRS |
| 200 | EA | GENERIC STRUCTURE ITEM BOLT REMOVAL AND REPLACEMENT |

Page: 57 of 62

L120221 001

STATE FUNDED PROPOSAL, CONTRACTOR LICENSE REQUIRED TO BID

CONTRACT ID: C200800 34418.3.5 DIV OFFICE GREENSBORO LENGTH = 13.231 MI

COUNTY: GUILFORD, ROCKINGHAM

WIDENING, GRADING, DRAINAGE, PAVING, SIGNALS, & STRUCTURES.

DBE GOAL 13.0% COMPLETION DATE: DEC 27 2016

US-220 FROM SR-2182 (HORSEPEN CREEK RD) TO EXISTING NC-68 & US-220 INTERSECTION.

| | | ROADWAY ITEMS | 35 | EA | **" SIDE DRAIN PIPE ELBOWS (15") |
|----------------------|-----------|--|----------------|----------|---|
| | | | 22 | EA | **" SIDE DRAIN PIPE ELBOWS (18") |
| Lump Sum Lump Sum | LS LS | MOBILIZATION CONSTRUCTION SURVEYING | 10 | EA | **" SIDE DRAIN PIPE ELBOWS (24") |
| Lump Sum | LS ACR | CLEARING & GRUBBING ACRE(S) SUPPLEMENTARY CLEARING & GRUB- | 2 | EA | **" SIDE DRAIN PIPE ELBOWS (36") |
| 9 | EA | BING SEALING ABANDONED WELLS | 16 | LF | 12" RC PIPE CULVERTS, CLASS |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | 4,264 | LF | 15" RC PIPE CULVERTS, CLASS III |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | 5,000 | LF LF | 18" RC PIPE CULVERTS, CLASS III |
| Lump Sum | LS | (11+43,200 US 220 SB RAMP) REINFORCED BRIDGE APPROACH | 2,748 1,424 | LF | 24" RC PIPE CULVERTS, CLASS III 30" RC PIPE CULVERTS, CLASS |
| • | | FILL, STATION ************************************ | 668 | LF | III 36" RC PIPE CULVERTS, CLASS |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | 368 | LF | III 42" RC PIPE CULVERTS, CLASS |
| Lump Sum | LS | (114+28.00-L-SB) REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | 292 | LF | III 48" RC PIPE CULVERTS, CLASS III |
| Lump Sum | LS | (134+30.00-L-NB) REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | 1,052 | LF | 54" RC PIPE CULVERTS, CLASS III |
| Lump Sum | LS | (134+30.00-L-SB) REINFORCED BRIDGE APPROACH | 240 | LF | 66" RC PIPE CULVERTS, CLASS III |
| Jump Dum | 2.5 | FILL, STATION ************************************ | 112 | LF | ****" RC PIPE CULVERTS, CLASS IV |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ********** | 8,420 | LF | (48") 15" RC PIPE CULVERTS, CLASS IV |
| | | (24+37.000 -L REV- NBL) | 1,196 | LF | 18" RC PIPE CULVERTS, CLASS IV |
| ump Sum | LS | REINFORCED BRIDGE APPROACH | 804 | LF | 24" RC PIPE CULVERTS, CLASS IV |
| | | FILL, STATION ************************************ | 452 | LF | 30" RC PIPE CULVERTS, CLASS IV |
| C | LS | (24+37.000 -L REV- SBL) REINFORCED BRIDGE APPROACH | 344 | LF | 36" RC PIPE CULVERTS, CLASS IV |
| Lump Sum | LS | FILL, STATION ************************************ | 380 2 | LF EA | 42" RC PIPE CULVERTS, CLASS IV **" PIPE END SECTION |
| Lump Sum | LS | REINFORCED BRIDGE APPROACH FILL, STATION ************************************ | 176 | LF | (15") **" CAA PIPE CULVERTS, *****" THICK |
| 33,860 | CY | UNDERCUT EXCAVATION | 136 | LF | (18", 0.064") **" CAA PIPE CULVERTS, *****" |
| 8,300 | CY | SHALLOW UNDERCUT | 150 | Li | THICK |
| 16,550 | TON | CLASS IV SUBGRADE STABILIZA- TION | 120 | LF | (72", 0.168") **" CS PIPE CULVERTS, *****" |
| 18,200 | CY | DRAINAGE DITCH EXCAVATION | | | THICK |
| 4,255 104,515 | LF SY | BERM DITCH CONSTRUCTION REMOVAL OF EXISTING ASPHALT PAVEMENT | 32 | LF | (36", 0.079") **" CS PIPE CULVERTS, *****" THICK |
| 40,940 | SY | BREAKING OF EXISTING ASPHALT PAVEMENT | 160 | LF | (48", 0.109") **" CS PIPE CULVERTS, *****" |
| 120 | HR | PROOF ROLLING | | | THICK (72", 0.168") |
| 29,320 | CY SY | SELECT GRANULAR MATERIAL | 1,852 | LF | 15" CS PIPE CULVERTS, 0.064" |
| 68,920 18,509 | SF | FABRIC FOR SOIL STABILIZATION TEMPORARY SHORING | | | THICK |
| 24,020 | TON | ROCK EMBANKMENTS | 160 | LF | 18" CS PIPE CULVERTS, 0.064" THICK |
| 5,400 100 | SY CY | ROCK PLATING GENERIC GRADING ITEM | 240 | LF | 30" CS PIPE CULVERTS, 0.079" THICK |
| | | EXCAVATION AND STOCKPILING CONTAMINATED SOIL | 31 | EA | **" CS PIPE ELBOWS, *****" THICK |
| 1,675 | SY | GENERIC GRADING ITEM FABRIC FOR EMBANKMENT STABILIZATION | 7 | EA | (15", 0.064") **" CS PIPE ELBOWS, *****" THICK |
| 11,650 | SY | GENERIC GRADING ITEM FILTER FABRIC FOR ROCK EMBANK- MENT | 4 | EA | (18", 0.064") **" CS PIPE ELBOWS, *****" THICK |
| Lump Sum | LS | GENERIC GRADING ITEM SUBGRADE IMPROVEMENT FIELD TEST | 2 | EA | (30", 0.079") **" CS PIPE ELBOWS, *****" THICK |
| 6,140 | TON | FOUNDATION CONDITIONING MATE- RIAL, MINOR STRS | 96 | LF | (36", 0.079") **" WELDED STEEL PIPE, ****" |
| 19,210 | SY | FOUNDATION CONDITIONING FABRIC | ,,, | - | THICK, GRADE ** IN SOIL |
| 3,100 | LF | **" SIDE DRAIN PIPE | 2.50 | ır | (18", 0.5", B) |
| 180 | LF | (30") **" SIDE DRAIN PIPE (36") | 260 | LF | **" WELDED STEEL PIPE, ****" THICK, GRADE ** IN SOIL (24", 0.5", B) |
| | LF | 15" SIDE DRAIN PIPE | 340 | LF | **" WELDED STEEL PIPE, ****" |
| 11.576 | | | | | |
| 11,576 6,924 | LF | 18" SIDE DRAIN PIPE | | | THICK, GRADE ** IN SOIL (36", 0.5", B) |

| | | | 5,159 | LF | PRECAST REINFORCED CONCRETE BARRIER, SINGLE FACED |
|---------------|------------|---|----------------|----------|---|
| | | | 44 | EA | GENERIC PAVING ITEM |
| 172 | LF | **" WELDED STEEL PIPE, ****" | | | CONCRETE CURB RAMPS |
| 1/2 | LI | THICK, GRADE ** IN SOIL | 3 | EA | ADJUSTMENT OF MANHOLES |
| 100 | T.F. | (42", 0.625", B) | 4 | EA EA | ADJUSTMENT OF MANHOLES IMPACT ATTENUATOR UNIT, TYPE |
| 108 | LF | **" WELDED STEEL PIPE, ****" THICK, GRADE ** IN SOIL | •• | | 350 |
| | | (54", 0.75", B) | 34,962.5 | LF | STEEL BM GUARDRAIL |
| 50 | LF | **" WELDED STEEL PIPE, ****" THICK, GRADE ** NOT IN SOIL | 862.5 | LF | STEEL BM GUARDRAIL, SHOP CURVED |
| | | (42", 0.625", B) | 16 | EA | STEEL BM GUARDRAIL TERMINAL |
| 88 | LF | GENERIC PIPE ITEM | 20 | | SECTIONS |
| | | 15" CS SLOTTED DRAIN, 0.064" THICK | 20 11 | EA EA | ADDITIONAL GUARDRAIL POSTS GUARDRAIL ANCHOR UNITS, TYPE |
| 1 | EA | GENERIC PIPE ITEM | 11 | Lit | AT-1 |
| 11,545 | LF | 15" FLAP GATE PIPE REMOVAL | 30 | EA | GUARDRAIL ANCHOR UNITS, TYPE |
| 11,545 | EA | PIPE CLEAN-OUT | 8 | EA | CAT-1 GUARDRAIL ANCHOR UNITS, TYPE |
| 510 | SY | 6" SLOPE PROTECTION | v | | III |
| Lump Sum | LS | FINE GRADING | 89 | EA | GUARDRAIL ANCHOR UNITS, TYPE |
| 10,050 | TON | #57 STONE | 8 | EA | 350 GUARDRAIL ANCHOR UNITS, TYPE |
| 500 46,700 | TON TON | STABILIZER AGGREGATE AGGREGATE BASE COURSE | Ü | Lit | M-350 |
| 6,310 | TON | INCIDENTAL STONE BASE | 49 | EA | GUARDRAIL ANCHOR UNITS, TYPE |
| 15,000 | GAL | PRIME COAT | 6 266 | LF | B-77 REMOVE EXISTING GUARDRAIL |
| 11,080 | TON | ASPHALT CONC BASE COURSE, TYPE | 6,366 3,750 | LF | TEMPORARY STEEL BM GUARDRAIL |
| 7 200 | TON | B25.0B | 1 | EA | GUARDRAIL ANCHOR UNITS, TYPE |
| 7,280 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0B | | | ********** TEMPORARY |
| 25,690 | TON | ASPHALT CONC SURFACE COURSE, | 6 | EA | (W-BEAM) GUARDRAIL ANCHOR UNITS, TYPE |
| - 40 | moss | TYPE S9.5B | · · | LA | 350 TEMPORARY |
| 640 | TON | ASPHALT PLANT MIX, PAVEMENT REPAIR | 21,400 | LF | DOUBLE FACED CABLE GUIDERAIL |
| 390 | EA | RIGHT OF WAY MARKERS | 10 | EA | ADDITIONAL GUIDERAIL POSTS |
| 4,915 | CY | SUBDRAIN EXCAVATION | 131 95,220 | EA LF | CABLE GUIDERAIL ANCHOR UNITS |
| 2,460 | CY | SUBDRAIN FINE AGGREGATE | 5,800 | EA | WOVEN WIRE FENCE, 47" FABRIC 4" TIMBER FENCE POSTS, 7'-6" |
| 14,830 | LF | 6" PERFORATED SUBDRAIN PIPE | 3,000 | Lit | LONG |
| 31 204 | EA LF | SUBDRAIN PIPE OUTLETS 6" OUTLET PIPE (SUBDRAINS) | 1,870 | EA | 5" TIMBER FENCE POSTS, 8'-0" |
| 55 | TON | BLOTTING SAND | 1,310 | LF | LONG CHAIN LINK FENCE, 48" FABRIC |
| 83.8 | CY | ENDWALLS | 1,310 | EA | METAL LINE POSTS FOR 48" CHAIN |
| 42.5 | CY | REINFORCED ENDWALLS | | | LINK FENCE |
| 41.67 | CY | PIPE COLLARS | 10 | EA | METAL TERMINAL POSTS FOR 48" |
| 8.14 686 | CY CY | PIPE PLUGS FLOWABLE FILL | 6 | EA | CHAIN LINK FENCE METAL GATE POSTS FOR **" CHAIN |
| 475 | EA | MASONRY DRAINAGE STRUCTURES | Ü | Lit | LINK FENCE, SINGLE GATE |
| 52.18 | CY | MASONRY DRAINAGE STRUCTURES | | | (48") |
| 197.2 | LF | MASONRY DRAINAGE STRUCTURES | 6 | EA | SINGLE GATES, **" HIGH, **' WIDE. **' OPENING |
| 14 | EA | FRAME WITH GRATE, STD 840.22 | | | (48", 16', 16') |
| 51 | EA | FRAME WITH TWO GRATES, STD 840.16 | 115 | LF | GENERIC FENCING ITEM |
| 29 | EA | FRAME WITH TWO GRATES, STD | 2,530 | TON | PEDESTRIAN SAFETY RAIL RIP RAP, CLASS I |
| | | 840.20 | 110 | TON | RIP RAP, CLASS II |
| 206 | EA | FRAME WITH TWO GRATES, STD 840.22 | 5,690 | TON | RIP RAP, CLASS B |
| 18 | EA | FRAME WITH TWO GRATES, STD | 43,320 | SY | FILTER FABRIC FOR DRAINAGE |
| | | 840.24 | 4 | EA | PREFORMED SCOUR HOLES WITH LEVEL SPREADER APRON |
| 75 | EA | FRAME WITH TWO GRATES, STD 840.29 | 1 | EA | GENERIC EROSION CONTROL ITEM |
| 7 | EA | FRAME WITH GRATE & HOOD, STD | | | RIP RAP ENERGY DISSIPATOR |
| , | 2.1 | 840.03, TYPE ** | 8 | CY | REINFORCED CONCRETE SIGN FOUN- DATIONS |
| 22 | E.4 | (E) | 2 | CY | PLAIN CONCRETE SIGN FOUNDA- |
| 32 | EA | FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** | _ | | TIONS |
| | | (F) | 84 | CY | OVERHEAD FOOTING |
| 33 | EA | FRAME WITH GRATE & HOOD, STD 840.03, TYPE ** | 5,793 | LB LB | SUPPORTS, BREAKAWAY STEEL BEAM SUPPORTS, SIMPLE STEEL BEAM |
| | | (G) | 2,440 6,928 | LF | SUPPORTS, SIMPLE STEEL BEAM SUPPORTS, 3-LB STEEL U-CHANNEL |
| 31 | EA | FRAME WITH COVER, STD 840.54 | Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- |
| 5 | EA | CONCRETE TRANSITIONAL SECTION FOR CATCH BASIN | | | TURE AT STA ****** |
| 51 | EA | CONCRETE TRANSITIONAL SECTION | Lump Sum | LS | (26+40 -L REV-) SUPPORTS, OVERHEAD SIGN STRUC- |
| | | FOR DROP INLETS | Zamp bam | 2.0 | TURE AT STA ***** |
| 2 | EA | **" SLUICE GATE | | | (27+40 -L REV-) |
| 3 | EA | (25") **" SLUICE GATE | Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- TURE AT STA ****** |
| , | Lit | (38-3/4") | | | (33+60 -L REV-) |
| 5 | EA | GENERIC DRAINAGE ITEM | Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- TURE AT STA ****** |
| 2,280 | LF | TEMPORARY CONCRETE LIDS **"X **" CONCRETE CURB | | | (35+40 -L REV-) |
| 2,200 | LI | (8" X 18") | Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- |
| 21,740 | LF | 1'-6" CONCRETE CURB & GUTTER | | | TURE AT STA ****** (41+60 -L REV-) |
| 14,060 | LF | 2'-6" CONCRETE CURB & GUTTER | Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- |
| 14,100 | LF | SHOULDER BERM GUTTER CONCRETE EXPRESSWAY GUTTER | Zump Juni | | TURE AT STA ***** |
| 2,040 370 | LF LF | CONCRETE EXPRESSWAY GUTTER CONCRETE VALLEY GUTTER | T C | 10 | (50+00 -L REV-) |
| 6,860 | SY | 4" CONCRETE SIDEWALK | Lump Sum | LS | SUPPORTS, OVERHEAD SIGN STRUC- TURE AT STA ****** |
| 840 | SY | 6" CONCRETE DRIVEWAY | | | (75+00 -L REV-) |
| 250 | SY | 4" CONCRETE PAVED DITCH | 26 | EA | SIGN ERECTION, TYPE D |
| 85 | SY | 4" CONCRETE ISLAND COVERS | 412 90 | EA EA | SIGN ERECTION, TYPE E SIGN ERECTION, TYPE F |
| 20,890 | SY | 5" MONOLITHIC CONCRETE ISLANDS (KEYED IN) | 90 | ьA | SIGN ENDERFOR, TILET |
| | | | | | |

| | | | 1 | EA | GENERIC UTILITY ITEM |
|----------------|-----------|---|------------------|-----------|--|
| | | | | | TEMPORARY WATER LINE SUPPORT |
| 10 | EA | SIGN ERECTION, TYPE *** | 82,800 32,450 | LF TON | TEMPORARY SILT FENCE STONE FOR EROSION CONTROL, |
| 10 | LA | (GROUND MOUNTED) (A) | 20,825 | TON | CLASS A STONE FOR EROSION CONTROL, |
| 3 | EA | SIGN ERECTION, TYPE *** | 20,650 | | CLASS B SEDIMENT CONTROL STONE |
| | | (GROUND MOUNTED) (B) | 380 | | TEMPORARY MULCHING |
| 23 | EA | SIGN ERECTION, RELOCATE, TYPE **** (GROUND MOUNTED) | 11,900 52 | LB TON | SEED FOR TEMPORARY SEEDING FERTILIZER FOR TEMPORARY SEED- |
| | | (D) | | | ING |
| 4 | EA | SIGN ERECTION, RELOCATE, TYPE **** (GROUND MOUNTED) | 36,875 260 | LF EA | TEMPORARY SLOPE DRAINS INLET PROTECTION AT TEMPORARY |
| 2 | EA | (E) DISPOSAL OF SIGN SYSTEM, STEEL | | | SLOPE DRAINS |
| | | BEAM | 3,000 141,300 | LF CY | SAFETY FENCE SILT EXCAVATION |
| 307 | EA | DISPOSAL OF SIGN SYSTEM, U- CHANNEL | 352,200 | SY | MATTING FOR EROSION CONTROL |
| 3 27 | EA EA | DISPOSAL OF SIGN SYSTEM, WOOD DISPOSAL OF SUPPORT, U-CHANNEL | 17,970 21,675 | SY SY | COIR FIBER MAT PERMANENT SOIL REINFORCEMENT |
| 793 | SF | WORK ZONE SIGNS (STATIONARY) | 29,500 | LF | MAT 1/4" HARDWARE CLOTH |
| 1,124 2,705 | SF SF | WORK ZONE SIGNS (PORTABLE) WORK ZONE SIGNS (BARRICADE | 170 | LF | **" TEMPORARY PIPE |
| | | MOUNTED) | 7,800 | SY | (72") FLOATING TURBIDITY CURTAIN |
| 2 1,680 | EA DAY | FLASHING ARROW PANELS, TYPE C CHANGEABLE MESSAGE SIGN (SHORT | 1,130 | CY | STILLING BASINS |
| | | TERM) | 40 15,320 | EA LF | SPECIAL STILLING BASINS COIR FIBER WATTLE |
| 1,010 200 | EA EA | DRUMS CONES | 16,700 | LB | POLYACRYLAMIDE (PAM) |
| 2,940 | LF | BARRICADES (TYPE III) | 38,750 60 | LF EA | COIR FIBER BAFFLE **" SKIMMER |
| 2,880 20 | MD EA | FLAGGER TEMPORARY CRASH CUSHIONS | | | (1-1/2") |
| 6 | EA | RESET TEMPORARY CRASH CUSHIONS | 8 | EA | **" SKIMMER (2") |
| 4 6,140 | EA LF | TMIA PORTABLE CONCRETE BARRIER | 5 | EA | **" SKIMMER |
| 1,960 | LF | PORTABLE CONCRETE BARRIER | 4 | EA | (2-1/2") **" SKIMMER |
| 1,040 | LF | (DRAINAGE) RESET PORTABLE CONCRETE BAR- | 315 | ACP | (3") SEEDING & MULCHING |
| | | RIER | 380 | ACR | |
| 360 | LF | RESET PORTABLE CONCRETE BAR- RIER (DRAINAGE) | 7,520 16 | LB TON | SEED FOR REPAIR SEEDING FERTILIZER FOR REPAIR SEEDING |
| 2,665 | EA | TEMPORARY RAISED PAVEMENT MARKERS | 7,530 | LB | SEED FOR SUPPLEMENTAL SEEDING |
| 9,689 | LF | THERMOPLASTIC PAVEMENT MARKING | 225 1,300 | TON LF | FERTILIZER TOPDRESSING IMPERVIOUS DIKE |
| 1,976 | LF | LINES (8", 90 MILS) THERMOPLASTIC PAVEMENT MARKING | 500 | | SPECIALIZED HAND MOWING |
| 3,922 | LF | LINES (8", 120 MILS) THERMOPLASTIC PAVEMENT MARKING | 300 450 | EA CY | RESPONSE FOR EROSION CONTROL CULVERT DIVERSION CHANNEL |
| | LI | LINES (24", 120 MILS) | 40 | | REFORESTATION |
| 70 | EA | THERMOPLASTIC PAVEMENT MARKING CHARACTER (120 MILS) | 32 | EA | PEDESTRIAN SIGNAL HEAD (**", ** SECTION) |
| 432 | EA | THERMOPLASTIC PAVEMENT MARKING SYMBOL (90 MILS) | 20.220 | LE | (16", 1 SECTION W/ COUNTDOWN) |
| 5,560 | LF | COLD APPLIED PLASTIC PAVEMENT | 30,330 187 | LF EA | SIGNAL CABLE VEHICLE SIGNAL HEAD (12", 3 |
| | | MARKING LINES, TYPE ** (4") (IV) | 13 | EA | SECTION) VEHICLE SIGNAL HEAD (12", 4 |
| 1,070,768 | LF | PAINT PAVEMENT MARKING LINES (4") | | | SECTION) |
| 11,368 | LF | PAINT PAVEMENT MARKING LINES | 13 | EA | VEHICLE SIGNAL HEAD (12", 5 SECTION) |
| 6,480 | LF | (8") PAINT PAVEMENT MARKING LINES | 6,596 12,270 | LF LF | MESSENGER CABLE (1/4") MESSENGER CABLE (3/8") |
| 4 | EA | (24") PAINT PAVEMENT MARKING CHARAC- | 23,685 | LF | TRACER WIRE |
| | | TER | 13,810 | LF | UNPAVED TRENCHING (********) (1, 2") |
| 370 28,000 | EA LF | PAINT PAVEMENT MARKING SYMBOL REMOVAL OF PAVEMENT MARKING | 22,578 | LF | UNPAVED TRENCHING (*******) |
| 20 | EA | LINES (4") PERMANENT RAISED PAVEMENT | 510 | LF | (2, 2") DIRECTIONAL DRILL (********) |
| 28 | | MARKERS | 1,067 | LF | (1, 2") DIRECTIONAL DRILL (********) |
| 3,953 142 | EA EA | SNOWPLOWABLE PAVEMENT MARKERS FLEXIBLE DELINEATORS (CRYSTAL) | | | (2, 2") |
| 48 | EA | FLEXIBLE DELINEATORS (YELLOW) | 53 45 | EA EA | JUNCTION BOX (STANDARD SIZE) JUNCTION BOX (OVER-SIZED, HEA- |
| 20 | EA | FLEXIBLE DELINEATORS (CRYSTAL & RED) | 61 | EA | VY DUTY) WOOD POLE |
| 20 | EA | FLEXIBLE DELINEATORS (YELLOW & RED) | 143 | EA | GUY ASSEMBLY |
| Lump Sum | LS | PORTABLE LIGHTING | 2 | EA | ***" RISER WITH ************************************ |
| 214 361 | LF LF | 6" WATER LINE 8" WATER LINE | 4 | EA | 1/2" RISER WITH WEATHERHEAD |
| 99 | LF | 12" WATER LINE | 13 56 | EA EA | 1" RISER WITH WEATHERHEAD 2" RISER WITH WEATHERHEAD |
| 2 2 | EA EA | 8" VALVE 2" BLOW OFF | 4 | EA | 2" RISER WITH HEAT SHRINK |
| 1 | EA EA | 2" BLOW OFF RELOCATE WATER METER | 35,850 | LF | TUBING INDUCTIVE LOOP SAWCUT |
| 2 | EA | FIRE HYDRANT | 85,650 | LF | LEAD-IN CABLE (*********) |
| 10 8 | EA EA | RELOCATE FIRE HYDRANT GENERIC UTILITY ITEM | 7,000 | LF | (14-2) COMMUNICATIONS CABLE (**FIBER) |
| | | ADJUSTMENT OF SEWER MANHOLES | | | (24) |
| 120 6 | LF EA | ABANDON 12" UTILITY PIPE GENERIC UTILITY ITEM | 24,816 | LF | COMMUNICATIONS CABLE (**FIBER) (72) |
| | | ADJUSTMENT OF VALVE BOX | 2,621 | LF EA | DROP CABLE |
| 1 | EA | GENERIC UTILITY ITEM TEMPORARY SEWER LINE SUPPORT | 6 | EA EA | SPLICE ENCLOSURE INTERCONNECT CENTER |
| | | | 29 | EA | DELINEATOR MARKER |

29 EA DELINEATOR MARKER

Page: 60 of 62

| | | | 96,620 | GAI | ASPHALT CURING SEAL |
|----------------------|------------|--|----------------------|-----------|--|
| | | | 185,400 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0C |
| 2 | EA | 900MHZ WIRELESS RADIO SYSTEM | 116,680 | TON | ASPHALT CONC INTERMEDIATE COURSE, TYPE 119.0C |
| 6,000 | LF | REMOVE EXISTING COMMUNICATIONS CABLE | 102,500 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5C |
| 36 | EA EA | METAL STRAIN SIGNAL POLE | 22,230 | TON | ASPHALT BINDER FOR PLANT MIX |
| 36 306 | CY | SOIL TEST DRILLED PIER FOUNDATION | 96,810 | LF | MILLED RUMBLE STRIPS (ASPHALT |
| 7 | EA | SIGNAL PEDESTAL WITH FOUNDA- | 10,360 | LF | CEMENT CONCRETE) SHOULDER DRAIN |
| | | TION | 10,360 | LF | 4" SHOULDER DRAIN PIPE |
| 39 | EA | SIGN FOR SIGNALS | 670 | LF | 4" OUTLET PIPE FOR SHOULDER |
| 9 | EA EA | SIGNAL CABINET FOUNDATION CONTROLLER WITH CABINET (TYPE | | | DRAINS |
| , | LA | 2070L, BASE MOUNTED) | 15 | EA | CONCRETE PAD FOR SHOULDER DRAIN PIPE OUTLET |
| 7 | EA | CONTROLLER WITH CABINET (TYPE | 174,271 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 92 | EA | 2070L, POLE MOUNTED) | | | LINES (4", 90 MILS) |
| 92 | EA EA | DETECTOR CARD (TYPE 2070L) CABINET BASE EXTENDER | 103,293 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 120 MILS) |
| 2 | EA | BEACON CONTROLLER ASSEMBLY & | 76,731 | LF | THERMOPLASTIC PAVEMENT MARKING |
| | | CABINET (*******) (F3) | | | LINES (6", 90 MILS) |
| 7 | EA | TRAFFIC SIGNAL REMOVAL | 12,228 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (6", 120 MILS) |
| 5 | EA | GENERIC SIGNAL ITEM | 6,519 | LF | THERMOPLASTIC PAVEMENT MARKING |
| | | 30' WOOD POLE | | | LINES (12", 90 MILS) |
| 28 | EA | GENERIC SIGNAL ITEM 5/8" X 10' GROUNDING ELECTRODE | 1,112 | LF | COLD APPLIED PLASTIC PAVEMENT MARKING LINES, TYPE ** (4") |
| 4 | EA | GENERIC SIGNAL ITEM | | | (II) |
| _ | | 60' WOOD POLE | 1,965 | LF | COLD APPLIED PLASTIC PAVEMENT |
| 2 | EA | GENERIC SIGNAL ITEM 900 MHZ WIRELESS ETHERNET | | | MARKING LINES, TYPE ** (6") (II) |
| | | RADIO | 3,077 | LF | CURING COMPOUND REMOVAL, LINES |
| 4 | EA | GENERIC SIGNAL ITEM | 5 | EA | CURING COMPOUND REMOVAL, SYM- |
| 1 | EA | CCTV ASSEMBLY GENERIC SIGNAL ITEM | | | BOLS & CHARACTERS |
| 1 | LA | CENTRAL ETHERNET SWITCH | 1 527 094 | CY | *** OR *** |
| 4 | EA | GENERIC SIGNAL ITEM | 1,537,084 717,390 | CY | UNCLASSIFIED EXCAVATION BORROW EXCAVATION |
| 4 | EA | DIGITAL VIDEO DECODER | 118,310 | SY | LIME TREATED SOIL (SLURRY |
| 4 | EA | GENERIC SIGNAL ITEM DIGITAL VIDEO ENCODER | | | METHOD) |
| 4 | EA | GENERIC SIGNAL ITEM | 1,200 | TON | LIME FOR LIME TREATED SOIL |
| | Б.4 | EQUIPMENT CABINET DISCONNECT | 19,000 | TON | AGGREGATE FOR CEMENT TREATED BASE COURSE |
| 4 | EA | GENERIC SIGNAL ITEM FIELD EQUIPMENT CABINET | 760 | TON | |
| 4 | EA | GENERIC SIGNAL ITEM | 100 600 | CXZ | TREATED BASE COURSE |
| 2 | Б.4 | FIELD ETHERNET SWITCH | 188,680 5,220 | SY TON | SOIL CEMENT BASE PORTLAND CEMENT FOR SOIL CE- |
| 3 | EA | GENERIC SIGNAL ITEM FUNISH WIRELESS LIGHTNING | 3,220 | 1011 | MENT BASE |
| | | ARRESTOR | 2,030 | TON | AGGREGATE FOR SOIL CEMENT BASE |
| 2 | EA | GENERIC SIGNAL ITEM | 83,520 | GAL | |
| 4 | EA | FURNISH WIRELESS RADIO MODEM GENERIC SIGNAL ITEM | 133,200 | TON | ASPHALT CONC BASE COURSE, TYPE B25.0C |
| • | | LOCAL TRAFFIC SIGNAL SOFTWARE | 74,860 | TON | ASPHALT CONC INTERMEDIATE |
| 4 | EA | GENERIC SIGNAL ITEM | 40.480 | morr | COURSE, TYPE I19.0C |
| | | METER BASE/DISCONNECT COMBIN- ATION PANEL | 62,650 | TON | ASPHALT CONC SURFACE COURSE, TYPE S9.5C |
| 2 | EA | GENERIC SIGNAL ITEM | 9,120 | TON | ASPHALT CONC SURFACE COURSE, |
| 3 | EA | MODIFY SPLICE ENCLOSURE GENERIC SIGNAL ITEM | 16.620 | TON | TYPE SF9.5A |
| 3 | EA | RELOCATE SOLAR POWERED FLASHER | 16,630 16,690 | TON | ASPHALT BINDER FOR PLANT MIX PERMEABLE ASPHALT DRAINAGE |
| | | BEACON | 10,070 | 1011 | COURSE, TYPE P-57 |
| 4 | EA | GENERIC SIGNAL ITEM RELOCATE SOLAR POWERED SCHOOL | 6,770 | LF | MILLED RUMBLE STRIPS (ASPHALT |
| | | FLASHER | 182,150 | SY | CEMENT CONCRETE) *****" PORT CEM CONC PAVEMENT, |
| 6 | EA | GENERIC SIGNAL ITEM | 102,130 | 51 | THROUGH LANES (WITH DOWELS) |
| 2 | EA | SOLAR POWERED FLASHER BEACON GENERIC SIGNAL ITEM | 52.160 | CX7 | (11-1/2") |
| - | | SOLAR POWERED, 900 MHZ WIRE- | 52,160 | SY | *****" PORT CEM CONC PAVEMENT, MISCELLANEOUS (WITHOUT DOWELS) |
| 200 | LF | LESS ETHERNET REPEATER RADIO GENERIC SIGNAL ITEM | | | (11-1/2") |
| 280 | LF | #4 SOLID BARE COPPER GROUNDING | 62,020 | SY | *****" PORT CEM CONC PAVEMENT, MISCELLANEOUS (WITHOUT DOWELS) |
| | | CONDUCTOR | | | (8-1/2") |
| 358 | LF | GENERIC SIGNAL ITEM 3-WIRE #12 COPPER FEEDER CON- | 90,050 | LF | GENERIC PAVING ITEM |
| | | DUCTORS | | | MILLED RUMBLE STRIPS (CONCRETE SHOULDER) |
| 66 | LF | GENERIC SIGNAL ITEM | Lump Sum | LS | SURFACE TESTING CONCRETE PAVE- |
| | | 3-WIRE #3 COPPER SERVICE ENT- RANCE CONDUCTORS | | | MENT |
| | | | Lump Sum | LS | FIELD LABORATORY RENTAL, PORT CEM CONC PAVEMENT |
| | | | 47,610 | LF | SHOULDER DRAIN |
| | | ****** BEGIN SCHEDULE AA ****** | 47,610 | LF | 4" SHOULDER DRAIN PIPE |
| 1 656 625 | CV | ******* (2 ALTERNATES) ******* LINCLASSIEIED EXCAVATION | 2,540 | LF | 4" OUTLET PIPE FOR SHOULDER DRAINS |
| 1,656,635 659,050 | CY CY | UNCLASSIFIED EXCAVATION BORROW EXCAVATION | 50 | EA | CONCRETE PAD FOR SHOULDER |
| 136,010 | SY | LIME TREATED SOIL (SLURRY | | | DRAIN PIPE OUTLET |
| | | METHOD) | 160,029 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (4", 90 MILS) |
| 1,380 130,100 | TON TON | LIME FOR LIME TREATED SOIL AGGREGATE FOR CEMENT TREATED | 101,453 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 130,100 | ION | BASE COURSE | | | LINES (4", 120 MILS) |
| 5,210 | TON | PORTLAND CEMENT FOR CEMENT | 1,391 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (6", 90 MILS) |
| 229,960 | SY | TREATED BASE COURSE SOIL CEMENT BASE | 390 | LF | THERMOPLASTIC PAVEMENT MARKING |
| 6,360 | TON | PORTLAND CEMENT FOR SOIL CE- | | | LINES (6", 120 MILS) |
| | | MENT BASE | 945 | LF | THERMOPLASTIC PAVEMENT MARKING LINES (12", 90 MILS) |
| 2,540 | TON | AGGREGATE FOR SOIL CEMENT BASE | | | ·· () /· · · · · · · · · · · · · · · · · · |

Page: 61 of 62

| | | | Lump Sum | LS | FOUNDATION EXCAVATION FOR BENT ** AT STATION ************************************ |
|---------------|-----------|--|----------------------|-----------|---|
| 17,182 | LF | POLYUREA PAVEMENT MARKING | Lump Sum | LS | FOUNDATION EXCAVATION FOR BENT ** AT STATION ************************************ |
| | | LINES (4", *********) (HIGHLY REFLECTIVE ELEMENTS) | | | (1,70+09.407-LREV-) |
| 87,725 | LF | POLYUREA PAVEMENT MARKING | 687 198.1 | LF LF | PILE EXCAVATION IN SOIL 4'-0" DIA DRILLED PIERS IN SO |
| | | LINES (6", *********) (HIGHLY REFLECTIVE ELEMENTS) | 170.1 | Li | IL |
| 6,037 | LF | POLYUREA PAVEMENT MARKING | 85.3 | LF | 4'-0" DIA DRILLED PIERS NOT IN SOIL |
| | | LINES (12", *********) (HIGHLY REFLECTIVE ELEMENTS) | 842.9 | LF | **'_**" DIA DRILLED PIERS |
| 111,239 51 | LF EA | CURING COMPOUND REMOVAL, LINES CURING COMPOUND REMOVAL, SYM- | 127.3 | LF | (4'-6") PERMANENT STEEL CASING FOR **'-**" DIA DRILLED PIER |
| | | BOLS & CHARACTERS | 05.2 | T.F. | (4'-6") |
| | | *** END SCHEDULE AA *** | 85.3 | LF | PERMANENT STEEL CASING FOR 4'-0" DIA DRILLED PIER |
| | | CULVERT ITEMS | 9 | EA | SID INSPECTION |
| | | | 6 Lump Sum | EA LS | SPT TESTING UNCLASSIFIED STRUCTURE EXCAVA- |
| Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE | ī | | TION AT STATION ******* |
| 1 | | AT STATION ******** | Lump Sum | LS | (134+30.00-L-LT) UNCLASSIFIED STRUCTURE EXCAVA- |
| Lump Sum | LS | (56+36.00-L-) REMOVAL OF EXISTING STRUCTURE | | | TION AT STATION ************************************ |
| | | AT STATION ******** | 104,338 | SF | (24+37.000-LREV-RT) REINFORCED CONCRETE DECK SLAB |
| Lump Sum | LS | (56+54.000-LREV-) REMOVAL OF EXISTING STRUCTURE | 109,757.2 | SF | GROOVING BRIDGE FLOORS |
| | | AT STATION ************************************ | 1,639 Lump Sum | CY LS | CLASS A CONCRETE (BRIDGE) BRIDGE APPROACH SLABS, STATION |
| Lump Sum | LS | CULVERT EXCAVATION, STA ***** | Lump Sum | LO | ******* |
| I C | 1.0 | (168+50.00-L-) | Lump Sum | LS | (11+43.200-SB US 220 RAMP-) BRIDGE APPROACH SLABS, STATION |
| Lump Sum | LS | CULVERT EXCAVATION, STA ****** (247+02.00-L-) | Zump bum | | ******* |
| Lump Sum | LS | CULVERT EXCAVATION, STA ****** (56+36.00-L-) | Lump Sum | LS | (114+28.00-L-LT) BRIDGE APPROACH SLABS, STATION |
| Lump Sum | LS | CULVERT EXCAVATION, STA ***** | r | | ******* |
| 752 | TON | (56+54.000-LREV-) | Lump Sum | LS | (114+28.00-L-RT) BRIDGE APPROACH SLABS, STATION |
| 753 | TON | FOUNDATION CONDITIONING MATER- IAL, BOX CULVERT | | | ************************************** |
| 1,629.5 | CY | CLASS A CONCRETE (CULVERT) | Lump Sum | LS | (134+30.00-L-LT) BRIDGE APPROACH SLABS, STATION |
| 232,485 40 | LB TON | REINFORCING STEEL (CULVERT) RIP RAP, CLASS ** | | | ************************************** |
| | | (I) | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| Lump Sum | LS | GENERIC CULVERT ITEM PEDESTRIAN CULVERT CONDUIT | | | ************************************** |
| | | SYSTEM | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| Lump Sum | LS | GENERIC CULVERT ITEM PRECAST REINF CONC 3-SIDED | | | ************************************** |
| | | CULVERT STA 57+45.800 -LREV- | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| | | | | | ************************************** |
| | | WALL ITEMS | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| | | WALLTENS | | | (45+30.610-LREV-LT) |
| 2.106 | ar. | MGE DETTA DUDAG WALL G | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| 3,106 150 | SF SF | MSE RETAINING WALLS SOLDIER PILE RETAINING WALLS | | | (45+30.610-LREV-RT) |
| 91,406 | SF | GENERIC RETAINING WALL ITEM | Lump Sum | LS | BRIDGE APPROACH SLABS, STATION |
| | | SOUND BARRIER WALL | | | (70+09.407-LREV-) |
| | | | 372,468 47,117 | LB LB | REINFORCING STEEL (BRIDGE) SPIRAL COLUMN REINFORCING |
| | | STRUCTURE ITEMS | 47,117 | LD | STEEL (BRIDGE) |
| | | | 2,180.72 | LF | 45" PRESTRESSED CONCRETE GIR- DERS |
| Lump Sum | LS | CONSTRUCTION, MAINTENANCE, & | 4,252.52 | LF | 54" PRESTRESSED CONCRETE GIR- |
| Lump Sum | Lo | REMOVAL OF TEMP ACCESS AT STA | 1,424,837 | LS | DERS APPROX LBS STRUCTURAL |
| | | ************************************** | | | STEEL |
| Lump Sum | LS | CONSTRUCTION, MAINTENANCE, & | 7,393 280 | LF LF | HP12X53 STEEL PILES HP12X53 GALVANIZED STEEL PILES |
| | | REMOVAL OF TEMP ACCESS AT STA ************************************ | 1,015 | LF | HP14X73 GALVANIZED STEEL PILES |
| Lump Sum | LS | (134+30.00-L-RT) CONSTRUCTION, MAINTENANCE, & | 7 | EA | STEEL PILE POINTS |
| Lump Sum | Lo | REMOVAL OF TEMP ACCESS AT STA | 563.32 4,087.71 | LF LF | TWO BAR METAL RAIL CONCRETE BARRIER RAIL |
| | | ************************************** | 593.32 | LF | 1'-**"X *****" CONCRETE PARA- |
| Lump Sum | LS | CONSTRUCTION, MAINTENANCE, & | | | PET (1'-2" X 2'-6") |
| | | REMOVAL OF TEMP ACCESS AT STA ************************************ | 2,761 | SY | 4" SLOPE PROTECTION |
| I C | 1.0 | (24+37.000-LREV-RT) | 3,477 3,848 | TON SY | RIP RAP CLASS II (2'-0" THICK) FILTER FABRIC FOR DRAINAGE |
| Lump Sum | LS | REMOVAL OF EXISTING STRUCTURE AT STATION *********** | Lump Sum | LS | POT BEARINGS |
| I umn Cum | LS | (114+28.00-L-) REMOVAL OF EXISTING STRUCTURE | Lump Sum | LS | ELASTOMERIC BEARINGS |
| Lump Sum | Lo | AT STATION ********* | Lump Sum Lump Sum | LS LS | EVAZOTE JOINT SEALS EXPANSION JOINT SEALS |
| Lump Sum | LS | (120+38.50-L-) REMOVAL OF EXISTING STRUCTURE | Lump Sum | LS | ELECTRICAL CONDUIT SYSTEM AT |
| Lamp Suill | LO | AT STATION ******** | | | STA************************************ |
| Lump Sum | LS | (134+30.00-L-LT) REMOVAL OF EXISTING STRUCTURE | Lump Sum | LS | ELECTRICAL CONDUIT SYSTEM AT |
| mp built | | AT STATION ********* | | | STA**************************(134+30.00-L-LT) |
| Lump Sum | LS | (24+37.000-LREV-RT) REMOVAL OF EXISTING STRUCTURE | Lump Sum | LS | ELECTRICAL CONDUIT SYSTEM AT STA********* |
| • | | AT STATION ************************************ | | | STA************************************ |
| | | (13.30.010 ERET KT) | | | |

Page: 62 of 62

43 LF GENERIC STRUCTURE ITEM 30" CS PIPE, 0.168" THICK

7 EA GENERIC STRUCTURE ITEM CSL TESTING