



Executive Committee for Highway Safety
January 8, 2016



*Dynamic All-Red Extension
Preliminary Results*


Carrie L. Simpson, PE



Dynamic All Red Extension

The Problem

Frequency of Red-Light Violations as a Function of Time-Into-Red
(Bonneson & Zimmerman 2004)



Dynamic All Red Extension

How It Works


Signalized Intersection with:

- Yellow Interval: 5 seconds
- Default Red Interval: 1 second
- Alarm Time: 5 seconds
- Closest Loop is 240' from Stop Bar

Example Scenario:

1. Vehicle below crosses the loops at 3 seconds into the yellow interval
2. 5 second stop time is placed on the red interval
3. Vehicle has remaining 2 seconds of yellow, 1 second of default red, and 2 seconds of red extension = 5 seconds from the time they cross the loops.

Total All-Red Time: 3 sec



<http://www.shutterstock.com/pic-104301266/stock-photo-d-renderings-of-an-all-red-traffic-light.html>

Inductive Loop



<http://cronkitezine.asu.edu/specialprojects/photoenforcement/pages/technology.html>



Dynamic All Red Extension

Equipment

- Signal Controller: Oasis/2070
- Detection method – Two 6' X 6' inductive loops spaced 10' apart
- Northstar Controls Model NQ4 Speed Advisory System
 - Unit is typically placed in separate cabinet next to inductive loops
 - Loop outputs feed into inputs of NQ4 logic unit and determines if preset speed threshold has been violated (threshold varies by location – typically 5 mph below design speed)
 - We tweaked outputs from our NQ4 detector systems to get the controller to handle the necessary “holds”
 - Duration of alarm output is 5 sec

Costs

- Estimate \$5,000 per approach, using our detection method

First Installation: NC 11 @ NC 561 – Ahoskie



Dynamic All Red Extension

Project Timeline

February 2011

- Ahoskie Test Site Installed (Case Study Only – Not Included in Aggregated Results)

Fall 2012

- Eight Pilot Sites Selected & Signal Designs Completed
- Before Period Compliance Data Collected at Eight Pilot Sites

January – October 2013

- Eight Pilot Sites Installed

February 2013 - October 2014

- After Period Compliance Data Collected at Eight Pilot Sites (1, 3, 6 and 12-Mo.)

April 2015

- Preliminary Crash Results

2017

- Final Crash Results (3 years of After Data)
– consider waiting for additional Crash Data....



Dynamic All Red Extension

Pilot Study Locations

Site	Location Description	Treated Approaches	Distance to Loop (ft)	Yellow Interval (sec)	Default Red Interval (sec)	Signal Phase	Mainline Cross Section	Mainline AADT	Mainline Speed Limit (mph)
1	US 17 at US 158 and SR 1416, Pasquotank County	US 17 - Both	290	5.5-5.6	1.0-1.1	5	4 Lane Divided	17,000	60
2	US 17 at SR 1300, Perquimans County	US 17 - Both	290	5.5	2.0	6	4 Lane Divided	15,500	55
3	US 17/158 at SR 1333), Pasquotank County	US 17 - Both	290	5.5	1.0	2	4 Lane Divided	8,000	60
4	NC 24 at SR 1141/SR 1144, Carteret County	NC 24 - Both	240	5.3	1.1	3	5 Lane Undivided	18,500	55
5	US 17 at NC 904, Brunswick County	US 17 - Both	240	5.2-5.3	1.0-1.2	5	4 Lane Divided	22,000	55
6	US 70 Business at SR 2558, Wake County	US 70 Bus - Eastbound	240	5.2	1.2	6	4 Lane Divided	29,500	55
7	US 601 at NC 268, Surry County	US 601 - Both	155	4.3	1.0	2	2 Lane	4,800	45
8	US 52 at US 52 Business and SR 2011, Surry County	US 52 - Westbound	240	5.1	2.0	6	4 Lane Divided	14,500	55



Site 5



Dynamic All Red Extension

Study Design

Compliance Data:

- Video collected by Quality Counts, LLC at Eight Pilot Sites
- Collected 1-2 Days @ Before, 1 Mo After, 3 Mo After, 6 Mo After & 1 Yr After Period
- **OBSERVING CHANGES IN DRIVER BEHAVIOR/ADAPTATION OVER TIME**
- **CHECKING SYSTEM OPERATION**

Measures of Effectiveness

- Average Yellow Light Runners (YLR)
- Average Red Light Runners (RLR)
- Average Target* RLR

* Target RLR consists of vehicles we assume should receive an all-red extension, excluding vehicles entering the intersection during the default all-red clearance interval.



Dynamic All Red Extension

Study Design

Crash Data:

- 3 Years of Before & After Data at Test Site (Case Study Only – Not Included in Aggregated Results)
- Preliminary Results at Eight Pilot Sites - Currently 1-2 years of After Period Crash Data (Wait until 3 years of After Period Crash Data for Final Results)
- Selected sites with moderate Red Light Running crash patterns (1-3 crashes per year) – Expect Regression to the Mean to be a factor
- **EXPECT A DECREASE IN RED LIGHT RUNNING CRASHES**

Measures of Effectiveness


- Total Crashes
- Fatal and Injury Crashes
- Angle Crashes
- Rear End Crashes



Dynamic All Red Extension

Overall Results

Compliance Study YLR



^a Denotes a statistically significant ($p < 0.05$) change from pre installation to post-installation conditions using a two-tailed unpaired t-test.

Yellow Light Runner Data

Time Period	Observation Period (hours)	Number of Observations	Average YLR/Hour	Average YLR/1,000 veh	Average YLR/Cycle
Pre-installation	304	2173	7.15	22.36	0.186
1 Month Post-installation	255	1370	5.37 ^a	17.13 ^a	0.127 ^a
3 Month Post-installation	155	1010	6.52	20.32	0.147 ^a
6 Months Post-installation	155	1067	6.88	19.75	0.158
12 Months Post-installation	193	1295	6.71	22.35	0.141 ^a



Dynamic All Red Extension


Overall Results

Compliance Study RLR

^a Denotes a statistically significant ($p < 0.05$) change from pre installation to post-installation conditions using a two-tailed unpaired t-test.

Target RLR consist of vehicles that based on our assumptions should receive an all-red extension, excluding vehicles entering the intersection during the default all-red clearance interval. The side street movement (4+8) is the next phase served for Target RLR. We assume RLR hit loops traveling at/above the set speed, and maintain speeds at the posted speed limit.

Average Red Light Runner/Hour



Red Light Runner Data

Time Period	Observation Period (hours)	Number of Observations	Average RLR/Hour	Average RLR/1,000 veh	Average RLR/Cycle
Pre-installation	304	111	0.37	1.21	0.0089
1 Month Post-installation	255	113	0.44	1.30	0.0102
3 Month Post-installation	155	86	0.55 ^a	1.79	0.0121
6 Months Post-installation	155	93	0.60 ^a	1.74	0.0125 ^a
12 Months Post-installation	193	82	0.42	1.40	0.0088

Target Red Light Runner Data


Time Period	Observation Period (hours)	Number of Observations	Average RLR/Hour	Average RLR/1,000 veh	Average RLR/Cycle
Pre-installation	304	13	0.043	0.139	0.0010
1 Month Post-installation	255	10	0.039	0.145	0.0008
3 Month Post-installation	155	10	0.065	0.240	0.0012
6 Months Post-installation	155	9	0.058	0.159	0.0012
12 Months Post-installation	193	15	0.078	0.275	0.0016



Dynamic All Red Extension

Overall Results


Compliance Study: *Time into Red – Before* (111 RLR)



Dynamic All Red Extension

Overall Results

Compliance Study: *Time into Red – After* (374 RLR)



Dynamic All Red Extension

Overall Results

Usage Data (From Signal Logs)

Average Extensions/Hour range from 0.11 – 3.13
Average Length of Extension range from 1.4 – 3.2 seconds

Number of Extension Calls Per Approach

Signal ID	After Period	Hours Collected	Average Extensions Per Hour		Average Length of Extension (Sec)		Average Cycles Per Hour
			Phase 2	Phase 6	Phase 2	Phase 6	
01-0314	1 month	192	2.21*		n/a		46
	2 years	168	2.91*		n/a		45
01-0381	2 years	144	1.23	1.20	1.5	1.4	39
01-0658	1 month	336	0.33	0.93	n/a	n/a	47
	2 years	432	0.53	0.56	2.8	2.9	48
02-0470	1 month	240	1.11	0.93	n/a	n/a	41
03-0342	1 year	72	2.79	2.69	2.5	2.4	56
05-1142	6 months	168	2.93	-	2.9	-	32
	2 years	144	3.13	-	2.8	-	32
11-1090	3 months	1368	0.11	0.27	3.2	3.2	65
11-1093	2 months	192	2.54	-	2.7	-	55

*Average extensions for both approaches combined.



Dynamic All Red Extension

Conclusions – Compliance Study

- Comparing the before period to the final after period, there is **no statistically significant change in YLR and RLR/hour** in the overall sample
 - 1062 Hours (about 1.5 months) of video data is included from 7 sites
 - There were some significant increases in RLR at the 3 & 6 mo. marks
 - However, by final after period, appears to be minimal habituation...
- The system is **not going to capture all RLR crashes** - provides extra protection against angle crashes caused by a specific group of mainline RLR vehicles.
 - Of 374 observed RLR, 6 entered the intersection too late for an extension (3 of these were police or EMS with lights on)
- Vehicle conflicts are rare. Even with hundreds of hours of observation, there were **too few conflicts to evaluate**.
 - Observed 2 near misses in the after period. The vehicles were too late to receive the all red extension, entering the intersection at 6 sec and 9 sec.



Dynamic All Red Extension

Conclusions – Crash Analysis

- We need to **wait for more after crash data** before trying to draw conclusions.
- Preliminary results are **promising** for target angle crashes & severe injury crashes.
- If possible, we will try to draw a connection between system parameters and crash performance. Perhaps there is more benefit when the target window is larger and extends later in the red:
 - Larger Target Window - Design speed is closer to what drivers are actually traveling and the loops are placed further back (however, more False+)
 - Extends Later into Red – A longer default red clearance is used (1.5+ seconds) and later protection can be offered



Dynamic All Red Extension

Conclusions – Operations

- The system **can work** as designed.
 - There were 44 Target RLR in the after period sample – 89% (39 of 44) got an extension.
- The system **can remain in operation** for an extended period of time.
 - All sites were operating at the 2-year after mark
- Signals with Dynamic Red **require periodic monitoring**.
 - Like monitoring already required to maintain proper signal operation
 - 03-0342 @ 3 mo mark (relay switch failed – *unrelated* to DARE)
 - 01-0381 @ 3 & 6 mo mark (water backed up in conduit – *unrelated*)
 - 05-1142 @ 1 yr mark (signal phasing change/construction-*unrelated*)
 - Supervisor Circuit planned for future installations
- Minimal risk with system
 - If it's not working, the signal will revert to standard red interval
- More sites in development....



Dynamic All Red Extension

Video Clips

Target

<http://youtu.be/LKQCvtPFMsQ>

<https://youtu.be/qJ52wMowehM?list=PLFPISVRUEsJqDGOS458c2HfhYNY1QM4It>

<https://youtu.be/-pHBTIOoKEU?list=PLFPISVRUEsJqDGOS458c2HfhYNY1QM4It>

<https://youtu.be/FwjAiPbKKwA?list=PLFPISVRUEsJqDGOS458c2HfhYNY1QM4It>

<https://youtu.be/4kSvUbj4c5E?list=PLFPISVRUEsJqDGOS458c2HfhYNY1QM4It>

Non Target

<https://youtu.be/uRsEUNWd7vQ?list=PLFPISVRUEsJqDGOS458c2HfhYNY1QM4It>

