On survey related matters, initial contact, including requests for summaries of surveys, should be with the Wage and Hour Regional Office for the area in which the survey was conducted because those Regional Offices have responsibility for the Davis-Bacon survey program. If the response from this initial contact is not satisfactory, then the process described in 2.) and 3.) should be followed.

With regard to any other matter not yet ripe for the formal process described here, initial contact should be with the Branch of Construction Wage Determinations. Write to:

Branch of Construction Wage Determinations Wage and Hour Division U. S. Department of Labor 200 Constitution Avenue, N.W. Washington, D.C. 20210

2.) If the answer to the question in 1.) is yes, then an interested party (those affected by the action) can request review and reconsideration from the Wage and Hour Administrator (See 29 CFR Part 1.8 and 29 CFR Part 7). Write to:

Wage and Hour Administrator U.S. Department of Labor 200 Constitution Avenue, N.W. Washington, D.C. 20210


The request should be accompanied by a full statement of the interested party's position and by any information (wage payment data, project description, area practice material, etc.) that the requestor considers relevant to the issue.


3.) If the decision of the Administrator is not favorable, an interested party may appeal directly to the Administrative Review Board (formerly the Wage Appeals Board). Write to:

Administrative Review Board U. S. Department of Labor 200 Constitution Avenue, N.W. Washington, D.C. 20210

4.) All decisions by the Administrative Review Board are final.

END OF GENERAL DECISION





APPROX. AREA: CLASS II REPAIR

APPROX. AREA: CLASS III REPAIR

APPROX. TEST BORING LOCATION

NOTES

FOR REPAIR OF BRIDGE WITH LATEX MODIFIED CONCRETE, VERY EARLY STRENGTH, SEE SPECIAL PROVISIONS.

SEE SPECIAL PROVISIONS FOR SURFACE PREPARATION.

EXPANSION JOINTS SHALL BE COVERED WITH POLYETHYLENE SHEETING OR OTHER APPROVED MATERIAL AND GRAVEL AGGREGATE DAMS PRIOR TO BEGINNING CLASS I SURFACE PREPARATION, SEE SPECIAL PROVISIONS.


FOR HYDRO-DEMOLITION, SEE SPECIAL PROVISIONS .

THE CONTRACTOR MUST COLLECT, TREAT AND DISPOSE OF RUN -OFF WATER FROM THE HYDRO- DEMOLITION PROCESS,

THE BOUNDARIES OF AREAS IDENTIFIED FOR CLASS III SURFACE PREPARATION ARE APPOXIMATE.

FOR EVAZOTE JOINT SEALS, SEE SPECIAL PROVISIONS.

PLAN



TYP. "BLOW THRU" CONTAINMENT AND FORMWORK

A METHOD TO CAPTURE WATER AND DEBRIS FROM BLOW THRU DURING HYDRO-DEMOLITION SHALL BE INSTALLED IN AREAS INDICATED AS CLASS III SURFACE PREPARATION.

SUBMIT DETAILS OF PROPOSED FORMWORK FOR APPROVAL PRIOR TO BEGINNING WORK.

COST FOR INSTALLING AND REMOVING FORMWORK SHALL BE INCIDENTAL TO THE PRICE PER SQ. YARD OF HYDRO-DEMOLITION.

	TOTAL BIL	L OF MATER	ZIAL			
I	HYDRO- DEMOLITION OF BRIDGE DECK	LATEX MODIFIED CONCRETE VERY EARLY STRENGTH	PLACING & FINISHING LATEX MODIFIED CONCRETE VERY EARLY STRENGTH	EVAZOTE JOINT SEALS	GROOVING BRIDGE FLOORS	ASPHALT CONCRETE SURFACE COURSE TYPE SF 9.5A
	SQ.YDS.	C.Y.	SQ.YDS.	LUMP SUM	SQ.FT.	TONS
	489	40	489	LUMP SUM	4398	35

* QUANTITY SHOWN IS FOR INFORMATION ONLY. ** INCLUDES APPROACH MILLING.

* CLASS II SURFACE

PREPARATION

SQ.YDS.

479

* CLASS I SURFACE

PREPARATION

SQ.YDS.

** SCARIFYING BRIDGE DECK

SQ.YDS.

811

* CLASS III SURFACE

PREPARATION

SQ.YDS.

10

FINISHED SURFACE OF LATEX MODIFIED OVERLAY AND SURFACE OF ORIGINAL DECK BEFORE WORK BEGINS. 2"MIN. OVERLAY DECK SURFACE BEFORE OVERLAY IS PLACED.

DETAIL FOR LATEX MODIFIED CONCRETE OVERLAY


> PROJECT NO. BK-5101 D MECKLENBURG COUNTY: STATION: DECK REPAIR BRIDGE NO. 53


STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

PLAN VIEW OF BRIDGE #53 ON NC 51 OVER LITTLE SUGAR CREEK 52' CLEAR ROADWAY-70° SKEW


SHEET NO.	revisions					
5-1	DATE	BY	NO.	DATE	BY	10.
TOTAL SMEETS			3			1
			4			2

DRAWN BY: CLB DATE: 11/09 CHECKED BY: AGA DATE: 11/09





\$\$\$\$USERNAME\$\$\$\$ \$\$\$\$\$\$SYSTIME\$\$\$\$\$



BK.

STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

PLAN FOR PROPOSED TRAFFIC CONTROL

MECKLENBURG COUNTY

LOCATION: BRIDGE #53, NC 51 OVER LITTLE SUGAR CREEK TYPE OF WORK: TRAFFIC CONTROL FOR BRIDGE PRESERVATION

ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" -PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JULY 2006 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
1101.02	TEMPORARY LANE CLOSURES
1101.04	TEMPORARY SHOULDER CLOSURES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.02	PORTABLE WORK ZONE SIGNS
1115.01	FLASHING ARROW PANELS
1130.01	DRUMS
1165.01	TRUCK MOUNTED IMPACT ATTENUATOR
1205.01	PAVEMENT MARKINGS - LINE TYPES & OFFSETS
1205.02	PAVEMENT MARKINGS - 2 LANE & MULTILANE ROADWAYS

INDEX OF SHEETS

SHEET NO.	TITLE
TCP-1	LIST OF APPLICABLE ROADWAY STANDARD DRAWINGS, LEGEND, AND INDEX OF SHEETS
TCP-2	GENERAL NOTES
TCP-3	PROJECT PHASING
TCP-4	PHASE I - STAGE I BRIDGE WORK
TCP-5	PHASE II - STAGE II BRIDGE WORK
TCP-6	PHASE III - STAGE III BRIDGE WORK
TCP-7	PHASE IV - STAGE IV BRIDGE WORK

LEGEND

GENERAL

DIRECTION OF TRAFFIC FLOW

STATE PROJECT REFERENCE NO.

BK-5101D

SHEET NO.

TCP-1

NORTH ARROW

WORK AREA

TRAFFIC CONTROL DEVICES

TYPE III BARRICADE

▲ CONE

■ DRUM ⑤ SKINNY DRUM

FLASHING ARROW PANEL (TYPE C)

- STATIONARY SIGN

PORTABLE SIGN

STATIONARY OR PORTABLE SIGN

- - PORTABLE CONCRETE BARRIER

→ TEMPORARY CRASH CUSHION

CHANGEABLE MESSAGE SIGN

TRUCK MOUNTED IMPACT ATTENUATOR (TMIA)

POLICE

■ FLAGGER



PLAN PREPARED BY:



BETSY L. WATSON, PE

GEORGE KARAGEORGE

TRAFFIC CONTROL ENGINEER TRAFFIC CONTROL DESIGNER

PROJECT REFERENCE NO.	SHEET NO.
BK-5101D	TCP-2

GENERAL NOTES

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS, OR RESULT IN DUPLICATE, OR UNDESIRED OVERLAPPING OF DEVICES. MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING OR REMOVAL OF DEVICES, AS DIRECTED BY THE ENGINEER.

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN, OR DIRECTED BY THE ENGINEER.

LANE CLOSURE TIME RESTRICTIONS

A) DO NOT CLOSE OR NARROW TRAVEL LANES AS FOLLOWS:

ROAD NAME

DAY AND TIME RESTRICTIONS

ALL ROADS

6:00 A.M.- 7:00 P.M. EVERY DAY

B) DO NOT CLOSE OR NARROW TRAVEL LANES DURING HOLIDAYS AND SPECIAL EVENTS AS FOLLOWS:

ROAD NAME ALL ROADS

HOLIDAY

- 1) FOR ANY UNEXPECTED OCCURRENCE THAT CREATES UNUSUALLY HIGH TRAFFIC VOLUMES, AS DIRECTED BY THE ENGINEER.
- 2) FOR NEW YEAR'S, BETWEEN THE HOURS OF 7:00 P.M. DECEMBER 31st TO 6:00 A.M. JANUARY 2nd. IF NEW YEAR'S DAY IS ON A FRIDAY, SATURDAY, SUNDAY, OR MONDAY THEN UNTIL 7:00 A.M. THE FOLLOWING TUESDAY.
- FOR EASTER, BETWEEN THE HOURS OF 7:00 P.M. THURSDAY AND 6:00 A.M. MONDAY.
- 4) FOR MEMORIAL DAY, BETWEEN THE HOURS OF 7:00 P.M. FRIDAY TO 6:00 A.M. TUESDAY.
- 5) FOR INDEPENDENCE DAY, BETWEEN THE HOURS OF 7:00 P.M. THE DAY BEFORE INDEPENDENCE DAY AND 6:00 A.M. THE DAY AFTER INDEPENDENCE DAY. IF INDEPENDENCE DAY IS ON A FRIDAY, SATURDAY, SUNDAY OR MONDAY; THEN BETWEEN THE HOURS OF 7:00 P.M. THE THURSDAY BEFORE INDEPENDENCE DAY AND 6:00 A.M. THE TUESDAY AFTER INDEPENDENCE DAY.
- 6) FOR LABOR DAY, BETWEEN THE HOURS OF 7:00 P.M. FRIDAY AND 6:00 A.M. TUESDAY.
- 7) FOR THANKSGIVING DAY, BETWEEN THE HOURS OF 7:00 P.M. TUESDAY TO 6:00 A.M. MONDAY.
- 8) FOR CHRISTMAS, BETWEEN THE HOURS OF 7:00 P.M. THE FRIDAY BEFORE THE WEEK OF CHRISTMAS DAY AND 6:00 A.M. THE FOLLOWING TUESDAY AFTER THE WEEK OF CHRISTMAS

LANE AND SHOULDER CLOSURE REQUIREMENTS

- C) REMOVE LANE CLOSURE DEVICES FROM THE LANE WHEN WORK IS NOT BEING PERFORMED BEHIND THE LANE CLOSURE OR WHEN A LANE CLOSURE IS NO LONGER NEEDED, OR AS DIRECTED BY THE ENGINEER.
- D) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN 15 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN SHOULDER USING ROADWAY STANDARD DRAWING NO. 1101.04 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL OR A LANE CLOSURE IS INSTALLED.
- E) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO AN UNDIVIDED FACILITY AND WITHIN 5 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.

WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO A DIVIDED FACILITY AND WITHIN 10 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.

F) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN A LANE OF TRAVEL OF AN UNDIVIDED OR DIVIDED FACILITY, CLOSE THE LANE ACCORDING TO THE TRAFFIC CONTROL PLANS, ROADWAY STANDARD DRAWINGS OR AS DIRECTED BY THE ENGINEER. CONDUCT THE WORK SO THAT ALL PERSONNEL AND/OR EQUIPMENT REMAIN WITHIN THE CLOSED TRAVEL LANE.

TRAFFIC CONTROL DEVICES

G) UNLESS OTHERWISE NOTED IN THE PLANS, SPACE CHANNELIZING DEVICES IN WORK AREAS NO GREATER THAN TWICE THE POSTED SPEED LIMIT (MPH), EXCEPT 10 FT ON-CENTER IN RADII, AND 3 FT OFF THE EDGE OF AN OPEN TRAVELWAY, WHEN LANE CLOSURES ARE NOT IN EFFECT. WHEN SKINNY DRUMS ARE ALLOWED, REFER TO SECTION 1180 OF STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES OR AS SHOWN IN THE PLANS.

PAVEMENT MARKINGS AND MARKERS


H) UPON COMPLETION OF EACH STAGE OF BRIDGE WORK REPLACE EXISTING PAVEMENT MARKINGS WITH PAINT.

UPON COMPLETION OF ALL BRIDGE WORK OPERATIONS INSTALL THERMOPLASTIC PAVEMENT MARKINGS USING LANE CLOSURES PER STD. 1101.02, SHEET 3 OF 9.

MISCELLANEOUS

- POLICE MAY BE USED TO MAINTAIN TRAFFIC THROUGH THE WORK AREA AND/OR INTERSECTIONS, AS DIRECTED BY THE ENGINEER.
- J) ALL DIMENSIONS AND STATIONING IN THE TRAFFIC CONTROL PLAN ARE APPROXIMATE (+/-); FIELD ADJUST AS NECESSARY OR AS DIRECTED BY THE ENGINEER.
- K) MAINTAIN ALL DRIVEWAY ACCESSESS.
- L) ENSURE THE OVERSIZE/OVERWEIGHT PERMIT UNIT (919) 733-4740 HAS BEEN ADVISED OF THE ONGOING TRAFFIC OPERATIONS THROUGH THE DIVISION OFFICE INCLUDING THE FOLLOWING AREAS OF CONCERN:
 - A. LANE CLOSURE RESTRICTIONS.
 - B. NARROW LANES.





GENERAL NOTES

NONE
JAN. 2010
BY: GK
KNEY: GK
KNEY: BI W



REVISIONS

.a.r.a]\bk-5101d bridge 53\top\plan sheets\BK-5101U_top_pshUz gkarayeorga

TRAFFIC CONTROL PHASING

PHASE I (TCP-4)

PERFORM STEPS 1 THROUGH 3 IN A CONTINUOUS OPERATION

STEP 1:

INSTALL LANE CLOSURES FOR BOTH DIRECTIONS OF NC 51 AS SHOWN ON SHEET TCP-4.

STEP 2:

CONSTRUCT STAGE I BRIDGE WORK (HYDRO-DEMOLITION AND LATEX MODIFIED CONCRETE OVERLAY) FOR THE NC 51 NORTHBOUND LEFT

REPLACE OBLITERATED PAVEMENT MARKINGS WITH PAINT.

STEP 3:

REMOVE LANE CLOSURES AND OPEN ALL LANES OF NC 51 TO TRAFFIC.

(TCP-5)

PERFORM STEPS 1 THROUGH 3 IN A CONTINUOUS OPERATION

STEP 1:

INSTALL LANE CLOSURES FOR BOTH DIRECTIONS OF NC 51 AS SHOWN ON SHEET TCP-5.

STEP 2:

CONSTRUCT STAGE II BRIDGE WORK (HYDRO-DEMOLITION AND LATEX MODIFIED CONCRETE OVERLAY) FOR THE NC 51 SOUTHBOUND LEFT

REPLACE OBLITERATED PAVEMENT MARKINGS WITH PAINT.

STEP 3:

REMOVE LANE CLOSURES AND OPEN ALL LANES OF NC 51 TO TRAFFIC.

PHASE III (TCP-6)

PERFORM STEPS 1 THROUGH 3 IN A CONTINUOUS OPERATION

STEP 1:

INSTALL LANE CLOSURES FOR BOTH DIRECTIONS OF NC 51 AS SHOWN ON SHEET TCP-6.

STEP 2:

CONSTRUCT STAGE III BRIDGE WORK (JOINT REPAIR) FOR THE NC 51 NORTHBOUND RIGHT LANE.

STEP 3:

REMOVE LANE CLOSURES AND OPEN ALL LANES OF NC 51 TO TRAFFIC.

PHASE IV (TCP-7)

PERFORM STEPS 1 THROUGH 3 IN A CONTINUOUS OPERATION

STEP 1:

INSTALL LANE CLOSURES FOR BOTH DIRECTIONS OF NC 51 AS SHOWN ON SHEET TCP-7.

STEP 2:


CONSTRUCT STAGE IV BRIDGE WORK (JOINT REPAIR) FOR THE NC 51 SOUTHBOUND RIGHT LANE.

STEP 3:

REMOVE LANE CLOSURES AND OPEN ALL LANES OF NC 51 TO TRAFFIC.

UPON COMPLETION OF ALL BRIDGE WORK OPERATIONS INSTALL THERMOPLASTIC MARKINGS USING THE SAME TYPE OF LANE CLOSURES AS WERE PREVIOUSLY USED.





TRAFFIC CONTROL PHASING

NONE

GK

GK

ON OF MILE
Tolker

REVISIONS

