DocuSign Envelope ID: 17EC9C75-4531-428F-8D3D-411DA04FD1FF

LOAD AND RESISTANCE FACTOR RATING (LRFD) SUMMARY FOR PRESTRESSED CONCRETE GIRDERS

LEVEL		VEHICLE	WEIGHT (W) (TONS)	CONTROLLING LOAD RATING	MINIMUM RATING FACTORS (RF)	TONS = W X RF	STRENGTH I LIMIT STATE											SERVICE III LIMIT STATE						COMMENT NUMBER
								MOMENT					SHEAR						MOMENT					
							LIVELOAD FACTORS	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	LIVELOAD FACTORS	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	
DESIGN LOAD RATING		HL-93(Inv)	N/A	1	1.06	--	1.75	0.280	1.06	70'	E	34.50	0.509	1.94	70'	E	6.9	0.80	0.280	1.10	70'	E	34.50	
		HL-93(Opr)	N/A	--	1.37	--	1.35	0.280	1.37	70'	E	34.50	0.509	2.51	70'	E	6.9	N/A	--	--	--	--	--	
		HS-20(Inv)	36.00	2	1.37	49.394	1.75	0.280	1.37	70'	E	34.50	0.509	2.24	70'	E	6.9	0.80	0.280	1.43	70'	E	34.50	
		HS-20(Opr)	36.00	--	1.78	64.030	1.35	0.280	1.78	70'	E	34.50	0.509	2.90	70'	E	6.9	N/A	--	--	--	--	--	
LEGAL LOAD RATING	SV	SNSH	13.50	--	3.20	43.160	1.40	0.280	3.82	70'	E	34.50	0.509	5.24	70'	E	6.9	0.80	0.280	3.20	70'	E	34.50	
		SNGARBS2	20.00	--	2.40	47.996	1.40	0.280	2.88	70'	E	34.50	0.509	3.94	70'	E	6.9	0.80	0.280	2.40	70'	E	34.50	
		SNAGRIS2	22.00	--	2.28	50.118	1.40	0.280	2.72	70'	E	34.50	0.509	3.70	70'	E	6.9	0.80	0.280	2.28	70'	E	34.50	
		SNCOTTS3	27.25	--	1.59	43.376	1.40	0.280	1.91	70'	E	34.50	0.509	2.95	70'	E	6.9	0.80	0.280	1.59	70'	E	34.50	
		SNAGGRS4	34.93	--	1.34	46.655	1.40	0.280	1.60	70'	E	34.50	0.509	2.58	70'	E	6.9	0.80	0.280	1.34	70'	E	34.50	
		SNS5A	35.55	--	1.31	46.438	1.40	0.280	1.57	70'	E	34.50	0.509	2.60	70'	E	6.9	0.80	0.280	1.31	70'	E	34.50	
		SNS6A	39.95	--	1.21	48.305	1.40	0.280	1.45	70'	E	34.50	0.509	2.46	70'	E	6.9	0.80	0.280	1.21	70'	E	34.50	
		SNS7B	42.00	--	1.14	48.043	1.40	0.280	1.37	70'	E	34.50	0.509	2.41	70'	E	6.9	0.80	0.280	1.14	70'	E	34.50	
	TTST	TNAGRIT3	33.00	--	1.47	48.365	1.40	0.280	1.75	70'	E	34.50	0.509	2.79	70'	E	6.9	0.80	0.280	1.47	70'	E	34.50	
		TNT4A	33.08	--	1.47	48.702	1.40	0.280	1.76	70'	E	34.50	0.509	2.71	70'	E	6.9	0.80	0.280	1.47	70'	E	34.50	
		TNT6A	41.60	--	1.21	50.171	1.40	0.280	1.45	70'	E	34.50	0.509	2.53	70'	E	6.9	0.80	0.280	1.21	70'	E	34.50	
		TNT7A	42.00	--	1.21	50.947	1.40	0.280	1.45	70'	E	34.50	0.509	2.49	70'	E	6.9	0.80	0.280	1.21	70'	E	34.50	
		TNT7B	42.00	--	1.26	52.850	1.40	0.280	1.51	70'	E	34.50	0.509	2.37	70'	E	6.9	0.80	0.280	1.26	70'	E	34.50	
		TNAGRIT4	43.00	--	1.19	51.367	1.40	0.280	1.43	70'	E	34.50	0.509	2.32	70'	E	6.9	0.80	0.280	1.19	70'	E	34.50	
		TNAGT5A	45.00	--	1.13	50.645	1.40	0.280	1.35	70'	E	34.50	0.509	2.32	70'	E	6.9	0.80	0.280	1.13	70'	E	34.50	
		TNAGT5B	45.00	3	1.11	49.989	1.40	0.280	1.33	70'	E	34.50	0.509	2.24	70'	E	6.9	0.80	0.280	1.11	70'	E	34.50	

LOAD FACTORS:

DESIGN LOAD RATING FACTORS	LIMIT STATE	γ_{DC}	γ_{DW}
	STRENGTH I	1.25	1.50
	SERVICE III	1.00	1.00

NOTES:

MINIMUM RATING FACTORS ARE BASED ON THE STRENGTH I AND SERVICE III LIMIT STATES.

ALLOWABLE STRESSES FOR SERVICE III LIMIT STATE ARE AS REQUIRED FOR DESIGN.

COMMENTS:

1.
2.
3.
4.

CONTROLLING LOAD RATING
1 DESIGN LOAD RATING (HL-93)
2 DESIGN LOAD RATING (HS-20)
3 LEGAL LOAD RATING **
** SEE CHART FOR VEHICLE TYPE

GIRDER LOCATION
I - INTERIOR GIRDER
EL - EXTERIOR LEFT GIRDER
ER - EXTERIOR RIGHT GIRDER



LRFR SUMMARY

FOR SPAN A

NORTH CAROLINA PROFESSIONAL SEAL 018080 ENGINEER PAUL CARRETT
5/15/2018 10:59:56 AM PDT

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. 17BP.1.R.77

GATES COUNTY

STATION: 17+05.00 -L-

V&M Vaughn & Melton Consulting Engineers
Asheville, North Carolina 828-253-2796
Raleigh, NC 919-977-9455
Charlotte, NC 704-357-0488
Boone, NC 828-355-9933
Tri-Cities, TN 423-467-8401
Knoxville, TN 865-546-5800
Spartanburg, SC 864-574-4775
Charleston, SC 843-974-5650
Middlesboro, KY 606-248-6600
Atlanta, GA 770-627-3509
Copyright © 2006 Vaughn & Melton, Inc. All Rights Reserved

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

LRFR SUMMARY FOR 70' CORED SLAB UNIT 90° SKEW
(NON-INTERSTATE TRAFFIC)

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-3
1			3			TOTAL SHEETS
2			4			13

ASSEMBLED BY :	WDC	DATE :	1-2018
CHECKED BY :	TPG	DATE :	3-2018
DES ENG OF RECORD:	JEB	DATE :	2-2018

$$$$$$SYSTIME$$$$$
$$$$$$$$$$$$$$$$$$$$DGN$$$$$$$$$$$$$$$$$$$$$$
$$$$USERNAME$$$$