

REFERENCE: U-5510

PROJECT: 45532

SEE SHEET 3 FOR PLAN SHEET LAYOUT  
AT TIME OF INVESTIGATION

**STATE OF NORTH CAROLINA**  
DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-5510	1	42

**CONTENTS**

LINE	STATION	PLAN	PROFILE
-L-	11+00.00 - 37+65.92	4 - 11	12 - 15
-YI-	11+07.00 - 26+00.00		16 - 18

**CROSS SECTIONS**

LINE	STATION	SHEETS
-L-	11+00.00 - 37+65.92	19 - 36

**APPENDICES**

APPENDIX	TITLE	SHEETS
A	SOIL TEST RESULTS	37 - 38

# ROADWAY SUBSURFACE INVESTIGATION

COUNTY CATAWBA  
PROJECT DESCRIPTION SR 1468 (SWEETWATER ROAD)  
EXTENSION FROM US 70 TO SR 1005 (STARTOWN ROAD)

## INVENTORY

**CAUTION NOTICE**

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
  - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

HPC

C. BUKOVITZ

A. ROTH

M. BREWER, P.E.

J. FRAZIER


INVESTIGATED BY ECS CAROLINAS, LLP

DRAWN BY M. BREWER, P.E.

CHECKED BY M. WALKO, P.E.

SUBMITTED BY ECS CAROLINAS, LLP

DATE AUGUST 2016



DocuSigned by:  
D. Matthew Brewer

EC2ABBE99DB48C...

8/29/2016

SIGNATURE

DATE

**DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED**

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION**  
**DIVISION OF HIGHWAYS**  
**GEOTECHNICAL ENGINEERING UNIT**  
**SUBSURFACE INVESTIGATION**  
**SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																																																						
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i>										<b>WELL GRADED</b> - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. <b>UNIFORMLY GRADED</b> - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. <b>GAP-GRADED</b> - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.										<b>HARD ROCK</b> IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL, SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:										<b>ALLUVIUM (ALLUV.)</b> - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. <b>AQUIFER</b> - A WATER BEARING FORMATION OR STRATA. <b>ARENACEOUS</b> - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. <b>ARGILLACEOUS</b> - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. <b>ARTESIAN</b> - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. <b>CALCAREOUS (CALC.)</b> - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. <b>COLLUVIUM</b> - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. <b>CORE RECOVERY (REC.)</b> - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. <b>DIKE</b> - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. <b>DIP</b> - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. <b>DIP DIRECTION (DIP AZIMUTH)</b> - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. <b>FAULT</b> - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. <b>FISSILE</b> - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. <b>FLOAT</b> - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOADED FROM PARENT MATERIAL. <b>FLOOD PLAIN (FP)</b> - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. <b>FORMATION (FM)</b> - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. <b>JOINT</b> - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. <b>LEDGE</b> - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. <b>LENS</b> - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. <b>MOTTLED (MOT.)</b> - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. <b>PERCHED WATER</b> - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. <b>RESIDUAL (RES.) SOIL</b> - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. <b>ROCK QUALITY DESIGNATION (RQD)</b> - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. <b>SAPROLITE (SAP.)</b> - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. <b>SILL</b> - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. <b>SLICKENSIDE</b> - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. <b>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT)</b> - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. <b>STRATA CORE RECOVERY (SREC.)</b> - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. <b>STRATA ROCK QUALITY DESIGNATION (SROD)</b> - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. <b>TOPSOIL (TS.)</b> - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																																																																																																						
<b>SOIL LEGEND AND AASHTO CLASSIFICATION</b>										<b>ANGULARITY OF GRAINS</b>										<b>WEATHERED ROCK (WR)</b>										<b>NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES &gt; 100 BLOWS PER FOOT IF TESTED.</b>																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="5">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (&gt; 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-2-6</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th colspan="5"></th> </tr> <tr> <th>SYMBOL</th> <td colspan="4">[Pattern]</td> <td colspan="4">[Pattern]</td> <td colspan="4">[Pattern]</td> <td colspan="5"></td> </tr> <tr> <th>% PASSING #10 #40 #200</th> <td colspan="4">[Table]</td> <td colspan="4">[Table]</td> <td colspan="4">[Table]</td> <td colspan="5"></td> </tr> <tr> <th>MATERIAL PASSING #40 LL PI</th> <td colspan="4">[Table]</td> <td colspan="4">[Table]</td> <td colspan="4">[Table]</td> <td colspan="5"></td> </tr> <tr> <th>GROUP INDEX</th> <td colspan="4">[Table]</td> <td colspan="4">[Table]</td> <td colspan="4">[Table]</td> <td colspan="5"></td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td colspan="4">[Table]</td> <td colspan="4">[Table]</td> <td colspan="4">[Table]</td> <td colspan="5"></td> </tr> <tr> <th>GEN. RATING AS SUBGRADE</th> <td colspan="4">[Table]</td> <td colspan="4">[Table]</td> <td colspan="4">[Table]</td> <td colspan="5"></td> </tr> </table>										GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-2-6	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7						SYMBOL	[Pattern]				[Pattern]				[Pattern]									% PASSING #10 #40 #200	[Table]				[Table]				[Table]									MATERIAL PASSING #40 LL PI	[Table]				[Table]				[Table]									GROUP INDEX	[Table]				[Table]				[Table]									USUAL TYPES OF MAJOR MATERIALS	[Table]				[Table]				[Table]									GEN. RATING AS SUBGRADE	[Table]				[Table]				[Table]									<b>MINERALOGICAL COMPOSITION</b> MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.										<b>CRYSTALLINE ROCK (CR)</b> FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.										<b>NON-CRYSTALLINE ROCK (NCR)</b> FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.									
GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																																																																																																										
GROUP CLASS.	A-1	A-3	A-2	A-2-6	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																								
SYMBOL	[Pattern]				[Pattern]				[Pattern]																																																																																																																																																																											
% PASSING #10 #40 #200	[Table]				[Table]				[Table]																																																																																																																																																																											
MATERIAL PASSING #40 LL PI	[Table]				[Table]				[Table]																																																																																																																																																																											
GROUP INDEX	[Table]				[Table]				[Table]																																																																																																																																																																											
USUAL TYPES OF MAJOR MATERIALS	[Table]				[Table]				[Table]																																																																																																																																																																											
GEN. RATING AS SUBGRADE	[Table]				[Table]				[Table]																																																																																																																																																																											
<b>COMPRESSION</b>										<b>PERCENTAGE OF MATERIAL</b>										<b>WEATHERING</b>										<b>CRUSTAL PLAIN SEDIMENTARY ROCK (CP)</b>																																																																																																																																																						
SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50										<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE 1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE 10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME 20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>&gt; 10%</td> <td>&gt; 20%</td> <td>HIGHLY 35% AND ABOVE</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE	<b>FRESH</b> ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE. <b>VERY SLIGHT (V SLI.)</b> ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE. <b>SLIGHT (SLI.)</b> ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS. <b>MODERATE (MOD.)</b> SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK. <b>MODERATELY SEVERE (MOD. SEV.)</b> ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <i>IF TESTED, WOULD YIELD SPT REFUSAL</i> <b>SEVERE (SEV.)</b> ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT, SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <i>IF TESTED, WOULD YIELD SPT N VALUES &gt; 100 BPF</i> <b>VERY SEVERE (V SEV.)</b> ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, WOULD YIELD SPT N VALUES &lt; 100 BPF</i> <b>COMPLETE</b> ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.										<b>GROUND WATER</b> WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING STATIC WATER LEVEL AFTER 24 HOURS PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA SPRING OR SEEP																																																																																																																																		
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																																																	
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%																																																																																																																																																																																	
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%																																																																																																																																																																																	
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%																																																																																																																																																																																	
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE																																																																																																																																																																																	
<b>CONSISTENCY OR DENSENESS</b>										<b>MISCELLANEOUS SYMBOLS</b>										<b>ROCK HARDNESS</b>										<b>RECOMMENDATION SYMBOLS</b>																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 &gt; 4</td> </tr> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )	GENERALLY GRANULAR MATERIAL (NON-COESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4											<b>VERY HARD</b> CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK. <b>HARD</b> CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN. <b>MODERATELY HARD</b> CAN BE SCRATCHED BY KNIFE OR PICK OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS. <b>MEDIUM HARD</b> CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK. <b>SOFT</b> CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE. <b>VERY SOFT</b> CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.																																																																																																																																																				
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )																																																																																																																																																																																	
GENERALLY GRANULAR MATERIAL (NON-COESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																																																	
GENERALLY SILT-CLAY MATERIAL (COESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																																																																																																	
<b>TEXTURE OR GRAIN SIZE</b>										<b>ABBREVIATIONS</b>										<b>FRACTURE SPACING</b>										<b>BEDDING</b>																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)								<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>GRAIN SIZE</th> <th>MM</th> <th>305</th> <th>75</th> <th>2.0</th> <th>0.25</th> <th>0.05</th> <th>0.005</th> </tr> <tr> <td></td> <td>IN.</td> <td>12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005		IN.	12	3					<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </table>										TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET	WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PLASTIC RANGE (PI)</td> <td>- WET - (W)</td> <td>SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PLASTIC RANGE (PI)	- WET - (W)	SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																						
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																														
	4.75	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																														
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																														
GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005																																																																																																																																																																													
	IN.	12	3																																																																																																																																																																																	
TERM	SPACING	TERM	THICKNESS																																																																																																																																																																																	
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET																																																																																																																																																																																	
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																	
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																	
CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																	
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																	
		THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																	
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																		
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																		
PLASTIC RANGE (PI)	- WET - (W)	SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																		
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																		
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																		
<b>PLASTICITY</b>										<b>EQUIPMENT USED ON SUBJECT PROJECT</b>										<b>INDURATION</b>										<b>NOTES:</b>																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="2">PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>NON PLASTIC</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table>										PLASTICITY INDEX (PI)		DRY STRENGTH	NON PLASTIC	0-5	VERY LOW	SLIGHTLY PLASTIC	6-15	SLIGHT	MODERATELY PLASTIC	16-25	MEDIUM	HIGHLY PLASTIC	26 OR MORE	HIGH	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td></td> </tr> <tr> <td><input checked="" type="checkbox"/> CME-550X</td> <td><input checked="" type="checkbox"/> 6" HOLLOW AUGERS</td> <td></td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td></td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE *STEEL TEETH</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE *TUNG-CARB.</td> <td></td> </tr> <tr> <td></td> <td><input type="checkbox"/> CORE BIT</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> </tr> </table>										DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER		<input checked="" type="checkbox"/> CME-550X	<input checked="" type="checkbox"/> 6" HOLLOW AUGERS		<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS		<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS			<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER			<input type="checkbox"/> TRICONE *STEEL TEETH			<input type="checkbox"/> TRICONE *TUNG-CARB.			<input type="checkbox"/> CORE BIT					<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>TERM</th> <th>INDURATION</th> </tr> <tr> <td>FRIABLE</td> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <td>MODERATELY INDURATED</td> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <td>INDURATED</td> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED</td> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>										TERM	INDURATION	FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	<b>BENCH MARK:</b> BL SWI2; N-716241.090, E-1322059.7824 Elevation: 937.05 FEET BL SWI4; N-716660.8392, E-1322116.2983 ELEVATION: 963.23 FEET																																																																																												
PLASTICITY INDEX (PI)		DRY STRENGTH																																																																																																																																																																																		
NON PLASTIC	0-5	VERY LOW																																																																																																																																																																																		
SLIGHTLY PLASTIC	6-15	SLIGHT																																																																																																																																																																																		
MODERATELY PLASTIC	16-25	MEDIUM																																																																																																																																																																																		
HIGHLY PLASTIC	26 OR MORE	HIGH																																																																																																																																																																																		
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																																																																																																		
<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																																																																																		
<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER																																																																																																																																																																																			
<input checked="" type="checkbox"/> CME-550X	<input checked="" type="checkbox"/> 6" HOLLOW AUGERS																																																																																																																																																																																			
<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS																																																																																																																																																																																			
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS																																																																																																																																																																																			
	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER																																																																																																																																																																																			
	<input type="checkbox"/> TRICONE *STEEL TEETH																																																																																																																																																																																			
	<input type="checkbox"/> TRICONE *TUNG-CARB.																																																																																																																																																																																			
	<input type="checkbox"/> CORE BIT																																																																																																																																																																																			
TERM	INDURATION																																																																																																																																																																																			
FRIABLE	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																																																																																																			
MODERATELY INDURATED	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																																																																																			
INDURATED	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																																																																																			
EXTREMELY INDURATED	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																																			
<b>COLOR</b>										<b>INDURATION</b>										<b>INDURATION</b>										<b>INDURATION</b>																																																																																																																																																						
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.										<b>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</b>										<b>INDURATION</b>										<b>INDURATION</b>																																																																																																																																																						


STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-5510	3	42
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
45532.1.1	TCSP-1468(2)	PE	
45532.2.1	TCSP-1468(2)	R/W, UTIL.	

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

**CATAWBA COUNTY**



LOCATION: SR 1468 (SWEETWATER RD) EXTENSION FROM  
US 70 TO SR 1005 (STARTOWN RD)

TYPE OF WORK: GRADING, PAVING, DRAINAGE, SIGNING, AND STRUCTURE



VICINITY MAP

BEGIN TIP PROJECT U-5510  
-L- STA. 8+00.00




CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

THIS PROJECT IS WITHIN THE MINICIPAL BOUNDARIES OF THE CITY OF HICKORY.

**INCOMPLETE PLANS**  
DO NOT USE FOR R/W ACQUISITION  
DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

**CONTRACT:**



**DESIGN DATA**

ADT 2015 =	400
ADT 2040 =	9500
K =	9 %
D =	55 %
T =	3 % *
V =	40 MPH
* TTST = 1% DUAL 2%	
FUNC CLASS =	
URBAN COLLECTOR	
REGIONAL TIER	

**PROJECT LENGTH**

LENGTH ROADWAY TIP PROJECT U-5510	=	0.562 MILES
TOTAL LENGTH TIP PROJECT U-5510	=	0.562 MILES

**NCDOT CONTACT: JACKIE McSWAIN**


PLANS PREPARED BY:	PLANS PREPARED FOR:
TGS ENGINEERS 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH (704) 476-0003 CORP. LICENSE NO. C-0275	NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION 12 1710 East Marion St. Shelby, NC 28151
RIGHT OF WAY DATE:	LEONARD G. FLETCHER, PE PROJECT ENGINEER
LETTING DATE:	JIMMY L. TERRY, PE PROJECT DESIGN ENGINEER
2012 STANDARD SPECIFICATIONS	

**HYDRAULICS ENGINEER**

SIGNATURE: \_\_\_\_\_ P.E.

**ROADWAY DESIGN ENGINEER**

SIGNATURE: \_\_\_\_\_ P.E.



09/28/99  
21-JUL-2016 19:15  
I:\2601TECH\02-PROJECTS\1000-1999\1600\1643 - U-5510 - Roadway Extension on SR 1468 from US 70 to SR 1005\CADD\_GEO\TECH\PlanProf\U5510\_Rdy\_tsh.dgn  
mbrwewer2 AT ECS-T014P6HLL0



**ECS Carolinas, LLP**

1812 Center Park Drive, Suite D  
 Charlotte, NC 28217  
 T 704.525.5152 | F 704.357.0023  
 www.ecslimited.com

August 18, 2016

WBS NO: 45532.1.1  
 TIP NO: U-5510  
 F.A. NUMBER: TCSP-1468(2)  
 PROJECT ID: 28070  
 COUNTY: Catawba  
 DESCRIPTION: SR 1468 (Sweetwater Road) Extension from US 70 to SR 1005 (Startown Road)

**SUBJECT: Geotechnical Report – Inventory**

ECS Carolinas, LLP, (ECS) has completed the roadway exploration for this project. More specifically, this report includes the following design segments:

<u>Line</u>	<u>Stations(±)</u>
-L- (SR 1148 – Robinwood Road)	8+00 to 12+04
-L- (SR 1468 – Sweetwater Road Extension / 21 <sup>st</sup> Street Drive SE)	12+04 to 37+66
-Y1- (SR 1005 – Startown Road)	11+07 to 26+00
-Y2- (Future Roadway)	13+20 to 15+15

Geotechnical cross sections and profiles presented in this report are based on the roadway plans and design files provided by the NCDOT on April 1, 2016, and the subsurface exploration information obtained by ECS. In cases where other areas of concern are encountered in addition to the areas addressed in this report, ECS should be notified for further evaluation based on the actual field conditions.

**Site Description**

The majority of the existing project site is undeveloped and heavily wooded. The proposed roadway corridor encounters residential properties at the intersection with SR 1005 and commercial properties at the tie in to 21<sup>st</sup> Street Drive SE. SR 1005 – Startown Road (-Y1-) is an existing asphalt paved two-lane road with 10-foot wide lanes and 2-foot wide paved shoulders. A portion of -L- has been previously constructed in the vicinity of SR 1005 and US 70. The section in the vicinity of SR 1005 consists of an asphalt paved two-lane roadway with 10-foot wide lanes and 2-foot wide shoulders. The section in the vicinity of US 70 consists of an existing asphalt paved, 36-foot wide roadway with existing curb and gutter. The site

topography along -L- ranges from approximate EL 1,034 feet at the southern end of the project to approximate EL 917 at the water crossing and to approximate EL 997 feet at the northern end of the project.

**Project Description**

The proposed construction consists of approximately 0.56 miles of new roadway alignment along the main alignment (-L-) with additional widening of the secondary roads (Y-lines). The beginning of the project site is located approximately 400 feet south of the intersection of SR 1148 (-L-) and SR 1005 (-Y1-) at -L- Station 12+04. The end of the project is located at the intersection of 21<sup>st</sup> Street Drive SE (-L-) and US HWY 70 at -L- Station 37+66. A traffic circle will be utilized to tie the proposed main line (-L-) to a proposed future roadway (-Y2-) at Station 26+85.

Based on the grading information provided to us by the NCDOT, the proposed roadway subgrade will typically encounter fills on the order of 1 to 5 feet along the main line (-L-) and SR 1005 (-Y1-). Cuts on the order of 5 to 17 feet in height are anticipated from approximate -L- Station 16+00 to 23+00 and -L- Station 27+00 to 31+00. A retaining wall supported cut slope will be constructed from approximately -L- Station 27+70 to 32+50 RT. The larger fill sections of the project are to be constructed at -L- Station 23+50 to 27+00 with proposed fill heights on the order of 5 to 24 feet. There is one water crossing along the main alignment (-L-) shown on the roadway plans. The crossing occurs near -L- Station 25+00. A Reinforced Concrete Box Culvert (RCBC) will be utilized at the water crossing.

**Subsurface Exploration**

A geotechnical field investigation was performed by ECS between May 31 and June 6, 2016. During this time period, a total of twenty-five (25) standard penetration test (SPT) borings were advanced with an ATV-mounted CME 550X drill rig equipped with an automatic hammer.

Representative portions of the split-barrel soil samples obtained throughout the exploration program were transported to our laboratory. In the laboratory, representative split-barrel soil samples were selected and tested for gradation and Atterberg Limits in accordance with AASHTO test methods T-87, T-88, T-89, and T-90 as modified by the NCDOT Materials and Tests Unit. The natural soil water content was also determined for these samples in accordance with AASHTO T-265. The purpose of the laboratory testing was to aid in our classification of the soil samples and development of engineering recommendations. Bulk samples and Shelby tube samples of selected soil materials were obtained for additional testing, if requested.

Split-barrel samples, bulk samples and Shelby tube samples recovered on this project will be stored at the ECS Charlotte office for a period of 90 days. After 90 days, the samples can be transferred to the NCDOT Western Regional Geotechnical Office in Harrisburg, North Carolina, if requested.

**Areas of Special Geotechnical Interest**

1) **High Plasticity Soils**: The following areas contain high plasticity soils with plasticity indices (PI's) in excess of 25. High plasticity soils have the potential to cause subgrade problems during construction, embankment stability or long term settlement problems:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	12+50 to 14+50, 18+00 to 22+00	CL
-L-	28+00 to 33+00	CL and RT
-Y1-	16+00	CL

2) **Wet or Saturated Soils**: The following areas contain soils with natural moisture contents in excess of the liquid limit, high moisture contents noted in the field during drilling, or soils encountered below the water table:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	24+72 to 25+12, 27+00, 29+00 to 30+00	LT to RT

3) **Alluvial Soils**: The following locations were found to have near surface very loose to loose alluvial soils at the approximate stationing:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	24+20 to 25+80	LT to RT

4) **Soft/Very Loose Soils**: The following areas contain relatively soft or very loose to loose soils that have the potential for subgrade problems, embankment stability or long-term settlement problems during construction:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	12+00 to 16+00, 27+00 to 31+00	CL to RT
-L-	24+20 to 25+80	LT to RT
-Y1-	16+00	LT

5) **Shallow Groundwater**: The following areas indicated relatively shallow groundwater which has the potential to cause subgrade problems or constructability issues.

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	24+72 to 25+12	LT to RT

6) **Micaceous Soils**: Micaceous soils were encountered at various depths and locations along the proposed alignments. Soils containing high amounts of mica have low strength properties, difficult to compact, and are generally lightweight in nature. Below is a summary of the locations where micaceous soils were noted by our field professional(s) at the time of drilling.

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	11+45, 15+00, 21+00 to 33+00	CL and RT
-Y1-	13+00, 16+00, 22+50	LT

**Physiography and Geology**

The project site is located in the Piedmont Physiographic Province. In accordance with the Geologic Map of North Carolina, 1985, the predominant rock types in this area are mapped as amphibolite and biotite gneiss. Weathered rock samples recovered from our borings exhibited the characteristics of Gneiss. The virgin soils are the residual product of in-place chemical weathering of rock that was similar to the rock presently underlying the site.

The topography along the project slopes towards the natural drainage area near approximate Station 25+00. A sanitary sewer utility easement runs perpendicular to the proposed alignment, through the NCDOT right-of-way (ROW), near approximate -L- Station 25+64. One area of the project contained a rock outcropping in the vicinity of the proposed culvert (near -L- Station 25+00).

Based on a review of the Design Drawings available at the time of our exploration, approximate cut and fill depths along the profile centerline are as follows for the provided sections:

<u>Line</u>	<u>Station (±)</u>	<u>Approximate Cut/Fill Depths</u>
-L-	8+00 to 12+20	Minimal Cut and Fill
-L-	12+20 to 14+90	Minimal Cut, Fill up to 3 ft.
-L-	14+90 to 23+50	Cut up to 17 ft.
-L-	23+50 to 27+30	Fill up to 23 ft.
-L-	27+30 to 32+50	Cut up to 17 ft.
-L-	32+50 to 34+50	Minimal Cut and Fill
-Y1-	11+07 to 26+00	Minimal Cut, Fill up to 4 ft.

**Soil Properties**

The subsurface conditions discussed below represent the subsurface conditions based on interpretation of the boring data using normally accepted geotechnical engineering judgments. The transitions between different soil strata are usually less distinct than those shown on the Borelogs. Sometimes the relatively small sample obtained in the field is insufficient to definitively describe the origin of the subsurface material. Although individual soil test borings are representative of the subsurface conditions at the boring locations on the dates shown, they are not necessarily indicative of subsurface conditions at other locations or at other times.

Soils within the area of this project have been divided into four categories: surficial materials (topsoil), artificial fill/roadway embankment, alluvial soils and residual soils.

**Surficial Materials:** With the exception of two isolated locations along the proposed centerline of the roadway, surficial organic soils (topsoil/rootmat) were encountered at the surface of the roadway and culvert borings and ranged in thickness from approximately 0.1 to 0.2 feet. It should be noted that in some locations, mechanical clearing was performed and some of the surficial soils may have been removed during clearing. In the wooded areas, surficial organic soil depths are anticipated to be deeper than what is reported on the boring logs.

**Artificial Fill/Roadway Embankment:** Artificial fill (A.F.) was encountered along the following alignments and at the approximate stationing:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	28+50 to 33+00	RT

The artificial fill encountered generally consisted of red, gray, brown, white, tan and red-brown moist, soft to stiff, silty clay (A-7-5), clayey silt (A-5) or fine sandy silt (A-4) and extend to depths ranging from approximately 5.0 to 12.0 feet below existing grades.

**Alluvial:** Alluvial soils were encountered along the following alignments and at the approximate stationing:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	24+20 to 25+80	LT to RT

The alluvial soils encountered generally consisted of red-brown, moist, very soft, sandy silt (A-4) and brown-white-orange to red-brown, moist to wet, very loose to loose, silty sand (A-2-4). The alluvial soils were encountered at depths ranging from approximately 0 to 5.5 feet below existing grades. Laboratory testing of the alluvial soils indicated that the material was non-plastic.

**Residual Soils:** Residual soils throughout the proposed alignments are derived from the weathering of the underlying parent bedrock. A majority of the residual soils encountered generally consisted of red, brown, orange, tan, purple, gray, white and black, moist to wet, soft to very stiff, fine to coarse sandy, silty clay (A-7-5, A-7-6) clayey and sandy silt (A-5, A-4) or very loose to very dense, moist to wet, silty fine to coarse sand (A-2-4). In general, the residual soils transitioned from fine-grained (clay) near the surface to coarse-grained (silt, sand) with increasing depth. Laboratory testing indicated PI's ranging from 53 to non-plastic for the A-7-5, A-7-6, A-5, A-4, and A-2-4 soils.

**Rock Properties**

**Weathered Rock:** Weathered Rock (WR) was encountered in two of the borings along the -L- Line. Weathered rock is defined as residual material exhibiting an SPT N-value of at least 100 blows per foot.

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	24+72, 24+93	LT and CL

Along the L-Line, the top of the weathered rock was encountered at depths ranging from approximately 11 to 13.5 feet below existing grades.

**Crystalline Rock:** Crystalline Rock (CR) is defined by SPT refusal (i.e., 60/0.1' or 60/0.0'). Crystalline rock was not encountered in any of the borings performed during this exploration. A rock outcrop was observed in the vicinity of the proposed culvert location and is discussed in Geology and Physiography section of this report.

**Groundwater Properties**

Groundwater levels were measured in the borings both immediately after drilling and, where applicable, after a stabilization period of at least 24 hours. At the time of drilling, water was encountered in five (5) borings at depths ranging from approximately 4.0 to 31.0 feet below existing grades. After a stabilization period of at least 24 hours, groundwater was encountered in five (5) borings at depths ranging from approximately 3.6 to 23.4 feet below existing grades. For safety reasons, several of the borings were backfilled immediately after drilling, making stabilized water readings unobtainable. The recovered soil samples were generally described as moist above the groundwater level and moist to wet below the groundwater level.

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	24+72 to 25+12	LT to RT
-L-	29+00, 30+00	RT

**Bulk Samples / Undisturbed Samples**

Four bulk soil samples from 0 to 15' were obtained from Borings RW-3, L\_2700, L-1900, and L\_2100 to be used for testing at the NCDOT's discretion.

An undisturbed thin wall Shelby tube sample was obtained at the following location to be used for testing at the NCDOT's discretion.

<u>Sample</u>	<u>Line</u>	<u>Station (±)</u>	<u>Depth</u>
ST-1	-L-	30+00	7.0-9.0

**Miscellaneous**

During the site visit, several dump sites containing wooden debris piles, trash and rip rap were observed within the proposed NCDOT Right of Way (ROW). The approximate locations and quantities of each location were field measured, and should be considered approximate.

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>	<u>Material</u>	<u>Area (ft<sup>2</sup>)</u>	<u>Pile Height (ft)</u>
-L-	19+60 to 19+75	CL to 20' LT	Rip-Rap	290	4.0
-L-	19+80 to 20+75	85' LT to 3' RT	Trees, Trash	4,050	9.0

A well was encountered during the site visit. The area where the well was encountered appeared to have been previously used as a foundation for a residential structure. The approximate location of the well was field measured and should be considered approximate.

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	15+65	25' LT

During the site visit, ECS was informed by the property owner of the existence of at least one buried septic tank. The location of the buried septic tank was not readily observable, however, based on conversations with the property owner, the approximate area of the buried septic tank was provided.

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	13+00	CL

Respectively submitted,



DocuSigned by:  
*D. Matthew Brewer*  
 EC2ABBE99DB48C...  
 D. Matthew Brewer, P.E.  
 Senior Project Engineer  
 N.C. Registration No. 041986



DocuSigned by:  
*Erik H. Freeburg*  
 C9F264C5186E4B0...  
 Erik H. Freeburg, P.E.  
 Principal Engineer / Branch Manager

PROJECT REFERENCE NO. U-5510	SHEET NO. 4
R/W SHEET NO.	HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER	
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
<b>TGS ENGINEERS</b>	<b>TGS ENGINEERS</b> 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH (704) 476-0003 CORP. LICENSE NO. C-0275

MATCH LINE STA. -Y1- 17+40.00  
MATCH TO SHEET NO. 10



BEGIN TIP PROJECT U-5510  
-L- STA 8+00.00

MATCH LINE STA. -L- 13+40.00  
MATCH TO SHEET NO. 5

MATCH LINE STA. -Y1- 21+00.00  
MATCH TO SHEET NO. 11

**-L- CURVE DATA**

PI Sta 11+32.84	PI Sta 13+10.29
$\Delta = 14^{\circ} 17' 12.5''$ (RT)	$\Delta = 17^{\circ} 34' 30.6''$ (RT)
$D = 16^{\circ} 22' 12.8''$	$D = 10^{\circ} 36' 37.2''$
$L = 87.27'$	$L = 165.64'$
$T = 43.86'$	$T = 83.48'$
$R = 350.00'$	$R = 540.00'$
$SE = 0.01$	$SE = 0.01$


20-JUN-2016 11:42 PROJECTS\11000-11999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEO\TECH\Plan\Prof\U5510\_gec\_psh04.dgn



8/17/09





I:\2006-2016\1652\PROJECTS\1000-1199\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEO\TECH\Plan\Prof\U5510\_geo\_psh05.dgn

PROJECT REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>5</b>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR P/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
<b>TGS ENGINEERS</b>	<b>TGS ENGINEERS</b> 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH (704) 476-0003 CORP. LICENSE NO.: C-0275



**MATCH LINE STA. -L- 13 + 40.00**  
**MATCH TO SHEET NO. 4**

**MATCH LINE STA. -L- 19 + 00.00**  
**MATCH TO SHEET NO. 6**



8/17/99  
 I:\2016\141\16\2016\141\2-PROJECTS\11000-11999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEOTECH\Plan\Prof\U5510\_geo\_psh06.dgn  
 2: JUL 2016 141  
 16: 2016 141



**-L- CURVE DATA**  
 PI Sta 21+72.71  
 $\Delta = 46^{\circ} 21' 23.2" (LT)$   
 $D = 7^{\circ} 38' 22.0"$   
 $L = 606.80'$   
 $T = 321.11'$   
 $R = 750.00'$   
 $SE = 0.04$   
 $DS = 40 \text{ MPH}$



PROJECT REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>6</b>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR P/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
	<b>TGS ENGINEERS</b> 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH (704) 476-0003 CORP. LICENSE NO.: C-0275

MATCH LINE STA. -L- 19+00.00  
 MATCH TO SHEET NO. 5


MATCH LINE  
 STA. -L- 24+20.00  
 MATCH TO SHEET NO. 7





28-JUN-2016 17:27 - PROJECTS\11000-11999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEOTECH\Plan\Prof\U5510\_gec\_psh08.dgn  
 15:26:07  
 8/17/99

MATCH LINE STA. -L- 29 + 80.00  
 MATCH TO SHEET NO. 7



MATCH LINE STA. -L- 35 + 00.00  
 MATCH TO SHEET NO. 9

PROJECT REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>8</b>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 TGS ENGINEERS 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH (704) 476-0003 CORP. LICENSE NO. C-0275	

NAD 83/2011

BOARD OF TRUSTEES OF CATAWBA VALLEY COMMUNITY COLLEGE  
DB 2951 PG 123

CATAWBA VALLEY COMMUNITY COLLEGE FOUNDATION, INC.  
DB 2087 PG 155  
PB 30 PG 94

BENCO STEEL, INC.  
DB 1205 PG 81


BST  
LOADING/STORAGE AREA

MTL. BUS




28-JUN-2016 15:02 PROJECTS\11000-11995\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_Geotech\Plan\Prof\U5510\_gec\_psh10.dgn  
 15:26:07  
 8/17/99

BEGIN CONSTRUCTION  
-Y1- STA. 11+07.00




MATCH LINE STA.  
-Y1- 12+00.00  
MATCH THIS SHEET

MATCH LINE STA. -Y1- 12+00.00  
MATCH THIS SHEET



MATCH LINE STA. -Y1- 17+40.00  
MATCH TO SHEET NO. 4

PROJECT REFERENCE NO. U-5510	SHEET NO. 10
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR A/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
	<b>TGS ENGINEERS</b> 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH (704) 476-0003 CORP. LICENSE NO. C-0275



CATAWBA VALLEY  
COMMUNITY COLLEGE  
DB 1883 PG 159

BOWMAN RENTALS, LLC  
DB 2568 PG 1

NANCY H. PROPPS  
DB 1832 PG 562

GLENN E. &  
BEVERLY S. BARGER  
DB 2222 PG 181




5/14/99  
 P:\JUL-2016\1828-PROJECTS\11000-11999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEO\TECH\Plan\Prof\U5510\_GEO\_PFILE.dgn  
 11/10/2016 10:42:10 AM  
 11/10/2016 10:42:10 AM  
 11/10/2016 10:42:10 AM

**-L- (SWEETWATER ROAD EXTENSION)**

PROJECT REFERENCE NO. U-5510	SHEET NO. 12
PROFILE BORINGS PROJECTED ALONG -L-	

0 25 50  
FEET  
VE=5:1



- (A) -RESIDUAL- SOFT TO VERY STIFF, MOIST, RED, FINE TO COARSE SANDY, SILTY CLAY (A-7-5)
- (B) -RESIDUAL- STIFF TO VERY STIFF, MOIST, RED-BROWN, FINE SANDY, CLAYEY SILT (A-5), MICACEOUS

-L- GROUNDLINE TAKEN FROM ROADWAY DESIGN PLANS PROVIDED BY NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORING, WITH BOTH PROJECTED ON THE PROFILE.



8+00      9+00      10+00      11+00      12+00      13+00      14+00



5/14/99  
 P:\JUL-2016-1829-PROJ\PROJECTS\11000-11999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEO\TECH\Plan\Prof\U5510\_GEO\_PFL.L.dgn  
 DATE: 07/14/2016 10:42:10 AM  
 BY: FRS-1042BHL10

# -L- (SWEETWATER ROAD EXTENSION)

PROJECT REFERENCE NO. U-5510	SHEET NO. 13
PROFILE BORINGS PROJECTED ALONG -L-	





- Ⓐ -RESIDUAL- SOFT TO VERY STIFF, MOIST, RED-ORANGE-BROWN, FINE TO COARSE SANDY, SILTY CLAY (A-7-5/A-7-6)
- Ⓑ -RESIDUAL- STIFF, MOIST, RED-ORANGE-BROWN-PURPLE-WHITE, FINE TO COARSE SANDY, CLAYEY SILT (A-5) AND SANDY SILT (A-4)
- Ⓒ -RESIDUAL- LOOSE, MOIST, RED-ORANGE-BROWN TO GRAY-WHITE-ORANGE, SILTY FINE SAND (A-2-4)

-L- GROUNDLINE TAKEN FROM ROADWAY DESIGN PLANS PROVIDED  
 BY NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH  
 THE BORING, WITH BOTH PROJECTED ON THE PROFILE.

5/14/99  
 2 JUL 2016 18:29  
 P:\PROJECTS\11000-11999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEO\TECH\Plan\Prof\U5510\_GEO\_PFL.L.dgn  
 11/14/2016 10:44 AM  
 11/14/2016 10:44 AM

**-L- (SWEETWATER ROAD EXTENSION)**

PROJECT REFERENCE NO. U-5510	SHEET NO. 14
PROFILE BORINGS PROJECTED ALONG -L-	



- (A) -RESIDUAL-** SOFT TO STIFF, MOIST, RED-TAN TO WHITE-ORANGE-BROWN, FINE TO COARSE SANDY, SILTY CLAY (A-7-5/A-7-6)
- (B) -RESIDUAL-** SOFT TO MEDIUM STIFF, MOIST TO WET, RED-BROWN TO WHITE-ORANGE-BROWN, FINE SANDY, CLAYEY SILT (A-5), MICACEOUS
- (C) -RESIDUAL-** LOOSE TO VERY DENSE, MOIST, GRAY-WHITE-BROWN, SILTY FINE TO COARSE SAND (A-2-4), MICACEOUS
- (D) -ALLUVIAL-** VERY LOOSE, MOIST TO WET, RED-BROWN, SILTY FINE TO COARSE SAND (A-2-4), MICACEOUS



-L- GROUNDLINE TAKEN FROM ROADWAY DESIGN PLANS PROVIDED BY NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORING, WITH BOTH PROJECTED ON THE PROFILE.



5/14/99  
27 JUN 2016 16:57  
C:\GEO\PROJECTS\1000-1199\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEO\TECH\Plan\Prof\U5510\_GEO\_PFI\_Y1.dgn  
11/20/2016 10:42 AM  
BY: J. B. BROWN  
CHECKED BY: J. B. BROWN

**-Y1- (SR 1005 - STARTOWN ROAD)**

PROJECT REFERENCE NO. U-5510	SHEET NO. 16
PROFILE BORINGS PROJECTED ALONG -Y1-	





-Y1- GROUNDLINE TAKEN FROM ROADWAY DESIGN PLANS PROVIDED BY NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORING, WITH BOTH PROJECTED ON THE PROFILE.

5/14/99  
SR 1005 - ROADWAY EXTENSION ON SR 1468 FROM US 70 TO SR 1005 - CADD - GEOTECH PLAN - U5510 - GEO\_PFI\_Y1.dgn  
20 JUN 2016 11:50 AM  
C:\DOT\CH\AT\ERS-1042\B110

**-Y1- (SR 1005 - STARTOWN ROAD)**



PROJECT REFERENCE NO. U-5510	SHEET NO. 17
PROFILE BORINGS PROJECTED ALONG -Y1-	



5/14/99  
20 JUN 2016 11:49  
C:\PROJECTS\1000-1199\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEO\TECH\Plan\Prof\U5510\_GEO\_PFI\_Y1.dgn  
BY NCDOT TECH  
DRAWN

**-Y1- (SR 1005 - STARTOWN ROAD)**

PROJECT REFERENCE NO. U-5510	SHEET NO. 18
PROFILE BORINGS PROJECTED ALONG -Y1-	






8/23/99

21-JUL-2016 18:39 I:\ZDOT\PROJECTS\10000\1999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\SSC\U5510\_Geo\_xsi.L.dgn

PROJ. REFERENCE NO.	SHEET NO.
U-5510	20
CROSS SECTION THROUGH -L-	
STATION 14+50	
STATION 14+00	
STATION 13+50	

0 5 10  
FEET  
VE=1:1





-L- GROUNDLINE TAKEN FROM ROADWAY DESIGN FILES PROVIDED BY NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORING, WITH BOTH PROJECTED ON THE CROSS SECTION.



8/23/99

21-JUL-2016 18:40 I:\ZDOT\PROJECTS\10000\1999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\SS-69\SS-69.dgn

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>21</b>
CROSS SECTION THROUGH -L- STATION 15+50 STATION 15+00	




-L- GROUNDLINE TAKEN FROM ROADWAY DESIGN FILES PROVIDED BY NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORING, WITH BOTH PROJECTED ON THE CROSS SECTION.

8/23/99  
29-JUN-2016 11:53  
I:\2016\CH\02-EGS-10\1643\1000\1999\1600\1643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\XSEC\U5510\_Geo\_xsi.L.dgn

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>22</b>
CROSS SECTION THROUGH -L- STATION 18+00 STATION 16+00	

0 5 10  
FEET  
VE=1:1



EXISTING GROUND LINE

2:1

-RESIDUAL-  
STIFF TO VERY STIFF, MOIST, RED-ORANGE, FINE TO COARSE SANDY, SILTY CLAY (A-7-6/A-7-5)

2:1

STIFF, MOIST, RED-BROWN-WHITE, FINE TO COARSE SANDY, CLAYEY SILT (A-5) AND SANDY SILT (A-4)

18 + 00.00

EXISTING GROUND LINE

2:1

-RESIDUAL- STIFF TO VERY STIFF, MOIST, RED-ORANGE-BROWN, FINE TO COARSE SANDY, SILTY CLAY (A-7-5)

2:1

STIFF, MOIST, RED-BROWN-WHITE, FINE TO COARSE SANDY, CLAYEY SILT (A-5) AND SANDY SILT (A-4)

16 + 00.00



☺  
-L-

-L- GROUNDLINE TAKEN FROM ROADWAY DESIGN FILES PROVIDED BY NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORING, WITH BOTH PROJECTED ON THE CROSS SECTION.

8/23/99

22-JUL-2016 10:40  
I:\2010\11643\11643-02-FIG-10-11643.dgn  
1005\CADD\_GEO\TECH\SSC\U5510\_Geo\_xsi.L.dgn  
- Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEO\TECH\SSC\U5510\_Geo\_xsi.L.dgn

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>23</b>
CROSS SECTION THROUGH -L- STATION 19+00 STATION 18+50	



L\_1900  
19+00  
CL

SS+82  
SS+84

- ⑩
- ⑫
- ⑮
- ⑬
- ⑪
- ⑫
- ⑩
- ⑨

BT  
DRY  
6/16

19 + 00.00

18 + 50.00


CL  
-L-

-L- GROUNDLINE TAKEN FROM ROADWAY DESIGN FILES PROVIDED BY  
NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH  
THE BORING, WITH BOTH PROJECTED ON THE CROSS SECTION.

8/23/99  
29-JUN-2016 11:57  
I:\2016\CH-02-EGS-10\1999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\XSEC\U5510\_Geo\_xsi.L.dgn  
User: jmc  
Printer: AT-EGS-10\1999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\XSEC\U5510\_Geo\_xsi.L.dgn

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>24</b>
CROSS SECTION THROUGH -L- STATION 20+00 STATION 19+50	

0 5 10  
FEET  
VE=1:1






8/23/99

29-JUN-2016 11:58 i:\2016\CH-02-EGS-10\11643\1000\1999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\XSEC\U5510\_Geo\_xsi.L.dgn

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>26</b>
CROSS SECTION THROUGH -L- STATION 22+00 STATION 21+50	

0 5 10  
FEET  
VE=1:1




8/23/99

28-JUN-2016 22:19 I:\2016\CH-02-PROJ\10000\1999\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEOTECH\XSEC\U5510\_Geo\_xsi.L.dgn

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>27</b>
CROSS SECTION THROUGH -L- STATION 24+50	

VE = 1:1



75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40

45 50 55 60 65 70 75

950

945

940

935

930

925

920

915

910

905

900


75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

8/23/99

28-JUN-2016 22:19 I:\2801\CH\28-02-PROJ\FIGS\10000\1999\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\_GEO\TECH\SSC\U5510\_Geo\_xsi.L.dgn

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>28</b>
CROSS SECTION THROUGH -L- STATION 25+00	

0 5 10  
FEET  
VE=1:1



-L- GROUNDLINE TAKEN FROM ROADWAY DESIGN FILES PROVIDED BY NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORING, WITH BOTH PROJECTED ON THE CROSS SECTION.




8/23/99


28-JUN-2016 22:19  
I:\2016\CH-02-PROJ\10000\1999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\XSEC\U5510\_Geo\_xsi.L.dgn  
Author: AT-EGS-101-RHS/MLB

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>29</b>
CROSS SECTION THROUGH -L- STATION 25+50	

VE = 1:1



25 + 50.00





-L- GROUNDLINE TAKEN FROM ROADWAY DESIGN FILES PROVIDED BY NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORING, WITH BOTH PROJECTED ON THE CROSS SECTION.

8/23/99

21-JUL-2016 18:41 I:\ZDOT\PROJECTS\10000\1999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\SSAC\U5510\_Geo\_xsi.L.dgn

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>30</b>
CROSS SECTION THROUGH -L- STATION 28+00	



55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60

65 70 75 80 85 90 95

965 960 955 950 945 940 935 930 925 920 915

EXISTING GROUND LINE

2:1

PROP. RETAINING WALL

-RESIDUAL-

SOFT TO STIFF, MOIST, RED TO WHITE

ORANGE-BROWN, FINE SANDY,

LOOSE TO VERY LOOSE,

BROWN, SILTY FINE SAND

MEDIUM STIFF TO VERY STIFF, MOIST, RED-WHITE-BROWN TO WHITE-ORANGE-BROWN, FINE TO COARSE SANDY, CLAYEY

- 11
- 22
- 8
- 8
- 5
- 5
- 4

SILTY CLAY (A-7-5/A-7-6)

SILT (A-5), MICACEOUS.

MOIST TO WET, RED-ORANGE

(A-2-4), MICACEOUS

SS-47

RW-1  
28+01  
67' RT

BT  
DRY  
6/16

28 + 00.00

☺  
-L-

-L- GROUNDLINE TAKEN FROM ROADWAY DESIGN FILES PROVIDED BY NCDOT ON DATE 4/16. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORING, WITH BOTH PROJECTED ON THE CROSS SECTION.


55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95

8/23/99

21-JUL-2016 18:41 I:\ZDOT\PROJECTS\10000\1999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\XSEC\U5510\_Geo\_xsi.L.dgn

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>31</b>
CROSS SECTION THROUGH -L- STATION 28+50	

VE=1:1



75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40

45 50 55 60 65 70 75

965 960 955 950 945 940 935 930 925 920







8/23/99

22-JUL-2016 10:59  
I:\2016\CH-02-PRG\JCS\1000\1999\1600\1643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\SS-6\U5510\_Geo\_xsi.L.dgn  
DWG: JCS

PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>34</b>
CROSS SECTION THROUGH -L- STATION 31+00 STATION 30+50	





8/23/99

28-JUN-2016 2:25  
I:\2016\11\CH\11\1000\1999\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\XSEC\U5510\_Geo\_xsi.L.dgn  
DWG: 11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\XSEC\U5510\_Geo\_xsi.L.dgn

55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95


PROJ. REFERENCE NO. <b>U-5510</b>	SHEET NO. <b>35</b>
CROSS SECTION THROUGH -L- STATION 31+50	



8/23/99  
29-JUN-2016 12:00  
I:\2016\11\CH\02-PROJ\11000\1999\11600\11643 - U-5510 - Roadway Extension on SR 1468 From US 70 to SR 1005\CADD\GEO\TECH\SSC\U5510\_Geo\_xsi.L.dgn  
dwgname2 AT ESS-10-11643

PROJ. REFERENCE NO.	SHEET NO.
U-5510	36
CROSS SECTION THROUGH -L-	
STATION 33+00	
STATION 32+50	
STATION 32+00	

0 5 10  
FEET  
VE=1:1





NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT  
**SUBSURFACE INVESTIGATION**  
APPENDIX A  
SOIL TEST RESULTS

REFERENCE: U-5510

PROJECT: 45532

<sup>DS</sup>  
DMB

DMB 8-18-16  
INITIALS DATE

### SOIL TEST RESULTS

SAMPLE NO.	BORING	OFFSET	STATION -L-	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
								C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-102	L_1350	CL	13+50	3.5-5.0	A-7-5(19)	62	30	19.2	17.0	8.4	55.4	97.0	86.0	65.0	25.3	-
SS-69	L-1500	CL	15+00	1.0-2.5	A-7-6(10)	48	22	27.3	17.6	10.1	45.0	95.0	77.0	55.0	23.9	-
SS-75	L_1700	CL	17+00	3.5-5.0	A-7-5(15)	61	19	19.8	15.6	16.5	48.1	99.0	86.0	68.0	24.8	-
SS-76	L_1700	CL	17+00	6.0-7.5	A-7-5(17)	60	15	6.9	15.6	36.0	41.4	100.0	97.0	81.0	29.7	-
SS-82	L_1900	CL	19+00	3.5-5.0	A-7-5(18)	61	20	14.1	14.7	20.6	50.6	100.0	91.0	75.0	27.0	-
SS-84	L_1900	CL	19+00	8.5-10.0	A-7-6(31)	72	53	15.9	27.3	25.8	30.9	100.0	89.0	63.0	27.0	-
SS-89	L_2100	CL	21+00	1.0-2.5	A-7-5(16)	56	25	20.8	16.6	9.5	53.1	99.0	86.0	65.0	23.0	-
SS-96	L_2300	CL	23+00	1.0-2.5	A-7-6(13)	50	23	22.3	17.9	12.5	47.3	99.0	85.0	62.0	21.9	-
SS-52	L_2700	CL	27+00	1.0-2.5	A-7-5(8)	52	20	29.0	22.0	22.5	26.4	99.0	80.0	52.0	22.9	-
SS-21	L_2900	CL	29+00	1.0-2.5	A-7-5(19)	61	29	18.2	19.2	10.0	52.5	100.0	89.0	65.0	28.1	-
SS-23	L_2900	CL	29+00	6.0-7.5	A-7-5(21)	71	20	12.3	14.7	19.5	53.5	99.0	91.0	76.0	35.7	-
SS-6	L_3100	CL	31+00	1.0-2.5	A-7-5(31)	76	29	9.3	10.8	18.8	61.1	100.0	94.0	82.0	31.2	-
SS-150	Y1_1300	15' LT	13+00	3.5-5.0	A-7-5(20)	64	22	13.1	17	20.2	49.7	100.0	92.0	74.0	23.8	-
SS-147	Y1_1600	15' LT	16+00	6.0-7.5	A-7-5(27)	74	34	15.7	13.9	8.8	61.6	99.0	89.0	72.0	27.5	-
SS-58	B-1	59' RT	27+72	3.5-5.0	A-2-4(0)	39	NP	39.7	37.6	15.7	7.0	98.0	59.0	29.0	41.9	-
SS-47	RW-1	67' RT	28+01	6.0-7.5	A-5 (0)	47	2	32.9	33.4	10.8	22.8	100.0	81.0	38.0	27.0	-
SS-13	RW-3	24' RT	30+00	3.5-5.0	A-7-6(11)	50	22	20.5	19.3	12.2	48.0	93.0	81.0	59.0	27.5	-
SS-115	RW-5	25' RT	32+00	6.0-7.5	A-7-5(27)	66	25	4.9	13.2	23.5	58.4	100.0	97.0	86.0	29.1	-
CBR-1	RW-3	24' RT	30+00	1.0-10.0	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	-
CBR-2	L_2700	CL	27+00	3.0-15.0	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	-
CBR-3	L_1900	CL	19+00	0.0-15.0	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	-
CBR-4	L_2100	CL	21+00	0.0-15.0	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	-
ST-1	RW-3	24' RT	30+00	7.0-9.0	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	-

SS = Split-Barrel Sample (ASTM D-1586)

ST= Shelby Tube Sample (ASTM D-1587) - Informed by NCDOT that testing would not be necessary

CBR = California Bearing Ratio Sample - Transferred to NCDOT, no testing performed

Lab Technician: Amanda R. Roth

NCDOT Certification No.: 112-09-1003

Signature: 