


09/08/19

TIP PROJECT: BP13.R002

CONTRACT: DM00406



FINAL PLAN SUBMITTAL



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

RUTHERFORD COUNTY


LOCATION: REPLACE BRIDGE NO. 090 OVER SANDY RUN
ON SR 1762 (NEW HOUSE RD)

TYPE OF WORK: GRADING, PAVING, DRAINAGE, & STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	BP13.R002	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
BP13.R002.1	N/A	P.E.	
BP13.R002.2	N/A	R/W & UTIL.	
BP13.R002.3	N/A	CONSTRUCTION	




4



NOTE: DESIGN EXCEPTION REQUIRED FOR DESIGN SPEED OF 35MPH

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



DESIGN DATA

ADT 2019 = 650
V = 35 MPH
FUNC CLASS = LOCAL
SUB REGIONAL TIER

PROJECT LENGTH

LENGTH OF ROADWAY TIP PROJECT BP13.R002 = 0.144 Miles
LENGTH OF STRUCTURE TIP PROJECT BP13.R002 = 0.019 Miles
TOTAL LENGTH OF TIP PROJECT BP13.R002 = 0.163 Miles

Prepared In the Office of

WSP USA
434 FAYETTEVILLE STREET
SUITE 1500
RALEIGH, NC 27601
TEL: 1.919.836.4040
FAX: 1.919.836.4099
LICENSE NO. 15-0165

FOR THE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

2024 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: FEBRUARY 2, 2023

LETTING DATE: JUNE 19, 2024

NCDOT CONTACT: EDDIE DOUGLAS
DIVISION 13 BRIDGE PROGRAM MANAGER

SHANE I. SHARPE, PE
PROJECT ENGINEER


DREW DAACK, EIT
PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER


DocuSigned by: Charles W. Heatley
SIGNATURE:

ROADWAY DESIGN ENGINEER

DocuSigned by: Shane I. Sharpe
SIGNATURE:



8:47:24 AM
800090.RDY - TSH-01.dgn
3/21/2024



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

PLANS PREPARED BY:



WSP USA
434 FAYETTEVILLE STREET
SUITE 1500
RALEIGH, NC 27601
TEL: 1.919.836.4040
FAX: 1.919.836.4099
LICENSE NO. F-0165

INDEX OF SHEETS

SHEET NUMBER	SHEET
1	TITLE SHEET
1A	INDEX OF SHEETS, GENERAL NOTES, AND STANDARD DRAWINGS
1B	CONVENTIONAL SYMBOLS
2A-1	PAVEMENT SCHEDULE AND TYPICAL SECTIONS
3B-1	ROADWAY & DRAINAGE SUMMARIES
3G-1	GEOTECHNICAL SUMMARIES
4	PLAN SHEET
5	PROFILE SHEET
RW01 THRU RW04	SURVEY CONTROL, EXISTING CENTERLINES, RIGHT OF WAY, EASEMENT AND PROPERTY TIES
TMP-1 THRU TMP-4	TRAFFIC MANAGEMENT PLANS
PMP-1 THRU PMP-2	PAVEMENT MARKING PLANS
EC-1 THRU EC-5	EROSION CONTROL PLANS
SIGN-001 THRU SIGN-003	SIGNING PLANS
UO-1 THRU UO-2	UTILITIES BY OTHERS PLANS
X-1A	CROSS-SECTION SUMMARY SHEET
X-1 THRU X-13	CROSS-SECTIONS
S-1 THRU S-17	STRUCTURE PLANS
SN	STANDARD NOTES

GENERAL NOTES: 2024 SPECIFICATIONS
EFFECTIVE: 01-16-2024
REVISED:

GRADE LINE:
GRADING AND SURFACING:

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. GRADE LINES MAY BE ADJUSTED AT THEIR BEGINNING AND ENDING AND AT STRUCTURES AS DIRECTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

SUPERELEVATION:

ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:

ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01

SIDE ROADS:

THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

SUBSURFACE DRAINS:

SUBSURFACE DRAINS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. NO. 815.02 AT LOCATIONS DIRECTED BY THE ENGINEER.

GUARDRAIL:

THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

TEMPORARY SHORING:

SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC WILL BE PAID FOR AS "EXTRA WORK" IN ACCORDANCE WITH SECTION 104-7.

END BENTS:

THE ENGINEER SHALL CHECK THE STRUCTURE END BENT PLANS, DETAILS, AND CROSS-SECTION PRIOR TO SETTING OF THE SLOPE STAKES FOR THE EMBANKMENT OR EXCAVATION APPROACHING A BRIDGE.

UTILITIES:

UTILITY OWNERS ON THIS PROJECT ARE AT&T

ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS.

RIGHT-OF-WAY MARKERS:

ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY OTHERS.

2024 ROADWAY ENGLISH STANDARD DRAWINGS

The following Roadway Standards as appear in "Roadway Standard Drawings" Contracts Standards and Development Unit – N. C. Department of Transportation – Raleigh, N. C., Dated January 16, 2024 are applicable to this project and by reference hereby are considered a part of these plans:

STD.NO.	TITLE
DIVISION 2 – EARTHWORK	
200.02	Method of Clearing – Method II
225.02	Guide for Grading Subgrade – Secondary and Local
225.04	Method of Obtaining Superelevation – Two Lane Pavement
DIVISION 3 – PIPE CULVERTS	
300.01	Method of Pipe Installation
310.10	Driveway Pipe Construction
DIVISION 4 – MAJOR STRUCTURES	
423.01	Bridge Approach Fills – Type 1 Approach Fill for Bridge Abutment
DIVISION 5 – SUBGRADE, BASES AND SHOULDERS	
560.01	Method of Shoulder Construction – High Side of Superelevated Curve – Method I
DIVISION 8 – INCIDENTALS	
815.02	Subsurface Drain
840.00	Concrete Base Pad for Drainage Structures
840.25	Anchorage for Frames – Brick or Concrete or Precast
840.29	Frames and Narrow Slot Flat Grates
840.35	Traffic Bearing Grated Drop Inlet – for Cast Iron Double Frame and Grates
840.46	Traffic Bearing Precast Drainage Structure
840.66	Drainage Structure Steps
846.01	Concrete Curb, Gutter and Curb & Gutter
846.04	Drop Inlet Installation in Shoulder Berm Gutter
862.01	Guardrail Placement
862.02	Guardrail Installation
862.03	Structure Anchor Units
876.02	Guide for Rip Rap at Pipe Outlets
876.04	Drainage Ditches with Class 'B' Rip Rap

EFF. 01-16-2024
REV.

STATE OF NORTH CAROLINA, DIVISION OF HIGHWAYS CONVENTIONAL PLAN SHEET SYMBOLS

Note: Not to Scale

BOUNDARIES AND PROPERTY:

State Line	-----
County Line	-----
Township Line	-----
City Line	-----
Reservation Line	-----
Property Line	-----
Existing Iron Pin (EIP)	○
Computed Property Corner	×
Existing Concrete Monument (ECM)	◻
Parcel/Sequence Number	(123)
Existing Fence Line	-x-x-x-
Proposed Woven Wire Fence	○
Proposed Chain Link Fence	□
Proposed Barbed Wire Fence	◇
Existing Wetland Boundary	-----WLB-----
Proposed Wetland Boundary	-----WLB-----
Existing Endangered Animal Boundary	-----EAB-----
Existing Endangered Plant Boundary	-----EPB-----
Existing Historic Property Boundary	-----HPB-----
Known Contamination Area: Soil	-----S-----
Potential Contamination Area: Soil	-----S-----
Known Contamination Area: Water	-----W-----
Potential Contamination Area: Water	-----W-----
Contaminated Site: Known or Potential	☠ ?

BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	○
Sign	⊙
Well	⊙
Small Mine	×
Foundation	◻
Area Outline	◻
Cemetery	⊕
Building	◻
School	⚡
Church	⚡
Dam	⚡

HYDROLOGY:

Stream or Body of Water	-----
Hydro, Pool or Reservoir	-----
Jurisdictional Stream	-----JS-----
Buffer Zone 1	-----BZ 1-----
Buffer Zone 2	-----BZ 2-----
Flow Arrow	←
Disappearing Stream	-----
Spring	○
Wetland	-----
Proposed Lateral, Tail, Head Ditch	-----
False Sump	-----

RAILROADS:

Standard Gauge	-----
RR Signal Milepost	○
Switch	⊕
RR Abandoned	-----
RR Dismantled	-----

RIGHT OF WAY & PROJECT CONTROL:

Primary Horiz Control Point	○
Primary Horiz and Vert Control Point	●
Secondary Horiz and Vert Control Point	◆
Vertical Benchmark	⊕
Existing Right of Way Monument	△
Proposed Right of Way Monument (Rebar and Cap)	▲
Proposed Right of Way Monument (Concrete)	⊕
Existing Permanent Easement Monument	◇
Proposed Permanent Easement Monument (Rebar and Cap)	◆
Existing C/A Monument	△
Proposed C/A Monument (Rebar and Cap)	▲
Proposed C/A Monument (Concrete)	⊕
Existing Right of Way Line	-----
Proposed Right of Way Line	-----
Existing Control of Access Line	-----
Proposed Control of Access Line	-----
Proposed ROW and CA Line	-----
Existing Easement Line	-----E-----
Proposed Temporary Construction Easement	-----E-----
Proposed Temporary Drainage Easement	-----TDE-----
Proposed Permanent Drainage Easement	-----PDE-----
Proposed Permanent Drainage/Utility Easement	-----DUE-----
Proposed Permanent Utility Easement	-----PUE-----
Proposed Temporary Utility Easement	-----TUE-----
Proposed Aerial Utility Easement	-----AUE-----

ROADS AND RELATED FEATURES:

Existing Edge of Pavement	-----
Existing Curb	-----
Proposed Slope Stakes Cut	-----C-----
Proposed Slope Stakes Fill	-----F-----
Proposed Curb Ramp	-----CR-----
Existing Metal Guardrail	-----
Proposed Guardrail	-----
Existing Cable Guiderail	-----
Proposed Cable Guiderail	-----
Equality Symbol	⊕
Pavement Removal	-----
VEGETATION:	
Single Tree	○
Single Shrub	○
Hedge	-----

Woods Line	-----
Orchard	-----
Vineyard	-----

EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	-----
Bridge Wing Wall, Head Wall and End Wall	-----
MINOR:	
Head and End Wall	-----
Pipe Culvert	-----
Footbridge	-----
Drainage Box: Catch Basin, DI or JB	-----
Paved Ditch Gutter	-----
Storm Sewer Manhole	-----
Storm Sewer	-----

UTILITIES:

* SUE - Subsurface Utility Engineering
LOS - Level of Service - A,B,C or D (Accuracy)

POWER:	
Existing Power Pole	●
Proposed Power Pole	○
Existing Joint Use Pole	●
Proposed Joint Use Pole	○
Power Manhole	⊕
Power Line Tower	⊕
Power Transformer	⊕
U/G Power Cable Hand Hole	⊕
H-Frame Pole	●
U/G Power Line Test Hole (SUE - LOS A)*	⊕
U/G Power Line (SUE - LOS B)*	-----P-----
U/G Power Line (SUE - LOS C)*	-----P-----
U/G Power Line (SUE - LOS D)*	-----P-----

TELEPHONE:

Existing Telephone Pole	●
Proposed Telephone Pole	○
Telephone Manhole	⊕
Telephone Pedestal	⊕
Telephone Cell Tower	⊕
U/G Telephone Cable Hand Hole	⊕
U/G Telephone Test Hole (SUE - LOS A)*	⊕
U/G Telephone Cable (SUE - LOS B)*	-----T-----
U/G Telephone Cable (SUE - LOS C)*	-----T-----
U/G Telephone Cable (SUE - LOS D)*	-----T-----
U/G Telephone Conduit (SUE - LOS B)*	-----TC-----
U/G Telephone Conduit (SUE - LOS C)*	-----TC-----
U/G Telephone Conduit (SUE - LOS D)*	-----TC-----
U/G Fiber Optics Cable (SUE - LOS B)*	-----TFO-----
U/G Fiber Optics Cable (SUE - LOS C)*	-----TFO-----
U/G Fiber Optics Cable (SUE - LOS D)*	-----TFO-----

WATER:

Water Manhole	⊕
Water Meter	○
Water Valve	⊕
Water Hydrant	⊕
U/G Water Line Test Hole (SUE - LOS A)*	⊕
U/G Water Line (SUE - LOS B)*	-----
U/G Water Line (SUE - LOS C)*	-----
U/G Water Line (SUE - LOS D)*	-----
Above Ground Water Line	-----A/G Water-----

TV:

TV Pedestal	⊕
TV Tower	⊕
U/G TV Cable Hand Hole	⊕
U/G TV Test Hole (SUE - LOS A)*	⊕
U/G TV Cable (SUE - LOS B)*	-----TV-----
U/G TV Cable (SUE - LOS C)*	-----TV-----
U/G TV Cable (SUE - LOS D)*	-----TV-----
U/G Fiber Optic Cable (SUE - LOS B)*	-----TV FO-----
U/G Fiber Optic Cable (SUE - LOS C)*	-----TV FO-----
U/G Fiber Optic Cable (SUE - LOS D)*	-----TV FO-----

GAS:

Gas Valve	◇
Gas Meter	⊕
U/G Gas Line Test Hole (SUE - LOS A)*	⊕
U/G Gas Line (SUE - LOS B)*	-----G-----
U/G Gas Line (SUE - LOS C)*	-----G-----
U/G Gas Line (SUE - LOS D)*	-----G-----
Above Ground Gas Line	-----A/G Gas-----

SANITARY SEWER:

Sanitary Sewer Manhole	⊕
Sanitary Sewer Cleanout	⊕
U/G Sanitary Sewer Line	-----SS-----
Above Ground Sanitary Sewer	-----A/G Sanitary Sewer-----
SS Force Main Line Test Hole (SUE - LOS A)*	⊕
SS Force Main Line (SUE - LOS B)*	-----FSS-----
SS Force Main Line (SUE - LOS C)*	-----FSS-----
SS Force Main Line (SUE - LOS D)*	-----FSS-----


MISCELLANEOUS:

Utility Pole	●
Utility Pole with Base	⊕
Utility Located Object	○
Utility Traffic Signal Box	⊕
Utility Unknown U/G Line (SUE - LOS B)*	-----TUTL-----
U/G Tank; Water, Gas, Oil	-----
Underground Storage Tank, Approx. Loc.	-----UST-----
A/G Tank; Water, Gas, Oil	-----
Geoenvironmental Boring	⊕
Abandoned According to Utility Records	AATUR
End of Information	E.O.I.


8/17/99

PAVEMENT SCHEDULE (FINAL PAVEMENT DESIGN)	
C1	PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YD.
C2	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
C3	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH TO BE PLACED IN LAYERS NOT TO EXCEED 1.5" IN DEPTH
E1	PROP. APPROX. 4" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 450 LBS. PER SQ. YD.
E2	PROP. VAR. DEPTH 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" TO BE PLACED IN LAYERS NOT LESS THAN 3.0" OR GREATER THAN 5.5" IN DEPTH.
J	PROP. 6" AGGREGATE BASE COURSE.
R1	SHOULDER BERM GUTTER
T	EARTH MATERIAL.
U	EXISTING PAVEMENT.
W	WEDGING (SEE WEDGING DETAIL).

NOTE: PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE. SEE STRUCTURE PLANS FOR BRIDGE CONSTRUCTION




DETAIL SHOWING METHOD OF WEDGING




SHOULDER BERM GUTTER DETAIL

USE IN CONJUNCTION WITH TYPICAL SECTION NO. 2
-L- STA 15+42.00 TO STA 15+54.00 (LT)




TYPICAL SECTION NO. 1

-L- STA 10+10.00 TO STA 13+40.00
-L- STA 16+85.00 TO STA 18+70.00




TYPICAL SECTION NO. 2

-L- STA 13+40.00 TO STA 14+28.88 (BEG. BRIDGE)
-L- STA 15+31.13 (END BRIDGE) TO STA 16+85.00




BRIDGE TYPICAL SECTION NO. 3

-L- STA 14+28.88 (BEGIN BRIDGE) TO STA 15+31.13 (END BRIDGE)




TYPICAL SECTION NO. 4

-Y- STA 10+10.12 TO STA 11+00.66




TYPICAL SECTION NO. 5

-DR1- STA 10+10.18 TO STA 11+20.00



DETAIL GUARDRAIL

-L- STA 10+68.21 TO STA 14+30.71 (LT)
-L- STA 13+80.71 TO STA 14+30.71 (RT)
-L- STA 15+54.00 TO STA 16+66.80 (LT)
-L- STA 15+29.30 TO STA 16+79.30 (RT)



MILLING DETAIL FOR PROFILE CONNECTIONS

TYING PROPOSED PAVEMENTS TO EXISTING PAVEMENTS

PROJECT REFERENCE NO. BP13.R002	SHEET NO. 2A-1
ROADWAY DESIGN ENGINEER 3/8/2024	PAVEMENT DESIGN ENGINEER 3/11/2024
<p>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</p>	
<p>PLANS PREPARED BY: </p>	
<p>WSP USA 434 FAYETTEVILLE STREET SUITE 1500 RALEIGH, NC 27601 TEL: 1.919.836.4040 FAX: 1.919.836.4099 LICENSE NO. E-0165</p>	

REVISIONS

12/4/2024
10:00 AM
RDY_TYP-02A
3/7/2024

**STATE OF NORTH CAROLINA
 DIVISION OF HIGHWAYS**

SUMMARY OF SUBSURFACE DRAINAGE

LINE	Station	Station	Location LT/RT/CL	Drain Type* UD/BD/SD	LF
CONTINGENCY				SD	200
TOTAL LF:					200

*UD = Underdrain
 *BD = Blind Drain
 *SD = Subsurface Drain

**SUMMARY OF GEOTEXTILE
 FOR SUBGRADE STABILIZATION**

LINE	Station	Station	Geotextile for Subgrade Stabilization SY
CONTINGENCY			200
TOTAL SY:			200*

*Total square yards of "Geotextile for Subgrade Stabilization" is only the estimated quantity for subgrades and may only represent a portion of the geotextile quantity shown in the Item Sheets of the Proposal.

SUMMARY OF AGGREGATE SUBGRADE/STABILIZATION

LINE	Station	Station	Aggregate Type* ASU(1/2)/ AST	Aggregate Thickness INCHES [8" for ASU(2)]	Shallow Undercut CY	Class IV Subgrade Stabilization TONS	Geotextile for Subgrade Stabilization SY	Stabilizer Aggregate TONS	Class IV Aggregate Stabilization TONS
CONTINGENCY			ASU(1)	12	100	200	300		
TOTAL CY/TONS/SY:					100	200**	300**	0	0


*ASU(1/2) = Aggregate Subgrade (Type 1 or 2)
 *AST = Aggregate Stabilization
 **Total tons of "Class IV Subgrade Stabilization" and total square yards of "Geotextile for Subgrade Stabilization" are only the estimated quantities for ASU(1/2)/AST and may only represent a portion of the subgrade stabilization and geotextile quantities shown in the Item Sheets of the Proposal.

8/17/99





REVISIONS

12:40:30 PM RDY_PSH-04
8/20/2024

-L-	-L-
PI Sta 12+37.11	PI Sta 17+59.45
$\Delta = 42' 39" 51.4" (LT)$	$\Delta = 0' 48" 00.8" (RT)$
$D = 16' 22" 12.8"$	$D = 0' 17" 11.3"$
$L = 260.62'$	$L = 279.33'$
$T = 136.69'$	$T = 139.67'$
$R = 350.00'$	$R = 20,000.00'$
$e = 6\%$	$e = NC$
$Ro = 99'$	$Ds = 45 MPH$
$Ds = 35 MPH **$	



PROJECT REFERENCE NO. BP13.R002	SHEET NO. 4
RW SHEET NO.	HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER 8/7/2024	HYDRAULICS ENGINEER 8/7/2024
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
PLANS PREPARED BY:	
	WSP USA 434 FAYETTEVILLE STREET SUITE 1500 RALEIGH, NC 27601 TEL: 1.919.836.4040 FAX: 1.919.836.4099 LICENSE NO. E-0165



**NOTE: DESIGN EXCEPTION IS REQUIRED


5/28/99

PIPE HYDRAULIC DATA
24" RCP-III STA. 12+39

DESIGN DISCHARGE	= 15.8	CFS
DESIGN FREQUENCY	= 25	YRS
DESIGN HW ELEVATION	= 874.6	FT
BASE DISCHARGE	= 18.6	CFS
BASE FREQUENCY	= 100	YRS
BASE HW ELEVATION	= 874.9	FT
OVERTOPPING DISCHARGE	= 32.6	CFS
OVERTOPPING FREQUENCY	= 500+	YRS
OVERTOPPING ELEVATION	= 877.5	FT

-L-
SR 1762
(NEW HOUSE RD.)

PROJECT REFERENCE NO. BPI3.R002	SHEET NO. 5
ROADWAY DESIGN ENGINEER 3/8/2024	HYDRAULICS ENGINEER 8/2024
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
PLANS PREPARED BY: 	
WSP USA 434 FAYETTEVILLE STREET SUITE 1500 RALEIGH, NC 27601 TEL: 1.919.836.4040 FAX: 1.919.836.4099 LICENSE NO. F-0165	




BRIDGE HYDRAULIC DATA

DESIGN DISCHARGE	= 1700	CFS
DESIGN FREQUENCY	= 25	YRS
DESIGN HW ELEVATION	= 864.5	FT
BASE DISCHARGE	= 2400	CFS
BASE FREQUENCY	= 100	YRS
BASE HW ELEVATION	= 865.4	FT
OVERTOPPING DISCHARGE	= 9800	CFS
OVERTOPPING FREQUENCY	= 500+	YRS
OVERTOPPING ELEVATION	= 872.18	FT
DATE OF SURVEY	= 8/18	
W.S. ELEVATION AT DATE OF SURVEY	= 855J	FT

-Y-
GENE WALKER RD.

-DR1-



12:39:44 PM
800050.RD_Y_PFL-05
3/7/2024

3/2023


STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	BP13.R002	RW01	5

TIP PROJECT: BP13.R002


STATE OF NORTH CAROLINA
 DIVISION OF HIGHWAYS

SURVEY CONTROL, EXISTING CENTERLINES,
 RIGHT OF WAY, EASEMENTS AND PROPERTY TIES

RUTHERFORD COUNTY



21-MAR-2024 14:52
 S:\Surveyors\Projects\LIB\800090\2023 RW Staking\as-submit\red_240321\800090_is_r_w01.dgn
 mcornewell AT MORNWELLAPTOP



DATUM DESCRIPTION

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "GPS 90-1" WITH NAD 83/NSRS 2011 STATE PLANE GRID COORDINATES OF NORTHING: 600,391.143(ft) EASTING: 1,192,006.603(ft) ELEVATION: 875.00(ft)

THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.99983699

THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "GPS 90-1" TO -L- STATION 10+00.00 IS S 42°09'38.9" W 754.467(ft)

ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES VERTICAL DATUM USED IS NAVD 88

Prepared in the Office of:

TGS ENGINEERS
 TGS ENGINEERS
 201 WEST MARION STREET
 SUITE 200
 SHELBY, NC 28150
 PH (704) 476-0003
 CORP. LICENSE NO.: C-0275

2024 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: 22/2023


LETTING DATE: 6/19/2024

PROFESSIONAL LAND SURVEYOR

DocuSigned by:
 Matthew Cornwell
 ESD01MF114716475

3/21/2024


SIGNATURE: _____ Date: _____



PROPOSED ALIGNMENT CONTROL SHEET

PROJECT REFERENCE NO.	SHEET NO.
BP13.R002	RW02D-1

Location and Surveys



TGS ENGINEERS
201 WEST MARION STREET
SUITE 200
SHELBY, NC 28150
PH (704) 476-0003
CORP. LICENSE NO.: C-0275

PROJECT SURVEYOR

DocuSigned by:
Matthew Cornwell
EBD36F11473E475...

3/30/2023



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

I, Matthew T. Cornwell, PLS, certify that the data compiled came from available surveys/mapping performed by others and provided to me by NCDOT and do not certify to the accuracy or quality of the individual data sources.

This 3/30/2023

DocuSigned by:
Matthew Cornwell
EBD36F11473E475...

Professional Land Surveyor L-4775

REVISIONS

L

TYPE	STATION	NORTH	EAST
POT	10+00.00	599831.8836	1191500.1941
PC	11+00.42	599866.4043	1191594.4966
PT	13+61.04	600034.9283	1191785.3946
PC	16+19.78	600264.9929	1191903.7836
PT	18+99.11	600512.4654	1192033.3243

Y

TYPE	STATION	NORTH	EAST
POT	10+00.00	600422.9688	1191985.9681
POT	12+00.00	600358.2901	1192175.2210

DR1



TYPE	STATION	NORTH	EAST
POT	10+00.00	600033.5548	1191784.6839
POT	11+20.00	599999.3855	1191899.7137

NOTES:

1. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
2. THE PROPOSED ALIGNMENT CONTROL DATA FOR THIS PROJECT HAS BEEN COMPILED FROM VARIOUS SOURCES. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.

30 MAR 2023 09:14
 S:\Projects\13\2023\800090.RW.MTC\800090_1s_rw02d-1.dgn
 Matthew T. Cornwell
 Professional Land Surveyor L-4775

RIGHT OF WAY CONTROL SHEET

PROJECT REFERENCE NO.	SHEET NO.
BP13.R002	RW03E-1
Location and Surveys	
 TGS ENGINEERS 201 WEST MARION STREET SUITE 200 SHELBY, NC 28150 PH (704) 476-0003 CORP. LICENSE NO.: C-0275	
PROJECT SURVEYOR	
Digitally signed by: <i>Matthew Cornwell</i> EBC09F1473E475...	
3/30/2023	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

I, Matthew T. Cornwell, certify that the right of way and permanent easement monumentation for this project shown herein was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:10,000 (Class A). Field work was performed from 3/22/2023 to 3/24/2023, and all coordinates are based on NAD83/2011; That this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 3/30/2023
 Digitally signed by:
Matthew Cornwell
 Professional Land Surveyor L-4775

ROW MARKER IRON PIN AND CAP

ALIGN	STATION	OFFSET	NORTH	EAST
L	10+00.00	-16.16	599847.0597	1191494.6387
L	10+00.00	-45.00	599874.1413	1191484.7251
L	10+00.00	15.84	599817.0096	1191505.6389
L	10+00.00	30.00	599803.7119	1191510.5067
L	11+00.42	30.00	599838.2325	1191604.8093
L	11+00.42	-45.00	599908.6620	1191579.0276
L	13+00.00	30.00	599965.2066	1191776.7720
L	13+40.79	70.00	599981.6259	1191835.8998
L	13+61.04	-45.00	600055.5186	1191745.3816
L	13+89.10	44.57	600039.4834	1191837.8593
L	16+19.78	-45.00	600285.5832	1191863.7706
L	16+19.78	45.00	600244.4025	1191943.7966
L	17+65.00	45.00	600372.9946	1192010.5605
L	18+70.00	-45.00	600507.8482	1191979.9104
L	18+70.00	-16.07	600494.2895	1192005.4680
L	18+70.00	15.93	600479.2927	1192033.7362

REBAR SET (NO CAP)

ROW MARKER IRON PIN AND CAP




ALIGN	STATION	OFFSET	NORTH	EAST
Y	10+50.00	-30.74	600435.8886	1192043.2229
Y	10+75.00	30.04	600370.2889	1192047.2233

REVISIONS


30_MAR_2023_09:17
 S:\Survey\Projects\13\2023\800090.RW.MTC\800090_1s_rw03e-1.dgn
 Matthew Cornwell
 Professional Land Surveyor L-4775

NOTES:

1. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.
2. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
3. RIGHT OF WAY MONUMENTATION ESTABLISHED 3/22/2023 TO 3/24/2023.

PROJECT REFERENCE NO.	SHEET NO.
BP13.R002	RW04
Location and Surveys	
 TGS ENGINEERS 201 WEST MARION STREET SUITE 200 SHELBY, NC 28150 PH (704) 476-0003 CORP. LICENSE NO.: C-0275	
PROJECT SURVEYOR	
Declassified by:  EBCOMP1475E475...	
	
4/5/2023	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

-L-	-L-
PI Sta 12+37.11	PI Sta 17+59.45
$\Delta = 42^{\circ} 39' 51.4" (LT)$	$\Delta = 0^{\circ} 48' 00.8" (RT)$
$D = 16^{\circ} 22' 12.8"$	$D = 0^{\circ} 17' 11.3"$
$L = 260.62'$	$L = 279.33'$
$T = 136.69'$	$T = 139.67'$
$R = 350.00'$	$R = 20,000.00'$
$e = 6\%$	$e = NC$
$Ro = 99'$	$Ds = 45 MPH$
$Ds = 35 MPH$	




I, Matthew T. Cornwell, certify that the right of way and permanent easement monumentation for this project shown herein was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:10,000 (Class A). Field work was performed from 3/22/2023 to 3/24/2023, and all coordinates are based on NAD83/2011; That this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 4/5/2023
 Declassified by:

 EBCOMP1475E475...
 Professional Land Surveyor L-4775

REVISIONS



NOTES:



1. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.
2. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
3. RIGHT OF WAY MONUMENTATION ESTABLISHED 3/22/2023 TO 3/24/2023.

05-APR-2023 14:30
 S:\Survey\Projects\1318\2023\800090.RW.MTC\800090_1.s_rw04.dgn
 Matthew T. Cornwell
 A PROFESSIONAL LAND SURVEYOR

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

TRANSPORTATION MANAGEMENT PLAN

RUTHERFORD COUNTY




INDEX OF SHEETS

SHEET NO.	TITLE
TMP-01	TITLE SHEET, VICINITY MAP AND INDEX OF SHEETS
TMP-02	ROADWAY STANDARD DRAWINGS AND LEGEND
TMP-02A	SIGN DESIGN
TMP-03	GENERAL NOTES AND WRITTEN PHASING
TMP-04	OFFSITE DETOUR ROUTE SIGNING

SHEET NO.
TMP-01

12/14/2023
F:\NCDOT_Div3_LIBR\Rutherford.dwg\090\Rutherford.d090_TMP-01.dgn
dohtm



PLANS PREPARED BY:


DERRICK DOHM, EI

RICHARD ODYSKI, PE


NCDOT CONTACTS:

ZACHARY CLARK, PE
PROJECT ENGINEER

KARMEN DAIS, PE
PROJECT DESIGN ENGINEER



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



APPROVED: *Richard Odynski*
3/8/2024

PROJECT: BP13.R002






ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS SHOWN IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2024 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

<u>STD. NO.</u>	<u>TITLE</u>
1101.01	WORK ZONE ADVANCE WARNING SIGNS
1101.02	TEMPORARY LANE CLOSURES
1101.03	TEMPORARY ROAD CLOSURES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.01	STATIONARY WORK ZONE SIGNS
1110.02	PORTABLE WORK ZONE SIGNS
1130.01	DRUM
1135.01	CONES
1145.01	BARRICADES
1150.01	FLAGGING DEVICES
1180.01	SKINNY-DRUM











LEGEND

GENERAL




-  DIRECTION OF TRAFFIC FLOW
-  DIRECTION OF PEDESTRIAN TRAFFIC FLOW
-  EXIST. PVMT.
-  NORTH ARROW
-  PROPOSED PVMT.




TRAFFIC CONTROL DEVICES


-  BARRICADE (TYPE III)
-  CONE
-  DRUM
-  SKINNY DRUM
-  TEMPORARY CRASH CUSHION
-  FLASHING ARROW BOARD
-  FLAGGER
-  LAW ENFORCEMENT
-  TRUCK MOUNTED ATTENUATOR (TMA)
-  CHANGEABLE MESSAGE SIGN

TEMPORARY SIGNING


-  PORTABLE SIGN
-  STATIONARY SIGN
-  STATIONARY OR PORTABLE SIGN

APPROVED: 
1987EAA8A8F87E4E

DATE: 3/8/2024




**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



TRANSPORTATION
MANAGEMENT PLANS
ROADWAY STANDARD
DRAWINGS & LEGEND

SIGN NUMBER: SP-01 TYPE: GROUND QUANTITY: 1 SIGN WIDTH: 3'-6" HEIGHT: 1'-0" TOTAL AREA: 3.5 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0.47" WIDTH: 0.63" RADII: 1.5" NO. Z BARS: LENGTH:	BACKG COLOR: Fluorescent Orange COPY COLOR: Black <table border="1"> <thead> <tr> <th>SYMBOL</th> <th>X</th> <th>Y</th> <th>WID</th> <th>HT</th> </tr> </thead> <tbody> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table> MAT'L: 0.063" (1.6 mm) ALUMINUM 0.060" (2.0 mm) ALUMINUM 0.125" (3.2 mm) ALUMINUM	SYMBOL	X	Y	WID	HT																																									DESIGN BY: DAD PROJECT ID: R.005 CHECKED BY: RAO DIV: 13 Apr 18, 2022
SYMBOL	X	Y	WID	HT																																											



Spacing Factor Is 1 unless specified otherwise

Letter spacings are to start of next letter															Series/Size	Text Length				
N	E	W	H	O	U	S	E	R	D						C 2000	35.8				
3.1	3.1	2.4	3	4	3	3.2	2.9	2.9	2	4	2.9	2.2	3.1							

USE NOTES:

- Legend and border shall be direct applied black non-reflective sheeting.
- Background shall be NC Grade B fluorescent orange retroreflective sheeting.
- To be mounted with Detour signing.

FILENAME: detour_sign NORTH CAROLINA D.O.T. SIGN DETAIL

APPROVED:  DATE: 3/8/2024 		TRANSPORTATION MANAGEMENT PLANS SIGN DESIGN
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		

GENERAL NOTES

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS, AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS OR RESULT IN DUPLICATE OR UNDESIRE OVERLAPPING OF DEVICES. MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING, OR REMOVAL OF DEVICES AS DIRECTED BY THE ENGINEER.

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT EXCEPT WHEN OTHERWISE NOTED IN THE PLAN OR DIRECTED BY THE ENGINEER.

LANE AND SHOULDER CLOSURE REQUIREMENTS

- A) REMOVE LANE CLOSURE DEVICES FROM THE LANE WHEN WORK IS NOT BEING PERFORMED BEHIND THE LANE CLOSURE OR WHEN A LANE CLOSURE IS NO LONGER NEEDED OR AS DIRECTED BY THE ENGINEER.
- B) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN 15 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN SHOULDER USING ROADWAY STANDARD DRAWING NO. 1101.04 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL OR A LANE CLOSURE IS INSTALLED.
- C) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO AN UNDIVIDED FACILITY AND WITHIN 5 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.

WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO A DIVIDED FACILITY AND WITHIN 10 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.

- D) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN A LANE OF TRAVEL OF AN UNDIVIDED OR DIVIDED FACILITY, CLOSE THE LANE ACCORDING TO THE TRAFFIC CONTROL PLANS, ROADWAY STANDARD DRAWINGS, OR AS DIRECTED BY THE ENGINEER. CONDUCT THE WORK SO THAT ALL PERSONNEL AND/OR EQUIPMENT REMAIN WITHIN THE CLOSED TRAVEL LANE.
- E) DO NOT WORK SIMULTANEOUSLY WITHIN 15 FT ON BOTH SIDES OF AN OPEN TRAVELWAY, RAMP, OR LOOP WITHIN THE SAME LOCATION UNLESS PROTECTED WITH GUARDRAIL OR BARRIER.

PAVEMENT EDGE DROP OFF REQUIREMENTS

- F) BACKFILL AT A 6:1 SLOPE UP TO THE EDGE AND ELEVATION OF EXISTING PAVEMENT IN AREAS ADJACENT TO AN OPENED TRAVEL LANE THAT HAS AN EDGE OF PAVEMENT DROP-OFF AS FOLLOWS:
 - BACKFILL DROP-OFFS THAT EXCEED 2 INCHES ON ROADWAYS WITH POSTED SPEED LIMITS OF 45 MPH OR GREATER.
 - BACKFILL DROP-OFFS THAT EXCEED 3 INCHES ON ROADWAYS WITH POSTED SPEED LIMITS LESS THAN 45 MPH.
 - BACKFILL WITH SUITABLE COMPACTED MATERIAL, AS APPROVED BY THE ENGINEER, AT NO EXPENSE TO THE DEPARTMENT.
- G) DO NOT EXCEED A DIFFERENCE OF 2 INCHES IN ELEVATION BETWEEN OPEN LANES OF TRAFFIC FOR NOMINAL LIFTS OF 1.5 INCHES. INSTALL ADVANCE WARNING "UNEVEN LANES" SIGNS (W8-11) 500 FT IN ADVANCE AND A MINIMUM OF EVERY HALF MILE THROUGHOUT THE UNEVEN AREA.

TRAFFIC PATTERN ALTERATIONS

- H) NOTIFY THE ENGINEER THIRTY (30) CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION.

SIGNING




- I) INSTALL ADVANCE WORK ZONE WARNING SIGNS WHEN WORK IS WITHIN 40 FT FROM THE EDGE OF TRAVEL LANE AND NO MORE THAN THREE (3) DAYS PRIOR TO THE BEGINNING OF CONSTRUCTION.
- J) PROVIDE SIGNING AND DEVICES REQUIRED TO CLOSE THE ROAD ACCORDING TO THE ROADWAY STANDARD DRAWINGS AND TRAFFIC CONTROL PLANS.
 - PROVIDE SIGNING REQUIRED FOR THE OFF-SITE DETOUR ROUTE AS SHOWN IN THE TRAFFIC CONTROL PLANS.
- K) COVER OR REMOVE ALL SIGNS AND DEVICES REQUIRED TO CLOSE THE ROAD WHEN ROAD CLOSURE IS NOT IN OPERATION.
 - COVER OR REMOVE ALL SIGNS REQUIRED FOR THE OFF-SITE DETOUR WHEN THE DETOUR IS NOT IN OPERATION.
- L) ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY TRAFFIC PATTERN.

TRAFFIC CONTROL DEVICES


- M) PLACE TYPE III BARRICADES, WITH "ROAD CLOSED" SIGN R11-2 ATTACHED, OF SUFFICIENT LENGTH TO CLOSE ENTIRE ROADWAY.

PHASING NOTES

- STEP 1: INSTALL WORK ZONE ADVANCE WARNING SIGNS ON NEW HOUSE RD. ACCORDING TO ROADWAY STANDARD DRAWING NO. 1101.01 WHERE WORK WILL BE OCCURRING NO MORE THAN THREE DAYS PRIOR TO BEGINNING CONSTRUCTION.
- STEP 2: USING ROADWAY STANDARD DRAWING NO. 1101.03, SHEETS 1 AND 2 OF 9, AND SHEET TMP-04, INSTALL ROAD CLOSURE AND DETOUR SIGNS FOR NEW HOUSE RD. COVER SIGNS UNTIL DETOUR IS READY FOR OPERATION.
- STEP 3: WHEN DETOUR IS READY UNCOVER SIGNS AND CLOSE NEW HOUSE RD. CONSTRUCT STRUCTURE AND ROADWAY IMPROVEMENTS INCLUDING FINAL ASPHALT OVERLAY AND PAVEMENT MARKINGS ALONG NEW HOUSE RD. USING ROADWAY STANDARD DRAWING NO. 1101.02, SHEET 1 OF 14, INSTALL MILL AND OVERLAY AND PAVEMENT MARKINGS ALONG GENE WALKER RD.
- STEP 4: REMOVE ROAD CLOSURE DEVICES AND SIGNS ONCE CONSTRUCTION IS COMPLETE. OPEN NEW HOUSE RD. TO TRAFFIC.

APPROVED:  DATE: 3/8/2024			TRANSPORTATION MANAGEMENT PLANS GENERAL NOTES AND WRITTEN PHASING
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			

NEW HOUSE RD SP-01 42" X 12"	NEW HOUSE RD SP-01 42" X 12"	NEW HOUSE RD SP-01 42" X 12"	NEW HOUSE RD SP-01 42" X 12"
DETOUR M4-8 24" X 12"	DETOUR M4-8 24" X 12"	DETOUR M4-8 24" X 12"	DETOUR M4-8 24" X 12"
M5-1 21" X 15"	M6-1 21" X 15"	M5-1 L 21" X 15"	M6-1 L 21" X 15"
(A)	(B)	(C)	(D)
END DETOUR M4-8 A 24" X 18"	ROAD CLOSED AHEAD W20-3 48" X 48"	DETOUR AHEAD W20-2 48" X 48"	ROAD CLOSED 1000 FT W20-3 48" X 48"
(E)	(F)	(G)	(H)
ROAD CLOSED 500 FT W20-3 48" X 48"	ROAD CLOSED AHEAD W20-3 48" X 48"	ROAD CLOSED AHEAD W20-3 48" X 48"	ROAD CLOSED W20-3 48" X 48"
(I)	NEXT LEFT SP-4L 42" X 12"	NEXT RIGHT SP-4R 42" X 12"	NEXT LEFT SP-4L 42" X 12"
(J)	(K)	(L)	(L)




NOTE: COORDINATE WITH THE ENGINEER TO FIELD LOCATE SIGNS AS NEEDED.

APPROVED: *Richard Odynski*
DATE: 3/8/2024

SEAL
037467
ENGINEER
RICHARD A ODYNSKI

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



TRANSPORTATION
MANAGEMENT PLANS
OFFSITE DETOUR
ROUTE SIGNING



3/6/2024 10:58:42 AM
 \\bususer\cma38456\8000090_pmp_tsh.dgn
 US1004421

CONTRACT: DM00406 PROJECT: BP13.R002

**STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION**

**PAVEMENT MARKING PLANS
 RUTHERFORD COUNTY**



TIP NO. BP13.R002	SHEET NO. PMP-1
APPROVED:  <small>DocuSigned by: Eric W. Bowman DADA2D3C6B0246F...</small>	
DATE: 3/6/2024	
SEAL 	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

GENERAL NOTES

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN, OR DIRECTED BY THE ENGINEER.

A) INSTALL PAVEMENT MARKINGS AND PAVEMENT MARKERS ON THE FINAL SURFACE AS FOLLOWS:

ROAD NAME	MARKING	MARKER
ALL	PAINT	NONE
BRIDGE	PAINT	NONE

B) PLACE TWO APPLICATIONS OF PAINT PAVEMENT MARKINGS ON THE FINAL WEARING SURFACE. PLACE THE SECOND APPLICATION OF PAINT UPON SUFFICIENT DRYING TIME OF THE FIRST.

C) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.

D) REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND MARKERS.

E) PASSING ZONES WILL BE DETERMINED IN THE FIELD AND MUST BE APPROVED BY THE ENGINEER.

F) SEE ROADWAY PLANS FOR GUARD/GUIDE RAIL DETAILS.

INDEX

SHEET NO.	DESCRIPTION
PMP-1	TITLE SHEET, INDEX, GENERAL NOTES & ROADWAY STANDARD DRAWINGS
PMP-2	PROPOSED PAVEMENT MARKING PLAN SHEET

ROADWAY STANDARD DRAWING

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2024 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:


STD. NO.	TITLE
1205.01	PAVEMENT MARKINGS - LINE TYPES AND OFFSETS
1205.02	PAVEMENT MARKINGS - TWO-LANE AND MULTILANE ROADWAYS
1205.04	PAVEMENT MARKINGS - INTERSECTIONS
1205.12	PAVEMENT MARKINGS - BRIDGES
1261.01	GUARDRAIL AND BARRIER DELINEATORS - INSTALLATION SPACING
1261.02	GUARDRAIL AND BARRIER DELINEATORS - TYPES AND MOUNTING
1262.01	GUARDRAIL END DELINEATION



WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 NC LIC. NO. F-0165



PLAN PREPARED BY:

ERIC W BOWMAN, PE *SR. TRANSPORTATION DESIGNER*
 SAYMA AFREEN *TRANSPORTATION DESIGNER*

TIP NO. BP13.R002	SHEET NO. PMP-02
APPROVED: <i>Eric W. Bowman</i> DADA203080246F	
DATE: 3/6/2024	
SEAL 	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

PAVEMENT MARKING SCHEDULE
TIP PROJECT # BP13.R002

SYMBOL	DESCRIPTION
	PAINT (4")
P1	WHITE EDGELINE
P5	2FT. - 6FT./SP WHITE MINISKIP
P13	YELLOW DOUBLE CENTER




12/15/2023
c:\bms\2\lbususer\dms38456\80000090_pmp_psh_2.dgn
USEB0442

**PAVEMENT MARKING
PLAN SHEET**

TIP PROJECT: BP13.R002

See Sheet 1A For Index of Sheets
See Sheet 1B For Conventional Symbols



VICINITY MAP


STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS
RUTHERFORD COUNTY

PLAN FOR PROPOSED
HIGHWAY EROSION CONTROL

LOCATION: REPLACE BRIDGE NO. 090 OVER SANDY RUN
ON SR 1762 (NEW HOUSE RD)

TYPE OF WORK: GRADING, PAVING, DRAINAGE, & STRUCTURE

●●● OFF-SITE DETOUR



THIS PROJECT CONTAINS
EROSION CONTROL PLANS
FOR CLEARING AND
GRUBBING PHASE OF
CONSTRUCTION.

GRAPHIC SCALE



THESE EROSION AND SEDIMENT CONTROL PLANS COMPLY WITH
THE APPLICABLE REGULATIONS SET FORTH BY THE NCG-010000
GENERAL CONSTRUCTION PERMIT EFFECTIVE APRIL 1, 2019
AND ISSUED BY THE NORTH CAROLINA DEPARTMENT OF
ENVIRONMENTAL QUALITY DIVISION OF WATER RESOURCES.



Prepared in the Office of:



WSP USA
1001 MOREHEAD SQUARE DRIVE
SUITE 610
CHARLOTTE, NC 28203
TEL: 1.704.342.5401

LICENSE NO. F-0165

Designed by:

James Owen Britt, P.E. 4228
NAME LEVEL III CERTIFICATION NO.

Roadway Standard Drawings

The "Roadway Standard Drawings"- Roadway Design Unit - N. C.
Department of Transportation - Raleigh, N. C., dated January 2024
and the latest revision thereto are applicable to this project and by
reference hereby are considered a part of these plans.

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	BP13.R002	EC-1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
BP13.R002.1	N/A	P.E.	
BP13.R002.2	N/A	R/W & UTIL.	

DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA




PROJECT REFERENCE NO.	SHEET NO.
BP13.R002	EC-2
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

EROSION & SEDIMENT CONTROL LEGEND

Std. #	Description	Symbol	Std. #	Description	Symbol
1605.01	Temporary Silt Fence		1633.01	Temporary Rock Silt Check Type A	
1606.01	Special Sediment Control Fence		1633.02	Temporary Rock Silt Check Type B	
1622.01	Temporary Berms and Slope Drains		1633.03	Temporary Rock Silt Check Type A with Excelsior Matting and Flocculant	
1630.02	Silt Basin Type B		1634.01	Temporary Rock Sediment Dam Type A	
1630.03	Temporary Silt Ditch		1634.02	Temporary Rock Sediment Dam Type B	
1630.04	Stilling Basin		1635.01	Rock Pipe Inlet Sediment Trap Type A	
1630.05	Temporary Diversion		1635.02	Rock Pipe Inlet Sediment Trap Type B	
1630.06	Special Stilling Basin		1636.01	Excelsior Wattle Check	
1630.07	Skimmer Basin		1636.01	Excelsior Wattle Check with Flocculant	
1630.08	Tiered Skimmer Basin		1636.01	Coir Fiber Wattle Check	
1630.09	Earthen Dam with Skimmer		1636.01	Coir Fiber Wattle Check with Flocculant	
	Infiltration Basin		1636.02	Silt Fence Excelsior Wattle Break	
	Rock Inlet Sediment Trap:			Silt Fence Coir Fiber Wattle Break	
1632.01	Type A		1636.03	Excelsior Wattle Barrier	
1632.02	Type B		1636.03	Coir Fiber Wattle Barrier	
1632.03	Type C				




PROJECT REFERENCE NO. <i>BPI3.R002</i>	SHEET NO. <i>EC-2A</i>
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

ONSITE CONCRETE WASHOUT STRUCTURE WITH LINER



BELOW GRADE WASHOUT STRUCTURE
NOT TO SCALE

- NOTES:**
1. ACTUAL LOCATION DETERMINED IN FIELD
 2. THE CONCRETE WASHOUT STRUCTURES SHALL BE MAINTAINED WHEN THE LIQUID AND/OR SOLID REACHES 75% OF THE STRUCTURES CAPACITY TO PROVIDE ADEQUATE HOLDING CAPACITY WITH A MINIMUM 12 INCHES OF FREEBOARD.
 3. CONCRETE WASHOUT STRUCTURE NEEDS TO BE CLEARLY MARKED WITH SIGNAGE NOTING DEVICE.



ABOVE GRADE WASHOUT STRUCTURE
NOT TO SCALE

- NOTES:**
1. ACTUAL LOCATION DETERMINED IN FIELD
 2. THE CONCRETE WASHOUT STRUCTURES SHALL BE MAINTAINED WHEN THE LIQUID AND/OR SOLID REACHES 75% OF THE STRUCTURES CAPACITY TO PROVIDE ADEQUATE HOLDING CAPACITY WITH A MINIMUM 12 INCHES OF FREEBOARD.
 3. CONCRETE WASHOUT STRUCTURE NEEDS TO BE CLEARLY MARKED WITH SIGNAGE NOTING DEVICE.

8/17/99

REVISIONS

3/25/2024
C:\Users\brinkhoff\Documents\152316\800090_EC-03.dgn
BRINKHOFF

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS


SOIL STABILIZATION TIMEFRAMES


PROJECT REFERENCE NO. BP13.R002	SHEET NO. EC-3
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
PLANS PREPARED BY:	
<div style="font-size: x-small; display: inline-block; vertical-align: middle; margin-left: 10px;"> WSP USA 434 FAYETTEVILLE STREET SUITE 1500 RALEIGH, NC 27601 TEL: 919.836.4040 FAX: 919.836.4099 LICENSE NO. F-0165 </div>	

SITE DESCRIPTION	STABILIZATION TIME	TIMEFRAME EXCEPTIONS
PERIMETER DIKES, SWALES, DITCHES AND SLOPES	7 DAYS	NONE
HIGH QUALITY WATER (HOW) ZONES	7 DAYS	NONE
SLOPES STEEPER THAN 3:1	7 DAYS	IF SLOPES ARE 10' OR LESS IN LENGTH AND ARE NOT STEEPER THAN 2:1, 14 DAYS ARE ALLOWED.
SLOPES 3:1 OR FLATTER	14 DAYS	7 DAYS FOR SLOPES GREATER THAN 50' IN LENGTH.
ALL OTHER AREAS WITH SLOPES FLATTER THAN 4:1	14 DAYS	NONE, EXCEPT FOR PERIMETERS AND HOW ZONES.

EROSION CONTROL PLAN


CLEARING AND GRUBBING
EROSION CONTROL FOR
CONSTRUCTION SHEET 4

PROJECT REFERENCE NO. BP13.R002	SHEET NO. EC-4/CONST.4
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
PLANS PREPARED BY:	
 WSP USA 434 FAYETTEVILLE STREET SUITE 1500 RALEIGH, NC 27601 TEL: 1.919.836.4040 FAX: 1.919.836.4099 LICENSE NO. F-0165	




NOTE:
PERIMETER EROSION CONTROL MEASURES SHALL BE
INSTALLED DURING CLEARING AND GRUBBING PHASE.

NOTE:
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B
AND TEMPORARY ROCK SILT CHECKS TYPE - A AT
DRAINAGE OUTLETS.







REVISIONS

8/17/99
 3/25/2024
 C:\Users\brinkner\OneDrive\Documents\152316\800090_EC-04.dgn
 CAROLAN BRINKNER


PROJECT REFERENCE NO. BP13.R002	SHEET NO. EC-5/CONST.4
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
PLANS PREPARED BY:	
 WSP USA 434 FAYETTEVILLE STREET SUITE 1500 RALEIGH, NC 27601 TEL: 1.919.836.4040 FAX: 1.919.836.4099 LICENSE NO. F-0165	

EROSION CONTROL PLAN



REVISIONS

3/25/2024
C:\Users\brink\Documents\40152316\8000090_EC-05.dgn
PARSONS BRINCKERHOFF



STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

SIGNING PLAN
RUTHERFORD COUNTY
LOCATION: REPLACE BRIDGE NO. 090 OVER SANDY RUN
ON SR 1762 (NEW HOUSE RD)


BP13.R002
SIGN 001

NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION


DocuSigned by:
Ashley Matthews
40171A41BC894CD

APPROVED: 3/5/2024 | 10:33 AM EST

SEAL



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



ROADWAY STANDARD DRAWING

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2024 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
904.10	ORIENTATION OF GROUND MOUNTED SIGNS
904.20	SECONDARY SIGN MOUNTING
904.50	MOUNTING OF TYPE 'D', 'E' AND 'F' SIGNS ON 'U' CHANNEL POSTS

GENERAL NOTES

- . SIGNS FURNISHED BY STATE
- . CONFIRM IN WRITING AT LEAST 4 MONTHS IN ADVANCE, THE ACTUAL DATE THE DEPARTMENT FURNISHED SIGNS WILL BE REQUIRED.
- . ALL TYPE 'D' SIGNS SHALL BE MOUNTED ON TWO U-CHANNEL POSTS UNLESS OTHERWISE INDICATED ON THE PLANS.
- . IF REMOVAL OR RELOCATION OF SIGNS ON PRIVATE STREET (NON-STATE MAINTAINED) IS REQUIRED DUE TO CONSTRUCTION, THE CONTRACTOR SHALL INFORM THE ENGINEER. THE WORK WILL BE COMPLETED BY OTHERS.
- . WHEN NOT STATIONED OR DIMENSIONED ON PLANS, ALL 'E' AND 'F' SIGNS SHALL BE FIELD LOCATED BY THE ENGINEER
- . ALL EXISTING SIGNS ON "U" CHANNEL POST WITHIN THE PROJECT LIMITS SHALL BE REMOVED AND DISPOSED OF UNLESS OTHERWISE NOTED ON PLANS.
- . WHEN EXISTING SIGNS ARE REMOVED AND INSTALLED ON NEW SUPPORTS, THE RE-ERECTION SHALL IMMEDIATELY FOLLOW THE REMOVAL.
- . THE BACKGROUND FOR TYPE E & F SIGNS SHALL BE TYPE C REFLECTIVE SHEETING.
- . DO NOT BEGIN FABRICATION FOR TYPES A & B SIGNS MOUNTED ON OVERHEAD STRUCTURES OR STEEL SUPPORTS UNTIL "S" DIMENSIONS HAVE BEEN FIELD VERIFIED.
- . SEE ROADWAY PLANS FOR GUARD/GUIDE RAIL DETAILS.

SUMMARY OF QUANTITIES

ITEM NO.		ITEM DESCRIPTION	QUANTITY	UNIT
DESC. NO.	SECT. NO.			
4072000000	903	SUPPORTS, 3 LB STEEL U-CHANNEL	155	L.F.
4102000000	904	SIGN ERECTION, TYPE E	14	EA.
4155000000	907	DISPOSAL OF SIGN SYSTEM, U-CHANNEL	10	EA.

INDEX

SHEET NO.	DESCRIPTION
SIGN-1	TITLE SHEET
SIGN-2	E AND F SHEETS
SIGN-3	SIGNING PLAN SHEETS

PLAN PREPARED BY: N.C.D.O.T. SIGNING AND DELINEATION UNIT

Kelvin Jordan SIGNING & DELINEATION REGIONAL ENGINEER
Ashley Matthews, PE SIGNING & DELINEATION PROJECT DESIGN ENGINEER

T.I.P.: BP13.R002

5/26/20

401 QUANTITY REQ'D 1



ONE "U" POST PER SIGN

406 QUANTITY REQ'D 1



ONE "U" POST PER SIGN

402 QUANTITY REQ'D 2



MOUNT BELOW SIGN 401 & 406
IN 2 INSTALLATIONS

407 QUANTITY REQ'D 1



ONE "U" POST PER SIGN

403 QUANTITY REQ'D 4



ONE "U" POST PER SIGN

404 QUANTITY REQ'D 4



ONE "U" POST PER SIGN

405 QUANTITY REQ'D 1



ONE "U" POST PER SIGN

BP13.R002

SIGN 002

NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

DESIGNED BY:


APPROVED: *Shelley Matthews*



3/5/2024 | 10:33 AM EST

SEAL:



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED





PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL


SIGNING PLAN SHEET

09/08/99


TIP PROJECT: BP13.R002

CONTRACT:

1:54:18 PM
800090_RDY - TSH-01.dgn
5/22/2023



VICINITY MAP



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS



**UTILITIES BY OTHERS PLANS
RUTHERFORD COUNTY**

**LOCATION: REPLACE BRIDGE NO. 090 OVER SANDY RUN
ON SR 1762 (NEW HOUSE RD)**

TYPE OF WORK: GRADING, PAVING, DRAINAGE, & STRUCTURE

T.I.P. NO.	SHEET NO.
BP13.R002	UO-1

NOTE:
ALL UTILITY WORK SHOWN ON THIS SHEET WILL BE DONE BY OTHERS.
NO PAYMENT WILL BE MADE TO THE CONTRACTOR FOR UTILITY WORK SHOWN ON THIS SHEET.



GRAPHIC SCALES



INDEX OF SHEETS

<u>SHEET NO.:</u>	<u>DESCRIPTION:</u>
UO-1	TITLE SHEET
UO-2	UBO PLAN SHEET

UTILITY OWNERS WITH CONFLICTS

(A) COMMUNICATION - AT&T

PREPARED IN THE OFFICE OF:



WSP USA
434 FAYETTEVILLE STREET
SUITE 1500
RALEIGH, NC 27601
TEL: 1.919.836.4040
FAX: 1.919.836.4099
LICENSE NO. F-0165

ROGER WORTHINGTON, PE UTILITY PROJECT MANAGER
BRANDT BROUGHTON, PE PROJECT UTILITY COORDINATOR




**DIVISION OF HIGHWAYS
UTILITIES UNIT**
1555 MAIL SERVICES CENTER
RALEIGH, NC 27699-1555
PHONE (919) 707-6690
FAX (919) 250-4151

R. KEITH RADCLIFF DIVISION SENIOR UTILITY COORDINATOR
JOHN D. METCALF DIVISION UTILITY COORDINATOR


THIS SHEET CORRESPONDS TO RDY SHEET 4

UTILITIES BY OTHERS


NOTE:
ALL PROPOSED UTILITY WORK SHOWN ON THIS SHEET WILL BE DONE BY OTHERS. NO PAYMENT WILL BE MADE TO THE CONTRACTOR FOR PROPOSED UTILITY WORK SHOWN ON THIS SHEET.





REVISIONS





**NOTE: DESIGN EXCEPTIS IS REQUIRED



























75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

END PROJECT 18+70.00




— / —


75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75




75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



BEGIN CONSTRUCTION 10+10.18
-DRI-


75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

END CONSTRUCTION 11+35.04



75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

3/6/2024 pwz/bgh-eus2-pw-02/Documents/2042955/Technical/Division 13/800090_Rutherford/DGns/2.0 Drafting/DGns/FINAL/401.001.BP13.R002_SMU.GDL.dgn




GRADE DATA -L-
 PI STA = 16+82.50 -L-
 EL = 871.60
 VC = 300'
 (-)0.3027% (+)5.6000%

HYDRAULIC DATA

DESIGN DISCHARGE	1700 CFS
FREQUENCY OF DESIGN FLOOD	25 YRS.
DESIGN HIGH WATER ELEVATION	864.5
DRAINAGE AREA	6.9 SQ.MI.
BASE DISCHARGE (Q100)	2400 CFS
BASE HIGH WATER ELEVATION	865.4

OVERTOPPING FLOOD DATA

OVERTOPPING FLOOD DISCHARGE	9800 CFS
FREQUENCY OF OVERTOPPING FLOOD	500+ YRS.
OVERTOPPING FLOOD ELEVATION	872.2
@ STA. 15+48.00 -L-	



I HEREBY CERTIFY THESE PLANS ARE THE AS-BUILT PLANS

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-
 SHEET 1 OF 4 REPLACES BRIDGE NO. 800090

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

GENERAL DRAWING
 FOR BRIDGE OVER SANDY RUN
 ON SR 1762 (NEW HOUSE RD.)
 BETWEEN SR 1764 & SR 1763

DESIGNED BY: T. KIRSCHBAUM DATE: JUN 2023
 DRAWN BY: T. KIRSCHBAUM DATE: JUN 2023
 CHECKED BY: E. LAWES DATE: JUN 2023
 DESIGN ENGINEER OF RECORD: T. KIRSCHBAUM DATE: JUN 2023

wsp
 WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. P-0165


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

DocuSigned by:
 Thomas Kirschbaum
 7384F51FC8E48E 3/6/2024

REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO. **S-1**
 TOTAL SHEETS 17

3/6/2024 10:41:13 AM C:\Users\T.Kirschbaum\Documents\20242955\Technical\Division 13\800090_Rutherford\Structures\2.0_Drafting\Drawings\FINAL\401_003_BP13.R002_SML_G02.dgn



FOUNDATION LAYOUT
(END BENTS ARE PARALLEL)

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

SHEET 2 OF 4

NOTES
 FOR SUMMARY OF PILE AND DRILLED PIER INFORMATION, SEE SHEET 3 OF 4.

DESIGNED BY:	T. KIRSCHBAUM	DATE:	JUN 2023
DRAWN BY:	T. KIRSCHBAUM	DATE:	JUN 2023
CHECKED BY:	E. LAWES	DATE:	JUN 2023
DESIGN ENGINEER OF RECORD:	T. KIRSCHBAUM	DATE:	JUN 2023

wsp
 WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. F-0165

DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED

Seal of T. Kirschbaum, Professional Engineer, State of North Carolina, License No. 042638.

Digitally signed by: *T. Kirschbaum*
 7304F51F0C8E486... 3/6/2024

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

GENERAL DRAWING
 FOR BRIDGE OVER SANDY RUN
 ON SR 1762 (NEW HOUSE RD.)
 BETWEEN SR 1764 & SR 1763

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-2 TOTAL SHEETS 17
2			4			

SUMMARY OF PILE INFORMATION/INSTALLATION

(Blank entries indicate item is not applicable to structure)

Table with columns: End Bent/Pile(s) #(-#), Factored Resistance per Pile TONS, Pile Cut-Off (Top of Pile) Elevation FT, Estimated Pile Length per Pile FT, Scour Critical Elevation FT, Driven Piles (Min Pile Tip, Required Driving Resistance, Total Pile Redrives), Predrilling for Piles* (Length, Elevation, Max Dia), Drilled-In Piles (Excavation, Exc Not In Soil).

*Predrilling for Piles is required for end bents/bents with a predrilling length and at the Contractor's option for end bents/bents with predrilling information but no predrilling length.

** RDR = (Factored Resistance + Factored Downdrag Load + Factored Dead Load) / Dynamic Resistance Factor + Nominal Downdrag Resistance + (Nominal Scour Resistance / Scour Resistance Factor)

SUMMARY OF PDA/PILE ORDER LENGTHS

(Blank entries indicate item is not applicable to structure)

Table with columns: PDA Testing Required? YES or MAYBE, PDA Test Pile Length FT, Total PDA Testing Quantity EACH, End Bent/Bent No(s), Pile Order Length Basis* EST or PDA

*EST = Pile order lengths from estimated pile lengths; PDA = Pile order lengths based on PDA testing. For groups of end bents/bents with pile order lengths based on PDA testing, the first end bent/bent no. listed for each group is the representative end bent/bent with the PDA.

PILE DESIGN INFORMATION

(Blank entries indicate item is not applicable to structure)

Table with columns: End Bent/Pile(s) #(-#), Factored Axial Load per Pile TONS, Factored Downdrag Load per Pile TONS, Factored Dead Load* per Pile TONS, Dynamic Resistance Factor, Nominal Downdrag Resistance per Pile TONS, Nominal Scour Resistance per Pile TONS, Scour Resistance Factor (Default = 1.00)

*Factored Dead Load is factored weight of pile above the ground line.

SUMMARY OF PILE ACCESSORIES

(Blank entries indicate item is not applicable to structure)

Table with columns: End Bent/Pile(s) #(-#), Pipe Pile Plates Required? YES or MAYBE, Steel Pile Points (Pipe Pile Cutting Shoes Required?, Pipe Pile Conical Points Required?, H-Pile Points Required? YES), Steel Pile Tips Required? YES

FOUNDATION NOTES:

- 1. For Piles, see Piles Provision and Section 450 of the Standard Specifications.
2. Fill holes for pile excavation at End Bent No. 1 with concrete.

PROJECT NO. BP13.R002

Rutherford COUNTY

STATION: 14+80 -L-


SHEET 3 OF 4

NOTES:

- 1. The Pile Foundation Tables are based on the bridge substructure design and foundation recommendations sealed by a North Carolina Professional Engineer Shiping Yang, #031361 on
2. Total Pile Driving Equipment Setup quantity (not shown in Pile Foundation Tables) equals the number of driven piles, i.e., the number of piles with a Required Driving Resistance.
3. The Engineer will determine the need for PDA Testing and Pipe Pile Plates when PDAs or plates may be required.
4. Any reference to "PDA Testing" shall be presumed to be updated to "Dynamic Pile Testing" per the updated 2024 Standard Provision.

Professional Engineer Seal for Thomas J. Kirschbaum, No. 042638. State of North Carolina Department of Transportation logo. PILE FOUNDATION TABLES title. Signature of Shiping Yang, dated 3/6/2024. Revisions table and sheet count table.

BM #1: STA. 14+12.92 -L-, OFFSET 110.65' LT, ELEV. 865.06', RAILROAD SPIKE IN 24" POPLAR



LOCATION SKETCH
FOR UTILITY INFORMATION, SEE UTILITY PLANS AND SPECIAL PROVISIONS.

NOTES

- ASSUMED LIVE LOAD = HL-93 OR ALTERNATE LOADING.
- THIS BRIDGE HAS BEEN DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS.
- THIS BRIDGE IS LOCATED IN SEISMIC ZONE 1.
- FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE SHEET SN.
- FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.
- FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.
- FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.
- FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.
- THE EXISTING PAVEMENT WITHIN THE AREA OF THE END BENT PILES SHALL BE REMOVED AND THE ROADBED SCARIFIED TO A MINIMUM DEPTH OF 2'-0".
- INASMUCH AS THE PAINT SYSTEM ON THE EXISTING STRUCTURAL STEEL CONTAINS LEAD, THE CONTRACTOR'S ATTENTION IS DIRECTED TO ARTICLE 107-1 OF THE STANDARD SPECIFICATIONS. ANY COSTS RESULTING FROM COMPLIANCE WITH APPLICABLE STATE OR FEDERAL REGULATIONS PERTAINING TO HANDLING OF MATERIALS CONTAINING LEAD BASED PAINT SHALL BE INCLUDED IN THE BID PRICE FOR "REMOVAL OF EXISTING STRUCTURE".
- THE MATERIAL SHOWN IN THE CROSS-HATCHED AREA ON SHEET S-1 SHALL BE EXCAVATED FOR A DISTANCE OF 29.5 FT (LEFT) AND 28.5 FT (RIGHT) OF CENTERLINE ROADWAY AT END BENT 1 AND 22.5 FT (LEFT) AND 23.5 FT (RIGHT) OF CENTERLINE ROADWAY AT END BENT 2, AS DIRECTED BY THE ENGINEER. THIS WORK WILL BE PAID FOR AT THE CONTRACT LUMP SUM PRICE FOR UNCLASSIFIED STRUCTURE EXCAVATION. SEE SECTION 412 OF THE STANDARD SPECIFICATIONS.
- THE EXISTING STRUCTURE CONSISTING OF THREE SPANS, ONE AT 25'-9", ONE AT 40'-2" AND ONE AT 20'-7", STEEL I-BEAM GIRDERS; 19'-9" CLEAR ROADWAY WIDTH WITH ASPHALT WEARING SURFACE ON END BENT AND INTERIOR BENT PILE CAPS AND LOCATED AT THE PROPOSED STRUCTURE SHALL BE REMOVED. THE EXISTING BRIDGE IS PRESENTLY POSTED FOR LOAD LIMIT. SHOULD THE STRUCTURAL INTEGRITY OF THE BRIDGE DETERIORATE DURING CONSTRUCTION OF THE PROPOSED BRIDGE, A LOAD LIMIT MAY BE POSTED AND MAY BE REDUCED AS FOUND NECESSARY DURING THE LIFE OF THE PROJECT.
- THE SUBSTRUCTURE OF THE EXISTING BRIDGE INDICATED ON THE PLANS IS FROM THE BEST INFORMATION AVAILABLE. SINCE THIS INFORMATION IS SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR, THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT OF TRANSPORTATION FOR ANY DELAYS OR ADDITIONAL COST INCURRED BASED ON DIFFERENCES BETWEEN THE EXISTING BRIDGE SUBSTRUCTURE SHOWN ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.
- REMOVAL OF THE EXISTING BRIDGE SHALL BE PERFORMED SO AS NOT TO ALLOW DEBRIS TO FALL INTO THE WATER. THE CONTRACTOR SHALL REMOVE THE BRIDGE AND SUBMIT PLANS FOR DEMOLITION IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS.
- THIS STRUCTURE HAS BEEN DESIGNED IN ACCORDANCE WITH "HEC-18 - EVALUATING SCOUR AT BRIDGES."
- ASPHALT WEARING SURFACE IS INCLUDED IN THE ROADWAY QUANTITY ON ROADWAY PLANS.
- FOR ASBESTOS ASSESSMENT FOR BRIDGE DEMOLITION AND RENOVATION ACTIVITIES, SEE SPECIAL PROVISIONS.
- FOR EROSION CONTROL MEASURES, SEE EROSION CONTROL PLANS.

TOTAL BILL OF MATERIAL


	REMOVAL OF EXISTING STRUCTURE @ STA. 14+80.00 -L-	ASBESTOS ASSESSMENT	PILE EXCAVATION IN SOIL	PILE EXCAVATION NOT IN SOIL	UNCLASSIFIED STRUCTURE EXCAVATION	CLASS A CONCRETE	BRIDGE APPROACH SLABS @ STA. 14+80.00 -L-	REINFORCING STEEL	PILE DRIVING EQUIPMENT SETUP FOR HP 14 x 73 STEEL PILES	HP 14 X 73 STEEL PILES	VERTICAL CONCRETE BARRIER RAIL	RIP RAP CLASS II (2'-0" THICK)	GEOTEXTILE FOR DRAINAGE	ELASTOMERIC BEARINGS	3'-0" X 3'-3" PRESTRESSED CONCRETE BOX BEAMS
	LUMP SUM	LUMP SUM	LIN. FT.	LIN. FT.	LUMP SUM	CU. YDS.	LUMP SUM	LBS.	No.	No. LIN. FT.	LIN. FT.	TONS	SQ. YDS.	LUMP SUM	No. LIN. FT.
SUPERSTRUCTURE															
END BENT 1			25.0	25.0	LUMP SUM	28.6		4,404		5 75.0	200.0	68	75	LUMP SUM	10 1,000
END BENT 2					LUMP SUM	28.6		4,404	5	5 100.0		102	113		
TOTAL	LUMP SUM	LUMP SUM	25.0	25.0	LUMP SUM	57.2	LUMP SUM	8,808	5	10 175.0	200.0	170	188	LUMP SUM	10 1,000

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

SHEET 4 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

GENERAL DRAWING
 FOR BRIDGE OVER SANDY RUN
 ON SR 1762 (NEW HOUSE RD.)
 BETWEEN SR 1764 & SR 1763



REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-4 TOTAL SHEETS 17
2			4			

3/6/2024 pwz/lbg-h-eus2-pw-bentley-combgh-eus2-pw-02/Documents/2042955/Technical/Division 13/800090_Rutherford/Structures/2.0 Drafting/DGns/FINAL/401.005.BP13.R002.SML.GD3.dgn

DESIGNED BY: T. KIRSCHBAUM DATE: JUN 2023
 DRAWN BY: T. KIRSCHBAUM DATE: JUN 2023
 CHECKED BY: E. LAWES DATE: JUN 2023
 DESIGN ENGINEER OF RECORD: T. KIRSCHBAUM DATE: JUN 2023

LOAD AND RESISTANCE FACTOR RATING (LRFR) SUMMARY FOR PRESTRESSED CONCRETE GIRDERS

LOAD TYPE	VEHICLE	WEIGHT (W) (TONS)	CONTROLLING LOAD RATING #	MINIMUM RATING FACTORS (RF)	TONS = W x RF	STRENGTH I LIMIT STATE								SERVICE III LIMIT STATE								COMMENT NUMBER		
						MOMENT				SHEAR				MOMENT										
						LIVE-LOAD FACTORS (γLL)	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	LIVE-LOAD FACTORS (γLL)	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION		DISTANCE FROM LEFT END OF SPAN (ft)	
DESIGN LOAD	HL-93 (INVENTORY)	N/A	①	1.035	--	1.75	0.272	1.26	100'	EL	49.25	0.489	1.34	100'	EL	4.925	0.80	0.272	1.04	100'	EL	49.25		
	HL-93 (OPERATING)	N/A		1.633	--	1.35	0.272	1.63	100'	EL	49.25	0.489	1.73	100'	EL	4.925	N/A	--	--	--	--	--	--	
	HS-20 (INVENTORY)	36.000	②	1.440	51.840	1.75	0.272	1.75	100'	EL	49.25	0.489	1.81	100'	EL	4.925	0.80	0.272	1.44	100'	EL	49.25		
	HS-20 (OPERATING)	36.000		2.271	81.756	1.35	0.272	2.27	100'	EL	49.25	0.489	2.35	100'	EL	4.925	N/A	--	--	--	--	--	--	
LEGAL LOAD	SINGLE VEHICLE (SV)	SNSH		3.413	46.079	1.4	0.272	5.19	100'	EL	49.25	0.489	5.59	100'	EL	4.925	0.80	0.272	3.41	100'	EL	49.25		
		SNGARBS2	20.000		2.473	49.452	1.4	0.272	3.76	100'	EL	49.25	0.489	3.91	100'	EL	4.925	0.80	0.272	2.47	100'	EL	49.25	
		SNAGRIS2	22.000		2.313	50.885	1.4	0.272	3.52	100'	EL	49.25	0.489	3.60	100'	EL	4.925	0.80	0.272	2.31	100'	EL	49.25	
		SNCOTTS3	27.250		1.696	46.228	1.4	0.272	2.58	100'	EL	49.25	0.489	2.78	100'	EL	4.925	0.80	0.272	1.70	100'	EL	49.25	
		SNAGGRS4	34.925		1.390	48.556	1.4	0.272	2.11	100'	EL	49.25	0.489	2.26	100'	EL	4.925	0.80	0.272	1.39	100'	EL	49.25	
		SNS5A	35.550		1.361	48.398	1.4	0.272	2.07	100'	EL	49.25	0.489	2.27	100'	EL	4.925	0.80	0.272	1.36	100'	EL	49.25	
		SNS6A	39.950		1.238	49.456	1.4	0.272	1.88	100'	EL	49.25	0.489	2.05	100'	EL	4.925	0.80	0.272	1.24	100'	EL	49.25	
	SNS7B	42.000		1.178	49.496	1.4	0.272	1.79	100'	EL	49.25	0.489	2.00	100'	EL	4.925	0.80	0.272	1.18	100'	EL	49.25		
	TRUCK TRACTOR SEMI-TRAILER (TTST)	TNAGRIT3	33.000		1.506	49.709	1.4	0.272	2.29	100'	EL	49.25	0.489	2.46	100'	EL	4.925	0.80	0.272	1.51	100'	EL	49.25	
		TNT4A	33.075		1.510	49.942	1.4	0.272	2.30	100'	EL	49.25	0.489	2.41	100'	EL	4.925	0.80	0.272	1.51	100'	EL	49.25	
		TNT6A	41.600		1.224	50.926	1.4	0.272	1.86	100'	EL	49.25	0.489	2.09	100'	EL	4.925	0.80	0.272	1.22	100'	EL	49.25	
		TNT7A	42.000		1.225	51.442	1.4	0.272	1.86	100'	EL	49.25	0.489	2.05	100'	EL	4.925	0.80	0.272	1.22	100'	EL	49.25	
		TNT7B	42.000		1.254	52.657	1.4	0.272	1.91	100'	EL	49.25	0.489	1.96	100'	EL	4.925	0.80	0.272	1.25	100'	EL	49.25	
		TNAGRIT4	43.000		1.203	51.711	1.4	0.272	1.83	100'	EL	49.25	0.489	1.91	100'	EL	4.925	0.80	0.272	1.20	100'	EL	49.25	
TNAGT5A		45.000		1.139	51.236	1.4	0.272	1.73	100'	EL	49.25	0.489	1.87	100'	EL	4.925	0.80	0.272	1.14	100'	EL	49.25		
TNAGT5B	45.000		③	1.129	50.805	1.4	0.272	1.72	100'	EL	49.25	0.489	1.82	100'	EL	4.925	0.80	0.272	1.13	100'	EL	49.25		
EMERGENCY VEHICLE (EV)	EV2	28.750		2.129	61.213	1.3	0.272	2.87	100'	EL	49.25	0.489	3.06	100'	EL	4.925	0.80	0.272	2.13	100'	EL	49.25		
	EV3	43.000		④	1.403	60.325	1.3	0.272	1.89	100'	EL	49.25	0.489	2.06	100'	EL	4.925	0.80	0.272	1.40	100'	EL	49.25	

LOAD FACTORS:

DESIGN LOAD RATING FACTORS	LIMIT STATE	γDC	γDW
	STRENGTH I	1.25	1.50
	SERVICE III	1.00	1.00

NOTES:

MINIMUM RATING FACTORS ARE BASED ON THE STRENGTH I AND SERVICE III LIMIT STATES.

ALLOWABLE STRESSES FOR SERVICE III LIMIT STATE ARE AS REQUIRED FOR DESIGN.

COMMENTS:

- 1.
- 2.
- 3.
- 4.

CONTROLLING LOAD RATING

① DESIGN LOAD RATING (HL-93)

② DESIGN LOAD RATING (HS-20)


③ LEGAL LOAD RATING **

④ EMERGENCY VEHICLE LOAD RATING **

** SEE CHART FOR VEHICLE TYPE

GIRDER LOCATION

I - INTERIOR GIRDER
EL - EXTERIOR LEFT GIRDER
ER - EXTERIOR RIGHT GIRDER



PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

3/6/2024 pwz/dgh-eus2-pw-bentley.combg-h-eus2-pw-02/Documents/2042955/Technical/Division 13/800090_Rutherford/Structures/2.0_Drafting/DGns/FINAL/401_007_BP13.R002_SML_LRFR.dgn

ASSEMBLED BY: T.KIRSCHBAUM DATE: JUN 2023
 CHECKED BY: E.LAWES DATE: JUN 2023
 DESIGN ENGINEER OF RECORD: T.KIRSCHBAUM DATE: JUN 2023

DRAWN BY: TMG II/II
 CHECKED BY: AAC II/II

REV. 06/23

AKP/AAI

WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. F-0165

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

Digitally signed by Thomas Kirschbaum
 7304F51F0C8E4B6 3/6/2024

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

STANDARD
 LRFR SUMMARY FOR
 100' BOX BEAM UNIT
 90° SKEW
 (NON-INTERSTATE TRAFFIC)

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-5 TOTAL SHEETS 17
1			3			
2			4			

STD. NO. 39LRFR1_90S.100L

NOTES

ALL PRESTRESSING STRANDS SHALL BE 7-WIRE LOW RELAXATION GRADE 270 STRANDS AND SHALL CONFORM TO AASHTO M203 EXCEPT FOR SAMPLING REQUIREMENTS WHICH SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

ALL REINFORCING STEEL CAST WITH THE BOX BEAM SECTIONS SHALL BE GRADE 60 AND SHALL BE INCLUDED IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE BOX BEAMS.

FLAME CUTTING OF THE TRANSVERSE POST-TENSIONING STRAND IS NOT ALLOWED.

RECESSES FOR TRANSVERSE STRANDS SHALL BE GROUTED AFTER THE TENSIONING OF THE STRANDS.

THE 2 1/2" Ø DOWEL HOLES AT FIXED ENDS OF BOX BEAM SECTIONS SHALL BE FILLED WITH NON-SHRINK GROUT.

THE BACKER RODS SHALL CONFORM TO THE REQUIREMENTS OF TYPE M BOND BREAKER. SEE SECTION 1028 OF THE STANDARD SPECIFICATIONS.

THE TRANSFER OF LOAD FROM THE ANCHORAGES TO THE BOX BEAM UNIT SHALL BE DONE WHEN THE CONCRETE HAS REACHED A COMPRESSIVE STRENGTH OF NOT LESS THAN 5,500 PSI.

ALL REINFORCING STEEL IN VERTICAL CONCRETE BARRIER RAILS SHALL BE EPOXY COATED.

PRESTRESSING STRANDS SHALL BE CUT FLUSH WITH THE BOX BEAM UNIT ENDS.

APPLY EPOXY PROTECTIVE COATING TO BOX BEAM UNIT ENDS.

VERTICAL GROOVED CONTRACTION JOINTS, 1/2" IN DEPTH, SHALL BE TOOLED IN ALL EXPOSED FACES OF THE BARRIER RAIL AND IN ACCORDANCE WITH ARTICLE 825-10(B) OF THE STANDARD SPECIFICATIONS. A VERTICAL CONTRACTION JOINT SHALL BE LOCATED AT EACH THIRD POINT BETWEEN BARRIER RAIL EXPANSION JOINTS. ONLY ONE CONTRACTION JOINT IS REQUIRED AT MIDPOINT OF BARRIER RAIL SEGMENTS LESS THAN 20 FEET IN LENGTH AND NO CONTRACTION JOINTS ARE REQUIRED FOR THOSE SEGMENTS LESS THAN 10 FEET IN LENGTH.

THE LOCATION OF THE VOID DRAINS MAY BE SHIFTED SLIGHTLY WHERE NECESSARY TO CLEAR PRESTRESSING STRANDS OR TRANSVERSE REINFORCING STEEL.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

THE PERMITTED THREADED INSERTS ARE DETAILED AS AN OPTION FOR THE CONTRACTOR TO ATTACH FALSEWORK AND FORMWORK DURING CONSTRUCTION.


THE PERMITTED THREADED INSERTS IN THE EXTERIOR UNITS SHALL BE SIZED BY THE CONTRACTOR, SPACED AT 4'-0" CENTERS AND GALVANIZED IN ACCORDANCE WITH SECTION 1076 OF THE STANDARD SPECIFICATIONS. STAINLESS STEEL THREADED INSERTS MAY BE USED AS AN ALTERNATE.

THE PERMITTED THREADED INSERTS SHALL BE GROUTED BY THE CONTRACTOR IMMEDIATELY FOLLOWING REMOVAL OF THE FALSEWORK.

THE COST OF THE PERMITTED THREADED INSERTS SHALL BE INCLUDED IN THE PRICE BID FOR THE PRECAST UNITS.

THE DRAIN OPENING AT THE GUTTERLINE SHALL BE 4" X 5". THE HEIGHT OF THE BLOCKOUT IN THE CONCRETE PARAPET SHALL EXTEND FROM THE TOP OF THE BOX BEAM UNIT TO THE TOP OF THE DRAIN OPENING.

APPLY EPOXY PROTECTIVE COATING TO EXTERIOR FACE OF THE EXTERIOR BOX BEAM UNITS THAT REQUIRE DRAINS IN THE VERTICAL CONCRETE BARRIER RAIL.




HALF SECTION AT INTERMEDIATE DIAPHRAGMS HALF SECTION THROUGH VOIDS

TYPICAL SECTION


* THE MAXIMUM BARRIER RAIL HEIGHT AND ASPHALT THICKNESS IS SHOWN. THE HEIGHT OF THE BARRIER RAIL AND ASPHALT THICKNESS VARIES WHILE THE TOP OF THE BARRIER RAIL FOLLOWS THE PROFILE OF THE GUTTERLINE. FOR RAIL HEIGHT DETAILS AND ASPHALT THICKNESS, SEE THE "VERTICAL CONCRETE BARRIER RAIL SECTION" DETAIL.

FIXED END



SECTION AT END BENT

PERMITTED THREADED INSERT CAST IN OUTSIDE FACE OF EXTERIOR UNIT AND RECESSED 3/8" SIZE TO BE DETERMINED BY CONTRACTOR.



THREADED INSERT DETAIL

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

SHEET 1 OF 5

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
 3'-0" X 3'-3"
 PRESTRESSED CONCRETE
 BOX BEAM UNIT

DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED

wsp
 WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. F-0165


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			17
2			4			

STD. NO. 39PCBB1_30


3/6/2024 p:\z\dgn-bentley.com\gh-eus2-pw-02\Documents\2042955\Technical\Division 13\800090_Rutherford\Structures\2.0 Drafting\DGNS\FINAL\401.009_BP13.R002_SML.BBI.dgn

ASSEMBLED BY: T.KIRSCHBAUM	DATE: JUN 2023	DRAWN BY: DCE	B/II	REV. 10/15	MAA/TMG
CHECKED BY: E.LAWES	DATE: JUN 2023	CHECKED BY: TMG	II/II		
DESIGN ENGINEER OF RECORD: T.KIRSCHBAUM	DATE: JUN 2023				

3/6/2024 p:\z\dgn-us2-pw-02\Documents\2042955\Technical\Division 13\800090_Rutherford\Structures\2.0 Drafting\DGNS\FINAL\401.011.BP13.R002_SML.BB2.dgn




PLAN OF UNIT



DIAPHRAGM AND VOID LAYOUT

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-
 SHEET 2 OF 5

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 PLAN OF 100' UNIT
 27'-10" CLEAR ROADWAY
 90° SKEW




REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-7
1			3			TOTAL SHEETS
2			4			17


wsp
 WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. P-0165

ASSEMBLED BY: T.KIRSCHBAUM	DATE: JUN 2023	DRAWN BY: DGE	8/10	REV. 8/14	MAA/TMG
CHECKED BY: E.LAWES	DATE: JUN 2023	CHECKED BY: TMG	11/11		
DESIGN ENGINEER OF RECORD: T.KIRSCHBAUM	DATE: JUN 2023				


3/6/2024 p:\wz\pgh-us2-pw.bentley.com\gh-eus2-pw-02\Documents\2042955\Technical\Division 13\800090\Other\for\Structures\2.0 Drafting\DGNS\FINAL\401.013.BP13.R002_SML_BB3.dgn




END ELEVATION
SHOWING PLACEMENT OF #5 & #4 "A" BARS AND LOCATION OF DOWEL HOLES. (INTERIOR BOX BEAM SECTION SHOWN-EXTERIOR SECTION SIMILAR EXCEPT SHEAR KEY LOCATION, STRAND LAYOUT NOT SHOWN.)



INTERIOR BOX BEAM SECTION
(STRAND LAYOUT NOT SHOWN)




EXTERIOR BOX BEAM SECTION
(STRAND LAYOUT NOT SHOWN)




0.6" Ø LOW RELAXATION STRAND LAYOUT
TYPICAL STRAND LOCATION
(32 STRANDS REQUIRED)
DEBONDING LEGEND

- FULLY BONDED STRANDS
 - ◻ STRANDS DEBONDED FOR 4'-0" FROM END OF GIRDER
 - ◻ STRANDS DEBONDED FOR 12'-0" FROM END OF GIRDER
- BOND SHALL BE BROKEN ON STRANDS AS SHOWN FOR THE SPECIFIED LENGTH FROM EACH END OF THE BOX BEAM. SEE STANDARD SPECIFICATIONS ARTICLE 1078-7.




SHEAR KEY DETAIL
NOTE: OMIT SHEAR KEY ON OUTSIDE FACE OF EXTERIOR BOX BEAMS.

GRADE 270 STRANDS	
AREA (SQUARE INCHES)	0.217
ULTIMATE STRENGTH (LBS. PER STRAND)	58,600
APPLIED PRESTRESS (LBS. PER STRAND)	43,950



ALL BAR DIMENSIONS ARE OUT TO OUT

BILL OF MATERIAL FOR ONE BOX BEAM SECTION									
BAR NUMBER	SIZE	TYPE	EXTERIOR UNIT LENGTH	EXTERIOR UNIT WEIGHT	INTERIOR UNIT LENGTH	INTERIOR UNIT WEIGHT			
A1	10	#5	7'-2"	75	7'-2"	75			
A2	44	#4	5'-7"	164	5'-7"	164			
B6	12	#5	STR	50'-11"	637	50'-11"	637		
K1	15	#4	6	7'-2"	72	7'-2"	72		
K2	10	#4	STR	2'-7"	17	2'-7"	17		
S1	81	#4	3	8'-6"	460	8'-6"	460		
S2	81	#4	3	5'-8"	307	5'-8"	307		
S3	141	#4	3	4'-10"	455	4'-10"	455		
S4	60	#4	4	5'-10"	234	5'-10"	234		
* S5	138	#5	5	5'-10"	840	--	--		
REINFORCING STEEL			2421	LBS.		2421	LBS.		
* EPOXY COATED REINF. STEEL			840	LBS.					
7500 P.S.I. CONCRETE			19.6	CU. YDS.		19.4	CU. YDS.		
0.6" Ø L.R. STRANDS			No. 32			No. 32			



PLAN OF BOX BEAM

EXTERIOR UNIT SHOWN, INTERIOR UNIT SIMILAR EXCEPT OMIT #5 S5 BARS. FOR LOCATION OF DIAPHRAGMS, SEE "PLAN OF UNIT". FOR THREADED INSERTS, SEE "THREADED INSERT DETAIL". FOR REINFORCING STEEL IN DIAPHRAGMS, SEE "DOUBLE DIAPHRAGM DETAILS".

WSP
WSP USA Inc.
434 FAYETTEVILLE STREET
SUITE 1500
RALEIGH, NC 27601
TEL: 1.919.836.4040
LICENSE NO. P-0165

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED
Seal of Thomas Kirschbaum, Professional Engineer, State of North Carolina, License No. 042638.




PROJECT NO. BP13.R002
RUTHERFORD COUNTY
STATION: 14+80.00 -L-
SHEET 3 OF 5

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
STANDARD
3'-0" X 3'-3" PRESTRESSED CONCRETE BOX BEAM UNIT

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		


TOTAL SHEETS: 17

STD. NO. 39PCBB6-90S-100L




DOUBLE DIAPHRAGM DETAILS


*4 "S" BARS NOT SHOWN. *4 "S" BARS MAY BE SHIFTED SLIGHTLY TO CLEAR 2 1/2" Ø HOLE.




VIEW Y-Y
SHOWING ELEVATION VIEW OF GROUDED RECESS



DETAIL "C"



PART SECTION AT RECESS




SECTION X-X
SHOWING PLAN VIEW OF GROUDED RECESS


GROUDED RECESS DETAIL AT END OF POST-TENSIONED STRANDS OF EXTERIOR BOX BEAM

DEAD LOAD DEFLECTION AND CAMBER	
100' BOX BEAM UNIT	3'-0" x 3'-3"
CAMBER (SLAB ALONE IN PLACE)	2" ↑
DEFLECTION DUE TO SUPERIMPOSED DEAD LOAD**	7/8" ↓
FINAL CAMBER	1 1/8" ↑

** INCLUDES FUTURE WEARING SURFACE



SECTION B-B



PART PLAN

VOID DRAIN DETAILS

(DIMENSIONS SHOWN ARE TYPICAL FOR EACH VOID)

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

SHEET 4 OF 5

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD


3'-0" X 3'-3"
 PRESTRESSED CONCRETE
 BOX BEAM UNIT

REVISIONS

NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		


SHEET NO.

S-9
 TOTAL SHEETS
 17




3/6/2024 pwr/dgn-eus2-pw-bentley.combg-h-eus2-pw-02/Documents/2042955/Technical/Division 13/800090_Rutherford/Structures/2.0 Drafting/DGNs/FINAL/401.015.BP13.R002_SML_BB4.dgn

STD.NO.39PCBB7_90S



ELASTOMERIC BEARING DETAILS


ELASTOMER IN ALL BEARINGS SHALL BE 60 DUROMETER HARDNESS.



END OF RAIL DETAILS


BOX BEAM UNITS REQUIRED

	NUMBER	LENGTH	TOTAL LENGTH
EXTERIOR B.B.	2	100'-0"	200'-0"
INTERIOR B.B.	8	100'-0"	800'-0"
TOTAL	10		1000'-0"




BILL OF MATERIAL FOR VERTICAL CONCRETE BARRIER RAIL

BAR	BARS PER PAIR OF EXTERIOR UNITS 100' UNIT	SIZE	TYPE	LENGTH	WEIGHT
*B12	96	#5	STR	24'-7"	2461
*S6	276	#5	1	7'-2"	2063
* EPOXY COATED REINFORCING STEEL				LBS.	4524
CLASS AA CONCRETE				CU.YDS.	25.9
TOTAL VERTICAL CONCRETE BARRIER RAIL				LN. FT.	200.0




VERTICAL CONCRETE BARRIER RAIL DETAILS



AT DAM IN OPEN JOINT
(THIS IS TO BE USED ONLY WHEN SLIP FORM IS USED)

1/2" EXP. JT. MAT'L HELD IN PLACE WITH GALVANIZED NAILS.
(NOTE: OMIT EXP. JT. MAT'L WHEN SLIP FORM IS USED)




GUTTERLINE ASPHALT THICKNESS & RAIL HEIGHT

	ASPHALT OVERLAY THICKNESS @ MID-SPAN	RAIL HEIGHT @ MID-SPAN
100' UNITS	2 3/8"	3'-8 3/8"

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

SHEET 5 OF 5

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
 3'-0" X 3'-3"
 PRESTRESSED CONCRETE
 BOX BEAM UNIT



wsp
 WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. F-0165

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-10
2			4			TOTAL SHEETS 17

STD. NO. 39PCBB8_90S

3/6/2024 pwz/dgn-eus2-pw-02/Documents/2042955/Technical/Division 13/800090_Rutherford/Structures/2.0 Drafting/DGns/FINAL/401.011_BP13.R002_SML.BB5.dgn

ASSEMBLED BY: T.KIRSCHBAUM	DATE: JUN 2023	DRAWN BY: DCE	10/11	REV. 5/18	MAA/THC
CHECKED BY: E.LAWES	DATE: JUN 2023	CHECKED BY: TMC	11/11		
DESIGN ENGINEER OF RECORD: T.KIRSCHBAUM	DATE: JUN 2023				

NOTES

THE GUARDRAIL ANCHOR ASSEMBLY SHALL CONSIST OF A 1/4" HOLD DOWN PLATE AND 7 - 1/8" Ø BOLTS WITH NUTS AND WASHERS.

THE HOLD-DOWN PLATE SHALL CONFORM TO AASHTO M270 GRADE 36. AFTER FABRICATION, THE HOLD-DOWN PLATE SHALL BE HOT-DIP GALVANIZED IN ACCORDANCE WITH AASHTO M111.

BOLTS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A307 AND NUTS SHALL CONFORM TO THE REQUIREMENTS OF AASHTO M291. BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED. (AT THE CONTRACTOR'S OPTION, STAINLESS STEEL BOLTS, NUTS AND WASHERS MAY BE USED AS AN ALTERNATE FOR THE 1/8" Ø GALVANIZED BOLTS, NUTS AND WASHERS. THEY SHALL CONFORM TO OR EXCEED THE MECHANICAL REQUIREMENTS OF ASTM A307. THE USE OF THIS ALTERNATE SHALL BE APPROVED BY THE ENGINEER.)


THE GUARDRAIL ANCHOR ASSEMBLY IS REQUIRED AT ALL POINTS WHERE APPROACH GUARDRAIL IS TO BE ATTACHED TO THE END OF BARRIER RAIL. FOR POINTS OF ATTACHMENT, SEE SKETCH.

AFTER INSTALLATION, THE EXPOSED THREAD OF THE BOLT SHALL BE BURRED WITH A SHARP POINTED TOOL.

THE COST OF THE GUARDRAIL ANCHOR ASSEMBLY SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR VERTICAL CONCRETE BARRIER RAIL.


THE VERTICAL REINFORCING BARS MAY BE SHIFTED SLIGHTLY IN THE VERTICAL CONCRETE BARRIER RAIL TO CLEAR ASSEMBLY BOLTS.

THE 1 1/4" Ø HOLES SHALL BE FORMED OR DRILLED WITH A CORE BIT. IMPACT TOOLS WILL NOT BE PERMITTED. ANY CONCRETE DAMAGED BY THIS WORK SHALL BE REPAIRED TO THE SATISFACTION OF THE ENGINEER.




PLAN


FOR LOCATION OF GUARDRAIL ANCHOR ASSEMBLY, SEE "PLAN" BELOW



ELEVATION



SECTION E-E
GUARDRAIL ANCHOR ASSEMBLY DETAILS



PLAN

LOCATION OF ANCHORS FOR GUARDRAIL

END BENT #1 SHOWN, END BENT #2 SIMILAR.



SKETCH SHOWING POINTS OF ATTACHMENT

* DENOTES GUARDRAIL ANCHOR ASSEMBLY

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
 GUARDRAIL ANCHORAGE
 DETAILS FOR
 VERTICAL CONCRETE
 BARRIER RAIL

REVISIONS

NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO. S-11
 TOTAL SHEETS 17

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. F-0165

ASSEMBLED BY: T.KIRSCHBAUM	DATE: JUN 2023	DRAWN BY: MAA	5/10	REV. 1/15	MAA/TMG
CHECKED BY: E.LAWES	DATE: JUN 2023	CHECKED BY: GM	5/10	REV. 12/17	MAA/THC
DESIGN ENGINEER OF RECORD: T.KIRSCHBAUM	DATE: JUN 2023			REV. 5/18	MAA/THC


NOTES

STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR DOWELS.


THE CONCRETE IN THE SHADED AREA OF THE WING SHALL BE POURED AFTER THE VERTICAL CONCRETE BARRIER RAIL IS CAST IF SLIP FORMING IS USED.

FOR PILE SPLICE DETAILS, SEE SHEET 4 OF 4.

FOR WING DETAILS, SEE SHEET 3 OF 4.



PLAN



ELEVATION

WINGS NOT SHOWN FOR CLARITY.
 FOR SECTION A-A, SEE SHEET 4 OF 4.
 CONCRETE COLLARS FOR STEEL PILES NOT SHOWN IN PLAN AND ELEVATION VIEWS FOR CLARITY.
 SEE "CORROSION PROTECTION FOR STEEL PILES DETAIL", SHEET 4 OF 4.

TOP OF PILE ELEVATIONS	
①	866.41
②	866.57
③	866.74
④	866.90
⑤	867.07

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

SHEET 1 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE
 END BENT No. 1

REVISIONS

NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO.

S-12

TOTAL SHEETS

17

DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED



DESIGNED BY: *Thomas Kirschbaum*
 3/6/2024



WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. P-0165

DRAWN BY: WJH 12/II REV. 4/15 MAA/TMG
 CHECKED BY: AAC 12/II
 ASSEMBLED BY: T.KIRSCHBAUM DATE: JUN 2023
 CHECKED BY: E.LAWES DATE: JUN 2023
 DESIGN ENGINEER OF RECORD: T.KIRSCHBAUM DATE: JUN 2023

3/6/2024 pwz/dgh-eus2-pw-02/Documents/2042955/Technical/Division 13/800090_Rutherford/Structures/2.0 Drafting/DGNs/FINAL/401_021_BP13.R002_SMU.EBI.dgn


NOTES

STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR DOWELS.


THE CONCRETE IN THE SHADED AREA OF THE WING SHALL BE POURED AFTER THE VERTICAL CONCRETE BARRIER RAIL IS CAST IF SLIP FORMING IS USED.

FOR PILE SPLICE DETAILS, SEE SHEET 4 OF 4.

FOR WING DETAILS, SEE SHEET 3 OF 4.



PLAN



ELEVATION

TOP OF PILE ELEVATIONS	
①	866.11
②	866.27
③	866.44
④	866.60
⑤	866.77

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

SHEET 2 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE
 END BENT No. 2

REVISIONS

NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		


SHEET NO.

S-13

TOTAL SHEETS

17

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. P-0165

Designed by
 Thomas Kirschbaum
 7304F51F0CBE486 3/6/2024


WINGS NOT SHOWN FOR CLARITY.
 FOR SECTION A-A, SEE SHEET 4 OF 4.
 CONCRETE COLLARS FOR STEEL PILES NOT SHOWN IN PLAN AND ELEVATION VIEWS FOR CLARITY.
 SEE "CORROSION PROTECTION FOR STEEL PILES DETAIL", SHEET 4 OF 4.

DRAWN BY : WJH 12/II REV. 4/15 MAA/TMG
 CHECKED BY : AAC 12/II
 ASSEMBLED BY : T.KIRSCHBAUM DATE : JUN 2023
 CHECKED BY : E.LAWES DATE : JUN 2023
 DESIGN ENGINEER
 OF RECORD : T.KIRSCHBAUM DATE : JUN 2023


3/6/2024 pwz/dgh-eus2-pw-02/Documents/2042955/Technical/Division 13/800090_Rutherford/Structures/2.0 Drafting/DGns/FINAL/401.023.BP13.R002_SMJ.EB2.dgn




PLAN OF WING (W1)




PLAN OF WING (W2)




SECTION X-X



ELEVATION OF WING (W1)



ELEVATION OF WING (W2)



SECTION Y-Y

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

SHEET 3 OF 4


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE
 END BENT
 WING DETAILS

REVISIONS

NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO.
S-14
 TOTAL SHEETS
17




WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. P-0165

WING DETAILS

DRAWN BY : WJH 12/11	REV. 4/15	MAA/TMG
CHECKED BY : AAC 12/11		
ASSEMBLED BY : T.KIRSCHBAUM	DATE : JUN 2023	
CHECKED BY : E.LAWES	DATE : JUN 2023	
DESIGN ENGINEER		
OF RECORD : T.KIRSCHBAUM	DATE : JUN 2023	

3/6/2024 pwz/dgh-eus2-pw-02/Documents/2042955/Technical/Division 13/800090_Rutherford/Structures/2.0 Drafting/DGns/Structures/FINAL/401.025.BP13.R002_SMJ.EB3.dgn




BAGGED STONE AND PIPE SHALL BE PLACED IMMEDIATELY AFTER COMPLETION OF END BENT EXCAVATION. PIPE MAY BE EITHER CONCRETE, CORRUGATED STEEL, CORRUGATED ALUMINUM ALLOY, OR CORRUGATED PLASTIC. PERFORATED PIPE WILL NOT BE ALLOWED.


BAGGED STONE SHALL REMAIN IN PLACE UNTIL THE ENGINEER DIRECTS THAT IT BE REMOVED. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF SILT ACCUMULATIONS AT BAGGED STONE WHEN SO DIRECTED BY THE ENGINEER. BAGS SHALL BE REMOVED AND REPLACED WHENEVER THE ENGINEER DETERMINES THAT THEY HAVE DETERIORATED AND LOST THEIR EFFECTIVENESS.

NO SEPARATE PAYMENT WILL BE MADE FOR THIS WORK AND THE ENTIRE COST OF THIS WORK SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR THE SEVERAL PAY ITEMS.

TEMPORARY DRAINAGE AT END BENT




PILE SPLICE DETAILS



BILL OF MATERIAL FOR ONE END BENT					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
B1	8	#9		38'-0"	1034
B2	28	#4	STR	19'-1"	357
B3	9	#4	STR	2'-8"	16
D1	20	#8	STR	2'-3"	120
H1	64	#6		15'-4"	1474
K1	12	#4	STR	2'-11"	23
K2	12	#4	STR	19'-1"	153
S1	46	#4	3	10'-8"	328
S2	46	#4	4	3'-5"	105
S3	20	#4	5	7'-7"	101
U1	30	#4	6	3'-8"	73
V1	76	#4	STR	7'-8"	389
V2	60	#4	STR	5'-9"	230
REINFORCING STEEL (FOR ONE END BENT)					4,404 LBS.


CLASS A CONCRETE BREAKDOWN (FOR ONE END BENT)		
POUR #1	CAP, LOWER PART OF WINGS & COLLARS	21.2 C.Y.
POUR #2	BACKWALL & UPPER PART OF WINGS	7.4 C.Y.
TOTAL CLASS A CONCRETE		28.6 C.Y.

END BENT No. 1	
HP 14 X 73 STEEL PILES	
NO: 5	LIN. FT. = 75.0
END BENT No. 2	
HP 14 X 73 STEEL PILES	
NO: 5	LIN. FT. = 100.0
PILE DRIVING EQUIPMENT SETUP FOR HP 14 X 73 STEEL PILES	NO: 5




CORROSION PROTECTION FOR STEEL PILES DETAIL

(END BENT No. 1 SHOWN, END BENT No. 2 SIMILAR BY ROTATION)



DETAIL "A"


(END BENT No. 1 SHOWN, END BENT No. 2 SIMILAR BY ROTATION)



PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-
 SHEET 4 OF 4

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE					
END BENT No. 1 & 2 DETAILS					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO. **S-15**
 TOTAL SHEETS **17**





wsp

WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. P-0165


3/6/2024 3:16:24 pm w:\bgn\eus2-pw-02\Documents\2042955\Technical\Division 13\800090_Rutherford\Structures\2.0 Drafting\Drawings\FINAL\401.027_BP13.R002_SML_EB4.dgn

DRAWN BY: WJH	12/11	REV. 4/17	MAA/THC
CHECKED BY: AAC	12/11		
ASSEMBLED BY: T.KIRSCHBAUM	DATE: JUN 2023		
CHECKED BY: E.LAWES	DATE: JUN 2023		
DESIGN ENGINEER			
OF RECORD: T.KIRSCHBAUM	DATE: JUN 2023		


ESTIMATED QUANTITIES		
BRIDGE @ STA. 14+80.00 -L-	RIP RAP CLASS II (2'-0" THICK)	GEOTEXTILE FOR DRAINAGE
	TONS	SQUARE YARDS
END BENT 1	68	75
END BENT 2	102	113



SECTION C-C
BERM RIP RAPPED



SECTION H-H




SECTION C-C

PROJECT NO. BP13.R002
RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

RIP RAP DETAILS

DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED




REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-16
1			3			TOTAL SHEETS
2			4			17




wsp
 WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. P-0165

3/6/2024 pww-eus2-pw.bentley.com bgh-eus2-pw-02/Documents/2042955/Technical/Division 13/800090_Rutherford/Structures/2.0 Drafting/DGns/FINAL/401.029.BP13.R002.SMJ.RR.dgn

3/6/2024 10:41:03 AM C:\Users\pwbentley\Documents\20242955\Technical\Division 13\800090_Rutherford\Structures\2.0 Drafting\Drawings\FINAL\401.031.BP13.R002_SML_AS.dgn



SPlice LENGTHS		
BAR SIZE	EPOXY COATED	UNCOATED
#4	1'-11"	1'-7"
#5	2'-5"	2'-0"
#6	3'-7"	2'-5"





TEMPORARY BERM AND SLOPE DRAIN DETAILS
 (TO BE USED WHEN SHOULDER BERM GUTTER IS REQUIRED)

NOTES

FOR BRIDGE APPROACH FILL, SEE ROADWAY PLANS.

AREA BETWEEN THE WINGWALL AND APPROACH SLAB SHALL BE GRADED TO DRAIN THE WATER AWAY FROM THE FILL FACE OF THE BRIDGE AND SHALL BE PAVED. SEE ROADWAY PLANS.

APPROACH SLAB GROOVING IS NOT REQUIRED.



BILL OF MATERIAL						
APPROACH SLAB AT EB #1						
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	
* A1	13	#4	STR	28'-10"	250	
A2	13	#4	STR	28'-10"	250	
* B1	58	#5	STR	11'-2"	676	
B2	58	#6	STR	11'-8"	1016	
REINFORCING STEEL					LBS.	1266
* EPOXY COATED REINFORCING STEEL					LBS.	926
CLASS AA CONCRETE					C. Y.	15.4
APPROACH SLAB AT EB #2						
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	
* A1	13	#4	STR	28'-10"	250	
A2	13	#4	STR	28'-10"	250	
* B1	58	#5	STR	11'-2"	676	
B2	58	#6	STR	11'-8"	1016	
REINFORCING STEEL					LBS.	1266
* EPOXY COATED REINFORCING STEEL					LBS.	926
CLASS AA CONCRETE					C. Y.	15.4

DRAWN BY: SHS/MAA 5-09	REV. 12-17	MAA/THC
CHECKED BY: BCH 5-09	REV. 08-19	BNB/THC
ASSEMBLED BY: T.KIRSCHBAUM	DATE: JUN 2023	
CHECKED BY: E.LAWES	DATE: JUN 2023	
DESIGN ENGINEER		
OF RECORD: T.KIRSCHBAUM	DATE: JUN 2023	

wsp

WSP USA Inc.
 434 FAYETTEVILLE STREET
 SUITE 1500
 RALEIGH, NC 27601
 TEL: 1.919.836.4040
 LICENSE NO. P-0165

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

STATE OF NORTH CAROLINA
 PROFESSIONAL SEAL
 SEAL 042638
 ENGINEER
 J. KIRSCHBAUM
 780451F03E486
 3/6/2024

PROJECT NO. BP13.R002
 RUTHERFORD COUNTY
 STATION: 14+80.00 -L-

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
BRIDGE APPROACH SLAB FOR PRESTRESSED CONCRETE BOX BEAM UNIT
 (SUB-REGIONAL TIER)

REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO. **S-17**
 TOTAL SHEETS 17

STD. NO. BAS_BB_30_90S

STANDARD NOTES

DESIGN DATA:

SPECIFICATIONS	AASHTO (CURRENT)
LIVE LOAD	SEE PLANS
IMPACT ALLOWANCE	SEE AASHTO
STRESS IN EXTREME FIBER OF STRUCTURAL STEEL - AASHTO M270 GRADE 36	20,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50W	27,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50	27,000 LBS. PER SQ. IN.
REINFORCING STEEL IN TENSION - GRADE 60	24,000 LBS. PER SQ. IN.
CONCRETE IN COMPRESSION	1,200 LBS. PER SQ. IN.
CONCRETE IN SHEAR	SEE AASHTO
STRUCTURAL TIMBER - TREATED OR UNTREATED EXTREME FIBER STRESS	1,800 LBS. PER SQ. IN.
COMPRESSION PERPENDICULAR TO GRAIN OF TIMBER	375 LBS. PER SQ. IN.
EQUIVALENT FLUID PRESSURE OF EARTH	30 LBS. PER CU. FT. (MINIMUM)

MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2024 "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; AND CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP.

CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED $\frac{3}{4}$ " WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO $1\frac{1}{2}$ " RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A $\frac{1}{4}$ " FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A $\frac{1}{4}$ " RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT, ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE.

ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER.

IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER.

DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS.

WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE $\frac{7}{8}$ " \emptyset SHEAR STUDS FOR THE $\frac{3}{4}$ " \emptyset STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - $\frac{7}{8}$ " \emptyset STUDS FOR 4 - $\frac{3}{4}$ " \emptyset STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF $\frac{7}{8}$ " \emptyset STUDS ALONG THE BEAM AS SHOWN FOR $\frac{3}{4}$ " \emptyset STUDS BASED ON THE RATIO OF 3 - $\frac{7}{8}$ " \emptyset STUDS FOR 4 - $\frac{3}{4}$ " \emptyset STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-0".

EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST $\frac{5}{16}$ " IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2" OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED.

WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES, ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY $\frac{1}{16}$ " OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB.

METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINIS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.