PROJECT REFERENCE NO.	SHEET NO.
WBS: 41665.10B	2

TYPICAL SECTION NO. 1

USE TYPICAL SECTION NO. 1

-L- STA. 12+50.00 TO STA. 13+25.00
-L- STA. 15+77.00 TO STA. 17+50.00

TYPICAL SECTION NO. 2

USE TYPICAL SECTION NO. 2

-L- STA. 13+25.00 TO STA. 15+77.00

PAVEMENT SCHEDULE	
C1	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 1½" IN DEPTH.
E1	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5½" IN DEPTH.
W	PROP. VAR. DEPTH ASPHALT CONCRETE WEDGING COURSE. TYPE I19 AT AN AVERAGE RATE OF 114 LBS. PER SQ. FT. PER 3" DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 3" IN DEPTH.
T	EARTH MATERIAL
U	EXISTING PAVEMENT

NOTE: ALL PAVEMENT SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.

23-NOV-2017 10:28
S:\Design\Projects\DN00615_NC129 Wall Fail Near Topton\New folder\NC129 Wall Fail Near Topton WORKING\dgn\TYPICALS\129_5TH TRY_Rdy_typ.dgn
jeebastian@DIVI14-27728