

PROJ. REFERENCE NO.	SHEET NO.
BP14.R002	TMP -2C

TEMPORARY SHORING NOTES

SHORING LOCATION NO. 7

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM -L189- STATION 11+10 +/-, 5.3 FT LT, TO STATION 11+27, 9.6 FT LT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:
UNIT WEIGHT = 120 PCF
FRICTION ANGLE = 30 DEGREES
COHESION (c) = 0 PSF
GROUNDWATER ELEVATION = BOTTOM OF CULVERT

NO SUBSURFACE INFORMATION IS AVAILABLE IN THE VICINITY OF TEMPORARY SHORING FROM -L189- STATION 11+10 +/-, 5.3 FT LT, TO STATION 11+27, 9.6 FT LT. THE INFORMATION PROVIDED FOR TEMPORARY SHORING DESIGN WAS ASSUMED AND MAY NOT BE APPLICABLE TO THE ACTUAL SITE CONDITIONS ENCOUNTERED DURING CONSTRUCTION.

DO NOT USE A TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -L189- STATION 11+10 +/-, 5.3 FT LT, TO STATION 11+27, 9.6 FT LT.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY SHORING FOR TEMPORARY SHORING FROM -L189- STATION 11+10 +/-, 5.3 FT LT, TO STATION 11+27, 9.6 FT LT. SEE GEOTECHNICAL STANDARD DETAIL NO. 1801.01 FOR STANDARD TEMPORARY SHORING.

IT MAY BE PREFERRED TO USE A TEMPORARY SOIL NAIL WALL FOR TEMPORARY SHORING FROM -L189- STATION 11+10 +/-, 5.3 FT LT, TO STATION 11+27, 9.6 FT LT. FOR TEMPORARY SOIL NAIL WALLS, SEE TEMPORARY SOIL NAIL WALLS PROVISION.

SHORING LOCATION NO. 8

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM -L189- STATION 11+49 +/-, 11.2 FT LT, TO STATION 11+64, 11.2 FT LT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:
UNIT WEIGHT = 120 PCF
FRICTION ANGLE = 30 DEGREES
COHESION (c) = 0 PSF
GROUNDWATER ELEVATION = BOTTOM OF CULVERT

NO SUBSURFACE INFORMATION IS AVAILABLE IN THE VICINITY OF TEMPORARY SHORING FROM -L189- STATION 11+49 +/-, 11.2 FT LT, TO STATION 11+64, 11.2 FT LT. THE INFORMATION PROVIDED FOR TEMPORARY SHORING DESIGN WAS ASSUMED AND MAY NOT BE APPLICABLE TO THE ACTUAL SITE CONDITIONS ENCOUNTERED DURING CONSTRUCTION.

DO NOT USE A TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -L189- STATION 11+49 +/-, 11.2 FT LT, TO STATION 11+64, 11.2 FT LT.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY SHORING FOR TEMPORARY SHORING FROM -L189- STATION 11+49 +/-, 11.2 FT LT, TO STATION 11+64, 11.2 FT LT. SEE GEOTECHNICAL STANDARD DETAIL NO. 1801.01 FOR STANDARD TEMPORARY SHORING.

IT MAY BE PREFERRED TO USE A TEMPORARY SOIL NAIL WALL FOR TEMPORARY SHORING FROM -L189- STATION 11+49 +/-, 11.2 FT LT, TO STATION 11+64, 11.2 FT LT. FOR TEMPORARY SOIL NAIL WALLS, SEE TEMPORARY SOIL NAIL WALLS PROVISION.

SHORING LOCATION NO. 9

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM -L190- STATION 13+42 +/-, 4.4 FT RT, TO STATION 13+66, 4.0 FT RT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:
UNIT WEIGHT = 120 PCF
FRICTION ANGLE = 30 DEGREES
COHESION (c) = 0 PSF
GROUNDWATER ELEVATION = BOTTOM OF CULVERT

NO SUBSURFACE INFORMATION IS AVAILABLE IN THE VICINITY OF TEMPORARY SHORING FROM -L190- STATION 13+42 +/-, 4.4 FT RT, TO STATION 13+66, 4.0 FT RT. THE INFORMATION PROVIDED FOR TEMPORARY SHORING DESIGN WAS ASSUMED AND MAY NOT BE APPLICABLE TO THE ACTUAL SITE CONDITIONS ENCOUNTERED DURING CONSTRUCTION.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY WALL FOR TEMPORARY SHORING FROM -L190- STATION 13+42 +/-, 4.4 FT RT, TO -L190- STATION 13+66, 4.0 FT RT. SEE GEOTECHNICAL STANDARD DETAIL NO. 1801.02 FOR STANDARD TEMPORARY SHORING.

RS&H 8521 SIX FORKS ROAD, SUITE 400
RALEIGH, NC 27615
NC FIRM LICENSE No: F-0493

<div>APPROVED: <div>Signed by: </div></div> <div>DATE: 11/24/2025</div> <div></div> <div>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</div>	<div></div>	TEMPORARY SHORING NOTES
--	-------------	-------------------------