

| STATE | STATE PROJECT REFERENCE NO. | SHEET NO. | TOTAL SHEETS |
|-------|-----------------------------|-----------|--------------|
| N.C. | SF-190170 | 1 | 7 |

**STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT**

**STRUCTURE
SUBSURFACE INVESTIGATION**

COUNTY CHEROKEE
PROJECT DESCRIPTION BRIDGE NO. 170 ON SR 1411
(OLD BLOCK PLANT RD.) OVER MARBLE CREEK

REFERENCE: SF-190170

PROJECT: 17BP.14.R.167

CONTENTS

| <u>SHEET NO.</u> | <u>DESCRIPTION</u> |
|------------------|------------------------------|
| 1 | TITLE SHEET |
| 2, 2A | LEGEND |
| 3 | BORING LOCATION PLAN |
| 4-6 | BORING AND SOUNDING ROD LOGS |

PERSONNEL
TRIGON
GOODNIGHT, D.J.

INVESTIGATED BY GOODNIGHT, D.J.
DRAWN BY HILL, M.J.
CHECKED BY HUNSBERGER, W.S.
SUBMITTED BY FALCON ENG.
DATE DECEMBER 2017


CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.



DocuSigned by
Jeremy R Hamm 4/8/2021

462202304BBC46A...
SIGNATURE DATE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT**

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS





(PAGE 1 OF 2)



| SOIL DESCRIPTION | | | | | | | | | | GRADATION | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|---|--|------|-------|-------|-------|--|--|---|----------------------------|--|--|--|---|--|---|---|--|--|---|---|---|---|---|---|-----------------------------|--------------------------------|--|---|--------------------------|--|--|--------------------------|---|--|--|-----------------------------------|--|--|-----------------------|---------------------------|-------------------------|------------------------|--------------------------------|--------------|----------|--------------------|--|--|--|------------------------|--|--|--|--|--|--|--|
| SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6 | | | | | | | | | | WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SOIL LEGEND AND AASHTO CLASSIFICATION | | | | | | | | | | ANGULARITY OF GRAINS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED. | | | | | | | | | | MINERALOGICAL COMPOSITION | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE. | | | | | | | | | | COMPRESSIBILITY | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50 | | | | | | | | | | PERCENTAGE OF MATERIAL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> </thead> <tbody> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE 1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE 10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME 20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>> 10%</td> <td>> 20%</td> <td>HIGHLY 35% AND ABOVE</td> </tr> </tbody> </table> | | | | | | | | | | ORGANIC MATERIAL | GRANULAR SOILS | SILT - CLAY SOILS | OTHER MATERIAL | TRACE OF ORGANIC MATTER | 2 - 3% | 3 - 5% | TRACE 1 - 10% | LITTLE ORGANIC MATTER | 3 - 5% | 5 - 12% | LITTLE 10 - 20% | MODERATELY ORGANIC | 5 - 10% | 12 - 20% | SOME 20 - 35% | HIGHLY ORGANIC | > 10% | > 20% | HIGHLY 35% AND ABOVE | GROUND WATER | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ORGANIC MATERIAL | GRANULAR SOILS | SILT - CLAY SOILS | OTHER MATERIAL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TRACE OF ORGANIC MATTER | 2 - 3% | 3 - 5% | TRACE 1 - 10% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| LITTLE ORGANIC MATTER | 3 - 5% | 5 - 12% | LITTLE 10 - 20% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MODERATELY ORGANIC | 5 - 10% | 12 - 20% | SOME 20 - 35% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| HIGHLY ORGANIC | > 10% | > 20% | HIGHLY 35% AND ABOVE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | MISCELLANEOUS SYMBOLS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> </thead> <tbody> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>< 4 4 TO 10 10 TO 30 30 TO 50 > 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30</td> <td>< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4</td> </tr> </tbody> </table> | | | | | | | | | | PRIMARY SOIL TYPE | COMPACTNESS OR CONSISTENCY | RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE) | RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²) | GENERALLY GRANULAR MATERIAL (NON-COHESIVE) | VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE | < 4 4 TO 10 10 TO 30 30 TO 50 > 50 | N/A | GENERALLY SILT-CLAY MATERIAL (COHESIVE) | VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD | < 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30 | < 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4 | <table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td> ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</td> <td> DIP & DIP DIRECTION OF ROCK STRUCTURES</td> <td> TEST BORING</td> <td> SLOPE INDICATOR INSTALLATION</td> </tr> <tr> <td> SOIL SYMBOL</td> <td> AUGER BORING</td> <td> CONE PENETROMETER TEST</td> <td> SOUNDING ROD</td> </tr> <tr> <td> ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</td> <td> CORE BORING</td> <td> TEST BORING WITH CORE</td> <td> PIEZOMETER INSTALLATION</td> </tr> <tr> <td> INFERRED SOIL BOUNDARY</td> <td> MONITORING WELL</td> <td> SPT N-VALUE</td> <td></td> </tr> <tr> <td> INFERRED ROCK LINE</td> <td> SHALLOW UNDERCUT</td> <td></td> <td></td> </tr> <tr> <td> ALLUVIAL SOIL BOUNDARY</td> <td> UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</td> <td></td> <td></td> </tr> <tr> <td></td> <td> UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td> <td></td> <td></td> </tr> </tbody> </table> | | | | | | | | | | ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION | DIP & DIP DIRECTION OF ROCK STRUCTURES | TEST BORING | SLOPE INDICATOR INSTALLATION | SOIL SYMBOL | AUGER BORING | CONE PENETROMETER TEST | SOUNDING ROD | ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT | CORE BORING | TEST BORING WITH CORE | PIEZOMETER INSTALLATION | INFERRED SOIL BOUNDARY | MONITORING WELL | SPT N-VALUE | | INFERRED ROCK LINE | SHALLOW UNDERCUT | | | ALLUVIAL SOIL BOUNDARY | UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE | | | | UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK | | |
| PRIMARY SOIL TYPE | COMPACTNESS OR CONSISTENCY | RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE) | RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| GENERALLY GRANULAR MATERIAL (NON-COHESIVE) | VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE | < 4 4 TO 10 10 TO 30 30 TO 50 > 50 | N/A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| GENERALLY SILT-CLAY MATERIAL (COHESIVE) | VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD | < 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30 | < 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION | DIP & DIP DIRECTION OF ROCK STRUCTURES | TEST BORING | SLOPE INDICATOR INSTALLATION | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SOIL SYMBOL | AUGER BORING | CONE PENETROMETER TEST | SOUNDING ROD | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT | CORE BORING | TEST BORING WITH CORE | PIEZOMETER INSTALLATION | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| INFERRED SOIL BOUNDARY | MONITORING WELL | SPT N-VALUE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| INFERRED ROCK LINE | SHALLOW UNDERCUT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ALLUVIAL SOIL BOUNDARY | UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| TEXTURE OR GRAIN SIZE | | | | | | | | | | RECOMMENDATION SYMBOLS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> </thead> <tbody> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </tbody> </table> | | | | | | | | | | U.S. STD. SIEVE SIZE OPENING (MM) | 4 | 10 | 40 | 60 | 200 | 270 | | 4.76 | 2.00 | 0.42 | 0.25 | 0.075 | 0.053 | <table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td> UNDERCUT</td> <td> SHALLOW UNDERCUT</td> <td> UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td> <td> UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</td> </tr> </tbody> </table> | | | | | | | | | | UNDERCUT | SHALLOW UNDERCUT | UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK | UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL | | | | | | | | | | | | | | | | | | | | | | |
| U.S. STD. SIEVE SIZE OPENING (MM) | 4 | 10 | 40 | 60 | 200 | 270 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 4.76 | 2.00 | 0.42 | 0.25 | 0.075 | 0.053 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| UNDERCUT | SHALLOW UNDERCUT | UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK | UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>GRAIN SIZE</th> <th>MM</th> <th>305</th> <th>75</th> <th>2.0</th> <th>0.25</th> <th>0.05</th> <th>0.005</th> </tr> </thead> <tbody> <tr> <td></td> <td>IN.</td> <td>12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> | | | | | | | | | | GRAIN SIZE | MM | 305 | 75 | 2.0 | 0.25 | 0.05 | 0.005 | | IN. | 12 | 3 | | | | | ABBREVIATIONS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| GRAIN SIZE | MM | 305 | 75 | 2.0 | 0.25 | 0.05 | 0.005 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | IN. | 12 | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>AR - AUGER REFUSAL</td> <td>MED. - MEDIUM</td> <td>VST - VANE SHEAR TEST</td> </tr> <tr> <td>BT - BORING TERMINATED</td> <td>MICA - MICACEOUS</td> <td>WEA. - WEATHERED</td> </tr> <tr> <td>CL - CLAY</td> <td>MOD. - MODERATELY</td> <td>U - UNIT WEIGHT</td> </tr> <tr> <td>CPT - CONE PENETRATION TEST</td> <td>NP - NON PLASTIC</td> <td>U_g - DRY UNIT WEIGHT</td> </tr> <tr> <td>CSE. - COARSE</td> <td>ORG. - ORGANIC</td> <td></td> </tr> <tr> <td>DMT - DILATOMETER TEST</td> <td>PMT - PRESSUREMETER TEST</td> <td style="text-align: center;">SAMPLE ABBREVIATIONS</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>SAP. - SAPROLITIC</td> <td>S - BULK</td> </tr> <tr> <td>e - VOID RATIO</td> <td>SD. - SAND, SANDY</td> <td>SS - SPLIT SPOON</td> </tr> <tr> <td>F - FINE</td> <td>SL. - SILT, SILTY</td> <td>ST - SHELBY TUBE</td> </tr> <tr> <td>FOSS. - FOSSILIFEROUS</td> <td>SLL. - SLIGHTLY</td> <td>RS - ROCK</td> </tr> <tr> <td>FRAC. - FRACTURED, FRACTURES</td> <td>TCR - TRICONE REFUSAL</td> <td>RT - RECOMPACTED TRIAXIAL</td> </tr> <tr> <td>FRAGS. - FRAGMENTS</td> <td>w - MOISTURE CONTENT</td> <td>CBR - CALIFORNIA BEARING RATIO</td> </tr> <tr> <td>HI. - HIGHLY</td> <td>v - VERY</td> <td></td> </tr> </tbody> </table> | | | | | | | | | | AR - AUGER REFUSAL | MED. - MEDIUM | VST - VANE SHEAR TEST | BT - BORING TERMINATED | MICA - MICACEOUS | WEA. - WEATHERED | CL - CLAY | MOD. - MODERATELY | U - UNIT WEIGHT | CPT - CONE PENETRATION TEST | NP - NON PLASTIC | U _g - DRY UNIT WEIGHT | CSE. - COARSE | ORG. - ORGANIC | | DMT - DILATOMETER TEST | PMT - PRESSUREMETER TEST | SAMPLE ABBREVIATIONS | DPT - DYNAMIC PENETRATION TEST | SAP. - SAPROLITIC | S - BULK | e - VOID RATIO | SD. - SAND, SANDY | SS - SPLIT SPOON | F - FINE | SL. - SILT, SILTY | ST - SHELBY TUBE | FOSS. - FOSSILIFEROUS | SLL. - SLIGHTLY | RS - ROCK | FRAC. - FRACTURED, FRACTURES | TCR - TRICONE REFUSAL | RT - RECOMPACTED TRIAXIAL | FRAGS. - FRAGMENTS | w - MOISTURE CONTENT | CBR - CALIFORNIA BEARING RATIO | HI. - HIGHLY | v - VERY | | EQUIPMENT USED ON SUBJECT PROJECT | | | | | | | | | | |
| AR - AUGER REFUSAL | MED. - MEDIUM | VST - VANE SHEAR TEST | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BT - BORING TERMINATED | MICA - MICACEOUS | WEA. - WEATHERED | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CL - CLAY | MOD. - MODERATELY | U - UNIT WEIGHT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CPT - CONE PENETRATION TEST | NP - NON PLASTIC | U _g - DRY UNIT WEIGHT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CSE. - COARSE | ORG. - ORGANIC | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DMT - DILATOMETER TEST | PMT - PRESSUREMETER TEST | SAMPLE ABBREVIATIONS | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DPT - DYNAMIC PENETRATION TEST | SAP. - SAPROLITIC | S - BULK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| e - VOID RATIO | SD. - SAND, SANDY | SS - SPLIT SPOON | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| F - FINE | SL. - SILT, SILTY | ST - SHELBY TUBE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FOSS. - FOSSILIFEROUS | SLL. - SLIGHTLY | RS - ROCK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FRAC. - FRACTURED, FRACTURES | TCR - TRICONE REFUSAL | RT - RECOMPACTED TRIAXIAL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| FRAGS. - FRAGMENTS | w - MOISTURE CONTENT | CBR - CALIFORNIA BEARING RATIO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| HI. - HIGHLY | v - VERY | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input checked="" type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6' CONTINUOUS FLIGHT AUGER</td> <td>CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input checked="" type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> -B _____ <input type="checkbox"/> -H _____</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> -N _____</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td>HAND TOOLS:</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE _____ * STEEL TEETH</td> <td><input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE _____ * TUNG-CARB.</td> <td><input checked="" type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> </tr> <tr> <td><input type="checkbox"/></td> <td></td> <td><input type="checkbox"/></td> </tr> </tbody> </table> | | | | | | | | | | DRILL UNITS: | ADVANCING TOOLS: | HAMMER TYPE: | <input type="checkbox"/> CME-45C | <input type="checkbox"/> CLAY BITS | <input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL | <input checked="" type="checkbox"/> CME-55 | <input type="checkbox"/> 6' CONTINUOUS FLIGHT AUGER | CORE SIZE: | <input type="checkbox"/> CME-550 | <input checked="" type="checkbox"/> 8" HOLLOW AUGERS | <input type="checkbox"/> -B _____ <input type="checkbox"/> -H _____ | <input type="checkbox"/> VANE SHEAR TEST | <input type="checkbox"/> HARD FACED FINGER BITS | <input type="checkbox"/> -N _____ | <input type="checkbox"/> PORTABLE HOIST | <input type="checkbox"/> TUNG-CARBIDE INSERTS | HAND TOOLS: | <input type="checkbox"/> | <input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER | <input type="checkbox"/> POST HOLE DIGGER | <input type="checkbox"/> | <input type="checkbox"/> TRICONE _____ * STEEL TEETH | <input type="checkbox"/> HAND AUGER | <input type="checkbox"/> | <input type="checkbox"/> TRICONE _____ * TUNG-CARB. | <input checked="" type="checkbox"/> SOUNDING ROD | <input type="checkbox"/> | <input type="checkbox"/> CORE BIT | <input type="checkbox"/> VANE SHEAR TEST | <input type="checkbox"/> | | <input type="checkbox"/> | | | | | | | | | | | | | | | | | |
| DRILL UNITS: | ADVANCING TOOLS: | HAMMER TYPE: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> CME-45C | <input type="checkbox"/> CLAY BITS | <input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input checked="" type="checkbox"/> CME-55 | <input type="checkbox"/> 6' CONTINUOUS FLIGHT AUGER | CORE SIZE: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> CME-550 | <input checked="" type="checkbox"/> 8" HOLLOW AUGERS | <input type="checkbox"/> -B _____ <input type="checkbox"/> -H _____ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> VANE SHEAR TEST | <input type="checkbox"/> HARD FACED FINGER BITS | <input type="checkbox"/> -N _____ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> PORTABLE HOIST | <input type="checkbox"/> TUNG-CARBIDE INSERTS | HAND TOOLS: | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> | <input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER | <input type="checkbox"/> POST HOLE DIGGER | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> | <input type="checkbox"/> TRICONE _____ * STEEL TEETH | <input type="checkbox"/> HAND AUGER | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> | <input type="checkbox"/> TRICONE _____ * TUNG-CARB. | <input checked="" type="checkbox"/> SOUNDING ROD | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> | <input type="checkbox"/> CORE BIT | <input type="checkbox"/> VANE SHEAR TEST | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> | | <input type="checkbox"/> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PLASTICITY | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>NON PLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> </thead> <tbody> <tr> <td>SLIGHTLY PLASTIC</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </tbody> </table> | | | | | | | | | | NON PLASTIC | PLASTICITY INDEX (PI) | DRY STRENGTH | SLIGHTLY PLASTIC | 0-5 | VERY LOW | MODERATELY PLASTIC | 6-15 | SLIGHT | HIGHLY PLASTIC | 16-25 | MEDIUM | | 26 OR MORE | HIGH | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| NON PLASTIC | PLASTICITY INDEX (PI) | DRY STRENGTH | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| SLIGHTLY PLASTIC | 0-5 | VERY LOW | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MODERATELY PLASTIC | 6-15 | SLIGHT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| HIGHLY PLASTIC | 16-25 | MEDIUM | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 26 OR MORE | HIGH | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| COLOR | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT**

SUBSURFACE INVESTIGATION

**SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS
(PAGE 2 OF 2)**

| ROCK DESCRIPTION | | TERMS AND DEFINITIONS | |
|--|--|---|--------------------------|
| <p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p> | | <p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS IN OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p> | |
| <p>WEATHERED ROCK (WR)</p> |  | <p>NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.</p> | |
| <p>CRYSTALLINE ROCK (CR)</p> |  | <p>FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.</p> | |
| <p>NON-CRYSTALLINE ROCK (NCR)</p> |  | <p>FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.</p> | |
| <p>COASTAL PLAIN SEDIMENTARY ROCK (CP)</p> |  | <p>COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.</p> | |
| WEATHERING | | | |
| <p>FRESH</p> | | <p>ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p> | |
| <p>VERY SLIGHT (V SL.)</p> | | <p>ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p> | |
| <p>SLIGHT (SL.)</p> | | <p>ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS, SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</p> | |
| <p>MODERATE (MOD.)</p> | | <p>SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</p> | |
| <p>MODERATELY SEVERE (MOD. SEV.)</p> | | <p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <i>IF TESTED, WOULD YIELD SPT REFUSAL</i></p> | |
| <p>SEVERE (SEV.)</p> | | <p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <i>IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF</i></p> | |
| <p>VERY SEVERE (V SEV.)</p> | | <p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</i></p> | |
| <p>COMPLETE</p> | | <p>ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</p> | |
| ROCK HARDNESS | | | |
| <p>VERY HARD</p> | | <p>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</p> | |
| <p>HARD</p> | | <p>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</p> | |
| <p>MODERATELY HARD</p> | | <p>CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</p> | |
| <p>MEDIUM HARD</p> | | <p>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</p> | |
| <p>SOFT</p> | | <p>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</p> | |
| <p>VERY SOFT</p> | | <p>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.</p> | |
| FRACTURE SPACING | | BEDDING | |
| <p>TERM</p> | <p>SPACING</p> | <p>TERM</p> | <p>THICKNESS</p> |
| <p>VERY WIDE</p> | <p>MORE THAN 10 FEET</p> | <p>VERY THICKLY BEDDED</p> | <p>4 FEET</p> |
| <p>WIDE</p> | <p>3 TO 10 FEET</p> | <p>THICKLY BEDDED</p> | <p>1.5 - 4 FEET</p> |
| <p>MODERATELY CLOSE</p> | <p>1 TO 3 FEET</p> | <p>THINLY BEDDED</p> | <p>0.16 - 1.5 FEET</p> |
| <p>CLOSE</p> | <p>0.16 TO 1 FOOT</p> | <p>VERY THINLY BEDDED</p> | <p>0.03 - 0.16 FEET</p> |
| <p>VERY CLOSE</p> | <p>LESS THAN 0.16 FEET</p> | <p>THICKLY LAMINATED</p> | <p>0.008 - 0.03 FEET</p> |
| | | <p>THINLY LAMINATED</p> | <p>< 0.008 FEET</p> |
| INDURATION | | | |
| <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> | | | |
| <p>FRIABLE</p> | <p>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> | | |
| <p>MODERATELY INDURATED</p> | <p>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> | | |
| <p>INDURATED</p> | <p>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> | | |
| <p>EXTREMELY INDURATED</p> | <p>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p> | | |
| <p>BENCH MARK: BL-2; N: 538434.1; E: 505754.1 STA. 11+44.5 OFFSET: 5.7' LT -L- ELEVATION: 1590.29 FEET</p> | | | |
| <p>NOTES: FIAD - FILLED IMMEDIATELY AFTER DRILLING</p> | | | |
| <p>DATE: 8-15-14</p> | | | |



NOTES:

- PLANS ADOPTED FROM ELECTRONIC SURVEY FILES RECEIVED FROM WSP DATED AUGUST 2016
- BRIDGE SKEW: 90°



FALCON ENGINEERING, INC.
1210 TRINITY ROAD, SUITE 110
RALEIGH, NC 27607
PHONE: 919.871.0800
FAX: 919.871.0803

BORING LOCATION PLAN


BRIDGE NO. 170 ON SR 1411
(OLD BLOCK PLANT RD.) OVER MARBLE CREEK
CHEROKEE COUNTY, NORTH CAROLINA
WBS NO.: 17BP.14.R.167 | TIP NO.: SF-190170
FALCON PROJECT NO.: G16038.01

GEOTECHNICAL BORING REPORT

BORE LOG

| | | | | | | | |
|---|--|----------------------------|--|---------------------------------|--|-----------------------------------|------------------------|
| WBS 17BP.14.R.167 | | TIP SF-190170 | | COUNTY CHEROKEE | | GEOLOGIST Goodnight, D. J. | |
| SITE DESCRIPTION BRIDGE NO. 170 ON SR 1411 (OLD BLOCK PLANT RD.) OVER MARBLE CREEK | | | | | | | GROUND WTR (ft) |
| BORING NO. B-1 | | STATION 11+38 | | OFFSET 3 ft LT | | ALIGNMENT -L- | |
| COLLAR ELEV. 1,590.5 ft | | TOTAL DEPTH 25.0 ft | | NORTHING 538,434 | | EASTING 505,747 | |
| DRILL RIG/HAMMER EFF./DATE TRI9435 CME-55 85% 02/22/2016 | | | | DRILL METHOD H.S. Augers | | HAMMER TYPE Automatic | |
| DRILLER Contract Driller | | START DATE 08/11/16 | | COMP. DATE 08/11/16 | | SURFACE WATER DEPTH N/A | |

| ELEV (ft) | DRIVE ELEV (ft) | DEPTH (ft) | BLOW COUNT | | | BLOWS PER FOOT | | | | | SAMP. NO. | MOI | LOG | SOIL AND ROCK DESCRIPTION | DEPTH (ft) | |
|-----------|-----------------|------------|------------|-------|-------|----------------|----|----|----|-----|-----------|-----|-----|---------------------------|------------|-----|
| | | | 0.5ft | 0.5ft | 0.5ft | 0 | 25 | 50 | 75 | 100 | | | | | | |
| 1595 | | | | | | | | | | | | | | | | |
| 1590 | 1,589.5 | 1.0 | 3 | 2 | 2 | | | | | | | | | | 1.0 | 1.0 |
| | 1,587.0 | 3.5 | 13 | 16 | 15 | | | | | | | | | | 3.0 | 3.0 |
| 1585 | 1,584.5 | 6.0 | 100/0.3 | | | | | | | | | | | | 7.5 | 7.5 |
| | 1,582.0 | 8.5 | 3 | 7 | 8 | | | | | | | | | | | |
| 1580 | 1,577.0 | 13.5 | 8 | 16 | 24 | | | | | | | | | | | |
| | 1,572.0 | 18.5 | 5 | 6 | 7 | | | | | | | | | | | |
| 1570 | 1,567.0 | 23.5 | 2 | 3 | 5 | | | | | | | | | | | |



NCDOT BORE SINGLE G16038.01 BRIDGE 170.GPJ NC_DOT.GDT 12/6/17



1210 TRINITY ROAD, SUITE 110
CARY, NC 27513

PHONE: 919.871.0800
www.falconengineers.com

TEST BORING LOG

| | | | | | |
|---|---|-------------------------------|-------------------------------------|-----------------------|---------------|
| PROJECT NO. G16038.01 | PROJECT LOCATION Cherokee County | LOGGED BY Goodnight, D | GROUND WATER | 0 HOUR | STATIC |
| PROJECT NAME Bridge No. 170 on SR 1411 (Old Block Plant Rd.) over Marble Creek | | | HOLE | | |
| BORING NO. BR-3 | BORING LOCATION 1145 6 FT LT -L- | | DEPTH | | |
| ELEVATION (ft) 1586.0 | NORTHING (ft) 538428 | DRILL MACHINE | | DATE 8/11/2016 | |
| TOTAL DEPTH (ft) 8.3 | EASTING (ft) 505770 | DRILLER Faison, E | SURFACE WATER DEPTH (ft) 0.2 | | |
| DATE STARTED 8/11/2016 | DATE COMPLETED 8/11/2016 | DRILL METHOD | HAMMER TYPE 16 lb Hammer | | |



| ELEV. (ft) | DEPTH (ft) | BLOW COUNT | | BLOWS PER FOOT | SAMP. NO. | LOG | Elev. (ft) | SOIL AND ROCK DESCRIPTION | Depth (ft) |
|------------|------------|------------|--------|-------------------------------------|-----------|-----|------------|---|------------|
| | | 0.5 ft | 0.5 ft | | | | | | |
| | | | | 0 15 30 45 60 75 90 105 120 135 150 | | | 1586.0 | | 0.0 |
| 1585 | 0.0 | 5 | 53 | | | | | SOUNDING ROD ONLY, NO SAMPLES TAKEN. | |
| | 1.0 | 4 | 4 | | | | | | |
| | 2.0 | 16 | 18 | 8 | | | | | |
| | 3.0 | 13 | 18 | 34 | | | | | |
| | 4.0 | 18 | 17 | 31 | | | | | |
| | 5.0 | 18 | 23 | 35 | | | | | |
| 1580 | 6.0 | 27 | 42 | 41 | | | | | |
| | 7.0 | 80 | 68/0.4 | 69 | | | | | |
| | 8.0 | 80/0.3 | | 148/0.9 80/0.3 | | | | | |
| | | | | | | | 1577.7 | | |
| | | | | | | | | Rod Sounding Refusal at 8.3 feet Below Current Ground Surface in PARTIALLY WEATHERED ROCK | |

ROD SOUNDING LOG: G:16038.01 BR-3 SR BORING.GPJ FALCON FORMAT.GDT 12/16/17

GEOTECHNICAL BORING REPORT BORE LOG

| | | | |
|--|---------------------|--------------------------|----------------------------|
| WBS 17BP.14.R.167 | TIP SF-190170 | COUNTY CHEROKEE | GEOLOGIST Goodnight, D. J. |
| SITE DESCRIPTION BRIDGE NO. 170 ON SR 1411 (OLD BLOCK PLANT RD.) OVER MARBLE CREEK | | | GROUND WTR (ft) |
| BORING NO. B-2 | STATION 11+85 | OFFSET 1 ft LT | ALIGNMENT -L- |
| COLLAR ELEV. 1,591.4 ft | TOTAL DEPTH 25.0 ft | NORTHING 538,410 | EASTING 505,788 |
| DRILL RIG/HAMMER EFF./DATE TRI9435 CME-55 85% 02/22/2016 | | DRILL METHOD H.S. Augers | HAMMER TYPE Automatic |
| DRILLER Contract Driller | START DATE 08/11/16 | COMP. DATE 08/11/16 | SURFACE WATER DEPTH N/A |

| ELEV (ft) | DRIVE ELEV (ft) | DEPTH (ft) | BLOW COUNT | | | BLOWS PER FOOT | | | | | SAMP. NO. | LOG MOI | SOIL AND ROCK DESCRIPTION | DEPTH (ft) | |
|-----------|-----------------|------------|------------|-------|-------|----------------|----|----|----|-----|-----------|---------|---------------------------|--|-----|
| | | | 0.5ft | 0.5ft | 0.5ft | 0 | 25 | 50 | 75 | 100 | | | | | |
| 1595 | | | | | | | | | | | | | | | |
| 1590 | 1,590.4 | 1.0 | 7 | 4 | 2 | | | | | | | | | 1.0' GRAVEL ROADWAY | 1.0 |
| | 1,587.9 | 3.5 | 1 | 1 | WOH | | | | | | | | | ROADWAY EMBANKMENT BROWN, CSE. TO F. SANDY CLAY (A-7) WITH TRACE GRAVEL | |
| 1585 | 1,585.4 | 6.0 | 10 | 11 | 12 | | | | | | | | | BROWN, SILTY CSE. TO F. SAND (A-2-4) WITH TRACE GRAVEL AND ORGANICS | 5.5 |
| | 1,582.9 | 8.5 | 10 | 17 | 23 | | | | | | | | | RESIDUAL TAN, F. SANDY SILT (A-4) WITH TRACE MICA, SAPROLITIC | 8.0 |
| 1580 | | | | | | | | | | | | | | | |
| | 1,577.9 | 13.5 | 13 | 15 | 15 | | | | | | | | | | |
| 1575 | | | | | | | | | | | | | | | |
| | 1,572.9 | 18.5 | 9 | 18 | 24 | | | | | | | | | | |
| 1570 | | | | | | | | | | | | | | | |
| | 1,567.9 | 23.5 | 10 | 17 | 27 | | | | | | | | | | |



NCDOT BORE SINGLE G16038.01 BRIDGE 170.GPJ NC_DOT.GDT 12/6/17