PROJECT REFERENCE NO.	SHEET NO.
43936.1.1 & 2016CPT.14.03.20561.1	3B

USE TYPICAL SECTION NO. 1

–L– STA. 10+00.00 TO STA. 11+00

TYPICAL SECTION NO. 1

USE TYPICAL SECTION NO. 2

–L– STA. 11+00 TO STA. 11+60

TYPICAL SECTION NO. 2

USE TYPICAL SECTION NO. 3

–L– STA. 11+60 TO STA. 14+60

TYPICAL SECTION NO. 3

USE TYPICAL SECTION NO. 4

–L– STA. 14+60.00 TO STA. 16+71

TYPICAL SECTION NO. 4

USE INSET A

–L– STA. 10+50 RT TO 14+13 RT
–L– STA. 17+25 RT TO 19+50 RT
–L– STA. 21+00 RT TO 22+25 RT

Wedging Detail

USE INSET B

–L– STA. 11+00 RT TO 24+10 RT

PAVEMENT SCHEDULE	
C1	PROP. 1½″ DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1″ DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 1½″ IN DEPTH.
E1	PROP. 8″ DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1″ DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 3″ IN DEPTH OR GREATER THAN 5½″ IN DEPTH.
W	PROP. VAR. DEPTH ASPHALT CONCRETE WEDGING COURSE. TYPE I19 AT AN AVERAGE RATE OF 114 LBS. PER SQ. FT. PER 3″ DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 3″ IN DEPTH.
T	EARTH MATERIAL
U	EXISTING PAVEMENT

NOTE: ALL PAVEMENT SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.

20-JUN-2016 09:48
C:\Users\tpcrosby\Desktop\topton alignment practice\3D\dgn\practice_new_align_12-14.dgn
mpcrosby AT-D14PA0227179a