PROJECT ID. NO.	SHEET NO.
SM-6114C	Sig.M6

Fabrication Details – Strain Pole Attachments



Strain Pole Attachments



Attachment of Cable to Intermediate Metal Pole



Metal Pole Grounding Detail For Strain Pole and Mast Arm

NOTE:

1. Strap all signal cables to the side of the pole with ¾″ stainless steel straps when the distance between the spanwire attachment clamp and the weatherheads exceeds 3′-0″.
2. Provide minimum two spanwire pole clamps per pole.
3. It is prohibited to attach two span wires at one pole clamp.
4. For general requirements refer to NCDOT Standard Specifications for Roadway and Structures, January 2018.

Prepared in the Offices of:
Transportation Mobility and Safety Division
Signal Design Section
750 N.Greenfield Pkwy.Garner.NC 27529

SCALE
0 NA
NONE

Typical Fabrication Details
For
Strain Pole Attachments

PLAN DATE:	OCTOBER 2017	DESIGNED BY:	C.F.ANDREWS
PREPARED BY:	N. BITTING	REVIEWED BY:	D.C. SARKAR

REVISIONS	INIT.	DATE

SEAL
NORTH CAROLINA PROFESSIONAL SEAL 028094 ENGINEER DEBASISH C. SARKAR

DocuSigned by: Debasish C. Sarkar
SIGNATURE
10/11/2017
DATE

11-OCT-2017 08:36
S:\TTSASU\TS Signals\Signal Design Section\Eastern Region\MM Sheets\2016\2014 Sig.M6 Std. Fabrication Details-Strain Poles.dgn
rmitnger