



STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION

PAT MCCRORY  
GOVERNOR

ANTHONY J. TATA  
SECRETARY

April 7, 2015

CONTRACT: DB00229  
WBS ELEMENT: 2CR.10071.12  
FA NUMBER: STATE FUNDED  
COUNTY: Beaufort  
ROUTE: NC 92-99  
DESCRIPTION: Widening, Resurfacing, and Shoulder Reconstruction on NC 92-99

**Addendum 1**

Please note the following addition to the proposal for the above referenced project.

**TRENCHING FOR BASE COURSE:**

(1-3-07)

RR 79 Rev

Perform all trenching necessary to place the asphalt concrete base course widening in accordance with the typical sections, at locations shown on the sketch maps, and as directed by the Engineer.

**Trenching for asphalt base course shall be completed by use of a milling machine approved by the Engineer. Areas that require widening more than the typical section requires, such as turn lanes, may be completed by other means of widening as approved. All materials excavated by milling shall be stockpiled in an approved manner and utilized as shoulder construction material. Stockpiled materials that remain after completion of the shoulder construction shall become the property of the Department and removed by NCDOT forces.**

Perform the trenching for the base course on the same day that the base course is to be placed. If the base course cannot be placed on the same day the trench section is excavated, backfill the trench with earth material and compact it to the satisfaction of the Engineer. Once the trench is open, perform backfilling and re-opening of the trench at no cost to the Department.

The Contractor will be restricted to widening one side of the project at a time unless otherwise permitted by the Engineer. In widening, operate equipment and conduct operations in the same direction as the flow of traffic.

Density tests may be taken every 2000 feet in the widened areas as directed by the Engineer. Shape and compact the subgrade in the widened areas to the satisfaction of the Engineer. Compact the asphalt concrete base course in the widened areas in accordance with the provisions of Article 610-9 of the *Standard Specifications*.

Place the excavated material from trenching operation on the adjacent shoulder area as directed by the Engineer. Cut adequate weep holes in the excavated material to provide for adequate drainage as directed by the Engineer. Remove all excavated material from all drives to provide ingress and egress to abutting properties and from in front of mailboxes and paper boxes. Saw a neat edge and remove all asphalt and/or concrete driveways, and existing asphalt widening, as directed by the Engineer, to the width of the widening and dispose of any excavated concrete or asphalt materials. Properly reconnect driveways.

Upon completion of the paving operation, backfill the trench to the satisfaction of the Engineer. Properly dispose of any excess material remaining after this operation.

MAILING ADDRESS:  
DIVISION TWO - OPERATIONS  
P.O. BOX 1587  
GREENVILLE, NC 27835

TELEPHONE: (252) 439-2800  
FAX: (252) 830-3325

WEBSITE: WWW.NCDOT.GOV

LOCATION:  
1704 N GREENE ST  
GREENVILLE, NC

No direct payment will be made for trenching, sawing, and removal of driveways, depositing material on shoulder area, backfilling trench, or removal of spoil material, as the cost of this work shall be included in the contract unit price per ton for *Asphalt Concrete Base Course, Type \_\_\_\_*.

The contract will be prepared accordingly.

Sincerely,

A handwritten signature in black ink, appearing to read "Sarah Lentine", written in a cursive style.

Sarah Lentine  
Division Contract Officer

cc: Ms. Maria Rogerson, PE  
Mr. Bill Kincannon, PE