PROJECT REFERENCE NO.	SHEET NO.
17BP.2.R.55	2
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	PAVEMENT DESIGN ENGINEER
11/16/2015	11/16/2015

C1	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5A, AT AN AVERAGE RATE OF 336 LBS. PER SQ.YD. IN EACH OF TWO LAYERS.
D1	PROP. APPROX. 3" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 342 LBS. PER SQ. YD.
D2	PROPOSED VARIABLE DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, TO BE PLACED IN LAYERS NOT LESS THAN 2.5" OR GREATER THAN 4" IN DEPTH.
E1	PROP. APPROX. 4" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
T	EARTH MATERIAL.
U	EXISTING PAVEMENT.
U1	CONCRETE CORED SLAB

NOTE: PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.



TYPICAL BRIDGE SECTION (NTS)
-L- 12+29.38 - 12+86.63



USE TYPICAL SECTION #3
-D- 10+22.17 - 10+62.26
-D- 11+10.09 - 11+46.07



USE TYPICAL SECTION #1 (NTS)
-L- 10+35.00 - 12+18.38
-L- 13+60.48 - 14+50.00



WEDGING DETAIL FOR BRIDGE
NOT TO SCALE



USE TYPICAL SECTION #2
-L- 12+97.63 - 13+60.48
SHOULDER BERM GUTTER

REVISIONS

8/17/99

10-NOV-2015 11:58
C:\WINDOWS\TEMP\BEAUFORT\beaufort 119\Beaufort119_ddc2_psb_2.dgn
$$$$USERNAME$$$$