


PHASING DIAGRAM



PHASING DIAGRAM DETECTION LEGEND
 ● ← DETECTED MOVEMENT
 ○ ← UNDETECTED MOVEMENT (OVERLAP)
 - - - ← UNSIGNALIZED MOVEMENT
 - - - → PEDESTRIAN MOVEMENT

TABLE OF OPERATION

SIGNAL FACE	PHASE		
	02+6	04+8	FLASH
21	F	R	Y
22, 23	G	R	Y
41	R	F	R
42, 43	R	G	R
61	F	R	Y
62, 63	G	R	Y
81	R	F	R
82, 83	R	G	R
P81, P82	DW	W	DRK

W - Walk
 DW - Don't Walk
 DRK - Dark

SE-PAC 2070 LOOP & DETECTOR UNIT INSTALLATION CHART



LOOP NO.	SIZE (ft)	TURNS	DIST. FROM STOPBAR (ft)	NEW	EXISTING	ASSIGNED PHASE	DETECTOR PROGRAMMING													
							DELAY	EXTEND (STRETCH)	OPERATION MODE							SWITCH	SYSTEM	LOOPS	STATUS	
									VEHICLE	PEDESTRIAN	LOCAL	STOP A	STOP B	PROTECTOR	PROTECTOR THROUGH					AND
2A	6X6	4	250	X	-	2	- SEC.	- SEC.	X	-	-	-	-	-	-	-	-	-	X	-
2B	6X40	2-4-2	0	X	-	2	- SEC.	- SEC.	X	-	-	-	-	-	-	-	-	-	X	-
4A	6X40	2-4-2	0	X	-	4	3 SEC.	- SEC.	X	-	-	-	-	-	-	-	-	X	-	
4B	6X40	2-4-2	0	X	-	4	10 SEC.	- SEC.	X	-	-	-	-	-	-	-	-	X	-	
6A	6X6	4	250	X	-	6	- SEC.	- SEC.	X	-	-	-	-	-	-	-	-	X	-	
6B	6X40	2-4-2	0	X	-	6	- SEC.	- SEC.	X	-	-	-	-	-	-	-	-	X	-	
8A	6X40	2-4-2	0	X	-	8	3 SEC.	- SEC.	X	-	-	-	-	-	-	-	-	X	-	
8B	6X40	2-4-2	0	X	-	8	10 SEC.	- SEC.	X	-	-	-	-	-	-	-	-	X	-	

2 Phase Fully Actuated (Raleigh Signal System)

NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Set all detector units to presence mode.
- Locate new cabinet so as not to obstruct sight distance of vehicles turning right on red.
- Omit "WALK" and flashing "DON'T WALK" with no pedestrian calls.
- Program pedestrian heads to countdown the flashing "Don't Walk" time only.
- Pavement markings are existing unless otherwise shown.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.

SIGNAL FACE I.D.





SE-PAC 2070 TIMING CHART

FEATURE	PHASE			
	2	4	6	8
Min Green *	12	7	12	7
Passage Gap *	6.0	2.0	6.0	2.0
Maximum Green *	90	30	90	30
Yellow Change	4.4	3.8	4.4	3.8
Red Clear	1.3	1.5	1.3	1.5
Walk *	-	-	-	7
Pedestrian Clear	-	-	-	16
Added Initial *	2.5	-	2.5	-
Maximum Initial *	34	-	34	-
Time Before Reduction *	15	-	15	-
Time To Reduce *	30	-	30	-
Minimum Gap	3.0	-	3.0	-
Recall Mode	MIN RECALL	-	MIN RECALL	-
Vehicle Call Memory	LOCK	NON-LOCK	LOCK	NON-LOCK
Dual Entry	-	ON	-	ON
Simultaneous Gap	ON	ON	ON	ON

* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

LEGEND



New Installation

Prepared in the Offices of:
 Transportation Mobility and Safety Solutions
 NORTH CAROLINA
 PROFESSIONAL ENGINEER
 SEAL 026486
 ROBERT J. ZIEMBA

SR 2012 (Litchford Road) at Hunting Ridge Road and Rowland Road
 Division 5 Wake County Raleigh
 PLAN DATE: October 2018 REVIEWED BY:
 PREPARED BY: C.E. Carter REVIEWED BY:
 REVISIONS INIT. DATE

750 N. Greenfield Pkwy, Garner, NC 27529
 SCALE 0 40
 1" = 40'


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED
 SEAL
 11/7/2018
 SIG. INVENTORY NO. 05-1695

07-Nov-2018 12:59
 S:\IT\55\UM\T\S\Signal\485\Signal\401\41\5-W-5705R\051695.sig_dgn_20181107.dgn
 rz:lemba

EDI MODEL 2018ECL-NC CONFLICT MONITOR PROGRAMMING DETAIL

(remove jumpers and set switches as shown)


REMOVE DIODE JUMPERS 2-6, 2-9, 2-11, 4-8, 4-10, 4-12, 4-16, 6-9, 6-11, 8-10, 8-12, 8-16, 9-11, 10-12, 10-16 and 12-16.



REMOVE JUMPERS AS SHOWN

NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Connect serial cable from conflict monitor to comm. port 1 of 2070 controller. Ensure conflict monitor communicates with 2070.



NOTES

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program controller to start up in phases 2 and 6 green.
- Enable simultaneous gap-out feature, on controller unit, for all phases.
- Program phases 4 and 8, on controller unit, for dual entry.
- Program phases 2 and 6, on controller unit, for volume density operation.
- The cabinet and controller are part of the Raleigh City Signal System.

EQUIPMENT INFORMATION

CONTROLLER.....2070
 CABINET.....332 W/ AUX
 SOFTWARE.....SE-PAC2070
 CABINET MOUNT.....BASE
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE
 LOAD SWITCHES USED.....S2,S5,S8,S11,S12,AUX S1,
 AUX S2,AUX S4,AUX S5
 PHASES USED.....2,4,6,8,8 PED
 OVERLAP "A".....*
 OVERLAP "B".....*
 OVERLAP "C".....*
 OVERLAP "D".....*

* See sheet 2 for Overlap and Protected & Permissive Phases programming.

SIGNAL HEAD HOOK-UP CHART


LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6	
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18	
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE	
SIGNAL HEAD NO.	NU	22,23	NU	NU	42,43	NU	NU	62,63	NU	NU	82,83	P81, P82	61	81	NU	21	41	NU	
RED		128			101			134				107							
YELLOW		129			102			135				108							
GREEN		130			103			136				109							
RED ARROW																A121	A124	A114	A101
YELLOW ARROW																A122	A125	A115	A102
FLASHING YELLOW ARROW																A123	A126	A116	A103
GREEN ARROW																			
Hand icon													110						
Person icon													112						

NU = Not Used

* See pictorial of head wiring in detail below.


FYA SIGNAL WIRING DETAIL

(wire signal heads as shown)



INPUT FILE POSITION LAYOUT

(front view)




EX.: 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE
 ST = STOP TIME

INPUT FILE CONNECTION & PROGRAMMING CHART

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	DETECTOR NO.	NEMA PHASE	DELAY TIME	EXTEND (STRETCH) TIME
2A	TB2-5,6	I2U	39	3	2		
2B	TB2-7,8	I2L	43	4	2		
4A	TB4-9,10	I6U	41	11	4	3	
4B	TB4-11,12	I6L	45	12	4	10	
6A	TB3-5,6	J2U	40	21	6		
6B	TB3-7,8	J2L	44	22	6		
8A	TB5-9,10	J6U	42	31	8	3	
8B	TB5-11,12	J6L	46	32	8	10	
PED PUSH BUTTONS							
P81,P82	TB8-8,9	I13L	70	PED 8	8 PED		

NOTE:
 INSTALL DC ISOLATORS IN INPUT FILE SLOT I13.



FLASHER CIRCUIT MODIFICATION DETAIL

IN ORDER TO INSURE THAT SIGNALS FLASH CONCURRENTLY ON THE SAME APPROACH, MAKE THE FOLLOWING FLASHER CIRCUIT CHANGES:

- ON REAR OF PDA - REMOVE WIRE FROM TERM. T2-4 AND TERMINATE ON T2-2.
- ON REAR OF PDA - REMOVE WIRE FROM TERM. T2-5 AND TERMINATE ON T2-3.
- REMOVE FLASHER UNIT 2.

THE CHANGES LISTED ABOVE TIES ALL PHASES AND OVERLAPS TO FLASHER UNIT 1.

COUNTDOWN PEDESTRIAN SIGNAL OPERATION

Countdown Ped Signals are required to display timing only during Ped Clearance Interval. Consult Ped Signal Module user's manual for instructions on selecting this feature.

Electrical Detail - Sheet 1 of 2

Electrical AND PROGRAMMING DETAILS FOR:

Prepared In the Offices of:

750 N. Greenfield Pkwy, Garner, NC 27529

SR 2012 (Litchford Road)
 at
Hunting Ridge Road and Rowland Road

Division 5 Wake County Raleigh

PLAN DATE: November 2018 REVIEWED BY: T. Joyce

PREPARED BY: C. Strickland REVIEWED BY:

SEAL

DocuSigned by:
 T. Todd Joyce 11/16/2018

SIG. INVENTORY NO. 05-1695

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 05-1695
 DESIGNED: October 2018
 SEALED: 11/7/2018
 REVISED:

FLASHING YELLOW ARROW PROTECTED/PERMISSIVE SEQUENCE

for
OVERLAPS "A" "B" "C" & "D"

(program controller as shown below)

FROM MAIN MENU PRESS 4 (UNIT DATA)

SE-PAC UNIT DATA	PRESS # DESIRED
1-STARTUP & MISC	6-ALT SEQUENCES
2-REMOTE FLASH	7-PORT 1 DATA
3-OVERLAP STANDARD	8-I/O MISC
4-OVERLAP SPECIAL	9-SIG DRV OUT
5-RING STRUCTURE	
F-PRIOR MENU	

DO NOT enter any OVL PHASES! →

SE-PAC OVERLAP - A	(0-NO/1-YES)
OVL PHASES:	00000000 0000000
PHS/CHN:	123456789 0123456789 01234
OVL CHN(S):	000000000 000100000 00000
A-UP B-DN D-DspChn E-EDIT F-PRIOR MENU	

PRESS "B" ONCE

DO NOT enter any OVL PHASES! →

SE-PAC OVERLAP - B	(0-NO/1-YES)
OVL PHASES:	00000000 0000000
PHS/CHN:	123456789 0123456789 01234
OVL CHN(S):	000000000 000010000 00000
A-UP B-DN D-DspChn E-EDIT F-PRIOR MENU	

PRESS "B" ONCE

DO NOT enter any OVL PHASES! →

SE-PAC OVERLAP - C	(0-NO/1-YES)
OVL PHASES:	00000000 0000000
PHS/CHN:	123456789 0123456789 01234
OVL CHN(S):	000000000 0000010000 00000
A-UP B-DN D-DspChn E-EDIT F-PRIOR MENU	

PRESS "B" ONCE

DO NOT enter any OVL PHASES! →

SE-PAC OVERLAP - D	(0-NO/1-YES)
OVL PHASES:	00000000 0000000
PHS/CHN:	123456789 0123456789 01234
OVL CHN(S):	000000000 0000001000 00000
A-UP B-DN D-DspChn E-EDIT F-PRIOR MENU	

OVERLAP PROGRAMMING COMPLETE
PRESS 'F' TO RETURN TO UNIT DATA

INIT & N.A. RESP PROGRAMMING DETAIL

(program controller as shown below)

From Main Menu, press '3' (Phase Data)

SE-PAC PHASE DATA	PRESS # DESIRED
1-VEHICLE TIMES	6-N.LOCK & MISC
2-DENSITY TIMES	7-SPEC. SEQUENCE
3-PEDEST. TIMES	8-SPEC. DETECTOR
4-INIT & N.A. RESP	9-PHASE COPY
5-V & P RECALLS	0-MISC PED OPTIONS
F-PRIOR MENU	

Note Phases 1, 3, 5, and 7 NOT used! →

PHASE.....	1...2...3...4...5...6...7...8
INITIAL	0 4 0 1 0 4 0 1
NA RESP	0 1 0 2 0 1 0 2
CODES.....	0....1....2....3....4....5
INITIAL	NONE INACT RED YEL GRN DRK
NA RESP	NONE NA1 NA2 BOTH --- ---
A-UP B-DN C-LT D-RT E-ENTER F-PRIOR MENU	

INIT & N.A. RESP programming complete.

PROTECTED & PERMISSIVE PHASES

for

FLASHING YELLOW ARROW

(program controller as shown below)

FROM MAIN MENU PRESS 4 (UNIT DATA)

SE-PAC UNIT DATA	PRESS # DESIRED
1-STARTUP & MISC	6-ALT SEQUENCES
2-REMOTE FLASH	7-PORT 1 DATA
3-OVERLAP STANDARD	8-I/O MISC
4-OVERLAP SPECIAL	9-SIG DRV OUT
5-RING STRUCTURE	
F-PRIOR MENU	

SE-PAC OVL P. A...B...C...D...E...F...G...H.								
TR GRN	0	0	0	0	0	0	0	0
YEL/10	40	40	40	40	40	40	40	40
RED/10	20	20	20	20	20	20	20	20
-G/Y	1	3	5	7	0	0	0	0
+GRN	2	4	6	8	0	0	0	0


← PROTECTED PHASES
← PERMISSIVE PHASES

THE FLASHING YELLOW ARROW FOR SIGNAL HEADS 21, 41, 61 & 81 TURNS ON EXCLUSIVELY DURING PERMITTED GREEN PHASES 2, 4, 6 & 8.

PPLT DEFINITION PROGRAMMING COMPLETE
PRESS 'F' TO RETURN TO UNIT DATA

Electrical Detail - Sheet 2 of 2

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 05-1695
DESIGNED: October 2018
SEALED: 11/7/2018
REVISED:



Electrical and Programming Details For:		SR 2012 (Litchford Road) at Hunting Ridge Road and Rowland Road	
Prepared In the Offices of:		Division 5	Wake County
750 N. Greenfield Pkwy, Garner, NC 27529		PLAN DATE: November 2018	REVIEWED BY: T. Joyce
		PREPARED BY: C. Strickland	REVIEWED BY:
		REVISIONS	INIT. DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


SEAL	
	SEAL 031001 ENGINEER TODD JOYCE
DocuSigned by:	11/16/2018
SIG. INVENTORY NO.	05-1695

15-NOV-2018 10:43
 S:\IT\SS\115\Sig\01\work\hgr\oups\Sig_Maps\Trk\lch\051695_sml_e_xxx.dgn
 C:\STR\lckland

1-18 STATE OF NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH, N.C.

ENGLISH STANDARD DRAWING FOR
ELECTRICAL SERVICE GROUNDING
GROUNDING AND BONDING


SHEET 1 OF 1
1700D01



1-18 STATE OF NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH, N.C.

ENGLISH STANDARD DRAWING FOR
WOOD POLES
METHODS OF ATTACHMENT AND GROUNDING

SHEET 1 OF 1
1720D01





DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED





See Plate for Title

<p>Prepared in the Offices of:</p> <p>750 N. Greenfield Parkway Garner, NC 27529</p>	<p>SEAL</p> <p>DocuSigned by: <i>Mohd Aslami</i> 10/11/2017</p>
--	---

11-0CT-2017_08:56
U:\2018_S14_Drawing\Plate_Sheets\2018_Plate_Sheet.dgn
r:\rough



- NOTES:**
- CAST FOUNDATION AGAINST UNDISTURBED SOIL WHEREVER CONDITIONS PERMIT. IN UNSTABLE SOIL, CAST-IN-PLACE TUBE FORMS ARE ALLOWED WITH APPROVAL.
 - COMPLY WITH APPLICABLE PROVISIONS OF SECTION 825 FOR CONCRETE CONSTRUCTION.
 - USE CLASS "A" CONCRETE THAT MEETS THE REQUIREMENTS OF SECTION 1000 WITH A COMPRESSION STRENGTH AT 28 DAYS OF $F'c = 3000$ PSI (MIN.).
 - USE ASTM GRADE 60 DEFORMED BARS FOR ALL REINFORCING STEEL.
 - GRADE IS ASSUMED TO BE (8H:1V) OR FLATTER. FOUNDATION SIZE AND DEPTHS ARE BASED ON THE FOLLOWING SOIL DESIGN PARAMETERS:
 - A. SANDY TYPE SOIL
 - B. NO GROUND WATER WITHIN 5'-0" OF SURFACE ELEVATION
 - C. WIND SPEED NOT TO EXCEED 140 MPH
 IF ACTUAL CONDITIONS VARY SUBSTANTIALLY FROM THOSE ASSUMED, THE FOUNDATION DEPTH MAY BE ADJUSTED. IN THIS CASE, CONTACT THE ENGINEER.
 - MAINTAIN AT LEAST 3" COVER ON ALL REINFORCEMENT.
 - ORIENT CONDUIT AS REQUIRED BY THE DESIGN OR AS DICTATED BY FIELD CONDITIONS.
 - USE ADHESIVE ANCHOR FOR THREADED COUPLING INSERT. FOR TYPE I MINIMUM DEPTH NECESSARY IS 0'-4 1/2" AND FOR TYPE II MINIMUM DEPTH NECESSARY IS 0'-6 5/8". FOLLOW MANUFACTURER'S INSTALLATION INSTRUCTIONS.



PEDESTAL FOUNDATION TYPE AND SIZE							
TYPE	PEDESTAL DESCRIPTION	SIZE			ANCHOR BOLT		INSTALL GROUNDING SYSTEM (YES/NO)
		DIAMETER "A" FT	DEPTH "B" FT	CONCRETE VOLUME CY	DIAMETER (MIN.) IN	LENGTH FT-IN	
I	PEDESTRIAN PUSHBUTTON	2'-0"	3'-6"	.41	1/2	1'-6"	NO
II	NORMAL-DUTY	2'-0"	5'-0"	.58	3/4	2'-0"	YES
III	HEAVY-DUTY	2'-6"	7'-0"	1.27	1	4'-0"	YES



REINFORCING STEEL SCHEDULE													
TYPE	V-BAR				STIRRUP								
	SIZE #	QTY	LENGTH	WEIGHT LBS	SIZE #	QUANTITY			LENGTH	DIAMETER "C" FT	OVERLAP MIN.	WEIGHT LBS	TOTAL STEEL WEIGHT LBS
						VERTICAL ON 6" CENTERS	ON 12" CENTERS	TOTAL					
I	8	6	3'-0"	56	4	0	4	4	5'-7"	1'-6"	0'-10"	15	71
II	8	6	4'-6"	86	4	5	3	8	5'-7"	1'-6"	0'-10"	30	116
III	8	6	6'-6"	122	4	7	4	11	7'-2"	2'-0"	0'-10"	53	175

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH STANDARD DRAWING FOR
PEDESTALS
FOUNDATIONS

SHEET 1 OF 1
1743D01

See Plate for Title



DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

11-10CT-2017_08x03
11-2018_S14 Drawings#Plate_Sheets#2018_Plate_Sheet - .dgn
r:\rough

- 1 INSTALL REA, PE - 22, SHIELDED, TWISTED PAIR COMMUNICATIONS CABLE
- 2 INSTALL COAX CABLE
- 3 INSTALL ETHERNET CABLE
- 4 INSTALL SMFO CABLE
- 5 INSTALL MMFO CABLE
- 6 INSTALL FIBER OPTIC DROP CABLE
- 7 INSTALL TRACER WIRE
- 8 TRENCH
- 9 INSTALL PVC CONDUIT
- 10 INSTALL RIGID, GALVANIZED STEEL CONDUIT
- 11 INSTALL RIGID, GALVANIZED STEEL RISER WITH WEATHERHEAD
- 12 INSTALL RIGID, GALVANIZED STEEL RISER WITH FIBER OPTIC CABLE SEAL
- 13 INSTALL OUTER-DUCT POLYETHYLENE CONDUIT
- 14 INSTALL POLYETHYLENE CONDUIT
- 15 DIRECTIONAL DRILL CONDUIT
- 16 BORE AND JACK CONDUIT
- 17 INSTALL CABLE(S) IN EXISTING CONDUIT
- 18 INSTALL CABLE(S) IN NEW CONDUIT
- 19 INSTALL CABLE(S) IN EXISTING RISER
- 20 INSTALL CABLE(S) IN NEW RISER
- 21 INSTALL CABLE(S) IN EXISTING CONDUIT STUB-OUTS
- 22 INSTALL NEW CONDUIT INTO EXISTING CABINET BASE (USE EXISTING CONDUIT STUB-OUTS WHEN AVAILABLE)
- 23 INSTALL NEW RISER INTO EXISTING CABINET BASE (USE EXISTING CONDUIT STUB-OUTS WHEN AVAILABLE)
- 24 INSTALL NEW CONDUIT INTO EXISTING POLE MOUNTED CABINET
- 25 INSTALL NEW RISER INTO EXISTING POLE MOUNTED CABINET
- 26 MODIFY EXISTING INTERCONNECT CENTER /SPLICE ENCLOSURE
- 27 INSTALL NEW FIBER OPTIC TRANSCEIVER
- 28 INSTALL INTERCONNECT CENTER, PATCH PANEL, JUMPERS AND FUSION SPLICE CABLE IN CABINET
- 29 INSTALL UNDERGROUND SPLICE ENCLOSURE
- 30 INSTALL AERIAL SPLICE ENCLOSURE
- 31 INSTALL POLE MOUNTED SPLICE CABINET
- 32 INSTALL BASE MOUNTED SPLICE CABINET
- 33 REMOVE EXISTING SPLICE CABINET

- 34 INSTALL CABINET FOUNDATION
- 35 INSTALL CCTV CAMERA POLE MOUNTED CABINET
- 36 INSTALL CCTV CAMERA ASSEMBLY
- 37 INSTALL CCTV CAMERA WOOD POLE
- 38 INSTALL CCTV CAMERA METAL POLE AND FOUNDATION
- 39 INSTALL JUNCTION BOX
- 40A INSTALL OVERSIZED JUNCTION BOX
- 40B INSTALL SPECIAL OVERSIZED JUNCTION BOX (36" x 36" x 24")
- 41 REMOVE EXISTING JUNCTION BOX
- 42 INSTALL WOOD POLE
- 43 REMOVE EXISTING WOOD POLE
- 44 INSTALL AERIAL GUY ASSEMBLY
- 45 INSTALL STANDARD GUY ASSEMBLY
- 46 INSTALL SIDEWALK GUY ASSEMBLY
- 47 INSTALL MESSENGER CABLE
- 48A REMOVE EXISTING COMMUNICATIONS AND MESSENGER CABLE
- 48B REMOVE EXISTING COMMUNICATIONS CABLE
- 49 BACK PULL EXISTING COMMUNICATIONS CABLE
- 50 INSTALL TELEPHONE SERVICE
- 51 INSTALL CABLE STORAGE RACKS (SNOW SHOES) AND STORE 100 FEET OF CABLE
- 52A INSTALL DELINEATOR MARKER
- 52B INSTALL JUNCTION BOX MARKER
- 53 STORE 20 FEET OF COMMUNICATIONS CABLE
- 54 LASH CABLE(S) TO EXISTING COMMUNICATIONS CABLE
- 55 LASH CABLE(S) TO EXISTING MESSENGER CABLE
- 56 LASH CABLE(S) TO NEW MESSENGER CABLE
- 57 MODIFY EXISTING ELECTRICAL SERVICE
- 58 INSTALL NEW ELECTRICAL SERVICE
- 59 INSTALL NEW ETHERNET EDGE SWITCH
- 60 BOND TRACER WIRE TO EQUIPMENT GROUND BUS
DO NOT BOND TRACER WIRE TO EQUIPMENT GROUND BUS
- 61 BOND RISER AND MESSENGER CABLE TO POLE GROUND
- 62 BOND RISER TO POLE GROUND
- 63 BOND MESSENGER CABLE TO POLE GROUND
- 64 INSTALL HEAT SHRINK TUBING RETROFIT KIT
- 65 INSTALL MOLDABLE DUCT SEAL
- 66 SLACK SPAN

LEGEND

	NEW FIBER OPTIC COMMUNICATIONS CABLE		NEW CABLE STORAGE RACKS (SNOW SHOES)
	NEW TWISTED PAIR COMMUNICATIONS CABLE		EXISTING CABLE STORAGE RACK (SNOW SHOE)
	EXISTING COMMUNICATIONS CABLE		EXISTING CONTROLLER AND CABINET
	EXISTING COMMUNICATIONS CABLE TO BE REMOVED		NEW CCTV CABINET
	NEW AERIAL GUY ASSEMBLY		EXISTING SPLICE CABINET
	NEW CONDUIT		NEW SPLICE CABINET
	EXISTING CONDUIT		SP
	NEW DIRECTIONAL DRILLED CONDUIT		SIGNAL POLE
	NEW BORED AND JACKED CONDUIT		FLAT PANEL ANTENNA (SINGLE)
	NEW JUNCTION BOX		YAGI ANTENNA (DOUBLE) FOR REPEATER OPERATION
	EXISTING JUNCTION BOX		YAGI ANTENNA (SINGLE)
	NEW WOOD POLE		OMNI ANTENNA
	EXISTING WOOD POLE		
	AERIAL SPLICE ENCLOSURE		
	UNDERGROUND SPLICE ENCLOSURE		
	NEW METAL POLE		
	EXISTING METAL POLE		
	NEW CCTV ASSEMBLY		
	NEW STANDARD GUY ASSEMBLY		
	NEW SIDEWALK GUY ASSEMBLY		
	SIGNAL INVENTORY NUMBER		

CONSTRUCTION NOTE SYMBOLOGY KEY

- INDICATES NUMBER OF CABLES, LOOPS, ETC.
- INDICATES NUMBER OF FIBERS PER CABLE, TWISTED PAIRS PER CABLE, ETC.
- INDICATES NUMBER OF RISER(S)/CONDUIT(S)
- INDICATES DIAMETER OF RISER(S)/CONDUIT(S) (INCH)

NUMBER OF CABLE(S) NUMBER OF FIBERS/TWISTED PAIRS

NEW/EXISTING CABLE
REMOVE/MODIFY CABLE
CONDUIT/RISER

NUMBER OF RISER(S)/CONDUIT(S) DIAMETER OF RISER(S)/CONDUIT(S) (INCH)

ATTACHMENT POINT:

DISTANCE ABOVE (IN)/ATTACHMENT POINT REFERENCE POINT

REFERENCE POINT DISTANCE BELOW (IN)/ATTACHMENT POINT


"SS" REFERENCE LOCATION

FS = FRONT SIDE OF POLE
BS = BACK SIDE OF POLE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	<p>CONSTRUCTION NOTES</p>		<p>SEAL</p>
	<p>DIVISION 05 WAKE COUNTY RALEIGH</p> <p>PLAN DATE: NOVEMBER 2018 REVIEWED BY: <i>Greg Green</i></p> <p>PREPARED BY: A. J. SKUCE</p>	<p>INIT. DATE</p>	


* - PRETERMINATED DROP CABLE



- 1) FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE CITY OF RALEIGH SENIOR TRANSPORTATION ENGINEER, JED NIFFENEGGER, AT 919-996-4039 TO ARRANGE FOR THE CITY TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR TRANSPORTATION ENGINEER AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND OPERATIONAL
- 2) CONTRACTOR TO RECORD EXISTING SPLICE ARRANGEMENT FOR COMPARISON TO THE SUPPLIED SPLICE DETAILS. IF DISCREPANCIES EXIST, CONTACT THE ENGINEER TO DETERMINE HOW TO PROCEED WITH RESPLICING. PROVIDE AS-BUILT PLANS TO THE ENGINEER IF FINAL SPLICE ARRANGEMENT DIFFERS FROM THE SUPPLIED SPLICE DETAILS.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	COMMUNICATIONS CABLE AND CONDUIT ROUTING PLANS		SEAL NORTH CAROLINA PROFESSIONAL ENGINEER M. A. ASLAMI License No. 032108 11/7/2018
	DIVISION 05 WAKE COUNTY RALEIGH PLAN DATE: NOVEMBER 2018 PREPARED BY: A. J. SKUCE REVIEWED BY: <i>Greg Green</i>	REVISIONS: _____ INIT: _____ DATE: _____ _____ _____	
Prepared in the Offices of: 750 N. Greenfield Pkwy., Garner, NC 27529	SCALE: 1" = 60' 		



- 1) FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE CITY OF RALEIGH SENIOR TRANSPORTATION ENGINEER, JED NIFFENEGGER, AT 919-996-4039 TO ARRANGE FOR THE CITY TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR TRANSPORTATION ENGINEER AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND OPERATIONAL

- 2) CONTRACTOR TO RECORD EXISTING SPLICE ARRANGEMENT FOR COMPARISON TO THE SUPPLIED SPLICE DETAILS. IF DISCREPANCIES EXIST, CONTACT THE ENGINEER TO DETERMINE HOW TO PROCEED WITH RESPLICING. PROVIDE AS-BUILT PLANS TO THE ENGINEER IF FINAL SPLICE ARRANGEMENT DIFFERS FROM THE SUPPLIED SPLICE DETAILS.

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

	COMMUNICATIONS CABLE AND CONDUIT ROUTING PLANS		SEAL
	DIVISION 05 WAKE COUNTY RALEIGH PLAN DATE: NOVEMBER 2018 REVIEWED BY: <i>Greg Green</i> PREPARED BY: A. J. SKUCE		DocuSigned by: <i>Mohd A. Aslami</i> 11/7/2018
	REVISIONS INIT. DATE	DATE	DATE

MATCHLINE A

CONSTITUTION DR.

NICHOLS RD.



NEW UNDERGROUND SPlice ENCLOSURE
LITCHFORD RD. AT HUNTING RIDGE RD.
SIG. INV. # 05-1695

Notes:
Unused fibers left coiled and stored in splice tray.
Unused Buffer Tubes left coiled and stored in splice tray.
UGSE – Under Ground Splice Enclosure
ASE – Aerial Splice Enclosure

COLOR CODE
TIA/EIA 598-A

(1) BLUE	(7) RED
(2) ORANGE	(8) BLACK
(3) GREEN	(9) YELLOW
(4) BROWN	(10) VIOLET
(5) SLATE	(11) ROSE
(6) WHITE	(12) AQUA

LEGEND
X = FUSION SPlice
C = CAP IN TRAY




EXISTING AERIAL SPlice ENCLOSURE
LITCHFORD RD. AT GRESHAM LAKE RD.
SIG. INV. # 05-1535

Notes:
Unused fibers left coiled and stored in splice tray.
Unused Buffer Tubes left coiled and stored in splice tray.
UGSE – Under Ground Splice Enclosure
ASE – Aerial Splice Enclosure

COLOR CODE
TIA/EIA 598-A

(1) BLUE	(7) RED
(2) ORANGE	(8) BLACK
(3) GREEN	(9) YELLOW
(4) BROWN	(10) VIOLET
(5) SLATE	(11) ROSE
(6) WHITE	(12) AQUA

LEGEND
X = FUSION SPlice
C = CAP IN TRAY



- 1) FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE CITY OF RALEIGH SENIOR TRANSPORTATION ENGINEER, JED NIFFENEGGER, AT 919-996-4039 TO ARRANGE FOR THE CITY TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR TRANSPORTATION ENGINEER AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND OPERATIONAL.
- 2) CONTRACTOR TO RECORD EXISTING SPlice ARRANGEMENT FOR COMPARISON TO THE SUPPLIED SPlice DETAILS. IF DISCREPANCIES EXIST, CONTACT THE ENGINEER TO DETERMINE HOW TO PROCEED WITH RESPLICING. PROVIDE AS-BUILT PLANS TO THE ENGINEER IF FINAL SPlice ARRANGEMENT DIFFERS FROM THE SUPPLIED SPlice DETAILS.
- 3) ETHERNET SWITCH TERMINATION CONFIGURATIONS ARE GENERIC. CONTRACTOR IS RESPONSIBLE FOR DETERMINING \ ENSURING PROPER TERMINATIONS.
- 4) INCLUDE ON THE COVER OF EACH SPlice TRAY THE FOLLOWING:
REFERENCE SECTION 1731 "FIBER OPTIC SPlice ENCLOSURE"
 - 1) SPlice LOCATION
 - 2) DATE
 - 3) COMPANY NAME
 - 4) NAME OF INDIVIDUAL PERFORMING THE SPlicing


PRIOR TO INSTALLING THE COVER ON THE SPlice TRAY TAKE A DIGITAL PHOTOGRAPH SHOWING THE SPlice TRAY AND INFORMATION SHOWN ABOVE (1-4) AND SUBMIT PHOTOGRAPH ALONG WITH OTDR TEST RESULTS.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	SPlice DETAIL		
	DIVISION 05 WAKE COUNTY RALEIGH PLAN DATE: NOVEMBER 2018 REVIEWED BY: <i>Greg Green</i> PREPARED BY: A. J. SKUCE	REVISIONS: _____ INIT: _____ DATE: _____ DocuSigned by: <i>Mohd A. Aslami</i> 11/7/2018	



- Project Notes**
1. Refer to "NCDOT January 2018 Roadway Standard Drawings" and "NCDOT Standard Specifications for Roads and Structures January 2018"
 2. Remove all markings noted with an "X".
 3. Install W3-3 "Signal Ahead" signs for both intersection approaches on SR 2012 (Litchford Rd). When existing terrain permits, locate these signs at least 250' in advance of the stop bar. Otherwise choose the best location available in the field. The supplemental "Street Name" plaques will be furnished by the City of Raleigh.
 4. Remove R1-1 "Stop" signs once signal is in operation.



PAVEMENT MARKING SCHEDULE

SYMBOL	DESCRIPTION	PAY ITEM	QUANTITY
T2	WHITE STOPBAR	THERMOPLASTIC (24", 120 MIL)	110 LF
T3	WHITE CROSSWALK LINE	THERMOPLASTIC (8", 120 MIL)	150 LF
TE	WHITE LANE LINE	THERMOPLASTIC (4", 120 MIL)	15 LF

LITCHFORD RD (SR 2012) AND HUNTING RIDGE RD / ROWLAND RD RALEIGH, WAKE COUNTY, NC PAVEMENT MARKING / SIGN PLACEMENT PLAN			
DIVISION 05 WAKE COUNTY			
REVISIONS	NO.	DATE	
N.C. DEPARTMENT of TRANSPORTATION DIVISION of HIGHWAYS DIVISION FIVE TRAFFIC ENGINEERING			SCALE: 60' = 1" DATE: 27 FEB 2015 PREPARED BY: SJL REVIEWED BY: JES REVISION BY: