DocuSign Envelope ID: D6FA97DC-F53A-4D98-83BC-4EE26B9BBC23

PROJECT REFERENCE	SHEET NO.
B-5682 – GRANVILLE 129	2A-1

ROADWAY DESIGN ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 21102 ENGINEER TIMOTHY JOHNSON

DocuSigned by: Timothy Johnson
4/12/2018

MOTT MACDONALD I & E, LLC
LICENSE NO. F-0669

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Prepared in the Office of:

MOTT MACDONALD
PO Box 700
Fuquay-Varina, NC 27526
www.mottmac.com



TYPICAL SECTION NO. 1

TRANSITION FROM EXISTING TO TYPICAL SECTION NO. 1:
–L– STA 11+00.00 TO 11+50.00

USE TYPICAL SECTION NO. 1:
–L– STA 11+50.00 TO 14+08.84 (BEGIN BRIDGE)
–L– STA 15+01.17 (END BRIDGE) TO 16+50.00

TRANSITION FROM TYPICAL SECTION NO. 1 TO EXISTING:
–L– STA 16+50.00 TO 17+00.00



DETAIL FOR FULL DEPTH PAVED SHOULDER IN CONJUNCTION WITH GUARDRAIL



DETAIL FOR SHOULDER BERM GUTTER IN CONJUNCTION WITH GUARDRAIL

–L– STA 13+78.00 TO 13+93.91 RT
–L– STA 13+78.00 TO 14+02.09 LT



TYPICAL SECTION NO. 2

USE TYPICAL SECTION NO. 2:
–L– STA 14+08.84 (BEGIN BRIDGE) TO 15+01.17 (END BRIDGE)

NOTE: SEE STRUCTURE PLANS FOR PAVEMENT DEPTHS ON STRUCTURE

PAVEMENT SCHEDULE	
C	PROP. APPROX. 3″ ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
C1	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1″ DEPTH. TO BE PLACED IN LAYERS NOT GREATER THAN 2″ IN DEPTH.
D	PROP. APPROX. 4″ ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
E	PROP. APPROX. 4″ ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
R	SHOULDER BERM GUTTER.
T	EARTH MATERIAL.

NOTE: PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.

4/12/2018 1:43:59 PM
R:\Roadway\Proj\B-5682_rdy_typ.dgn
jor66165