DocuSign Envelope ID: 42E4E6EC-4E81-4CAF-ADF8-826965C6977F

TIP NO.	SHEET NO.
DF16905.2091011	PMP-1A

APPROVED: Matthew V. Springer
DATE: 8/30/2019
DocuSign Envelope ID: BC60F6E8B584403...

SEAL
NORTH CAROLINA PROFESSIONAL SEAL 042546 ENGINEER MATTHEW V. SPRINGER

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

8-19

ENGLISH DETAIL DRAWING FOR
PAVEMENT MARKINGS
BRIDGES

STANDARD BRIDGE

CLEAR ROADWAY WIDTH > 25 FT.

NARROW BRIDGE

18 FT. ≥ CLEAR ROADWAY WIDTH ≤ 25 FT.

ONE-LANE BRIDGE

CLEAR ROADWAY WIDTH < 18 FT.

GENERAL NOTES:

1- NO PASSING ZONES SHOWN ARE MINIMUMS. APPLY MINIMUM PASSING AND STOPPING SIGHT DISTANCES AS DETERMINED BY THE ENGINEER.

2- FOR BRIDGES WITH 18 TO 25 FEET CLEAR ROADWAY WIDTH, SIGNS MUST BE USED WHEN THE APPROACH PAVEMENT WIDTH IS 2 FOOT OR GREATER THAN THE CLEAR ROADWAY WIDTH.

LEGEND

- DIRECTION OF TRAFFIC FLOW
- STATIONARY SIGN
- YELLOW/YELLOW PAVEMENT MARKER
- CRYSTAL/CRYSTAL PAVEMENT MARKER

SHEET 1 OF 1
1205D12

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

8-19

ENGLISH DETAIL DRAWING FOR
PAVEMENT MARKINGS
BRIDGES

SHEET 1 OF 1
1205D12

REVISED PAVEMENT MARKING ROADWAY STANDARD DRAWING

08/30/19
S:\S&DU\Standards Group\Standards and Drawings\Drawings\2018 Standard Dwgs\Division 12 Final\1205\20L-08-29-19.dgn
UserRdstokes