

FINAL PHASE



BEGIN TIP PROJECT HS-20050
BEGIN CONSTRUCTION
-Y- POT STA 11+31.00

SEED, AND MULCH
HATCHED AREAS
IN ACCORDANCE WITH
SECTION 1660 OF
NCDOT STANDARD SPECIFICATIONS

INSTALL COIR FIBER WATTLE
BARRIER BETWEEN REMOVED
PAVEMENT AND EXISTING
S & G PARKING

CUR DATA -Y-
Plc 12+30.76
 $\Delta c = 35^\circ 51' 32.9''$ (RT)
D = 45°50'11.8"
Lc = 78.23'
Tc = 40.45'
R = 125'

CUR DATA -L-
Plc 11+83.16
 $\Delta c = 11^\circ 22' 09.3''$ (RT)
D = 03°06'50.0"
Lc = 365.11'
Tc = 183.16'
R = 1,840'

CUR DATA -L-
Plc 15+46.22
 $\Delta c = 09^\circ 30' 49.9''$ (RT)
D = 02°46'52.9"
Lc = 342.06'
Tc = 171.42'
R = 2,060'

END TIP PROJECT HS-20050
END CONSTRUCTION
-Y- POT STA 13+10.00

PAVEMENT REMOVAL

