

**TIP PROJECT: W-5206AF**


**CONTRACT: DF00106**

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

**CUMBERLAND COUNTY**


**LOCATION: CLIFFDALE ROAD (SR 1400) AT McPHERSON  
CHURCH ROAD**

**TYPE OF WORK: WIDENING, GRADING, PAVING, SIGNAL REVISION  
AND PAVEMENT MARKINGS**




VICINITY MAP


**BEGIN STATE PROJECT W-5206AF  
-L- STA 11+75.00**



STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	W-5206AF	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
45336.1.FD32	HSIP-1400(9)	P.E.	
45336.2.FD32	HSIP-1400(9)	ROW, UTILS	
45336.3.32	HSIP-1400(9)	CONSTR	



**GRAPHIC SCALES**



**DESIGN DATA**

ADT 19000 = 2012  
ADT 33500 = 2032  
V = 50 MPH

**PROJECT LENGTH**

TOTAL LENGTH OF STATE PROJECT W-5206AF = 0.113mi

Prepared in the Office of:  
**DIVISION OF HIGHWAYS**  
431 Transportation Drive Fayetteville, NC 28301


**2012 STANDARD SPECIFICATIONS**

**RIGHT OF WAY DATE:**  
SEPTEMBER 30, 2014

**LETTING DATE:**  
SEPTEMBER 16, 2015

**SEAN MATUSZEWSKI**  
PROJECT ENGINEER

**NEIL BUTLER**  
PROJECT DESIGN ENGINEER



# STATE OF NORTH CAROLINA, DIVISION OF HIGHWAYS CONVENTIONAL PLAN SHEET SYMBOLS

Note: Not to Scale \*S.U.E. = Subsurface Utility Engineering

### BOUNDARIES AND PROPERTY:

State Line	-----
County Line	-----
Township Line	-----
City Line	-----
Reservation Line	-----
Property Line	-----
Existing Iron Pin	○ EIP
Property Corner	----->
Property Monument	□ EDM
Parcel/Sequence Number	⑫③
Existing Fence Line	-x-x-x-
Proposed Woven Wire Fence	○
Proposed Chain Link Fence	□
Proposed Barbed Wire Fence	◇
Existing Wetland Boundary	----- WLB
Proposed Wetland Boundary	----- WLB
Existing Endangered Animal Boundary	----- EAB
Existing Endangered Plant Boundary	----- EPB
Existing Historic Property Boundary	----- HPB
Known Contamination Area: Soil	-----
Potential Contamination Area: Soil	-----
Known Contamination Area: Water	-----
Potential Contamination Area: Water	-----
Contaminated Site: Known or Potential	☠ ?

### BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	○
Sign	○ S
Well	○ W
Small Mine	✕
Foundation	□
Area Outline	□
Cemetery	□
Building	□
School	□
Church	□
Dam	□

### HYDROLOGY:

Stream or Body of Water	-----
Hydro, Pool or Reservoir	□
Jurisdictional Stream	----- JS
Buffer Zone 1	----- BZ 1
Buffer Zone 2	----- BZ 2
Flow Arrow	←
Disappearing Stream	----->
Spring	○
Wetland	-----
Proposed Lateral, Tail, Head Ditch	----- FLOW
False Sump	▽

### RAILROADS:

Standard Gauge	-----
RR Signal Milepost	○ CSX TRANSPORTATION MILEPOST 35
Switch	□ SWITCH
RR Abandoned	-----
RR Dismantled	-----

### RIGHT OF WAY:

Baseline Control Point	◆
Existing Right of Way Marker	△
Existing Right of Way Line	-----
Proposed Right of Way Line	----- RW
Proposed Right of Way Line with Iron Pin and Cap Marker	----- RW ▲
Proposed Right of Way Line with Concrete or Granite R/W Marker	----- RW ▲
Proposed Control of Access Line with Concrete CA Marker	----- CA
Existing Control of Access	----- CA
Proposed Control of Access	----- CA
Existing Easement Line	----- E
Proposed Temporary Construction Easement	----- E
Proposed Temporary Drainage Easement	----- TDE
Proposed Permanent Drainage Easement	----- PDE
Proposed Permanent Drainage / Utility Easement	----- DUE
Proposed Permanent Utility Easement	----- PUE
Proposed Temporary Utility Easement	----- TUE
Proposed Aerial Utility Easement	----- AUE
Proposed Permanent Easement with Iron Pin and Cap Marker	◆

### ROADS AND RELATED FEATURES:

Existing Edge of Pavement	-----
Existing Curb	-----
Proposed Slope Stakes Cut	----- C
Proposed Slope Stakes Fill	----- F
Proposed Curb Ramp	----- CR
Existing Metal Guardrail	-----
Proposed Guardrail	-----
Existing Cable Guiderail	-----
Proposed Cable Guiderail	-----
Equality Symbol	⊕
Pavement Removal	▣

### VEGETATION:

Single Tree	☼
Single Shrub	☼
Hedge	-----
Woods Line	-----

Orchard	☼ ☼ ☼ ☼
Vineyard	□ Vineyard

### EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	----- CONC
Bridge Wing Wall, Head Wall and End Wall	----- CONC WW
MINOR:	
Head and End Wall	----- CONC HW
Pipe Culvert	-----
Footbridge	-----
Drainage Box: Catch Basin, DI or JB	□ CB
Paved Ditch Gutter	-----
Storm Sewer Manhole	○ S
Storm Sewer	----- S

### UTILITIES:

POWER:	
Existing Power Pole	●
Proposed Power Pole	○
Existing Joint Use Pole	●
Proposed Joint Use Pole	○
Power Manhole	⊕
Power Line Tower	⊠
Power Transformer	⊠
U/G Power Cable Hand Hole	●
H-Frame Pole	●
U/G Power Line LOS B (S.U.E.*)	----- P
U/G Power Line LOS C (S.U.E.*)	----- P
U/G Power Line LOS D (S.U.E.*)	----- P

### TELEPHONE:

Existing Telephone Pole	●
Proposed Telephone Pole	○
Telephone Manhole	⊕
Telephone Pedestal	⊠
Telephone Cell Tower	⊠
U/G Telephone Cable Hand Hole	●
U/G Telephone Cable LOS B (S.U.E.*)	----- T
U/G Telephone Cable LOS C (S.U.E.*)	----- T
U/G Telephone Cable LOS D (S.U.E.*)	----- T
U/G Telephone Conduit LOS B (S.U.E.*)	----- TC
U/G Telephone Conduit LOS C (S.U.E.*)	----- TC
U/G Telephone Conduit LOS D (S.U.E.*)	----- TC
U/G Fiber Optics Cable LOS B (S.U.E.*)	----- T FO
U/G Fiber Optics Cable LOS C (S.U.E.*)	----- T FO
U/G Fiber Optics Cable LOS D (S.U.E.*)	----- T FO

### WATER:

Water Manhole	⊕
Water Meter	○
Water Valve	⊗
Water Hydrant	⊕
U/G Water Line LOS B (S.U.E.*)	----- W
U/G Water Line LOS C (S.U.E.*)	----- W
U/G Water Line LOS D (S.U.E.*)	----- W
Above Ground Water Line	----- A/G Water

### TV:

TV Pedestal	⊠
TV Tower	⊗
U/G TV Cable Hand Hole	●
U/G TV Cable LOS B (S.U.E.*)	----- TV
U/G TV Cable LOS C (S.U.E.*)	----- TV
U/G TV Cable LOS D (S.U.E.*)	----- TV
U/G Fiber Optic Cable LOS B (S.U.E.*)	----- TV FO
U/G Fiber Optic Cable LOS C (S.U.E.*)	----- TV FO
U/G Fiber Optic Cable LOS D (S.U.E.*)	----- TV FO

### GAS:


Gas Valve	◇
Gas Meter	⊕
U/G Gas Line LOS B (S.U.E.*)	----- G
U/G Gas Line LOS C (S.U.E.*)	----- G
U/G Gas Line LOS D (S.U.E.*)	----- G
Above Ground Gas Line	----- A/G Gas

### SANITARY SEWER:


Sanitary Sewer Manhole	⊕
Sanitary Sewer Cleanout	⊕
U/G Sanitary Sewer Line	----- SS
Above Ground Sanitary Sewer	----- A/G Sanitary Sewer
SS Forced Main Line LOS B (S.U.E.*)	----- FSS
SS Forced Main Line LOS C (S.U.E.*)	----- FSS
SS Forced Main Line LOS D (S.U.E.*)	----- FSS

### MISCELLANEOUS:

Utility Pole	●
Utility Pole with Base	□
Utility Located Object	○
Utility Traffic Signal Box	⊠
Utility Unknown U/G Line LOS B (S.U.E.*)	----- ?UTL
U/G Tank; Water, Gas, Oil	□
Underground Storage Tank, Approx. Loc.	⊕
A/G Tank; Water, Gas, Oil	□
Geoenvironmental Boring	⊕
U/G Test Hole LOS A (S.U.E.*)	●
Abandoned According to Utility Records	AATUR
End of Information	E.O.I.



**TYPICAL SECTION NO. 1**  
-L- STA. 11+75.00 TO STA 16+30.00





**TYPICAL SECTION NO. 2**  
-Y- STA. 13+35.00 TO STA 15+45.00

**NOTES TO CONTRACTOR**

For surface mixes over 1" in thickness, mill the existing pavement in accordance with the following sketch as directed by the Engineer.

Locations shall include ties into existing concrete pavement, at bridge approaches where the bridge will not be resurfaced, and at the beginning and ending point of each resurfacing map.

Perform the work in accordance with Section 607 of the January 2012 North Carolina Department of Transportation Standard Specifications for Roads and Structures. Resurfacing will be accomplished at the same time as the milling operation.



**TYPICAL SECTION NO. 3**  
-Y- STA. 15+45.00 TO STA 18+70.00

PAVEMENT SCHEDULE	
C1	PROP. APPROX. 1½" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD.
C2	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
D1	PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
E1	PROP. APPROX. 3" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 342 LBS. PER SQ. YD.
R1	2' 6" CONCRETE CURB AND GUTTER
R2	EXISTING 2' 6" CONCRETE CURB AND GUTTER
R3	4" CONCRETE SIDEWALK
T	EARTH MATERIAL
U	EXISTING PAVEMENT
V	MILLING FOR CURB AND GUTTER TIE IN

**PROJECT NOTES**


- The Contractor shall not work on both sides of the road simultaneously within the same area.
- Ingress and egress shall be maintained to all businesses and dwellings on the project.
- At the end of each workday, the Contractor shall be required to backfill any area adjacent to existing travelway that has been graded leaving no more than a 1½" drop-off.
- A minimum of two-way, two-lane traffic (plus all existing left and right turn lanes) shall be maintained during periods of construction inactivity.
- The Contractor shall not be allowed to stop traffic for more than 5 minutes at a time in any one direction.
- During periods of construction inactivity, the difference in elevation between lanes shall not exceed 1-1/2 inch.
- Access to police and fire station, fire hydrants, and hospitals shall be maintained at all times.
- During periods of construction inactivity, place cones/drums 3' from existing edge of pavement (travelway) as directed by the Engineer.
- Channelizing devices in work areas shall be spaced not greater than 50' on center in tangent areas, 45' on center in tapers, and 10' on center in radii, and shall be set 3' off the edge of travelway, unless otherwise indicated on plans.
- Contractor to install Erosion Control devices as directed by the Engineer.
- Contractor shall coordinate with the Division Six Traffic Services Unit (910-486-1452) for placement of all pavement markings and signs.

6/2/09  
29 JUL 2015 11:27 AM W:\5206AF ClifFdale Rd at McPherson Church Rd\CumberLand Co\Roadway\p-rj\W5206AF\_Rdy\_typ.dgn



**BEGIN STATE PROJECT W-5206AF**  
**-L- STA 11+75.00**

**END STATE PROJECT W-5206AF**  
**-L- STA 18+00.00**



**DATUM DESCRIPTION**  
 THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCGS FOR MONUMENT "ACACIA"  
 WITH NAD 83/95 STATE PLANE GRID COORDINATES OF  
 NORTHING: 466066.280(±ft) EASTING: 1984258.880(±ft)  
 THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.9998727  
 THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "ACACIA" TO -L- STATION 12+00.00 IS  
 N 71°38'52.70" E 33,069.888(±ft)  
 ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES  
 VERTICAL DATUM USED IS NAVD 88

**BL-5**  
 N 477075.0908  
 E 2016099.8441  
 ELEV 219.19  
 -L- 20+53.15  
 15.80' LT

**BM #81**  
 -Y- STA 16+86.33  
 58.11' RT  
 ELEV 222.18

**BL-4**  
 N 476959.9232  
 E 2015681.1923  
 ELEV 219.78  
 -L- 16+19.19  
 18.73' LT

**BL-3**  
 N 476847.6450  
 E 2015356.3334  
 ELEV 221.75  
 -L- 16+42.28  
 40.68' LT

**BL-2**  
 N 476498.7142  
 E 2015596.0958  
 ELEV 223.53  
 -L- 12+18.38  
 31.43' LT

-Y-	-L-	-L-
PI Sta 13+17.77	PI Sta 18+75.69	PI Sta 15+89.28
$\Delta = 1' 12" 54.8" (RT)$	$\Delta = 0' 50" 44.1" (LT)$	$\Delta = 0' 54" 33.7" (LT)$
$D = 1' 00" 00.0"$	$D = 1' 00" 00.0"$	$D = 1' 00" 00.0"$
$L = 121.52'$	$L = 84.56'$	$L = 90.94'$
$T = 60.76'$	$T = 42.28'$	$T = 45.47'$
$R = 5,729.58'$	$R = 5,729.58'$	$R = 5,729.58'$

REVISIONS


8/17/99

31-001-2015 10+46 W-5206AF Cliffdale Rd at McPherson Church Rd.Cumberland Co.Roadway\proj\W5206AF\_Rdy.psh\_4.dgn  
 31-001-2015 10+46 W-5206AF Cliffdale Rd at McPherson Church Rd.Cumberland Co.Roadway\proj\W5206AF\_Rdy.psh\_4.dgn  
 31-001-2015 10+46 W-5206AF Cliffdale Rd at McPherson Church Rd.Cumberland Co.Roadway\proj\W5206AF\_Rdy.psh\_4.dgn

# STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

## STANDARD DRAWINGS FOR METAL POLES

**NCDOT METAL POLE STANDARDS**



<https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

Prepared In the Offices of:

750 N. Greenfield Pkwy, Garner, NC 27529

Designed in conformance with the latest 2012 Interim to the 5th Edition 2009 **AASHTO** Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals


INDEX OF PLANS	
DRAWING NUMBER	DESCRIPTION
M 1	Title Sheet
M 2	Fabrication Details - All Poles
M 3	Fabrication Details - Strain Poles
M 4,5	Fabrication Details - Mast Arm Poles
M 6	Construction Details - Strain Poles
M 7	Construction Details - Foundations
M 8,9	Standard Strain Pole Foundations

**NCDOT CONTACTS:**  
**MOBILITY AND SAFETY DIVISION - ITS AND SIGNALS UNIT**




**G. A. FULLER, P.E. - STATE ITS AND SIGNALS ENGINEER**  
**G. G. MURR, JR., P.E. - STATE SIGNALS ENGINEER**  
**D.C. SARKAR, P.E. - ITS AND SIGNALS SENIOR STRUCTURAL ENGINEER**  
**C.F. ANDREWS - ITS AND SIGNALS JOURNEY STRUCTURAL ENGINEER**

SEAL

8/26/2014  
DATE



**Terminal Compartment Detail**



MFG _____	MFG. DATE: MM/YY _____
SHAFT D/T/L/Y _____	
ARM-A D/T/L/Y _____	
ARM-B D/T/L/Y _____	
A.B. DIA./B.C./L/Y _____	
NCDOT STANDARD _____	

**Shaft I.D. Tag**  
(Provide on Strain Poles and Mast Arm Poles)

MFG _____	MFG. DATE: MM/YY _____
SECTION D/T/L/Y _____	
NCDOT STANDARD _____	

**Arm I.D. Tag**  
(Provide on each section of a multi-section mast arm)


- Notes:
- 1) D= Diameter, T= Thickness, L= Length, Y= Yield Strength
  - 2) A.B. = Anchor Bolt
  - 3) B.C. = Bolt Circle of Anchor Bolts
  - 4) If Custom Design, use "NCDOT STANDARD" line for pole I.D. number and Signal Inv. Number.
  - 5) See drawing M4 for mounting positions of I.D. tags.

**Identification Tag Details**


<p>750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p>Typical Fabrication Details Common To All Metal Poles</p>		
	<p>PLAN DATE: AUGUST 2013</p> <p>DESIGNED BY: C.F. ANDREWS</p> <p>PREPARED BY: N. BITTING</p> <p>REVIEWED BY: D.C. SARKAR</p>	<p>REVISIONS</p> <p>INIT. DATE</p>	

06-AUG-2014 08:55  
 S:\IT\5206AF\115\_Signal\Signal Design\Section\Eastern Region\M2\_Fab\_Details\All\_Poles.dgn  
 Top | Lowy


**Fabrication Details – All Poles**




Cable Entrances at Top of Pole



Section B-B  
Pole Base Plate  
(See drawing M2)




Radial Orientation for Factory Installed  
Accessories at Top of Pole



Socket Connection Weld Detail

2 Cable Clamps designed for variable attachment heights from 1'-6" to 10' below the top of the pole.









Monotube Strain Pole  
(.14"/Foot Taper)

	Typical Fabrication Details For Strain Poles		
	PLAN DATE: AUGUST 2013 PREPARED BY: N. BITTING	DESIGNED BY: C.F. ANDREWS REVIEWED BY: D.C. SARKAR	
SCALE: 0 NA NONE	REVISIONS: _____ INIT.: _____ DATE: _____	SIG. INVENTORY NO.	4486320147644

06-AUG-2014 09:51  
 S:\TCS\Signal Design Section\Eastern Region\MM Sheets\2012\_M3\_Fab\_Details\Strain Poles.dgn  
 Top View

**Fabrication Details – Strain Poles**








<p>Prepared In the Offices of: Signal Design Section 750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p>Typical Fabrication Details for Mast Arm Poles</p>		
	<p>PLAN DATE: AUGUST 2013</p>	<p>DESIGNED BY: C.F. ANDREWS</p>	
<p>SCALE: 0 NA NONE</p>	<p>PREPARED BY: N. BITTING</p>	<p>REVIEWED BY: D.C. SARKAR</p>	<p>SIG. INVENTORY NO.</p>

06-AUG-2014 08:50  
 S:\IT\5206AF\15\_Signal\Signal Design Section\Eastern Region\M4\_Fab\_Details\MastArms.dgn  
 J:\1110002

**Fabrication Details – Mast Arm Poles**

# Welded Ring Stiffened Mast Arm Connection



**Full-Penetration Groove Weld Detail**


**Notes:**

1. Provide a permanent means of identification above the mast arm to indicate proper attachment orientation of the mast arm.
2. Designer will determine the size of all structural components, plates, fasteners, and welds shown unless they are already specified.
3. Designer is responsible for providing appropriate drainage points.

	<p>Fabrication Details For Mast Arm Connection To Pole</p>		
	<p>PLAN DATE: AUGUST 2013</p>	<p>DESIGNED BY: C.F. ANDREWS</p>	
<p>SCALE: 0 NA NONE</p>	<p>PREPARED BY: N. BITTING</p>	<p>REVIEWED BY: D.C. SARKAR</p>	<p>INIT. DATE</p>
<p>750 N. Greenfield Pkwy, Garner, NC 27529</p>			<p>DocuSign by: D. C. Sarkar 8/26/2014</p>


06-10-2014 08:47  
 S:\Projects\2013\Signal Design\Section\Eastern Region\MM Sheets\2012\_M5\_Fab\_Details\MastArms.dgn  
 Topilowoy

**Fabrication Details – Mast Arm Poles**




### Strain Pole Attachments

Note: Strap all signal cables to the side of the pole with 3/4" stainless steel straps when the distance between the spanwire attachment clamp and the weatherheads exceeds 36"






### Attachment of Cable to Intermediate Metal Pole



### Metal Pole Grounding Detail

	<b>Construction Details Strain Poles</b>		
	PLAN DATE: AUGUST 2013 PREPARED BY: N. BITTING	REVIEWED BY: C.F. ANDREWS REVIEWED BY: D.C. SARKAR	
SCALE: 0 NA NONE	REVISIONS:	INIT. DATE:	8/26/2014 DATE:

### Reinforcing Steel Bars




Typical "C" Bars

REINFORCING STEEL TABLE FOR STANDARD DRILL PIER SHAFT (4'-0" DIAMETER)						
Shaft Dia (in.)	Conc. Volume (cu. yds.)	Bar Name	MIN.	Size	Type	Length
48"	.465 x L	V1	***	#8	STR.	**
		C	*	#4	CIR.	12'-6"


\* See Note No. 1  
 \*\* See Note No. 3  
 \*\*\* See Note No. 4

### Typical Foundation Anchor Bolt Details

(Reinforcing Cage Not Shown for Clarity)



### Typical Foundation Conduit Details



### Notes

- The number of C-bars is based on foundation depth and/or as required. For standard foundations, see sheets M 8 and M 9 for details.
- Circular tie reinforcing rings may be vertically adjusted by +/- 3" at a depth between 2'-0" and 3'-0" to facilitate the installation of electrical conduit entering in the cage.
- The length of V1-bars is based on foundation depth. For standard foundations, see sheets M 8 and M 9 for details. Vertical reinforcing bars (V1) may be horizontally adjusted by +/- 3" to facilitate the installation of electrical conduit entering into the cage.
- Provide vertical reinforcement as required per design. See sheets M 8 and M9 for details.

26-AUG-2014 08:44  
 S:\PROJECTS\115\SIGNAL\Signal Design Section\Eastern Region\M\_Sheets\2012\_M7\_Con\_Details\Foundations.dgn  
 J:\J110602

**Construction Details – Foundations**

	<b>Construction Details Foundations</b>	
	PLAN DATE: AUGUST 2013 PREPARED BY: N. BITTING	DESIGNED BY: K.C. DURIGON REVIEWED BY: D.C. SARKAR
SCALE: 0 NA NONE	REVISIONS: _____ INITI.: _____ DATE: _____	DocuSign by: <i>Dinesh C. Sarkar</i> 44EBE32E147E4CA 8/26/2014 DATE: _____ SIG. INVENTORY NO. _____

# SATURATED SOIL CONDITION

		STANDARD STRAIN POLES						STANDARD FOUNDATIONS 48" Diameter Drilled Pier Length (L) - Feet						Reinforcement				
		Case No.	Pole Height (Ft.)	Base Plate BC (In.)	Reactions at the Pole Base			Clay				Sand		Longitudinal		Stirrups		
					Axial (kip)	Shear (kip)	Moment (ft-kip)	Medium N-Value 4-8	Stiff N-Value 9-15	Very Stiff N-Value 16-30	Hard N-Value >30	Loose N-Value 4-10	Medium N-Value 11-30	Dense N-Value >30	Bar Size (#)	Quantity	Bar Size (#)	Spacing (in.)
WIND ZONE 1	LIGHT	S26L3	26	25	2	11	270	19	13	9	8	17	14.5	12.5	8	13	4	12
		S30L3	30	25	2	11	300	20	13.5	9	8	17.5	15	13	8	14	4	12
		S35L3	35	25	3	11	320	20	13.5	9.5	8	17.5	15	13	8	15	4	12
	HEAVY	S30H3	30	29	3	16	450	24.5	17	13	11	21	17.5	15	8	18	4	12
		S35H3	35	29	4	16	515	26	17.5	12	8.5	22	18.5	16	8	20	4	12
WIND ZONE 2	LIGHT	S26L2	26	23	2	10	245	18	12.5	8.5	8	16.5	14	12	8	13	4	12
		S30L2	30	23	2	10	270	19	12.5	9	8	16.5	14	12.5	8	13	4	12
		S35L2	35	23	3	10	300	19.5	13	9	8	17	14.5	13	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	25.5	15.5	11	8	20	17	14.5	8	17	4	12
		S35H2	35	29	4	15	475	25	16.5	11.5	8	21	17.5	15.5	8	19	4	12
WIND ZONE 3	LIGHT	S26L2	26	23	2	10	245	18	12.5	8.5	8	16.5	14	12	8	13	4	12
		S30L2	30	23	2	10	270	19	12.5	9	8	16.5	14	12.5	8	13	4	12
		S35L2	35	23	3	10	300	19.5	13	9	8	17	14.5	13	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	25.5	15.5	11	8	20	17	14.5	8	17	4	12
		S35H2	35	29	4	15	475	25	16.5	11.5	8	21	17.5	15.5	8	19	4	12
WIND ZONE 4	LIGHT	S26L1	26	22	2	8	190	16	11	8	8	15	12.5	11	8	12	4	12
		S30L1	30	22	2	8	205	16.5	11.5	8	8	15	13	11.5	8	12	4	12
		S35L1	35	22	3	8	230	17	12	8	8	15.5	13.5	11.5	8	12	4	12
	HEAVY	S30H1	30	25	3	12	320	20.5	14	9.5	8	18	15	13.5	8	15	4	12
		S35H1	35	25	4	12	350	21	14.5	10	8	18.5	15.5	13.5	8	16	4	12
WIND ZONE 5	LIGHT	S26L2	26	23	2	10	245	18	12.5	8.5	8	16.5	14	12	8	13	4	12
		S30L2	30	23	2	10	270	19	12.5	9	8	16.5	14	12.5	8	13	4	12
		S35L2	35	23	3	10	300	19.5	13	9	8	17	14.5	13	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	25.5	15.5	11	8	20	17	14.5	8	17	4	12
		S35H2	35	29	4	15	475	25	16.5	11.5	8	21	17.5	15.5	8	19	4	12

**Fabrication Design Notes:**

- Values shown in the "Reactions at the Pole Base" column represent the minimum acceptable capacity allowed for design using a design CSR of 1.00.
- Min. base plate thickness (T) is 2.0 inches.



**Foundation Selection:**

- Perform a standard penetration test at each proposed foundation site to determine "N" value.
- Select the appropriate wind zone from M 1 drawing.
- Select the soil type (Clay or Sand) that best describes the soil characteristics.
- Get the appropriate standard pole case number from the plans or from the Engineer.
- Select the appropriate column in the chart based on soil type and "N" value. Select the appropriate row based on the pole load case.  
The foundation depth is the value where the column and the row intersect.
- Reference Drilled Shafts: Construction Procedures and Design Methods, FHWA -IF-99-025

- S30H1 - Hard Clay-Stirrup Spacing: 6 in. c/c
- S30H2 - Hard Clay-Stirrup Spacing: 6 in. c/c
- S30H3 - Hard Clay-Stirrup Spacing: 6 in. c/c  
- Dense Sand-Stirrup Spacing: 6 in. c/c
- S35H1 - Hard Clay - Stirrup Spacing: 6 in. c/c
- S35H2 - Very Stiff Clay-Stirrup Spacing: 6 in. c/c  
- Hard Clay- Stirrup Spacing: 6 in. c/c  
- Dense Sand- Stirrup Spacing: 6 in. c/c
- S35H3 - Very Stiff Clay-Stirrup Spacing: 6 in. c/c  
- Dense Sand-Stirrup Spacing: 6 in. c/c

48" Dia. Foundations Concrete Volume (cubic yards) = (0.465) x Foundation Depth

26-MAR-2014 08:42 S:\TCS\115\Sig\Design\Section\Eastern Region\MM\_Sheets\2012\_M8\_Standard Foundations\_Wet.dgn J:\JL\JL

	<p><b>Standard Strain Pole Foundation for Saturated Soil Condition</b></p> <p>PLAN DATE: SEPTEMBER 2013    DESIGNED BY: C.B. COGDILL                  PREPARED BY: N. BITTING    REVIEWED BY: D. SARKAR</p>	
SCALE: 0 NA None	REVISIONS:    INIT.    DATE	DocuSigned by: Deborah C. Sarkar 3/26/2014 44EBE32E147E4C4...    DATE

Standard Strain Pole Foundation - Saturated Soil Condition

# DRY SOIL CONDITION

		STANDARD STRAIN POLES						STANDARD FOUNDATIONS 48" Diameter Drilled Pier Length (L) - Feet						Reinforcement				
		Case No.	Pole Height (Ft.)	Base Plate BC (In.)	Reactions at the Pole Base			Clay				Sand			Longitudinal		Stirrups	
					Axial (kip)	Shear (kip)	Moment (ft-kip)	Medium N-Value 4-8	Stiff N-Value 9-15	Very Stiff N-Value 16-30	Hard N-Value >30	Loose N-Value 4-10	Medium N-Value 11-30	Dense N-Value >30	Bar Size (#)	Quantity	Bar Size (#)	Spacing (in.)
WIND ZONE 1	LIGHT	S26L3	26	25	2	11	270	18	12.5	9	8	14.5	11	10	8	13	4	12
		S30L3	30	25	2	11	300	18.5	13	9	8	15	11.5	10	8	14	4	12
		S35L3	35	25	3	11	320	19	13.5	9.5	8	15	11.5	10.5	8	15	4	12
	HEAVY	S30H3	30	29	3	16	450	23	16	11	8	17.5	13.5	11.5	8	18	4	12
		S35H3	35	29	4	16	515	24.5	16.5	12	8.5	18.5	14	12	8	20	4	12
WIND ZONE 2	LIGHT	S26L2	26	23	2	10	245	17	12	8.5	8	14	11	9.5	8	13	4	12
		S30L2	30	23	2	10	270	18	12.5	8.5	8	14.5	11	10	8	13	4	12
		S35L2	35	23	3	10	300	18.5	13	9	8	14.5	11.5	10	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	22	15	10.5	8	17	13	11.5	8	17	4	12
		S35H2	35	29	4	15	475	23.5	16	11.5	8	18	13.5	12	8	19	4	12
WIND ZONE 3	LIGHT	S26L2	26	23	2	10	245	17	12	8.5	8	14	11	9.5	8	13	4	12
		S30L2	30	23	2	10	270	18	12.5	8.5	8	14.5	11	10	8	13	4	12
		S35L2	35	23	3	10	300	18.5	13	9	8	14.5	11.5	10	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	22	15	10.5	8	17	13	11.5	8	17	4	12
		S35H2	35	29	4	15	475	23.5	16	11.5	8	18	13.5	12	8	19	4	12
WIND ZONE 4	LIGHT	S26L1	26	22	2	8	190	15.5	10.5	8	8	13	10	9	8	12	4	12
		S30L1	30	22	2	8	205	15.5	11	8	8	13	10	9	8	12	4	12
		S35L1	35	22	3	8	230	16.5	11.5	8	8	13.5	10.5	9	8	12	4	12
	HEAVY	S30H1	30	25	3	12	320	19.5	13.5	9.5	8	15	12	10.5	8	15	4	12
		S35H1	35	25	4	12	350	20	14	10	8	15.5	12	10.5	8	15	4	12
WIND ZONE 5	LIGHT	S26L2	26	23	2	10	245	17	12	8.5	8	14	11	9.5	8	13	4	12
		S30L2	30	23	2	10	270	18	12.5	8.5	8	14.5	11	10	8	13	4	12
		S35L2	35	23	3	10	300	18.5	13	9	8	14.5	11.5	10	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	22	15	10.5	8	17	13	11.5	8	17	4	12
		S35H2	35	29	4	15	475	23.5	16	11.5	8	18	13.5	12	8	19	4	12

### Fabrication Design Notes:



- Values shown in the "Reactions at the Pole Base" column represent the minimum acceptable capacity allowed for design using a design CSR of 1.00.
- Min. base plate thickness (T) is 2.0 inches.

### Foundation Selection:

- Perform a standard penetration test at each proposed foundation site to determine "N" value.
- Select the appropriate wind zone from M 1 drawing.
- Select the soil type (Clay or Sand) that best describes the soil characteristics.
- Get the appropriate standard pole case number from the plans or from the Engineer.
- Select the appropriate column in the chart based on soil type and "N" value. Select the appropriate row based on the pole load case. The foundation depth is the value where the column and the row intersect.
- Reference Drilled Shafts: Construction Procedures and Design Methods, FHWA -IF-99-025

- S30H1 - Hard Clay-Stirrup Spacing: 6 in. c/c  
 - Dense Sand-Stirrup Spacing: 6 in. c/c
- S30H2 - Very Stiff Clay: Stirrup Spacing: 6 in. c/c  
 - Hard Clay: Stirrup Spacing: 6 in. c/c  
 - Medium Clay: Stirrup Spacing: 6 in. c/c  
 - Dense Sand: Stirrup Spacing: 6 in. c/c
- S30H3 - Very Stiff Clay: Stirrup Spacing: 6 in. c/c  
 - Hard Clay: Stirrup Spacing: 6 in. c/c  
 - Medium Clay: Stirrup Spacing: 6 in. c/c  
 - Dense Sand: Stirrup Spacing: 6 in. c/c
- S35H1 - Hard Clay: tirrup Spacing: 6 in. c/c  
 - Dense Sand: Stirrup Spacing: 6 in. c/c
- S35H2 - Very Stiff Clay: Stirrup Spacing: 6 in. c/c  
 - Hard Clay: Stirrup Spacing: 6 in. c/c  
 - Medium Clay: Stirrup Spacing: 6 in. c/c  
 - Dense Sand: Stirrup Spacing: 6 in. c/c
- S35H3 - Very Stiff Clay: Stirrup Spacing: 6 in. c/c  
 - Hard Clay: Stirrup Spacing: 6 in. c/c  
 - Medium Clay: Stirrup Spacing: 6 in. c/c  
 - Dense Sand: Stirrup Spacing: 6 in. c/c


48" Dia. Foundations Concrete Volume (cubic yards) = (0.465) x Foundation Depth

	<p><b>Standard Strain Pole Foundation for Dry Soil Condition</b></p> <p>PLAN DATE: SEPTEMBER 2013    DESIGNED BY: C.B. COGDILL                  PREPARED BY: N. BITTING    REVIEWED BY: D. SARKAR</p>							
<p>SCALE: 0 NA</p> <p>None</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>REVISIONS</th> <th>INIT.</th> <th>DATE</th> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </table>	REVISIONS	INIT.	DATE				<p>DocuSigned by:                  Deborah C. Sarkar 3/26/2014                  44EB3E2E147E4C4</p>
REVISIONS	INIT.	DATE						


06-MAR-2014 09:38  
 S:\TCS\1415 - Signal\Signal Design Section\Eastern Region\MM\_Sheets\2012\_M9\_Standard Foundations\_Dry.dgn  
 JGC/LOWEY

Standard Strain Pole Foundation-Dry Soil Condition

PHASING DIAGRAM



PHASING DIAGRAM DETECTION LEGEND



SIGNAL FACE I.D.




TABLE OF OPERATION

SIGNAL FACE	PHASE							
	01+5	01+6	02+5	02+6	03+7	03+8	04+7	04+8
11	-	-	F	F	R	R	R	Y
21	R	R	G	G	R	R	R	Y
22	R	R	G	G	R	R	R	Y
31	R	R	R	R	-	-	F	F
41	R	R	R	R	R	G	G	R
42	R	R	R	R	R	G	G	R
51	-	F	-	F	R	R	R	Y
61	R	G	R	G	R	R	R	Y
62	R	G	R	G	R	R	R	Y
71	R	R	R	R	-	F	F	R
81,82	R	R	R	R	G	G	R	R
P21,P22	DW	DW	W	W	DW	DW	DW	DRK
P81,P82	DW	DW	DW	DW	W	DW	W	DRK


OASIS 2070 LOOP & DETECTOR INSTALLATION CHART

LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	DETECTOR PROGRAMMING						
					PHASE	CALLING	EXTENSION	STRETCH TIME	DELAY TIME	SYSTEM LOOP	NEW CARD
1A	6X40	0	2-4-2	Y	1	Y	Y	-	15	-	-
2A,2B	6X6	70	4	Y	2	Y	Y	-	-	-	-
3A	6X40	0	2-4-2	Y	3	Y	Y	-	15	-	-
4A	6X40	0	2-4-2	Y	4	Y	Y	-	-	-	-
5A	6X40	0	2-4-2	Y	5	Y	Y	-	15	-	-
5B	6X40	0	2-4-2	Y	5	Y	Y	-	20	-	-
6A,6B	6X6	70	4	Y	6	Y	Y	-	-	-	-
7A	6X40	0	2-4-2	Y	7	Y	Y	-	15	-	-
8A	6X40	0	2-4-2	Y	8	Y	Y	-	-	-	-
8B	6X40	0	2-4-2	Y	8	Y	Y	-	10	-	-
S2A	6X6	+240	5	-	-	-	-	-	-	Y	-
S2B	6X6	+240	5	-	-	-	-	-	-	Y	-
S6A	6X6	+200	3	Y	-	-	-	-	-	-	Y
S6B	6X6	+200	3	Y	-	-	-	-	-	-	Y

8 Phase Fully Actuated Fayetteville City System

NOTES



- Refer to "Roadway Standard Drawings NCDOT" dated January 2012 and "Standard Specifications for Roads and Structures" dated January 2012.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Phase 1 and/or phase 5 may be lagged.
- Phase 3 and/or phase 7 may be lagged.
- Reposition existing signal heads numbered 21, 81, and 82.
- Set all detector units to presence mode.
- Omit "WALK" and flashing "DON'T WALK" with no pedestrian calls.
- Program pedestrian heads to countdown the flashing "Don't Walk" time only.
- Pedestrian pedestals are conceptual and shown for reference only. See sheets P1-P3 for pushbutton location details.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.



OASIS 2070 TIMING CHART

FEATURE	PHASE							
	1	2	3	4	5	6	7	8
Min Green 1 *	7	10	7	7	7	10	7	7
Extension 1 *	2.0	3.0	2.0	2.0	2.0	3.0	2.0	2.0
Max Green 1 *	20	60	20	40	20	60	40	40
Yellow Clearance	3.0	3.9	3.0	4.5	3.0	3.9	3.0	4.5
Red Clearance	3.4	2.6	2.8	2.6	3.5	2.6	2.8	2.6
Walk 1 *	-	7	-	-	-	-	-	7
Don't Walk 1	-	19	-	-	-	-	-	27
Seconds Per Actuation *	-	-	-	-	-	-	-	-
Max Variable Initial *	-	-	-	-	-	-	-	-
Time Before Reduction *	-	-	-	-	-	-	-	-
Time To Reduce *	-	-	-	-	-	-	-	-
Minimum Gap	-	-	-	-	-	-	-	-
Recall Mode	-	MIN RECALL	-	-	-	MIN RECALL	-	-
Vehicle Call Memory	-	YELLOW	-	-	-	YELLOW	-	-
Dual Entry	-	-	-	ON	-	-	-	ON
Simultaneous Gap	ON	ON	ON	ON	ON	ON	ON	ON

\* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.



Signal Upgrade

McPherson Church Road At SR 1400 (Cliffdale Road)

Division 6 Cumberland County Fayetteville

PLAN DATE: March 2015 REVIEWED BY: PLA

PREPARED BY: JPG REVIEWED BY:

REVISIONS INIT. DATE

SCALE 1"=30'

750 N. Greenfield Pkwy, Garner, NC 27529



SEAL NORTH CAROLINA PROFESSIONAL ENGINEER JASON P. GALLOWAY SEAL 029904

DocuSigned by: Jason Galloway 4/14/2015

SIG. INVENTORY NO. 06-0225

1:10/06/2015 15:51  
 S:\Projects\5206AF\15\_Signal\Signal Design Section\Eastern Region\015-06\W-5206AF-060225-10.dgn, 20150414.dgn  
 J:\011\0002

**EDI MODEL 2010ECL-NC CONFLICT MONITOR PROGRAMMING DETAIL**




REMOVE DIODE JUMPERS 1-5, 1-6, 1-9, 1-11, 2-5, 2-6, 2-9, 2-11, 2-13, 3-7, 3-8, 3-10, 3-12, 3-16, 4-7, 4-8, 4-10, 4-12, 4-16, 5-9, 5-11, 5-13, 6-9, 6-11, 6-13, 7-10, 7-12, 8-10, 8-12, 8-16, 9-11, 9-13, 10-12, 10-16, 11-13, and 12-16.

REMOVE JUMPERS AS SHOWN

NOTES:

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Make sure jumpers SEL2-SEL5 are present on the monitor board.



**NOTES**

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Ensure that Red Enable is active at all times during normal operation. To prevent Red Failures on unused monitor channels, tie unused red monitor inputs 1, 13, 14, 15 & 16 to load switch AC+ per the cabinet manufacturer's instructions.
- Program phases 4 and 8, for Dual Entry.
- Enable Simultaneous Gap-Out for all phases.
- Program phases 2 and 6 for Start Up In Green.
- Program phases 2 and 6 for 'STARTUP PED CALL'.
- Program phases 2 and 6 for Yellow Flash, and overlaps 1 and 2 as Wag Overlaps.
- The cabinet and controller are part of the Fayetteville City System.

**EQUIPMENT INFORMATION**


CONTROLLER.....2070L  
 CABINET.....332 W/ AUX  
 SOFTWARE.....ECONOLITE OASIS  
 CABINET MOUNT.....BASE  
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE  
 LOAD SWITCHES USED.....S1,S2,S2P,S3,S4,S5,S6,S7,S8,S8P,S9,S10,S12,S13  
 PHASES USED.....1,2,2PED,3,4,5,6,7,8,8PED  
 OVERLAP "A".....1+2  
 OVERLAP "B".....3+4  
 OVERLAP "C".....5+6  
 OVERLAP "D".....7+8

**SIGNAL HEAD HOOK-UP CHART**

LOAD SWITCH NO.	S1	S2	S2P	S3	S4	S4P	S5	S6	S6P	S7	S8	S8P	S9	S10	S11	S12	S13	S14
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	9	10	11	12	13	14
SIGNAL HEAD NO.	11	21,22	P21, P22	22	31	41,42	51	61,62	71	81,82	P81, P82	11	31	51	71	91	111	131
RED		128	*		101	*		134	*		107							
YELLOW	*	129			102			135			108							
GREEN		130			103			136			109							
RED ARROW														A121	A124		A114	A101
YELLOW ARROW				117				132		123				A122	A125		A115	A102
FLASHING YELLOW ARROW														A123	A126		A116	A103
GREEN ARROW	127			118	118		133	133		124	124							
Hand				113														
Foot																		

NU = Not Used  
 \* Denotes install load resistor. See load resistor installation detail this sheet.  
 ★ See pictorial of head wiring in detail below.

**4 SECTION FYA PPLT SIGNAL WIRING DETAIL**



NOTE: The sequence display for these signals require special logic programming. See sheet 2 for programming instructions.

**INPUT FILE POSITION LAYOUT**

FILE "I"	1	2	3	4	5	6	7	8	9	10	11	12	13	14
U	∅ 1	∅ 2	∅ 3	∅ 4	SYS. DET. S2A	S	S	S	SYS. DET. S2A	S	S	∅ 2 PED DC ISOLATOR	NOT USED	FS DC ISOLATOR
L	NOT USED	NOT USED	NOT USED	NOT USED	SYS. DET. S2B	S	S	S	SYS. DET. S2B	S	S	NOT USED	∅ 8 PED DC ISOLATOR	ST DC ISOLATOR
U	∅ 5	∅ 5	∅ 7	∅ 8	SYS. DET. S6A	S	S	S	SYS. DET. S6A	S	S	S	S	S
L	NOT USED	∅ 6	NOT USED	∅ 8	SYS. DET. S6B	S	S	S	SYS. DET. S6B	S	S	S	S	S

EX.: 1A, 2A, ETC. = LOOP NO.'S  
 FS = FLASH SENSE  
 ST = STOP TIME  
 \* Wired Input - Do not populate slot with detector card

**COUNTDOWN PEDESTRIAN SIGNAL OPERATION**

Countdown Ped Signals are required to display timing only during Ped Clearance Interval. Consult Ped Signal Module user's manual for instructions on selecting this feature.

**INPUT FILE CONNECTION & PROGRAMMING CHART**


LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	INPUT ASSIGNMENT NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND	FULL TIME DELAY	STRETCH TIME	DELAY TIME
1A <sup>1</sup>	TB2-1,2	I1U	56	18	1	1	Y	Y			15
	-	J4U	48	10	26	6	Y	Y			
2A,2B	TB2-5,6	I2U	39	1	2	2	Y	Y			
	-	J8U	50	12	28	8	Y	Y			3
3A <sup>2</sup>	TB4-5,6	I5U	58	20	3	3	Y	Y			15
	-	J8U	50	12	28	8	Y	Y			
4A	TB4-9,10	I6U	41	3	4	4	Y	Y			
* S2A	TB6-9,10	I9U	60	22	11	SYS					
* S2B	TB6-11,12	I9L	62	24	13	SYS					
5A <sup>3</sup>	TB3-1,2	J1U	55	17	5	5	Y	Y			15
	-	I4U	47	9	22	2	Y	Y			
5B	TB3-5,6	J2U	40	2	6	5	Y	Y			20
6A,6B	TB3-7,8	J2L	44	6	16	6	Y	Y			
7A <sup>4</sup>	TB5-5,6	J5U	57	19	7	7	Y	Y			15
	-	I8U	49	11	24	4	Y	Y			3
8A	TB5-9,10	J6U	42	4	8	8	Y	Y			
8B	TB5-11,12	J6L	46	8	18	8	Y	Y			10
* S6A	TB7-9,10	J9U	59	21	15	SYS					
* S6B	TB7-11,12	J9L	61	23	17	SYS					
PED PUSH BUTTONS											
P21,P22	TB8-4,6	I12U	67	29	PED 2	2 PED					
P81,P82	TB8-8,9	I13L	70	32	PED 8	8 PED					

NOTE: INSTALL DC ISOLATORS IN INPUT FILE SLOTS 112 AND 113.

- Add jumper from I1-W to J4-W, on rear of input file.
- Add jumper from I5-W to J8-W, on rear of input file.
- Add jumper from J1-W to I4-W, on rear of input file.
- Add jumper from J5-W to I8-W, on rear of input file.


\* System detector only. Remove the vehicle phase assigned to this detector in the default programming.

INPUT FILE POSITION LEGEND: J2L




**LOAD RESISTOR INSTALLATION DETAIL**

VALUE (ohms)	WATTAGE
1.5K - 1.9K	25W (min)
2.0K - 3.0K	10W (min)



**IMPORTANT:** Move Load Resistor from Yellow Field Terminal to Red Field Terminal for Phase 3.

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 06-0225  
 DESIGNED: March 2015  
 SEALED: 4/17/2015  
 REVISED: N/A



ELECTRICAL DETAIL SHEET 1 OF 2

McPherson Church Road at SR 1400 (Cliffdale Road)

Division 06 Cumberland County Fayetteville

PLAN DATE: 3-10-10 REVIEWED BY: D.T. Joyce

PREPARED BY: D.H. Spaulding REVIEWED BY:

REVISIONS: Added 5-section head 22, peds, and loop 88. (WSA) 4/17/2015

750 N. Greenfield Pkwy, Garner, NC 27529

SIG. INVENTORY NO. 06-0225

16-APR-2016 07:58 S:\MIS\AS\15\_Signal\work\hgr\oups\51g\_McPherson\trng\060225\_sml.elec.xxx.dgn somstr00g



## LOGICAL I/O PROCESSOR PROGRAMMING DETAIL TO PRODUCE SPECIAL FYA-PPLT SIGNAL SEQUENCE

(program controller as shown below)

1. FROM MAIN MENU PRESS '2' (PHASE CONTROL), THEN '1' (PHASE CONTROL FUNCTIONS), SCROLL TO THE BOTTOM OF THE MENU AND ENABLE ACT LOGIC COMMANDS 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, AND 12.
2. FROM MAIN MENU PRESS '6' (OUTPUTS), THEN '3' (LOGICAL I/O PROCESSOR).

```

LOGICAL I/O COMMAND #1 (+/-COMMAND#)
IF ACTIVE PHASE #1 IS ON
AND RED CLEAR ON PHASE #1 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #50 ON
SET OUTPUT ASSIGNMENT #51 OFF
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR PHASE 1 RED CLEAR WHEN TRANSITIONING FROM PHASE 1 TO PHASE 2 (HEAD 11).

```

LOGICAL I/O COMMAND #2 (+/-COMMAND#)
IF ACTIVE PHASE #1 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #52 OFF
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR SWITCHING FLASHING YELLOW ARROW "OFF" DURING PHASE 1 (HEAD 11).

```

LOGICAL I/O COMMAND #3 (+/-COMMAND#)
IF YELLOW ON PHASE #1 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #51 ON
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR YELLOW ARROW CLEARANCE FROM PHASE 1 (HEAD 11).

```

LOGICAL I/O COMMAND #4 (+/-COMMAND#)
IF ACTIVE PHASE #5 IS ON
AND RED CLEAR ON PHASE #5 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #42 ON
SET OUTPUT ASSIGNMENT #43 OFF
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR PHASE 5 RED CLEAR WHEN TRANSITIONING FROM PHASE 5 TO PHASE 6 (HEAD 51).

```

LOGICAL I/O COMMAND #5 (+/-COMMAND#)
IF ACTIVE PHASE #5 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #44 OFF
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR SWITCHING FLASHING YELLOW ARROW "OFF" DURING PHASE 5 (HEAD 51).

```

LOGICAL I/O COMMAND #6 (+/-COMMAND#)
IF YELLOW ON PHASE #5 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #43 ON
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR YELLOW ARROW CLEARANCE FROM PHASE 5 (HEAD 51).

```

LOGICAL I/O COMMAND #7 (+/-COMMAND#)
IF ACTIVE PHASE #3 IS ON
AND RED CLEAR ON PHASE #3 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #47 ON
SET OUTPUT ASSIGNMENT #48 OFF
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR PHASE 3 RED CLEAR WHEN TRANSITIONING FROM PHASE 3 TO PHASE 4 (HEAD 31).

```

LOGICAL I/O COMMAND #8 (+/-COMMAND#)
IF ACTIVE PHASE #3 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #49 OFF
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR SWITCHING FLASHING YELLOW ARROW "OFF" DURING PHASE 3 (HEAD 31).

```

LOGICAL I/O COMMAND #9 (+/-COMMAND#)
IF YELLOW ON PHASE #3 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #48 ON
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR YELLOW ARROW CLEARANCE FROM PHASE 3 (HEAD 31).

```

LOGICAL I/O COMMAND #10 (+/-COMMAND#)
IF ACTIVE PHASE #7 IS ON
AND RED CLEAR ON PHASE #7 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #39 ON
SET OUTPUT ASSIGNMENT #40 OFF
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR PHASE 7 RED CLEAR WHEN TRANSITIONING FROM PHASE 7 TO PHASE 8 (HEAD 71).

```

LOGICAL I/O COMMAND #11 (+/-COMMAND#)
IF ACTIVE PHASE #7 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #41 OFF
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR SWITCHING FLASHING YELLOW ARROW "OFF" DURING PHASE 7 (HEAD 71).

```

LOGICAL I/O COMMAND #12 (+/-COMMAND#)
IF YELLOW ON PHASE #7 IS ON
    ↓
    SCROLL DOWN
    ↓
THEN:
SET OUTPUT ASSIGNMENT #40 ON
    ↓
    PRESS '+'
    
```

NOTE: LOGIC FOR YELLOW ARROW CLEARANCE FROM PHASE 7 (HEAD 71).

LOGIC I/O PROCESSOR PROGRAMMING COMPLETE

## OVERLAP PROGRAMMING DETAIL

(program controller as shown below)

FROM MAIN MENU PRESS '8' (OVERLAPS), THEN '1' (VEHICLE OVERLAP SETTINGS).

```

PAGE 1: VEHICLE OVERLAP 'A' SETTINGS
PHASE: 12345678910111213141516
VEH OVL PARENTS: XX
VEH OVL NOT VEH:
VEH OVL NOT PED:
VEH OVL GRN EXT:
STARTUP COLOR: - RED - YELLOW - GREEN
FLASH COLORS: - RED - YELLOW X GREEN
SELECT VEHICLE OVERLAP OPTIONS: (Y/N)
FLASH YELLOW IN CONTROLLER FLASH?...Y
GREEN EXTENSION (0=255 SEC)...0
YELLOW CLEAR (0=PARENT,3-25.5 SEC)...0.0
RED CLEAR (0=PARENT,0.1-25.5 SEC)...0.0
OUTPUT AS PHASE # (0=NONE, 1-16)...0
    ↓
    PRESS '+'
    
```

← NOTICE GREEN FLASH

```

PAGE 1: VEHICLE OVERLAP 'B' SETTINGS
PHASE: 12345678910111213141516
VEH OVL PARENTS: XX
VEH OVL NOT VEH:
VEH OVL NOT PED:
VEH OVL GRN EXT:
STARTUP COLOR: - RED - YELLOW - GREEN
FLASH COLORS: - RED - YELLOW X GREEN
SELECT VEHICLE OVERLAP OPTIONS: (Y/N)
FLASH YELLOW IN CONTROLLER FLASH?...Y
GREEN EXTENSION (0=255 SEC)...0
YELLOW CLEAR (0=PARENT,3-25.5 SEC)...0.0
RED CLEAR (0=PARENT,0.1-25.5 SEC)...0.0
OUTPUT AS PHASE # (0=NONE, 1-16)...0
    ↓
    PRESS '+'
    
```

← NOTICE GREEN FLASH

```

PAGE 1: VEHICLE OVERLAP 'C' SETTINGS
PHASE: 12345678910111213141516
VEH OVL PARENTS: XX
VEH OVL NOT VEH:
VEH OVL NOT PED:
VEH OVL GRN EXT:
STARTUP COLOR: - RED - YELLOW - GREEN
FLASH COLORS: - RED - YELLOW X GREEN
SELECT VEHICLE OVERLAP OPTIONS: (Y/N)
FLASH YELLOW IN CONTROLLER FLASH?...Y
GREEN EXTENSION (0=255 SEC)...0
YELLOW CLEAR (0=PARENT,3-25.5 SEC)...0.0
RED CLEAR (0=PARENT,0.1-25.5 SEC)...0.0
OUTPUT AS PHASE # (0=NONE, 1-16)...0
    ↓
    PRESS '+'
    
```

← NOTICE GREEN FLASH

```

PAGE 1: VEHICLE OVERLAP 'D' SETTINGS
PHASE: 12345678910111213141516
VEH OVL PARENTS: XX
VEH OVL NOT VEH:
VEH OVL NOT PED:
VEH OVL GRN EXT:
STARTUP COLOR: - RED - YELLOW - GREEN
FLASH COLORS: - RED - YELLOW X GREEN
SELECT VEHICLE OVERLAP OPTIONS: (Y/N)
FLASH YELLOW IN CONTROLLER FLASH?...Y
GREEN EXTENSION (0=255 SEC)...0
YELLOW CLEAR (0=PARENT,3-25.5 SEC)...0.0
RED CLEAR (0=PARENT,0.1-25.5 SEC)...0.0
OUTPUT AS PHASE # (0=NONE, 1-16)...0
    ↓
    PRESS '+'
    
```

← NOTICE GREEN FLASH

OVERLAP PROGRAMMING COMPLETE

## FLASHER CIRCUIT MODIFICATION DETAIL


IN ORDER TO INSURE THAT SIGNALS FLASH CONCURRENTLY ON THE SAME APPROACH, MAKE THE FOLLOWING FLASHER CIRCUIT CHANGES:

1. ON REAR OF PDA - REMOVE WIRE FROM TERM. T2-4 AND TERMINATE ON T2-2.
2. ON REAR OF PDA - REMOVE WIRE FROM TERM. T2-5 AND TERMINATE ON T2-3.
3. REMOVE FLASHER UNIT 2.

THE CHANGES LISTED ABOVE TIES ALL PHASES AND OVERLAPS TO FLASHER UNIT 1.

OUTPUT REFERENCE SCHEDULE	
USE TO INTERPRET LOGIC PROCESSOR	
OUTPUT 39 =	Overlap D Red
OUTPUT 40 =	Overlap D Yellow
OUTPUT 41 =	Overlap D Green
OUTPUT 42 =	Overlap C Red
OUTPUT 43 =	Overlap C Yellow
OUTPUT 44 =	Overlap C Green
OUTPUT 47 =	Overlap B Red
OUTPUT 48 =	Overlap B Yellow
OUTPUT 49 =	Overlap B Green
OUTPUT 50 =	Overlap A Red
OUTPUT 51 =	Overlap A Yellow
OUTPUT 52 =	Overlap A Green

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 06-0225  
DESIGNED: March 2015  
SEALED: 4/14/2015  
REVISED: N/A




ELECTRICAL DETAIL SHEET 2 OF 2

	<p><b>McPherson Church Road</b> at <b>SR 1400 (Cliffdale Road)</b></p>	<p>SEAL</p>
Prepared in the Offices of: 750 N. Greenfield Pkwy, Garner, NC 27529	Division 06 Cumberland County Fayetteville PLAN DATE: 3-10-10 REVIEWED BY: D.T. Joyce PREPARED BY: D.H. Spaulding REVIEWED BY: REVISIONS Added 5-section head 22, peds, and 1000 88. (WSA) <i>gtr</i> 4/17/2015	This document originally issued and sealed by George C. Brown, #022013, on 03/26/2010. This media shall not be considered a certified document.  SIGNATURE _____ DATE _____ SIG. INVENTORY NO. 06-0225

I:\6-0225-2015\_01-158  
 S:\MITSAS\15\_Signal\work\hgr\oups\51g\_McPherson\trng\060225\_sml.ele.xxx.dgn  
 s0rnmstrfong

Design Loading for METAL POLE NO. 1



Elevation View

SPECIAL NOTE

The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

Elevation Data for Mast Arm Attachment (H1)

Elevation Differences for:	Pole 1
Baseline reference point at $\phi$ Foundation @ ground level	0.0 ft.
Elevation difference at High point of roadway surface	+0.5 ft.
Elevation difference at Edge of travelway or face of curb	+/-0.0 ft.

METAL POLE No. 1

PROJECT REFERENCE NO.	SHEET NO.
W-5206AF	Fig. 1.3

MAST ARM LOADING SCHEDULE

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	25.5"W X 66.0"L	74 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-3 SECTION-WITH BACKPLATE	9.3 S.F.	25.5"W X 52.5"L	60 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-5 SECTION-WITH BACKPLATE	16.3 S.F.	42.0"W X 56.0"L	103 LBS
	STREET NAME SIGN RIGID MOUNTED	12.0 S.F.	18.0"W X 96.0"L	27 LBS


NOTES

DESIGN REFERENCE MATERIAL


- Design the traffic signal structure and foundation in accordance with:
  - The 5th Edition 2009 AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
  - The 2012 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
  - The 2012 NCDOT Roadway Standard Drawings.
  - The traffic signal project plans and special provisions.
  - The NCDOT "Metal Pole Standards" located at the following NCDOT website: <https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

DESIGN REQUIREMENTS

- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using stress ratios that do not exceed 0.9.
- The camber design for the mast arm deflection should provide an appearance of a low pitched arch where the tip or the free end of the mast arm does not deflect below horizontal when fully loaded.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
  - Mast arm slope and deflection are not considered in determining the arm attachment height as they are assumed to offset each other.
  - Signal heads are rigidly mounted and vertically centered on the mast arm.
  - The roadway clearance height for design is as shown in the elevation views.
  - The top of the pole base plate is 0.75 feet above the ground elevation.
  - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
- The pole manufacturer will determine the total height (H2) of each pole using the greater of the following:
  - Mast arm attachment height (H1) plus 2 feet, or
  - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 773-2800.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The contractor is responsible for providing soil penetration testing data (SPT) to the pole manufacturer so site specific foundations can be designed.




POLE RADIAL ORIENTATION



8 BOLT BASE PLATE DETAIL

See Note 6




BASE PLATE TEMPLATE & ANCHOR BOLT LOCK PLATE DETAIL For 8 Bolt Base Plate



NCDOT Wind Zone 3 (110 mph)

<p>Prepared In the Offices of: TRANSPORTATION MOBILITY AND SAFETY DIVISION SIGNAL DESIGN SECTION 750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p>McPherson Church Road At SR 1400 (Cliffdale Road)</p>		<p>SEAL NORTH CAROLINA PROFESSIONAL ENGINEER JASON P. GALLOWAY SEAL 029904</p>
	<p>Division 6 Cumberland County Fayetteville</p> <p>PLAN DATE: April 2015 REVIEWED BY: PLA</p> <p>PREPARED BY: JPG REVIEWED BY:</p>	<p>REVISIONS</p> <p>INIT. DATE</p>	
<p>SCALE 0 N/A N/A</p>	<p>SIG. INVENTORY NO. 06-0225</p>		

08-APR-2015 10:15  
 S:\MTS\SIG\ITS\SIGNAL\Eastern Region\01\06\W-5206AF\060225.sia\_rpt\_201504.dgn  
 J:\galloway



ITEM DESCRIPTION	MATERIAL SPECIFICATION
FLATWASHERS	ASTM-F436
NUTS	ASTM-A563 GR DH
H.S. BOLTS	ASTM-A325
PLATE	ASTM-A572 GR 50 OR ASTM-A709 GR 50
ROUND HSS	ASTM-A500 GR B
PIPE	ASTM-A53 GR B




**GENERAL NOTES:**

1. FIELD VERIFY EXISTING ANCHOR BOLTS AND BASE PLATE FOR POSSIBLE CORROSION.
2. FIELD VERIFY EXISTING ANCHOR BOLT PROJECTION (6" PER UNION METAL DWG. NO. ATS 8-1211-3 REVIEWED BY NCDOT ON 12/4/1998).
3. PROVIDE MATERIALS AND WORKMANSHIP IN ACCORDANCE WITH THE LATEST SIGNALS AND ITS PROJECT SPECIAL PROVISION.
4. VERIFY ALL ELEVATIONS AND DIMENSIONS IN THE FIELD PRIOR TO FABRICATION AND CONSTRUCTION.
5. VERIFY AND LOCATE ALL EXISTING UTILITIES PRIOR TO STARTING WORK. CONDUCT OPERATIONS IN A MANNER WHICH ENSURES THAT UTILITIES WILL NOT BE DISTURBED OR ENDANGERED.
6. REFER TO NCDOT STANDARD CONSTRUCTION DETAILS FOR ADDITIONAL INFORMATION INCLUDING GROUNDING LUG PROVISIONS.

**CONSTRUCTION SEQUENCE:**

1. REMOVE EXISTING TOP NUT COVERS.
2. VERIFY ANCHOR BOLT PROJECTION FROM TOP OF FOUNDATION IS GREATER THAN OR EQUAL TO DIMENSION "P" PROVIDED IN THE ORIGINAL SHOP DRAWING (SEE SECTION B-B).
3. REMOVE TOP NUTS AND WASHERS AT BASE PLATE, AND CAREFULLY REMOVE MAST ARM POLE WITH BASE PLATE AWAY FROM FOUNDATION WITHOUT CAUSING DAMAGE TO EXISTING STRUCTURE, ANCHORS BOLTS, FOUNDATION AND SURROUNDING PROPERTY.
4. REMOVE EXISTING GROUT FROM UNDER EXISTING BASE PLATE AND FROM AROUND ANCHOR BOLTS.
5. ATTACH ADAPTER ASSEMBLY TO EXISTING ANCHOR BOLTS USING THE PREVIOUSLY REMOVED WASHERS AND NUTS IF THEY ARE IN GOOD CONDITION. OTHERWISE, USE NEW NUTS AND WASHERS. REFER TO FOUNDATION AND ANCHOR ROD ASSEMBLIES FOR METALS POLES SPO9\_R005 FOR THE ANCHOR ROD NUT TIGHTENING, PREPARATION AND LEVELING.
6. VERIFY ADAPTER ASSEMBLY IS LEVEL FOR INSTALLING EXISTING MAST ARM POLE.
7. ATTACH EXISTING MAST ARM POLE TO TOP OF ADAPTER ASSEMBLY USING FOUR (4) - 1 1/2" DIA. X 5 1/4" LG ASTM-A325 H.S. BOLTS.
8. INSTALL RODENT BARRIER BETWEEN PLATE AND TOP OF FOUNDATION.



**MAST ARM POLE NO.14**  
(EXISTING POLE WITH ADAPTER ASSEMBLY)

**SECTION B-B**

\* SEE GENERAL NOTE 2.  
\*\* EACH H.S. BOLT SHALL HAVE (1) ASTM-A563 NUT AND (2) ASTM-F436 CIRCULAR WASHERS.

WIND ZONE 03-110 mph

	<p>Metal Pole Adapter for MP#14 at McPherson Church Road and SR 1400 (Cliffdale Road)</p>										
	<p>Division 6 Cumberland County Fayetteville</p> <p>PLAN DATE: June 2015 DESIGNED BY: K. Durigon PREPARED BY: K. Durigon REVIEWED BY: D. Sarkar</p>										
<p>SCALE 0 N/A N/A</p>	<table border="1"> <thead> <tr> <th>REVISIONS</th> <th>REV.</th> <th>INIT.</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>		REVISIONS	REV.	INIT.	DATE					<p>DocuSigned by: Kevin C. Durigon 6/23/2015</p>
REVISIONS	REV.	INIT.	DATE								
<p>SIG. INVENTORY NO. 06-0225</p>			<p>DATE</p>								

23-jul-2015 01:56  
 C:\Users\kccour\Documents\kccour\014 06-06-0225 Adapter#060225\_M14 Adapter\_Plate Detail - FINAL.dgn  
 kccour.dgn



STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

06-14



ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL

SHEET 1 OF 3  
**1705D01**

**PUSHBUTTON PLACEMENT**  
SEPARATE CURB RAMPS



**PUSHBUTTON PLACEMENT**  
SHARED CURB RAMP



- NOTES**
1. Pushbutton pedestals should not be located further than 10 feet from the edge of curb, shoulder, or pavement.
  2. The face of the pushbutton should be parallel to the applicable crosswalk.
  3. Separate pushbuttons used on the same corner should be separated by a distance of at least 10 feet.
  4. Pushbuttons shall be installed adjacent to a level surface with a maximum reach distance of 10 inches.
  5. Maintain 4 feet of clearance around pedestal if located in sidewalk.
  6. Refer to section 1705 of the 2012 NCDOT Roadway Standard Drawings for Pushbutton Assembly details.
  7. Refer to section 1743 of the 2012 NCDOT Roadway Standard Drawings for Pedestal details.
  8. Contact Division Traffic Engineer for pushbutton location approval prior to installation.
  9. Curb ramps are for symbolic use only and may not reflect actual design or field conditions.

PROPOSED	LEGEND
	Signal Pole
	Type I Pushbutton Post
	Type II Signal Pedestal
	Pushbutton & Sign
	Pedestrian Signal Head
	Curb Ramp
	Pushbutton Location Area

STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

06-14

ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL

SHEET 1 OF 3  
**1705D01**

See Plate for Title

Prepared in the Offices of:

750 N. Greenfield Parkway  
Garner, NC 27529

SEAL

DocuSigned by:  
*Robert J. Ziemba*  
18084828744604

SIGNATURE DATE

6/17/2014

06-AUG-2014 16:37  
 S:\ITS\ASU\ITS\_Signal\Signal Design\Section\Central\_Regional\Rob's Files\Red Stds\Pushbutton Drawings\Pushbutton Place Drawings\20140617.dgn  
 rz1emba


STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

06-14


ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL

SHEET 2 OF 3  
**1705D01**


TYPICAL PUSHBUTTON LOCATIONS (CASE I)  
SEPARATE CURB RAMPS W/ TYPE I PEDESTALS



BACK OF SIDEWALK IS WITHIN 10'  
OF CURB OR PAVEMENT/SHOULDER



GRASS STRIP PLACEMENT IF BACK  
OF SIDEWALK EXCEEDS 10' FROM  
CURB OR PAVEMENT/SHOULDER




PUSHBUTTON PLACEMENT  
IN WIDE SIDEWALK

**PROPOSED**


- Signal Pole
- Type I Pushbutton Post
- Type II Signal Pedestal
- Pushbutton & Sign
- Pedestrian Signal Head
- Curb Ramp
- Pushbutton Location Area

**LEGEND**


TYPICAL PUSHBUTTON LOCATIONS (CASE II)  
SEPARATE CURB RAMPS W/ TYPE II PEDESTALS



BACK OF SIDEWALK IS WITHIN 10'  
OF CURB OR PAVEMENT/SHOULDER




GRASS STRIP PLACEMENT IF BACK  
OF SIDEWALK EXCEEDS 10' FROM  
CURB OR PAVEMENT/SHOULDER



PUSHBUTTON PLACEMENT  
IN WIDE SIDEWALK

OPTIONAL PUSHBUTTON EXTENSION  
FACE OF PUSHBUTTON PARALLEL TO  
APPLICABLE CROSSWALK



STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

06-14

ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL

SHEET 2 OF 3  
**1705D01**

See Plate for Title

Prepared in the Offices of:

750 N. Greenfield Parkway  
Garner, NC 27529

SEAL

DocuSigned by:  
*Robert J. Ziemba*  
188B486274464

SIGNATURE

6/17/2014  
DATE

06-1406-2014.r16.r38  
 S:\1705D01\SIGNAL Design Section\Central Region\Rob's Files\Red State\Pushbutton Drawings\Pushbutton Place Drawings\20140617.dgn  
 rz1emba

STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

06-14

ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL

SHEET 3 OF 3  
**1705D01**

STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.


06-14

ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL


SHEET 3 OF 3  
**1705D01**

**TYPICAL PUSHBUTTON LOCATIONS (CASE III)**


SHARED CURB RAMPS




BACK OF SIDEWALK IS WITHIN 10' OF CURB OR PAVEMENT/SHOULDER



GRASS STRIP PLACEMENT IF BACK OF SIDEWALK EXCEEDS 10' FROM CURB OR PAVEMENT/SHOULDER




PUSHBUTTON PLACEMENT IN WIDE SIDEWALK (CORRESPONDING PUSHBUTTONS AND SIGNAL HEADS ON DIFFERENT PEDESTALS)




PUSHBUTTON PLACEMENT WITH SHARED TYPE II SIGNAL PEDESTAL AND TYPE I PUSHBUTTON POST

**TRAFFIC ISLAND PUSHBUTTON LOCATIONS**



PUSHBUTTON PLACEMENT IN LARGE "PORK CHOP ISLAND" WITH SEPARATE PEDESTALS



PUSHBUTTON PLACEMENT IN SMALL "PORK CHOP ISLAND" WITH SHARED PEDESTAL

**PUSHBUTTON PLACEMENT IN MEDIAN**

TYPE II PEDESTAL (FOR STAGED OR MULTI-PHASE CROSSING)

TYPE I PEDESTAL (FOR COMPLETE CROSSING CURB TO CURB WITH OPTIONAL REFUGE)

**PROPOSED**

	Signal Pole
	Type I Pushbutton Post
	Type II Signal Pedestal
	Pushbutton & Sign
	Pedestrian Signal Head
	Curb Ramp
	Pushbutton Location Area

**LEGEND**

06-AUG-2014 16:39  
 S:\ITS\ASU\ITS\_Signal\Signal Design Section\Central Region\Rob's Files\Red Stds\Pushbutton Drawings\Pushbutton Place Drawings\20140617.dgn  
 rz1emba

See Plate for Title

Prepared in the Offices of:


750 N. Greenfield Parkway  
Garner, NC 27529

SEAL


DocuSigned by:  
*Robert J. Ziemba*  
18084982744494

SIGNATURE DATE


6/17/2014



75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



PROJ. REFERENCE NO.  
W-5206AF

SHEET NO.  
X-2

