

**This electronic collection of documents is provided  
for the convenience of the user  
and is Not a Certified Document –**

**The documents contained herein were originally issued  
and sealed by the individuals whose names and license  
numbers appear on each page, on the dates appearing  
with their signature on that page.**


**This file or an individual page  
shall not be considered a certified document.**

09/08/99

25-MAR-2025 08:49  
\\Roadway\Proj\BP7C001\_RDY\_TSH.dgn  
HNTB

WBS PROJECT: BP7.C001

CONTRACT: DF00663



FINAL PLANS


STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

ROCKINGHAM COUNTY

LOCATION: REPLACE EXISTING CULVERT ON SR 1785 (CHURCH ST)

TYPE OF WORK: GRADING, DRAINAGE, PAVING, AND CULVERT


STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	BP7.C001	1	
STATE PROJ. NO.		F.A. PROJ. NO.	DESCRIPTION
BP7.C001.1			PE
BP7.C001.2			ROW & UTIL
BP7.C001.3			CONST



4

\* A DESIGN EXCEPTION HAS BEEN APPROVED FOR DESIGN SPEED.

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED




DESIGN DATA
ADT 2025 = 7,250
ADT 2045 = 10,800
V = 15 MPH*
FUNC CLASS = MINOR ARTERIAL REGIONAL TIER

PROJECT LENGTH
TOTAL LENGTH OF PROJECT BP7.C001 = 0.077 MI

Prepared In the Office of: <b>HNTB</b> HNTB NORTH CAROLINA, P.C. 4000 CENTER AT NORTH HILLS ST. SUITE 500 RALEIGH, NORTH CAROLINA 27609 NC LICENSE NO: C-1554	
2024 STANDARD SPECIFICATIONS	
RIGHT OF WAY DATE: DECEMBER 1, 2023	BRIAN P. BLACKWELL, PE PROJECT ENGINEER
LETTING DATE: JUNE 19, 2025	DANIEL R. DAGENHART NCDOT CONTACT

HYDRAULICS ENGINEER
DocuSigned by: Galen Cail SIGNATURE: _____ P.E. 3/26/2025
ROADWAY DESIGN ENGINEER
DocuSigned by: Brian Blackwell SIGNATURE: _____ P.E. 3/25/2025





INDEX OF SHEETS

SHEET NUMBER

SHEET

1  
1A  
1B  
2A-1  
2C-1 THRU 2C-2  
3B-1  
3D-1  
4 THRU 5  
RW01 THRU RW04  
TMP-1 THRU TMP-4

TITLE SHEET  
INDEX OF SHEETS, GENERAL NOTES & LIST OF STANDARDS  
SYMBOLGY SHEET  
TYPICAL SECTION SHEET  
ROADWAY SPECIAL DETAILS  
ROADWAY SUMMARY SHEET (EARTHWORK, GUARDRAIL)  
DRAINAGE SUMMARY SHEET  
PLAN & PROFILE SHEETS  
SURVEY CONTROL & RW SHEETS  
TRAFFIC CONTROL PLANS

PMP-1 THRU PMP-2  
EC-1 THRU EC-5  
SIGN-1 THRU SIGN-2  
UC-01 THRU UC-06  
UO-1 THRU UO-2  
X-1  
X-1A  
X-2 THRU X-8

PAVEMENT MARKING PLANS  
EROSION CONTROL PLANS  
SIGNING PLANS  
UTILITY CONSTRUCTION PLANS  
UTILITY BY OTHERS PLANS  
CROSS SECTION INDEX  
CROSS SECTION SUMMARY  
CROSS SECTION SHEETS



HNTB NORTH CAROLINA, P.C.  
4000 CENTER AT NORTH HILLS ST.  
SUITE 500  
RALEIGH, NORTH CAROLINA 27609  
NC LICENSE NO. C-1954


PROJECT REFERENCE NO.

BP7.C001

SHEET NO.

1A

ROADWAY DESIGN  
ENGINEER



DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

GENERAL NOTES:

2024 SPECIFICATIONS

EFFECTIVE: 01-16-2024  
REVISED:

EFF. 01-16-2024  
REV.

GRADING AND SURFACING OR RESURFACING AND WIDENING:

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. WHERE NO GRADE LINES ARE SHOWN, THE PROFILES SHOWN DENOTE THE TOP ELEVATION OF THE EXISTING PAVEMENT ALONG THE CENTER LINE OF SURVEY ON WHICH THE PROPOSED RESURFACING WILL BE PLACED. GRADE LINES MAY BE ADJUSTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

SUPERELEVATION:

ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SIDE ROADS:

THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

DRIVEWAYS:

DRIVEWAYS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. 848.02 USING 3 FOOT RADII OR RADII AS SHOWN ON THE PLANS. LOCATIONS OF DRIVES WILL BE AS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER.

STREET TURNOUT:

STREET RETURNS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. NO. 848.04 USING THE RADII NOTED ON PLANS.

GUARDRAIL:

THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

TEMPORARY SHORING:

SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC WILL BE PAID FOR AS "EXTRA WORK" IN ACCORDANCE WITH SECTION 104-7.

SUBSURFACE PLANS:

NO SUBSURFACE PLANS ARE AVAILABLE ON THIS PROJECT. THE CONTRACTOR SHOULD MAKE HIS OWN INVESTIGATION AS TO THE SUBSURFACE CONDITIONS.

UTILITIES:

UTILITY OWNERS ON THIS PROJECT ARE

WATER – CITY OF EDEN

SANITARY SEWER – CITY OF EDEN

GAS (DISTRIBUTION) – PNG

COMMUNICATION – BRIGHTSPEED

ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS, EXCEPT AS SHOWN ON THE PLANS.

RIGHT-OF-WAY MARKERS:

ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY OTHERS.

2024 ROADWAY ENGLISH STANDARD DRAWINGS

The following Roadway Standards as appear in "Roadway Standard Drawings" Contracts Standards and Development Unit – N. C. Department of Transportation – Raleigh, N. C., Dated January 16, 2024 are applicable to this project and by reference hereby are considered a part of these plans:

STD.NO.	TITLE
DIVISION 2	– EARTHWORK
200.02	Method of Clearing – Method II
225.02	Guide for Grading Subgrade – Secondary and Local
225.04	Method of Obtaining Superelevation – Two Lane Pavement
275.01	Rock Plating

DIVISION 3	– PIPE CULVERTS
300.01	Method of Pipe Installation (Use Details in Lieu of Standards for Sheets 1 and 2 of 2)

DIVISION 6	– ASPHALT BASES AND PAVEMENTS
654.01	Pavement Repairs

DIVISION 8	– INCIDENTALS
840.00	Concrete Base Pad for Drainage Structures
840.01	Brick Catch Basin – 12" thru 54" Pipe
840.02	Concrete Catch Basin – 12" thru 54" Pipe
840.03	Frame, Grates and Hood – for Use on Standard Catch Basin
840.17	Concrete Grated Drop Inlet Type 'A' – 12" thru 72" Pipe
840.24	Frames and Narrow Slot Sag Grates
840.26	Brick Grated Drop Inlet Type 'A' – 12" thru 72" Pipe
840.66	Drainage Structure Steps
840.71	Concrete and Brick Pipe Plug
840.72	Pipe Collar
846.01	Concrete Curb, Gutter and Curb & Gutter
848.02	Driveway Turnout – Radius Type
862.01	Guardrail Placement (Use Details in Lieu of Standards for Sheets 4, 6, 12, and 14 of 15)
862.02	Guardrail Installation

CONVENTIONAL PLAN SHEET SYMBOLS

*Note: Not to Scale*

BOUNDARIES AND PROPERTY:

State Line	
County Line	
Township Line	
City Line	
Reservation Line	
Property Line	
Existing Iron Pin (EIP)	
Computed Property Corner	
Existing Concrete Monument (ECM)	
Parcel/Sequence Number	
Existing Fence Line	
Proposed Woven Wire Fence	
Proposed Chain Link Fence	
Proposed Barbed Wire Fence	
Existing Wetland Boundary	
Proposed Wetland Boundary	
Existing Endangered Animal Boundary	
Existing Endangered Plant Boundary	
Existing Historic Property Boundary	
Known Contamination Area: Soil	
Potential Contamination Area: Soil	
Known Contamination Area: Water	
Potential Contamination Area: Water	
Contaminated Site: Known or Potential	
BUILDINGS AND OTHER CULTURE:	
Gas Pump Vent or U/G Tank Cap	
Sign	
Well	
Small Mine	
Foundation	
Area Outline	
Cemetery	
Building	
School	
Church	
Dam	
HYDROLOGY:	
Stream or Body of Water	
Hydro, Pool or Reservoir	
Jurisdictional Stream	
Buffer Zone 1	
Buffer Zone 2	
Flow Arrow	
Disappearing Stream	
Spring	
Wetland	
Proposed Lateral, Tail, Head Ditch	
False Sump	

RAILROADS:

Standard Gauge	
RR Signal Milepost	
Switch	
RR Abandoned	
RR Dismantled	

RIGHT OF WAY & PROJECT CONTROL:

Primary Horiz Control Point	
Primary Horiz and Vert Control Point	
Secondary Horiz and Vert Control Point	
Vertical Benchmark	
Existing Right of Way Monument	
Proposed Right of Way Monument (Rebar and Cap)	
Proposed Right of Way Monument (Concrete)	
Existing Permanent Easement Monument	
Proposed Permanent Easement Monument (Rebar and Cap)	
Existing C/A Monument	
Proposed C/A Monument (Rebar and Cap)	
Proposed C/A Monument (Concrete)	
Existing Right of Way Line	
Proposed Right of Way Line	
Existing Control of Access Line	
Proposed Control of Access Line	
Proposed ROW and CA Line	
Existing Easement Line	
Proposed Temporary Construction Easement	
Proposed Temporary Drainage Easement	
Proposed Permanent Drainage Easement	
Proposed Permanent Drainage/Utility Easement	
Proposed Permanent Utility Easement	
Proposed Temporary Utility Easement	
Proposed Aerial Utility Easement	

ROADS AND RELATED FEATURES:

Existing Edge of Pavement	
Existing Curb	
Proposed Slope Stakes Cut	
Proposed Slope Stakes Fill	
Proposed Curb Ramp	
Existing Metal Guardrail	
Proposed Guardrail	
Existing Cable Guiderail	
Proposed Cable Guiderail	
Equality Symbol	
Pavement Removal	
VEGETATION:	
Single Tree	
Single Shrub	
Hedge	

Woods Line	
Orchard	
Vineyard	

EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	
Bridge Wing Wall, Head Wall and End Wall	
MINOR:	
Head and End Wall	
Pipe Culvert	
Footbridge	
Drainage Box: Catch Basin, DI or JB	
Paved Ditch Gutter	
Storm Sewer Manhole	
Storm Sewer	

UTILITIES:

\* SUE – Subsurface Utility Engineering  
LOS – Level of Service – A,B,C or D (Accuracy)

POWER:	
Existing Power Pole	
Proposed Power Pole	
Existing Joint Use Pole	
Proposed Joint Use Pole	
Power Manhole	
Power Line Tower	
Power Transformer	
U/G Power Cable Hand Hole	
H-Frame Pole	
U/G Power Line Test Hole (SUE – LOS A)*	
U/G Power Line (SUE – LOS B)*	
U/G Power Line (SUE – LOS C)*	
U/G Power Line (SUE – LOS D)*	

TELEPHONE:

Existing Telephone Pole	
Proposed Telephone Pole	
Telephone Manhole	
Telephone Pedestal	
Telephone Cell Tower	
U/G Telephone Cable Hand Hole	
U/G Telephone Test Hole (SUE – LOS A)*	
U/G Telephone Cable (SUE – LOS B)*	
U/G Telephone Cable (SUE – LOS C)*	
U/G Telephone Cable (SUE – LOS D)*	
U/G Telephone Conduit (SUE – LOS B)*	
U/G Telephone Conduit (SUE – LOS C)*	
U/G Telephone Conduit (SUE – LOS D)*	
U/G Fiber Optics Cable (SUE – LOS B)*	
U/G Fiber Optics Cable (SUE – LOS C)*	
U/G Fiber Optics Cable (SUE – LOS D)*	

WATER:

Water Manhole	
Water Meter	
Water Valve	
Water Hydrant	
U/G Water Line Test Hole (SUE – LOS A)*	
U/G Water Line (SUE – LOS B)*	
U/G Water Line (SUE – LOS C)*	
U/G Water Line (SUE – LOS D)*	
Above Ground Water Line	

TV:

TV Pedestal	
TV Tower	
U/G TV Cable Hand Hole	
U/G TV Test Hole (SUE – LOS A)*	
U/G TV Cable (SUE – LOS B)*	
U/G TV Cable (SUE – LOS C)*	
U/G TV Cable (SUE – LOS D)*	
U/G Fiber Optic Cable (SUE – LOS B)*	
U/G Fiber Optic Cable (SUE – LOS C)*	
U/G Fiber Optic Cable (SUE – LOS D)*	

GAS:

Gas Valve	
Gas Meter	
U/G Gas Line Test Hole (SUE – LOS A)*	
U/G Gas Line (SUE – LOS B)*	
U/G Gas Line (SUE – LOS C)*	
U/G Gas Line (SUE – LOS D)*	
Above Ground Gas Line	

SANITARY SEWER:

Sanitary Sewer Manhole	
Sanitary Sewer Cleanout	
U/G Sanitary Sewer Line	
Above Ground Sanitary Sewer	
SS Force Main Line Test Hole (SUE – LOS A)*	
SS Force Main Line (SUE – LOS B)*	
SS Force Main Line (SUE – LOS C)*	
SS Force Main Line (SUE – LOS D)*	


MISCELLANEOUS:

Utility Pole	
Utility Pole with Base	
Utility Located Object	
Utility Traffic Signal Box	
Utility Unknown U/G Line (SUE – LOS B)*	
U/G Tank; Water, Gas, Oil	
Underground Storage Tank, Approx. Loc.	
A/G Tank; Water, Gas, Oil	
Geoenvironmental Boring	
Abandoned According to Utility Records	
End of Information	




FINAL PAVEMENT SCHEDULE	
C1	PROP. APPROX. 1 1/2" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YARD.
C2	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YARD IN EACH OF TWO LAYERS.
C3	PROP. VARIABLE DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B AT AN AVERAGE RATE OF 110 LBS. PER SQ. YARD PER INCH. DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 1" IN DEPTH OR GREATER THAN 1.5" IN DEPTH.
D1	PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YARD.
D2	PROP. VARIABLE DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C AT AN AVERAGE RATE OF 114 LBS. PER SQ. YARD PER INCH. DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 2.5" IN DEPTH OR GREATER THAN 4" IN DEPTH.
E1	PROP. APPROX. 4" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YARD.
E2	PROP. VARIABLE DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0C AT AN AVERAGE RATE OF 114 LBS. PER SQ. YARD PER INCH. DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5.5" IN DEPTH.
J	8" AGGREGATE BASE COURSE
R1	2'-6" CURB AND GUTTER
T	EARTH MATERIAL
U	EXISTING PAVEMENT
V	INCIDENTAL MILLING
W	WEDGING


ALL PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE



DETAIL FOR INCIDENTAL MILLING



Detail Showing Method of Wedging




TYPICAL SECTION NO. 1

-L- SR 1785 (CHURCH ST)

USE TYPICAL SECTION NO. 1

-L- STA. 10+70.00 TO STA. 11+90.00  
-L- STA. 13+30.00 TO STA. 14+75.00




TYPICAL SECTION NO. 2

-L- SR 1785 (CHURCH ST)

USE TYPICAL SECTION NO. 2

-L- STA. 11+90.00 TO STA. 13+30.00



TYPICAL SECTION NO. 3

-Y1- CARROLL ST  
-Y2- PARK RD  
-Y3- SHORT MORGAN ST

USE TYPICAL SECTION NO. 3

-Y1- STA. 10+24.42 TO STA. 11+00.00  
-Y2- STA. 10+70.00 TO STA. 11+38.50  
-Y3- STA. 10+60.00 TO STA. 11+05.88



HNTB NORTH CAROLINA, P.C.  
4000 CENTER AT NORTH HILLS ST.  
SUITE 200  
RALEIGH, NORTH CAROLINA 27609  
NC LICENSE NO: C-1554

PROJECT REFERENCE NO.


BP7.C001

SHEET NO.

2A-1


RW SHEET NO.

ROADWAY DESIGN  
ENGINEER



DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

PROJECT REFERENCE NO.	SHEET NO.
BP7.C001	2C-1



USE FLARE RATE AS THE CONTROL IF THE "N<sub>1</sub>" DISTANCE IS NOT OBTAINED.  
("N<sub>1</sub>" IS BASED ON SHOULDER WIDTHS IN THE ROADWAY DESIGN MANUAL)

SEE STD. 862.03 FOR STRUCTURE ANCHOR UNITS

FOR POSTED SPEEDS ≥ 45MPH USE GREU TYPE TL-3  
FOR POSTED SPEEDS < 45MPH USE GREU TYPE TL-2

GUARDRAIL LENGTH OF NEED (X) IS CALCULATED BASED ON THE AASHTO ROADSIDE DESIGN GUIDE.

STATE OF  
NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

ROADWAY DETAIL DRAWING FOR  
**GUARDRAIL PLACEMENT**



**LENGTHS AND OFFSETS FOR PROPOSED GUARDRAIL AT TWO LANE - TWO WAY LOCATIONS**

SHEET 4 OF 15

**862D01**

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED


**CONTRACTS STANDARDS  
AND DEVELOPMENT UNIT**

Office 919-707-6950 FAX 919-250-4119

**SEE TITLE BLOCK**

ORIGINAL BY: S.CALHOUN DATE: 7-25-2024  
MODIFIED BY: DATE:   
CHECKED BY: DATE:   
FILE SPEC.:





STATE OF  
NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

ROADWAY DETAIL DRAWING FOR  
**GUARDRAIL PLACEMENT**  
GUARDRAIL TREATMENT AT CURB AND GUTTER



SHEET 12 OF 15  
**862D01**

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

**CONTRACTS STANDARDS  
AND DEVELOPMENT UNIT**  
Office 919-707-6950 FAX 919-250-4119

**SEE TITLE BLOCK**

ORIGINAL BY: S.CALHOUN	DATE: 7-25-2024
MODIFIED BY:	DATE:
CHECKED BY:	DATE:
FILE SPEC.:	

**HNTB** HNTB NORTH CAROLINA, P.C.  
4000 CENTER AT NORTH HILLS ST.  
SUITE 500  
RALEIGH, NORTH CAROLINA 27609  
NC LICENSE NO: C-1554

## **PAVEMENT REMOVAL SUMMARY (IN SQUARE YARDS)**

STATION	STATION	UNCL. EXCAV.	EMBANK. +%	BORROW	WASTE
-L- STA 10+70.00	-L- STA 14+75.00	99	723	624	
-Y1- STA 10+50.00	-Y1- STA 11+00.00	13	7		6
-Y2- STA 10+70.00	-Y2- STA 11+00.00	7	6		1
-Y3- STA 10+60.00	-Y3- STA 11+00.00	11	8		3
TOTALS:		130	744	624	10
WASTE IN LIEU OF BORROW:				-10	-10
PROJECT TOTALS:		130	744	614	
EST. 5% TO REPLACE TOP SOIL ON BORROW PIT				30	
GRAND TOTALS:		130	744	644	
SAY:		150		650	

Note: Approximate quantities only. Unclassified Excavation, Borrow Excavation, Fine Grading, Clearing and Grubbing, and Removal of Existing Pavement will be paid for at the contract lump sum price for "Grading."

Earthwork quantities are calculated by the roadway designer.

SURVEY LINE	STATION	STATION	LOCATION LT/RT/CL	YD
-L-	11 + 90.00	13 + 30.00	CL	711
			TOTAL:	711
			SAY:	725

PARCEL NO.	PROPERTY OWNERS NAMES	PROP. RW	PERM. UTILITY EASE.	PERM. DRAIN. UTILITY EASE.	PERM. DRAIN. EASE.	CONST. EASE.
1	JOEY CLARK					276.47 SF
2	SANDRA ALVAREZ					1816.08 SF
3	MAYNARD WAYNE RIESON ESTATE			0.14 AC		2128.13 SF
4	ROGER N PIERCE, JR					960.26 SF
5	CHANCE E LAWRENCE					869.24 SF
6	MYRTLE CLARK	244.71 SF				216.61 SF
7	EDEN PRESERVATION SOCIETY			0.14 AC		0.21 AC


"N" = DISTANCE FROM EDGE OF LANE TO FACE OF GUARDRAIL.  
 TOTAL SHOULDER WIDTH = DISTANCE FROM EDGE OF TRAVEL LANE TO SHOULDER BREAK POINT.  
 FLARE LENGTH = DISTANCE FROM LAST SECTION OF PARALLEL GUARDRAIL TO END OF GUARDRAIL.  
 W = TOTAL WIDTH OF FLARE FROM BEGINNING OF TAPER TO END OF GUARDRAIL.  
 G = GATING IMPACT ATTENUATOR TL-3  
 NG = NON-GATING IMPACT ATTENUATOR TL-3

[illegible]














STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	BP7.C001	RW01	07

TIP PROJECT: BP7-C001


STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

SURVEY CONTROL, EXISTING CENTERLINES,  
RIGHT OF WAY, EASEMENTS AND PROPERTY TIES

**ROCKINGHAM COUNTY**



4



**DATUM DESCRIPTION**

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "BL-101" WITH NAD 83/NA2011 STATE PLANE GRID COORDINATES OF NORTHING: 1,003,903.2648(ft) EASTING: 1,776,392.6803(ft) ELEVATION: 539.020(ft) THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 1.000091649 THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "BL-101" TO -L- STATION 10+70.00 IS S 84°22'22.5" W 269.65(ft) ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES VERTICAL DATUM USED IS NAVD 88

Prepared in the Office of:


**GEL SOLUTIONS**  
an Affiliate of THE GEL GROUP, INC.  
111 CREEK RIDGE ROAD  
SUITE C  
GREENSBORO, NC 27406  
(336) 516-9840  
WWW.GEL-SOLUTIONS.COM

2018 STANDARD SPECIFICATIONS

**RIGHT OF WAY DATE:**  
12/01/2023


**LETTING DATE:**  
10/7/2025

**PROFESSIONAL LAND SURVEYOR**



*H. Icenhour, Jr.*  
SIGNATURE:


Digitally signed by H. Icenhour, Jr.  
Date: 2024.03.20 15:04:24 -04'00'







# SURVEY CONTROL SHEET

W/EXISTING CENTERLINE ALIGNMENTS PRIOR TO CONSTRUCTION




SEE SHEET RW2C-3  
FOR FURTHER  
ALIGNMENT DETAILS

PROJECT REFERENCE NO.	SHEET NO.
BP7-C001	RW02C-1
Location and Surveys	
<b>GEL SOLUTIONS</b> 111-C CREEKRIDGE ROAD GREENSBORO, NC 27406	
PROJECT SURVEYOR  	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

I, Parks H Icenhour Jr, PLS, certify that the Project Control was performed under my supervision from an actual GPS survey made under my supervision and the following information was used to perform the survey:

Class of survey: **AA**  
Type of GPS field procedure:  
Dates of survey: Unknown  
Datum/Epoch:NAD83/NA2011  
Published/Fixed-control use: N/A  
Localized around: BL-101  
Northing:1003903.2648  
Easting:1776392.6803  
Combined grid factor:1.000091649  
Geoid model:12BNC  
Units:FEET

I also certify that the Baseline Control for this project was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:20,000 (Class AA) and Vertical accuracy to Class A. Field work was performed from 5-5-22 to 5-18-2022 , and all coordinates are based on NAD 83/2011 and all elevations are based on NAVD 88; that this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 20th day of May, 2022.  
Date:  
  
Professional Land Surveyor of North Carolina  
2022.05.20  
11:56:33 -04'00'

## NOTES:

- PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
- THE SURVEY CONTROL DATA FOR THIS PROJECT HAS BEEN COMPILED FROM VARIOUS SOURCES. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.

REVISIONS

SURVEY CONTROL SHEET  
W/EXISTING CENTERLINE ALIGNMENTS PRIOR TO CONSTRUCTION

BL	POINT	DESC.	NORTH	EAST	ELEVATION
3		BL - 3	1003765.3850	1775884.9350	571.79
102		BL - 102	1003883.0345	1776212.9851	542.20
101		BL - 101	1003903.2648	1776392.6803	539.02
1		B3509 BL - 1	1003656.6040	1776619.7380	552.32

BY1	POINT	DESC.	NORTH	EAST	ELEVATION
A102		BL - 102	1003883.0345	1776212.9851	542.20
4		BY1 - 4	1003608.7520	1776051.8510	557.49

BY2	POINT	DESC.	NORTH	EAST	ELEVATION
5		BY2 - 5	1004236.3040	1776211.2180	539.85
B102		BL - 102	1003883.0345	1776212.9851	542.20

BY3	POINT	DESC.	NORTH	EAST	ELEVATION
6		BY3 - 6	1004181.8690	1776485.1700	555.05
A101		BL - 101	1003903.2648	1776392.6803	539.02

\*\*\*\*\*  
BM1 ELEVATION = 560.71  
N 1003899 E 1776604  
BL STATION 11+75.00 153 LEFT  
SPIKE SET IN 30" OAK TREE  
\*\*\*\*\*

\*\*\*\*\*  
BM2 ELEVATION = 550.03  
N 1003816 E 1776138  
BL STATION 7+55.00 38 RIGHT  
SPIKE SET IN POWER POLE  
\*\*\*\*\*

PROJECT REFERENCE NO.  
BP7-C001

SHEET NO.  
RW02-2

Location and Surveys

GEL

SOLUTIONS

111-C CREEKRIDGE ROAD  
GREENSBORO, NC 27406

PROJECT SURVEYOR

SEAL  
L-3996


GEL ENGINEERING  
OF NC, INC  
NO. C-1938

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

I, Parks H Icenhour Jr, PLS, certify that the Project Control was performed under my supervision from an actual GPS survey made under my supervision and the following information was used to perform the survey:

Class of survey: **AA**  
Type of GPS field procedure:  
Dates of survey: Unknown  
Datum/Epoch:NAD83/NA2011  
Published/Fixed-control use: N/A  
Localized around: BL-101  
Northing:1003903.2648  
Easting:1776392.6803  
Combined grid factor:1.000091649  
Geoid model:12BNC  
Units:FEET

I also certify that the Baseline Control for this project was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:20,000 (Class AA) and Vertical accuracy to Class A. Field work was performed from 5-5-22 to 5-18-2022 , and all coordinates are based on NAD 83/2011 and all elevations are based on NAVD 88; that this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 20th day of May, 2022,  
Date: 2022.05.20  
  
Professional Land Surveyor 11-557-13 -04'00"

NOTES:

1. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
2. THE SURVEY CONTROL DATA FOR THIS PROJECT HAS BEEN COMPILED FROM VARIOUS SOURCES. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.



REVISIONS

SURVEY CONTROL SHEET  
W/ EXISTING CENTERLINE ALIGNMENTS PRIOR TO CONSTRUCTION

EL POINT	N	E	BEARING	DIST	DELTA	D	L	T	R
PC	1003807.953	1775990.548							
CURVE			N 62°37'42.4" E	144.88	07°05'58.1"(RT)	04°53'49.5"	144.97	72.58	1170.00
PT	1003874.563	1776119.209							
LINE			N 66°10'41.4" E	67.02					
PC	1003901.631	1776180.516							
CURVE			N 73°59'23.7" E	108.73	15°37'24.5"(RT)	14°19'26.2"	109.07	54.88	400.00
PT	1003931.620	1776285.033							
LINE			N 81°48'05.9" E	46.22					
PC	1003938.211	1776330.776							
CURVE			S 75°19'11.9" E	93.31	45°45'24.3"(RT)	47°44'47.3"	95.83	50.64	120.00
PT	1003914.565	1776421.037							
LINE			S 52°26'29.7" E	127.63					
PC	1003836.764	1776522.216							
CURVE			S 42°10'03.0" E	71.34	20°32'53.5"(RT)	28°38'52.4"	71.73	36.25	200.00
PT	1003783.885	1776570.108							
LINE			S 31°53'36.2" E	116.51					
POT	1003684.968	1776631.663							

EY1 POINT	N	E	BEARING	DIST
POT	1003910.351	1776201.920		
LINE			S 23°15'00.4" W	285.93
POT	1003647.641	1776089.051		

EY2 POINT	N	E	BEARING	DIST	DELTA	D	L	T	R
POT	1004263.932	1776239.342							
LINE			S 00°00'03.3" W	14.07					
PC	1004249.859	1776239.342							
CURVE			S 03°57'35.3" W	69.04	07°55'04.0"(RT)	11°27'33.0"	69.10	34.60	500.00
PT	1004180.983	1776234.574							
LINE			S 07°55'07.3" W	110.29					
PC	1004071.746	1776219.379							
CURVE			S 06°17'53.6" W	56.56	03°14'27.6"(LT)	05°43'46.5"	56.57	28.29	1000.00
PT	1004015.529	1776213.175							
LINE			S 04°40'39.8" W	104.52					
POT	1003911.361	1776204.651							

EY3 POINT	N	E	BEARING	DIST	DELTA	D	L	T	R
POT	1004214.768	1776517.046							
LINE			S 29°48'45.9" W	21.90					
PC	1004195.765	1776506.157							
CURVE			S 25°56'43.9" W	80.93	07°44'03.9"(LT)	09°32'57.5"	80.99	40.56	600.00
PT	1004122.989	1776470.747							
LINE			S 22°04'42.0" W	65.64					
PC	1004062.164	1776446.076							
CURVE			S 25°30'43.3" W	59.89	06°52'02.5"(RT)	11°27'33.0"	59.93	30.00	500.00
PT	1004008.110	1776420.280							
LINE			S 28°56'44.5" W	83.44					
POT	1003935.090	1776379.894							

EY4 POINT	N	E	BEARING	DIST
POT	1003960.848	1776612.305		
LINE			S 29°48'08.5" W	155.41
POT	1003825.995	1776535.067		

PROJECT REFERENCE NO.  
BP7-C001

SHEET NO.  
RW02-3

Location and Surveys

GEL

SOLUTIONS

111-C CREEKRIDGE ROAD  
GREENSBORO, NC 27406

PROJECT SURVEYOR

SEAL  
L-3996

PROFESSIONAL  
LAND SURVEYOR  
H. ICENHOUR

STATE OF NORTH CAROLINA

GEL  
ENGINEERING  
OF NC, INC  
NO. C-1938

CERTIFICATE OF AUTHORIZATION

STATE OF NORTH CAROLINA

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

I, Parks H Icenhour Jr, PLS, certify that the Project Control was performed under my supervision from an actual GPS survey made under my supervision and the following information was used to perform the survey:

Class of survey: **AA**  
Type of GPS field procedure:  
Dates of survey: Unknown  
Datum/Epoch:NAD83/NA2011  
Published/Fixed-control use: N/A  
Localized around: BL-101  
Northing:1003903.2648  
Easting:1776392.6803  
Combined grid factor:1.000091649  
Geoid model:12BNC  
Units:FEET

I also certify that the Baseline Control for this project was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:20,000 (Class AA) and Vertical accuracy to Class A. Field work was performed from 5-5-22 to 5-18-2022 , and all coordinates are based on NAD 83/2011 and all elevations are based on NAVD 88; that this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 20th day of May, 2022, 

Date:  
2022.05.20  
11:57:51  
-0400

Parks H. Icenhour Jr

Professional Land Surveyor L-3996

NOTES:

1. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
2. THE SURVEY CONTROL DATA FOR THIS PROJECT HAS BEEN COMPILED FROM VARIOUS SOURCES. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.





## REVISIONS

ROW MARKER IRON PIN AND CAP-E				
ALIGN	STATION	OFFSET	NORTH	EAST
Y1	10+82.00	24.73	1003841.5524	1776145.4413

ROW MARKER PERMANENT EASEMENT-E				
ALIGN	STATION	OFFSET	NORTH	EAST
Y2	10+55.00	-26.23	1004008.9506	1776238.9555

NOTES:

1. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.
2. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
3. RIGHT OF WAY MONUMENTATION ESTABLISHED 2-22-24 TO 3-12-24 .


I, Parks H Icenhour Jr., certify that the right of way and permanent easement monumentation for this project shown herein was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:10,000 (Class A). Field work was performed from 2-22-24 to 3-12-24, and all coordinates are based on NAD83/2011; That this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 20th day of March, 2024.

Digitally signed by  
Parks H. Icenhour, Jr.  
Date: 2024.03.20  
15:05:07 -04'00'  
Professional Land Surveyor L-3996



REVISIONS



PI Sta 10+32.21 Δ = 3° 09' 13.4" (RT) D = 4° 53' 49.5" L = 64.40' T = 32.21' R = 1170.00' SE = EXIST	PI Sta 11+86.03 Δ = 15° 35' 01.4" (RT) D = 7° 44' 33.6" L = 201.27' T = 101.26' R = 740.00' SE = 6% RO = 192' V = 15 MPH	PI Sta 13+36.73 Δ = 45° 47' 47.5" (RT) D = 47° 44' 47.3" L = 95.92' T = 50.69' R = 1200.00' SE = 6% RO = 192' V = 15 MPH	PI Sta 15+45.84 Δ = 20° 32' 53.5" (RT) D = 28° 38' 52.4" L = 71.73' T = 50.69' R = 200.00' SE = EXIST	PI Sta 10+25.28 Δ = 2° 53' 45.9" (LT) D = 11° 27' 33.0" L = 50.55' T = 25.28' R = 1000.00' SE = EXIST	PI Sta 10+20.45 Δ = 4° 41' 02.3" (RT) D = 11° 27' 33.0" L = 40.88' T = 20.45' R = 500.00' SE = EXIST
--	--	--	---	---	--

NOTES:

1. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.
2. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
3. RIGHT OF WAY MONUMENTATION ESTABLISHED \_\_\_\_ TO \_\_\_\_ .

PROJECT REFERENCE NO.  
BP7-C001

SHEET NO.  
RW04

Location and Surveys

GEL SOLUTIONS

an Affiliate of THE GEL GROUP, INC.  
111 CREEK RIDGE ROAD  
SUITE C  
GREENSBORO NC 27406  
(336) 516-9840  
WWW.GEL-SOLUTIONS.COM

PROJECT SURVEYOR

NORTH CAROLINA  
PROFESSIONAL  
SEAL  
L-3996  
LAND SURVEYOR

NORTH CAROLINA  
GEL ENGINEERING  
OF NC, INC.  
NO. C-1938  
CERTIFICATE OF AUTHORIZATION

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

I, Parks H Icenhour Jr., certify that the right of way and permanent easement monumentation for this project shown herein was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:10,000 (Class A). Field work was performed from 2-22-24 to 3-12-24, and all coordinates are based on NAD83/2011. That this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 20th day of March, 2024.


*Parks H. Icenhour Jr.*  
Digitally signed by Parks H. Icenhour, Jr.  
Date: 2024.03.20 15:04:48 -04'00'

Professional Land Surveyor L-3996



STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

TRANSPORTATION MANAGEMENT PLAN  
ROCKINGHAM COUNTY



LOCATION: REPLACE EXISTING CULVERT ON SR 1785 (CHURCH ST)  
TYPE OF WORK: GRADING, DRAINAGE, PAVING, AND CULVERT


PLANS PREPARED BY: HNTB

H. SHYU, P.E.  
PROJECT ENGINEER

G. RODRIGUEZ, E.I.  
PROJECT DESIGN ENGINEER

NCDOT CONTACTS:

DAWN MCPHERSON  
DIVISION TRAFFIC ENGINEER



INDEX OF SHEETS

SHEET NO.	TITLE
TMP-1	TITLE SHEET, VICINITY, INDEX OF SHEETS, AND LIST OF APPLICABLE ROADWAY STANDARD DRAWINGS
TMP-1A	GENERAL NOTES
TMP-2	OFFSITE DETOUR AND LEGEND
TMP-2A	TEMPORARY SIGN DESIGN
TMP-3	PHASING AND DETAIL
TMP-4	TEMPORARY PAVEMENT MARKINGS

ROADWAY STANDARD DRAWINGS


THE FOLLOWING ROADWAY STANDARDS AS SHOWN IN "ROADWAY STANDARD DRAWINGS" CONTRACT STANDARDS AND DEVELOPMENT UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C. DATED JAN 2024 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
1101.01	WORK ZONE ADVANCE WARNING SIGNS
1101.02	TEMPORARY LANE CLOSURES
1101.03	TEMPORARY ROAD CLOSURES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.01	STATIONARY WORK ZONE SIGNS
1110.02	PORTABLE WORK ZONE SIGNS
1115.01	FLASHING ARROW BOARDS
1130.01	DRUMS
1135.01	CONES
1145.01	BARRICADES
1150.01	FLAGGERS
1205.01	PAVEMENT MARKINGS - LINE TYPES & OFFSETS
1205.02	PAVEMENT MARKINGS - TWO LANE & MULTILANE ROADWAYS
1205.04	PAVEMENT MARKINGS - INTERSECTIONS
1205.05	PAVEMENT MARKINGS - TURN LANES
1205.08	PAVEMENT MARKINGS - SYMBOLS AND WORD MESSAGES
1250.01	RAISED PAVEMENT MARKERS - INSTALLATION SPACING
1251.01	RAISED PAVEMENT MARKERS - PERMANENT AND TEMPORARY

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

**HNTB**

HNTB NORTH CAROLINA, P.C.  
4000 Center at North Hills Street  
Suite 500  
Raleigh, North Carolina 27609  
NC License No: C-1554

APPROVED:   
DATE: 3/10/2025

SEAL



SHEET NO.  
TMP-1

BP7.C001

TIP PROJECT:



GENERAL NOTES

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS, AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS OR RESULT IN DUPLICATE OR UNDESIRE

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT EXCEPT WHEN OTHERWISE NOTED IN THE PLAN OR DIRECTED BY THE ENGINEER.

TIME RESTRICTIONS

A) DO NOT CLOSE OR NARROW TRAVEL LANES AS FOLLOWS:

ROAD NAME	DAY AND TIME RESTICTIONS
-L- SR 1785 (CHURCH STREET)	MONDAY THRU SUNDAY 7:00 AM-9:00AM AND 4:00 PM-6:00 PM

B) DO NOT CLOSE OR NARROW TRAVEL LANES DURING HOLIDAYS AND SPECIAL EVENTS AS FOLLOWS:

ROAD NAME
ANY ROAD
HOLIDAY
1. FOR ANY UNEXPECTED OCCURRENCE THAT CREATES UNUSUALLY HIGH TRAFFIC VOLUMES, AS DIRECTED BY THE ENGINEER.
2. FOR NEW YEAR'S, BETWEEN THE HOURS OF 7:00 A.M. DECEMBER 31ST TO 6:00 P.M. JANUARY 2ND. IF NEW YEAR'S DAY IS ON A FRIDAY, SATURDAY, SUNDAY, OR MONDAY THEN UNTIL 6:00 P.M. THE FOLLOWING TUESDAY.
3. FOR EASTER, BETWEEN THE HOURS OF 7:00 A.M. THURSDAY AND 6:00 P.M. MONDAY.
4. FOR MEMORIAL DAY, BETWEEN THE HOURS OF 7:00 A.M. FRIDAY TO 6:00 P.M. TUESDAY.
5. FOR INDEPENDENCE DAY, BETWEEN THE HOURS OF 7:00 A.M. THE DAY BEFORE INDEPENDENCE DAY AND 6:00 P.M. THE DAY AFTER INDEPENDENCE DAY.  IF INDEPENDENCE DAY IS ON A FRIDAY, SATURDAY, SUNDAY OR MONDAY THEN BETWEEN THE HOURS OF 7:00 A.M. THE THURSDAY BEFORE INDEPENDENCE DAY AND 6:00 P.M. THE TUESDAY AFTER INDEPENDENCE DAY.
6. FOR LABOR DAY, BETWEEN THE HOURS OF 7:00 A.M. FRIDAY AND 6:00 P.M. TUESDAY.
7. FOR THANKSGIVING DAY, BETWEEN THE HOURS OF 7:00 A.M. TUESDAY TO 6:00 P.M. MONDAY.
8. FOR CHRISTMAS, BETWEEN THE HOURS OF 7:00 A.M. THE FRIDAY BEFORE THE WEEK OF CHRISTMAS DAY AND 6:00 P.M. THE FOLLOWING TUESDAY AFTER THE WEEK OF CHRISTMAS.

C) DO NOT CONDUCT ANY HAULING OPERATIONS AGAINST THE FLOW OF TRAFFIC OF AN OPEN TRAVELWAY UNLESS THE HAULING OPERATION IS PROTECTED BY BARRIER OR GUARDRAIL OR AS DIRECTED BY THE ENGINEER.

LANE AND SHOULDER CLOSURE REQUIREMENTS

- D) REMOVE LANE CLOSURE DEVICES FROM THE LANE WHEN WORK IS NOT BEING PERFORMED BEHIND THE LANE CLOSURE OR WHEN A LANE CLOSURE IS NO LONGER NEEDED OR AS DIRECTED BY THE ENGINEER.
- E) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN 15 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN SHOULDER USING ROADWAY STANDARD DRAWING NO. 1101.04 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL OR A LANE CLOSURE IS INSTALLED.
- F) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING ON THE SHOULDER ADJACENT TO AN UNDIVIDED FACILITY AND WITHIN 5 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN TRAVEL LANE USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL.
- G) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN A LANE OF TRAVEL OF AN UNDIVIDED OR DIVIDED FACILITY, CLOSE THE LANE ACCORDING TO THE TRAFFIC CONTROL PLANS, ROADWAY STANDARD DRAWINGS, OR AS DIRECTED BY THE ENGINEER. CONDUCT THE WORK SO THAT ALL PERSONNEL AND/OR EQUIPMENT REMAIN WITHIN THE CLOSED TRAVEL LANE.

PAVEMENT EDGE DROP OFF REQUIREMENTS

- H) BACKFILL AT A 6:1 SLOPE UP TO THE EDGE AND ELEVATION OF EXISTING PAVEMENT IN AREAS ADJACENT TO AN OPENED TRAVEL LANE THAT HAS AN EDGE OF PAVEMENT DROP-OFF AS FOLLOWS:
- BACKFILL DROP-OFFS THAT EXCEED 2 INCHES ON ROADWAYS WITH POSTED SPEED LIMITS OF 45 MPH OR GREATER.
- BACKFILL DROP-OFFS THAT EXCEED 3 INCHES ON ROADWAYS WITH POSTED SPEED LIMITS LESS THAN 45 MPH.
- BACKFILL WITH SUITABLE COMPACTED MATERIAL, AS APPROVED BY THE ENGINEER, AT NO EXPENSE TO THE DEPARTMENT.
- I) DO NOT EXCEED A DIFFERENCE OF 2 INCHES IN ELEVATION BETWEEN OPEN LANES OF TRAFFIC FOR NOMINAL LIFTS OF 1.5 INCHES. INSTALL ADVANCE WARNING "UNEVEN LANES" SIGNS (W8-11) 200 FEET IN ADVANCE AND A MINIMUM OF EVERY HALF MILE THROUGHOUT THE UNEVEN AREA.

TRAFFIC PATTERN ALTERATIONS

J) NOTIFY THE ENGINEER THIRTY (30) CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION.

SIGNING

- K) INSTALL ADVANCE WORK ZONE WARNING SIGNS WHEN WORK IS WITHIN 40 FT FROM THE EDGE OF TRAVEL LANE AND NO MORE THAN THREE (3) DAYS PRIOR TO THE BEGINNING OF CONSTRUCTION.
- L) PROVIDE SIGNING AND DEVICES REQUIRED TO CLOSE THE ROAD ACCORDING TO THE ROADWAY STANDARD DRAWINGS AND TRAFFIC CONTROL PLANS
- M) PROVIDE SIGNING REQUIRED FOR THE OFFSITE DETOUR ROUTE AS SHOWN IN THE TRAFFIC CONTROL PLANS.
- N) ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY TRAFFIC PATTERN.

O) COVER OR REMOVE ALL SIGNS REQUIRED FOR THE OFF-SITE DETOUR WHEN THE DETOUR IS NOT IN OPERATION.

COVER OR REMOVE ALL SIGNS AND DEVICES REQUIRED TO CLOSE THE ROAD WHEN ROAD CLOSURE IS NOT IN OPERATION.

P) INSTALL BLACK ON ORANGE "DIP" SINGS (W8-2) AND/OR "BUMP" SIGN (W8-1) 200 FT IN ADVANCE OF THE UNEVEN AREA, OR AS DIRECTED BY THE ENGINEER

TRAFFIC CONTROL DEVICES

- Q) WHEN LANE CLOSURES ARE NOT IN EFFECT SPACE CHANNELIZING DEVICES IN WORK AREAS NO GREATER IN FEET THAN TWICE THE POSTED SPEED LIMIT (MPH) EXCEPT, 10 FT ON-CENTER IN RADII, AND 3 FT OFF THE EDGE OF AN OPEN TRAVELWAY. REFER TO STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES SECTIONS 1130 (DRUMS), 1135 (CONES) AND 1180 (SKINNY DRUMS) FOR ADDITIONAL REQUIREMENTS.
- R) PLACE TYPE III BARRICADES, WITH "ROAD CLOSED" SIGN R11-2 ATTACHED, OF SUFFICIENT LENGTH TO CLOSE ENTIRE ROADWAY.

PAVEMENT MARKINGS AND MARKERS

- Y) INSTALL TEMPORARY PAVEMENT MARKINGS AND TEMPORARY PAVEMENT MARKERS ON INTERIM LAYERS OF PAVEMENT AS FOLLOWS:
- | ROAD NAME               | MARKING | MARKER           |
|-------------------------|---------|------------------|
| -L- SR 1785 (CHURCH ST) | PAINT   | TEMPORARY RAISED |
- Z) PLACE ONE APPLICATION OF PAINT FOR TEMPORARY TRAFFIC PATTERNS. PLACE A SECOND APPLICATION OF PAINT SIX (6) MONTHS AFTER THE INITIAL APPLICATION AND EVERY SIX MONTHS AS DIRECTED BY THE ENGINEER.

AA) TIE PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.


MISCELLANEOUS

BB) IN THE EVENT OF LOOP REPLACEMENT, REFER TO THE CURRENT ITS AND SIGNALS DESIGN MANUAL AND SUBMIT A PLAN OF RECORD TO THE SIGNAL DESIGN SECTION.





HNTB NORTH CAROLINA, P.C.  
4000 Center at North Hills Street  
Suite 500  
Raleigh, North Carolina 27609  
NC License No: C-1554

APPROVED: <div>DESIGNED BY: Helen Shyu DP15975AB9E44EF</div>	
DATE: 3/10/2025	
SEAL	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	



GENERAL NOTES





SEE TMP-3 AND RSD 1101.03 (SHEET 1 OF 9)  
FOR ADDITIONAL TRAFFIC CONTROL  
DEVICES



HNTB NORTH CAROLINA, P.C.  
4000 Center at North Hills Street  
Suite 500  
Raleigh, North Carolina 27609  
NC License No: C-1554

### ***LEGEND***

## GENERAL



NORTH ARROW

## TRAFFIC CONTROL DEVICES






### BARRICADE (TYPE III)

## TEMPORARY SIGNING



STATIONARY SIGN





APPROVED:

DATE: 3/10/2025

Designed by:  
*Helen Shy*

0F15975A95E44E

SEAL



TRANSPORTATION  
MANAGEMENT PLAN

## OFFSITE DETOUR AND LEGEND

9:17:04 PM  
...\\BP7.C001+c\_TCP\_02\_detour.dgn  
3/10/2025

PROJ. REFERENCE NO.	SHEET NO.
BP7.C001	TMP-2A

[illegible][illegible]

APPROVED: _____ <small>Digitally signed by: Helen Shyu DN: c=US, o=North Carolina Department of Transportation, ou=North Carolina Department of Transportation, cn=Helen Shyu, email=Helen.Shyu@dot.nc.gov</small> DATE: 3/10/2025 _____	SEAL 	TRANSPORTATION MANAGEMENT PLAN  TEMPORARY SIGN DESIGN
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>		



PROJ. REFERENCE NO.	SHEET NO.
BP7.C001	TMP-3

PHASING

NOTES:

REPLACE MARKING AND RETURN TO THE CURRENT TRAFFIC PATTERN AT THE END OF EACH WORK PERIOD UNLESS OTHERWISE NOTED IN THE PHASING OR DIRECTED BY THE ENGINEER.

MAINTAIN VEHICULAR ACCESS TO ALL RESIDENCES AND BUSINESSES DURING THE LIFE OF THE CONTRACT UNLESS OTHERWISE NOTED IN THE PHASING OR DIRECTED BY THE ENGINEER.

COMPLETE ANY PROPOSED WIDENING IN SUCH A MANNER THAT PONDING OF WATER WILL NOT OCCUR IN THE TRAVEL LANE. THIS MAY REQUIRE A COMBINATION OF INSTALLATION OF PROPOSED PIPES, TEMPORARY PIPES, STEEL PLATES, TEMPORARY MEDIAN, AND OUTSIDE DITCHES.

PAVE PROPOSED CONSTRUCTION UP TO BUT NOT INCLUDING THE FINAL LAYER OF SURFACE COURSE, IN ALL PHASES UNTIL STATED TO INSTALL FINAL LAYER IN PHASING.

THE TERM RSD REFERS TO ROADWAY STANDARD DRAWINGS.

PHASE I

STEP 1: USING RSD 1101.01 (SHEET 3 OF 3), INSTALL ADVANCE WARNING SIGNS ON -L- (CHURCH STREET). 2 WEEKS BEFORE ROAD CLOSURE, INSTALL CMS ON EACH DIRECTION OF -L- IN THE PROJECT LIMITS WITH ADVANCED WARNING MESSAGE OF "ROAD WILL BE CLOSED XX/XX/XX THRU XX/XX/XX".

STEP 2: INSTALL AND COVER DETOUR SIGNS AS SHOWN ON THIS SHEET AND IN ACCORDANCE WITH RSD 1101.03 (SHEETS 1 OF 9).

STEP 3: UNCOVER DETOUR SIGNS, CLOSE -L- (CHURCH STREET) TO TRAFFIC AND CONSTRUCT PROPOSED CULVERT. KEEP ADJACENT Y-LINES OPEN: -Y1- CARROLL STREET, -Y2- PARK ROAD, AND -Y3- MORGAN STREET. USE BARRICADE TO CLOSE DRIVEWAY ADJACENT TO CULVERT, AND ONLY ALLOW ACCESS TO PROPERTY FROM CARROLL STREET.

PHASE II


STEP 1: UPON COMPLETION OF CULVERT, REPAIR PAVEMENT EXCEPT FOR THE FINAL LAYER OF SURFACE COURSE. INSTALL PROPOSED GUARDRAILS. PLACE TEMPORARY PAVEMENT MARKINGS AND OPEN -L- (CHURCH STREET) TO TRAFFIC.

STEP 2: USING RSD 1101.02 (SHEET 1 OF 19), CONSTRUCT -L- AND ADJACENT -Y- LINES.



PHASE III

STEP 1: USING RSD 1101.02 (SHEET 1 OF 19) AS NEEDED, PLACE FINAL LAYER OF SURFACE COURSE AND FINAL PAVEMENT MARKINGS AND MARKERS AS SHOWN ON PMP.

STEP 2: REMOVE ALL TRAFFIC CONTROL DEVICES AND OPEN -L- (CHURCH STREET) TO FINAL PATTERN.



SEE TMP-2 AND RSD 1101.03 (SHEET 1 OF 9)  
FOR ADDITIONAL TRAFFIC CONTROL  
DEVICES



9:48:29 PM  
\\BP7.C001.fc\_tcp\_03.phasing.dgn  
BMD/2025

HNTB

HNTB NORTH CAROLINA, P.C.  
4000 Center at North Hills Street  
Suite 500  
Raleigh, North Carolina 27609  
NC License No: C-1554

APPROVED: 

DESIGNED BY:

Helen Shyu

DP15975AB9E44EF

DATE: 3/10/2025

SEAL

NORTH CAROLINA

PROFESSIONAL

SEAL


042517

ENGINEER

HELEN SHYU

DOCUMENT NOT CONSIDERED FINAL

UNLESS ALL SIGNATURES COMPLETED



TRANSPORTATION  
MANAGEMENT PLAN

DETAIL AND  
PHASING

PROJ. REFERENCE NO.	SHEET NO.
BP7.C001	TMP - 4

LEGEND

TEMPORARY PAVEMENT MARKING

SYMBOL	DESCRIPTION	PAY ITEM
PAVEMENT MARKING LINES		PAINT (4")
P2	WHITE LANE LINE	
P4	3 FT.- 9FT./SP WHITE MINISKIP	
P13	YELLOW DOUBLE CENTER LINE	

PAVEMENT MARKING SYMBOLS & CHARACTERS

P70	LEFT TURN ARROW
P72	STRAIGHT ARROW

NOTE: FOR EACH PAINT PAVEMENT MARKING ITEM, REFER TO GENERAL NOTES FOR NUMBER OF APPLICATIONS.

PAVEMENT MARKERS

YELLOW & YELLOW	TEMPORARY RAISED MARKERS
CRYSTAL & RED	TEMPORARY RAISED MARKERS

PAVEMENT MARKINGS

---	EXISTING LINES
---	TEMPORARY LINES


PAVEMENT MARKING SYMBOLS

↑↩↪	PAVEMENT MARKING SYMBOLS
-----	--------------------------

↑↩↪	EXISTING MARKING SYMBOLS
-----	--------------------------

SIGNALS

	EXISTING		PROPOSED		TEMPORARY
--	----------	--	----------	--	-----------




---	EXIST. PVMT.
---	NORTH ARROW
---	PROPOSED PVMT.

9:47:03 PM  
\\TCP\BP7.C001 to TCP\_04.dgn  
BMD/2025


HNTB

HNTB NORTH CAROLINA, P.C.  
4000 Center at North Hills Street  
Suite 500  
Raleigh, North Carolina 27609  
NC License No: C-1554

APPROVED:   
DATE: 3/10/2025

SEAL

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED



TRANSPORTATION  
MANAGEMENT PLAN

TEMPORARY PAVEMENT  
MARKINGS



T.I.P.: BP7.C001

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION

PAVEMENT MARKING PLAN  
ROCKINGHAM COUNTY

LOCATION: REPLACE EXISTING CULVERT ON SR 1785 (CHURCH ST)

ROADWAY STANDARD DRAWING

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" -  
CONTRACT STANDARDS AND DEVELOPMENT UNIT - N.C. DEPARTMENT OF TRANSPORTATION -  
RALEIGH, N.C., DATED JANUARY 2024 ARE APPLICABLE TO THIS PROJECT AND BY  
REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
1205.01	PAVEMENT MARKINGS - LINE TYPES AND OFFSETS
1205.02	PAVEMENT MARKINGS - TWO-LANE AND MULTI-LANE ROADWAYS
1205.04	PAVEMENT MARKINGS - INTERSECTIONS
1205.05	PAVEMENT MARKINGS - TURN LANES
1205.08	PAVEMENT MARKINGS - SYMBOLS AND WORD MESSAGES
1261.01	GUARDRAIL AND BARRIER DELINEATORS - INSTALLATION SPACING
1261.02	GUARDRAIL AND BARRIER DELINEATORS - TYPES AND MOUNTING
1262.01	GUARDRAIL END DELINEATION

PAVEMENT MARKING SCHEDULE

THERMOPLASTIC (4", 90 MILS)

T2	WHITE SOLID LANE LINE
T4	3 FT. - 9 FT./SP WHITE MINISKIP
T13	YELLOW DOUBLE CENTER

THERMOPLASTIC (24", 90 MILS)

T61	WHITE STOPBAR
-----	---------------

THERMOPLASTIC PAVEMENT MARKING SYMBOLS (90 MILS)

T70	LEFT TURN ARROW
T72	STRAIGHT ARROW

GENERAL NOTES

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF  
THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN,  
OR DIRECTED BY THE ENGINEER.

- A) INSTALL PAVEMENT MARKINGS AND PAVEMENT MARKERS ON THE FINAL SURFACE  
AS FOLLOWS:

ROAD NAME	MARKING	MARKER
ALL	THERMOPLASTIC	NONE

- B) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.
- C) REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND MARKERS.
- D) PASSING ZONES WILL BE DETERMINED IN THE FIELD AND MUST BE APPROVED BY  
THE ENGINEER.
- E) STOP BAR LOCATION AT NON-SIGNALIZED INTERSECTIONS MAY BE ADJUSTED AS  
DIRECTED BY THE ENGINEER.
- F) UNLESS OTHERWISE SPECIFIED, HEATED-IN-PLACE THERMOPLASTIC MAY BE USED  
IN LIEU OF EXTRUDED THERMOPLASTIC FOR STOP BARS, SYMBOLS, CHARACTERS  
AND DIAGONALS. IF HEATED-IN-PLACE IS USED, IT SHALL BE PAID FOR USING  
THE EXTRUDED THERMOPLASTIC PAY ITEM.

PAVEMENT MARKING  
SYMBOLS

↩	T70
↑	T72

INDEX

SHEET NO.	DESCRIPTION
PMP-1	PAVEMENT MARKING PLAN TITLE AND SCHEDULE
PMP-2	PAVEMENT MARKING DETAIL


PROJECT REFERENCE NO.	SHEET NO.
BP7.C001	PMP - 1
APPROVED: <div>DocuSigned by: Andrew D. Klinksiek E3D78FB4596E44B</div>	
DATE: 3/14/2025	
SEAL <div><div>NORTH CAROLINA PROFESSIONAL ENGINEER ANDREW D. KLINSIEK</div><div>SEAL 403II</div></div>	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

PLAN PREPARED BY: HNTB NORTH CAROLINA, P.C.


A.D. Klinksiek, PE, PTOE	PROJECT ENGINEER
J.A. Wagner, PE	DESIGN ENGINEER

HNTB

HNTB NORTH CAROLINA, P.C.  
4000 CENTER AT NORTH HILLS ST.  
SUITE 500  
RALEIGH, NORTH CAROLINA 27609  
NC LICENSE NO: C-1554  
(919) 546-8997




ENGINEER TO APPROVE LOCATION OF ALL UNSIGNALIZED STOPBARS.



## PAVEMENT MARKING DETAIL



TIP PROJECT: BP7.C001




STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

PLAN FOR PROPOSED  
HIGHWAY EROSION CONTROL


**ROCKINGHAM COUNTY**

LOCATION: REPLACE EXISTING CULVERT ON SR 1785 (CHURCH ST)  
TYPE OF WORK: GRADING, DRAINAGE, PAVING, AND CULVERT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	BP7.C001	EC-1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	



THIS PROJECT CONTAINS  
EROSION CONTROL PLANS  
FOR CLEARING AND  
GRUBBING PHASE OF  
CONSTRUCTION.



THESE EROSION AND SEDIMENT CONTROL PLANS COMPLY  
WITH THE REGULATIONS SET FORTH BY THE  
NCG-010000 GENERAL STORMWATER CONSTRUCTION PERMIT  
ISSUED BY THE NORTH CAROLINA DEPARTMENT OF  
ENVIRONMENTAL QUALITY DIVISION OF ENERGY,  
MINERAL AND LAND RESOURCES.

**HNTB**

Prepared In the Office of:

**HNTB**

HNTB NORTH CAROLINA, P.C.  
4000 CENTER AT NORTH HILLS ST.  
SUITE 500  
RALEIGH, NORTH CAROLINA 27609  
NC LICENSE NO: C-1554

Designed by:

**NATALIE CHAN, P.E.**

NAME

**3444**

LEVEL III CERTIFICATION NO.

Roadway Standard Drawings

The "Roadway Standard Drawings"- Roadway Design Unit - N. C.  
Department of Transportation - Raleigh, N. C., dated January 2024  
and the latest revision thereto are applicable to this project and by  
reference hereby are considered a part of these plans.

DIVISION OF HIGHWAYS

PROJECT REFERENCE NO.	SHEET NO.
BP7.C001	EC-2
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

Std. #	Description	Symbol
1605.01	Temporary Silt Fence	
1606.01	Special Sediment Control Fence	
1622.01	Temporary Berms and Slope Drains	
1630.02	Silt Basin Type B	
1630.03	Temporary Silt Ditch	
1630.04	Stilling Basin	
1630.05	Temporary Diversion	
1630.06	Special Stilling Basin	
1630.07	Skimmer Basin	
1630.08	Tiered Skimmer Basin	
1630.09	Earthen Dam with Skimmer	
	Infiltration Basin	
	Rock Inlet Sediment Trap:	
1632.01	Type A	
1632.02	Type B	
1632.03	Type C	


Std. #	Description	Symbol
1633.01	Temporary Rock Silt Check Type A	
1633.02	Temporary Rock Silt Check Type B	
1633.03	Temporary Rock Silt Check Type A with Excelsior Matting and Flocculant	
1634.01	Temporary Rock Sediment Dam Type A	
1634.02	Temporary Rock Sediment Dam Type B	
1635.01	Rock Pipe Inlet Sediment Trap Type A	
1635.02	Rock Pipe Inlet Sediment Trap Type B	
1636.01	Excelsior Wattle Check	
1636.01	Excelsior Wattle Check with Flocculant	
1636.01	Coir Fiber Wattle Check	
1636.01	Coir Fiber Wattle Check with Flocculant	
1636.02	Silt Fence Excelsior Wattle Break	
	Silt Fence Coir Fiber Wattle Break	
1636.03	Excelsior Wattle Barrier	
1636.03	Coir Fiber Wattle Barrier	



# EXAMPLE OF PUMP-AROUND OPERATION

PROJECT REFERENCE NO.	SHEET NO.
<i>BP7.C001</i>	<i>EC-2A</i>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

- NOTES:
- 1) All excavation shall be performed in only dry or isolated areas of the work zone.
  - 2) Impervious dikes are to be used to isolate work from stream flow when necessary.
  - 3) Maintenance of stream flow operations shall be incidental to the work. This includes polyethylene sheeting, diversion pipes, pumps and hoses.
  - 4) Pumps and hoses shall be of sufficient size to dewater the work area.



- SEQUENCE OF CONSTRUCTION FOR TYPICAL WORK AREA
- 1. INSTALL SPECIAL STILLING BASIN(S).
  - 2. INSTALL UPSTREAM PUMP AND TEMPORARY FLEXIBLE HOSE.
  - 3. PLACE UPSTREAM IMPERVIOUS DIKE AND BEGIN PUMPING OPERATIONS FOR STREAM DIVERSION.
  - 4. PLACE DOWNSTREAM IMPERVIOUS DIKE AND PUMPING APPARATUS. DEWATER ENTRAPPED AREA. AREA TO BE DEWATERED SHALL BE EQUAL TO ONE DAY'S WORK.
  - 5. INSTALL CULVERT(S) IN ACCORDANCE WITH THE PLANS.
  - 6. EXCAVATE ANY ACCUMULATED SILT AND DEWATER BEFORE REMOVAL OF IMPERVIOUS DIKES. REMOVE IMPERVIOUS DIKES, PUMPS, AND TEMPORARY FLEXIBLE HOSE. (DOWNSTREAM IMPERVIOUS DIKES FIRST).
  - 7. REMOVE SPECIAL STILLING BASIN(S) AND BACKFILL. STABILIZE DISTURBED AREA WITH SEED AND MULCH.

DIVISION OF HIGHWAYS  
STATE OF NORTH CAROLINA

PROJECT REFERENCE NO.	SHEET NO.
BP7.C001	EC-3
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

SOIL STABILIZATION TIMEFRAMES

SITE DESCRIPTION	STABILIZATION TIME	TIMEFRAME EXCEPTIONS
PERIMETER DIKES, SWALES, DITCHES AND SLOPES	7 DAYS	NONE
HIGH QUALITY WATER (HQW) ZONES	7 DAYS	NONE
SLOPES STEEPER THAN 3:1	7 DAYS	IF SLOPES ARE 10' OR LESS IN LENGTH AND ARE NOT STEEPER THAN 2:1, 14 DAYS ARE ALLOWED.
SLOPES 3:1 TO 4:1	14 DAYS	7 DAYS FOR SLOPES GREATER THAN 50' IN LENGTH WITH SLOPES STEEPER THAN 4:1. 7 DAYS FOR PERIMETER DIKES, SWALES, DITCHES PERIMETER SLOPES, AND HQW ZONES
ALL OTHER AREAS WITH SLOPES FLATTER THAN 4:1	14 DAYS	7 DAYS FOR PERIMETER DIKES, SWALES, DITCHES PERIMETER SLOPES, AND HQW ZONES



INLET/OUTLET  
ALUMINUM STRUCTURAL PLATE &  
CHANNEL DETAIL  
NOT TO SCALE

X-SECTION VIEW

17'-3" x 11'-0" CASPIA WWWH & BW

1' SILGRASS

EXCAVATION

PROFILE VIEW

33'-0" 33'-0" 33'-0" 33'-0"

PLAN VIEW

NOTES

- SILGRASS DIMENSIONS THE HOLE THROUGHOUT STRUCTURE


QUANTITIES

- 95 TONS GUARD ROP RAP
- 87 CY INLET/OUTLET
- 50 CY EXCAVATION

FOR -Y1-, -Y2-, & -Y3- PROFILES, SEE SHEET 5.

HNTB NORTH CAROLINA, P.C.  
4000 CENTER AT NORTH HILLS ST  
SUITE 500  
RALEIGH, NORTH CAROLINA 27609  
NC LICENSE NO: C-1554

PROJECT REFERENCE NO.	SHEET NO.
BP7.C001	EC-4/CONST.4
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER





**CULVERT CONSTRUCTION SEQUENCE STA. 12 + 32 -L-**



PHASE I	
---------	--

1. UTILIZE SPECIAL STILLING BASIN(S) THROUGH OUT CULVERT CONSTRUCTION.
2. CLOSE SR 1785 CHURCH STREET AND SET UP DETOUR ACCORDING TO TRAFFIC CONTROL PLAN.
3. INSTALL IMPERVIOUS DIKES A, B, AND C.
4. INSTALL 36" TEMPORARY PIPES A AND B AND PUMP AROUND OPERATIONS A AND B
5. DEWATER WORK AREA(S) WITH SPECIAL STILLING BASIN(S).
6. REMOVE EXISTING CATCH BASIN AND 24" CMP AS SHOWN BELOW.
7. REMOVE THE TWO EXISTING 96" CMP.
8. REMOVE EXISTING CATCH BASIN AND 36" RCP AS SHOWN BELOW.
9. INSTALL PROPOSED 42" PIPES, CB, AND 2GI-NS TYPE A.

PHASE II	
----------	--

1. MAINTAIN TEMPORARY PIPES A AND B AND PUMP AROUND OPERATIONS A AND B.
2. INSTALL PROPOSED 17'-3" X 11'-0" CASPPA.
3. INSTALL UPSTREAM AND DOWNSTREAM RIP RAP AND ROCK PLATING AS SHOWN ON PLAN.
4. BACKFILL EXISTING DITCH ACCORDING TO NOTE SHOWN BELOW.
5. REMOVE ALL IMPERVIOUS DIKES, TEMPORARY PIPES AND PUMP AROUND OPERATIONS.
6. REMOVE ANY REMAINING SPECIAL STILLING BASIN(S).
7. COMPLETE ROADWAY.

NOTE: REPOSITION PUMP AND HOSE LOCATIONS AS NEEDED FOR THE BANK STABILIZAATION AND ROCK PLATING INSTALLATION.







T.I.P.: BP7.C001

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION

SIGNING PLAN  
ROCKINGHAM COUNTY

LOCATION: REPLACE EXISTING CULVERT ON SR 1785 (CHURCH ST)

ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" -  
CONTRACT STANDARDS AND DEVELOPMENT UNIT - N.C. DEPARTMENT OF TRANSPORTATION -  
RALEIGH, N.C., DATED JANUARY 2024 ARE APPLICABLE TO THIS PROJECT AND BY  
REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
901.40	ORIENTATION OF GROUND MOUNTED SIGNS
904.50	MOUNTING OF TYPE 'D', 'E' AND 'F' SIGNS ON 'U' CHANNEL SUPPORTS

PAY ITEM NOTES

- SIGN ERECTION, TYPE D, E OR F
- DISPOSAL OF SIGN SYSTEM, U-CHANNEL

GENERAL NOTES

- SIGNS FURNISHED BY STATE.
- ALL PROPOSED SIGNS SEE PAY ITEM NOTE 1 UNLESS OTHERWISE NOTED.
- CONFIRM IN WRITING AT LEAST 4 MONTHS IN ADVANCE, THE ACTUAL DATE THE DEPARTMENT FURNISHED SIGNS WILL BE REQUIRED.
- IF REMOVAL OR RELOCATION OF SIGNS ON PRIVATE STREET (NON-STATE MAINTAINED) IS REQUIRED DUE TO CONSTRUCTION, THE CONTRACTOR SHALL INFORM THE ENGINEER. THE WORK WILL BE COMPLETED BY OTHERS.
- WHEN NOT STATIONED OR DIMENSIONED ON PLANS, ALL TYPE E SIGNS SHALL BE FIELD LOCATED BY THE ENGINEER.
- ALL EXISTING SIGNS ON U-CHANNEL SUPPORT(S) WITHIN THE PROJECT LIMITS SHALL BE REMOVED AND DISPOSED OF UNLESS OTHERWISE NOTED ON PLANS.
- THE BACKGROUND FOR TYPE E SIGNS SHALL BE GRADE C REFLECTIVE SHEETING.
- SEE ROADWAY PLANS FOR GUARD/GUIDE RAIL DETAILS.

SUMMARY OF QUANTITIES

ITEM NO.		ITEM DESCRIPTION	QUANTITY	UNIT
DESC. NO.	SECT. NO.			
4072000000	903	SUPPORTS, 3-LB STEEL U-CHANNEL	79	LF
4102000000	904	SIGN ERECTION, TYPE E	8	EA
4155000000	907	DISPOSAL OF SIGN SYSTEM, U-CHANNEL	6	EA

PLANS PREPARED BY: HNTB NORTH CAROLINA, P.C.

A.D. KLINKSIEK, PE, PTOE SIGNING PROJECT MANAGER  
J.A. WAGNER, PE SIGNING PROJECT ENGINEER  
G.D. BERRY SIGNING DESIGN TECHNICIAN

HNTB

HNTB NORTH CAROLINA, P.C.  
4000 CENTER AT NORTH HILLS ST.  
SUITE 500  
RALEIGH, NORTH CAROLINA 27609  
NC LICENSE NO: C-1554  
(919) 546-8997

INDEX


SHEET NO.	DESCRIPTION
SIGN-1	TITLE SHEET
SIGN-2	EXISTING & PROPOSED SIGNING

PROJECT REFERENCE NO.	SHEET NO.
BP7.C001	SIGN-1
APPROVED: <div>DocuSigned by: Andrew D. Klinksiek E3D78FB4506E44B...</div>	
DATE: 3/14/2025	
SEAL	
<div>SEAL 40311 ENGINEER ANDREW D. KLINSIEK</div>	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	



401

QUANTITY REQ'D 3




36" X 36"  
R1-1

ONE "U" POST PER SIGN

402

QUANTITY REQ'D 3




30" X 30"  
R5-1

ONE "U" POST PER SIGN  
MOUNTED BACK TO BACK WITH SIGN 401  
IN 1 INSTALLATION

403

QUANTITY REQ'D 1




36" X 12"  
R6-1 (L)

ONE "U" POST PER SIGN


404



QUANTITY REQ'D 1



36" X 12"  
R6-1 (R)

MOUNTED BACK TO BACK WITH SIGN 403  
IN 1 INSTALLATION



PROJECT REFERENCE NO.	SHEET NO.
BP7.C001	SIGN-2
APPROVED:  <small>E3D78FB459E44B</small>	
DATE: 3/14/2025	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	



HNTB NORTH CAROLINA, P.C.  
4000 CENTER AT NORTH HILLS ST.  
SUITE 500  
RALEIGH, NORTH CAROLINA 27609  
NC LICENSE NO: C-1554  
(919) 546-8997


EXISTING & PROPOSED SIGNING

3/18/2025  
\\wse03\local\WSE\Projects\NC\HNTB\Division 7\ENG22-0889\_BP7.C001\Rockingham County\Utilities\Engineering\UC\Proj\BP7C001.Lut\_UC-01\_L+sh.dgn  
9:35:32 AM

09/08/99

WBS PROJECT: BP7.C001

CONTRACT: DG00663



VICINITY MAP (N.T.S.)


STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

UTILITY CONSTRUCTION PLANS  
ROCKINGHAM COUNTY

LOCATION: REPLACE EXISTING CULVERT ON SR 1785 (CHURCH ST)  
TYPE OF WORK: WATER LINE AND SANITARY SEWER RELOCATION




UC-04



THIS PROJECT IS WITHIN THE MUNICIPAL BOUNDARIES OF EDEN.

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

GRAPHIC SCALES



INDEX OF SHEETS

SHEET NO.:	DESCRIPTION:
UC-01	TITLE SHEET
UC-02	UTILITY SYMBOLOGY
UC-03	UTILITY NOTES
UC-03A TO UC-03D	DETAIL SHEETS
UC-04 TO UC-04A	PLAN SHEETS
UC-05 TO UC-06	PROFILE SHEETS

WATER AND SEWER  
OWNERS ON PROJECT

- (A) WATER LINE - CITY OF EDEN  
(B) SANITARY SEWER - CITY OF EDEN

PREPARED IN THE OFFICE OF  
Weston & Sampson  
WSE of North Carolina, PC  
2052 Energy Drive  
Apex, NC 27502  
Phone: 919.297.0220  
NC License: C-4647


FOR

HNTB

HNTB NORTH CAROLINA, P.C.  
4000 CENTER AT NORTH HILLS ST.  
SUITE 500  
RALEIGH, NORTH CAROLINA 27609  
NC LICENSE NO: C-1554

KEVIN S. HUTCHENS, PE	SENIOR PROJECT ENGINEER
KATERINA DOMINGUEZ	PROJECT DESIGN ENGINEER
	PROJECT DESIGN ENGINEER

SEAL



DIVISION OF HIGHWAYS  
HIGHWAY DIVISION 7

P.O. BOX 14996  
1584 YANCEYVILLE STREET  
GREENSBORO, NC 27415-4996  
PHONE (336) 487-0000  
FAX (336) 334-3637

DANIEL R. DAGENHART	DIVISION BRIDGE PROGRAM MANAGER
WRIGHT R. ARCHER, III, PE	DIVISION ENGINEER
BOJAN CVIJETIC, PE	DIVISION CONST. ENGINEER
N/A	DIVISION UTILITY COORDINATOR





























5/14/99  
3/18/2025  
C:\Users\Local\WSE\Projects\NC\HNTB\Division 7\ENG22-0889\_BP7.C001\1\_Rockingham County\Utilities\Engineering\UC\Pro\BP7C001.ut UC-02.sym.dgn  
10:46:53 AM

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS


PROJECT REFERENCE NO.	SHEET NO.
BP7.C001	UC-02

UTILITIES PLAN SHEET SYMBOLS









PROPOSED WATER SYMBOLS








Water Line (Sized as Shown)	
11¼ Degree Bend	
22½ Degree Bend	
45 Degree Bend	
90 Degree Bend	
Plug	
Tee	
Cross	
Reducer	
Gate Valve	
Butterfly Valve	
Tapping Valve	
Line Stop	
Line Stop with Bypass	
Blow Off	
Fire Hydrant	
Relocate Fire Hydrant	
Remove Fire Hydrant	
Water Meter	
Relocate Water Meter	
Remove Water Meter	
Water Pump Station	
RPZ Backflow Preventer	
DCV Backflow Preventer	
Relocate RPZ Backflow Preventer	
Relocate DCV Backflow Preventer	

PROPOSED SEWER SYMBOLS

Gravity Sewer Line (Sized as Shown)	
Force Main Sewer Line (Sized as Shown)	
Manhole (Sized per Note)	
Sewer Pump Station	





















PROPOSED MISCELLANEOUS UTILITIES SYMBOLS




















Power Pole	
Telephone Pole	
Joint Use Pole	
Telephone Pedestal	
Utility Line by Others (Type as Shown)	
Trenchless Installation	
Encasement by Open Cut	
Encasement	

Thrust Block	
Air Release Valve	
Utility Vault	
Concrete Pier	
Steel Pier	
Plan Note	
Pay Item Note	

NOTE  
PAY ITEM

EXISTING UTILITIES SYMBOLS

Power Pole	
Telephone Pole	
Joint Use Pole	
Utility Pole	
Utility Pole with Base	
H-Frame Pole	
Power Transmission Line Tower	
Water Manhole	
Power Manhole	
Telephone Manhole	
Sanitary Sewer Manhole	
Hand Hole for Cable	
Power Transformer	
Telephone Pedestal	
CATV Pedestal	
Gas Valve	
Gas Meter	
Located Miscellaneous Utility Object	
Abandoned According to Utility Records	
End of Information	

*Underground Power Line	
*Underground Telephone Cable	
*Underground Telephone Conduit	
*Underground Fiber Optics Telephone Cable	
*Underground TV Cable	
*Underground Fiber Optics TV Cable	
*Underground Gas Pipeline	
Aboveground Gas Pipeline	
*Underground Water Line	
Aboveground Water Line	
*Underground Gravity Sanitary Sewer Line	
Aboveground Gravity Sanitary Sewer Line	
*Underground SS Forced Main Line	
Underground Unknown Utility Line	
SUE Test Hole	
Water Meter	
Water Valve	
Fire Hydrant	
Sanitary Sewer Cleanout	

\*For Existing Utilities  
Utility Line Drawn from Record (Type as Shown)  
Designated Utility Line (Type as Shown)



# UTILITY CONSTRUCTION

## GENERAL NOTES:

1.

THE PROPOSED UTILITY CONSTRUCTION SHALL MEET THE APPLICABLE REQUIREMENTS OF THE NC DEPARTMENT OF TRANSPORTATION'S "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" DATED JANUARY 2024.
2.

THE EXISTING WATER LINE AND SANITARY SEWER UTILITIES BELONG TO THE CITY OF EDEN.

CONTACT: BEVERLY O'DELL  
PHONE: 336-612-8035
3.

ALL WATER LINES TO BE INSTALLED WITHIN COMPLIANCE OF THE RULES AND REGULATIONS OF THE NORTH CAROLINA DEPARTMENT OF ENVIRONMENTAL QUALITY, DIVISION OF WATER RESOURCES, PUBLIC WATER SUPPLY SECTION. ALL SEWER LINES TO BE INSTALLED WITHIN COMPLIANCE OF THE RULES AND REGULATIONS OF THE NORTH CAROLINA DEPARTMENT OF ENVIRONMENTAL QUALITY, DIVISION OF WATER RESOURCES, WATER QUALITY SECTION. PERFORM ALL WORK IN ACCORDANCE WITH THE APPLICABLE PLUMBING CODES.
4.

THE UTILITY OWNER OWNS THE EXISTING UTILITY FACILITIES AND WILL OWN THE NEW UTILITY FACILITIES AFTER ACCEPTANCE BY THE DEPARTMENT. THE DEPARTMENT OWNS THE CONSTRUCTION CONTRACT AND HAS ADMINISTRATIVE AUTHORITY. COMMUNICATIONS AND DECISIONS BETWEEN THE CONTRACTOR AND UTILITY OWNER ARE NOT BINDING UPON THE DEPARTMENT OR THIS CONTRACT UNLESS AUTHORIZED BY THE ENGINEER. AGREEMENTS BETWEEN THE UTILITY OWNER AND CONTRACTOR FOR THE WORK THAT IS NOT PART OF THIS CONTRACT OR IS SECONDARY TO THIS CONTRACT ARE ALLOWED, BUT ARE NOT BINDING UPON THE DEPARTMENT.
5.

PROVIDE ACCESS FOR THE DEPARTMENT PERSONNEL AND THE OWNER'S REPRESENTATIVES TO ALL PHASES OF CONSTRUCTION. NOTIFY DEPARTMENT PERSONNEL AND THE UTILITY OWNER TWO WEEKS PRIOR TO COMMENCEMENT OF ANY WORK AND ONE WEEK PRIOR TO SERVICE INTERRUPTION. KEEP UTILITY OWNERS' REPRESENTATIVES INFORMED OF WORK PROGRESS AND PROVIDE OPPORTUNITY FOR INSPECTION OF CONSTRUCTION AND TESTING.

6.

THE PLANS DEPICT THE BEST AVAILABLE INFORMATION FOR THE LOCATION, SIZE, AND TYPE OF MATERIAL FOR ALL EXISTING UTILITIES. MAKE INVESTIGATIONS FOR DETERMINING THE EXACT LOCATION, SIZE, AND TYPE MATERIAL OF THE EXISTING FACILITIES AS NECESSARY FOR THE CONSTRUCTION OF THE PROPOSED UTILITIES AND FOR AVOIDING DAMAGE TO EXISTING FACILITIES. REPAIR ANY DAMAGE INCURRED TO EXISTING FACILITIES TO THE ORIGINAL OR BETTER CONDITION AT NO ADDITIONAL COST TO THE DEPARTMENT.
7.

MAKE FINAL CONNECTIONS OF THE NEW WORK TO THE EXISTING SYSTEM WHERE INDICATED ON THE PLANS, AS REQUIRED TO FIT THE ACTUAL CONDITIONS, OR AS DIRECTED.
8.

MAKE CONNECTIONS BETWEEN EXISTING AND PROPOSED UTILITIES AT TIMES MOST CONVENIENT TO THE PUBLIC, WITHOUT ENDANGERING THE UTILITY SERVICE, AND IN ACCORDANCE WITH THE UTILITY OWNER'S REQUIREMENTS. MAKE CONNECTIONS ON WEEKENDS, AT NIGHT, AND ON HOLIDAYS IF NECESSARY.
9.

ALL UTILITY MATERIALS SHALL BE APPROVED PRIOR TO DELIVERY TO THE PROJECT. SEE 1500-7, " SUBMITTALS AND RECORDS" IN SECTION 1500 OF THE STANDARD SPECIFICATIONS.

## PROJECT QUANTITIES

ITEM NUMBER	DESCRIPTION	QUANTITY	
0318000000-E	FOUNDATION CONDITIONING MATERIAL, MINOR STRUCTURES	49	TON
0320000000-E	FOUNDATION CONDITIONING GEOTEXTILE	155	SY
2830000000-N	ADJUSTMENT OF MANHOLES	2	EA
5326200000-E	12" WATER LINE	90	LF
5329000000-E	DUCTILE IRON WATER PIPE FITTINGS	390	LBS
5558000000-E	12" VALVE	1	EA
5691300000-E	8" SANITARY GRAVITY SEWER	273	LF
5691600000-E	16" SANITARY GRAVITY SEWER	102	LF
5769000000-E	DUCTILE IRON SEWER PIPE FITTINGS	65	LBS
5775000000-E	4' DIA. UTILITY MANHOLE	1	EA
5776000000-E	5' DIA. UTILITY MANHOLE	2	EA
5781000000-E	UTILITY MANHOLE WALL, 4' DIA.	2.1	LF
5782000000-E	UTILITY MANHOLE WALL, 5' DIA.	31.7	LF
5802000000-E	ABANDON 8" UTILITY PIPE	273	LF
5804000000-E	ABANDON 12" UTILITY PIPE	90	LF
5810000000-E	ABANDON 16" UTILITY PIPE	110	LF
5816000000-E	ABANDON UTILITY MANHOLE	1	EA
5828000000-E	REMOVE UTILITY MANHOLE	2	EA

Weston & Sampson  
WSE of North Carolina, PC  
2062 Energy Drive  
Phone: 919.297.0220

NC License:  
C-4847  
Apex, NC 27602  
westonandsampson.com

PROJECT REFERENCE NO.  
BP7.C001

SHEET NO.  
UC-03

DESIGNED BY: KCZ  
DRAWN BY: KCZ  
CHECKED BY: KSH  
APPROVED BY: KSH  
REVISED:  
NORTH CAROLINA  
DEPARTMENT OF  
TRANSPORTATION  
UTILITIES ENGINEERING SEC.  
PHONE: (919) 707-6690  
FAX: (919) 250-4151



UTILITY CONSTRUCTION  
PLANS ONLY

## UTILITY CONSTRUCTION

**DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED**

## PROJECT SPECIFIC NOTES:

1.

THERE ARE NO KNOWN WATER SERVICE LINES OR SEWER SERVICE LINES WITHIN THE DISTURBED AREA OF THE PROJECT LIMITS WHERE THE PROPOSED EXCAVATION IS TO OCCUR FOR INSTALLATION OF THE PROPOSED CULVERT CROSSING CHURCH STREET.
2.

IN THE EVENT THAT EXCESSIVE GROUNDWATER OR SPRINGS ARE ENCOUNTERED DURING PIPE CONSTRUCTION, THE CONTRACTOR SHALL EMPLOY ALL METHODS NECESSARY TO KEEP THE TRENCHES DRY AS DIRECTED BY THE RESIDENT ENGINEER.
3.

PROPOSED WATER LINE SHALL BE 12" DUCTILE IRON PIPE, CLASS 350, RESTRAINED JOINT PIPE.
4.

ALL WATER LINE FITTINGS, 4-INCHES THROUGH 24-INCHES IN DIAMETER, SHALL BE DUCTILE IRON PRESSURE CLASS 350.
5.

ALL PROPOSED FITTINGS (BENDS, TEES, CROSSES, REDUCERS, PLUGS, ETC.) SHALL BE RESTRAINED BY THE USE OF RESTRAINED JOINT CONSTRUCTION, OR CAST IN PLACE CONCRETE THRUST RESTRAINTS AS DETAILED ON THESE DRAWINGS, OR AS DIRECTED BY THE ENGINEER.
6.

FINAL CONNECTIONS TO THE EXISTING FACILITIES SHALL BE WITNESSED BY THE UTILITY OWNER'S REPRESENTATIVE.
7.

ANY HYDRANTS TAKEN OUT OF SERVICE DUE TO THIS CONSTRUCTION WORK SHALL BE BAGGED UNTIL SERVICE IS RESTORED.
8.

ALL WATER LINE AND SANITARY SEWER LINE REMOVED AS PART OF THIS WORK SHALL BECOME CONTRACTOR'S PROPERTY AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL AND STATE REQUIREMENTS. REMOVED PIPE SHALL NOT BE USED AS PIPE FOR NEW CONSTRUCTION.
9.

PROPOSED GRAVITY SEWER PIPE SHALL BE OF NOMINAL SIZE NOTED ON THE PLANS AND BE EITHER: DUCTILE IRON PIPE CLASS 350 WITH A CERAMIC EPOXY LINING (SUCH AS PROTECTO 401) APPLIED AT THE FACTORY BY THE MANUFACTURER; OR PVC C900 DR-18; OR PVC SDR-35.
10.

THE EXISTING WATER LINE IN CONFLICT WITH THE PROPOSED CULVERT WORK SHALL BE REMOVED. CONTRACTOR SHALL FIRST COORDINATE WITH THE UTILITY OWNER TO CLOSE THE NECESSARY VALVES BEFORE EXCAVATING AND REMOVING THE WATER LINE. WATER LINE REMOVAL SHALL BE TO THE CLOSEST JOINTS TO THE LIMITS SHOWN ON THE PLANS AS NOTED BY THE PROPOSED PLUGS. ONCE THE WATER LINE HAS BEEN REMOVED THE CONTRACTOR SHALL INSTALL A TEMPORARY PLUG INTO THE END OF EACH PIPE TO REMAIN FOR THE DURATION OF THE CULVERT WORK. WATER LINE SHALL BE BACKFILLED AS NEEDED. VALVES SHALL REMAIN CLOSED FOR THE DURATION OF THE CULVERT CONSTRUCTION. ONCE THE CULVERT CONSTRUCTION IS COMPLETED AND BACKFILL REACHES THE APPROPRIATE GRADE, AS DETERMINED BY THE ENGINEER, THEN THE ENDS OF THE EXISTING WATER LINE CAN BE EXCAVATED AND REMOVE THE TEMPORARY PLUGS. THE NEW WATER LINE SHALL THEN BE CONSTRUCTED, BACKFILLED, AND TESTED. UPON SUCCESSFUL TESTING AND APPROVAL BY THE UTILITY OWNER, THE WATER LINE SHALL BE PLACED BACK INTO SERVICE BY OPENING THE VALVES, AS COORDINATED WITH THE UTILITY OWNER.
11.

THE EXISTING GRAVITY SEWER LINE IN CONFLICT WITH THE PROPOSED CULVERT WORK SHALL BE REMOVED. CONTRACTOR SHALL FIRST PLUG ALL PIPES AT THE NECESSARY MANHOLES BEFORE EXCAVATING AND REMOVING THE GRAVITY SEWER LINE. GRAVITY SEWER REMOVAL SHALL BE FROM MANHOLE TO MANHOLE. ONCE THE SEWER PIPE HAS BEEN REMOVED THE CONTRACTOR SHALL PLUG / PATCH THE MANHOLE WALLS AND EMPLOY A PUMP AND HAUL OPERATION FOR THE DURATION OF THE CULVERT WORK. ONCE THE CULVERT CONSTRUCTION IS COMPLETED AND BACKFILL REACHES THE APPROPRIATE GRADE, AS DETERMINED BY THE ENGINEER, THEN THE NEW GRAVITY SEWER AND MANHOLES SHALL BE CONSTRUCTED, BACKFILLED, AND TESTED. UPON SUCCESSFUL TESTING AND APPROVAL BY THE UTILITY OWNER, THE GRAVITY SEWER SYSTEM SHALL BE PLACED BACK INTO SERVICE.



PROJECT REFERENCE NO.  
BP7.C001

SHEET NO.  
UC-03A

DESIGNED BY: KCZ

DRAWN BY: KCZ

CHECKED BY: KSH

APPROVED BY: KSH

REVISED:

NORTH CAROLINA  
DEPARTMENT OF  
TRANSPORTATION



UTILITIES ENGINEERING SEC.  
PHONE: (919) 707-6690  
FAX: (919) 250-4151

SEAL  
39283  
K. S. HUTCHESON  
Professional Engineer  
09/18/2025

UTILITY CONSTRUCTION  
PLANS ONLY

UTILITY CONSTRUCTION

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED



FITTING		REQUIRED RESTRAINED LENGTH (FT) OF D.I. PIPE BY DEPTH OF COVER							
HORIZONTAL BENDS		3FT	4FT	5FT	6FT	7FT	8FT	9FT	10FT
6 INCH - 11.25 DEG		3	2	2	2	2	1	1	1
6 INCH - 22.5 DEG		5	4	3	3	3	2	2	2
6 INCH - 45 DEG		10	8	6	6	5	4	4	4
6 INCH - PLUG		31	28	25	23	21	20	19	17
HORIZONTAL BENDS		3FT	4FT	5FT	6FT	7FT	8FT	9FT	10FT
8 INCH - 11.25 DEG		3	3	2	2	2	2	2	2
8 INCH - 22.5 DEG		5	5	4	4	4	3	3	3
8 INCH - 45 DEG		11	9	8	8	7	6	6	5
8 INCH - PLUG		41	37	33	31	28	26	25	23
HORIZONTAL BENDS		3FT	4FT	5FT	6FT	7FT	8FT	9FT	10FT
10 INCH - 11.25 DEG		3	3	3	3	2	2	2	2
10 INCH - 22.5 DEG		6	6	5	5	4	4	4	3
10 INCH - 45 DEG		13	11	10	9	8	8	7	6
10 INCH - PLUG		49	44	40	37	34	32	30	28
HORIZONTAL BENDS		3FT	4FT	5FT	6FT	7FT	8FT	9FT	10FT
12 INCH - 11.25 DEG		4	4	3	3	3	2	2	2
12 INCH - 22.5 DEG		8	7	6	5	5	5	4	4
12 INCH - 45 DEG		15	13	12	11	10	9	8	8
12 INCH - PLUG		59	53	48	44	41	38	35	33
HORIZONTAL BENDS		3FT	4FT	5FT	6FT	7FT	8FT	9FT	10FT
14 INCH - 11.25 DEG		4	4	4	3	3	3	3	2
14 INCH - 22.5 DEG		9	7	7	6	6	5	5	4
14 INCH - 45 DEG		17	15	13	12	11	10	9	9
14 INCH - PLUG		67	61	55	50	47	43	40	38




ASSUMPTIONS:  
SAFETY FACTOR = 1.5  
DESIGN PRESSURE = 200 PSI (TEST PRESSURE)  
LAYING CONDITION = TYPE 4  
SOIL DESIGNATION: CL (BROWN CLAY)

- NOTES:
- RESTRAINED LENGTH IS MEASURED FROM THE CENTER OF THE BEND AS FOLLOWS:
    - HORIZONTAL AND VERTICAL BENDS: ALONG EACH SIDE OF THE BEND.
    - HORIZONTAL AND VERTICAL BENDS - OFFSET OR COMBINED: ALONG THE OUTER SIDE OF EACH BEND. ALL PIPE BETWEEN THE TWO BENDS SHALL BE RESTRAINED JOINT WHEN:
      - THE DISTANCE BETWEEN THEM IS EQUAL THE REQUIRED LENGTH
      - THE DISTANCE BETWEEN THEM LESS THAN THE REQUIRED LENGTH
      - AS NOTED ON THE PLANS
      - AS DIRECTED BY THE ENGINEER


8/17/99

I:\2024\wse03\local\wse\Projects\NC\HNTB\Division 7\ENG22-0889\_BP7.C001\Rockingham County\Utilities\Engineering\UC\Proj\BP7C001\ut\_UC-03B.dtl.dgn 3:01:53 PM

APPROVED METHOD FOR  
EXTENSION OF VALVE BOX




- NOTES:
1. VALVE BOX SHALL BE PER ONWASA'S SPECIFICATIONS
  2. CONCRETE VALVE COLLAR REQUIRED ON ALL VALVES.




### VALVE BOX INSTALLATION AND EXTENSION DETAIL

NOT TO SCALE



### TYPICAL VALVE DETAIL

NOT TO SCALE



### INSERTION VALVE DETAIL

NOT TO SCALE

Weston & Sampson  
WSE of North Carolina, PC  
2052 Energy Drive  
Phone: 919.297.0220

NC  
License:  
C-4647  
Apex, NC 27502  
westonandsampson.com

PROJECT REFERENCE NO.

BP7.C001

SHEET NO.

UC-03B

DESIGNED BY: KCZ

DRAWN BY: KCZ


CHECKED BY: KSH

APPROVED BY: KSH

REVISED:

NORTH CAROLINA  
DEPARTMENT OF  
TRANSPORTATION


UTILITIES ENGINEERING SEC.  
PHONE: (919) 707-6690  
FAX: (919) 250-4151




UTILITY CONSTRUCTION  
PLANS ONLY

### UTILITY CONSTRUCTION


DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED



PLAN BENDS



SECTION X-X  
BENDS & TEES




PLAN & ELEV.  
PLUGS

PIPE SIZE	90° BEND		45° BEND		22 1/2° BEND		11 1/4° BEND		PLUG	
	A	B	A	B	A	B	A	B	C	D
6"	10"	12"	8"	10"	8"	8"	8"	8"	12"	18"
8"	15"	12"	10"	10"	8"	8"	8"	8"	12"	24"
10"	16"	14"	10"	12"	6"	10"	6"	10"	14"	25"
12"	20"	16"	12"	14"	8"	12"	8"	12"	16"	30"
14"	22"	18"	14"	16"	10"	14"	10"	14"	18"	34"


- NOTES:
1. READY-MIX CONCRETE SHALL BE 3,000 PSI MINIMUM.
  2. SAKRETE SHALL NOT BE USED FOR CONCRETE THRUST BLOCKS.
  3. CONCRETE FOR THRUST BLOCKING SHALL BE KEPT FAIRLY DRY, THUS MAKING THE CONCRETE WEDGE SHAPE MORE EASILY FORMED WITH THE WIDEST PART (BLOCKING AREA) AGAINST UNDISTURBED SOIL.
  4. NO CONCRETE SHALL COVER ANY BOLTS OR GLANDS.
  5. ALL FITTING AND ACCESSORIES TO BE WRAPPED WITH 10 MIL POLYETHYLENE PRIOR TO POURING BLOCKING.

### THRUST BLOCK DETAIL

NOT TO SCALE



PLAN VIEW



FRONT VIEW

MINIMUM CUBIC YARDS OF CONCRETE	
PIPE DIAMETER	CUBIC YARDS
6"	1
8"	2
10"	3
12"	5
14"	7.25

### END OF LINE DEADMAN DETAIL

NOT TO SCALE


WATER DETAILS




5/14/20

V2/2024  
\\wse03-local\wse\Projects\NC\HNTB\Division 7\ENG22-0889\_BP7.C001.L\Rockingham County Utilities\Engineering\UC\Proj\BP7C001-ut-UC-03C.dtl.dgn  
03/22/2025 10:37:46 AM

Weston & Sampson  
WSE of North Carolina, PC  
2052 Energy Drive  
Phone: 919.297.0220  
NC License: C-4847  
Apex, NC 27502  
westonandsampson.com

PROJECT REFERENCE NO. BP7.C007		SHEET NO. UC-03C
DESIGNED BY: KCZ		
DRAWN BY: KCZ		
CHECKED BY: KSH		
APPROVED BY: KSH		
REVISED: NORTH CAROLINA DEPARTMENT OF TRANSPORTATION		
UTILITIES ENGINEERING SEC. PHONE: (919) 707-6690 FAX: (919) 250-4151		UTILITY CONSTRUCTION PLANS ONLY
UTILITY CONSTRUCTION		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		




\*\* SIZE OF BASE MAY NOT PERMIT BOOT IN WHICH CASE NON-SHRINK GROUT SHALL BE USED TO MAKE CONNECTION - REFER TO NOTE BELOW

NOTE:  
WHEN NON-FLEXIBLE CONNECTION IS APPROVED, FIRST PIPE JOINT SHALL BE NO MORE THAN 12" FROM MANHOLE WALL.


SHALLOW MANHOLE TYPE 1

NOT TO SCALE



SHALLOW MANHOLE TYPE 2

NOT TO SCALE




MANHOLE ABANDONMENT PROCEDURE

MANHOLES WHICH ARE TO BE ABANDONED WILL FIRST HAVE BOTH INFLUENT AND BOTH INFLUENT AND EFFLUENT LINES PLUGGED INSIDE THE MANHOLE WITH WATERTIGHT MASONRY. THE MINIMUM LENGTH OF WATERTIGHT MASONRY PLUGS WILL BE THE DIAMETER OF THE ABANDONED PIPE PLUS ONE FOOT. THE MANHOLE WILL THEN BE FILLED WITH INCOMPRESSIBLE MATERIAL (CRUSHED STONE OR AS APPROVED), TO A POINT THREE FEET (3'-0") BELOW THE FINISH GRADE. THE REMAINDER OF THE MANHOLE SHALL BE BROKEN DOWN AND REMOVED. THEN THE EXCAVATION SHALL BE BACKFILLED TO FINISH GRADE AS SPECIFIED UNDER TRENCH BACKFILL.

MANHOLE ABANDONMENT

NOT TO SCALE



- NOTES:
1. MANHOLE STEPS TO BE VERTICALLY IN LINE WITH "INVERT OUT" FOR PIPE 18" AND LESS. OVER 18" TO BE LOCATED IN LINE WITH BENCH.
  2. FOR MANHOLES LARGER THAN 4FT. DIA., MAINTAIN FULL MANHOLE DIA. TO 6FT. ABOVE INVERT BENCH.
  3. FOR 5FT. AND 6FT. DIA. MANHOLES, USE A TRANSITION CONE TO REDUCE TO 4FT. DIA.
  4. FOR 7FT. TO 10FT. DIA. MANHOLES, USE A TRANSITION TOP TO REDUCE TO 4FT. DIA.
  5. INSTALL MASTIC ON MANHOLE LID WITHIN GROUT ON THE INSIDE AND OUTSIDE TO SEAL MANHOLES.

STANDARD MANHOLE


NOT TO SCALE



SANITARY SEWER DETAILS

Weston & Sampson

WSE of North Carolina, PC  
2052 Energy Drive  
Phone: 919.297.0220

NC  
License:  
C-4847  
Apex, NC 27502  
westonandsampson.com

PROJECT REFERENCE NO.		SHEET NO.
BP7-C001		UC-03D
DESIGNED BY: KCZ		<div>UTILITY CONSTRUCTION PLANS ONLY</div>
DRAWN BY: KCZ		
CHECKED BY: KSH		
APPROVED BY: KSH		
REVISED:		
NORTH CAROLINA DEPARTMENT OF TRANSPORTATION		
UTILITIES ENGINEERING SEC. PHONE: (919) 707-6690 FAX: (919) 250-4151		
UTILITY CONSTRUCTION PLANS ONLY		
UTILITY CONSTRUCTION		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		





5/14/09

3/18/2025  
\\s06310001\WSE\Projects\NC\HNTB\Division 7\EN022-0889\BP7.C001\Rockingham County\Utilities\Engineering\UC\Pro\BP7C001-ut-UC-04\_psh.dgn

GENERAL NOTES:


1. THIS SHEET ONLY PERTAINS TO SANITARY SEWER ITEMS.  
REFER TO SHEET UC-4A FOR WATER LINE RELATED ITEMS.
2. CONTRACTOR SHALL PERFORM PUMP AND HAUL OPERATIONS OR PUMPING OPERATIONS BETWEEN THE SANITARY MANHOLES ON EITHER SIDE OF THE CONSTRUCTION LIMITS FOR THE INSTALLATION OF THE PROPOSED CASPPA PIPE AS SHOWN ON THIS SHEET. CONTRACTOR IS RESPONSIBLE FOR OBTAINING THE APPROPRIATE PERMIT.
3. AFTER THE INSTALLATION OF THE CASSPA PIPE, THE CONTRACTOR SHALL INSTALL THE 8" SANITARY GRAVITY SEWER IN CHURCH STREET TO RECONNECT THE SANITARY SEWER SYSTEM. REMOVE THE TEMPORARY PIPE PLUGS, TEMPORARY PIPING, AND PUMPS AS NEEDED TO PUT THE GRAVITY SEWER BACK INTO SERVICE.
4. AFTER THE GRAVITY SEWER RELOCATIONS HAVE BEEN COMPLETED, THEN THE WATER LINE IN CHURCH STREET SHALL BE CONSTRUCTED, TESTED, AND PLACED INTO SERVICE.
5. ACCORDING TO AS-BUILTS PROVIDED BY THE CITY OF EDEN, THE EXISTING 18" RCP GRAVITY SEWER NORTH OF CHURCH STREET IS ACTUALLY A 16" DIP, AND THE EXISTING 18" RCP GRAVITY SEWER SOUTH OF CHURCH STREET IS ACTUALLY AN 18" VCP.


NAD 83NA 2011

THE ESTIMATED QUANTITY OF DUCTILE IRON SEWER PIPE FITTINGS ON THIS PLAN SHEET IS 65 LBS. THE ACTUAL QUANTITY AND TYPE OF FITTINGS WILL VARY BASED ON FIELD CONDITIONS.

WATER / SANITARY SEWER UTILITY OWNERS ON THIS SHEET:  
CITY OF EDEN  
EXISTING UTILITIES:  
SEWER LINE: 8", 16"  
WATER LINE: 6", 8", 10", 12"  
CONTACT: BEVERLY O'DELL  
PHONE: (336) 612-8035

EXISTING MANHOLE TO REMAIN

PROJECT REFERENCE NO.		SHEET NO.	
BP7.C001		UC-04	
DESIGNED BY: KCZ			
DRAWN BY: KCZ			
CHECKED BY: KSH			
APPROVED BY: KSH			
REVISED:			
NORTH CAROLINA DEPARTMENT OF TRANSPORTATION		UTILITY CONSTRUCTION PLANS ONLY	
UTILITIES ENGINEERING SEC. PHONE: (919) 707-6690 FAX: (919) 250-4151			
UTILITY CONSTRUCTION			
UTILITY CONSTRUCTION PLANS ONLY			
UTILITY CONSTRUCTION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			
Weston & Sampson <sup>INC</sup>		NC License: C-4847	
WSE of North Carolina, PC 2052 Energy Drive Phone: 919.297.0220		Apex, NC 27502 westonandsampson.com	





5/14/09

3/18/2025  
\\wse\Projects\NC\HNTB\Division 7\EN022-0889\BP7.C001\Rockingham County\Utilities\Engineering\UC\Pro\BP7C001-ut-UC-04A-psd.dgn  
10/24/2027 4:00


- GENERAL NOTES:
1. THIS SHEET ONLY PERTAINS TO WATER LINE ITEMS.  
REFER TO SHEET UC-04 FOR SANITARY SEWER RELATED ITEMS.
  2. CONTRACTOR SHALL REMOVE 90 LF OF 12" WATER LINE AND INSTALL TEMPORARY DUCTILE IRON RESTRAINED JOINT PLUGS ON THE EXISTING 12" WATER LINE ON EITHER SIDE OF THE CONSTRUCTION LIMITS FOR THE INSTALLATION OF THE PROPOSED CASPPA PIPE AS SHOWN ON THIS SHEET. CONTRACTOR SHALL ALSO INSTALL A CONCRETE DEADMAN AT BOTH LOCATIONS AS SHOWN ON THIS SHEET. CONCRETE DEADMAN SHALL BE INSTALLED A MINIMUM OF 24 HOURS PRIOR TO THE TEMPORARY SHUT DOWN OF THE WATER LINE TO PERFORM THE REMOVAL AND PLUGGING OF THE WATER LINE. ROD THE PLUG TO THE DEADMAN TO PROVIDE RESTRAINT. SEE THE DETAIL ON SHEET UC-03B.
  3. AFTER THE INSTALLATION OF THE CASPPA PIPE, THE CONTRACTOR SHALL INSTALL THE 8" SANITARY GRAVITY SEWER IN CHURCH STREET TO RECONNECT THE SANITARY SEWER SYSTEM AND PLACE THE GRAVITY SEWER BACK INTO SERVICE.
  4. AFTER THE GRAVITY SEWER RELOCATIONS HAVE BEEN COMPLETED, THEN THE WATER LINE IN CHURCH STREET SHALL BE CONSTRUCTED, TESTED, AND PLACED INTO SERVICE.
  5. ACCORDING TO AS-BUILTS PROVIDED BY THE CITY OF EDEN, THE EXISTING 18" RCP GRAVITY SEWER NORTH OF CHURCH STREET IS ACTUALLY A 16" DIP, AND THE EXISTING 18" RCP GRAVITY SEWER SOUTH OF CHURCH STREET IS ACTUALLY AN 18" VCP.
  6. CONTRACTOR SHALL INSURE THAT THE EXISTING FIRE HYDRANT ON THE NE CORNER OF CHURCH STREET AND PARK ROAD REMAINS IN SERVICE DURING CONSTRUCTION. THE CITY OF EDEN BELIEVES THAT THE FIRE HYDRANT IS ACTUALLY CONNECTED TO THE WATER LINE ALONG PARK RD.
  7. THE CITY OF EDEN SHALL VERIFY WHETHER THIS IS AN ACTIVE WATER WELL, OR A WATER VAULT WITH A SERVICE LINE THAT IS CONNECTED TO THE WATER LINE IN CHURCH STREET, OR AN ABANDONED STRUCTURE NO LONGER IN SERVICE.



THE ESTIMATED QUANTITY OF DUCTILE IRON WATER PIPE FITTINGS ON THIS PLAN SHEET IS 390 LBS. THE ACTUAL QUANTITY AND TYPE OF FITTINGS WILL VARY BASED ON FIELD CONDITIONS.

WATER / SANITARY SEWER UTILITY OWNERS ON THIS SHEET:  
CITY OF EDEN  
EXISTING UTILITIES:  
SEWER LINE: 8", 16"  
WATER LINE: 6", 8", 10", 12"  
CONTACT: BEVERLY O'DELL  
PHONE: (336) 612-8035

PROJECT REFERENCE NO. BP7.C001		SHEET NO. UC-04A	
DESIGNED BY: KCZ			
DRAWN BY: KCZ			
CHECKED BY: KSH			
APPROVED BY: KSH			
REVISED:		UTILITY CONSTRUCTION PLANS ONLY	
NORTH CAROLINA DEPARTMENT OF TRANSPORTATION			
UTILITIES ENGINEERING SEC. PHONE: (919) 707-6690 FAX: (919) 250-4151			
<b>UTILITY CONSTRUCTION</b>			
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>			
		NC License: C-4847 Apex, NC 27502 westonandsampson.com	
WSE of North Carolina, PC 2052 Energy Drive Phone: 919.297.0220			



SEE NOTE #6  
INSTALL 12" DI PLUG  
INSTALL DEADMAN  
SEE NOTE #2  
**BEGIN PROJECT**  
-L- POT Sta. 10+70.00


12" 11.25" BEND  
WL-01  
ABANDON 12" UTILITY  
PIPE - 90 LF  
12" WATER  
LINE - 90 LF  
12" VALVE - 1 EA  
INSTALL 12" DI PLUG  
INSTALL DEADMAN  
SEE NOTE #2

WATER VAULT  
EIP  
SEE NOTE #7

**END PROJECT**  
-L- POT Sta. 14+75.00


TOP=539.11'  
INV. IN(N) =518.71'  
OLD INV. IN(E) =530.61'  
INV. IN(E) =519.11'  
INV. IN(W) =519.01'  
OLD INV. IN(W) =532.75'  
INV. OUT(S)=518.61'






5/28/24

I:\Projects\Engineering\UC\Proj\BP7C001\ut\_UC-06.pfl.dgn  
4/18/24




Weston & Sampson  
WSE of North Carolina, PC  
2062 Energy Drive  
Phone: 919.297.0220

NC  
License:  
C-4847  
Apex, NC 27502  
westonandsampson.com

PROJECT REFERENCE NO.		SHEET NO.	
BP7.C001		UC-06	
DESIGNED BY: KCZ			
DRAWN BY: KCZ			
CHECKED BY: KSH			
APPROVED BY: KSH			
REVISED:			
NORTH CAROLINA DEPARTMENT OF TRANSPORTATION		UTILITY CONSTRUCTION PLANS ONLY	
UTILITIES ENGINEERING SEC. PHONE: (919) 707-6690 FAX: (919) 250-4151			


UTILITY CONSTRUCTION

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED





WBS PROJECT: BP7.C001



STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS


**UTILITIES BY OTHERS PLANS**  
**ROCKINGHAM COUNTY**

LOCATION: REPLACE EXISTING CULVERT ON SR 1785 (CHURCH ST)


TYPE OF WORK: COMMUNICATIONS AND GAS DISTRIBUTION

T.I.P. NO.	SHEET NO.
BP7.C001	UO-1

NOTE:  
ALL UTILITY WORK SHOWN ON THIS SHEET WILL BE DONE BY OTHERS.  
NO PAYMENT WILL BE MADE TO THE CONTRACTOR FOR UTILITY WORK SHOWN ON THIS SHEET.



GRAPHIC SCALES



INDEX OF SHEETS

SHEET NO.:	DESCRIPTION:
UO-1	TITLE SHEET
UO-02	UBO PLAN SHEET

UTILITY OWNERS WITH CONFLICTS


- (A) COMMUNICATIONS - BRIGHTSPEED  
(B) GAS (DISTRIBUTION) - PNG

PREPARED IN THE OFFICE OF:



2641 Summer Boulevard  
Suite 116  
Raleigh, NC 27616  
(919) 878-7466

Matthew Ward PROJECT UTILITY COORDINATOR



DIVISION OF HIGHWAYS

DIVISION 7

DIV ADDRESS

1584 Yanceyville St  
Greensboro, 27405

DANIEL R. DAGENHART DIV BRIDGE PROGRAM MANAGER  
WRIGHT P. ARCHER, III, PE DIVISION ENGINEER  
KELVIN S. MARTIN DIV UTILITY ENGINEER

