


**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**

**This file or an individual page
shall not be considered a certified document.**

09/08/1999

See Sheet 1A For Index of Sheets
See Sheet 1B For Conventional Symbols



VICINITY MAP

●●●●● OFF-SITE DETOUR


STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

RANDOLPH COUNTY

LOCATION: REPLACE BRIDGE NO. 371 OVER PENWOOD BRANCH ON SR 2182 (ALLRED STREET)


TYPE OF WORK: GRADING, PAVING, DRAINAGE AND STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.8.R.101	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
17BP.8.R.101		P.E.	




TIP PROJECT: 17BP.8.R.101

CONTRACT: DH00220



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



DESIGN DATA

ADT (2016) =	815
ADT (2036) =	1365
K =	%
D =	%
T =	7 % *
V =	40 MPH
* TTST =	% DUAL %
FUNC CLASS =	COLLECTOR SUB-REGIONAL TIER

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT 17BP.8.R.101 =	0.051 MILES
TOTAL LENGTH TIP PROJECT 17BP.8.R.101 =	0.051 MILES

Prepared for the North Carolina Department of Transportation
In the office of:

ICA Engineering, Inc.
5121 Kingdom Way, Suite 100
Raleigh, NC 27607
NC License No: F-0258

2012 STANDARD SPECIFICATIONS	
RIGHT OF WAY DATE:	JUNE 17, 2016
LETTING DATE:	JANUARY 24, 2017


DENA C. SNEAD, PE PROJECT ENGINEER
ALEXANDER D. SNIDER, PE PROJECT DESIGN ENGINEER
TIM WELCH, PE NCDOT CONTACT DIV 8 BRIDGE PROGRAM MANAGER

HYDRAULICS ENGINEER


TRENTON J. CORMIER
12/14/2016
P.E.

ROADWAY DESIGN ENGINEER

ALEXANDER D. SNIDER
12/14/2016
P.E.



12/14/2016 RANDOLPH COUNTY, ICA ENGINEERING, INC.



**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

INDEX OF SHEETS	
SHEET NUMBER	SHEET
1	TITLE SHEET
1A	INDEX OF SHEETS, GENERAL NOTES, AND STANDARD DRAWINGS
1B	CONVENTIONAL SYMBOLS
1C-1	SURVEY CONTROL SHEET
2A-1	PAVEMENT SCHEDULE AND TYPICAL SECTIONS
3B-1	ROADWAY SUMMARIES
4 THRU 5	PLAN AND PROFILE SHEETS
TMP-1 THRU TMP-4	TRAFFIC MANAGEMENT PLANS
EC-1 THRU EC-4	EROSION CONTROL PLANS
UD-1 THRU UD-2	UTILITIES BY OTHERS PLANS
X-1 THRU X-3	CROSS-SECTIONS
C-1 THRU C-3	CULVERT PLANS

GENERAL NOTES:

2012 SPECIFICATIONS
 EFFECTIVE: 01-17-2012
 REVISED: 10-31-2014

**GRADE LINE:
 GRADING AND SURFACING:**

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. GRADE LINES MAY BE ADJUSTED AT THEIR BEGINNING AND ENDING AND AT STRUCTURES AS DIRECTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD III.

SUPERELEVATION:

ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:

ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01

SIDE ROADS:

THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

GUARDRAIL:

THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

TEMPORARY SHORING:

SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC WILL BE PAID FOR AS "EXTRA WORK" IN ACCORDANCE WITH SECTION 104-7.

UTILITIES:

UTILITY OWNERS ON THIS PROJECT ARE Duke Energy, CenturyLink, Piedmont Natural Gas, Time Warner Cable and City of Asheboro

ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS.

RIGHT-OF-WAY MARKERS:

ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY CONTRACT.

EFF. 01-17-2012
 REV. 10-30-2012

2012 ROADWAY ENGLISH STANDARD DRAWINGS

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch - N. C. Department of Transportation - Raleigh, N. C., Dated January, 2012 are applicable to this project and by reference hereby are considered a part of these plans:

STD.NO.	TITLE
DIVISION 2 - EARTHWORK	
200.03	Method of Clearing - Method III
225.02	Guide for Grading Subgrade - Secondary and Local
225.04	Method of Obtaining Superelevation - Two Lane Pavement
225.06	Method of Grading Sight Distance at Intersections
DIVISION 5 - SUBGRADE, BASES AND SHOULDERS	
560.01	Method of Shoulder Construction - High Side of Superelevated Curve - Method I
DIVISION 6 - ASPHALT BASES AND PAVEMENTS	
654.01	Pavement Repairs
DIVISION 8 - INCIDENTALS	
806.01	Concrete Right-of-Way Marker
862.01	Guardrail Placement
862.02	Guardrail Installation
876.01	Rip Rap in Channels

Note: Not to Scale

*S.U.E. = Subsurface Utility Engineering

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

CONVENTIONAL PLAN SHEET SYMBOLS

BOUNDARIES AND PROPERTY:

State Line	_____
County Line	-----
Township Line	-----
City Line	-----
Reservation Line	-----
Property Line	-----
Existing Iron Pin	○ EIP
Property Corner	✕
Property Monument	□ ECM
Parcel/Sequence Number	⑫③
Existing Fence Line	-x-x-x-
Proposed Woven Wire Fence	○
Proposed Chain Link Fence	□
Proposed Barbed Wire Fence	◇
Existing Wetland Boundary	--- WLB ---
Proposed Wetland Boundary	--- WLB ---
Existing Endangered Animal Boundary	--- EAB ---
Existing Endangered Plant Boundary	--- EPB ---
Known Soil Contamination: Area or Site	☠ ☠
Potential Soil Contamination: Area or Site	☠ ?

BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	○
Sign	○
Well	○ W
Small Mine	✕
Foundation	▭
Area Outline	▭
Cemetery	⊕
Building	▭
School	▭
Church	▭
Dam	▭

HYDROLOGY:

Stream or Body of Water	~~~~~
Hydro, Pool or Reservoir	▭
Jurisdictional Stream	--- JS ---
Buffer Zone 1	--- BZ 1 ---
Buffer Zone 2	--- BZ 2 ---
Flow Arrow	←
Disappearing Stream	→
Spring	○
Wetland	⌵
Proposed Lateral, Tail, Head Ditch	→ FLOW
False Sump	▽

RAILROADS:

Standard Gauge	_____
RR Signal Milepost	○
Switch	□ SWITCH
RR Abandoned	-----
RR Dismantled	-----

RIGHT OF WAY:

Baseline Control Point	◆
Existing Right of Way Marker	△
Existing Right of Way Line	_____
Proposed Right of Way Line	○ R/W
Proposed Right of Way Line with Iron Pin and Cap Marker	○ R/W ▲
Proposed Right of Way Line with Concrete or Granite R/W Marker	▲ R/W
Proposed Control of Access Line with Concrete CA Marker	○ C/A
Existing Control of Access	○ C/A
Proposed Control of Access	○ C/A
Existing Easement Line	--- E ---
Proposed Temporary Construction Easement	--- E ---
Proposed Temporary Drainage Easement	--- TDE ---
Proposed Permanent Drainage Easement	--- PDE ---
Proposed Permanent Drainage / Utility Easement	--- DUE ---
Proposed Permanent Utility Easement	--- PUE ---
Proposed Temporary Utility Easement	--- TUE ---
Proposed Aerial Utility Easement	--- AUE ---
Proposed Permanent Easement with Iron Pin and Cap Marker	◆

ROADS AND RELATED FEATURES:

Existing Edge of Pavement	-----
Existing Curb	-----
Proposed Slope Stakes Cut	--- C ---
Proposed Slope Stakes Fill	--- F ---
Proposed Curb Ramp	○ CR
Existing Metal Guardrail	— — — — —
Proposed Guardrail	— — — — —
Existing Cable Guiderail	— — — — —
Proposed Cable Guiderail	— — — — —
Equality Symbol	⊕
Pavement Removal	▨

VEGETATION:

Single Tree	☼
Single Shrub	☼
Hedge	~~~~~
Woods Line	~~~~~

Orchard	☼☼☼☼
Vineyard	▭ Vineyard

EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	▭ CONC
Bridge Wing Wall, Head Wall and End Wall	▭ CONC WW
MINOR:	
Head and End Wall	▭ CONC HW
Pipe Culvert	—
Footbridge	—
Drainage Box: Catch Basin, DI or JB	▭ CB
Paved Ditch Gutter	—
Storm Sewer Manhole	○ S
Storm Sewer	— S

UTILITIES:

POWER:	
Existing Power Pole	●
Proposed Power Pole	○
Existing Joint Use Pole	●
Proposed Joint Use Pole	○
Power Manhole	⊕
Power Line Tower	⊗
Power Transformer	⊗
U/G Power Cable Hand Hole	—
H-Frame Pole	●●
Recorded U/G Power Line	— P
Designated U/G Power Line (S.U.E.*)	--- P ---

TELEPHONE:

Existing Telephone Pole	●
Proposed Telephone Pole	○
Telephone Manhole	⊕
Telephone Booth	▭
Telephone Pedestal	⊕
Telephone Cell Tower	⊕
U/G Telephone Cable Hand Hole	—
Recorded U/G Telephone Cable	— T
Designated U/G Telephone Cable (S.U.E.*)	--- T ---
Recorded U/G Telephone Conduit	— TC
Designated U/G Telephone Conduit (S.U.E.*)	--- TC ---
Recorded U/G Fiber Optics Cable	— T FO
Designated U/G Fiber Optics Cable (S.U.E.*)	--- T FO ---

WATER:

Water Manhole	⊕
Water Meter	○
Water Valve	⊗
Water Hydrant	⊕
Recorded U/G Water Line	— W
Designated U/G Water Line (S.U.E.*)	--- W ---
Above Ground Water Line	— A/G Water

TV:

TV Satellite Dish	☼
TV Pedestal	⊕
TV Tower	⊗
U/G TV Cable Hand Hole	—
Recorded U/G TV Cable	— TV
Designated U/G TV Cable (S.U.E.*)	--- TV ---
Recorded U/G Fiber Optic Cable	— TV FO
Designated U/G Fiber Optic Cable (S.U.E.*)	--- TV FO ---

GAS:

Gas Valve	◇
Gas Meter	⊕
Recorded U/G Gas Line	— G
Designated U/G Gas Line (S.U.E.*)	--- G ---
Above Ground Gas Line	— A/G Gas

SANITARY SEWER:



Sanitary Sewer Manhole	⊕
Sanitary Sewer Cleanout	⊕
U/G Sanitary Sewer Line	— SS
Above Ground Sanitary Sewer	— A/G Sanitary Sewer
Recorded SS Forced Main Line	— FSS
Designated SS Forced Main Line (S.U.E.*)	--- FSS ---

MISCELLANEOUS:

Utility Pole	●
Utility Pole with Base	□
Utility Located Object	○
Utility Traffic Signal Box	⊕
Utility Unknown U/G Line	— ?UTL
U/G Tank; Water, Gas, Oil	▭
Underground Storage Tank, Approx. Loc.	⊕
A/G Tank; Water, Gas, Oil	▭
Geoenvironmental Boring	⊕
U/G Test Hole (S.U.E.*)	⊕
Abandoned According to Utility Records	AATUR
End of Information	E.O.I.

17BP.8.R.101 SURVEY CONTROL SHEET

8/17/09



BEGIN TIP PROJECT 17BP.8.R.101
-L- POT STA 10+09.54
LOCALIZED PROJECT COORDINATES
N = 724153.1170 E = 1766362.8960

END TIP PROJECT 17BP.8.R.101
-L- POT STA 20+45.70
LOCALIZED PROJECT COORDINATES
N = 723966.7660 E = 1767378.7015

BENCHMARK DATA	
BM1	ELEVATION = 699.63
N 724079	E 1766349
BL STATION 11+20.00 98 RIGHT	
RR SPIKE IN 20' POPLAR	

BASELINE DATA

BL POINT	DESC.	NORTH	EAST	ELEVATION	L STATION	OFFSET
1	GPS 750371-1	724081.5099	1765775.6516	738.33		OUTSIDE PROJECT LIMITS
2	GPS 750371-2	724198.0700	1766300.8390	709.87		OUTSIDE PROJECT LIMITS
3	BL-3	724102.4190	1766599.0987	695.23	12+50.67	13.63 LT
4	BL-4	724029.2182	1766908.1116	675.00	15+69.84	15.22 LT
5	BL-5	723982.5535	1767384.6213	696.00		OUTSIDE PROJECT LIMITS

DATUM DESCRIPTION

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "750371-2" WITH NAD 83/NA 2011 STATE PLANE GRID COORDINATES OF NORTHING: 724198.070(ft) EASTING: 1766300.839(ft) ELEVATION: 709.87(ft)

THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.999879204

THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "750371-2" TO -L- STATION 10+09.54 IS S 54°04'51.92" E 76.63'

ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
 VERTICAL DATUM USED IS NAVD 88

NOTES

- THE CONTROL DATA FOR THIS PROJECT WAS PROVIDED BY NCDOT. CONTROL POINTS PROVIDED ARE AS FOLLOWS:

750371-1	N = 724081.5099	E = 1765775.6515	ELEV. = 738.330
750371-2	N = 724198.0700	E = 1766300.8390	ELEV. = 709.870
- SITE CALIBRATION INFORMATION HAS NOT BEEN PROVIDED FOR THIS PROJECT. IF FURTHER INFORMATION IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.
- ◆ INDICATES GEODETIC CONTROL MONUMENTS USED OR SET FOR HORIZONTAL PROJECT CONTROL BY NCDOT.
 - ◆ INDICATES CONTROL MONUMENTS USED OR SET FOR HORIZONTAL PROJECT CONTROL BY NCDOT.


NOTE: DRAWING NOT TO SCALE

2/14/2016 10:41:54 AM C:\Users\randy_rdy\My Documents\17BP.8.R.101\17BP.8.R.101.dgn


PAVEMENT SCHEDULE

C1	PROP. APPROX. 2" ASPHALT CONCRETE SURFACE COURSE, TYPE SF9.5A, AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
C2	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE SF9.5A, AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 1½" IN DEPTH.
D1	PROP. APPROX. 3" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 342 LBS. PER SQ. YD.
D2	PROP. VAR. DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0X, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 2½" IN DEPTH OR GREATER THAN 4" IN DEPTH.
E1	PROP. APPROX 5.5" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 627 LBS. PER SQ. YD.
E2	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5½" IN DEPTH.
T	EARTH MATERIAL
U	EXISTING PAVEMENT
W	WEDGING (SEE DETAIL SHOWING METHOD OF WEDGING)

NOTE: ALL PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE




Detail Showing Method of Wedging
USE IN CONJUNCTION WITH TYPICAL SECTION NO. 1



TYPICAL SECTION NO. 1

-L-



TYPICAL SECTION NO. 2

-L-



ICA Engineering, Inc.
5121 Kingdom Way,
Suite 100
Raleigh, NC 27607
NC License No: F-0258

PROJECT REFERENCE NO.

17BP.8.R.J01

SHEET NO.

2A-1

ROADWAY DESIGN ENGINEER



DocuSigned by:
Alexander D. Smider
12/14/2016


**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

USE TYPICAL SECTION NO. 1 FROM:

-L- STA 13+50.00 TO -L- STA 14+90.00
-L- STA 15+40.00 TO -L- STA 16+17.00

USE TYPICAL SECTION NO. 2 FROM:

-L- STA 14+90.00 TO -L- STA 15+40.00






Note: A temporary asphalt wedge will be required immediately after milling to ensure smooth travel if the final layer of surface course is not placed on the same day as milling.

Incidental Milling Pavement Key-In Detail (Tie-In)

Professional Engineer seals for Alexander D. Snider and Newton J. Corrier, dated 12/14/2016. Includes text: 'DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED'.


Table with 2 columns: Station, Curve Data. Row 1: PI Sta 11+18.23, Δ = 0° 39' 17.3" (RT), D = 0' 33' 13.8", L = 118.23', T = 59.11', R = 10,345.10'. Row 2: PI Sta 15+72.79, Δ = 1° 19' 52.0" (LT), D = 2' 25' 40.0", L = 466.73', T = 234.13', R = 2,360.00', SE = SEE PLANS.



NOTE: FOR CUT CONDITION, USE CLASS II RIP RAP FLOOD BENCH BORDER WITH NATURAL GROUND COVERED WITH COIR FIBER MAT INSIDE BORDER. IN FILL CONDITION, USE CLASS II RIP RAP FILL THROUGHOUT WITH NATIVE BED MATERIAL FILLING THE VOIDS ON TOP.

FOR -L- PROFILE, SEE SHEET 5


8/17/19 14/2016 ICA ENGINEERING, INC.



8/17/09



PROJECT REFERENCE NO. <i>17BP.8.RJ01</i>	SHEET NO. 5
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
DocuSigned by: <i>Alexander D. Smiles</i> 12/14/2016	DocuSigned by: <i>Devon J. Corbett</i> 12/14/2016
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	





8/13/2016
C:\Users\p\OneDrive\Projects\17BP.8.RJ01\RDY_PFL_05.dgn
ICA ENGINEERING, INC.

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

TRANSPORTATION MANAGEMENT PLAN

RANDOLPH COUNTY




LOCATION: REPLACE BRIDGE NO. 371 OVER PENWOOD BRANCH ON SR 2182 (ALLRED ST)

TYPE OF WORK: GRADING, PAVING, DRAINAGE AND STRUCTURE

N.C.D.O.T. WORK ZONE TRAFFIC CONTROL
1561 MAIL SERVICE CENTER (MSC) RALEIGH, NC 27699-1561
750 N. GREENFIELD PARKWAY, GARNER, NC 27529 (DELIVERY)
PHONE: (919) 773-2800 FAX: (919) 771-2745

J. S. BOURNE, P.E. STATE TRAFFIC MANAGEMENT ENGINEER
M. STEELMAN TRAFFIC CONTROL PROJECT ENGINEER
M. T. RZEPKA, P.E. TRAFFIC CONTROL PROJECT DESIGN ENGINEER
TRAFFIC CONTROL DESIGN ENGINEER



INDEX OF SHEETS

SHEET NO.	TITLE
TMP-1	TITLE SHEET, VICINITY MAP, AND INDEX OF SHEETS
TMP-1A	LIST OF APPLICABLE ROADWAY STANDARD DRAWINGS, AND LEGEND
TMP-1B	TRANSPORTATION OPERATIONS PLAN: (MANAGEMENT STRATEGY GENERAL NOTES, LOCAL NOTES AND PHASING)
TMP-2	ALLRED ST. SIGN DESIGN
TMP-3	DETOUR FOR ALLRED STREET
TMP-4	ROAD CLOSURE SIGNS AND DETOUR SIGNS

SHEET NO.
TMP-1


17BP.8.R.101

TIP PROJECT:

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

APPROVED: *Michael T. Rzepka*
DATE: 12/14/2016

SEAL



ICA Engineering, Inc.
5121 Kingdom Way,
Suite 100
Raleigh, NC 27607
NC License No: F-0258


ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS SHOWN IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2012 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

<u>STD. NO.</u>	<u>TITLE</u>
1101.03	TEMPORARY ROAD CLOSURES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.01	STATIONARY WORK ZONE SIGNS
1145.01	BARRICADES

LEGEND


GENERAL

 NORTH ARROW




TRAFFIC CONTROL DEVICES

 BARRICADE (TYPE III)

TEMPORARY SIGNING

 STATIONARY SIGN

12/12/2016
 P:\LIBR\Projects\Div08\Rand...371\Traffic\TrafficControl\TCP\and371_tmp_file.dgn
 ICA Engineering

APPROVED:  <small>DocuSigned by: Michael T. Rzepka 01BC3490C26049D...</small> DATE: 12/14/2016 SEAL 		<p style="text-align: center;">ROADWAY STANDARD DRAWINGS & LEGEND</p>
<p style="text-align: center;">DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</p>		

GENERAL NOTES

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS, AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS OR RESULT IN DUPLICATE OR UNDESIRED OVERLAPPING OF DEVICES. MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING, OR REMOVAL OF DEVICES AS DIRECTED BY THE ENGINEER.

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT EXCEPT WHEN OTHERWISE NOTED IN THE PLAN OR DIRECTED BY THE ENGINEER.

TRAFFIC PATTERN ALTERATIONS

- A) NOTIFY THE ENGINEER TWENTY ONE (21) CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION.

SIGNING

- B) PROVIDE SIGNING AND DEVICES REQUIRED TO CLOSE THE ROAD ACCORDING TO THE ROADWAY STANDARD DRAWINGS AND TRAFFIC CONTROL PLANS.

PROVIDE SIGNING REQUIRED FOR THE OFF-SITE DETOUR ROUTE AS SHOWN IN THE TRAFFIC CONTROL PLANS.

- C) COVER OR REMOVE ALL SIGNS AND DEVICES REQUIRED TO CLOSE THE ROAD WHEN ROAD CLOSURE IS NOT IN OPERATION.

COVER OR REMOVE ALL SIGNS REQUIRED FOR THE OFF-SITE DETOUR WHEN THE DETOUR IS NOT IN OPERATION.

- D) ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY TRAFFIC PATTERN.

LOCAL NOTES

- 1) MAINTAIN ACCESS TO ALL RESIDENCES AND BUSINESSES BETWEEN THE CLOSURE POINTS AT ALL TIMES DURING CONSTRUCTION.

MANAGEMENT STRATEGY

THIS PROJECT CONSISTS OF REPLACING BRIDGE NO. 371 OVER PENWOOD BRANCH ON SR 2182 (ALLRED ST). DURING CONSTRUCTION, SR 2182 (ALLRED ST) WILL BE CLOSED AT THE CONSTRUCTION LIMITS AND TRAFFIC WILL BE PLACED ON AN OFF-SITE DETOUR ALONG US 220 BUS, OLD LIBERTY RD, CENTRAL FALLS RD, DRAPER ST AND GOLD HILL RD.

SR 2182 (ALLRED ST) WILL BE REOPENED TO 2-LANE/2-WAY TRAFFIC UPON COMPLETION OF CONSTRUCTION.

PHASING

STEP 1

USING ROADWAY STANDARD DRAWING 1101.03 (SHEET 1 OF 9), INSTALL ROAD CLOSURE AND DETOUR SIGNS. CLOSE SR 2182 (ALLRED ST) AND DETOUR TRAFFIC.

STEP 2

REMOVE EXISTING BRIDGE.

STEP 3

CONSTRUCT PROPOSED STRUCTURE AND ROADWAY.


STEP 4

PLACE FINAL PAVEMENT MARKINGS AND MARKERS ON SR 2182 (ALLRED ST) AND OPEN ROAD TO TRAFFIC.


STEP 5

REMOVE ALL WORK ZONE TRAFFIC CONTROL DEVICES.


12/12/2016 P:\BRP\projects\Div08\Rand..371\Traffic\TrafficControl\TCP\and371_tmp-fHle_ib.dgn ICA Engineering

APPROVED: 
DATE: 12/14/2016

SEAL



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



TRANSPORTATION OPERATIONS PLAN



ICA Engineering, Inc.
5121 Kingdom Way,
Suite 100
Raleigh, NC 27607
NC License No: F-0258

PROJ. REFERENCE NO.	SHEET NO.
17BP.8.R.101	TMP-2

SIGN NUMBER: ALLRED STREET **BACKG COLOR:** Fluorescent Orange
TYPE: STATIONARY **COPY COLOR:** Black

DESIGN BY: MTR
PROJECT ID: 17BP.8.R.101

CHECKED BY:
DIV: 8

DATE: Jul 18, 2016

QUANTITY: SEE PLANS


SYMBOL	X	Y	WID	HT

SIGN WIDTH: 2'-6"
HEIGHT: 2'-0"
TOTAL AREA: 5.0 Sq.Ft.

BORDER TYPE: INSET
RECESS: 0.47"
WIDTH: 0.63"
RADII: 1.5"

NO. Z BARS:
LENGTH:

MAT'L: 0.080" (2.0 mm) ALUMINUM



- USE NOTES:** 1,2
1. Legend and border shall be direct applied black non-reflective sheeting.
 2. Background shall be NC GRADE B fluorescent orange retroreflective sheeting.

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter										Series/Size
										Text Length
	A	l	l	r	e	d				C 2000
7.4	3.8	1.6	1.6	2.1	3.1	2.6	7.9			14.7
	S	t	r	e	e	t				C 2000
7.4	3.2	2.3	2	3.1	2.8	1.8	7.4			15.2

FILENAME: rand371_tmp_spec_sign_2

NORTH CAROLINA D.O.T. SIGN DETAIL

APPROVED: *Michael T. Rzepka*
DocuSigned by: Michael T. Rzepka 018C3480C26049D

DATE: 12/14/2016



SEAL

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED





ALLRED STREET SIGN DESIGN


12/12/2016
 P:\LIBR\Projects\01v08\Rand..371\Traffic\TrafficControl\TCP\rand371_tmp_spec_sign_2.dgn
 ICA Engineering



NOTES: SEE SHEET TMP-4 FOR ROAD CLOSURE SIGNS AND DETOUR SIGNS
 REFER TO RSD 1101.03 (SHEET 1 OF 9) FOR APPLICABLE NOTES


12/12/2016
 P:\LIBR\Projects\Div08\Rand...371\Traffic\TrafficControl\TCP\rand371_tmp_detour_3.dgn
 ICA Engineering

APPROVED: 
 DATE: 12/14/2016
 SEAL




**DETOUR FOR
ALLRED ST.**


**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



TYPE III BARRICADE(S)


(A)

- L- STA 13+50±
- L- STA 20+50±




TYPE III BARRICADE

(B)




TYPE III BARRICADE


(C)




(D)




(E)




(F)




(G)




(H)




(I)




(J)



(K)



(L)




(M)

NOTE: SEE SHEET TMP-2 FOR ALLRED STREET SIGN DESIGN

12/14/2016
P:\BRP\projects\Div08\Rand...371\Traffic\TrafficControl\TCP\and371\mp_signs_4.dgn
ICA Engineering

APPROVED: *Michael T. Rzepka*
DATE: 12/14/2016
SEAL
NORTH CAROLINA PROFESSIONAL ENGINEER
SEAL 15876
MICHAEL T. RZEPKA




ROAD CLOSURE SIGNS AND DETOUR SIGNS

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.8.R.101	EC-1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS
PLAN FOR PROPOSED
HIGHWAY EROSION CONTROL
RANDOLPH COUNTY

**BRIDGE NO. 371 OVER PENWOOD BRANCH
ON SR 2182 (ALLRED STREET)**




EROSION AND SEDIMENT CONTROL MEASURES


Std. #	Description	Symbol
1630.03	Temporary Silt Ditch	TD
1630.05	Temporary Diversion	TD
1605.01	Temporary Silt Fence	
1606.01	Special Sediment Control Fence	▲▲▲
1622.01	Temporary Berms and Slope Drains	—
1630.02	Silt Basin Type B	▨
1633.01	Temporary Rock Silt Check Type-A	⊗
	Temporary Rock Silt Check Type-A with Matting and Polyacrylamide (PAM)	⊗
1633.02	Temporary Rock Silt Check Type-B	▶
	Wattle / Coir Fiber Wattle	—
	Wattle / Coir Fiber Wattle with Polyacrylamide (PAM)	—
1634.01	Temporary Rock Sediment Dam Type-A	▬
1634.02	Temporary Rock Sediment Dam Type-B	▬
1635.01	Rock Pipe Inlet Sediment Trap Type-A	⊓
1635.02	Rock Pipe Inlet Sediment Trap Type-B	⊓
1630.04	Stilling Basin	▭
1630.06	Special Stilling Basin	▭
	Rock Inlet Sediment Trap:	
1632.01	Type A	A
1632.02	Type B	B
1632.03	Type C	C
	Skimmer Basin	▭
	Tiered Skimmer Basin	▭
	Infiltration Basin	▭

**THIS PROJECT CONTAINS
EROSION CONTROL PLANS
FOR CLEARING AND
GRUBBING PHASE OF
CONSTRUCTION.**

TRENTON J. CORMIER, PE
ROADSIDE ENVIRONMENTAL ENGINEER
3377
LEVEL III CERTIFICATION NUMBER
ALEXANDER D. SNIDER, PE
ROADSIDE ENVIRONMENTAL PROJECT ENGINEER
3064
LEVEL III CERTIFICATION NUMBER



GRAPHIC SCALE



THESE EROSION AND SEDIMENT CONTROL PLANS COMPLY WITH THE REGULATIONS SET FORTH BY THE NCG-010000 GENERAL CONSTRUCTION PERMIT EFFECTIVE AUGUST 1, 2016 AND ISSUED BY THE NORTH CAROLINA DEPARTMENT OF ENVIRONMENT AND NATURAL RESOURCES DIVISION OF WATER RESOURCES.

Prepared In the Office of:



Designed by:

TRENTON J. CORMIER, PE 3377
NAME LEVEL III CERTIFICATION NO.

Reviewed In the Office of:

ROADSIDE ENVIRONMENTAL UNIT
1 South Wilmington St.
Raleigh, NC 27611
2012 STANDARD SPECIFICATIONS

Reviewed by:

BARRY HARRINGTON, P.E.

Roadway Standard Drawings

The following roadway english standards as appear in "Roadway Standard Drawings"- Roadway Design Unit - N. C. Department of Transportation - Raleigh, N. C., dated January 2012 and the latest revision thereto are applicable to this project and by reference hereby are considered a part of these plans.

1604.01 Railroad Erosion Control Detail	1632.01 Rock Inlet Sediment Trap Type A
1605.01 Temporary Silt Fence	1632.02 Rock Inlet Sediment Trap Type B
1606.01 Special Sediment Control Fence	1632.03 Rock Inlet Sediment Trap Type C
1607.01 Gravel Construction Entrance	1633.01 Temporary Rock Silt Check Type A
1622.01 Temporary Berms and Slope Drains	1633.02 Temporary Rock Silt Check Type B
1630.01 Riser Basin	1634.01 Temporary Rock Sediment Dam Type A
1630.02 Silt Basin Type B	1634.02 Temporary Rock Sediment Dam Type B
1630.03 Temporary Silt Ditch	1635.01 Rock Pipe Inlet Sediment Trap Type A
1630.04 Stilling Basin	1635.02 Rock Pipe Inlet Sediment Trap Type B
1630.05 Temporary Diversion	1640.01 Coir Fiber Baffle
1630.06 Special Stilling Basin	1645.01 Temporary Stream Crossing
1631.01 Matting Installation	

12/14/2016 ICA ENGINEERING, INC. erosion_tsh.dgn

DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

SOIL STABILIZATION TIMEFRAMES

<i>SITE DESCRIPTION</i>	<i>STABILIZATION TIME</i>	<i>TIMEFRAME EXCEPTIONS</i>
PERIMETER DIKES, SWALES, DITCHES AND SLOPES	7 DAYS	NONE
HIGH QUALITY WATER (HQW) ZONES	7 DAYS	NONE
SLOPES STEEPER THAN 3:1	7 DAYS	IF SLOPES ARE 10' OR LESS IN LENGTH AND ARE NOT STEEPER THAN 2:1, 14 DAYS ARE ALLOWED.
SLOPES 3:1 OR FLATTER	14 DAYS	7 DAYS FOR SLOPES GREATER THAN 50' IN LENGTH.
ALL OTHER AREAS WITH SLOPES FLATTER THAN 4:1	14 DAYS	NONE, EXCEPT FOR PERIMETERS AND HQW ZONES.

8.17.7/99
 12/14/2016
 P:\Hydro\3711\17BP.8.R.101\Control\cadd\17BP.8.R.101_hyd_erosion_c&g.dgn
 ICA ENGINEERING, INC.

CLEARING AND GRUBBING
 EROSION CONTROL FOR
 CONSTRUCTION SHEET 4






ICA Engineering, Inc.
 5121 Kingdom Way,
 Suite 100
 Raleigh, NC 27607
 NC License No: F-0258

PROJECT REFERENCE NO.	SHEET NO.
17BP.8.R.101	EC-3/CONST.4

ROADSIDE ENVIRONMENTAL PROJECT ENGINEER

LEVEL III CERTIFIED BY:
TRENTON J. CORMIER, PE
 CERTIFICATION NUMBER: 3377
 ISSUED: DECEMBER 13, 2016






NOTE:
 ALL EROSION CONTROL DEVICES SHOWN ARE LOCATED WITHIN EXISTING RW OR EASEMENT.

NOTE:
 PERIMETER EROSION CONTROL MEASURES SHALL BE INSTALLED DURING CLEARING AND GRUBBING PHASE.

NOTE:
 PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B AND TEMPORARY ROCK SILT CHECKS TYPE - A AT DRAINAGE OUTLETS.

FOR -L- PROFILE, SEE SHEET 5



**CULVERT PHASING
SF-750371**

PHASE 1

- 1.) INSTALL ALL TEMPORARY SEDIMENT CONTROL DEVICES NECESSARY FOR CULVERT CONSTRUCTION.
- 2.) INSTALL SPECIAL STILLING BASIN WITHIN FOOTPRINT OF PROPOSED ROADWAY. SPECIAL STILLING BASIN CAPACITY SHOULD ALLOW FOR A MINIMUM OF 114 CUBIC YARDS OF EFFLUENT WHICH IS HALF OF THE VOLUME FROM THE PROPOSED CULVERT. PUMP ALL EFFLUENT INTO SPECIAL STILLING BASIN.
- 3.) INSTALL IMPERVIOUS DIKES AND INSTALL 30" TEMP. PIPE.
- 4.) DE-WATER EFFLUENT FROM WORK SITE INTO SPECIAL STILLING BASIN.
- 5.) CONSTRUCT PROPOSED 32'9" x 12'0" ALUMINUM BOX CULVERT AND FLOOD BENCH PER PLANS.
- 6.) STABILIZE CHANNEL BANKS.

PHASE 2

- 6.) REMOVE TEMPORARY IMPERVIOUS DIKES AND TEMP. PIPE TO ALLOW FLOW THROUGH NEWLY CONSTRUCTED CULVERT.
- 7.) UPON STABILIZATION OF ALL DISTURBED AREAS, REMOVE ALL TEMPORARY SEDIMENT CONTROL DEVICES.

8.17.7.99
12/14/2016
F:\Hydro\Projects\Erosion Control\cadd\17BP.8.R.101_hyd_erosion_f.mxd.dgn
ICA ENGINEERING, INC.


HR ICA
ICA Engineering, Inc.
5121 Kingdom Way,
Suite 100
Raleigh, NC 27607
NC License No: F-0258

PROJECT REFERENCE NO.	SHEET NO.
17BP.8.R.101	EC-4/CONST.4

ROADSIDE ENVIRONMENTAL PROJECT ENGINEER

LEVEL III CERTIFIED BY:
TRENTON J. CORMIER, PE
CERTIFICATION NUMBER: 3377
ISSUED: DECEMBER 13, 2016


FINAL EROSION CONTROL FOR
CONSTRUCTION SHEET 4



FOR -L- PROFILE, SEE SHEET 5

09/08/99

TIP PROJECT: 17BP.8.R.101



●●●●● OFF-SITE DETOUR

STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS


UTILITIES BY OTHERS PLANS RANDOLPH COUNTY

LOCATION: REPLACE BRIDGE NO. 371 OVER PENWOOD BRANCH
ON SR 2182 (ALLRED RD)


TYPE OF WORK: GRADING, PAVING, DRAINAGE AND STRUCTURE

T.I.P. NO.	SHEET NO.
17BP.8.R.101	UO-01

NOTE:
ALL UTILITY WORK SHOWN ON THIS SHEET IS DONE BY OTHERS.
NO PAYMENT WILL BE MADE TO THE CONTRACTOR FOR UTILITY WORK SHOWN ON THIS SHEET.



UO-02



GRAPHIC SCALES



INDEX OF SHEETS

SHEET NO.:	DESCRIPTION:
UO-01	TITLE SHEET
UO-02	UBO PLAN SHEET

UTILITY OWNERS WITH CONFLICTS


- (A) DUKE ENERGY PROGRESS - POWER
- (B) CENTURYLINK - TELEPHONE
- (C) PIEDMONT NATURAL GAS - GAS
- (D) CHARTER COMMUNICATIONS - CATV
- (E) CITY OF ASHEBORO - WATER & SEWER

PLANS PREPARED BY:



3220 GLEN ROYAL RD. RALEIGH, NC 27617
 TELE 919.788.0224 FAX 919.788.0232
 NC LICENSE #P-0189

UTILITIES PROJECT ENGINEER
 Mary Jo Lee, P.E.



DIVISION OF HIGHWAYS
 UTILITIES UNIT
 1555 MAIL SERVICES CENTER
 RALEIGH, NC 27699-1555
 PHONE (919) 707-6690
 FAX (919) 250-4151

UTILITIES REGIONAL ENGINEER
 UTILITIES ENGINEER
 JAMIE YOW DIV. UTILITIES COORDINATOR
 UTILITIES COORDINATOR




10/19/2016
 R:\Utilities\Engineering\UBO\Proj\RAND371\ut_tsh_u001_psh.dgn
 -USERNAME-

UTILITIES BY OTHERS


CH ENGINEERING
 3220 GLEN ROYAL RD. RALEIGH, NC 27617
 TELE 919.788.0224 FAX 919.788.0232
 NC LICENSE #P-0189


NOTE:
 ALL PROPOSED UTILITY WORK SHOWN ON THIS SHEET WILL BE DONE BY OTHERS. NO PAYMENT WILL BE MADE TO THE CONTRACTOR FOR PROPOSED UTILITY WORK SHOWN ON THIS SHEET.

-L-	
PI Sta 11+18.23	PI Sta 15+72.79
$\Delta = 0^\circ 39' 17.3" (RT)$	$\Delta = 1^\circ 19' 52.0" (LT)$
$D = 0^\circ 33' 13.8"$	$D = 2^\circ 25' 40.0"$
$L = 118.23'$	$L = 466.73'$
$T = 59.11'$	$T = 234.13'$
$R = 10,345.10'$	$R = 2,360.00'$
	SE = SEE PLANS




8/17/99
 10/19/2016
 N:\SERVICES\Engineering\UBO\ProJ\17BP.8.R.101\UO-02.psh.dgn





75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



16+50.00


EXIST. EXIST.

676.62


16+17.00

0

BM #1: RR SPIKE IN 20" POPLAR, 75' RT. OF STA. 10+15.00 -L-, EL. 699.63



LOCATION SKETCH



PROFILE ALONG CULVERT

DRAWN BY : H. B. DESAI DATE : 9/13/16
 CHECKED BY : H. LOCKLEAR DATE : 9-21-16
 DESIGN ENGINEER OF RECORD: R. P. PATEL DATE : 9-21-16

ROADWAY DATA	
GRADE POINT EL. @ STA. 15+14.00 -L-	= 678.37
BED ELEVATION @ STA. 15+14.00 -L-	= 662.21
ROADWAY SLOPES	= 2 : 1
HYDRAULIC DATA	
DESIGN DISCHARGE	= 1800 C.F.S.
FREQUENCY OF DESIGN FLOOD	= 50 YRS
DESIGN HIGH WATER ELEVATION	= 673.6
DRAINAGE AREA	= 2.9 SQ. MI.
BASE DISCHARGE (Q100)	= 2000 C.F.S.
BASE HIGH WATER ELEVATION	= 674.16
OVERTOPPING FLOOD DATA	
OVERTOPPING DISCHARGE	= 2800 C.F.S.
FREQUENCY OF OVERTOPPING FLOOD	= 500+ YRS
OVERTOPPING FLOOD ELEVATION	= 677.1

TOTAL STRUCTURE QUANTITIES	
REMOVAL OF EXISTING STRUCTURE	LUMP SUM
CULVERT EXCAVATION	LUMP SUM
FOUNDATION CONDITIONING MATERIAL	132 TONS
CLASS A CONCRETE	7.5 C.Y.
REINFORCING STEEL	789 LBS.
ASBESTOS ASSESSMENT	LUMP SUM
ALUMINUM BOX CULVERT	LUMP SUM
PLACEMENT OF NATURAL STREAM BED MATERIAL	LUMP SUM
CULVERT BACKFILL	670 TONS

NOTES

- ASSUMED LIVE LOAD = HL-93 OR ALTERNATE LOADING.
- DESIGN FILL = 4.91' MAXIMUM AND 3.50' MINIMUM ABOVE THE CROWN OF THE CULVERT.
- FOR OTHER DESIGN DATA AND NOTES SEE STANDARD NOTE SHEET.
- THE RESIDENT ENGINEER SHALL CHECK THE LENGTH OF CULVERT BEFORE STAKING IT OUT TO MAKE CERTAIN THAT IT WILL PROPERLY TAKE CARE OF THE FILL.
- THE EXISTING STRUCTURE CONSISTING OF ONE SPAN @ 20'-10" WITH A TIMBER DECK ON STEEL GIRDER/FLOOR BEAM SYSTEM AND A CLEAR ROADWAY OF 24'-10" ON TIMBER CAPS AND TIMBER PILES AND LOCATED AT THE PROPOSED STRUCTURE SHALL BE REMOVED. THE EXISTING BRIDGE IS PRESENTLY POSTED FOR THE LEGAL LOAD LIMIT. SHOULD THE STRUCTURAL INTEGRITY OF THE BRIDGE FURTHER DETERIORATE, THIS LOAD LIMITATION MAY BE REDUCED AS FOUND NECESSARY DURING THE LIFE OF THE PROJECT.
- REMOVAL OF THE EXISTING BRIDGE SHALL BE PERFORMED IN A MANNER THAT PREVENTS DEBRIS FROM FALLING INTO THE WATER. THE CONTRACTOR SHALL SUBMIT DEMOLITION PLANS FOR REVIEW AND REMOVE THE BRIDGE IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS.
- INASMUCH AS THE PAINT SYSTEM ON THE EXISTING STRUCTURAL STEEL CONTAINS LEAD, THE CONTRACTOR'S ATTENTION IS DIRECTED TO ARTICLE 107-1 OF THE STANDARD SPECIFICATIONS. ANY COSTS RESULTING FROM COMPLIANCE WITH APPLICABLE STATE OR FEDERAL REGULATIONS PERTAINING TO HANDLING OF MATERIALS CONTAINING LEAD BASED PAINT SHALL BE INCLUDED IN THE BID PRICE FOR REMOVAL OF EXISTING STRUCTURE AT STATION 15+14.00 -L-
- THE SUBSTRUCTURE OF THE EXISTING BRIDGE INDICATED ON THE PLANS IS FROM THE BEST INFORMATION AVAILABLE. THIS INFORMATION IS SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR. THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT OF TRANSPORTATION FOR ANY DELAYS OR ADDITIONAL COST INCURRED BASED ON DIFFERENCE BETWEEN THE EXISTING BRIDGE SUBSTRUCTURE SHOWN ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.
- FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.
- FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.
- FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.
- FOR ASBESTOS ASSESSMENT FOR BRIDGE DEMOLITION AND RENOVATION ACTIVITIES, SEE SPECIAL PROVISIONS.
- SEE SECTION 414 OF THE STANDARD SPECIFICATION FOR CULVERT EXCAVATION AND BACKFILLING.
- NATIVE MATERIAL SHALL BE USED TO BACKFILL THE CULVERT BETWEEN THE SILLS. NATIVE MATERIAL CONSISTS OF MATERIAL THAT IS EXCAVATED FROM THE STREAM BED OR FLOODPLAIN AT THE PROJECT SITE DURING CONSTRUCTION. ONLY MATERIAL THAT IS EXCAVATED FROM THE STREAM BED MAY BE USED TO LINE THE LOW FLOW CULVERT BARREL. RIP RAP MAY BE USED TO SUPPLEMENT NATIVE MATERIAL IN THE HIGH FLOW BARREL(S). IF RIP RAP IS USED TO LINE THE HIGH FLOW CULVERT BARREL(S), NATIVE MATERIAL SHOULD BE PLACED ON TOP TO FILL VOIDS AND PROVIDE A FLAT SURFACE FOR ANIMAL PASSAGE. NATIVE MATERIAL IS SUBJECT TO APPROVAL BY THE ENGINEER AND MAY BE SUBJECT TO PERMIT CONDITIONS.
- FOR ALUMINUM BOX CULVERT, SEE SPECIAL PROVISIONS
- ALL MATERIALS SHALL MEET THE REQUIREMENTS OF THE NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES DATED JANUARY 2012.
- THE DETAILS SHOWN ARE FOR GENERAL LAYOUT ONLY. THE SUPPLIER SHALL PROVIDE DESIGNS AND DETAILS FOR REVIEW AND APPROVAL THAT MEET THE REQUIREMENTS OF AASHTO SECTION 12, AND ARE SEALED BY A NORTH CAROLINA REGISTERED PROFESSIONAL ENGINEER.
- UNLESS OTHERWISE INDICATED, THE SUPPLIER SHALL DESIGN DETAIL, AND FURNISH ALL STRUCTURAL ELEMENTS AND HARDWARE.
- GUARDRAIL POST LOCATIONS SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER TO ENSURE ADEQUATE COVER FOR INSTALLATION.
- FOR CULVERT DIVERSION DETAILS AND PAY ITEMS, SEE EROSION CONTROL PLANS.
- FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

I HEREBY CERTIFY THESE PLANS ARE THE AS-BUILT PLANS

PROJECT NO. 17BP.8.R.101
 RANDOLPH COUNTY
 STATION: 15+14.00 -L-


SHEET 1 OF 3 REPLACES BRIDGE NO. 371




STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 32'-9" x 12'-0"
 ALUMINUM BOX CULVERT
 98° SKEW

REVISIONS						SHEET NO. C-1
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			TOTAL SHEETS 3
2			4			

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




CULVERT SECTION NORMAL TO ROADWAY




END ELEVATION


SECTION B-B




PLAN OF MOMENT SLAB



FLOOR SILL/BAFFLE LAYOUT



ELEVATION SECTION A-A



FLOOR SILL ELEVATION

BILL OF MATERIAL					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
A1	134	#4	STR	5'-8"	507
B1	24	#4	STR	17'-7"	282
REINFORCING STEEL				789 LBS.	
CLASS A CONCRETE				7.5 C.Y.	

PROJECT NO. 17BP.8.R.101
 RANDOLPH COUNTY
 STATION: 15+14.00 -L-
 SHEET 2 OF 3




STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 32'-9" x 12'-0"
 ALUMINUM BOX CULVERT
 98° SKEW

DRAWN BY: R. P. PATEL DATE: 9-20-16
 CHECKED BY: H. LOCKLEAR DATE: 9-21-16
 DESIGN ENGINEER OF RECORD: R. P. PATEL DATE: 9-21-16

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:	C-2	
1			3			TOTAL SHEETS	
2			4			3	




PLAN

† ALUMINUM WING WALL DIMENSIONS TO BE DETERMINED BY THE ENGINEER
 * THIS DIMENSION TO BE CONFIRMED BY THE ENGINEER IN THE FIELD.


NOTES

- THE GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS SHALL CONSIST OF THE FOLLOWING COMPONENTS :
- A. FERRULES SHALL BE MADE FROM STEEL MEETING THE REQUIREMENTS OF AASHTO M169, GRADE 12L14 AND SHALL HAVE A MINIMUM LENGTH OF THREADS OF 2 1/2".
 - B. 4 - 1" Ø X 2 1/4" BOLTS WITH WASHERS, BOLTS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A307. BOLTS AND WASHERS SHALL BE GALVANIZED. (AT THE CONTRACTOR'S OPTION, STAINLESS STEEL BOLTS AND WASHERS MAY BE USED AS AN ALTERNATE FOR THE 1" Ø X 2 1/4" GALVANIZED BOLTS AND WASHERS. THEY SHALL CONFORM TO OR EXCEED THE MECHANICAL REQUIREMENTS OF ASTM A307. THE USE OF THIS ALTERNATE SHALL BE APPROVED BY THE ENGINEER.)
 - C. WIRE STRUTS SHOWN IN THE GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS DETAIL ARE MINIMUM ALLOWABLE SIZE AND SHALL HAVE A MINIMUM TENSILE STRENGTH OF 100,000 P.S.I. AS AN OPTION, A 7/16" Ø WIRE STRUT WITH A MINIMUM TENSILE STRENGTH OF 90,000 PSI IS ACCEPTABLE.
- GUARDRAIL ANCHOR ASSEMBLY WITH BOLTS SHALL BE ASSEMBLED IN THE SHOP. BOLT THREADS MAY BE RECUT AS NECESSARY TO INSURE FIT.
- THE COST OF THE GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS COMPLETE IN PLACE, SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR CLASS "A" CONCRETE.
- FERRULES TO BE PLUGGED DURING POURING OF SLAB AS RECOMMENDED BY THE MANUFACTURER.
- AT THE CONTRACTOR'S OPTION, FERRULES WITH OPEN OR CLOSED ENDS MAY BE USED.
- PAYMENT FOR GUARDRAIL, POSTS, AND POST BASE PLATES IS INCLUDED IN ROADWAY PAY ITEMS.
- SLAB REINFORCING STEEL MAY BE SHIFTED AS NECESSARY TO CLEAR GUARDRAIL ANCHOR ASSEMBLY. CARE SHOULD BE TAKEN TO KEEP THE SHIFTING OF REINFORCING STEEL TO A MINIMUM.
- THE CONTRACTOR MAY USE ADHESIVELY ANCHORED ANCHOR BOLTS IN PLACE OF GUARDRAIL ANCHOR ASSEMBLY. LEVEL TWO FIELD TESTING IS REQUIRED, AND THE YIELD LOAD OF THE 1" Ø BOLT IS 21.8 KIPS. FOR ADHESIVELY ANCHORED ANCHOR BOLTS OR DOWELS, SEE STANDARD SPECIFICATIONS.



SECTION A-A

SECTION B-B




ELEVATION

SIDE VIEW

GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS

PROJECT NO. 17BP.8.R.101
 RANDOLPH COUNTY
 STATION: 15+14.00 -L-

SHEET 3 OF 3



STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
 ANCHORAGE DETAILS FOR
 GUARDRAIL ANCHOR ASSEMBLY
 FOR CULVERTS

ASSEMBLED BY : R. P. PATEL	DATE : 9-20-16
CHECKED BY : H. LOCKLEAR	DATE : 9-21-16
DRAWN BY : FCJ 6/88	REV. 5/7/03 RWW/JTE
CHECKED BY : ARB 6/88	REV. 5/1/06R KMM/GM
	REV. 10/1/11 MAA/GM

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	C-3
1			3			TOTAL SHEETS
2			4			3

STANDARD NOTES

DESIGN DATA:

SPECIFICATIONS	-----	A.A.S.H.T.O. (CURRENT)
LIVE LOAD	-----	SEE PLANS
IMPACT ALLOWANCE	-----	SEE A.A.S.H.T.O.
STRESS IN EXTREME FIBER OF		
STRUCTURAL STEEL - AASHTO M270 GRADE 36	-	20,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50W	-	27,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50	-	27,000 LBS. PER SQ. IN.
REINFORCING STEEL IN TENSION		
GRADE 60	--	24,000 LBS. PER SQ. IN.
CONCRETE IN COMPRESSION	-----	1,200 LBS. PER SQ. IN.
CONCRETE IN SHEAR	-----	SEE A.A.S.H.T.O.
STRUCTURAL TIMBER - TREATED OR		
UNTREATED - EXTREME FIBER STRESS	-----	1,800 LBS. PER SQ. IN.
COMPRESSION PERPENDICULAR TO GRAIN OF TIMBER	-----	375 LBS. PER SQ. IN.
EQUIVALENT FLUID PRESSURE OF EARTH	-----	30 LBS. PER CU. FT. (MINIMUM)

MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2012 "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; AND CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP.

CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED 3/4" WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO 1-1/2" RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A 1/4" FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A 1/4" RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT, ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE.
ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER.
IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER.
DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS.
WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE 7/8" Ø SHEAR STUDS FOR THE 3/4" Ø STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF 7/8" Ø STUDS ALONG THE BEAM AS SHOWN FOR 3/4" Ø STUDS BASED ON THE RATIO OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-0".
EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST 5/16" IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2" OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED.
WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES, ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY 1/16 INCH OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB.
METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.

ENGLISH

JANUARY, 1990