LOAD AND RESISTANCE FACTOR RATING (LRFR) SUMMARY FOR PRESTRESSED CONCRETE CORED SLABS

LEVEL		VEHICLE	WEIGHT (W) (TONS)	CONTROLLING LOAD RATING	MINIMUM RATING FACTORS (RF)	TONS = W X RF	STRENGTH I LIMIT STATE											SERVICE III LIMIT STATE						COMMENT NUMBER
								MOMENT					SHEAR						MOMENT					
							LIVELOAD FACTORS	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	LIVELOAD FACTORS	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	
DESIGN LOAD RATING		HL-93(Inv)	N/A	(1)	1.330	--	1.75	0.275	1.33	60′	EL	29.5	0.52	**1.33**	60′	EL	5.9	0.80	0.275	1.37	60′	EL	29.5	
		HL-93(Opr)	N/A	--	1.725	--	1.35	0.275	1.73	60′	EL	29.5	0.52	1.72	60′	EL	5.9	N/A	--	--	--	--	--	
		HS-20(Inv)	36.000	(2)	1.601	57.643	1.75	0.275	1.69	60′	EL	29.5	0.52	**1.60**	60′	EL	5.9	0.80	0.275	1.74	60′	EL	29.5	
		HS-20(Opr)	36.000	--	2.076	74.723	1.35	0.275	2.19	60′	EL	29.5	0.52	2.08	60′	EL	5.9	N/A	--	--	--	--	--	
LEGAL LOAD RATING	SV	SNSH	13.500	--	3.745	50.557	1.40	0.275	4.55	60′	EL	29.5	0.52	4.63	60′	EL	5.9	0.80	0.275	3.74	60′	EL	29.5	
		SNGARBS2	20.000	--	2.867	57.338	1.40	0.275	3.48	60′	EL	29.5	0.52	3.33	60′	EL	5.9	0.80	0.275	2.87	60′	EL	29.5	
		SNAGRIS2	22.000	--	2.748	60.460	1.40	0.275	3.34	60′	EL	29.5	0.52	3.11	60′	EL	5.9	0.80	0.275	2.75	60′	EL	29.5	
		SNCOTTS3	27.250	--	1.866	50.841	1.40	0.275	2.27	60′	EL	29.5	0.52	2.31	60′	EL	5.9	0.80	0.275	1.87	60′	EL	29.5	
		SNAGGRS4	34.925	--	1.588	55.465	1.40	0.275	1.93	60′	EL	29.5	0.52	1.95	60′	EL	5.9	0.80	0.275	1.59	60′	EL	29.5	
		SNS5A	35.550	--	1.551	55.139	1.40	0.275	1.89	60′	EL	29.5	0.52	1.99	60′	EL	5.9	0.80	0.275	1.55	60′	EL	29.5	
		SNS6A	39.950	--	1.435	57.347	1.40	0.275	1.74	60′	EL	29.5	0.52	1.83	60′	EL	5.9	0.80	0.275	1.44	60′	EL	29.5	
		SNS7B	42.000	--	1.367	57.434	1.40	0.275	1.66	60′	EL	29.5	0.52	1.81	60′	EL	5.9	0.80	0.275	1.37	60′	EL	29.5	
	TTST	TNAGRIT3	33.000	--	1.754	57.887	1.40	0.275	2.13	60′	EL	29.5	0.52	2.17	60′	EL	5.9	0.80	0.275	1.75	60′	EL	29.5	
		TNT4A	33.075	--	1.765	58.389	1.40	0.275	2.15	60′	EL	29.5	0.52	2.10	60′	EL	5.9	0.80	0.275	1.77	60′	EL	29.5	
		TNT6A	41.600	--	1.456	60.551	1.40	0.275	1.77	60′	EL	29.5	0.52	1.96	60′	EL	5.9	0.80	0.275	1.46	60′	EL	29.5	
		TNT7A	42.000	--	1.469	61.714	1.40	0.275	1.79	60′	EL	29.5	0.52	1.88	60′	EL	5.9	0.80	0.275	1.47	60′	EL	29.5	
		TNT7B	42.000	--	1.535	64.463	1.40	0.275	1.87	60′	EL	29.5	0.52	1.76	60′	EL	5.9	0.80	0.275	1.53	60′	EL	29.5	
		TNAGRIT4	43.000	--	1.450	62.329	1.40	0.275	1.76	60′	EL	29.5	0.52	1.70	60′	EL	5.9	0.80	0.275	1.45	60′	EL	29.5	
		TNAGT5A	45.000	--	1.361	61.247	1.40	0.275	1.65	60′	EL	29.5	0.52	1.71	60′	EL	5.9	0.80	0.275	1.36	60′	EL	29.5	
		TNAGT5B	45.000	(3)	1.340	60.282	1.40	0.275	1.63	60′	EL	29.5	0.52	1.61	60′	EL	5.9	0.80	0.275	**1.34**	60′	EL	29.5	

LOAD FACTORS:

DESIGN LOAD RATING FACTORS	LIMIT STATE	γ_{DC}	γ_{DW}
	STRENGTH I	1.25	1.50
	SERVICE III	1.00	1.00

NOTES:

MINIMUM RATING FACTORS ARE BASED ON THE STRENGTH I AND SERVICE III LIMIT STATES.

ALLOWABLE STRESSES FOR SERVICE III LIMIT STATE ARE AS REQUIRED FOR DESIGN.

(#) CONTROLLING LOAD RATING
(1) DESIGN LOAD RATING (HL-93)
(2) DESIGN LOAD RATING (HS-20)
(3) LEGAL LOAD RATING **
** SEE CHART FOR VEHICLE TYPE

GIRDER LOCATION
I - INTERIOR GIRDER
EL - EXTERIOR LEFT GIRDER
ER - EXTERIOR RIGHT GIRDER



LRFR SUMMARY

FOR SPAN A

PROJECT NO. 17BP.8.R.113

LEE COUNTY

STATION: 15+17.00 -L-

NORTH CAROLINA PROFESSIONAL SEAL 29048 ENGINEER RAMAN P. PATEL

DocuSigned by: Raman Patel 60F537B5DA1F41D...

1/31/2017

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

STANDARD

LRFR SUMMARY FOR 60′ CORED SLAB UNIT 90° SKEW

(NON-INTERSTATE TRAFFIC)

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-4
1			3			TOTAL SHEETS
2			4			14

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

ASSEMBLED BY :	H. KIM	DATE :	8/10/16
CHECKED BY :	R.P. PATEL	DATE :	8/10/16
DRAWN BY :	CVC		6/10
CHECKED BY :	DNS		6/10

27-JAN-2017 14:24
Q:\Division08\520087\Structures\Plans\Final Plans\17BP.8.R.113_LRFR.dgn
ksedal

STD. NO. 24LRFR1_90S_60L