PROJECT REFERENCE NO.	SHEET NO.
U-5758	PM-2
R/W SHEET NO.	

DocuSigned by: Greg S Davis 33D47B5FD78F4A8...

NORTH CAROLINA PROFESSIONAL SEAL 26930 ENGINEER GREG S. DAVIS

6/17/2017

DIVISION DESIGN / CONSTRUCT ENGINEER

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PAVEMENT MARKING LEGEND

- ---CRYSTAL / RED PAVEMENT MARKER
- ---YELLOW / YELLOW PAVEMENT MARKER
- ---CRYSTAL / CRYSTAL PAVEMENT MARKER

PI Sta 25+76.28
△ = 3° 16′ 28.0″ (LT)
D = 5° 00′ 00.0″
L = 65.49′
T = 32.75′
R = 1,145.92′

NC GRID NAD 83 NA 2011

PI Sta 20+65.75
△ = 0° 31′ 00.7″ (RT)
D = 0° 30′ 00.0″
L = 103.37′
T = 51.69′
R = 11,459.16′

50′ 0 50′ 100′

PAVEMENT MARKING LINES

T2 -	THERMOPLASTIC (24″	WHITE,	120 MILS)	STOPBAR
T8 -	THERMOPLASTIC (4″	WHITE,	120 MILS)	2′ X 6′ SP MINISKIP
TC -	THERMOPLASTIC (4″	WHITE,	120 MILS)	10′ SKIP
TD -	THERMOPLASTIC (4″	WHITE,	120 MILS)	3′ X 9′ SP MINISKIP
TE -	THERMOPLASTIC (4″	WHITE,	120 MILS)	SOLID LANE LINE
TI -	THERMOPLASTIC (4″	YELLOW,	120 MILS)	DOUBLE CENTERLINE
TP -	THERMOPLASTIC (8″	YELLOW,	90 MILS)	DIAGONALS
TQ -	THERMOPLASTIC (8″	WHITE,	120 MILS)	CROSSWALK

PAVEMENT MARKING SYMBOLS

UA -	THERMOPLASTIC	(LEFT TURN ARROW, 90 MILS)
UB -	THERMOPLASTIC	(RIGHT TURN ARROW, 90 MILS)
UE -	THERMOPLASTIC	(STRAIGHT/RIGHT TURN ARROW, 90 MILS)

REVISIONS

8/17/99

17-JUN-2017 14:30
Z:\pwworking\ddi\bus2200\er2344\preshell.st\path\pmp\U-5758_pmp_2.dgn
Options AT PB-AD-270410