PROJECT REFERENCE NO.	SHEET NO.
W-5601CL	2-A
R/W SHEET NO.	

NORTH CAROLINA PROFESSIONAL SEAL 26930 ENGINEER GREG S. DAVIS

DocuSigned by: Greg S Davis 33D47B5FD78E4A8...

6/21/2016

DIVISION DESIGN / CONSTRUCT ENGINEER

REVISIONS

8/17/99

TYPICAL SECTION NO. 4
-L-MED- STA. 20+15 TO 21+45.11



TYPICAL SECTION NO. 5
-L-MED- STA. 21+45.11 TO 22+18.12



TYPICAL SECTION NO. 6
-L-MED- STA. 22+18.12 TO 23+33.94



TYPICAL SECTION NO. 7
-L-MED- STA. 23+33.94 TO 26+20.00



PAVEMENT SCHEDULE	
C1	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. PER 1½" DEPTH. TO BE PLACED IN TWO LAYERS.
C2	PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD.
D1	PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.B, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
E1	PROP. APPROX. 5.5" ASPHALT CONCRETE BASE COURSE, TYPE B25.B, AT AN AVERAGE RATE OF 627 LBS. PER SQ. YD.
R1	5" MONOLITHIC CONCRETE ISLAND. (KEYED IN)
R2	EXPRESSWAY GUTTER (STD 846.01)
T_	EARTH MATERIAL.
U_	EXISTING PAVEMENT.
V1	1.5" MILLING