

REFERENCE: BP8.R014

PROJECT: N/A

CONTENTS

<u>SHEET NO.</u>	<u>DESCRIPTION</u>
1	TITLE SHEET
2	LEGEND (SOIL & ROCK)
3	SITE PLAN
4	PROFILE
5	CROSS SECTION
6-10	BORE LOGS
11	SITE PHOTO

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STRUCTURE
SUBSURFACE INVESTIGATION

COUNTY HOKE
PROJECT DESCRIPTION REPLACE BRIDGE NO. 39 AND
BRIDGE NO. 40 ON BALFOUR RD (SR 1436) OVER
BIG MARSH SWAMP

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	BP8.R014	1	

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

NOTES:

1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

S. MELECOSKY

T. WILLIAMS

K. DAEKE

INVESTIGATED BY S&ME, Inc.

DRAWN BY J. SWARTLEY, C. CHANDLER

CHECKED BY J. DAILY

SUBMITTED BY S&ME, Inc.

DATE JULY 2023



3201 SPRING FOREST ROAD
RALEIGH, NC 27616
(919) 872-2660



DocuSigned by:

72275FD8BA38437...
SIGNATURE

7/24/2023


DATE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION										GRADATION					ROCK DESCRIPTION					TERMS AND DEFINITIONS																																																																																																																																																																														
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 208, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i>										WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.					HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:					ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOADED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																																																																																																																														
SOIL LEGEND AND AASHTO CLASSIFICATION <table border="1"> <tr> <th>GENERAL CLASS.</th> <th colspan="6">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="4">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="4">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th colspan="2">A-2</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th colspan="4"></th> </tr> <tr> <th>SYMBOL</th> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td colspan="4"></td> </tr> <tr> <th>% PASSING #10 #40 #200</th> <td>50 MX 30 MX 15 MX</td> <td>50 MX 25 MX</td> <td>51 MN 35 MX 35 MX</td> <td>40 MX 35 MX</td> <td>41 MN 35 MX</td> <td>41 MN 35 MX</td> <td>40 MX 36 MN</td> <td>41 MN 36 MN</td> <td>40 MX 36 MN</td> <td>41 MN 36 MN</td> <td colspan="4">GRANULAR SOILS</td> <td colspan="2">SILT-CLAY SOILS</td> <td>MUCK, PEAT</td> </tr> <tr> <th>MATERIAL PASSING #40 LL PI</th> <td colspan="2">-</td> <td>40 MX 10 MX</td> <td>41 MN 10 MX</td> <td>41 MN 11 MN</td> <td>40 MX 11 MN</td> <td>40 MX 11 MN</td> <td>40 MX 11 MN</td> <td>40 MX 11 MN</td> <td>41 MN 11 MN</td> <td colspan="4">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td colspan="2">HIGHLY ORGANIC SOILS</td> <td></td> </tr> <tr> <th>GROUP INDEX</th> <td>0</td> <td>0</td> <td>0</td> <td>4 MX</td> <td>8 MX</td> <td>12 MX</td> <td>16 MX</td> <td>NO MX</td> <td colspan="4"></td> <td colspan="2"></td> <td></td> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <td>STONE FRAGS. GRAVEL, AND SAND</td> <td>FINE SAND</td> <td colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="2">SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="4"></td> <td colspan="2"></td> <td></td> </tr> <tr> <th>GEN. RATING AS SUBGRADE</th> <td colspan="3">EXCELLENT TO GOOD</td> <td colspan="3">FAIR TO POOR</td> <td>FAIR TO POOR</td> <td>POOR</td> <td colspan="4">UNSATURABLE</td> <td colspan="2"></td> <td></td> </tr> <tr> <td colspan="10">PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30</td> <td colspan="5"></td> <td colspan="5"></td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)						SILT-CLAY MATERIALS (> 35% PASSING #200)				ORGANIC MATERIALS				GROUP CLASS.	A-1	A-3	A-2		A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7					SYMBOL																			% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 35 MX 35 MX	40 MX 35 MX	41 MN 35 MX	41 MN 35 MX	40 MX 36 MN	41 MN 36 MN	40 MX 36 MN	41 MN 36 MN	GRANULAR SOILS				SILT-CLAY SOILS		MUCK, PEAT	MATERIAL PASSING #40 LL PI	-		40 MX 10 MX	41 MN 10 MX	41 MN 11 MN	40 MX 11 MN	40 MX 11 MN	40 MX 11 MN	40 MX 11 MN	41 MN 11 MN	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER				HIGHLY ORGANIC SOILS			GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	NO MX								USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS									GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD			FAIR TO POOR			FAIR TO POOR	POOR	UNSATURABLE							PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30																				ANGULARITY OF GRAINS THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.					MINERALOGICAL COMPOSITION MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.					WEATHERED ROCK (WR) 					CRYSTALLINE ROCK (CR) 					NON-CRYSTALLINE ROCK (NCR) 					COASTAL PLAIN SEDIMENTARY ROCK (CP) 				
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)						SILT-CLAY MATERIALS (> 35% PASSING #200)				ORGANIC MATERIALS																																																																																																																																																																																							
GROUP CLASS.	A-1	A-3	A-2		A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																																						
SYMBOL																																																																																																																																																																																																		
% PASSING #10 #40 #200	50 MX 30 MX 15 MX	50 MX 25 MX	51 MN 35 MX 35 MX	40 MX 35 MX	41 MN 35 MX	41 MN 35 MX	40 MX 36 MN	41 MN 36 MN	40 MX 36 MN	41 MN 36 MN	GRANULAR SOILS				SILT-CLAY SOILS		MUCK, PEAT																																																																																																																																																																																	
MATERIAL PASSING #40 LL PI	-		40 MX 10 MX	41 MN 10 MX	41 MN 11 MN	40 MX 11 MN	40 MX 11 MN	40 MX 11 MN	40 MX 11 MN	41 MN 11 MN	SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER				HIGHLY ORGANIC SOILS																																																																																																																																																																																			
GROUP INDEX	0	0	0	4 MX	8 MX	12 MX	16 MX	NO MX																																																																																																																																																																																										
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND	FINE SAND	SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS																																																																																																																																																																																											
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD			FAIR TO POOR			FAIR TO POOR	POOR	UNSATURABLE																																																																																																																																																																																									
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30																																																																																																																																																																																																		
CONSISTENCY OR DENSENESS <table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>< 4 4 TO 10 10 TO 30 30 TO 50 > 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30</td> <td>< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4</td> </tr> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	MISCELLANEOUS SYMBOLS ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION SOIL SYMBOL ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT INFERRED SOIL BOUNDARY INFERRED ROCK LINE ALLUVIAL SOIL BOUNDARY DIP & DIP DIRECTION OF ROCK STRUCTURES SPT TEST BORING AUGER BORING CORE BORING MONITORING WELL PIEZOMETER INSTALLATION SLOPE INDICATOR INSTALLATION CONE PENETROMETER TEST SOUNDING ROD TEST BORING WITH CORE SPT N-VALUE					ROCK HARDNESS VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK. HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN. MODERATELY HARD CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS. MEDIUM HARD CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK. SOFT CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE. VERY SOFT CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.					RECOMMENDATION SYMBOLS UNDERCUT SHALLOW UNDERCUT UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL					ABBREVIATIONS AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - CONE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS. - FOSSILIFEROUS FRAC. - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HI. - HIGHLY MED. - MEDIUM MICA. - MICACEOUS MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SLI. - SLIGHTLY TCR - TRICONE REFUSAL w - MOISTURE CONTENT V - VERY VST - VANE SHEAR TEST WEA. - WEATHERED UG - UNIT WEIGHT UG - DRY UNIT WEIGHT SAMPLE ABBREVIATIONS S - BULK SS - SPLIT SPOON ST - SHELBY TUBE RS - ROCK RT - RECOMPACTED TRIAXIAL CBR - CALIFORNIA BEARING RATIO																																																																																																																																																													
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																																																																																																															
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																																																															
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																																																																																																															
TEXTURE OR GRAIN SIZE <table border="1"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE, SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td>GRAIN SIZE</td> <td>MM 305 IN. 12</td> <td>75</td> <td>2.0</td> <td>0.25</td> <td>0.05</td> <td>0.005</td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE, SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)	GRAIN SIZE	MM 305 IN. 12	75	2.0	0.25	0.05	0.005	EQUIPMENT USED ON SUBJECT PROJECT DRILL UNITS: <input type="checkbox"/> CME-45C <input type="checkbox"/> CME-55 <input type="checkbox"/> CME-550 <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/> PORTABLE HOIST <input checked="" type="checkbox"/> D-50 ADVANCING TOOLS: <input checked="" type="checkbox"/> CLAY BITS <input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER <input checked="" type="checkbox"/> 8" HOLLOW AUGERS <input type="checkbox"/> HARD FACED FINGER BITS <input type="checkbox"/> TUNG-CARBIDE INSERTS <input checked="" type="checkbox"/> CASING <input type="checkbox"/> w/ ADVANCER <input type="checkbox"/> TRICONE <input type="checkbox"/> STEEL TEETH <input checked="" type="checkbox"/> TRICONE 2-7/8" TUNG-CARB. <input type="checkbox"/> CORE BIT <input type="checkbox"/> HAMMER TYPE: <input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -H <input type="checkbox"/> -N HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input type="checkbox"/> VANE SHEAR TEST					FRACATURE SPACING <table border="1"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table>					TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FOOT	VERY CLOSE	LESS THAN 0.16 FEET	BEDDING <table border="1"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table>					TERM	THICKNESS	VERY THICKLY BEDDED	4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET	INDURATION FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC. FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE. MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER. EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																			
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																												
	4.75	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																																												
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE, SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																												
GRAIN SIZE	MM 305 IN. 12	75	2.0	0.25	0.05	0.005																																																																																																																																																																																												
TERM	SPACING																																																																																																																																																																																																	
VERY WIDE	MORE THAN 10 FEET																																																																																																																																																																																																	
WIDE	3 TO 10 FEET																																																																																																																																																																																																	
MODERATELY CLOSE	1 TO 3 FEET																																																																																																																																																																																																	
CLOSE	0.16 TO 1 FOOT																																																																																																																																																																																																	
VERY CLOSE	LESS THAN 0.16 FEET																																																																																																																																																																																																	
TERM	THICKNESS																																																																																																																																																																																																	
VERY THICKLY BEDDED	4 FEET																																																																																																																																																																																																	
THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																																	
THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																																	
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																																	
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																																	
THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																																	
PLASTICITY <table border="1"> <tr> <th>NON PLASTIC</th> <th colspan="2">PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>0-5</td> <td></td> <td>VERY LOW</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>6-15</td> <td></td> <td>SLIGHT</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>16-25</td> <td></td> <td>MEDIUM</td> </tr> <tr> <td></td> <td>26 OR MORE</td> <td></td> <td>HIGH</td> </tr> </table>										NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH	SLIGHTLY PLASTIC	0-5		VERY LOW	MODERATELY PLASTIC	6-15		SLIGHT	HIGHLY PLASTIC	16-25		MEDIUM		26 OR MORE		HIGH	COLOR DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.					NOTES: BENCH MARK: BM-200 N: 413,853 E: 1,960,385 ELEVATION: 191.58 FEET																																																																																																																																																															
NON PLASTIC	PLASTICITY INDEX (PI)		DRY STRENGTH																																																																																																																																																																																															
SLIGHTLY PLASTIC	0-5		VERY LOW																																																																																																																																																																																															
MODERATELY PLASTIC	6-15		SLIGHT																																																																																																																																																																																															
HIGHLY PLASTIC	16-25		MEDIUM																																																																																																																																																																																															
	26 OR MORE		HIGH																																																																																																																																																																																															

SKEW = 90 DEGREES



-L- PT Sta. 13+82.85

-L- PC Sta. 17+78.28

END BENT 1 LINE


END BENT 2 LINE

END BENT 1 LINE

END BENT 2 LINE

BM-200 ELEVATION = 191.58'
 N 413853' E 1960385'
 BL STATION 23+53.00 51' LEFT
 NAIL SET IN 18" PINE TREE

LAKE McNEILL




-L- POC Sta. 19+11.12 =
 -Y- POT Sta. 10+00.00

L-2000


EXISTING R/W
 INV = 191.91'
 INV = 193.60'

5/14/99

-L-




PROJECT REFERENCE NO.	SHEET NO.
BP8.R014	4
PROFILE PROJECTED ALONG CENTERLINE OF -L-	



NOTE: EXISTING GROUND SURFACE PROFILE OF -L- CENTERLINE TAKEN FROM ELECTRONIC TIN FILE 'BP8R014_ls_tin.tin' DATED 09/21/22. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE PROFILE.

6/23/16



NOTE: CROSS SECTION GROUND LINE IS DRAWN USING TIN FILE 'BP8R014_ls_tin.tin' DATED 9/21/22. INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO IT.

DATE: 6/23/16
 DRAWN BY: [illegible]
 CHECKED BY: [illegible]
 APPROVED BY: [illegible]

-L-

GEOTECHNICAL BORING REPORT

BORE LOG

WBS BP8.R014		TIP N/A		COUNTY HOKE		GEOLOGIST Melecosky, S.	
SITE DESCRIPTION BRIDGE NOS. 39 & 40 ON SR 1436 (-L-) OVER BIG MARSH SWAMP						GROUND WTR (ft)	
BORING NO. EB1-B_BRDG39		STATION 14+95		OFFSET 4 ft RT		ALIGNMENT -L-	
COLLAR ELEV. 190.0 ft		TOTAL DEPTH 100.0 ft		NORTHING 413,723		EASTING 1,960,343	
DRILL RIG/HAMMER EFF./DATE SME275 DIEDRICH D-50 85% 11/09/2021				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic	
DRILLER Williams, T.		START DATE 01/16/23		COMP. DATE 01/16/23		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
190														190.0 GROUND SURFACE 0.0	
	189.0	1.0	5	5	5								M	ROADWAY EMBANKMENT (PAVEMENT) 1.0	
	186.5	3.5	4	3	3								M	LOOSE, BROWN AND GRAY, SILTY SAND, A-2-4	
185	184.0	6.0	1	0	1								Sat.	ALLUVIAL VERY SOFT, BROWN MUCK 6.0	
	181.5	8.5	1	1	0								Sat.		
180	176.5	13.5	4	3	3								W	COASTAL PLAIN LOOSE, BROWN SAND, A-3 (MIDDENDORF FORMATION) 12.0	
	171.5	18.5	2	2	9								W	MEDIUM DENSE, TAN, CLAYEY SAND, TRACE ORGANIC MATTER, A-2-6 17.0	
170	166.5	23.5	4	4	5								W	LOOSE TO MEDIUM DENSE, GRAY AND WHITE, SAND, A-3 19.5	
	161.5	28.5	2	2	3								W	LOOSE, GRAY, SILTY SAND, A-2-4 27.0	
165	156.5	33.5	2	3	3								W	LOOSE TO MEDIUM DENSE, GRAY, SAND, A-3 32.0	
	151.5	38.5	3	5	7								W		
150	146.5	43.5	6	7	10								W		
	141.5	48.5	8	10	14								W	MEDIUM DENSE, GRAY, SILTY SAND, A-2-4 47.0	
140	136.5	53.5	8	11	15								W		
	131.5	58.5	7	8	10								W	MEDIUM DENSE, GRAY, SAND, A-3 57.0	
135	126.5	63.5	8	9	12								W	MEDIUM DENSE, GRAY, SILTY SAND, A-2-4 62.0	
	121.5	68.5	8	9	13								W	COASTAL PLAIN MEDIUM DENSE TO VERY DENSE, GRAY, SILTY SAND, A-2-4 (CAPE FEAR FORMATION) 67.0	
120	116.5	73.5	27	40	38								W		
	111.5	78.5	21	25	24								W	DENSE, GRAY, SAND, A-3 77.0	
110													W		

WBS BP8.R014		TIP N/A		COUNTY HOKE		GEOLOGIST Melecosky, S.	
SITE DESCRIPTION BRIDGE NOS. 39 & 40 ON SR 1436 (-L-) OVER BIG MARSH SWAMP						GROUND WTR (ft)	
BORING NO. EB1-B_BRDG39		STATION 14+95		OFFSET 4 ft RT		ALIGNMENT -L-	
COLLAR ELEV. 190.0 ft		TOTAL DEPTH 100.0 ft		NORTHING 413,723		EASTING 1,960,343	
DRILL RIG/HAMMER EFF./DATE SME275 DIEDRICH D-50 85% 11/09/2021				DRILL METHOD Mud Rotary		HAMMER TYPE Automatic	
DRILLER Williams, T.		START DATE 01/16/23		COMP. DATE 01/16/23		SURFACE WATER DEPTH N/A	

ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
110														110.0 Match Line	
	106.5	83.5	27	29	28								W	DENSE, GRAY, SAND, A-3 (continued) 83.0	
105	101.5	88.5	5	5	5								W	HARD, GRAY, SANDY CLAY, A-6 87.0	
	96.5	93.5	39	61/0.5									W	LOOSE, GRAY, SILTY SAND, A-2-4 92.0	
100	91.5	98.5	13	21	26								W	HARD, GRAY, SANDY CLAY, A-6 100.0	
95															
90															

Boring Terminated at Elevation 90.0 ft In Hard Sandy Clay (Coastal Plain)

-Artesian flow was observed after drilling completed

NCDOT BORE DOUBLE HOKE_39&40.GPJ NC_DOT.GDT 7/20/23

GEOTECHNICAL BORING REPORT

BORE LOG

WBS BP8.R014		TIP N/A		COUNTY HOKE		GEOLOGIST Melecosky, S.									
SITE DESCRIPTION BRIDGE NOS. 39 & 40 ON SR 1436 (-L-) OVER BIG MARSH SWAMP						GROUND WTR (ft)									
BORING NO. EB2-A_BRDG39		STATION 15+65		OFFSET 7 ft LT		ALIGNMENT -L-									
COLLAR ELEV. 190.3 ft		TOTAL DEPTH 94.3 ft		NORTHING 413,787		EASTING 1,960,374									
DRILL RIG/HAMMER EFF./DATE SME275 DIEDRICH D-50 85% 11/09/2021			DRILL METHOD Mud Rotary		HAMMER TYPE Automatic										
DRILLER Williams, T.		START DATE 01/18/23		COMP. DATE 01/18/23		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
195															
190	189.3	1.0	7	9	7										
	186.8	3.5	5	2	2										
185	184.3	6.0	WOH	WOH	WOH										
	181.8	8.5	WOH	WOH	1										
180	176.8	13.5													
175	171.8	18.5													
170	166.8	23.5													
165	161.8	28.5													
160	156.8	33.5													
155	151.8	38.5													
150	146.8	43.5													
145	141.8	48.5													
140	136.8	53.5													
135	131.8	58.5													
130	126.8	63.5													
125	121.8	68.5													
120	116.8	73.5													
115															

WBS BP8.R014		TIP N/A		COUNTY HOKE		GEOLOGIST Melecosky, S.									
SITE DESCRIPTION BRIDGE NOS. 39 & 40 ON SR 1436 (-L-) OVER BIG MARSH SWAMP						GROUND WTR (ft)									
BORING NO. EB2-A_BRDG39		STATION 15+65		OFFSET 7 ft LT		ALIGNMENT -L-									
COLLAR ELEV. 190.3 ft		TOTAL DEPTH 94.3 ft		NORTHING 413,787		EASTING 1,960,374									
DRILL RIG/HAMMER EFF./DATE SME275 DIEDRICH D-50 85% 11/09/2021			DRILL METHOD Mud Rotary		HAMMER TYPE Automatic										
DRILLER Williams, T.		START DATE 01/18/23		COMP. DATE 01/18/23		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
115															
	111.8	78.5	21	29	27										
110	106.8	83.5	30	55	45/0.4										
105	101.8	88.5	4	5	4										
100	96.8	93.5	43	57/0.3											

NCDOT BORE DOUBLE HOKE_39&40.GPJ NC_DOT.GDT 7/20/23

GEOTECHNICAL BORING REPORT

BORE LOG

WBS BP8.R014		TIP N/A		COUNTY HOKE		GEOLOGIST Melecosky, S.										
SITE DESCRIPTION BRIDGE NOS. 39 & 40 ON SR 1436 (-L-) OVER BIG MARSH SWAMP							GROUND WTR (ft)									
BORING NO. EB2-A_BRDG40		STATION 17+10		OFFSET 8 ft LT		ALIGNMENT -L-										
COLLAR ELEV. 191.0 ft		TOTAL DEPTH 80.0 ft		NORTHING 413,907		EASTING 1,960,455										
DRILL RIG/HAMMER EFF./DATE SME275 DIEDRICH D-50 85% 11/09/2021			DRILL METHOD Mud Rotary		HAMMER TYPE Automatic											
DRILLER Williams, T.		START DATE 01/18/23		COMP. DATE 01/18/23		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
195																
190	190.0	1.0	3	4	5											191.0 GROUND SURFACE 0.0
	187.5	3.5	7	4	4											190.0 ROADWAY EMBANKMENT (PAVEMENT) 1.0
185	185.0	6.0	1	0	1											185.5 LOOSE, BROWN, SILTY SAND, A-2-4
	182.5	8.5	WOH	WOH	WOH											184.0 ALLUVIAL BROWN, VERY SOFT, MUCK VERY SOFT, GRAY, SANDY SILT, A-4
180																179.0 COASTAL PLAIN MEDIUM DENSE, GRAY, SAND, A-3 (MIDDENDORF FORMATION) 12.0
175	177.5	13.5	13	10	9											174.0 LOOSE, GRAY, CLAYEY SAND, A-2-6 17.0
170	172.5	18.5	4	3	3											172.0 LOOSE, GRAY, SILTY SAND, A-2-4 19.0
165	167.5	23.5	9	15	17											169.0 DENSE, GRAY, SAND, A-3 22.0
160	162.5	28.5	1	1	2											164.0 VERY LOOSE, GRAY, CLAYEY SAND, A-2-6 27.0
155	157.5	33.5	3	3	4											159.0 LOOSE, GRAY, SILTY SAND, A-2-4 32.0
150	152.5	38.5	5	7	9											154.0 MEDIUM DENSE, GRAY, SAND, A-3 37.0
145	147.5	43.5	3	3	3											148.0 LOOSE, GRAY, SILTY SAND, A-2-4 43.0
140	142.5	48.5	6	8	9											146.5 LOOSE, GRAY, CLAYEY SAND, A-2-6 44.5
135	137.5	53.5	6	10	18											144.0 MEDIUM DENSE, GRAY, SILTY SAND, A-2-4 47.0
130	132.5	58.5	19	22	35											139.0 MEDIUM DENSE TO VERY DENSE, GRAY, SAND, A-3 52.0
125	127.5	63.5	11	14	14											124.0 COASTAL PLAIN MEDIUM DENSE TO VERY DENSE, GRAY, SAND, A-3 (CAPE FEAR FORMATION) 67.0
120	122.5	68.5	6	12	16											
115	117.5	73.5	7	8	10											

WBS BP8.R014		TIP N/A		COUNTY HOKE		GEOLOGIST Melecosky, S.										
SITE DESCRIPTION BRIDGE NOS. 39 & 40 ON SR 1436 (-L-) OVER BIG MARSH SWAMP							GROUND WTR (ft)									
BORING NO. EB2-A_BRDG40		STATION 17+10		OFFSET 8 ft LT		ALIGNMENT -L-										
COLLAR ELEV. 191.0 ft		TOTAL DEPTH 80.0 ft		NORTHING 413,907		EASTING 1,960,455										
DRILL RIG/HAMMER EFF./DATE SME275 DIEDRICH D-50 85% 11/09/2021			DRILL METHOD Mud Rotary		HAMMER TYPE Automatic											
DRILLER Williams, T.		START DATE 01/18/23		COMP. DATE 01/18/23		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
115																
	112.5	78.5	19	28	44											Match Line
																111.0 Boring Terminated at Elevation 111.0 ft In Very Dense Silty Sand (Coastal Plain) 80.0

NCDOT BORE DOUBLE HOKE_39&40.GPJ NC_DOT.GDT 7/20/23

GEOTECHNICAL BORING REPORT

BORE LOG

WBS BP8.R014		TIP N/A		COUNTY HOKE		GEOLOGIST Melecosky, S.										
SITE DESCRIPTION BRIDGE NOS. 39 & 40 ON SR 1436 (-L-) OVER BIG MARSH SWAMP							GROUND WTR (ft)									
BORING NO. L_2000		STATION 20+00		OFFSET 25 ft RT		ALIGNMENT -L-	0 HR. 7.8									
COLLAR ELEV. 196.4 ft		TOTAL DEPTH 15.0 ft		NORTHING 414,119		EASTING 1,960,654	24 HR. FIAD									
DRILL RIG/HAMMER EFF./DATE SME275 DIETRICH D-50 85% 11/09/2021				DRILL METHOD H.S. Augers		HAMMER TYPE Automatic										
DRILLER Williams, T.		START DATE 01/19/23		COMP. DATE 01/19/23		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
			0.5ft	0.5ft	0.5ft	0	25	50	75	100			ELEV. (ft)	DEPTH (ft)		
200																
195	195.4	1.0	2	1	2									196.4	0.0	GROUND SURFACE
	192.9	3.5	3	2	2											COASTAL PLAIN VERY LOOSE TO DENSE, BROWN, SILTY SAND, A-2-4 (MIDDENDORF FORMATION)
190	190.4	6.0	4	10	22											
	187.9	8.5	50	21	16											
185	182.9	13.5	5	12	10											
														181.4	15.0	Boring Terminated at Elevation 181.4 ft In Dense Silty Sand (Coastal Plain)

NCDOT BORE DOUBLE HOKE_39&40.GPJ NC_DOT.GDT 7/20/23

SITE PHOTOGRAPHS

Bridge Nos. 39 & 40 on -L- (SR 1436) over Big Marsh Swamp



Looking Northeast (Bridge 39)



Looking Southwest (Bridge 40)