

09/08/19

PROJECT WBS: 17BP.9.R.96

CONTRACT: DI00378



See Sheet 1A For Index of Sheets
See Sheet 1B For Standard Symbol Sheet

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS


ROWAN COUNTY

**LOCATION: BRIDGE #254 OVER KERR CREEK
ON SR 1547 (CALDWELL RD)**
TYPE OF WORK: GRADING, PAVING, DRAINAGE, & STRUCTURE


STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.9.R.96	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
17BP.9.R.96		P.E.	
17BP.9.R.96		R.O.W.	
17BP.9.R.96		CONSTRUCTION	



FINAL PLANS



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



DESIGN DATA

ADT 2026 =	1670
ADT 2046 =	2428
DHV =	N/A
D =	N/A
T =	6 %
V =	55 MPH

FUNC. CLASSIFICATION:
LOCAL
SUB REGIONAL TIER

PROJECT LENGTH

LENGTH OF ROADWAY PROJECT WBS 17BP.9.R.96 =	0.095 MILES
LENGTH OF STRUCTURE PROJECT WBS 17BP.9.R.96 =	0.017 MILES
TOTAL LENGTH OF PROJECT WBS 17BP.9.R.96 =	0.112 MILES

NCDOT CONTACT: JEREMY KEATON, P.E.
Division Bridge Manager

PLANS PREPARED FOR THE NCDOT BY:

stv STV Engineers, Inc.
2151 Hawkins Street, Suite 1400
Charlotte, NC 28203
NC License Number F-0991

2024 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE:
JANUARY 25, 2023

LETTING DATE:
FEBRUARY 25, 2026

GERALD H. McCAULEY, PE
PROJECT ENGINEER

CARLOS G. OWENS JR.
PROJECT DESIGNER

HYDRAULICS ENGINEER

1/23/2026
SIGNATURE:

ROADWAY DESIGN ENGINEER

1/23/2026
SIGNATURE:





PROJECT REFERENCE NO. <i>17BP.9.R.96</i>	SHEET NO. <i>1A</i>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

INDEX OF SHEETS

GENERAL NOTES

STANDARD DRAWINGS

SHEET NUMBER	SHEET
1	TITLE SHEET
1A	INDEX OF SHEETS, GENERAL NOTES, AND LIST OF STANDARD DRAWINGS
1B	CONVENTIONAL SYMBOLS
2A-1	TYPICAL SECTIONS SHEET
3B-1	EARTHWORK, DRAINAGE SUMMARY, AND GUARDRAIL SUMMARY SHEET
3G-1	GEOTECHNICAL SUMMARIES
3P-1	PARCEL DATA SHEET
4-5	PLAN AND PROFILE SHEETS
RW01 THRU RW05	RIGHT-OF-WAY PLANS
TMP-1 THRU TMP-5	TRANSPORTATION MANAGEMENT PLANS
PMP-1 THRU PMP-2	PAVEMENT MARKING PLANS
EC-1 THRU EC-7	EROSION CONTROL PLANS
UO-1 THRU UO-3	UTILITIES BY OTHERS PLANS
X-1 THRU X-9	CROSS-SECTIONS
S-1 THRU S-16	STRUCTURE PLANS
SN	STRUCTURE NOTES

GENERAL NOTES: 2024 SPECIFICATIONS EFFECTIVE: 01-01-2024

GRADE LINE:
GRADING AND SURFACING:
THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. GRADE LINES MAY BE ADJUSTED AT THEIR BEGINNING AND ENDING AND AT STRUCTURES AS DIRECTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:
CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

SUPERELEVATION:
ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:
ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01.

SIDE ROADS:
THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

SUBSURFACE DRAINS:
SUBSURFACE DRAINS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. NO. 815.02 AT LOCATIONS DIRECTED BY THE ENGINEER.

GUARDRAIL:
THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

SUBSURFACE PLANS:
NO SUBSURFACE PLANS ARE AVAILABLE ON THIS PROJECT. THE CONTRACTOR SHOULD MAKE HIS OWN INVESTIGATION AS TO THE SUBSURFACE CONDITIONS.

END BENTS:
THE ENGINEER SHALL CHECK THE STRUCTURE END BENT PLANS, DETAILS, AND CROSS-SECTION PRIOR TO SETTING OF THE SLOPE STAKES FOR THE EMBANKMENT OR EXCAVATION APPROACHING A BRIDGE.

UTILITIES:
UTILITY OWNERS ON THIS PROJECT ARE:
POWER - DUKE ENERGY
TELECOM - CONTERRA NETWORKS

RIGHT-OF-WAY MARKERS:
ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY CONTRACT.

2024 ROADWAY ENGLISH STANDARD DRAWINGS EFF. January, 2024

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch - N. C. Department of Transportation - Raleigh, N. C., Dated January, 2024 are applicable to this project and by reference hereby are considered a part of these plans:



















STD.NO.	TITLE
DIVISION 2 - EARTHWORK	
200.02	Method of Clearing - Method II
225.02	Guide for Grading Subgrade - Secondary and Local
225.04	Method of Obtaining Superelevation - Two Lane Pavement
DIVISION 3 - PIPE CULVERTS	
310.10	Driveway Pipe Construction
DIVISION 4 - MAJOR STRUCTURES	
423.01	Bridge Approach Fills - Type I Approach Fill
DIVISION 5 - SUBGRADE, BASES AND SHOULDERS	
560.01	Method of Shoulder Construction - High Side of Superelevated Curve - Method I
DIVISION 8 - INCIDENTALS	
806.01	Concrete Right-of-Way Marker
815.02	Subsurface Drain
840.29	Frames and Narrow Slot Flat Grates
840.35	Traffic Bearing Grated Drop Inlet - for Cast Iron Double Frame Grates
862.01	Guardrail Placement
862.02	Guardrail Installation
862.03	Structure Anchor Units
866.01	Chain Link Fence - 4' High Fence
876.01	Rip Rap in Channels and Ditches
876.02	Guide for Rip Rap at Pipe Outlets
DIVISION 11 - WORK ZONE TRAFFIC CONTROL	
1101.01	Work Zone Warning Signs
1101.03	Temporary Road Closures
1101.11	Traffic Control Design Tables
1110.01	Stationary Work Zone Signs - Mounting Height & Lateral Clearance
1110.02	Portable Work Zone Signs - Mounting Height & Lateral Clearance
1145.01	Barricades - Type III

1/22/2026
R:\Roadway\Proj\SH17R96_r_dy_psh01A.dgn
OwensC












STATE OF NORTH CAROLINA, DIVISION OF HIGHWAYS CONVENTIONAL PLAN SHEET SYMBOLS

Note: Not to Scale











BOUNDARIES AND PROPERTY:

State Line	_____
County Line	_____
Township Line	_____
City Line	_____
Reservation Line	_____
Property Line	_____
Existing Iron Pin (EIP)	
Computed Property Corner	
Existing Concrete Monument (ECM)	
Parcel/Sequence Number	
Existing Fence Line	
Proposed Woven Wire Fence	
Proposed Chain Link Fence	
Proposed Barbed Wire Fence	
Existing Wetland Boundary	
Proposed Wetland Boundary	
Existing Endangered Animal Boundary	
Existing Endangered Plant Boundary	
Existing Historic Property Boundary	
Known Contamination Area: Soil	
Potential Contamination Area: Soil	
Known Contamination Area: Water	
Potential Contamination Area: Water	
Contaminated Site: Known or Potential	

BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	
Sign	
Well	
Small Mine	
Foundation	
Area Outline	
Cemetery	
Building	
School	
Church	
Dam	

















HYDROLOGY:

Stream or Body of Water	_____
Hydro, Pool or Reservoir	
Jurisdictional Stream	
Buffer Zone 1	
Buffer Zone 2	
Flow Arrow	
Disappearing Stream	
Spring	
Wetland	
Proposed Lateral, Tail, Head Ditch	
False Sump	













RAILROADS:


Standard Gauge	_____
RR Signal Milepost	
Switch	
RR Abandoned	_____
RR Dismantled	_____

RIGHT OF WAY & PROJECT CONTROL:







Primary Horiz Control Point	
Primary Horiz and Vert Control Point	
Secondary Horiz and Vert Control Point	
Vertical Benchmark	
Existing Right of Way Monument	
Proposed Right of Way Monument (Rebar and Cap)	
Proposed Right of Way Monument (Concrete)	
Existing Permanent Easement Monument	
Proposed Permanent Easement Monument (Rebar and Cap)	
Existing C/A Monument	
Proposed C/A Monument (Rebar and Cap)	
Proposed C/A Monument (Concrete)	
Existing Right of Way Line	_____
Proposed Right of Way Line	
Existing Control of Access Line	
Proposed Control of Access Line	
Proposed ROW and CA Line	
Existing Easement Line	_____
Proposed Temporary Construction Easement	_____
Proposed Temporary Drainage Easement	_____
Proposed Permanent Drainage Easement	_____
Proposed Permanent Drainage/Utility Easement	_____
Proposed Permanent Utility Easement	_____
Proposed Temporary Utility Easement	_____
Proposed Aerial Utility Easement	_____

ROADS AND RELATED FEATURES:

Existing Edge of Pavement	_____
Existing Curb	_____
Proposed Slope Stakes Cut	
Proposed Slope Stakes Fill	
Proposed Curb Ramp	
Existing Metal Guardrail	
Proposed Guardrail	
Existing Cable Guiderail	
Proposed Cable Guiderail	
Equality Symbol	
Pavement Removal	
VEGETATION:	
Single Tree	
Single Shrub	
Hedge	











Woods Line	_____
Orchard	
Vineyard	

EXISTING STRUCTURES:








MAJOR:	
Bridge, Tunnel or Box Culvert	
Bridge Wing Wall, Head Wall and End Wall	
MINOR:	
Head and End Wall	
Pipe Culvert	_____
Footbridge	
Drainage Box: Catch Basin, DI or JB	
Paved Ditch Gutter	_____
Storm Sewer Manhole	
Storm Sewer	_____

UTILITIES:











* SUE - Subsurface Utility Engineering
LOS - Level of Service - A,B,C or D (Accuracy)

POWER:	
Existing Power Pole	
Proposed Power Pole	
Existing Joint Use Pole	
Proposed Joint Use Pole	
Power Manhole	
Power Line Tower	
Power Transformer	
U/G Power Cable Hand Hole	
H-Frame Pole	
U/G Power Line Test Hole (SUE - LOS A)*	
U/G Power Line (SUE - LOS B)*	_____
U/G Power Line (SUE - LOS C)*	_____
U/G Power Line (SUE - LOS D)*	_____





TELEPHONE:

Existing Telephone Pole	
Proposed Telephone Pole	
Telephone Manhole	
Telephone Pedestal	
Telephone Cell Tower	
U/G Telephone Cable Hand Hole	
U/G Telephone Test Hole (SUE - LOS A)*	
U/G Telephone Cable (SUE - LOS B)*	_____
U/G Telephone Cable (SUE - LOS C)*	_____
U/G Telephone Cable (SUE - LOS D)*	_____
U/G Telephone Conduit (SUE - LOS B)*	_____
U/G Telephone Conduit (SUE - LOS C)*	_____
U/G Telephone Conduit (SUE - LOS D)*	_____
U/G Fiber Optics Cable (SUE - LOS B)*	_____
U/G Fiber Optics Cable (SUE - LOS C)*	_____
U/G Fiber Optics Cable (SUE - LOS D)*	_____





WATER:

Water Manhole	
Water Meter	
Water Valve	
Water Hydrant	
U/G Water Line Test Hole (SUE - LOS A)*	
U/G Water Line (SUE - LOS B)*	_____
U/G Water Line (SUE - LOS C)*	_____
U/G Water Line (SUE - LOS D)*	_____
Above Ground Water Line	
TV:	
TV Pedestal	
TV Tower	
U/G TV Cable Hand Hole	
U/G TV Test Hole (SUE - LOS A)*	
U/G TV Cable (SUE - LOS B)*	_____
U/G TV Cable (SUE - LOS C)*	_____
U/G TV Cable (SUE - LOS D)*	_____
U/G Fiber Optic Cable (SUE - LOS B)*	_____
U/G Fiber Optic Cable (SUE - LOS C)*	_____
U/G Fiber Optic Cable (SUE - LOS D)*	_____











GAS:

Gas Valve	
Gas Meter	
U/G Gas Line Test Hole (SUE - LOS A)*	
U/G Gas Line (SUE - LOS B)*	_____
U/G Gas Line (SUE - LOS C)*	_____
U/G Gas Line (SUE - LOS D)*	_____
Above Ground Gas Line	

SANITARY SEWER:

Sanitary Sewer Manhole	
Sanitary Sewer Cleanout	
U/G Sanitary Sewer Line	_____
Above Ground Sanitary Sewer	
SS Force Main Line Test Hole (SUE - LOS A)*	
SS Force Main Line (SUE - LOS B)*	_____
SS Force Main Line (SUE - LOS C)*	_____
SS Force Main Line (SUE - LOS D)*	_____

MISCELLANEOUS:

Utility Pole	
Utility Pole with Base	
Utility Located Object	
Utility Traffic Signal Box	
Utility Unknown U/G Line (SUE - LOS B)*	_____
U/G Tank; Water, Gas, Oil	
Underground Storage Tank, Approx. Loc.	
A/G Tank; Water, Gas, Oil	
Geoenvironmental Boring	
Abandoned According to Utility Records	
End of Information	


9/10/2021

I:\22\2026
R:\Roadway\Proj\SH\T\96_rdy_psh0\B.dgn
OwensC




PROJECT REFERENCE NO. 17BP.9.R.96	SHEET NO. 2A-1
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	PAVEMENT DESIGN ENGINEER
PAVEMENT DESIGN PROVIDED BY NCDOT	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

PAVEMENT SCHEDULE	
C1	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YD. IN TWO LAYERS
C2	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 1.0" IN DEPTH OR GREATER THAN 1.5" IN DEPTH.
D1	PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
D2	PROP. VAR. DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 2.5" IN DEPTH OR GREATER THAN 4" IN DEPTH.
E1	PROP. APPROX. 4.0" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
E2	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 3.0" IN DEPTH OR GREATER THAN 5.5" IN DEPTH.
R	CONCRETE SHOULDER BERM GUTTER
T	EARTH MATERIAL
U	EXISTING PAVEMENT
W	PAVEMENT WEDGING




ALL PAVEMENT SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.



* 9' MIN. WITH GUARDRAIL
 ** 2:1 WITH GUARDRAIL



* 9' MIN. WITH GUARDRAIL
 ** 2:1 WITH GUARDRAIL



1/22/2026
 R:\Roadway\Proj\SH\17BP.9.R.96_rdy_psh02A-1.dgn
 OwensC

COMPUTED BY: M. CRUZ, PE DATE: MARCH, 2023
 CHECKED BY: D. DEWEY, PE DATE: MARCH, 2023

PROJECT NO. SHEET NO.
 17BP.9.R.96 3G-1

(2-3-23)

**STATE OF NORTH CAROLINA
 DIVISION OF HIGHWAYS**

SUMMARY OF SUBSURFACE DRAINAGE

LINE	Station	Station	Location LT/RT/CL	Drain Type* UD/BD/SD	LF
CONTINGENCY				SD	200
				TOTAL LF:	200

*UD = Underdrain
 *BD = Blind Drain
 *SD = Subsurface Drain

**SUMMARY OF GEOTEXTILE
 FOR SUBGRADE STABILIZATION**

LINE	Station	Station	Geotextile for Subgrade Stabilization SY
CONTINGENCY			500
TOTAL SY:			500*

*Total square yards of "Geotextile for Subgrade Stabilization" is only the estimated quantity for subgrades and may only represent a portion of the geotextile quantity shown in the Item Sheets of the Proposal.


SUMMARY OF AGGREGATE SUBGRADE/STABILIZATION

LINE	Station	Station	Aggregate Type* ASU(1/2)/ AST	Aggregate Thickness INCHES [8" for ASU(2)]	Shallow Undercut CY	Class IV Subgrade Stabilization TONS	Geotextile for Subgrade Stabilization SY	Stabilizer Aggregate TONS	Class IV Aggregate Stabilization TONS
CONTINGENCY			ASU (1)	12	100	100	100		
TOTAL CY/TONS/SY:					100	100**	100**	0	0

*ASU(1/2) = Aggregate Subgrade (Type 1 or 2)
 *AST = Aggregate Stabilization
 **Total tons of "Class IV Subgrade Stabilization" and total square yards of "Geotextile for Subgrade Stabilization" are only the estimated quantities for ASU(1/2)/AST and may only represent a portion of the subgrade stabilization and geotextile quantities shown in the Item Sheets of the Proposal.

6/2/99





STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

PROJECT REFERENCE NO. <i>17BP.9.R.96</i>	SHEET NO. <i>3P-1</i>
 STV Engineers, Inc. <small>2151 Hawkins Street, Suite 1400 Charlotte, NC 28203 NC License Number F-0991</small>	

PARCEL INDEX SHEET

PARCEL NO.	SHEET NO.	PROPERTY OWNER NAME
1	4	NANNIE HOWELL GRAHAM AND LARRY MCCUTCHEON GRAHAM
2	4 & 5	MICHAEL W. STEED AND WIFE, CATHY STEED
3	4	JESSICA DAWN SMITH AND BURTON D MCLEOD JR.
4	4 & 5	PATTERSON VENTURES, LLC



1/22/2026
C:\Users\j\Project\SHI\17BP.9.R.96_rdy_psh\03P-1.dgn



STV STV Engineers, Inc.
2151 Hawkins Street, Suite 1400
Charlotte, NC 28203
NC License Number F-0991

②
MICHAEL W. STEED AND
CATHY STEED
DB 1042 PG 789
MB 9995 PG 3342

PROJECT REFERENCE NO. 17BP.9.R.96	SHEET NO. 4
RW SHEET NO.	HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	






12/2/2026 10:00 AM \\Proj\17BP.9.R.96_rdy_psh04.dgn

8/17/26

STV STV Engineers, Inc.
 2151 Hawkins Street, Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991

PROJECT REFERENCE NO. 17BP.9.R.96		SHEET NO. 5	
RW SHEET NO.		HYDRAULICS ENGINEER	
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			

②
 MICHAEL W. STEED AND WIFE,
 CATHY STEED
 DB 1042 PG 789
 MB 9995 PG 3342




END PROJECT WBS 17BP.9.R.96
 -L- POT STA. 18+40.00

④
 PATTERSON VENTURES, LLC
 DB 1183 PG 246

PI Sta 19+68.17	PI Sta 20+57.70
$\Delta = 4' 37'' 51.8''$ (LT)	$\Delta = 6' 31'' 43.0''$ (LT)
$D = 4' 46'' 28.7''$	$D = 7' 57'' 27.9''$
$L = 96.99'$	$L = 82.04'$
$T = 48.52'$	$T = 41.06'$
$R = 1,200.00'$	$R = 720.00'$

NOTE: INCIDENTAL MILL APPROXIMATELY 50' AT END PROJECT TO PROVIDE A SMOOTH TRANSITION TO THE EXISTING PAVEMENT.



* NOTE: DESIGN SPEED SHOWN FOR VERTICAL CURVES IS UP TO 20 MPH LESS THAN OVERALL DESIGN SPEED PER SUB-REGIONAL TIER DESIGN GUIDELINES.

I:\2026\17BP.9.R.96\Drawings\17BP.9.R.96_rdy_psh05.dgn
 8/17/26




STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.9.R.96	RW01	05

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

SURVEY CONTROL, EXISTING CENTERLINES,
RIGHT OF WAY, EASEMENTS AND PROPERTY TIES

ROWAN COUNTY

TIP PROJECT: 17BP.9.R.96



DATUM DESCRIPTION

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "GPS 2" WITH NAD 83/NA 2011 STATE PLANE GRID COORDINATES OF NORTHING: 685,626.160(ft) EASTING: 1,505,782.618(ft) ELEVATION: 725.57(ft)

THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.999863739

THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "GPS 2" TO -L- STATION 10+00.00 IS N 34°40'06.85" W 603.72(ft)

ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES VERTICAL DATUM USED IS NAVD 88

Prepared in the Office of:

2018 STANDARD SPECIFICATIONS


RIGHT OF WAY DATE: XXXX/XXXX	LETTING DATE: XXXX/XXXX
----------------------------------------	-----------------------------------

PROFESSIONAL LAND SURVEYOR

Seal of Michael L. Mottlinger, Professional Land Surveyor, License No. L-3877, State of North Carolina.

DocuSigned by:
Michael L. Mottlinger
FOBBF7E2534DE
SIGNATURE: _____


Date: 07/27/2023




27-JUL-2023 10:12 F:\Bridge\Division_Low\mpac\79-0254-Caldwell_Rd\RW Staking\tobechecked\79-0254_ls_rw01.dgn mmo\tsinger AT LS-3286.NL

SURVEY CONTROL SHEET

W/ EXISTING CENTERLINE ALIGNMENTS PRIOR TO CONSTRUCTION

PROJECT REFERENCE NO. 79-0254	SHEET NO. RW02C-1
Location and Surveys	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	



I, Michael L. Motsinger, PLS, certify that the Project Control was verified under my supervision from an actual GPS survey made under my supervision and the following information was used to perform the survey:

Class of survey: **AA**
 Type of GPS field procedure: RTN
 Dates of survey: December 2017
 Datum/Epoch: NAD 83/2011
 Published/Fixed-control use: [Project Control if applicable, N/A for RTN]
 Localized around: 790254-2
 Northing: 685626.1600
 Easting: 1505782.6180
 Combined grid factor: 0.999863739
 Geoid model: Geoid 18
 Units: English

I also certify that the Baseline Control for this project was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:20,000 (Class AA) and Vertical accuracy to Class A. Field work was performed from December 2017 to February 2018, and all coordinates are based on NAD 83/2011 and all elevations are based on NAVD 88; that this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 27th day of July, 2023.

DocuSigned by:

 Professional Land Surveyor L-3877

SEE SHEET RW02C-2
 FOR FURTHER
 ALIGNMENT DETAILS

NOTES:

1. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
2. THE SURVEY CONTROL DATA FOR THIS PROJECT HAS BEEN COMPILED FROM VARIOUS SOURCES. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.


SURVEY CONTROL SHEET

BASELINE AND BENCHMARKS

BL	POINT	DESC.	NORTH	EAST	ELEVATION
3		BL3	686022.9550	1505493.7050	730.53
2		GPS2	685626.1600	1505782.6100	725.57
1		GPS1	685265.6000	1505970.4410	739.69

.....
 BM*1 ELEVATION = 732.23
 N 685309 E 1505882
 RR SPIKE IN 21" DIA POPLAR

 BM*2 ELEVATION = 723.26
 N 685669 E 1505814
 RR SPIKE IN 17" DIA POPLAR

PROJECT REFERENCE NO. 79-0254	SHEET NO. RW02C-2
Location and Surveys	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

I, Michael L. Motsinger, PLS, certify that the Project Control was verified under my supervision from an actual GPS survey made under my supervision and the following information was used to perform the survey:

Class of survey: **AA**
 Type of GPS field procedure: RTN
 Dates of survey: December 2017
 Datum/Epoch: NAD 83/2011
 Published/Fixed-control use: [Project Control if applicable, N/A for RTN]
 Localized around: 790254-2
 Northing: 685626.1600
 Easting: 1505782.6100
 Combined grid factor: 0.999863739
 Geoid model: Geoid 18
 Units: English

I also certify that the Baseline Control for this project was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:20,000 (Class AA) and Vertical accuracy to Class A. Field work was performed from December 2017 to February 2018, and all coordinates are based on NAD 83/2011 and all elevations are based on NAVD 88; that this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 27th day of July, 2023.

DocuSigned by:

 Professional Land Surveyor L-3877



REVISIONS

SURVEY CONTROL SHEET

W/ EXISTING CENTERLINE ALIGNMENTS PRIOR TO CONSTRUCTION

EL POINT	N	E	BEARING	DIST	DELTA	D	L	T	R
PC	686122.647	1505438.879							
CURVE			S 34°51'54.6" E	361.09	04°45'26.7"(RT)	01°19'01.7"	361.19	180.70	4350.00
PT	685826.374	1505645.295							
LINE			S 32°29'11.2" E	39.08					
PC	685793.407	1505666.286							
CURVE			S 30°49'23.7" E	92.88	03°19'34.9"(RT)	03°34'51.6"	92.89	46.46	1600.00
PT	685713.649	1505713.875							
LINE			S 29°09'36.2" E	54.11					
PC	685666.398	1505740.239							
CURVE			S 27°26'37.3" E	77.87	03°25'57.9"(RT)	04°24'26.5"	77.89	38.95	1300.00
PCC	685597.287	1505776.130							
CURVE			S 26°56'44.4" E	148.84	02°26'12.1"(LT)	01°38'13.3"	148.85	74.44	3500.00
PT	685464.608	1505843.575							
LINE			S 28°09'50.4" E	145.82					
PC	685336.051	1505912.403							
CURVE			S 30°28'46.3" E	96.97	04°37'51.8"(LT)	04°46'28.7"	96.99	48.52	1200.00
PCC	685252.484	1505961.587							
CURVE			S 36°03'33.7" E	82.00	06°31'43.0"(LT)	07°57'27.9"	82.04	41.06	720.00
PT	685186.197	1506009.852							

PROPOSED ALIGNMENT

TYPE	STATION	NORTH	EAST
POT	10+00.00	686122.6960	1505439.2030
PC	10+50.00	686082.5464	1505469.0025
PCC	13+93.29	685799.1021	1505662.5177
PRC	16+55.13	685570.3338	1505789.6455
PRC	16+55.13	685570.3338	1505789.6455
PT	17+83.61	685455.9757	1505848.1966
PC	19+19.64	685336.0505	1505912.4030
PCC	20+16.64	685252.4841	1505961.5872
PT	20+98.68	685186.1974	1506009.8523
POT	21+18.68	685170.7259	1506022.5263

NOTES:

- PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
- THE SURVEY CONTROL DATA FOR THIS PROJECT HAS BEEN COMPILED FROM VARIOUS SOURCES. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.


Location and Surveys

PROJECT SURVEYOR




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

6/2/19



INSERT A



PI Sta	Δ	D	L	T	R	DS
12+21.74	4° 31' 18.0" (RT)	1° 19' 01.7"	343.29'	171.74'	4,350.00'	55 MPH
15+24.33	6° 00' 03.2" (RT)	2° 17' 30.6"	261.84'	131.04'	2,500.00'	50 MPH
17+19.38	2° 06' 11.9" (LT)	1° 38' 13.3"	128.48'	64.25'	3,500.00'	55 MPH

ROW MARKER IRON PIN AND CAP - E

ALIGN	STATION	OFFSET	NORTH	EAST
L	13+30.00	-30.00	685868.7882	1505653.7209
L	13+55.00	30.00	685815.3164	1505616.7650
L	15+00.00	50.00	685682.7797	1505673.7465
L	15+00.00	-65.00	685739.6110	1505773.7225
L	16+55.13	50.00	685548.3677	1505744.7290
L	17+20.00	30.16	685498.5754	1505791.8352
L	17+83.61	-30.00	685470.1356	1505874.6446


ROW MARKER PERMANENT EASEMENT - E

ALIGN	STATION	OFFSET	NORTH	EAST
L	11+56.00	30.00	685979.3807	1505506.6159
L	11+62.00	64.00	685954.9545	1505482.2318
L	11+65.00	30.00	685972.0707	1505511.7588
L	11+71.00	63.00	685948.2683	1505488.1435
L	13+91.00	-62.00	685833.9842	1505713.8263
L	13+92.00	-53.00	685828.3452	1505706.7392
L	13+99.00	-64.00	685828.1114	1505719.8577
L	14+01.00	-55.00	685821.6162	1505713.2998
L	16+44.00	-81.00	685616.2308	1505857.3387
L	16+65.00	-43.71	685580.7870	1505833.2041

I, Michael L. Molsinger, certify that the right of way and permanent easement monumentation for this project shown herein was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:10,000 (Class A). Field work was performed from July 3, 2023 to July 12, 2023, and all coordinates are based on NAD83/2011; That this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 27th day of July, 2023

Designed by:
Michael L. Molsinger
Professional Land Surveyor L-3877



NOTES:

1. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.
2. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
3. RIGHT OF WAY MONUMENTATION ESTABLISHED ____ TO ____.

REVISIONS

F:\7-2023\1547\7-2023\Division\LowImpact\79-0254-Caldwell.Rd.RW Staking\to be checked\79-0254-1s-rw04.dgn
 M.L. Molsinger
 7/1/2023 15:47



Location and Surveys

INSERT CONSULTANT'S NAME

PROJECT SURVEYOR



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




REVISIONS

F:\Jul-2023\1855... 7-11-2023 11:55... 79-0254-Caldwell1.Rd.RW Staking\to be checked\79-0254-1s-rw05.dgn

I, Michael L. Motsinger, certify that the right of way and permanent easement monumentation for this project shown herein was completed under my direct and responsible charge from an actual survey made under my supervision; that all horizontal closures had a minimum ratio of precision of 1:10,000 (Class A). Field work was performed from July 3, 2023 to July 12, 2023 and all coordinates are based on NAD83/2011; That this survey was performed to meet the requirements of 21NCAC 56.1600 as applicable.

This 27th day of July, 2023.

DocuSigned by:
Michael L. Motsinger
Professional Land Surveyor L-3877




NOTES:

1. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.
2. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
3. RIGHT OF WAY MONUMENTATION ESTABLISHED ____ TO ____ .


STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

TRANSPORTATION MANAGEMENT PLAN

ROWAN COUNTY



**LOCATION: BRIDGE #254 OVER KERR CREEK
ON SR 1547 (CALDWELL RD)**




VICINITY MAP —●—●—●—● OFFSITE DETOUR

INDEX OF SHEETS	
<u>SHEET NO.</u>	<u>TITLE</u>
TMP-1	TITLE SHEET, VICINITY MAP, AND INDEX OF SHEETS
TMP-2	LIST OF APPLICABLE ROADWAY STANDARD DRAWINGS, AND LEGEND
TMP-3	TRANSPORTATION OPERATIONS PLAN: (GENERAL NOTES, LOCAL NOTES & PHASING)
TMP-4	TEMPORARY TRAFFIC CONTROL DETAILS
TMP-5	SPECIAL SIGN DESIGN

SHEET NO.
TMP-1

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**




PLANS PREPARED BY:

 GERALD H. McCAULEY, PE
 TRAFFIC ENGINEER

 CARLOS G. OWENS JR.
 TRANSPORTATION DESIGNER

NCDOT CONTACTS:

 JEREMY KEATON, PE
 PROJECT ENGINEER



stv STV Engineers, Inc.
2151 Hawkins Street, Suite 1400
Charlotte, NC 28203
NC License Number F-0991

APPROVED: _____
DATE: _____

SEAL

1/22/2026
C:\TrafficControl\TCP\TMP\R_96_rdy_tmp01.tsh.dgn
G. Owens

ROADWAY STANDARD DRAWINGS


THE FOLLOWING ROADWAY STANDARDS AS SHOWN IN "ROADWAY STANDARD DRAWINGS" - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2024 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
1101.01	WORK ZONE WARNING SIGNS
1101.02	TEMPORARY LANE CLOSURES
1101.03	TEMPORARY ROAD CLOSURES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.01	STATIONARY WORK ZONE SIGNS
1110.02	PORTABLE WORK ZONE SIGNS
1145.01	BARRICADES

LEGEND

GENERAL

- DIRECTION OF TRAFFIC FLOW
- DIRECTION OF PEDESTRIAN TRAFFIC FLOW
- EXIST. PVMT.
- NORTH ARROW
- PROPOSED PVMT.



SIGNALS

- EXISTING
- PROPOSED
- TEMPORARY
- MODIFIED

PAVEMENT MARKINGS

- EXISTING LINES
- TEMPORARY LINES

TRAFFIC CONTROL DEVICES

- BARRICADE (TYPE III)
- CONE
- DRUM SKINNY DRUM TUBULAR MARKER
- TEMPORARY CRASH CUSHION
- FLASHING ARROW BOARD
- FLAGGER
- LAW ENFORCEMENT
- TRUCK MOUNTED ATTENUATOR (TMA)
- CHANGEABLE MESSAGE SIGN

TEMPORARY SIGNING

- PORTABLE SIGN
- STATIONARY SIGN
- STATIONARY OR PORTABLE SIGN

PAVEMENT MARKERS

- CRYSTAL/CRYSTAL
- CRYSTAL/RED
- YELLOW/YELLOW

PAVEMENT MARKING SYMBOLS

- PAVEMENT MARKING SYMBOLS

1/22/2026
 C:\TrafficControl\TCP\TMP\R.96_rdy_tmp02.dgn
 OwenSC

APPROVED: _____ DATE: _____		
ROADWAY STANDARD DRAWINGS & LEGEND		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		

PROJECT NOTES

GENERAL NOTES

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS, AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS OR RESULT IN DUPLICATE OR UNDESIRE OVERLAPPING OF DEVICES. MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING, OR REMOVAL OF DEVICES AS DIRECTED BY THE ENGINEER.

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT EXCEPT WHEN OTHERWISE NOTED IN THE PLAN OR DIRECTED BY THE ENGINEER.

HOLIDAYS & EVENTS

1. FOR UNEXPECTED OCCURRENCE THAT CREATES UNUSUALLY HIGH TRAFFIC VOLUMES, AS DIRECTED BY THE ENGINEER.
2. FOR NEW YEAR'S DAY, BETWEEN THE HOURS OF 6:00 AM DECEMBER 31ST AND 9:00 AM JANUARY 2ND. IF NEW YEAR'S DAY IS ON A FRIDAY, SATURDAY, SUNDAY OR MONDAY, THEN UNTIL 9:00 AM THE FOLLOWING TUESDAY.
3. FOR EASTER, BETWEEN THE HOURS OF 6:00 AM THURSDAY AND 9:00 AM MONDAY.
4. FOR MEMORIAL DAY, BETWEEN THE HOURS OF 6:00 AM FRIDAY AND 9:00 AM TUESDAY.
5. FOR INDEPENDENCE DAY, BETWEEN THE HOURS OF 6:00 AM THE DAY BEFORE INDEPENDENCE DAY AND 7:00 PM THE DAY AFTER INDEPENDENCE DAY.
 IF INDEPENDENCE DAY IN ON A FRIDAY, SATURDAY, SUNDAY, OR MONDAY, THEN BETWEEN THE HOURS OF 6:00 AM THE THURSDAY BEFORE INDEPENDENCE DAY AND 7:00 PM THE TUESDAY AFTER INDEPENDENCE DAY.
6. FOR LABOR DAY, BETWEEN THE HOURS OF 6:00 AM FRIDAY AND 9:00 AM TUESDAY.
7. FOR THANKSGIVING DAY, BETWEEN THE HOURS OF 6:00 AM FRIDAY AND 9:00 AM TUESDAY.
8. FOR CHRISTMAS, BETWEEN THE HOURS OF 7:00 PM THE FRIDAY BEFORE THE WEEK OF CHRISTMAS DAY AND 9:00 AM THE FOLLOWING TUESDAY AFTER THE WEEK OF CHRISTMAS DAY.

TRAFFIC PATTERN ALTERATIONS

- A) NOTIFY THE ENGINEER THIRTY (30) CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION.

LANE AND SHOULDER CLOSURE REQUIREMENTS

- B) REMOVE LANE CLOSURE DEVICES FROM THE LANE WHEN WORK IS NOT BEING PERFORMED BEHIND THE LANE CLOSURE OR WHEN A LANE CLOSURE IS NO LONGER NEEDED OR AS DIRECTED BY THE ENGINEER.
- C) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN 15 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN SHOULDER USING ROADWAY STANDARD DRAWING NO. 1101.02 UNLESS THE WORK AREA IS PROTECTED BARRIER OR GUARDRAIL.

SIGNING

- D) INSTALL WORK ZONE WARNING SIGNS WHEN WORK IS WITHIN 40 FT FROM THE EDGE OF TRAVEL LANE AND NO MORE THAN THREE (3) DAYS PRIOR TO THE BEGINNING OF CONSTRUCTION.
- E) ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY TRAFFIC PATTERN.
- F) PROVIDE SIGNING REQUIRED FROM THE OFF-SITE DETOUR ROUTE AS SHOWN IN THE TRAFFIC CONTROL PLANS.
- G) COVER OR REMOVE ALL SIGNS AND DEVICES REQUIRED FOR OFF-SITE DETOUR WHEN DETOUR IS NOT IN OPERATION.

TRAFFIC CONTROL DEVICES

- H) PLACE TYPE III BARRICADES WITH "ROAD CLOSED" SIGN R11-2 ATTACHED, OF SUFFICIENT LENGTH TO CLOSE ENTIRE ROADWAY.

TRAFFIC MANAGEMENT STRATEGIES

THE PROJECT WILL BE CONSTRUCTED AWAY FROM TRAFFIC USING OFF SITE DETOUR WHEREVER POSSIBLE, WHERE TRAFFIC IS AFFECTED, A COMBINATION OF LANE CLOSURES AND FLAGGERS WILL BE USED AS NECESSARY.

LANE SHIFTS OR CLOSURES
 SHOULDER CLOSURES
 ONE-LANE, TWO WAY OPERATION (FLAGGING)

DURING OFF PEAK TIMES USE TEMPORARY LANE CLOSURE AS REQUIRED, CONSTRUCT PAVEMENT TIE INS, DRAINAGE AND PAVEMENT WEDGING WHEN WORK ZONE IS LESS THAN 5' FROM AN OPEN TRAVEL LANE

LOCAL NOTES

1. CONTACT ROWAN COUNTY AND TOWN OF CHINA GROVE EMERGENCY SERVICES AND SCHOOLS AT LEAST ONE MONTH PRIOR TO CONSTRUCTION.

PHASING

NOTE: BEFORE BEGINNING CONSTRUCTION, THE CONTRACTOR SHALL PLACE ADVANCE WORK ZONE WARNING SIGNS. (SEE RSD 1101.01, SHEET 3 OF 3)

PHASE 1

STEP 1

INSTALL OFF-SITE DETOUR SIGNING TO CLOSE CALDWELL ROAD (SR 1547) TO THROUGH TRAFFIC (SEE TMP-4).

USING RSD 1101.03 (SHEETS 1 OF 9) INSTALL TYPE III BARRICADES AND CLOSE CALDWELL ROAD TO THROUGH TRAFFIC.

STEP 2



AWAY FROM TRAFFIC, REMOVE THE EXISTING BRIDGE, CONSTRUCT PROPOSED BRIDGE, DRAINAGE, AND ROADWAY INCLUDING THE FINAL LAYER OF SURFACE COURSE.
 PLACE FINAL PAVEMENT MARKINGS.

STEP 3

USING RSD 1101.02 SHEET 1 OF 19, REMOVE ALL TRAFFIC CONTROL DEVICES, SIGNING AND DETOUR ROUTE SIGNING.

OPEN CALDWELL ROAD (SR 1547) TO THE FINAL TRAFFIC PATTERN.

I:\22\2026\17BP.9.R.96\TrafficControl\TCP\TMP\R.96_rdy_tmp03.dgn
 02/22/2026
 R:\TrafficControl\TrafficControl\TCP\TMP\R.96_rdy_tmp03.dgn
 02/22/2026
 02/22/2026

APPROVED: _____ DATE: _____ <div style="text-align: center;">SEAL</div>			<h3>TRANSPORTATION MANAGEMENT PLAN PROJECT NOTES</h3>
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			



OFF-SITE DETOUR SIGNING AND ROAD CLOSURE SIGNING

STV STV Engineers, Inc.
2151 Hawkins Street, Suite 1400
Charlotte, NC 28203
NC License Number F-0991

PROJ. REFERENCE NO.	SHEET NO.
17BP.9.R.96	TMP-4

NOTE: MAINTAIN DRIVEWAY ACCESS THROUGHOUT THE PROJECT LIMITS.

SEE ROADWAY STD DWG 1101.03, SHEET 1 OF 9 FOR ADVANCE WARNING AND BARRICADE PLACEMENT.



N.T.S.

● ● ROADWAY DETOUR

APPROVED: _____

DATE: _____

SEAL


DESIGNED BY: *[Signature]*

ENGINEER: *[Signature]*

GERALD H. MCCANN, P.E.

12/23/2026

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



**TRANSPORTATION
MANAGEMENT PLAN
DETOUR ROUTE**


I:\22\2026
 R:\Traffic\TrafficControl\TCP\TMP\R\36_rdy_tmp04.dgn
 Owens

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

stv STV Engineers, Inc.
2151 Hawkins Street, Suite 1400
Charlotte, NC 28203
NC License Number F-0991

PROJECT REFERENCE NO. 17BP.9.R.96	SHEET NO. PMP-1
--------------------------------------	--------------------

RW SHEET NO.
**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



PAVEMENT MARKING & SIGNING PLANS
ROWAN COUNTY

LOCATION: BRIDGE #254 OVER KERR CREEK ON SR 1547 (CALDWELL ROAD)

INDEX

SHEET NO.	DESCRIPTION
PMP-1	PAVEMENT MARKING PLAN TITLE SHEET
PMP-2	PAVEMENT MARKING PLAN

ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS SHOWN IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2024 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
1205.01	PAVEMENT MARKINGS - LINE TYPES AND OFFSETS
1205.02	PAVEMENT MARKINGS - TWO-LANE AND MULTILANE ROADWAYS
1205.04	PAVEMENT MARKINGS - INTERSECTIONS
1205.09	PAVEMENT MARKINGS - PAINTED ISLANDS
1205.12	PAVEMENT MARKINGS - BRIDGES
1261.01	GUARDRAIL AND BARRIER DELINEATORS - INSTALLATION SPACING
1261.02	GUARDRAIL AND BARRIER DELINEATORS - TYPES AND MOUNTING
1262.01	GUARDRAIL END DELINEATION

GENERAL NOTES

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN, OR DIRECTED BY THE ENGINEER.

A) INSTALL PAVEMENT MARKINGS ON THE FINAL SURFACE.

ROAD NAME	MARKING	MARKERS
SR 1547 (CALDWELL ROAD)	THERMO PLASTIC	NONE

- B) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.
- C) REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND MARKERS.
- D) PASSING ZONES WILL BE DETERMINED IN THE FIELD AND MUST BE APPROVED BY THE ENGINEER.
- E) REPLACE ANY PAVEMENT MARKINGS BEYOND THE PROJECT LIMITS DAMAGED BY THE CONTRACTORS' OPERATIONS DURING CONSTRUCTION.

SUMMARY OF QUANTITIES

ITEM NO.	DESC. NO.	SECT. NO.	ITEM DESCRIPTION	QUANTITY	UNIT
4025000000	901		CONTRACTOR FURNISHED, TYPE E SIGN.....	6.5	S.F.
4072000000	903		SUPPORTS, 3 LBS STEEL U-CHANNEL.....	14	L.F.
4102000000	904		SIGN ERECTION, TYPE E.....	1	EA.
4155000000	907		DISPOSAL OF SIGN SYSTEM, U-CHANNEL.....	1	EA.

PLAN PREPARED BY:
STV Engineers, Inc.

GERALD H. McCAULEY, PE TRAFFIC ENGINEER
CARLOS G. OWENS JR. TRANSPORTATION DESIGNER

stv STV Engineers, Inc.
2151 Hawkins Street, Suite 1400
Charlotte, NC 28203
NC License Number F-0991


8/17/99

PAVEMENT MARKING PLAN

stv STV Engineers, Inc.
2151 Hawkins Street, Suite 1400
Charlotte, NC 28203
NC License Number F-0991



PROJECT REFERENCE NO. 17BP.9.R.96	SHEET NO. PMP-2
RW SHEET NO.	

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



PAVEMENT MARKING SCHEDULE	
T1 - THERMOPLASTIC	WHITE EDGELINE (4", 90MIL)
T13 - THERMOPLASTIC	YELLOW DOUBLE CENTER (4", 90MIL)

NOTES	
1) REMOVE EXIST. SIGN SYSTEM.	




PAVEMENT MARKING SCHEDULE	
T1 - THERMOPLASTIC	WHITE EDGELINE (4", 90MIL)
T13 - THERMOPLASTIC	YELLOW DOUBLE CENTER (4", 90MIL)

NOTES	
2) ERECT NEW SIGN SYSTEM AND ERECT NEW U-CHANNEL.	

1/22/2026
K:\Projects\TrafficControl\TCP\SH\17BP.9.R.96.PMP-2.dgn
G:\Users\jmc\OneDrive\Documents\TrafficControl\TCP\SH\17BP.9.R.96.PMP-2.dgn

PROJECT WBS: 17BP.9.R.96






VICINITY MAP
NOT TO SCALE

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS
**PLAN FOR PROPOSED
HIGHWAY EROSION CONTROL
ROWAN COUNTY**


LOCATION: BRIDGE #254 OVER KERR CREEK ON SR 1547 (CALDWELL RD)

TYPE OF WORK: GRADING, PAVING, DRAINAGE, & STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.9.R.96	EC-1	10
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
17BP.9.R.96		P.E.	
17BP.9.R.96		RW & UTILITY	
17BP.9.R.96		CONSTRUCTION	



- THIS PROJECT HAS BEEN DESIGNED TO SENSITIVE WATERSHED STANDARDS.
- ENVIRONMENTALLY SENSITIVE AREA(S) EXIST ON THIS PROJECT
Refer To E. C. Special Provisions for Special Considerations.
- HIGH QUALITY WATER(S) EXIST ON THIS PROJECT
High Quality Water Zone(s) Exist From Sta. -L- STA. 12+50.00 to Sta. -L- STA. 18+40.00 Refer To E. C. Special Provisions for Special Considerations.
- THIS PROJECT CONTAINS EROSION CONTROL PLANS FOR CLEARING AND GRUBBING PHASE OF CONSTRUCTION.



THESE EROSION AND SEDIMENT CONTROL PLANS COMPLY WITH THE APPLICABLE REGULATIONS SET FORTH BY THE NCG-010000 GENERAL STORMWATER CONSTRUCTION PERMIT ISSUED BY THE NORTH CAROLINA DEPARTMENT OF ENVIRONMENTAL QUALITY DIVISION OF ENERGY, MINERAL, AND LAND RESOURCES.



Prepared In the Office of:
STV ENGINEERS, INC.
2151 HAWKINS STREET, SUITE 1400
CHARLOTTE, NC 28203

Designed by:
JOY SADDLER, PE **4143**
NAME LEVEL III CERTIFICATION NO.

Roadway Standard Drawings


The "Roadway Standard Drawings"- Roadway Design Unit - N. C. Department of Transportation - Raleigh, N. C., dated January 2024 and the latest revision thereto are applicable to this project and by reference hereby are considered a part of these plans.

DIVISION OF HIGHWAYS STATE OF NORTH CAROLINA


EROSION & SEDIMENT CONTROL LEGEND

Std. #	Description	Symbol	Std. #	Description	Symbol
1605.01	Temporary Silt Fence		1633.01	Temporary Rock Silt Check Type A	
1606.01	Special Sediment Control Fence		1633.02	Temporary Rock Silt Check Type B	
1622.01	Temporary Berms and Slope Drains		1633.03	Temporary Rock Silt Check Type A with Excelsior Matting and Flocculant	
1630.02	Silt Basin Type B		1634.01	Temporary Rock Sediment Dam Type A	
1630.03	Temporary Silt Ditch		1634.02	Temporary Rock Sediment Dam Type B	
1630.04	Stilling Basin		1635.01	Rock Pipe Inlet Sediment Trap Type A	
1630.05	Temporary Diversion		1635.02	Rock Pipe Inlet Sediment Trap Type B	
1630.06	Special Stilling Basin		1636.01	Excelsior Wattle Check	
1630.07	Skimmer Basin		1636.01	Excelsior Wattle Check with Flocculant	
1630.08	Tiered Skimmer Basin		1636.01	Coir Fiber Wattle Check	
1630.09	Earthen Dam with Skimmer		1636.01	Coir Fiber Wattle Check with Flocculant	
	Infiltration Basin		1636.02	Silt Fence Excelsior Wattle Break	
	Rock Inlet Sediment Trap:			Silt Fence Coir Fiber Wattle Break	
1632.01	Type A		1636.03	Excelsior Wattle Barrier	
1632.02	Type B		1636.03	Coir Fiber Wattle Barrier	
1632.03	Type C				

SILT FENCE COIR FIBER WATTLE BREAK DETAIL



ISOMETRIC VIEW





VIEW FROM SLOPE

NOTES:




- USE MINIMUM 12 IN. DIAMETER COIR FIBER (COCONUT FIBER) WATTLE AND LENGTH OF 10 FT.
- EXCAVATE A 1 TO 2 INCH TRENCH FOR WATTLE TO BE PLACED.
- DO NOT PLACE WATTLE ON TOE OF SLOPE.
- USE 2 FT. WOODEN STAKES WITH A 2 IN. BY 2 IN. NOMINAL CROSS SECTION.
- INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO GROUND.
- PROVIDE STAPLES MADE OF 0.125 IN. DIAMETER STEEL WIRE FORMED INTO A U SHAPE NOT LESS THAN 12" IN LENGTH.
- INSTALL STAPLES APPROXIMATELY EVERY 1 LINEAR FOOT ON BOTH SIDES OF WATTLE AND AT EACH END TO SECURE IT TO THE SOIL.
- WATTLE INSTALLATION CAN BE ON OUTSIDE OF THE SILT FENCE AS DIRECTED.
- INSTALL TEMPORARY SILT FENCE IN ACCORDANCE WITH SECTION 1605 OF THE STANDARD SPECIFICATIONS.

INSET A






SIDE VIEW

ONSITE CONCRETE WASHOUT STRUCTURE WITH LINER



BELOW GRADE WASHOUT STRUCTURE
NOT TO SCALE

- NOTES:
1. ACTUAL LOCATION DETERMINED IN FIELD
 2. THE CONCRETE WASHOUT STRUCTURES SHALL BE MAINTAINED WHEN THE LIQUID AND/OR SOLID REACHES 75% OF THE STRUCTURES CAPACITY TO PROVIDE ADEQUATE HOLDING CAPACITY WITH A MINIMUM 12 INCHES OF FREEBOARD.
 3. CONCRETE WASHOUT STRUCTURE NEEDS TO BE CLEARLY MARKED WITH SIGNAGE NOTING DEVICE.





ABOVE GRADE WASHOUT STRUCTURE
NOT TO SCALE

- NOTES:
1. ACTUAL LOCATION DETERMINED IN FIELD
 2. THE CONCRETE WASHOUT STRUCTURES SHALL BE MAINTAINED WHEN THE LIQUID AND/OR SOLID REACHES 75% OF THE STRUCTURES CAPACITY TO PROVIDE ADEQUATE HOLDING CAPACITY WITH A MINIMUM 12 INCHES OF FREEBOARD.
 3. CONCRETE WASHOUT STRUCTURE NEEDS TO BE CLEARLY MARKED WITH SIGNAGE NOTING DEVICE.

DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

SOIL STABILIZATION TIMEFRAMES

<i>SITE DESCRIPTION</i>	<i>STABILIZATION TIME</i>	<i>TIMEFRAME EXCEPTIONS</i>
PERIMETER DIKES, SWALES, DITCHES AND SLOPES	7 DAYS	NONE
HIGH QUALITY WATER (HQW) ZONES	7 DAYS	NONE
SLOPES STEEPER THAN 3:1	7 DAYS	IF SLOPES ARE 10' OR LESS IN LENGTH AND ARE NOT STEEPER THAN 2:1, 14 DAYS ARE ALLOWED.
SLOPES 3:1 TO 4:1	14 DAYS	7 DAYS FOR SLOPES GREATER THAN 50' IN LENGTH WITH SLOPES STEEPER THAN 4:1. 7 DAYS FOR PERIMETER DIKES, SWALES, DITCHES PERIMETER SLOPES, AND HQW ZONES
ALL OTHER AREAS WITH SLOPES FLATTER THAN 4:1	14 DAYS	7 DAYS FOR PERIMETER DIKES, SWALES, DITCHES PERIMETER SLOPES, AND HQW ZONES




CLEARING AND GRUBBING
EROSION CONTROL FOR
CONSTRUCTION SHEET 4

NOTE:
UTILIZE TEMPORARY SEDIMENT BASIN OR SPECIAL STILLING
BASIN(S) AS STILLING BASIN WHERE APPLICABLE.



NOTE:
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B
AND TEMPORARY ROCK SILT CHECKS TYPE - A AT
DRAINAGE OUTLETS.

NOTE:
FOLLOW NCDOT BMP MANUAL FOR CONSTRUCTION
ACTIVITIES FOR THE BRIDGE DEMOLITION AND
CONSTRUCTION

CLEAN WATER DIVERSION




TEMPORARY EARTH BERM




 ENVIRONMENTALLY SENSITIVE AREA
SEE PROJECT SPECIAL PROVISIONS

1/29/2026 Environmental\Design\Sheets\17BP.9.R.96_EC.CG_psh04.dgn


MATCHLINE -L- STA 17+50 (SHEET EC-5)



②
MICHAEL W. STEED AND WIFE,
CATHY STEED
DB 1042 PG 789
MB 9995 PG 3342



MATCHLINE -L- STA 17+50 (SHEET EC-4)






CLEARING AND GRUBBING
EROSION CONTROL FOR
CONSTRUCTION SHEET 5

NOTE:
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B
AND TEMPORARY ROCK SILT CHECKS TYPE - A AT
DRAINAGE OUTLETS.

NOTE:
UTILIZE TEMPORARY SEDIMENT BASIN OR SPECIAL STILLING
BASIN(S) AS STILLING BASIN WHERE APPLICABLE.

8/17/99
1/29/2026 Environmental\Design\Sheets\17.96_EC.CG_psh05.dgn

MICHAEL W. STEED AND CATHY STEED DB 1042 PG 789 MB 9995 PG 3342



FINAL PHASE EROSION CONTROL FOR CONSTRUCTION SHEET 4

PLACE MATTING FOR EROSION CONTROL ON ALL GRADED SLOPES BEHIND GUARDRAIL


NOTE: UTILIZE TEMPORARY SEDIMENT BASIN OR SPECIAL STILLING BASIN(S) AS STILLING BASIN WHERE APPLICABLE.

NOTE: FOLLOW NCDOT BMP MANUAL FOR CONSTRUCTION ACTIVITIES FOR THE BRIDGE DEMOLITION AND CONSTRUCTION


8/17/2026 Environmental\Design\Sheets\17BP.9.R.96_EC_6.PSHT06.dgn

MATCHLINE -L- STA 17+50 (SHEET EC-7)

8/17/99



②
 MICHAEL W. STEED AND WIFE,
 CATHY STEED
 DB 1042 PG 789
 MB 9995 PG 3342



④
 PATTERSON VENTURES, LLC
 DB 1183 PG 246

FINAL PHASE
 EROSION CONTROL FOR
 CONSTRUCTION SHEET 5

NOTE:
 UTILIZE TEMPORARY SEDIMENT BASIN OR SPECIAL STILLING
 BASIN(S) AS STILLING BASIN WHERE APPLICABLE.


NOTE:
 FOLLOW NCDOT BMP MANUAL FOR CONSTRUCTION
 ACTIVITIES FOR THE BRIDGE DEMOLITION AND
 CONSTRUCTION

I:\2025\Environmental\Design\Sheets\17BP.9.R.96_EC_FP_psh07.dgn

09/28/99

TIP PROJECT: 17BP.9.R.96

\$\$\$\$\$ SYSTEM \$\$\$\$\$\$
\$\$\$\$\$ DGN \$\$\$\$\$\$
\$\$\$\$\$ USERNAME \$\$\$\$\$\$



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS




**UTILITIES BY OTHERS PLANS
ROWAN COUNTY**

**LOCATION: BRIDGE #254 OVER KERR CREEK
ON SR 1547 (CALDWELL RD)**


**TYPE OF WORK: GRADING, PAVING, DRAINAGE,
& STRUCTURE**

T.I.P. NO.	SHEET NO.
17BP.9.R.96	UO-1

NOTE:
ALL UTILITY WORK SHOWN ON THIS SHEET IS DONE BY OTHERS.
NO PAYMENT WILL BE MADE TO THE CONTRACTOR FOR UTILITY WORK SHOWN ON THIS SHEET.



PRELIMINARY PLANS
DO NOT USE FOR CONSTRUCTION



INDEX OF SHEETS

SHEET NO.:	DESCRIPTION:
UO-1	TITLE SHEET
UO-2 THRU UO-3	UBO PLAN SHEETS

UTILITY OWNERS WITH CONFLICTS

(A) POWER - DUKE ENERGY
(B) TELECOM - CONTERRA NETWORKS

PREPARED IN THE OFFICE OF:

stv STV Engineers, Inc.
2151 Hawkins Street, Suite 1400
Charlotte, NC 28203
NC License Number F-0991



Oriana Roumillat	UTILITY PROJECT MANAGER
Phillip Vang	PROJECT UTILITY COORDINATOR
Justin Hill	PROJECT UTILITY CAD

**DIVISION OF HIGHWAYS
UTILITIES UNIT**
1555 MAIL SERVICES CENTER
RALEIGH NC 27699-1555
PHONE (919) 707-6690
FAX (919) 250-4151


Ali Koucheki, PE	UTILITIES REGIONAL ENGINEER
Ian R. Armstrong	UTILITIES ENGINEER
Arlene Harper	UTILITIES AREA COORDINATOR
Roderick L. Mitchell	UTILITIES COORDINATOR

UTILITIES BY OTHERS

NOTE:
ALL UTILITY WORK SHOWN ON THIS SHEET WILL BE DONE BY OTHERS. NO PAYMENT WILL BE MADE TO THE CONTRACTOR FOR UTILITY WORK SHOWN ON THIS SHEET.



INSERT UO-A




MATCHLINE -L- STA 12+00 SEE INSET UO-A

MATCHLINE -L- STA 17+50 (SHEET UO-3)

5/14/99
 55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
00


6/23/16

0 2.5 5	PROJ. REFERENCE NO. 17BP.9.R.96	SHEET NO. X-2
---------	------------------------------------	------------------




NOTE: APPROXIMATE QUANTITIES ONLY. UNCLASSIFIED EXCAVATION, BORROW EXCAVATION, FINE GRADING, CLEARING AND GRUBBING, AND REMOVAL OF EXISTING PAVEMENT WILL BE PAID FOR AT THE CONTRACT LUMP SUM PRICE FOR "GRADING."

1/22/2026 R:\Roadway\Corridor Modeling\17BP.rd\17BP.rd\1.L.dgn



6/23/16


0 2.5 5	PROJ. REFERENCE NO. 17BP.9.R.96	SHEET NO. X-3
---------	------------------------------------	------------------



1/22/2026
R:\Roadway\Corridor Modeling\196_rdy_xpl.dgn
awensc

6/23/16

0 2.5 5	PROJ. REFERENCE NO. 17BP.9.R.96	SHEET NO. X-4
---------	------------------------------------	------------------





1/22/2026
R:\Roadway\Corridor_Modeling\17BP.rdj_xpl.dgn
awensc

6/23/16

0 2.5 5	PROJ. REFERENCE NO. 17BP.9.R.96	SHEET NO. X-5
---------	------------------------------------	------------------

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75





75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

1/22/2026
R:\Roadway\Corridor Modeling\17BP\rdj_xpl.L.dgn
rdj

6/23/16

0 2.5 5	PROJ. REFERENCE NO. 17BP.9.R.96	SHEET NO. X-6
---------	------------------------------------	------------------

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75




75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

1/22/2026
R:\Roadway\Corridor_Modeling\17BP.rdj_xpl.dgn
jwensc


6/23/16

0 2.5 5	PROJ. REFERENCE NO. 17BP.9.R.96	SHEET NO. X-7
---------	------------------------------------	------------------

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



17+50



17+00


75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

1/22/2026
R:\Roadway\Corridor Modeling\17BP\rdj_xpl.dgn
awensc


6/23/16

0 2.5 5	PROJ. REFERENCE NO. 17BP.9.R.96	SHEET NO. X-8
---------	------------------------------------	------------------

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



18 + 40
END PROJECT



18 + 00


1/22/2026
R:\Roadway\Corridor_Modeling\17BP.rdj_xpl.dgn
awensc

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

6/23/16

0 2.5 5	PROJ. REFERENCE NO. 17BP.9.R.96	SHEET NO. X-9
---------	------------------------------------	------------------

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



1/22/2026
R:\Roadway\Corridor Modeling\196_rdy_xpl.dgn
awensc

PROJECT WBS: 17BP.9.R.96





CONTRACT: DI00378

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

ROWAN COUNTY

**LOCATION: BRIDGE #254 OVER KERR CREEK
ON SR 1547 (CALDWELL RD)**
TYPE OF WORK: GRADING, PAVING, DRAINAGE, & STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.9.R.96	1	18
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
17BP.9.R.96		P.E.	
17BP.9.R.96		R.O.W.	
17BP.9.R.96		CONSTRUCTION	



STRUCTURE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

DESIGN DATA

ADT 2026 = 1670
ADT 2046 = 2428
DHV = N/A
D = N/A
T = 6 %
V = 55 MPH

FUNC. CLASSIFICATION:
LOCAL
SUB REGIONAL TIER

PROJECT LENGTH

LENGTH OF ROADWAY PROJECT WBS 17BP.9.R.96 = 0.095 MILES
LENGTH OF STRUCTURE PROJECT WBS 17BP.9.R.96 = 0.017 MILES
TOTAL LENGTH OF PROJECT WBS 17BP.9.R.96 = 0.112 MILES

NCDOT CONTACT: JEREMY KEATON, P.E.
Division Bridge Manager

PLANS PREPARED FOR THE NCDOT BY:

stv STV Engineers, Inc.
2151 Hawkins Street, Suite 1400
Charlotte, NC 28203
NC License Number F-0991

2024 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE:
JANUARY 25, 2023

LETTING DATE:
FEBRUARY 25, 2026

LIU ZHUGANG, P.E.
PROJECT ENGINEER

J. WESLEY JONES, P.E.
PROJECT DESIGNER


STRUCTURES ENGINEER

WESLEY JONES
1/23/2026

SIGNATURE: _____ P.E.



1/22/2026 R:\Structures\02_Station\RFC\401_000_17BP.9.R.96_SML_TSH_000_790254.dgn Jones



HYDRAULIC DATA


DESIGN DISCHARGE: 1,900 CFS
 FREQUENCY OF DESIGN FLOOD: 25 YRS.
 DESIGN HIGH WATER ELEVATION: 720.1
 DRAINAGE AREA: 7.82 SQ. MI.
 BASE DISCHARGE (Q100): 2,713 CFS
 BASE HIGH WATER ELEVATION: 721.9

OVERTOPPING DATA

OVERTOPPING DISCHARGE: 6,500 CFS
 FREQUENCY OF OVERTOPPING: 500± YRS.
 OVERTOPPING FLOOD ELEVATION: 726.3
 OVERTOPS @ STA. 14+38.58 -L-

I HEREBY CERTIFY THESE ARE THE AS-BUILT PLANS

RESIDENT ENGINEER




HORIZONTAL CURVE DATA -L-

PI = 15+24.33 -L-
 Δ = 6°-00'-03.2" (RT.)
 D = 2°-17'-30.6"
 L = 261.84'
 T = 131.04'
 R = 2,500.00'

HORIZONTAL CURVE DATA -L-

PI = 17+19.38 -L-
 Δ = 2°-06'-11.9" (LT.)
 D = 1°-38'-13.3"
 L = 128.48'
 T = 64.25'
 R = 3,500.00'

BRIDGE TO BE LAID OUT ALONG LONG CHORD



stv STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. 17BP.9.R.96
 ROWAN COUNTY
 STATION: 15+55.00 -L-
 SHEET 1 OF 3 REPLACES BRIDGE NO. 790254

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
GENERAL DRAWING
 FOR BRIDGE ON SR 1547
 (CALDWELL RD.) OVER
 KERR CREEK BETWEEN
 NC 150 AND SR 1350

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

S-1
 TOTAL SHEETS
 16

DRAWN BY: JWJ DATE: 9-22
 CHECKED BY: MLO DATE: 9-22
 DESIGN ENGINEER OF RECORD: JWJ DATE: 9-25

(STEEL PILES NOT SHOWN FOR CLARITY)

R:\Structures\02_Station\REFC\401_001\7BP.9.R.96_SMU_GDI_001_790254.dgn 10/9/2025 9:03:01 PM khnm

SUMMARY OF PILE INFORMATION/INSTALLATION

(Blank entries indicate item is not applicable to structure)

End Bent/ Bent No, Pile(s) #(-#) (e.g., "Bent 1, Piles 1-5")	Factored Resistance per Pile TONS	Pile Cut-Off (Top of Pile) Elevation FT	Estimated Pile Length per Pile FT	Scour Critical Elevation FT	Driven Piles			Predrilling for Piles*			Drilled-In Piles			
					Min Pile Tip (Tip No Higher Than) Elev FT	Required Driving Resistance (RDR)** per Pile TONS	Total Pile Redrives Quantity EACH	Predrilling Length per Pile Lin FT	Predrilling Elevation (Elev Not To Predrill Below) FT	Maximum Predrilling Dia INCHES	Pile Excavation (Bottom of Hole) Elev FT	Pile Exc Not In Soil per Pile Lin FT	Pile Exc In Soil per Pile Lin FT	
End Bent No. 1, Piles 1-7	111	See Structure Drawings	15								709.0	4.0	6.0	
End Bent No. 2, Piles 1-7	111		15			184								

*Predrilling for Piles is required for end bents/bents with a predrilling length and at the Contractor's option for end bents/bents with predrilling information but no predrilling length.

$$**RDR = \frac{\text{Factored Resistance} + \text{Factored Downdrag Load} + \text{Factored Dead Load}}{\text{Dynamic Resistance Factor}} + \text{Nominal Downdrag Resistance} + \frac{\text{Nominal Scour Resistance}}{\text{Scour Resistance Factor}}$$

SUMMARY OF PDA/PILE ORDER LENGTHS

(Blank entries indicate item is not applicable to structure)

Pile Driving Analyzer (PDA)				Pile Order Lengths	
End Bent/ Bent No	PDA Testing Required? YES or MAYBE	PDA Test Pile Length FT	Total PDA Testing Quantity EACH	End Bent/ Bent No(s)	Pile Order Length Basis* EST or PDA

*EST = Pile order lengths from estimated pile lengths; PDA = Pile order lengths based on PDA testing. For groups of end bents/bents with pile order lengths based on PDA testing, the first end bent/bent no. listed for each group is the representative end bent/bent with the PDA.

PILE DESIGN INFORMATION

(Blank entries indicate item is not applicable to structure)

End Bent/ Bent No, Pile(s) #(-#) (e.g., "Bent 1, Piles 1-5")	Factored Axial Load per Pile TONS	Factored Downdrag Load per Pile TONS	Factored Dead Load* per Pile TONS	Dynamic Resistance Factor	Nominal Downdrag Resistance per Pile TONS	Nominal Scour Resistance per Pile TONS	Scour Resistance Factor (Default = 1.00)
End Bent No. 2, Piles 1-7	110			0.60			1.00

*Factored Dead Load is factored weight of pile above the ground line.

SUMMARY OF PILE ACCESSORIES

(Blank entries indicate item is not applicable to structure)


End Bent/ Bent No, Pile(s) #(-#) (e.g., "Bent 1, Piles 1-5")	Pipe Pile Plates Required? YES or MAYBE	Steel Pile Points			Steel Pile Tips Required? YES
		Pipe Pile Cutting Shoes Required? YES	Pipe Pile Conical Points Required? YES	H-Pile Points Required? YES	
End Bent No. 2, Piles 1-7				YES	
TOTAL QTY:				7	

FOUNDATION NOTES

1. For Piles, see Piles Provision and Section 450 of the Standard Specifications.
2. Fill the holes for pile excavation at End Bent No. 1 with concrete.

NOTES:

1. The Pile Foundation Tables are based on the bridge substructure design and foundation recommendations sealed by a North Carolina Professional Engineer Shiping Yang, License #031361 on 07/12/2023
2. Total Pile Driving Equipment Setup quantity (not shown in Pile Foundation Tables) equals the number of driven piles, i.e., the number of piles with a Required Driving Resistance.
3. The Engineer will determine the need for PDA Testing and Pipe Pile Plates when PDAs or plates may be required.



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

PROJECT NO. 17BP.9.R.96

ROWAN COUNTY


STATION: 15+55.00 -L-

SHEET 2 OF 3

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

**PILE
FOUNDATION
TABLES**

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-2
1			3			TOTAL SHEETS
2			4			16



GENERAL NOTES

ASSUMED LIVE LOAD = HL-93 OR ALTERNATE LOADING.

THIS BRIDGE HAS BEEN DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS.

THIS BRIDGE IS LOCATED IN SEISMIC ZONE 1.

FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE "STANDARD NOTES" SHEET.

FOR EROSION CONTROL MEASURES, SEE EROSION CONTROL PLANS.

THE EXISTING STRUCTURE CONSISTING OF (1) 51'-2" SPAN WITH STEEL PLANK DECK ON 9 LINES OF STEEL I-BEAMS WITH A CLEAR ROADWAY WIDTH OF 24'-2"± AND SUPPORTED BY MASS CONCRETE ABUTMENTS AND LOCATED AT THE PROPOSED STRUCTURE SHALL BE REMOVED. THE EXISTING BRIDGE IS PRESENTLY NOT POSTED FOR LOAD LIMIT. SHOULD THE STRUCTURAL INTEGRITY OF THE BRIDGE DETERIORATE DURING CONSTRUCTION OF THE PROPOSED BRIDGE, A LOAD LIMIT MAY BE POSTED AND MAY BE REDUCED AS FOUND NECESSARY DURING THE LIFE OF THE PROJECT.

REMOVAL OF THE EXISTING BRIDGE SHALL BE PERFORMED SO AS NOT TO ALLOW DEBRIS TO FALL INTO THE WATER. THE CONTRACTOR SHALL SUBMIT DEMOLITION PLANS FOR REVIEW AND REMOVE THE BRIDGE IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS.

INASMUCH AS THE PAINT SYSTEM ON THE EXISTING STRUCTURAL STEEL CONTAINS LEAD, THE CONTRACTOR'S ATTENTION IS DIRECTED TO ARTICLE 107-1 OF THE STANDARD SPECIFICATIONS. ANY COSTS RESULTING FROM COMPLIANCE WITH APPLICABLE STATE OR FEDERAL REGULATIONS PERTAINING TO HANDLING OF MATERIALS CONTAINING LEAD BASED PAINT SHALL BE INCLUDED IN THE BID PRICE FOR "REMOVAL OF EXISTING STRUCTURE AT STATION 15+55.00 -L-".

THE MATERIAL SHOWN IN THE CROSS-HATCHED AREA (ON SHEET 1 OF 3) SHALL BE EXCAVATED FOR A DISTANCE FROM THE CENTERLINE OF ROADWAY OF 29'± (LEFT) AND 28'± (RIGHT) AT END BENT 1 TO EL. 717.5±, AND 35'± (LEFT) AND 35'± (RIGHT) AT END BENT 2 TO EL. 717.5±, AS DIRECTED BY THE ENGINEER. THIS WORK WILL BE PAID FOR AT THE CONTRACT LUMP SUM PRICE FOR UNCLASSIFIED STRUCTURE EXCAVATION. SEE SECTION 412 OF THE STANDARD SPECIFICATIONS.

THE SUBSTRUCTURE OF THE EXISTING BRIDGE INDICATED ON THE PLANS IS FROM THE BEST INFORMATION AVAILABLE. SINCE THIS INFORMATION IS SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR, THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT OF TRANSPORTATION FOR ANY DELAYS OR ADDITIONAL COST INCURRED BASED ON DIFFERENCES BETWEEN THE EXISTING BRIDGE SUBSTRUCTURE SHOWN ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

THIS STRUCTURE HAS BEEN DESIGNED IN ACCORDANCE WITH "HEC 18 - EVALUATING SCOUR AT BRIDGES".

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

ASPHALT WEARING SURFACE IS INCLUDED IN ROADWAY QUANTITY ON ROADWAY PLANS.


FOR ASBESTOS ASSESSMENT, SEE SPECIAL PROVISIONS.

LOCATION SKETCH

TOTAL BILL OF MATERIAL

	REMOVAL OF EXISTING STRUCTURE AT STA. 15+55.00 -L-	ASBESTOS ASSESSMENT	PILE EXCAVATION IN SOIL	PILE EXCAVATION NOT IN SOIL	UNCLASSIFIED STRUCTURE EXCAVATION	CLASS A CONCRETE	BRIDGE APPROACH SLABS STA. 15+55.00 -L-	REINFORCING STEEL	PILE DRIVING EQUIPMENT SETUP FOR HP 12 X 53 STEEL PILES	HP 12 X 53 STEEL PILES	STEEL PILE POINTS	VERTICAL CONCRETE BARRIER RAIL	RIP RAP CLASS II (2'-0" THICK)	GEOTEXTILE FOR DRAINAGE	ELASTOMERIC BEARINGS	3'-0" X 2'-9" PRESTRESSED CONCRETE BOX BEAMS		
	LUMP SUM	LUMP SUM	LIN. FT.	LIN. FT.	LUMP SUM	CU. YD.	LUMP SUM	LBS.	EA.	NO.	LIN. FT.	EA.	LIN. FT.	TONS	SQ. YDS.	LUMP SUM	NO.	LIN. FT.
SUPERSTRUCTURE												180.0					12	1080.0
END BENT 1			42	28		27.0		3,809	7	7	105		180	200				
END BENT 2						27.0		3,809	7	7	105	7	140	155				
TOTAL	LUMP SUM	LUMP SUM	42	28	LUMP SUM	54.0	LUMP SUM	7,618	14	14	210	7	180.0	320	355	LUMP SUM	12	1080.0

PROJECT NO. 17BP.9.R.96
ROWAN COUNTY
 STATION: 15+55.00 -L-
 SHEET 3 OF 3



STV STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
GENERAL DRAWING
 FOR BRIDGE ON SR 1547
 (CALDWELL RD.) OVER
 KERR CREEK BETWEEN
 NC 150 AND SR 1350

REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

S-3	TOTAL SHEETS
16	

DRAWN BY : JWJ DATE : 9-22
 CHECKED BY : MLO DATE : 9-22
 DESIGN ENGINEER OF RECORD : JWJ DATE : 9-25

R:\Structures\02_station\RFC\401_005_17BP.9.R.96_SML_603_003_790254.dgn 10/9/2025 9:03:11 PM khnm

LOAD AND RESISTANCE FACTOR RATING (LRFD) SUMMARY FOR PRESTRESSED CONCRETE GIRDERS

LEVEL	VEHICLE	WEIGHT (W) (TONS)	CONTROLLING LOAD RATING	MINIMUM RATING FACTORS (RF)	TONS = W X RF	STRENGTH I LIMIT STATE										SERVICE III LIMIT STATE					COMMENT NUMBER		
						MOMENT					SHEAR					MOMENT							
						LIVELOAD FACTORS	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (FF)	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (FF)	LIVELOAD FACTORS	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN		GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (FF)
DESIGN LOAD RATING	HL-93(Inv)	N/A	1	1.109	--	1.75	0.272	1.47	A	EL	44.25	0.493	1.26	A	EL	4.425	0.80	0.272	1.11	A	EL	44.25	
	HL-93(Opr)	N/A	--	1.633	--	1.35	0.272	1.9	A	EL	44.25	0.493	1.63	A	EL	4.425	N/A	--	--	--	--	--	
	HS-20(Inv)	36.000	2	1.507	54.255	1.75	0.272	1.99	A	EL	44.25	0.493	1.65	A	EL	4.425	0.80	0.272	1.51	A	EL	44.25	
	HS-20(Opr)	36.000	--	2.14	77.039	1.35	0.272	2.59	A	EL	44.25	0.493	2.14	A	EL	4.425	N/A	--	--	--	--	--	
LEGAL LOAD RATING	SV	SNSH	13.500	--	3.519	47.501	1.4	0.272	5.82	A	EL	44.25	0.493	5.05	A	EL	4.425	0.80	0.272	3.52	A	EL	44.25
		SNGARBS2	20.000	--	2.572	51.43	1.4	0.272	4.25	A	EL	44.25	0.493	3.55	A	EL	4.425	0.80	0.272	2.57	A	EL	44.25
		SNAGRIS2	22.000	--	2.415	53.122	1.4	0.272	4	A	EL	44.25	0.493	3.27	A	EL	4.425	0.80	0.272	2.41	A	EL	44.25
		SNCOTTS3	27.250	--	1.749	47.674	1.4	0.272	2.89	A	EL	44.25	0.493	2.52	A	EL	4.425	0.80	0.272	1.75	A	EL	44.25
		SNAGGRS4	34.925	--	1.443	50.381	1.4	0.272	2.39	A	EL	44.25	0.493	2.06	A	EL	4.425	0.80	0.272	1.44	A	EL	44.25
		SNS5A	35.550	--	1.412	50.195	1.4	0.272	2.34	A	EL	44.25	0.493	2.07	A	EL	4.425	0.80	0.272	1.41	A	EL	44.25
		SNS6A	39.950	--	1.287	51.435	1.4	0.272	2.13	A	EL	44.25	0.493	1.88	A	EL	4.425	0.80	0.272	1.29	A	EL	44.25
	TTST	SNS7B	42.000	--	1.226	51.483	1.4	0.272	2.03	A	EL	44.25	0.493	1.83	A	EL	4.425	0.80	0.272	1.23	A	EL	44.25
		TNAGRIT3	33.000	--	1.568	51.733	1.4	0.272	2.59	A	EL	44.25	0.493	2.24	A	EL	4.425	0.80	0.272	1.57	A	EL	44.25
		TNT4A	33.075	--	1.572	52.007	1.4	0.272	2.6	A	EL	44.25	0.493	2.2	A	EL	4.425	0.80	0.272	1.57	A	EL	44.25
		TNT6A	41.600	--	1.278	53.17	1.4	0.272	2.11	A	EL	44.25	0.493	1.92	A	EL	4.425	0.80	0.272	1.28	A	EL	44.25
		TNT7A	42.000	--	1.281	53.782	1.4	0.272	2.12	A	EL	44.25	0.493	1.89	A	EL	4.425	0.80	0.272	1.28	A	EL	44.25
		TNT7B	42.000	--	1.315	55.229	1.4	0.272	2.18	A	EL	44.25	0.493	1.79	A	EL	4.425	0.80	0.272	1.31	A	EL	44.25
		TNAGRIT4	43.000	--	1.258	54.101	1.4	0.272	2.08	A	EL	44.25	0.493	1.74	A	EL	4.425	0.80	0.272	1.26	A	EL	44.25
EMERGENCY VEHICLE (EV)	TNAGT5A	45.000	--	1.19	53.537	1.4	0.272	1.97	A	EL	44.25	0.493	1.71	A	EL	4.425	0.80	0.272	1.19	A	EL	44.25	
	TNAGT5B	45.000	3	1.178	53.027	1.4	0.272	1.95	A	EL	44.25	0.493	1.66	A	EL	4.425	0.80	0.272	1.18	A	EL	44.25	
EMERGENCY VEHICLE (EV)	EV2	28.750	--	2.296	66.005	1.3	0.272	3.25	A	EL	44.25	0.493	2.49	A	EL	4.425	0.80	0.272	2.30	A	EL	44.25	
	EV3	43.000	4	1.510	64.924	1.3	0.272	2.14	A	EL	44.25	0.493	1.67	A	EL	4.425	0.80	0.272	1.51	A	EL	44.25	

LOAD FACTORS:

DESIGN LOAD RATING FACTORS	LIMIT STATE	γ_{DC}	γ_{DW}
	STRENGTH I	1.25	1.50
	SERVICE III	1.00	1.00

NOTES:

MINIMUM RATING FACTORS ARE BASED ON THE STRENGTH I AND SERVICE III LIMIT STATES.
ALLOWABLE STRESSES FOR SERVICE III LIMIT STATE ARE AS REQUIRED FOR DESIGN.

COMMENTS:

- 1.
- 2.
- 3.
- 4.

CONTROLLING LOAD RATING

① DESIGN LOAD RATING (HL-93)

② DESIGN LOAD RATING (HS-20)


③ LEGAL LOAD RATING **

④ EMERGENCY VEHICLE LOAD RATING **

** SEE CHART FOR VEHICLE TYPE

GIRDER LOCATION

I - INTERIOR GIRDER
EL - EXTERIOR LEFT GIRDER
ER - EXTERIOR RIGHT GIRDER



PROJECT NO. 17BP.9.R.96
ROWAN COUNTY
 STATION: 15+55.00 -L-



stv STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

STANDARD
 LRFR SUMMARY FOR
 90' BOX BEAM UNIT
 90° SKEW
 (NON-INTERSTATE TRAFFIC)

REVISIONS				SHEET NO.		
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS
1			3			16
2			4			16

10/9/2025 9:03:42 PM R:\Structures\02_ustation\RFC\401_007_17BP.9.R.96_SML_LRFR_004_790254.dgn

ASSEMBLED BY : <u>JWJ</u>	DATE : <u>9-22</u>
CHECKED BY : <u>MLO</u>	DATE : <u>9-22</u>
DESIGN ENGINEER OF RECORD : <u>JWJ</u>	DATE : <u>9-25</u>
DRAWN BY : <u>TMG</u> II/II	REV. 06/23
CHECKED BY : <u>AAC</u> II/II	AKP/AAI

NOTES

ALL PRESTRESSING STRANDS SHALL BE 7-WIRE LOW RELAXATION GRADE 270 STRANDS AND SHALL CONFORM TO AASHTO M203 EXCEPT FOR SAMPLING REQUIREMENTS WHICH SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

ALL REINFORCING STEEL CAST WITH THE BOX BEAM SECTIONS SHALL BE GRADE 60 AND SHALL BE INCLUDED IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE BOX BEAMS.

FLAME CUTTING OF THE TRANSVERSE POST-TENSIONING STRAND IS NOT ALLOWED.

RECESSES FOR TRANSVERSE STRANDS SHALL BE GROUTED AFTER THE TENSIONING OF THE STRANDS.

THE 2 1/2" Ø DOWEL HOLES AT FIXED ENDS OF BOX BEAM SECTIONS SHALL BE FILLED WITH NON-SHRINK GROUT.

THE BACKER RODS SHALL CONFORM TO THE REQUIREMENTS OF TYPE M BOND BREAKER. SEE SECTION 1028 OF THE STANDARD SPECIFICATIONS.

THE TRANSFER OF LOAD FROM THE ANCHORAGES TO THE BOX BEAM UNIT SHALL BE DONE WHEN THE CONCRETE HAS REACHED A COMPRESSIVE STRENGTH OF NOT LESS THAN 6000 PSI.

ALL REINFORCING STEEL IN VERTICAL CONCRETE BARRIER RAILS SHALL BE EPOXY COATED.

PRESTRESSING STRANDS SHALL BE CUT FLUSH WITH THE BOX BEAM UNIT ENDS.

APPLY EPOXY PROTECTIVE COATING TO BOX BEAM UNIT ENDS.

VERTICAL GROOVED CONTRACTION JOINTS, 1/2" IN DEPTH, SHALL BE TOOLED IN ALL EXPOSED FACES OF THE BARRIER RAIL AND IN ACCORDANCE WITH ARTICLE 825-10(B) OF THE STANDARD SPECIFICATIONS. A VERTICAL CONTRACTION JOINT SHALL BE LOCATED AT EACH THIRD POINT BETWEEN BARRIER RAIL EXPANSION JOINTS. ONLY ONE CONTRACTION JOINT IS REQUIRED AT MIDPOINT OF BARRIER RAIL SEGMENTS LESS THAN 20 FEET IN LENGTH AND NO CONTRACTION JOINTS ARE REQUIRED FOR THOSE SEGMENTS LESS THAN 10 FEET IN LENGTH.

THE LOCATION OF THE VOID DRAINS MAY BE SHIFTED SLIGHTLY WHERE NECESSARY TO CLEAR PRESTRESSING STRANDS OR TRANSVERSE REINFORCING STEEL.


FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

THE PERMITTED THREADED INSERTS ARE DETAILED AS AN OPTION FOR THE CONTRACTOR TO ATTACH FALSEWORK AND FORMWORK DURING CONSTRUCTION.

THE PERMITTED THREADED INSERTS IN THE EXTERIOR UNITS SHALL BE SIZED BY THE CONTRACTOR, SPACED AT 4'-0" CENTERS AND GALVANIZED IN ACCORDANCE WITH SECTION 1076 OF THE STANDARD SPECIFICATIONS. STAINLESS STEEL THREADED INSERTS MAY BE USED AS AN ALTERNATE.

THE PERMITTED THREADED INSERTS SHALL BE GROUTED BY THE CONTRACTOR IMMEDIATELY FOLLOWING REMOVAL OF THE FALSEWORK.

THE COST OF THE PERMITTED THREADED INSERTS SHALL BE INCLUDED IN THE PRICE BID FOR THE PRECAST UNITS.




HALF SECTION THROUGH VOIDS

HALF SECTION AT INTERMEDIATE DIAPHRAGMS

TYPICAL SECTION


*THE MAXIMUM BARRIER RAIL HEIGHT AND ASPHALT THICKNESS IS SHOWN. THE HEIGHT OF THE BARRIER RAIL AND ASPHALT THICKNESS VARIES WHILE THE TOP OF THE BARRIER RAIL FOLLOWS THE PROFILE OF THE GUTTERLINE. FOR RAIL HEIGHT DETAILS AND ASPHALT THICKNESS, SEE THE "VERTICAL CONCRETE BARRIER RAIL SECTION" DETAIL.

FIXED END



SECTION AT END BENT

PERMITTED THREADED INSERT CAST IN OUTSIDE FACE OF EXTERIOR UNIT AND RECESSED 3/8" SIZE TO BE DETERMINED BY CONTRACTOR.



THREADED INSERT DETAIL

PROJECT NO. 17BP.9.R.96

ROWAN COUNTY

STATION: 15+55.00 -L-

SHEET 1 OF 5

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
 3'-0" X 2'-9"
 PRESTRESSED CONCRETE
 BOX BEAM UNIT



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


ASSEMBLED BY : JWJ	DATE : 9-22
CHECKED BY : MLO	DATE : 9-22
DESIGN ENGINEER OF RECORD : JWJ	DATE : 9-25
DRAWN BY : DGE 8/11	REV. 9/14 MAA/TMG
CHECKED BY : TMG 11/11	

REVISIONS				SHEET NO.
NO.	BY:	DATE:	NO.	DATE:
1			3	
2			4	


S-5
TOTAL SHEETS 16

R:\Structures\02_ustation\RFC\401_009_17BP_9.R.96_SMJ_BBL_005_790254.dgn 10/24/2025 6:02:53 PM

R:\Structures\02_Station\RFC\401_OIL\ITBP_9.R.96_SMU_BB2_006_790254.dgn 10/9/2025 9:03:14 PM




PLAN OF UNIT



DIAPHRAGM AND VOID LAYOUT

PROJECT NO. 17BP.9.R.96
ROWAN COUNTY
 STATION: 15+55.00 -L-
 SHEET 2 OF 5

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 PLAN OF 90' UNIT
 36'-10" CLEAR ROADWAY
 90° SKEW










stv STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

ASSEMBLED BY : JWJ	DATE : 9-22
CHECKED BY : MLO	DATE : 9-22
DESIGN ENGINEER OF RECORD : JWJ	DATE : 9-25
DRAWN BY : DGE 8/11	REV. 8/14 MAA/TMG
CHECKED BY : TMG 11/11	

REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		


TOTAL SHEETS 16



DOUBLE DIAPHRAGM DETAILS

#4 "S" BARS NOT SHOWN. #4 "S" BARS MAY BE SHIFTED SLIGHTLY TO CLEAR 2 1/2" Ø HOLE.

GROUTED RECESS DETAIL AT END OF POST-TENSIONED STRANDS OF EXTERIOR BOX BEAM




VOID DRAIN DETAILS

(DIMENSIONS SHOWN ARE TYPICAL FOR EACH VOID)

DEAD LOAD DEFLECTION AND CAMBER	
	3'-0" x 2'-9"
90' BOX BEAM UNIT	0.6" Ø L.R. STRAND
CAMBER (SLAB ALONE IN PLACE)	2 3/4" ↑
DEFLECTION DUE TO SUPERIMPOSED DEAD LOAD**	3/4" ↓
FINAL CAMBER	2" ↑

** INCLUDES FUTURE WEARING SURFACE

PROJECT NO. 17BP.9.R.96
ROWAN COUNTY
 STATION: 15+55.00 -L-
 SHEET 4 OF 5




stv STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
STANDARD 3'-0" X 2'-9" PRESTRESSED CONCRETE BOX BEAM UNIT					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					S-8
					TOTAL SHEETS 16


10/9/2025 9:03:45 PM R:\Structures\02_ustation\RFC\401_015_17BP.9.R.96_SMU_BB4_008_790254.dgn

ASSEMBLED BY : JWJ	DATE : 9-22
CHECKED BY : MLO	DATE : 9-22
DESIGN ENGINEER OF RECORD : JWJ	DATE : 9-25
DRAWN BY : DGE 10/11	REV. 8/14 MAA/TMG
CHECKED BY : TMG 11/11	




ELASTOMERIC BEARING DETAILS


ELASTOMER IN ALL BEARINGS SHALL BE 60 DUROMETER HARDNESS.




END OF RAIL DETAILS



VERTICAL CONCRETE BARRIER RAIL DETAILS




ELEVATION AT EXPANSION JOINTS



BOX BEAM UNITS REQUIRED

	NUMBER	LENGTH	TOTAL LENGTH
EXTERIOR B.B.	2	90'-0"	180'-0"
INTERIOR B.B.	10	90'-0"	900'-0"
TOTAL	12		1080'-0"




GUTTERLINE ASPHALT THICKNESS & RAIL HEIGHT

	ASPHALT OVERLAY THICKNESS @ MID-SPAN	RAIL HEIGHT @ MID-SPAN
90' UNITS	1 3/4"	3'-7 3/4"

BILL OF MATERIAL FOR VERTICAL CONCRETE BARRIER RAIL

BAR	BARS PER PAIR OF EXTERIOR UNITS	SIZE	TYPE	LENGTH	WEIGHT	
	90' UNIT					
*B10	96	#5	STR	22'-1"	2211	
*S6	252	#5	1	7'-2"	1884	
* EPOXY COATED REINFORCING STEEL					LBS.	4095
CLASS AA CONCRETE					CU. YDS.	23.3
TOTAL VERTICAL CONCRETE BARRIER RAIL					LN. FT.	180.0



stv STV Engineers, Inc.
2151 Hawkins St., Suite 1400
Charlotte, NC 28203
NC License Number F-0991

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

PROJECT NO. 17BP.9.R.96
ROWAN COUNTY
STATION: 15+55.00 -L-
SHEET 5 OF 5

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
**3'-0" X 2'-9"
PRESTRESSED CONCRETE
BOX BEAM UNIT**


REVISIONS				SHEET NO.
NO.	BY:	DATE:	NO.	DATE:
1			3	
2			4	

TOTAL SHEETS	S-9
16	




10/9/2025 9:03:16 PM R:\Structures\02_ustation\RFC\401_017_17BP.9.R.96_SMU_BB5_009_790254.dgn

ASSEMBLED BY : JWJ	DATE : 9-22
CHECKED BY : MLO	DATE : 9-22
DESIGN ENGINEER OF RECORD : JWJ	DATE : 9-25
DRAWN BY : DGE 10/11	REV. 5/18
CHECKED BY : TMG 11/11	MAA/THC

R:\Structures\02_Station\REF\401_019_17BP_9.R.96_SMU_GR_010_790254.dgn
10/9/2025 9:03:46 PM



FOR LOCATION OF GUARDRAIL ANCHOR ASSEMBLY, SEE "PLAN" BELOW



LOCATION OF ANCHORS FOR GUARDRAIL

END BENT #1 SHOWN, END BENT #2 SIMILAR.

NOTES

THE GUARDRAIL ANCHOR ASSEMBLY SHALL CONSIST OF A 1/4" HOLD DOWN PLATE AND 7 - 7/8" Ø BOLTS WITH NUTS AND WASHERS.

THE HOLD-DOWN PLATE SHALL CONFORM TO AASHTO M270 GRADE 36. AFTER FABRICATION, THE HOLD-DOWN PLATE SHALL BE HOT-DIP GALVANIZED IN ACCORDANCE WITH AASHTO M111.

BOLTS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A307 AND NUTS SHALL CONFORM TO THE REQUIREMENTS OF AASHTO M291. BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED. (AT THE CONTRACTOR'S OPTION, STAINLESS STEEL BOLTS, NUTS AND WASHERS MAY BE USED AS AN ALTERNATE FOR THE 7/8" Ø GALVANIZED BOLTS, NUTS AND WASHERS. THEY SHALL CONFORM TO OR EXCEED THE MECHANICAL REQUIREMENTS OF ASTM A307. THE USE OF THIS ALTERNATE SHALL BE APPROVED BY THE ENGINEER.)

THE GUARDRAIL ANCHOR ASSEMBLY IS REQUIRED AT ALL POINTS WHERE APPROACH GUARDRAIL IS TO BE ATTACHED TO THE END OF BARRIER RAIL. FOR POINTS OF ATTACHMENT, SEE SKETCH.

AFTER INSTALLATION, THE EXPOSED THREAD OF THE BOLT SHALL BE BURRED WITH A SHARP POINTED TOOL.

THE COST OF THE GUARDRAIL ANCHOR ASSEMBLY SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR VERTICAL CONCRETE BARRIER RAIL.


THE VERTICAL REINFORCING BARS MAY BE SHIFTED SLIGHTLY IN THE VERTICAL CONCRETE BARRIER RAIL TO CLEAR ASSEMBLY BOLTS.

THE 1 1/4" Ø HOLES SHALL BE FORMED OR DRILLED WITH A CORE BIT. IMPACT TOOLS WILL NOT BE PERMITTED. ANY CONCRETE DAMAGED BY THIS WORK SHALL BE REPAIRED TO THE SATISFACTION OF THE ENGINEER.



* DENOTES GUARDRAIL ANCHOR ASSEMBLY

PROJECT NO. 17BP.9.R.96
ROWAN COUNTY
 STATION: 15+55.00 -L-



stv STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
 GUARDRAIL ANCHORAGE
 DETAILS FOR
 VERTICAL CONCRETE
 BARRIER RAIL

ASSEMBLED BY : JWW	DATE : 9-22
CHECKED BY : MLO	DATE : 9-22
DESIGN ENGINEER OF RECORD : JWW	DATE : 9-25
DRAWN BY : MAA 5/10	REV. 1/15 MAA/TMG
CHECKED BY : GM 5/10	REV. 12/17 MAA/THC
	REV. 5/18 MAA/THC

REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

S-10
TOTAL SHEETS 16

R:\Structures\02_Station\REF\401_02\17BP.9.R.96_SMU_EL_OIL_790254.dgn 10/9/2025 9:03:17 PM khnm


NOTES

STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR DOWELS.

THE CONCRETE IN THE SHADED AREA OF THE WING SHALL BE POURED AFTER THE VERTICAL CONCRETE BARRIER RAIL IS CAST IF SLIP FORMING IS USED.


FOR PILE SPLICE DETAILS, SEE SHEET 4 OF 4.

FOR WING DETAILS, SEE SHEET 3 OF 4.



PLAN

TOP OF PILE ELEVATIONS	
①	721.91
②	721.72
③	721.52
④	721.33
⑤	721.13
⑥	720.94
⑦	720.74




ELEVATION

WINGS NOT SHOWN FOR CLARITY.
 FOR SECTION A-A, SEE SHEET 4 OF 4.
 CONCRETE COLLARS FOR STEEL PILES NOT SHOWN IN PLAN AND ELEVATION VIEWS FOR CLARITY.
 SEE "CORROSION PROTECTION FOR STEEL PILES DETAIL", SHEET 4 OF 4.

PROJECT NO. 17BP.9.R.96
 ROWAN COUNTY
 STATION: 15+55.00 -L-
 SHEET 1 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE
 END BENT No. 1



stv STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

ASSEMBLED BY : JWJ	DATE : 9-22
CHECKED BY : MLO	DATE : 9-22
DESIGN ENGINEER OF RECORD : JWJ	DATE : 9-25
DRAWN BY : WJH 12/11	REV. 4/15 MAA/TMG
CHECKED BY : AAC 12/11	

REVISIONS				SHEET NO.
NO.	BY:	DATE:	NO.	DATE:
1			3	
2			4	

S-11
 TOTAL SHEETS 16


NOTES

STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR DOWELS.

THE CONCRETE IN THE SHADED AREA OF THE WING SHALL BE POURED AFTER THE VERTICAL CONCRETE BARRIER RAIL IS CAST IF SLIP FORMING IS USED.


FOR PILE SPLICE DETAILS, SEE SHEET 4 OF 4.

FOR WING DETAILS, SEE SHEET 3 OF 4.



PLAN

TOP OF PILE ELEVATIONS	
①	722.84
②	722.65
③	722.45
④	722.26
⑤	722.06
⑥	721.87
⑦	721.67



ELEVATION

PROJECT NO. 17BP.9.R.96
 ROWAN COUNTY
 STATION: 15+55.00 -L-
 SHEET 2 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE
 END BENT No. 2



stv STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991


**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

ASSEMBLED BY : JWJ	DATE : 9-22
CHECKED BY : MLO	DATE : 9-22
DESIGN ENGINEER OF RECORD : JWJ	DATE : 9-25
DRAWN BY : WJH 12/11	REV. 4/15 MAA/TMG
CHECKED BY : AAC 12/11	


WINGS NOT SHOWN FOR CLARITY.
 FOR SECTION A-A, SEE SHEET 4 OF 4.
 CONCRETE COLLARS FOR STEEL PILES NOT SHOWN IN PLAN AND ELEVATION VIEWS FOR CLARITY.
 SEE 'CORROSION PROTECTION FOR STEEL PILES DETAIL', SHEET 4 OF 4.

REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		


S-12
 TOTAL SHEETS 16




PLAN OF WING (W1)




PLAN OF WING (W2)




SECTION X-X



ELEVATION OF WING (W1)



ELEVATION OF WING (W2)




SECTION Y-Y

WING DETAILS

PROJECT NO. 17BP.9.R.96
ROWAN COUNTY
 STATION: 15+55.00 -L-
 SHEET 3 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE
 END BENT
 WING DETAILS



stv STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991


**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

ASSEMBLED BY : JWJ	DATE : 9-22
CHECKED BY : MLO	DATE : 9-22
DESIGN ENGINEER OF RECORD : JWJ	DATE : 9-25
DRAWN BY : WJH 12/11	REV. 4/15
CHECKED BY : AAC 12/11	MAA/TMG

REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

TOTAL SHEETS 16

10/9/2025 9:03:18 PM R:\Structures\02_Station\RFC\401_025_17BP.9.R.96_SML_E3_013_790254.dgn




BAGGED STONE AND PIPE SHALL BE PLACED IMMEDIATELY AFTER COMPLETION OF END BENT EXCAVATION. PIPE MAY BE EITHER CONCRETE, CORRUGATED STEEL, CORRUGATED ALUMINUM ALLOY, OR CORRUGATED PLASTIC. PERFORATED PIPE WILL NOT BE ALLOWED.

BAGGED STONE SHALL REMAIN IN PLACE UNTIL THE ENGINEER DIRECTS THAT IT BE REMOVED. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF SILT ACCUMULATIONS AT BAGGED STONE WHEN SO DIRECTED BY THE ENGINEER. BAGS SHALL BE REMOVED AND REPLACED WHENEVER THE ENGINEER DETERMINES THAT THEY HAVE DETERIORATED AND LOST THEIR EFFECTIVENESS.


NO SEPARATE PAYMENT WILL BE MADE FOR THIS WORK AND THE ENTIRE COST OF THIS WORK SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR THE SEVERAL PAY ITEMS.

TEMPORARY DRAINAGE AT END BENT



PILE SPLICE DETAILS

BAR TYPES



ALL BAR DIMENSIONS ARE OUT TO OUT.

BILL OF MATERIAL FOR ONE END BENT

BAR NO.	NO.	SIZE	TYPE	LENGTH	WEIGHT
B1	8	#9	1	44'-0"	1197
B2	28	#4	STR	22'-1"	413
B3	11	#4	STR	2'-5"	18
D1	24	#8	STR	2'-3"	144
H1	48	#5	2	11'-4"	567
K1	12	#4	STR	2'-11"	23
K2	12	#4	STR	22'-1"	177
S1	56	#4	3	10'-5"	390
S2	56	#4	4	3'-2"	118
S3	28	#4	5	6'-6"	122
U1	36	#4	6	3'-10"	92
V1	60	#4	STR	7'-2"	287
V2	72	#4	STR	5'-5"	261


REINFORCING STEEL (FOR ONE END BENT) 3809 LBS.

CLASS A CONCRETE BREAKDOWN (FOR ONE END BENT)

POUR #1	CAP, LOWER PART OF WINGS & COLLARS	21.3 C.Y.
POUR #2	BACKWALL & UPPER PART OF WINGS	5.7 C.Y.


TOTAL CLASS A CONCRETE 27.0 C.Y.

END BENT No. 1	END BENT No. 2
HP 12 X 53 STEEL PILES	HP 12 X 53 STEEL PILES
NO: 7	NO: 7
LIN. FT.= 105	LIN. FT.= 105
PILE DRIVING EQUIPMENT SETUP FOR HP 12 X 53 STEEL PILES	PILE DRIVING EQUIPMENT SETUP FOR HP 12 X 53 STEEL PILES
NO: 7	NO: 7
PILE REDRIVES	PILE REDRIVES
NO: 0	NO: 0



DETAIL "A"


(END BENT No. 1 SHOWN, END BENT No. 2 SIMILAR BY ROTATION)




PLAN

CORROSION PROTECTION FOR STEEL PILES DETAIL

(END BENT No. 1 SHOWN, END BENT No. 2 SIMILAR BY ROTATION)




ELEVATION



SECTION A-A

(CONCRETE COLLAR NOT SHOWN FOR CLARITY. SEE "CORROSION PROTECTION FOR STEEL PILES DETAIL.")



stv STV Engineers, Inc.
2151 Hawkins St., Suite 1400
Charlotte, NC 28203
NC License Number F-0991

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. 17BP.9.R.96

ROWAN COUNTY

STATION: 15+55.00 -L-

SHEET 4 OF 4

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE


END BENT No. 1 & 2
DETAILS

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

TOTAL SHEETS 16

STD. NO. EB_36_90S4_33BB




R:\Structures\02_ustation\RFC\401_027_17BP.9.R.96_SMJ.E4_014_790254.dgn 10/9/2025 9:03:19 PM khm



ESTIMATED QUANTITIES		
BRIDGE @ STA. 15+55.00 -L-	RIP RAP CLASS II (2'-0" THICK)	GEOTEXTILE FOR DRAINAGE
	TONS	SQUARE YARDS
END BENT 1	180	200
END BENT 2	140	155

PLAN - END BENT 1

PLAN - END BENT 2




END BENT 1 SHOWN, END BENT 2 SIMILAR

PROJECT NO. 17BP.9.R.96
ROWAN COUNTY
 STATION: 15+55.00 -L-

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

RIP RAP DETAILS

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-15
1			3			TOTAL SHEETS
2			4			16




stv STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991


**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

10/9/2025 9:03:20 PM R:\Structures\02_station\RFC\401_029_17BP.9.R.96_SML_RR_015_790254.dgn

R:\Structures\02_ustation\RFC\401_031\7BP.9.R.96_SMU_AS.016_790254.dgn 10/9/2025 9:03:20 PM khnm




PLAN @ END BENT #1 **PLAN @ END BENT #2**
 DIMENSIONS SHOWN ARE TYPICAL FOR BOTH APPROACH SLABS



SECTION THRU SLAB


NOTES

FOR BRIDGE APPROACH FILL, SEE ROADWAY PLANS.
 AREA BETWEEN THE WINGWALL AND APPROACH SLAB SHALL BE GRADED TO DRAIN THE WATER AWAY FROM THE FILL FACE OF THE BRIDGE AND SHALL BE PAVED. SEE ROADWAY PLANS.
 APPROACH SLAB GROOVING IS NOT REQUIRED.




NOTE: IF THE APPROACH SLAB IS NOT CONSTRUCTED IMMEDIATELY AFTER THE BACKFILLING OF THE END BENT EXCAVATION, GRADE TO DRAIN TO THE BOTTOM OF THE SLOPE AND PROVIDE EROSION RESISTANT MATERIAL, SUCH AS FIBERGLASS ROVING OR AS DIRECTED BY THE ENGINEER TO PREVENT SOIL EROSION AND TO PROTECT THE AREA ADJACENT TO THE STRUCTURE. THE CONTRACTOR WILL BE REQUIRED TO REMOVE THESE MATERIALS PRIOR TO CONSTRUCTION OF THE APPROACH SLAB.

TEMPORARY DRAINAGE DETAIL




TEMPORARY BERM AND SLOPE DRAIN DETAILS
 (TO BE USED WHEN SHOULDER BERM GUTTER IS REQUIRED)



SECTION N-N
CURB DETAILS

SPlice LENGTHS		
BAR SIZE	EPOXY COATED	UNCOATED
#4	1'-11"	1'-7"
#5	2'-5"	2'-0"
#6	3'-7"	2'-5"

BILL OF MATERIAL						
APPROACH SLAB AT EB #1						
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	
* A1	13	#4	STR	34'-10"	302	
A2	13	#4	STR	34'-10"	302	
* B1	70	#5	STR	11'-2"	815	
B2	70	#6	STR	11'-8"	1227	
REINFORCING STEEL					LBS.	1529
* EPOXY COATED REINFORCING STEEL					LBS.	1117
CLASS AA CONCRETE					C. Y.	18.6
APPROACH SLAB AT EB #2						
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	
* A1	13	#4	STR	34'-10"	302	
A2	13	#4	STR	34'-10"	302	
* B1	70	#5	STR	11'-2"	815	
B2	70	#6	STR	11'-8"	1227	
REINFORCING STEEL					LBS.	1529
* EPOXY COATED REINFORCING STEEL					LBS.	1117
CLASS AA CONCRETE					C. Y.	18.6



stv STV Engineers, Inc.
 2151 Hawkins St., Suite 1400
 Charlotte, NC 28203
 NC License Number F-0991

**DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED**

PROJECT NO. **17BP.9.R.96**
 ROWAN COUNTY
 STATION: **15+55.00 -L-**

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
 BRIDGE APPROACH SLAB
 BOX BEAM UNIT
 (SUB-REGIONAL TIER)
 90° SKEW

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

TOTAL SHEETS: 16

STANDARD NOTES

DESIGN DATA:

SPECIFICATIONS	AASHTO (CURRENT)
LIVE LOAD	SEE PLANS
IMPACT ALLOWANCE.....	SEE AASHTO
STRESS IN EXTREME FIBER OF STRUCTURAL STEEL - AASHTO M270 GRADE 36	---- 20,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50W	--- 27,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50	---- 27,000 LBS. PER SQ. IN.
REINFORCING STEEL IN TENSION - GRADE 60	----- 24,000 LBS. PER SQ. IN.
CONCRETE IN COMPRESSION	----- 1,200 LBS. PER SQ. IN.
CONCRETE IN SHEAR	----- SEE AASHTO
STRUCTURAL TIMBER - TREATED OR UNTREATED EXTREME FIBER STRESS	---- 1,800 LBS. PER SQ. IN.
COMPRESSION PERPENDICULAR TO GRAIN OF TIMBER	----- 375 LBS. PER SQ. IN.
EQUIVALENT FLUID PRESSURE OF EARTH	----- 30 LBS. PER CU. FT. (MINIMUM)

MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2024 "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; AND CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP.

CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED 3/4" WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO 1 1/2" RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A 1/4" FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A 1/4" RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT,
ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE.

ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER.

IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER.

DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS.

WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE 7/8" Ø SHEAR STUDS FOR THE 3/4" Ø STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF 7/8" Ø STUDS ALONG THE BEAM AS SHOWN FOR 3/4" Ø STUDS BASED ON THE RATIO OF 3 - 7/8"Ø STUDS FOR 4 - 3/4" Ø STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-0".

EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST 5/16" IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2" OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED.

WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES, ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY 1/16" OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB.

METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINIS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.