DocuSign Envelope ID: 63B99F10-5B56-439E-BCE5-B5D5838AF970

PROJECT REFERENCE NO.	SHEET NO.
17BP.9.R.25	EC-2B
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

SILT FENCE WATTLE BREAK DETAIL



ISOMETRIC VIEW

NOTES:

USE MINIMUM 12 IN. DIAMETER EXCELSIOR WATTLE AND LENGTH OF 10 FT.

EXCAVATE A 1 TO 2 INCH TRENCH FOR WATTLE TO BE PLACED.

DO NOT PLACE WATTLE ON TOE OF SLOPE.

USE 2 FT. WOODEN STAKES WITH A 2 IN. BY 2 IN. NOMINAL CROSS SECTION.

INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO GROUND.

PROVIDE STAPLES MADE OF 0.125 IN. DIAMETER STEEL WIRE FORMED INTO A U SHAPE NOT LESS THAN 12″ IN LENGTH.

INSTALL STAPLES APPROXIMATELY EVERY 1 LINEAR FOOT ON BOTH SIDES OF WATTLE AND AT EACH END TO SECURE IT TO THE SOIL.

WATTLE INSTALLATION CAN BE ON OUTSIDE OF THE SILT FENCE AS DIRECTED.

INSTALL TEMPORARY SILT FENCE IN ACCORDANCE WITH SECTION 1605 OF THE STANDARD SPECIFICATIONS.

INSET A





VIEW FROM SLOPE



SIDE VIEW

5/14/99
26-MAR-2016 17:10
$$$$HSE_PNAME $$$$
$$$$HSE_LNAME $$$$
$$$$HSE_FNAME $$$$
$$$$HSE_TITLE $$$$
$$$$HSE_EMAIL $$$$
$$$$HSE_PHONE $$$$
$$$$HSE_FAX $$$$
$$$$HSE_ADDR $$$$
$$$$HSE_CITY $$$$
$$$$HSE_STATE $$$$
$$$$HSE_ZIP $$$$
$$$$HSE_COUNTRY