


**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**

**This file or an individual page
shall not be considered a certified document.**

09/08/99

See Sheet 1-A For Index of Sheets
See Sheet 1-B For Conventional Symbols



● — ● — ● — DETOUR ROUTE


STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

ROWAN COUNTY

LOCATION: REPLACE EXISTING BRIDGE NO. 50 OVER NAILS BRANCH ON MT. VERNON RD. (SR 1986) WITH BOX CULVERT


TYPE OF WORK: GRADING, DRAINAGE, WIDENING, BOX CULVERT, AND PAVEMENT MARKINGS

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5160	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
42335.1.1	BRZ-1986(001)	PE	
42335.2.1	BRZ-1986(001)	RWUTILS	
42335.3.1	BRZ-1986(001)	CONST	




TIP PROJECT: B-5160

CONTRACT: DI00144



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



DESIGN DATA

ADT 2015 =	700
ADT 2035 =	XXX
DHV =	X %
D =	XX %
T =	X % *
V =	60 MPH
* X% TTST + X% DUALS	
FUNC CLASS =	LOCAL SUBREGIONAL TIER

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT B-5160 =	0.071 MILE
LENGTH STRUCTURE TIP PROJECT B-5160 =	0.009 MILE
TOTAL LENGTH TIP PROJECT B-5160 =	0.071 MILE

Prepared in the Office of:
DIVISION OF HIGHWAYS
1000 Birch Ridge Dr., Raleigh NC, 27610


2012 STANDARD SPECIFICATIONS	
RIGHT OF WAY DATE: DECEMBER 2015	MATTHEW W. JONES, PE PROJECT ENGINEER
LETTING DATE: DECEMBER 20, 2016	W. AL BLANTON, PE, PLS PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER


DocuSigned by:
Matthew S. Lauffer 9/20/2016
SIGNATURE: _____

ROADWAY DESIGN ENGINEER

DocuSigned by:
William A. Blanton 9/19/2016
SIGNATURE: _____



12-AUG-2016 13:56
S:\DDC\2015-02-B5160-Rowan\B5160_cddc_rsh.dgn
wablanton AT DIV9-294552

PROJECT REFERENCE NO.	SHEET NO.
B-5160	1-A
ROADWAY DESIGN ENGINEER	
	
DocuSigned by: William A. Blanton 09/19/2016	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

SHEET NUMBER	SHEET
1	TITLE SHEET
1A	INDEX OF SHEETS, GENERAL NOTES, AND STANDARD DRAWINGS
1B	CONVENTIONAL SYMBOLS
1C-1	SURVEY CONTROL SHEETS
1D-1	CENTERLINE COORDINATE LIST
2A-1	PAVEMENT SCHEDULE AND TYPICAL SECTIONS
3B-1	ROADWAY AND DRAINAGE SUMMARIES
4	PLAN AND PROFILE SHEET
TMP-1 THRU TMP-2	TRAFFIC MANAGEMENT PLANS
EC-1 THRU EC-6	EROSION CONTROL PLANS
UD-1 THRU UD-4	UTILITIES BY OTHERS PLANS
X-1 THRU X-5	CROSS-SECTIONS
C-1 THRU C-6	STRUCTURE PLANS - CULVERT

GENERAL NOTES: 2012 SPECIFICATIONS
EFFECTIVE: 01-17-2012
REVISED: 10-31-2014

GRADING AND SURFACING OR RESURFACING AND WIDENING:
THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. WHERE NO GRADE LINES ARE SHOWN, THE PROFILES SHOWN DENOTE THE TOP ELEVATION OF THE EXISTING PAVEMENT ALONG THE CENTER LINE OF SURVEY ON WHICH THE PROPOSED RESURFACING WILL BE PLACED. GRADE LINES MAY BE ADJUSTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:
CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD III.

SUPERELEVATION:
ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:
ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01

SIDE ROADS:
THE CONTRACTOR WILL BE REQUIRED TO DO ALL NECESSARY WORK TO PROVIDE SUITABLE CONNECTIONS WITH ALL ROADS, STREETS, AND DRIVES ENTERING THIS PROJECT. THIS WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PARTICULAR ITEMS INVOLVED.

GUARDRAIL:
THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

SUBSURFACE PLANS:
NO SUBSURFACE PLANS ARE AVAILABLE ON THIS PROJECT. THE CONTRACTOR SHOULD MAKE HIS OWN INVESTIGATION AS TO THE SUBSURFACE CONDITIONS.

UTILITIES:
UTILITY OWNERS ON THIS PROJECT ARE Duke Energy, AT&T
ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS.

RIGHT-OF-WAY MARKERS:
ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY CONTRACT.

2012 ROADWAY ENGLISH STANDARD DRAWINGS
EFF. 01-17-2012
REV. 02-29-2016

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch - N. C. Department of Transportation - Raleigh, N. C., Dated January, 2012 are applicable to this project and by reference hereby are considered a part of these plans:

STD. NO.	TITLE
DIVISION 2 - EARTHWORK	
200.03	Method of Clearing - Method III
225.02	Guide for Grading Subgrade - Secondary and Local
225.04	Method of Obtaining Superelevation - Two Lane Pavement
DIVISION 3 - PIPE CULVERTS	
300.01	Method of Pipe Installation
310.10	Driveway Pipe Construction
DIVISION 5 - SUBGRADE, BASES AND SHOULDERS	
560.01	Method of Shoulder Construction - High Side of Superelevated Curve - Method I
DIVISION 8 - INCIDENTALS	
806.01	Concrete Right-of-Way Marker
840.00	Concrete Base Pad for Drainage Structures
840.14	Concrete Drop Inlet - 12" thru 30" Pipe
840.15	Brick Drop Inlet - 12" thru 30" Pipe
840.17	Concrete Grated Drop Inlet Type "A" - 12" thru 72" Pipe
840.24	Frames and Narrow Slot Sag Grates
840.26	Brick Grated Drop Inlet Type "A" - 12" thru 72" Pipe
840.45	Precast Drainage Structure
840.66	Drainage Structure Steps
862.01	Guardrail Placement
862.02	Guardrail Installation
876.01	Rip Rap in Channels
876.02	Guide for Rip Rap at Pipe Outlets

STATE OF NORTH CAROLINA, DIVISION OF HIGHWAYS

CONVENTIONAL PLAN SHEET SYMBOLS

Note: Not to Scale *S.U.E. = *Subsurface Utility Engineering*

04/05/15

BOUNDARIES AND PROPERTY:

State Line	-----
County Line	-----
Township Line	-----
City Line	-----
Reservation Line	-----
Property Line	-----
Existing Iron Pin	○ EIP
Property Corner	----->
Property Monument	EDM
Parcel/Sequence Number	(123)
Existing Fence Line	-x-x-x-
Proposed Woven Wire Fence	○
Proposed Chain Link Fence	□
Proposed Barbed Wire Fence	◇
Existing Wetland Boundary	----- WLB
Proposed Wetland Boundary	----- WLB
Existing Endangered Animal Boundary	----- EAB
Existing Endangered Plant Boundary	----- EPB
Existing Historic Property Boundary	----- HPB
Known Contamination Area: Soil	☠
Potential Contamination Area: Soil	☠
Known Contamination Area: Water	☠
Potential Contamination Area: Water	☠
Contaminated Site: Known or Potential	☠ ?

BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	○
Sign	○ S
Well	○ W
Small Mine	⌵
Foundation	▭
Area Outline	▭
Cemetery	⊕
Building	▭
School	▭
Church	⊕
Dam	▭

HYDROLOGY:

Stream or Body of Water	-----
Hydro, Pool or Reservoir	▭
Jurisdictional Stream	----- JS
Buffer Zone 1	----- BZ 1
Buffer Zone 2	----- BZ 2
Flow Arrow	←
Disappearing Stream	----->
Spring	○
Wetland	-----
Proposed Lateral, Tail, Head Ditch	----- FLOW
False Sump	▽

RAILROADS:

Standard Gauge	-----
RR Signal Milepost	○ MILEPOST 35
Switch	SWITCH
RR Abandoned	-----
RR Dismantled	-----

RIGHT OF WAY:

Baseline Control Point	◆
Existing Right of Way Marker	△
Existing Right of Way Line	-----
Proposed Right of Way Line	----- R/W
Proposed Right of Way Line with Iron Pin and Cap Marker	----- R/W ▲
Proposed Right of Way Line with Concrete or Granite R/W Marker	----- R/W ▲
Proposed Control of Access Line with Concrete CA Marker	----- C/A
Existing Control of Access	----- C/A
Proposed Control of Access	----- C/A
Existing Easement Line	----- E
Proposed Temporary Construction Easement	----- E
Proposed Temporary Drainage Easement	----- TDE
Proposed Permanent Drainage Easement	----- PDE
Proposed Permanent Drainage / Utility Easement	----- DUE
Proposed Permanent Utility Easement	----- PUE
Proposed Temporary Utility Easement	----- TUE
Proposed Aerial Utility Easement	----- AUE
Proposed Permanent Easement with Iron Pin and Cap Marker	◆

ROADS AND RELATED FEATURES:

Existing Edge of Pavement	-----
Existing Curb	-----
Proposed Slope Stakes Cut	----- C
Proposed Slope Stakes Fill	----- F
Proposed Curb Ramp	----- CR
Existing Metal Guardrail	-----
Proposed Guardrail	-----
Existing Cable Guiderail	-----
Proposed Cable Guiderail	-----
Equality Symbol	⊕
Pavement Removal	▨

VEGETATION:

Single Tree	☼
Single Shrub	☼
Hedge	-----
Woods Line	-----

Orchard	☼ ☼ ☼ ☼
Vineyard	▭ Vineyard

EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	----- CONC
Bridge Wing Wall, Head Wall and End Wall	----- CONC WW
MINOR:	
Head and End Wall	----- CONC HW
Pipe Culvert	-----
Footbridge	-----
Drainage Box: Catch Basin, DI or JB	----- CB
Paved Ditch Gutter	-----
Storm Sewer Manhole	----- S
Storm Sewer	----- S

UTILITIES:

POWER:	
Existing Power Pole	●
Proposed Power Pole	○
Existing Joint Use Pole	●
Proposed Joint Use Pole	○
Power Manhole	⊕
Power Line Tower	⊠
Power Transformer	⊠
U/G Power Cable Hand Hole	●
H-Frame Pole	●
U/G Power Line LOS B (S.U.E.*)	----- P
U/G Power Line LOS C (S.U.E.*)	----- P
U/G Power Line LOS D (S.U.E.*)	----- P

TELEPHONE:

Existing Telephone Pole	●
Proposed Telephone Pole	○
Telephone Manhole	⊕
Telephone Pedestal	⊠
Telephone Cell Tower	⊠
U/G Telephone Cable Hand Hole	●
U/G Telephone Cable LOS B (S.U.E.*)	----- T
U/G Telephone Cable LOS C (S.U.E.*)	----- T
U/G Telephone Cable LOS D (S.U.E.*)	----- T
U/G Telephone Conduit LOS B (S.U.E.*)	----- TC
U/G Telephone Conduit LOS C (S.U.E.*)	----- TC
U/G Telephone Conduit LOS D (S.U.E.*)	----- TC
U/G Fiber Optics Cable LOS B (S.U.E.*)	----- T FO
U/G Fiber Optics Cable LOS C (S.U.E.*)	----- T FO
U/G Fiber Optics Cable LOS D (S.U.E.*)	----- T FO

WATER:

Water Manhole	⊕
Water Meter	○
Water Valve	⊗
Water Hydrant	⊕
U/G Water Line LOS B (S.U.E.*)	----- W
U/G Water Line LOS C (S.U.E.*)	----- W
U/G Water Line LOS D (S.U.E.*)	----- W
Above Ground Water Line	----- A/G Water

TV:

TV Pedestal	⊠
TV Tower	⊗
U/G TV Cable Hand Hole	●
U/G TV Cable LOS B (S.U.E.*)	----- TV
U/G TV Cable LOS C (S.U.E.*)	----- TV
U/G TV Cable LOS D (S.U.E.*)	----- TV
U/G Fiber Optic Cable LOS B (S.U.E.*)	----- TV FO
U/G Fiber Optic Cable LOS C (S.U.E.*)	----- TV FO
U/G Fiber Optic Cable LOS D (S.U.E.*)	----- TV FO

GAS:

Gas Valve	◇
Gas Meter	⊕
U/G Gas Line LOS B (S.U.E.*)	----- G
U/G Gas Line LOS C (S.U.E.*)	----- G
U/G Gas Line LOS D (S.U.E.*)	----- G
Above Ground Gas Line	----- A/G Gas

SANITARY SEWER:


Sanitary Sewer Manhole	⊕
Sanitary Sewer Cleanout	⊕
U/G Sanitary Sewer Line	----- SS
Above Ground Sanitary Sewer	----- A/G Sanitary Sewer
SS Forced Main Line LOS B (S.U.E.*)	----- FSS
SS Forced Main Line LOS C (S.U.E.*)	----- FSS
SS Forced Main Line LOS D (S.U.E.*)	----- FSS

MISCELLANEOUS:


Utility Pole	●
Utility Pole with Base	⊠
Utility Located Object	○
Utility Traffic Signal Box	⊠
Utility Unknown U/G Line LOS B (S.U.E.*)	----- TUL
U/G Tank; Water, Gas, Oil	▭
Underground Storage Tank, Approx. Loc.	UST
A/G Tank; Water, Gas, Oil	▭
Geoenvironmental Boring	⊕
U/G Test Hole LOS A (S.U.E.*)	⊕
Abandoned According to Utility Records	AATUR
End of Information	E.O.I.

SURVEY CONTROL SHEET B-5160

6/2/99



◆ BL-3
N=749189.696
E=1513214.304
ELEV=691.59'



◆ BL-6
N=750350.520
E=1513491.501
ELEV=686.54'

DATUM DESCRIPTION

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "B5160-1" WITH NAD 83/NA 2011 STATE PLANE GRID COORDINATES OF NORTHING: 748345.169(ft) EASTING: 1512486.853(ft) ELEVATION: 709.67(ft)

THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.99988857

THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "B5160-1" TO -L- STATION 10+00.00 IS
N 35°38'21.6" E 1457.24

ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
VERTICAL DATUM USED IS NAVD 88

BL	POINT	DESC.	NORTH	EAST	ELEVATION	L STATION	OFFSET
1	B5160-1		748345.1690	1512486.8530	709.67	OUTSIDE PROJECT LIMITS	
2	B5160-2		748889.1260	1512945.2260	700.96	OUTSIDE PROJECT LIMITS	
3	BL-3		749189.6960	1513214.3040	691.59	OUTSIDE PROJECT LIMITS	
4	BL-4		749748.4480	1513420.2480	673.36	12+34.37	11.38 RT
5	BL-5		749966.8340	1513477.2910	678.49	OUTSIDE PROJECT LIMITS	
6	BL-6		750350.5200	1513491.5010	686.54	OUTSIDE PROJECT LIMITS	

BENCHMARK (NAVD88)
.....
BM1 ELEVATION = 670.63'
N 749782 E 1513380
L STATION 12+54 38' LEFT
RR SPIKE IN BASE OF 12" WALNUT
.....

NOTES:

- ◆ INDICATES CONTROL MONUMENTS USED OR SET FOR HORIZONTAL PROJECT CONTROL BY THE NCDOT DIVISION 9 DDC UNIT.
- PROJECT CONTROL ESTABLISHED USING GLOBAL POSITIONING SYSTEM.

NOTE: DRAWING NOT TO SCALE

04-MAY-2016 08:22:00 B:\proj\B05160.dwg -1C-1.dgn
S:\DDC\2015-05-15\09-28\B05160.dwg

SURVEY CONTROL SHEET B-5160

DESIGN ALIGNMENT

L

TYPE	STATION	NORTH	EAST
POT	10+00.00	749529.4670	1513335.9577
PC	12+94.56	749809.1702	1513428.3187
PCC	15+22.00	750032.1342	1513469.5240
PT	16+70.11	750180.1735	1513473.8065

ROW MARKER CONCRETE OR GRANITE

ALIGN	STATION	OFFSET	NORTH	EAST
L	10+90.00	22.50	749607.8731	1513385.5432
L	11+50.00	60.00	749653.0888	1513439.9656
L	11+90.00	-60.00	749728.6986	1513338.5596
L	11+90.00	-22.50	749716.9402	1513374.1684
L	12+35.00	22.50	749745.5606	1513431.0091
L	12+35.00	60.00	749733.8022	1513466.6180
L	12+44.00	-60.00	749779.9753	1513355.4917
L	13+50.00	-22.50	749867.9739	1513422.1562

ROW MARKER PERMANENT EASEMENT

ALIGN	STATION	OFFSET	NORTH	EAST
L	10+50.00	-22.50	749584.0005	1513330.2703
L	11+40.00	-43.00	749675.8896	1513339.0244
L	11+90.00	-43.00	749723.3681	1513354.7023
L	12+35.00	40.00	749740.0734	1513447.6266
L	13+40.00	34.00	749843.7977	1513474.2040
L	15+15.00	33.00	750023.3312	1513502.1191
L	15+15.00	22.50	750023.9077	1513491.6350


DATUM DESCRIPTION

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "B5160-1" WITH NAD 83/NA 2011 STATE PLANE GRID COORDINATES OF NORTHING: 748345.169(ft) EASTING: 1512486.853(ft) ELEVATION: 709.67(ft)

THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.99988857


THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "B5160-1" TO -L- STATION 10+00.00 IS
N 35°38'21.6" E 1457.24

ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
VERTICAL DATUM USED IS NAVD 88




TYPICAL SECTION #1

USE TYPICAL SECTION NO. 1 AS FOLLOWS:
 FROM -L- 10+50 TO -L- STA. 12+01
 FROM -L- 12+28 TO -L- STA. 14+25




TYPICAL SECTION #2

USE TYPICAL SECTION No. 2 AS FOLLOWS:
 FROM -L- STA. 12+01 (BEGIN CULVERT)
 TO -L- STA. 12+28 (END CULVERT)



Detail for Incidental Milling







Detail Showing Method of Wedging

PAVEMENT SCHEDULE	
C1	PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD.
C2	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
D1	PROP. APPROX. 2.5" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I9.0B, AT AN AVERAGE RATE OF 285 LBS. PER SQ. YD.
D2	PROP. VAR. DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACE IN LAYERS NOT LESS THAN 2.5" IN DEPTH OR GREATER THAN 4" IN DEPTH.
E1	PROP. APPROX. 4" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
E2	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5.5" IN DEPTH.
T	EARTH MATERIAL
U	EXISTING PAVEMENT
W	VARIABLE DEPTH ASPHALT PAVEMENT (SEE WEDGING DETAIL)

NOTE: PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.

6/2/09

15-AUG-2016 12:46 PM C:\Users\Rowan\B5160-ddc-tp.dgn



8/17/99
 REVISIONS
 04 MAY 2016 09:03:51 160-Rover\B5160-ddc-psh4.dwg
 3:48:50 (CST) WAF 8:53:38

PLAN FOR PROPOSED TRAFFIC CONTROL, MARKING & DELINEATION ROWAN COUNTY

ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS SHOWN IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2012 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
1101.03	TEMPORARY ROAD CLOSURES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.01	STATIONARY WORK ZONE SIGNS
1145.01	BARRICADES
1205.01	PAVEMENT MARKINGS - LINE TYPES AND OFFSETS
1205.02	PAVEMENT MARKINGS - TWO-LANE AND MULTI-LANE ROADWAYS
1261.01	GUARDRAIL AND BARRIER DELINEATORS - INSTALLATION SPACING
1261.02	GUARDRAIL AND BARRIER DELINEATORS - TYPES AND MOUNTING

INDEX OF SHEETS

SHEET NO.	TITLE
TCP-1	LIST OF APPLICABLE ROADWAY STANDARD DRAWINGS, LEGEND, AND INDEX OF SHEETS
TMP-1A	GENERAL NOTES, PHASING AND DETOUR SIGNING.

LEGEND

GENERAL

- DIRECTION OF TRAFFIC FLOW
- DIRECTION OF PEDESTRIAN TRAFFIC FLOW
- EXIST. PVMT.
- NORTH ARROW
- PROPOSED PVMT.
- TEMP. SHORING (LOCATION PURPOSES ONLY)

WORK AREA

REMOVAL

USER DEFINED (IF NEEDED)

USER DEFINED (IF NEEDED)

SIGNALS

- EXISTING
- PROPOSED
- TEMPORARY

PAVEMENT MARKINGS

- EXISTING LINES
- TEMPORARY LINES

TRAFFIC CONTROL DEVICES

- BARRICADE (TYPE III)
- CONE
- DRUM
- SKINNY DRUM
- TUBULAR MARKER
- TEMPORARY CRASH CUSHION
- FLASHING ARROW BOARD
- FLAGGER
- LAW ENFORCEMENT
- TRUCK MOUNTED ATTENUATOR (TMA)
- CHANGEABLE MESSAGE SIGN

TEMPORARY SIGNING

- PORTABLE SIGN
- STATIONARY SIGN
- STATIONARY OR PORTABLE SIGN


PAVEMENT MARKERS


- CRYSTAL/CRYSTAL
- CRYSTAL/RED
- YELLOW/YELLOW

PAVEMENT MARKING SYMBOLS

- PAVEMENT MARKING SYMBOLS

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

	<p>APPROVED: <u>William A. Blanton</u> <small>CC637181FC4D</small></p> <p>DATE: <u>9/19/2016</u></p> <p style="text-align: center;">SEAL</p>
---	--



03-MAY-2016 11:14 \\DOT\DFSROOT\GROUPS-DIV9CC\DDC\2015-02-B5160-Rowan\WZTC\b5160_ddc_TMP.dgn wablanton AT DIV9-294552 09/08/16

TIP PROJECT: B-5160

PROJECT REFERENCE NO. B-5160	SHEET NO. TMP-2
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

GENERAL NOTES

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS, AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS OR RESULT IN DUPLICATE OR UNDESIRED OVERLAPPING OF DEVICES. MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING, OR REMOVAL OF DEVICES AS DIRECTED BY THE ENGINEER.

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT EXCEPT WHEN OTHERWISE NOTED IN THE PLAN OR DIRECTED BY THE ENGINEER.

LANE AND SHOULDER CLOSURE REQUIREMENTS:

- A) REMOVE LANE CLOSURE DEVICES FROM THE LANE WHEN WORK IS NOT BEING PERFORMED BEHIND THE LANE CLOSURE OR WHEN A LANE CLOSURE IS NO LONGER NEEDED OR AS DIRECTED BY THE ENGINEER.
- B) WHEN PERSONNEL AND/OR EQUIPMENT ARE WORKING WITHIN 15 FT OF AN OPEN TRAVEL LANE, CLOSE THE NEAREST OPEN SHOULDER USING ROADWAY STANDARD DRAWING NO. 1101.04 UNLESS THE WORK AREA IS PROTECTED BY BARRIER OR GUARDRAIL OR A LANE CLOSURE IS INSTALLED.

TRAFFIC PATTERN ALTERATIONS

- C) NOTIFY THE ENGINEER TWENTY ONE (21) CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION

SIGNING

- D) INSTALL ADVANCE WORK ZONE WARNING SIGNS WHEN WORK IS WITHIN 40 FT FROM THE EDGE OF TRAVEL LANE AND NO MORE THAN THREE (3) DAYS PRIOR TO THE BEGINNING OF CONSTRUCTION.
- E) PROVIDE SIGNING AND DEVICES REQUIRED TO CLOSE THE ROAD ACCORDING TO THE ROADWAY STANDARD DRAWINGS AND TRAFFIC CONTROL PLANS.

PROVIDE SIGNING REQUIRED FOR THE OFF-SITE DETOUR ROUTE AS SHOWN ON THIS SHEET.
- F) COVER OR REMOVE ALL SIGNS AND DEVICES REQUIRED TO CLOSE THE ROAD WHEN ROAD CLOSURE IS NOT IN OPERATION.

COVER OR REMOVE ALL SIGNS REQUIRED FOR THE OFF-SITE DETOUR WHEN THE DETOUR IS NOT IN OPERATION.
- G) ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY TRAFFIC PATTERN.

TRAFFIC CONTROL DEVICES

- I) PLACE TYP III BARRICADES, WITH "ROAD CLOSED" SIGN R11-2 ATTACHED, OF SUFFICIENT LENGTH TO CLOSE ENTIRE ROADWAY.

PAVEMENT MARKINGS AND MARKERS

- J) INSTALL PAVEMENT MARKINGS ON THE FINAL SURFACE AS FOLLOWS:

ROAD NAME	MARKING
SR 1986 (MT. VERNON RD.)	PAINT
- K) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.
- L) REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS.
- M) PASSING ZONE WILL BE DETERMINED IN THE FIELD AND MUST BE APPROVED BY THE ENGINEER.

PHASING

PHASE I



PRIOR TO ANY CONSTRUCTION OPERATIONS, PLACE AND COVER OFF-SITE DETOUR SIGNING AS SHOWN ON TCP-2 AND IN ACCORDANCE WITH RSD 1102.03 (SHEET 1 OF 9).

PHASE II


USING OFF-SITE DETOUR, UNCOVER DETOUR SIGNS, CLOSE -L- (SR 1986/MT. VERNON RD.) TO TRAFFIC, EXCAVATE AND CONSTRUCT NEW CULVERT AND ROADWAY UP TO AND INCLUDING FINAL LAYER OF SURFACE COURSE.

PHASE III

UPON COMPLETION OF CULVERT AND ROADWAY, PLACE FINAL PAVEMENT MARKING IN ACCORDANCE WITH RSD 1205.01. REMOVE BARRICADES, DETOUR SIGNS, AND OPEN -L- (SR 1986) TO TRAFFIC.



DETOUR ROUTE ●—●—●—● DETOUR LENGTH 6.1 MILES



REVISIONS



8/17/99
R:\AUG-2006\GROUPS-D\900-DDC\2015-02-B5160-Bowman\ZTC\B5160.dwg, TMP.dwg

TIP PROJECT: B-5160

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS
**PLAN FOR PROPOSED
HIGHWAY EROSION CONTROL**

ROWAN COUNTY

**LOCATION: REPLACE EXISTING BRIDGE NO. 50 OVER NAILS BRANCH
ON MT. VERNON RD. (SR 1986) WITH BOX CULVERT**
**TYPE OF WORK: GRADING, DRAINAGE, WIDENING, BOX CULVERT,
AND PAVEMENT MARKINGS**




STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5160	EC-1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	

EROSION AND SEDIMENT CONTROL MEASURES


Std. #	Description	Symbol
1630.03	Temporary Silt Ditch	TD
1630.05	Temporary Diversion	TD
1605.01	Temporary Silt Fence	III III III
1606.01	Special Sediment Control Fence	△△△△△△△△
1622.01	Temporary Berms and Slope Drains	— T —
1630.02	Silt Basin Type B	▨
1633.01	Temporary Rock Silt Check Type-A	⊗
	Temporary Rock Silt Check Type-A with Matting and Polyacrylamide (PAM)	⊗
1633.02	Temporary Rock Silt Check Type-B	▶
	Wattle / Coir Fiber Wattle	⌒
	Wattle / Coir Fiber Wattle with Polyacrylamide (PAM)	⌒
1634.01	Temporary Rock Sediment Dam Type-A	⊞
1634.02	Temporary Rock Sediment Dam Type-B	⊞
1635.01	Rock Pipe Inlet Sediment Trap Type-A	⊞
1635.02	Rock Pipe Inlet Sediment Trap Type-B	⊞
1630.04	Stilling Basin	⊞
1630.06	Special Stilling Basin	⊞
	Rock Inlet Sediment Trap:	
1632.01	Type A	A ⊞
1632.02	Type B	B ⊞
1632.03	Type C	C ⊞
	Skimmer Basin	⊞
	Tiered Skimmer Basin	⊞
	Infiltration Basin	⊞

THIS PROJECT CONTAINS
EROSION CONTROL PLANS
FOR CLEARING AND
GRUBBING PHASE OF
CONSTRUCTION.


GRAPHIC SCALE



PLANS



PROFILE (HORIZONTAL)



PROFILE (VERTICAL)

ROADSIDE ENVIRONMENTAL UNIT
DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

THESE EROSION AND SEDIMENT CONTROL PLANS COMPLY
WITH THE REGULATIONS SET FORTH BY THE
NCG-010000 GENERAL CONSTRUCTION PERMIT EFFECTIVE AUGUST 3, 2011
ISSUED BY THE NORTH CAROLINA DEPARTMENT OF ENVIRONMENT AND
NATURAL RESOURCES DIVISION OF WATER QUALITY.

Prepared in the Office of:
ROADSIDE ENVIRONMENTAL UNIT
1 South Wilmington St.
Raleigh, NC 27611
2012 STANDARD SPECIFICATIONS

Designed by:
Natalie Chan, P.E. 491
NAME LEVEL III CERTIFICATION NO.




Roadway Standard Drawings

The following roadway english standards as appear in "Roadway Standard Drawings"- Roadway Design Unit - N. C. Department of Transportation - Raleigh, N. C., dated January 2012 and the latest revision thereto are applicable to this project and by reference hereby are considered a part of these plans.



1604.01 Railroad Erosion Control Detail	1632.01 Rock Inlet Sediment Trap Type A
1605.01 Temporary Silt Fence	1632.02 Rock Inlet Sediment Trap Type B
1606.01 Special Sediment Control Fence	1632.03 Rock Inlet Sediment Trap Type C
1607.01 Gravel Construction Entrance	1633.01 Temporary Rock Silt Check Type A
1622.01 Temporary Berms and Slope Drains	1633.02 Temporary Rock Silt Check Type B
1630.01 Riser Basin	1634.01 Temporary Rock Sediment Dam Type A
1630.02 Silt Basin Type B	1634.02 Temporary Rock Sediment Dam Type B
1630.03 Temporary Silt Ditch	1635.01 Rock Pipe Inlet Sediment Trap Type A
1630.04 Stilling Basin	1635.02 Rock Pipe Inlet Sediment Trap Type B
1630.05 Temporary Diversion	1640.01 Coir Fiber Baffle
1630.06 Special Stilling Basin	1645.01 Temporary Stream Crossing
1631.01 Matting Installation	

PROJECT REFERENCE NO. B-5160	SHEET NO. EC-2
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

COIR FIBER WATTLE WITH POLYACRYLAMIDE (PAM) DETAIL



- NOTES:
- USE MINIMUM 12 IN. DIAMETER COIR FIBER (COCONUT FIBER) WATTLE.
 - USE 2 FT. WOODEN STAKES WITH A 2 IN. BY 2 IN. NOMINAL CROSS SECTION.
 - ONLY INSTALL WATTLE(S) TO A HEIGHT IN DITCH SO FLOW WILL NOT WASH AROUND WATTLE AND SCOUR DITCH SLOPES AND AS DIRECTED.
 - INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO BOTTOM OF DITCH.
 - PROVIDE STAPLES MADE OF 0.125 IN. DIAMETER STEEL WIRE FORMED INTO A U SHAPE NOT LESS THAN 12" IN LENGTH.
 - INSTALL STAPLES APPROXIMATELY EVERY 1 LINEAR FOOT ON BOTH SIDES OF WATTLE AND AT EACH END TO SECURE IT TO THE SOIL.
 - INSTALL MATTING IN ACCORDANCE WITH SECTION 1631 OF THE STANDARD SPECIFICATIONS.
 - PRIOR TO POLYACRYLAMIDE (PAM) APPLICATION, OBTAIN A SOIL SAMPLE FROM PROJECT LOCATION, AND FROM OFFSITE MATERIAL, AND ANALYZE FOR APPROPRIATE PAM FLOCCULANT TO BE APPLIED TO EACH WATTLE.
 - INITIALLY APPLY 2 OUNCES OF ANIONIC OR NEUTRALLY CHARGED PAM OVER WATTLE WHERE WATER WILL FLOW AND 1 OUNCE OF PAM ON MATTING ON EACH SIDE OF WATTLE. REAPPLY PAM AFTER EVERY RAINFALL EVENT THAT IS EQUAL TO OR EXCEEDS 0.50 IN.










DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

PROJECT REFERENCE NO. <i>B-5160</i>	SHEET NO. <i>EC-3A</i>
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

SOIL STABILIZATION TIMEFRAMES

<i>SITE DESCRIPTION</i>	<i>STABILIZATION TIME</i>	<i>TIMEFRAME EXCEPTIONS</i>
PERIMETER DIKES, SWALES, DITCHES AND SLOPES	7 DAYS	NONE
HIGH QUALITY WATER (HQW) ZONES	7 DAYS	NONE
SLOPES STEEPER THAN 3:1	7 DAYS	IF SLOPES ARE 10' OR LESS IN LENGTH AND ARE NOT STEEPER THAN 2:1, 14 DAYS ARE ALLOWED.
SLOPES 3:1 OR FLATTER	14 DAYS	7 DAYS FOR SLOPES GREATER THAN 50' IN LENGTH.
ALL OTHER AREAS WITH SLOPES FLATTER THAN 4:1	14 DAYS	NONE, EXCEPT FOR PERIMETERS AND HQW ZONES.



8/17/99



NOTE:
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B AND TEMPORARY ROCK SILT CHECKS TYPE - A AT DRAINAGE OUTLETS.

CLEARING AND GRUBBING EROSION CONTROL FOR CONSTRUCTION SHEET 4

PROJECT REFERENCE NO.	SHEET NO.
B-5160	EC-4/CONST.4
R/W SHEET NO.	HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER	




19-JAN-2016 10:49
C:\Users\jvegan\OneDrive\Documents\B-5160 Div 9\B5160.ddc_pah4.dgn










PROJECT REFERENCE NO.	SHEET NO.
B-5160	EC-5/CONST.4
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

CULVERT CONSTRUCTION SEQUENCE STA. 12+25 -L-

1. INSTALL SPECIAL STILLING BASIN(S).
2. INSTALL UPSTREAM IMPERVIOUS DIKE AND 24" TEMPORARY PIPE ON 0.7% SLOPE TO CONVEY FLOW THROUGH THE WORK AREA.
3. INSTALL DOWNSTREAM IMPERVIOUS DIKE AND DEWATER WORK AREA.
4. INSTALL CULVERT(S) IN ACCORDANCE WITH THE PLANS.
5. REMOVE DOWNSTREAM IMPERVIOUS DIKE AND 24" TEMPORARY PIPE.
6. REMOVE UPSTREAM IMPERVIOUS DIKE AND SPECIAL STILLING BASIN(S).




PROJECT REFERENCE NO.	SHEET NO.
B-5160	EC-6/CONST.4
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER



8/17/99


19-JAN-2016 10:51
 C:\Users\jvegan\OneDrive\Documents\B-5160 Div 9\B5160.ddc_pah4.dgn

8/23/99




PROJ. REFERENCE NO.
B-5160


SHEET NO.
X-1



04-MAY-2016 09:35
S:\DDC\2015-02-F5160-Rowan\B5160-Rowan.ddc.sp1.L.dgn
\$\$\$\$\$USERNAME\$\$\$\$\$




8/23/99




PROJ. REFERENCE NO.
B-5160

SHEET NO.
X-3




04-MAY-2016 09:35
S:\DDC\2015-02-F5160-Rowan\B5160-ddc-ep1.L.dgn
\$\$\$\$\$USERNAME\$\$\$\$\$

8/23/99




PROJ. REFERENCE NO.
B-5160

SHEET NO.
X-4



04-MAY-2016 09:35
S:\DDC\2015-02-F5160-Rowan\B5160-ddc-ep1.L.dgn
\$\$\$\$\$USERNAME\$\$\$\$\$

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

685
680
675

685
680
675

682.36
16 + 50.00

-L-

TIP PROJECT: B-5160



CONTRACT: C

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS


ROWAN COUNTY

**LOCATION: REPLACE BRIDGE 50 OVER NAILS BRANCH ON
MT. VERNON RD. (SR 1986) WITH BOX CULVERT**

**TYPE OF WORK: GRADING, DRAINAGE, WIDENING, BOX CULVERT,
AND PAVEMENT MARKINGS**



CULVERT



DESIGN DATA
 ADT 2014 = 700
 ADT 2035 = XXXX
 K = XX %
 D = XX %
 *T = XX %
 V = 60 MPH
 (RURAL LOCAL)
 SUB-REGIONAL TIER
 * TTST XX% + DUAL XX%

PROJECT LENGTH
 LENGTH OF ROADWAY TIP PROJECT B-5160 = 0.071 MILE
 LENGTH OF STRUCTURE TIP PROJECT B-5160 = 0.008 MILE
 TOTAL LENGTH OF TIP PROJECT B-5160 = 0.079 MILE

Prepared in the Office of:
DIVISION OF HIGHWAYS
 STRUCTURE MANAGEMENT UNIT
 1000 Birch Ridge Dr., Raleigh NC, 27610

2012 STANDARD SPECIFICATIONS

LETTING DATE:
 DECEMBER 20, 2016


L. E. SUTTON, PE
 PROJECT ENGINEER

V. A. PATEL, PE
 PROJECT DESIGN ENGINEER

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5160		
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
42335.1.1	BRZ-1986(1)	PE	
42335.2.1	BRZ-1986(1)	RW, UTILITIES	
42335.3.1	BRZ-1986(1)	CONSTR.	

B.M. #1: R.R. SPIKE IN BASE OF 12" WALNUT TREE, 38' LEFT OF
STA. 12+54.00 -L-, EL. 670.63


F. A. PROJECT NO. BRZ-1986(1)



LOCATION SKETCH

ROADWAY DATA

GRADE POINT EL. @ STA. 12+13.00 -L-	= 673.76
BED ELEVATION @ STA. 12+13.00 -L-	= 661.36
ROADWAY SLOPES	= 2:1



PROFILE ALONG CULVERT

DRAWN BY : N.D. AIUTO DATE : 7/30/15
 CHECKED BY : J.K. BOWLES DATE : 8/5/15
 DESIGN ENGINEER OF RECORD : H.A. LOCKLEAR DATE : 8/5/15

NOTES

- ASSUMED LIVE LOAD-----HL-93 OR ALTERNATE LOADING.
- DESIGN FILL-----3.71 FT. (MAX. FILL), 3.11 FT. (MIN. FILL)
- FOR OTHER DESIGN DATA AND NOTES, SEE STANDARD NOTE SHEET.
- 3"Ø WEEP HOLES INDICATED TO BE IN ACCORDANCE WITH THE SPECIFICATIONS.
- CONCRETE IN CULVERT TO BE POURED IN THE FOLLOWING ORDER:
 1. WING FOOTINGS AND FLOOR SLAB INCLUDING 4" OF ALL VERTICAL WALLS.
 2. THE REMAINING PORTIONS OF THE WALLS AND WINGS FULL HEIGHT FOLLOWED BY ROOF SLAB AND HEADWALLS.
- THE RESIDENT ENGINEER SHALL CHECK THE LENGTH OF CULVERT BEFORE STAKING IT OUT TO MAKE CERTAIN THAT IT WILL PROPERLY TAKE CARE OF THE FILL.
- STEEL IN THE BOTTOM SLAB MAY BE SPLICED AT THE PERMITTED CONSTRUCTION JOINT AT THE CONTRACTOR'S OPTION. EXTRA WEIGHT OF STEEL DUE TO THE SPLICES SHALL BE PAID FOR BY THE CONTRACTOR.
- AT THE CONTRACTOR'S OPTION, HE MAY SPLICE THE VERTICAL REINFORCING STEEL IN THE INTERIOR FACE OF EXTERIOR WALL AND BOTH FACES OF INTERIOR WALLS ABOVE LOWER WALL CONSTRUCTION JOINT. THE SPLICE LENGTH SHALL BE AS PROVIDED IN THE SPLICE LENGTH CHART SHOWN ON THE PLANS. EXTRA WEIGHT OF STEEL DUE TO THE SPLICES SHALL BE PAID FOR BY THE CONTRACTOR.
- AT THE CONTRACTOR'S OPTION HE MAY SUBMIT, TO THE ENGINEER FOR APPROVAL, DESIGN AND DETAIL DRAWINGS FOR A PRECAST REINFORCED CONCRETE BOX CULVERT IN LIEU OF THE CAST-IN-PLACE CULVERT SHOWN ON THE PLANS. THE DESIGN SHALL PROVIDE THE SAME SIZE AND NUMBER OF BARRELS AS USED ON THE CAST-IN-PLACE DESIGN. FOR OPTIONAL PRECAST REINFORCED CONCRETE BOX CULVERT, SEE SPECIAL PROVISIONS.
- THE EXISTING STRUCTURE CONSISTS OF 1 SPAN @ 30'-6" WITH 19.1' CLEAR ROADWAY WIDTH AND TIMBER DECK ON STEEL I-BEAMS ON END BENTS OF TIMBER CAPS, POST AND SILLS, AND TIMBER BULKHEADS LOCATED AT THE PROPOSED STRUCTURE SHALL BE REMOVED. THE EXISTING BRIDGE IS PRESENTLY POSTED FOR LOAD LIMIT, SHOULD THE STRUCTURAL INTEGRITY OF THE BRIDGE DETERIORATE DURING CONSTRUCTION OF THE PROPOSED CULVERT, A LOAD LIMIT MAY BE POSTED AND MAY BE REDUCED AS FOUND NECESSARY DURING THE LIFE OF THE PROJECT.

HYDRAULIC DATA

DESIGN DISCHARGE	= 1,200 C.F.S.
FREQUENCY OF DESIGN FLOOD	= 25 YRS.
DESIGN HIGH WATER ELEVATION	= 673.0
DRAINAGE AREA	= 3.73 SQ. MI.
BASE DISCHARGE (Q100)	= 1,738 C.F.S.
BASE HIGH WATER ELEVATION	= 674.4

OVERTOPPING FLOOD DATA

OVERTOPPING DISCHARGE	= 1,450 C.F.S.
FREQUENCY OF OVERTOPPING FLOOD	= 50 +/- YRS.
OVERTOPPING FLOOD ELEVATION	= 673.7

TOTAL STRUCTURE QUANTITIES

REMOVAL OF EXISTING STRUCTURE	LUMP SUM
CULVERT EXCAVATION	LUMP SUM
FOUNDATION CONDITIONING MAT'L	130 TONS
CLASS A CONCRETE	
BARREL @ 3.268 CY/FT	150.3 C.Y.
WING, ETC.	43.3 C.Y.
TOTAL	193.6 C.Y.
REINFORCING STEEL	
BARREL	21,951 LBS.
WINGS, ETC.	2,148 LBS.
TOTAL	24,099 LBS.
PLACEMENT OF NATURAL STREAM BED MATERIAL	LUMP SUM
ASBESTOS ASSESSMENT	LUMP SUM

INASMUCH AS THE PAINT SYSTEM ON THE EXISTING STRUCTURAL STEEL CONTAINS LEAD, THE CONTRACTOR'S ATTENTION IS DIRECTED TO ARTICLE 107-1 OF THE STANDARD SPECIFICATIONS. ANY COSTS RESULTING FROM COMPLIANCE WITH APPLICABLE STATE OR FEDERAL REGULATIONS PERTAINING TO HANDLING OF MATERIALS CONTAINING LEAD BASED PAINT SHALL BE INCLUDED IN THE BID PRICE FOR "REMOVAL OF EXISTING STRUCTURE AT STATION 12+13.00 -L-".

REMOVAL OF THE EXISTING BRIDGE SHALL BE PERFORMED IN A MANNER THAT PREVENTS DEBRIS FROM FALLING INTO THE WATER. THE CONTRACTOR SHALL SUBMIT DEMOLITION PLANS FOR REVIEW AND REMOVE THE BRIDGE IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS.

THE SUBSTRUCTURE OF THE EXISTING BRIDGE INDICATED ON THE PLANS IS FROM THE BEST INFORMATION AVAILABLE. SINCE THIS INFORMATION IS SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR, THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT OF TRANSPORTATION FOR ANY DELAYS OR ADDITIONAL COST INCURRED BASED ON DIFFERENCES BETWEEN THE EXISTING BRIDGE SUBSTRUCTURE INDICATED ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

THE CONTRACTOR SHALL PROVIDE INDEPENDENT ASSURANCE SAMPLES OF REINFORCING STEEL AS FOLLOWS: FOR PROJECTS REQUIRING UP TO 400 TONS OF REINFORCING STEEL, ONE 30 INCH SAMPLE OF EACH SIZE BAR USED, AND FOR PROJECTS REQUIRING OVER 400 TONS OF REINFORCING STEEL, TWO 30 INCH SAMPLES OF EACH SIZE BAR USED. THE BARS FROM WHICH THE SAMPLES ARE TAKEN MUST THEN BE SPLICED WITH REPLACEMENT BARS OF THE SIZE AND LENGTH OF THE SAMPLE, PLUS A MINIMUM LAP SPICE OF THIRTY BAR DIAMETERS. PAYMENT FOR THE SAMPLES OF REINFORCING STEEL SHALL BE CONSIDERED INCIDENTAL TO VARIOUS PAY ITEMS.

FOR CULVERT DIVERSION DETAILS & PAY ITEM, SEE EROSION CONTROL PLAN.

A 3 FOOT STRIP OF FILTER FABRIC SHALL BE ATTACHED TO THE FILL FACE OF THE WING COVERING THE ENTIRE LENGTH OF THE EXPANSION JOINT.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

NATURAL STREAM BED MATERIAL SHALL BE USED TO BACKFILL THE CULVERT BETWEEN THE SILLS. FOR PLACEMENT OF NATURAL STREAM BED MATERIAL, SEE SPECIAL PROVISIONS.

FOR ASBESTOS ASSESSMENT FOR BRIDGE DEMOLITION AND RENOVATION ACTIVITIES, SEE SPECIAL PROVISIONS.

I HEREBY CERTIFY THESE PLANS ARE THE AS-BUILT PLANS


PROJECT NO. B-5160
ROWAN COUNTY
 STATION: 12+13.00 -L-

SHEET 1 OF 6 REPLACES BRIDGE NO. 50

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

TRIPLE 11 FT. X 9 FT.
 CONCRETE BOX CULVERT

120° SKEW



REVISIONS						SHEET NO. C-1
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			TOTAL SHEETS 6
2			4			

LOAD AND RESISTANCE FACTOR RATING (LRFR) SUMMARY FOR REINFORCED CONCRETE BOX CULVERT

LEVEL	VEHICLE	WEIGHT (W) (TONS)	CONTROLLING LOAD RATING #	MINIMUM RATING FACTORS (RF)	TONS = W x RF	STRENGTH I LIMIT STATE								COMMENT NUMBER		
						LIVE-LOAD FACTORS (LL)	MOMENT				SHEAR					
							RATING FACTOR	BOX NO.	ELEMENT TYPE	DISTANCE FROM LEFT END OF ELEMENT (ft)	RATING FACTOR	BOX NO.	ELEMENT TYPE		DISTANCE FROM LEFT END OF ELEMENT (ft)	
DESIGN LOAD RATING	HL-93 (INVENTORY)	N/A	①	1.00	--	1.75	1.00	1	TOP SLAB	4.96	1.20	1	TOP SLAB	10.61	4	
	HL-93 (OPERATING)	N/A		1.30	--	1.35	1.30	1	TOP SLAB	4.96	1.51	1	TOP SLAB	10.61	3	
	HS-20 (INVENTORY)	36.000	②	1.14	41.12	1.75	1.14	1	TOP SLAB	4.96	1.22	1	BOTTOM SLAB	10.76	2	
	HS-20 (OPERATING)	36.000		1.48	53.30	1.35	1.48	1	TOP SLAB	4.96	1.58	1	BOTTOM SLAB	10.76	2	
LEGAL LOAD RATING	SINGLE VEHICLE (SV)	SNSH	13.500		2.08	28.03	1.40	2.08	1	TOP SLAB	4.96	2.60	1	TOP SLAB	10.61	1
		SNGARBS2	20.000		1.94	38.89	1.40	1.94	1	TOP SLAB	4.96	2.43	1	TOP SLAB	10.61	1
		SNAGRIS2	22.000		2.08	45.67	1.40	2.08	1	TOP SLAB	4.96	2.50	1	BOTTOM SLAB	10.76	2
		SNCOTTS3	27.250		1.26	34.46	1.40	1.26	1	TOP SLAB	4.96	1.46	1	TOP SLAB	10.61	1
		SNAGGRS4	34.925		1.55	53.98	1.40	1.55	1	TOP SLAB	5.25	1.58	1	BOTTOM SLAB	10.76	2
		SNS5A	35.550		1.46	52.00	1.40	1.46	1	TOP SLAB	4.96	1.56	1	BOTTOM SLAB	10.76	4
		SNS6A	39.950		1.39	55.64	1.40	1.46	1	TOP SLAB	4.96	1.39	1	BOTTOM SLAB	10.76	4
	TRUCK TRACTOR SEMI-TRAILER (TTST)	SNS7B	42.000		1.32	55.42	1.40	1.51	1	TOP SLAB	4.96	1.32	1	BOTTOM SLAB	10.76	4
		TNAGRIT3	33.000		1.68	55.30	1.40	2.08	1	TOP SLAB	4.96	1.68	1	BOTTOM SLAB	10.76	2
		TNT4A	33.075		1.50	49.66	1.40	1.50	1	TOP SLAB	4.96	1.69	1	BOTTOM SLAB	10.76	4
		TNT6A	41.600		1.33	55.41	1.40	1.53	1	TOP SLAB	4.96	1.33	1	BOTTOM SLAB	10.76	2
		TNT7A	42.000		1.40	58.79	1.40	1.56	1	TOP SLAB	4.96	1.40	1	BOTTOM SLAB	10.76	2
		TNT7B	42.000		1.40	58.90	1.40	1.48	1	TOP SLAB	5.25	1.40	1	BOTTOM SLAB	10.76	4
		TNAGRIT4	43.000		1.30	55.72	1.40	1.43	1	TOP SLAB	4.96	1.30	1	BOTTOM SLAB	10.76	4
TNAGT5A	45.000	③	1.24	55.66	1.40	1.47	1	TOP SLAB	4.96	1.24	1	BOTTOM SLAB	10.76	4		
TNAGT5B	45.000		1.24	55.92	1.40	1.50	1	TOP SLAB	4.96	1.24	1	BOTTOM SLAB	10.76	4		

LOAD FACTORS

DESIGN LOAD RATING FACTORS

LOAD TYPE	MAX FACTOR	MIN FACTOR
DC	1.25	0.90
DW	1.50	0.65
EV	1.30	0.90
EH	1.35	0.90
ES	1.35	0.90
LS	1.75	-
WA	1.00	-


NOTES

RATING FACTORS ARE BASED ON THE STRENGTH I LIMIT STATE.

COMMENTS

1. BOTH MOMENT AND SHEAR RATING FACTORS ARE CONTROLLED BY MINIMUM FILL.
2. MOMENT RATING FACTOR IS CONTROLLED BY MINIMUM FILL, SHEAR RATING FACTOR IS CONTROLLED BY MAXIMUM FILL.
3. MOMENT RATING FACTOR IS CONTROLLED BY MAXIMUM FILL, SHEAR RATING FACTOR IS CONTROLLED BY MINIMUM FILL.
4. BOTH MOMENT AND SHEAR RATING FACTORS ARE CONTROLLED BY MAXIMUM FILL.


#	CONTROLLING LOAD RATING
①	DESIGN LOAD RATING HL-93
②	DESIGN LOAD RATING HS-20 (INVENTORY)
③	LEGAL LOAD RATING **
	** SEE CHART FOR VEHICLE TYPE



LRFR SUMMARY
(LOOKING DOWNSTREAM)

PROJECT NO. B-5160
ROWAN COUNTY
 STATION: 12+13.00 -L-

SHEET 2 OF 6




STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH						SHEET NO. C-6
STANDARD LRFR SUMMARY FOR REINFORCED CONCRETE BOX CULVERT (NON-INTERSTATE TRAFFIC)						
REVISIONS						TOTAL SHEETS 6
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			
2			4			


ASSEMBLED BY : H.A. LOCKLEAR DATE : 7/30/15
 CHECKED BY : N.D. AIUTO DATE : 8/5/15

DRAWN BY : WMC 7/11
 CHECKED BY : GM 7/11

DESIGN ENGINEER OF RECORD:
 H.A. LOCKLEAR DATE : 8/5/15




CULVERT SECTION NORMAL TO ROADWAY



END ELEVATION-NORMAL TO SKEW

(LOOKING DOWNSTREAM)
(SILLS NOT SHOWN)




PART PLAN - ROOF SLAB

PART PLAN - FLOOR SLAB

I HEREBY CERTIFY THESE PLANS
ARE THE AS-BUILT PLANS



PROJECT NO. B-5160
ROWAN COUNTY
STATION: 12+13.00 -L-

SHEET 3 OF 6



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
BARREL STANDARD					
TRIPLE 11 FT. X 9 FT. CONCRETE BOX CULVERT					
120° SKEW					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					SHEET NO. C-3
					TOTAL SHEETS 6

DRAWN BY: N.D. AIUTO DATE: 7/30/15
CHECKED BY: J.K. BOWLES DATE: 8/5/15
DESIGN ENGINEER OF RECORD: H.A. LOCKLEAR DATE: 8/5/15




BAR	SIZE	SPLICE LENGTH
"A"	#5	1'-9"
B1, B3	#4	1'-5"
C1	#4	1'-11"
S2	#8	4'-0"


BAR TYPE						BILL OF MATERIAL					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
A1	158	#5	1	5'-1"	838	A305	4	#5	STR	25'-0"	104
A2	158	#5	1	4'-6"	742	A306	4	#5	STR	23'-0"	96
						A307	4	#5	STR	21'-0"	88
A100	44	#5	STR	35'-3"	1618	A308	4	#5	STR	19'-0"	79
A101	4	#5	STR	33'-1"	138	A309	4	#5	STR	16'-11"	71
A102	4	#5	STR	31'-1"	130	A310	4	#5	STR	14'-11"	62
A103	4	#5	STR	29'-1"	121	A311	4	#5	STR	12'-11"	54
A104	4	#5	STR	27'-1"	113	A312	4	#5	STR	10'-11"	46
A105	4	#5	STR	25'-0"	104	A313	4	#5	STR	8'-10"	37
A106	4	#5	STR	23'-0"	96	A314	4	#5	STR	6'-10"	29
A107	4	#5	STR	21'-0"	88	A315	4	#5	STR	4'-10"	20
A108	4	#5	STR	19'-0"	79	A316	4	#5	STR	2'-10"	12
A109	4	#5	STR	16'-11"	71						
A110	4	#5	STR	14'-11"	62	A400	44	#5	STR	35'-3"	1618
A111	4	#5	STR	12'-11"	54	A401	4	#5	STR	33'-1"	138
A112	4	#5	STR	10'-11"	46	A402	4	#5	STR	31'-1"	130
A113	4	#5	STR	8'-10"	37	A403	4	#5	STR	29'-1"	121
A114	4	#5	STR	6'-10"	29	A404	4	#5	STR	27'-1"	113
A115	4	#5	STR	4'-10"	20	A405	4	#5	STR	25'-0"	104
A116	4	#5	STR	2'-10"	12	A406	4	#5	STR	23'-0"	96
						A407	4	#5	STR	21'-0"	88
A200	44	#5	STR	35'-3"	1618	A408	4	#5	STR	19'-0"	79
A201	4	#5	STR	33'-1"	138	A409	4	#5	STR	16'-11"	71
A202	4	#5	STR	31'-1"	130	A410	4	#5	STR	14'-11"	62
A203	4	#5	STR	29'-1"	121	A411	4	#5	STR	12'-11"	54
A204	4	#5	STR	27'-1"	113	A412	4	#5	STR	10'-11"	46
A205	4	#5	STR	25'-0"	104	A413	4	#5	STR	8'-10"	37
A206	4	#5	STR	23'-0"	96	A414	4	#5	STR	6'-10"	29
A207	4	#5	STR	21'-0"	88	A415	4	#5	STR	4'-10"	20
A208	4	#5	STR	19'-0"	79	A416	4	#5	STR	2'-10"	12
A209	4	#5	STR	16'-11"	71						
A210	4	#5	STR	14'-11"	62	B1	92	#4	STR	10'-3"	630
A211	4	#5	STR	12'-11"	54	B2	158	#5	STR	8'-4"	1373
A212	4	#5	STR	10'-11"	46	B3	184	#4	STR	10'-3"	1260
A213	4	#5	STR	8'-10"	37						
A214	4	#5	STR	6'-10"	29	C1	260	#4	STR	23'-11"	4154
A215	4	#5	STR	4'-10"	20						
A216	4	#5	STR	2'-10"	12	D1	4	#6	STR	1'-4"	8
						D2	8	#6	STR	2'-4"	28
A300	44	#5	STR	35'-3"	1618						
A301	4	#5	STR	33'-1"	138	G1	8	#5	STR	40'-9"	340
A302	4	#5	STR	31'-1"	130						
A303	4	#5	STR	29'-1"	121	S2	12	#8	STR	40'-9"	1306
A304	4	#5		27'-1"	113	REINFORCING STEEL		LBS.		21,951	

RIGHT ANGLE SECTION OF BARREL

THERE ARE 130 "C" BARS IN SECTION OF BARREL.
 * ALL CONTINUOUS HIGH CHAIR UPPER (C.H.C.U.) @ 3'-0" CTS.



ELEVATION



SECTION THROUGH SILL

* DOWELS MAY BE PUSHED INTO GREEN CONCRETE AFTER SLAB HAS BEEN FLOAT FINISHED.

SILL DETAILS

PROJECT NO. B-5160
ROWAN COUNTY
 STATION: 12+13.00 -L-


SHEET 4 OF 6

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


TRIPLE 11 FT. X 9 FT. CONCRETE BOX CULVERT

120° SKEW


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	C-4
1			3			TOTAL SHEETS
2			4			6




DRAWN BY : N.D. AIUTO DATE : 7/30/15
 CHECKED BY : J.K. BOWLES DATE : 8/5/15
 DESIGN ENGINEER OF RECORD : H. A. LOCKLEAR DATE : 8/5/15




PLAN W2




PLAN W1



ELEVATION W2



ELEVATION W1




TYPICAL WING SECTION

BAR TYPES
ALL BAR DIMENSIONS ARE OUT TO OUT.

BILL OF MATERIAL					
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
H1	16	#4	STR	9'-4"	100
H2	4	#4	STR	6'-3"	17
H3	4	#4	STR	2'-10"	8
H4	28	#4	1	3'-3"	61
H5	4	#4	STR	10'-2"	27
H6	16	#4	STR	17'-10"	191
H7	4	#4	STR	12'-4"	33
H8	4	#4	STR	6'-3"	17
H9	28	#4	2	3'-3"	61
H10	4	#4	STR	18'-5"	49
N1	4	#6	3	11'-2"	67
N2	6	#6	3	9'-11"	89
N3	6	#5	3	8'-7"	54
N4	8	#4	3	6'-10"	37
N5	4	#6	3	11'-4"	68
N6	6	#6	3	10'-9"	97
N7	8	#6	3	9'-10"	118
N8	8	#5	3	8'-10"	74
N9	8	#4	3	7'-10"	42
N10	8	#4	3	6'-10"	37
S1	12	#6	STR	6'-0"	108
T1	6	#5	STR	11'-3"	70
T2	6	#5	STR	19'-9"	124
V1	4	#4	STR	9'-1"	24
V2	6	#4	STR	7'-10"	31
V3	6	#4	STR	6'-6"	26
V4	8	#4	STR	4'-10"	26
V5	4	#4	STR	9'-4"	25
V6	6	#4	STR	8'-9"	35
V7	8	#4	STR	7'-9"	41
V8	8	#4	STR	6'-9"	36
V9	8	#4	STR	5'-9"	31
V10	8	#4	STR	4'-9"	25
Z1	4	#5	4	6'-7"	27
Z2	4	#5	4	6'-0"	25
Z3	8	#5	4	4'-9"	40
Z4	8	#4	4	3'-4"	18
Z5	4	#5	4	6'-9"	28
Z6	6	#5	4	6'-3"	39
Z7	10	#5	4	5'-3"	55
Z8	10	#5	4	4'-4"	45
Z9	10	#4	4	3'-4"	22
REINFORCING STEEL FOR 4 WINGS					LBS. 2,148
CLASS A CONCRETE					
4 WINGS					C.Y. 30.2
2 HEADWALLS					C.Y. 3.8
2 END CURTAIN WALLS					C.Y. 4.6
6 SILLS					C.Y. 4.7
TOTAL					C.Y. 43.3

ASSEMBLED BY : N.D'AIUTO DATE : 7/30/15
 CHECKED BY : J.K.BOWLES DATE : 8/5/15
 DRAWN BY : CCJ 12/99
 CHECKED BY : RWW 03/00


12-OCT-2015 13:10
 R:\Structures\Plans\B5160.SD.CU.01.dgn
 thcorroll



PROJECT NO. B-5160
 ROWAN COUNTY
 STATION: 12+13.00 -L-
 SHEET 5 OF 6

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
STANDARD WINGS FOR CONCRETE BOX CULVERT H = 9'-0" SLOPE = 2:1 120° SKEW					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					C-5
					TOTAL SHEETS 6

STD. NO. CW6009



PLAN

* THIS DIMENSION TO BE CONFIRMED BY THE ENGINEER IN THE FIELD.

NOTES

THE GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS SHALL CONSIST OF THE FOLLOWING COMPONENTS :

- A. FERRULES SHALL BE MADE FROM STEEL MEETING THE REQUIREMENTS OF AASHTO M169, GRADE 12L14 AND SHALL HAVE A MINIMUM LENGTH OF THREADS OF 2 1/2".
- B. 4 - 1" Ø X 2 1/4" BOLTS WITH WASHERS, BOLTS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A307. BOLTS AND WASHERS SHALL BE GALVANIZED. (AT THE CONTRACTOR'S OPTION, STAINLESS STEEL BOLTS AND WASHERS MAY BE USED AS AN ALTERNATE FOR THE 1" Ø X 2 1/4" GALVANIZED BOLTS AND WASHERS. THEY SHALL CONFORM TO OR EXCEED THE MECHANICAL REQUIREMENTS OF ASTM A307. THE USE OF THIS ALTERNATE SHALL BE APPROVED BY THE ENGINEER.)
- C. WIRE STRUTS SHOWN IN THE GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS DETAIL ARE MINIMUM ALLOWABLE SIZE AND SHALL HAVE A MINIMUM TENSILE STRENGTH OF 100,000 P.S.I. AS AN OPTION, A 1/16" Ø WIRE STRUT WITH A MINIMUM TENSILE STRENGTH OF 90,000 PSI IS ACCEPTABLE.

GUARDRAIL ANCHOR ASSEMBLY WITH BOLTS SHALL BE ASSEMBLED IN THE SHOP. BOLT THREADS MAY BE RECUT AS NECESSARY TO INSURE FIT.

THE COST OF THE GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS COMPLETED IN PLACE SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR CLASS "A" CONCRETE.


FERRULES TO BE PLUGGED DURING POURING OF SLAB AS RECOMMENDED BY THE MANUFACTURER.

AT THE CONTRACTOR'S OPTION, FERRULES WITH OPEN OR CLOSED ENDS MAY BE USED.

PAYMENT FOR GUARDRAIL, POSTS, AND POST BASE PLATES IS INCLUDED IN ROADWAY PAY ITEMS.


SLAB REINFORCING STEEL MAY BE SHIFTED AS NECESSARY TO CLEAR GUARDRAIL ANCHOR ASSEMBLY. CARE SHOULD BE TAKEN TO KEEP THE SHIFTING OF REINFORCING STEEL TO A MINIMUM.

THE CONTRACTOR MAY USE ADHESIVELY ANCHORED ANCHOR BOLTS IN PLACE OF GUARDRAIL ANCHOR ASSEMBLY. LEVEL TWO FIELD TESTING IS REQUIRED, AND THE YIELD LOAD OF THE 1" Ø BOLT IS 21.8 KIPS. FOR ADHESIVELY ANCHORED ANCHOR BOLTS OR DOWELS, SEE STANDARD SPECIFICATIONS.



SECTION A-A

SECTION B-B



ELEVATION


SIDE VIEW

GUARDRAIL ANCHOR ASSEMBLY FOR CULVERT

PROJECT NO. B-5160
ROWAN COUNTY
 STATION: 12+13.00 -L-

SHEET 6 OF 6

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH STANDARD ANCHORAGE DETAILS FOR GUARDRAIL ANCHOR ASSEMBLY FOR CULVERTS					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
TOTAL SHEETS					6



ASSEMBLED BY :	N.D'AIUTO	DATE :	7/30/15
CHECKED BY :	J.K.BOWLES	DATE :	8/5/15
DRAWN BY :	FCJ	6/88	REV. 5/7/03 RWW/JTE
CHECKED BY :	ARB	6/88	REV. 5/1/06R KMM/GM
			REV. 10/1/11 MAA/GM

STANDARD NOTES

DESIGN DATA:

SPECIFICATIONS	-----	A.A.S.H.T.O. (CURRENT)
LIVE LOAD	-----	SEE PLANS
IMPACT ALLOWANCE	-----	SEE A.A.S.H.T.O.
STRESS IN EXTREME FIBER OF		
STRUCTURAL STEEL - AASHTO M270 GRADE 36	-	20,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50W	-	27,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50	-	27,000 LBS. PER SQ. IN.
REINFORCING STEEL IN TENSION		
GRADE 60	--	24,000 LBS. PER SQ. IN.
CONCRETE IN COMPRESSION	-----	1,200 LBS. PER SQ. IN.
CONCRETE IN SHEAR	-----	SEE A.A.S.H.T.O.
STRUCTURAL TIMBER - TREATED OR		
UNTREATED - EXTREME FIBER STRESS	-----	1,800 LBS. PER SQ. IN.
COMPRESSION PERPENDICULAR TO GRAIN		
OF TIMBER	-----	375 LBS. PER SQ. IN.
EQUIVALENT FLUID PRESSURE OF EARTH	-----	30 LBS. PER CU. FT.
		(MINIMUM)

MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2012 "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; AND CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP.

CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED 3/4" WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO 1-1/2" RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A 1/4" FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A 1/4" RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT, ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE.

ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER.

IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER.

DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS.

WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE 7/8" Ø SHEAR STUDS FOR THE 3/4" Ø STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF 7/8" Ø STUDS ALONG THE BEAM AS SHOWN FOR 3/4" Ø STUDS BASED ON THE RATIO OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-0".

EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST 5/16" IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2" OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED.

WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES, ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY 1/16 INCH OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB.

METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINIS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.

ENGLISH

JANUARY, 1990