# 2012 APPENDIX B
# BUILDING CODE SUMMARY
# FOR ALL COMMERCIAL PROJECTS
**(EXCEPT 1 AND 2-FAMILY DWELLINGS AND TOWNHOUSES)**
(Reproduce the following data on the building plans sheet 1 or 2)

Name of Project: CAMDEN COUNTY REST AREA REFURBISHMENT
Address: 2356 HWY 17 N, SOUTH MILLS, NC Zip Code 27976
Proposed Use: RESTROOM FACILITY- BUSINESS (B)
Owner/Authorized Agent: NCDOT Phone # ( 919 ) 707 - 4548 E-Mail llkeel@ncdot.gov
Owned By: ☐ City/County ☐ Private ☒ State
Code Enforcement Jurisdiction: ☐ City_____ ☐ County_____ ☒ State

**LEAD DESIGN PROFESSIONAL:** Lisa Keel

| DESIGNER | FIRM | NAME | LICENSE # | TELEPHONE # | E-MAIL |
|---|---|---|---|---|---|
| Architectural | NCDOT | Lisa Keel | 6195 | (919 )707-4548 | llkeel@ncdot.gov |
| Civil | | | | ( ) | |
| Electrical | Burke Design Group | Ben Burke | 22038 | 919 )771-1916 | benburke@nc.rr.com |
| Fire Alarm | | | | ( ) | |
| Plumbing | Burke Design Group | Ben Burke | 22038 | 919 )771-1916 | benburke@nc.rr.com |
| Mechanical | Burke Design Group | Ben Burke | 22038 | 919 )771-1916 | benburke@nc.rr.com |
| Sprinkler System | | | | ( ) | |
| Structural | | | | ( ) | |
| Retaining Walls >5' High | | | | ( ) | |
| Other | | | | ( ) | |

**2012 EDITION OF NC CODE FOR:** ☐ New Construction ☐ Addition ☐ Upfit
**EXISTING:** ☐ Reconstruction ☐ Alteration ☐ Repair ☒ Renovation
**CONSTRUCTED:** (date) 1989 **ORIGINAL USE(S)** (Ch. 3): _____
**RENOVATED:** (date) 1996 **CURRENT USE(S)** (Ch. 3): _____
**PROPOSED USE(S)** (Ch. 3): _____

**BASIC BUILDING DATA**
**Construction Type:** (check all that apply) ☐ I-A ☐ I-B ☐ II-A ☐ II-B ☐ III-A ☐ III-B ☐ IV ☒ V-A ☐ V-B
**Sprinklers:** ☒ No ☐ Partial ☐ Yes ☐ NFPA 13 ☐ NFPA 13R ☐ NFPA 13D
**Standpipes:** ☒ No ☐ Yes Class ☐ I ☐ II ☐ III ☐ Wet ☐ Dry
**Fire District:** ☒ No ☐ Yes (Primary) **Flood Hazard Area:** ☒ No ☐ Yes
**Building Height:** (feet) 15'-0"
**Gross Building Area:**

| FLOOR | EXISTING (SQ FT) | NEW (SQ FT) | SUB-TOTAL |
|---|---|---|---|
| 6th Floor | | | |
| 5th Floor | | | |
| 4th Floor | | | |
| 3rd Floor | | | |
| 2nd Floor | | | |
| Mezzanine | | | |
| 1st Floor | 1,560 | | 1,560 |
| Basement | | | |
| TOTAL | 1,560 | | 1,560 |

## ALLOWABLE AREA

**Occupancy:**
Assembly ☐ A-1 ☐ A-2 ☐ A-3 ☐ A-4 ☐ A-5
Business ☒
Educational ☐
Factory ☐ F-1 Moderate ☐ F-2 Low
Hazardous ☐ H-1 Detonate ☐ H-2 Deflagrate ☐ H-3 Combust ☐ H-4 Health ☐ H-5 HPM
Institutional ☐ I-1 ☐ I-2 ☐ I-3 ☐ I-4
I-3 Condition ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5
Mercantile ☐
Residential ☐ R-1 ☐ R-2 ☐ R-3 ☐ R-4
Storage ☐ S-1 Moderate ☐ S-2 Low ☐ High-piled
☐ Parking Garage ☐ Open ☐ Enclosed ☐ Repair Garage
Utility and Miscellaneous ☐

**Accessory Occupancies:**
Assembly ☐ A-1 ☐ A-2 ☐ A-3 ☐ A-4 ☐ A-5
Business ☐
Educational ☐
Factory ☐ F-1 Moderate ☐ F-2 Low
Hazardous ☐ H-1 Detonate ☐ H-2 Deflagrate ☐ H-3 Combust ☐ H-4 Health ☐ H-5 HPM
Institutional ☐ I-1 ☐ I-2 ☐ I-3 ☐ I-4
I-3 Condition ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5
Mercantile ☐
Residential ☐ R-1 ☐ R-2 ☐ R-3 ☐ R-4
Storage ☐ S-1 Moderate ☐ S-2 Low ☐ High-piled
☐ Parking Garage ☐ Open ☐ Enclosed ☐ Repair Garage
Utility and Miscellaneous ☐

**Incidental Uses** (Table 508.2.5):
☐ Furnace room where any piece of equipment is over 400,000 Btu per hour input
☐ Rooms with boilers where the largest piece of equipment is over 15 psi and 10 horsepower
☐ Refrigerant machine room
☐ Hydrogen cutoff rooms, not classified as Group H
☐ Incinerator rooms
☐ Paint shops, not classified as Group H, located in occupancies other than Group F
☐ Laboratories and vocational shops, not classified as Group H. located in a Group E or I-2 occupancy
☐ Laundry rooms over 100 square feet
☐ Group I-3 cells equipped with padded surfaces
☐ Group I-2 waste and linen collection rooms
☐ Waste and linen collection rooms over 100 square feet
☐ Stationary storage battery systems having a liquid electrolyte capacity of more than 50 gallons, or a lithium-ion capacity of 1,000 pounds used for facility standby power, emergency power or uninterrupted power supplies
☐ Rooms containing fire pumps
☐ Group I-2 storage rooms over 100 square feet
☐ Group I-2 commercial kitchens
☐ Group I-2 laundries equal to or less than 100 square feet
☐ Group I-2 rooms or spaces that contain fuel-fired heating equipment

**Special Uses:** ☐ 402 ☐ 403 ☐ 404 ☐ 405 ☐ 406 ☐ 407 ☐ 408 ☐ 409 ☐ 410 ☐ 411 ☐ 412 ☐ 413 ☐ 414 ☐ 415 ☐ 416 ☐ 417 ☐ 418 ☐ 419 ☐ 420 ☐ 421 ☐ 422 ☐ 423 ☐ 424 ☐ 425 ☐ 426 ☐ 427
**Special Provisions:** ☐ 509.2 ☐ 509.3 ☐ 509.4 ☐ 509.5 ☐ 509.6 ☐ 509.7 ☐ 509.8 ☐ 509.9
**Mixed Occupancy:** ☒ No ☐ Yes Separation:___ Hrs. Exception: _____
☐ Incidental Use Separation (508.2.5)

This separation is not exempt as a Non-Separated Use (see exceptions).
☐ Non-Separated Use (508.3)
The required type of construction for the building shall be determined by applying the height and area limitations for each of the applicable occupancies to the entire building. The most restrictive type of construction, so determined, shall apply to the entire building.
☐ Separated Use (508.4) - See below for area calculations
For each story, the area of the occupancy shall be such that the sum of the ratios of the actual floor area of each use divided by the allowable floor area for each use shall not exceed 1.

$$\frac{\text{Actual Area of Occupancy A}}{\text{Allowable Area of Occupancy A}} + \frac{\text{Actual Area of Occupancy B}}{\text{Allowable Area of Occupancy B}} \leq 1$$

_____ + _____ + ..... = _____ ≤ 1.00

| STORY NO. | DESCRIPTION AND USE | (A) BLDG AREA PER STORY (ACTUAL) | (B) TABLE 503[3] AREA | (C) AREA FOR FRONTAGE INCREASE[1] | (D) AREA FOR SPRINKLER INCREASE[2] | (E) ALLOWABLE AREA OR UNLIMITED[3] | (F) MAXIMUM BUILDING AREA[4] |
|---|---|---|---|---|---|---|---|
| 1 | B | 1,560 | 9,000 | NOT USED | N/A | 9,000 | 9,000 |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |

[1] Frontage area increases from Section 506.2 are computed thus:
a. Perimeter which fronts a public way or open space having 20 feet minimum width = ___ (F)
b. Total Building Perimeter = ___ (P)
c. Ratio (F/P) = ___ (F/P)
d. W = Minimum width of public way = ___ (W)
e. Percent of frontage increase $I_f = 100\ [\ F/P - 0.25]\ x\ W/30$ = ___ (%)
[2] The sprinkler increase per Section 506.3 is as follows:
a. Multi-story building $I_s$ = 200 percent
b. Single story building $I_s$ = 300 percent
[3] Unlimited area applicable under conditions of Section 507.
[4] Maximum Building Area = total number of stories in the building x E (506.4).
[5] The maximum area of open parking garages must comply with Table 406.3.5. The maximum area of air traffic control towers must comply with Table 412.1.2.

## ALLOWABLE HEIGHT

| | ALLOWABLE (TABLE 503) | INCREASE FOR SPRINKLERS | SHOWN ON PLANS | CODE REFERENCE |
|---|---|---|---|---|
| Type of Construction | Type V - B | | Type V - B | 602.5 |
| Building Height in Feet | 40 | Feet = H + 20' = N/A | 15'-0" | 503 |
| Building Height in Stories | 2 | Stories + 1 = N/A | 1 | 503 |

## FIRE PROTECTION REQUIREMENTS

| BUILDING ELEMENT | FIRE SEPARATION DISTANCE (FEET) | RATING REQ'D | RATING PROVIDED (W/ * REDUCTION) | DETAIL # AND SHEET # | DESIGN # FOR RATED ASSEMBLY | DESIGN # FOR RATED PENETRATION | DESIGN # FOR RATED JOINTS |
|---|---|---|---|---|---|---|---|
| Structural Frame, including columns, girders, trusses | >30' | 0 | | | | | |
| Bearing Walls | | | | | | | |
| Exterior | | 0 | | | | | |
| North | | | | | | | |
| East | | | | | | | |
| West | | | | | | | |
| South | | | | | | | |
| Interior | | 0 | | | | | |
| Nonbearing Walls and Partitions | | 0 | | | | | |
| Exterior walls | | | | | | | |
| North | | | | | | | |
| East | | | | | | | |
| West | | | | | | | |
| South | | | | | | | |
| Interior walls and partitions | | 0 | | | | | |
| Floor Construction Including supporting beams and joists | | 0 | | | | | |
| Roof Construction Including supporting beams and joists | | 0 | | | | | |
| Shaft Enclosures - Exit | | | | | | | |
| Shaft Enclosures - Other | | | | | | | |
| Corridor Separation | | | | | | | |
| Occupancy Separation | | | | | | | |
| Party/Fire Wall Separation | | | | | | | |
| Smoke Barrier Separation | | | | | | | |
| Tenant Separation | | | | | | | |
| Incidental Use Separation | | | | | | | |

* Indicate section number permitting reduction

## LIFE SAFETY SYSTEM REQUIREMENTS

Emergency Lighting: ☐ No ☒ Yes
Exit Signs: ☐ No ☒ Yes
Fire Alarm: ☒ No ☐ Yes
Smoke Detection Systems: ☒ No ☐ Yes ☐ Partial _____
Panic Hardware: ☐ No ☒ Yes

## LIFE SAFETY PLAN REQUIREMENTS

Life Safety Plan Sheet #: T1

☐ Fire and/or smoke rated wall locations (Chapter 7)
☐ Assumed and real property line locations
☐ Exterior wall opening area with respect to distance to assumed property lines (705.8)
☐ Existing structures within 30' of the proposed building
☒ Occupancy types for each area as it relates to occupant load calculation (Table 1004.1.1)
☒ Occupant loads for each area
☒ Exit access travel distances (1016) 250 ft.
☒ Common path of travel distances (1014.3 & 1028.8) 30 ft.
☐ Dead end lengths (1018.4) 20 ft.
☒ Clear exit widths for each exit door
☒ Maximum calculated occupant load capacity each exit door can accommodate based on egress width (1005.1)
☒ Actual occupant load for each exit door
☐ A separate schematic plan indicating where fire rated floor/ceiling and/or roof structure is provided for purposes of occupancy separation
☒ Location of doors with panic hardware (1008.1.10)
☐ Location of doors with delayed egress locks and the amount of delay (1008.1.9.7)
☐ Location of doors with electromagnetic egress locks (1008.1.9.8)
☐ Location of doors equipped with hold-open devices
☐ Location of emergency escape windows (1029)
☐ The square footage of each fire area (902)
☐ The square footage of each smoke compartment (407.4). Smoke barricades <22,500 sf. Max.
☐ Note any code exceptions or table notes that may have been utilized regarding the items above

## ACCESSIBLE DWELLING UNITS
(SECTION 1107)

| TOTAL UNITS | ACCESSIBLE UNITS REQUIRED | ACCESSIBLE UNITS PROVIDED | TYPE A UNITS REQUIRED | TYPE A UNITS PROVIDED | TYPE B UNITS REQUIRED | TYPE B UNITS PROVIDED | TOTAL ACCESSIBLE UNITS PROVIDED |
|---|---|---|---|---|---|---|---|
| | | | | | | | |

## ACCESSIBLE PARKING
(SECTION 1106)

| LOT OR PARKING AREA | TOTAL # OF PARKING SPACES REQUIRED | TOTAL # OF PARKING SPACES PROVIDED | # OF ACCESSIBLE SPACES PROVIDED: REGULAR WITH 5' ACCESS AISLE | VAN SPACES WITH 132" ACCESS AISLE | VAN SPACES WITH 5' ACCESS AISLE | TOTAL # ACCESSIBLE PROVIDED |
|---|---|---|---|---|---|---|
| EXISTING | 30 | 30 | 1 | | 1 | 2 |
| | | | | | | |
| | | | | | | |
| TOTAL | | | | | | |

## STRUCTURAL DESIGN

**DESIGN LOADS:**
**Importance Factors:** Wind ($I_W$) ____ Snow ($I_S$) ____ Seismic ($I_E$) ____
**Live Loads:** Roof ____ psf Mezzanine ____ psf Floor ____ psf
**Ground Snow Load:** psf

NOT APPLICABLE-EXISTING BUILDING

**Wind Load:** Basic Wind Speed _____ mph (ASCE-7)
Exposure Category _____
Wind Base Shears (for MWFRS) Vx = _____ Vy = _____

**SEISMIC DESIGN CATEGORY:** ☐ A ☐ B ☐ C ☐ D
Provide the following Seismic Design Parameters:
**Occupancy Category** (Table 1604.5) ☐ I ☐ II ☐ III ☐ IV
**Spectral Response Acceleration** $S_S$ %g $S_1$ %g
**Site Classification** (Table 1613.5.2) ☐ A ☐ B ☐ C ☐ D ☐ E ☐ F
Data Source: ☐ Field Test ☐ Presumptive ☐ Historical Data
**Basic structural system** (check one)
☐ Bearing Wall ☐ Dual w/Special Moment Frame
☐ Building Frame ☐ Dual w/Intermediate R/C or Special Steel
☐ Moment Frame ☐ Inverted Pendulum
**Seismic base shear:** $V_X$ = _____ $V_Y$ = _____
**Analysis Procedure:** ☐ Simplified ☐ Equivalent Lateral Force ☐ Dynamic
**Architectural, Mechanical, Components anchored?** ☐ Yes ☐ No

**LATERAL DESIGN CONTROL:** Earthquake ☐ Wind ☐

**SOIL BEARING CAPACITIES:**
Field Test (provide copy of test report) _____ psf
Presumptive Bearing capacity _____ psf
Pile size, type, and capacity _____

**SPECIAL INSPECTIONS REQUIRED:** ☐ Yes ☐ No

## PLUMBING FIXTURE REQUIREMENTS
(TABLE 2902.1)

| USE | | WATER CLOSETS MALE | WATER CLOSETS FEMALE | URINALS | LAVATORIES MALE | LAVATORIES FEMALE | SHOWERS/ TUBS | DRINKING FOUNTAINS REGULAR | DRINKING FOUNTAINS ACCESSIBLE |
|---|---|---|---|---|---|---|---|---|---|
| A | EXISTING | 3 | 5 | 2 | 3 | 3 | 0 | 1 | 1 |
| | NEW | 3 | 5 | 2 | 3 | 3 | 0 | 1 | 1 |
| | REQUIRED | 1 | 1 | 0 | 1 | 1 | 0 | 1 | 1 |

Alternate Restroom 4 water closets existing & new. 3 existing lavatories, 2 new lavatories.
The Alternate Toilet is used when Men's or Women's is closed for cleaning.
The Family Restroom provides 1 additional lavatory and 1 additional toilet (new & existing)

## SPECIAL APPROVALS

**Special approval:** (Local Jurisdiction, Department of Insurance, OSC, DPI, DHHS, ICC, etc., describe below)

_____
_____
_____

## ENERGY SUMMARY

**ENERGY REQUIREMENTS:**
The following data shall be considered minimum and any special attribute required to meet the energy code shall also be provided. Each Designer shall furnish the required portions of the project information for the plan data sheet. If performance method, state the annual energy cost for the standard reference design vs annual energy cost for the proposed design.

**Climate Zone:** ☒ 3 ☐ 4 ☐ 5

**Method of Compliance:**
☒ Prescriptive (Energy Code)
☐ Performance (Energy Code)
☐ Prescriptive (ASHRAE 90.1)
☐ Performance (ASHRAE 90.1)

**THERMAL ENVELOPE** 100% RENOVATION-NO CHANGES MADE TO BUILDING ENVELOPE

**Roof/ceiling Assembly** (each assembly)
Description of assembly: Asphalt shingle roof w/ attic batt insulation
U-Value of total assembly: 0.025
R-Value of insulation: 38
Skylights in each assembly: NONE
U-Value of skylight: _____
total square footage of skylights in each assembly: _____

**Exterior Walls** (each assembly)- Type I
Description of assembly: Existing-Cedar siding, 1" air space, R-19 in 2x6 stud wall.
U-Value of total assembly: 0.036
R-Value of insulation: 26.5
Openings (windows or doors with glazing)
U-Value of assembly: Original windows to remain
Solar heat gain coefficient: -
projection factor: -
Door R-Values: Original doors to remain

**Walls below grade** – NONE

**Floors over unconditioned space** – NONE

**Floors slab on grade**
Description of assembly: Poured-in-place concrete over vapor barrier
U-Value of total assembly: -
R-Value of insulation: -
Horizontal/vertical requirement: -
slab heated: NO

## MECHANICAL SUMMARY

**MECHANICAL SYSTEMS, SERVICE SYSTEMS AND EQUIPMENT**

**Thermal Zone** 3A
winter dry bulb: N/A-EXISTING HVAC SYSTEM IS NOT BEING MODIFIED
summer dry bulb: -ONLY UPDATING REGISTERS & CLEANING DUCTS

**Interior design conditions**
winter dry bulb: N/A
summer dry bulb: N/A
relative humidity: N/A

**Building heating load:** N/A

**Building cooling load:** N/A

**Mechanical Spacing Conditioning System**
Unitary
description of unit: N/A
heating efficiency: " " "
cooling efficiency: " " "
size category of unit: " " "
Boiler
Size category. If oversized, state reason.: N/A
Chiller
Size category. If oversized, state reason.: _____

**List equipment efficiencies:** _____

## ELECTRICAL SUMMARY

**ELECTRICAL SYSTEM AND EQUIPMENT**

**Method of Compliance:**
Energy Code: ☒ Prescriptive ☐ Performance
ASHRAE 90.1: ☐ Prescriptive ☐ Performance

**Lighting schedule** (each fixture type)
lamp type required in fixture SEE LIGHT FIXTURE SCHEDULE
number of lamps in fixture " " " "
ballast type used in the fixture " " " "
number of ballasts in fixture " " " "
total wattage per fixture " " " "
total interior wattage specified vs. allowed (whole building or space by space) 1460 VA/ 1226 VA
total exterior wattage specified vs. allowed

**Additional Prescriptive Compliance**
☐ 506.2.1 More Efficient Mechanical Equipment
☐ 506.2.2 Reduced Lighting Power Density
☒ 506.2.3 Energy Recovery Ventilation Systems
☐ 506.2.4 Higher Efficiency Service Water Heating
☐ 506.2.5 On-Site Supply of Renewable Energy
☐ 506.2.6 Automatic Daylighting Control Systems

BID DOCUMENTS

LISA LARKIN KEEL REGISTERED ARCHITECT 6195 NORTH CAROLINA RALEIGH, N.C.
SEAL: SEAL NOT VALID UNLESS SIGNED AND DATED

DESIGNED BY:
FACILITIES DESIGN
ARCHITECTS & ENGINEERS
FACILITIES MANAGEMENT DIVISION, NCDOT
1 SOUTH WILMINGTON STREET
RALEIGH, NORTH CAROLINA 27601
PH:919/707-4540 FAX:919/715-0369

CONSULTANT:

DRAWING TITLE / DESCRIPTION: BUILDING CODE SUMMARY

PROJECT TITLE:
CAMDEN COUNTY REST AREA REFURBISHMENT
2356 HWY 17 NORTH, SOUTH MILLS NC 27976
CAMDEN COUNTY, NORTH CAROLINA

| | |
|---|---|
| SCO ID NO. | 14-11342-01A |
| - | - |
| WBS NO. | 36059.27 |
| - | - |

ASSET NUMBER:
CO.# SITE.# BLDG.#
15 - 04 - 02

REVISIONS
NO. DATE

DATE ISSUED: 4/17/15
DRAWN BY: LK
CHECKED BY: -
SHEET NO.
T2