DocuSign Envelope ID: AD49546D-5BFE-4687-A3DE-BCD05980B178

LOAD AND RESISTANCE FACTOR RATING (LRFD) SUMMARY FOR PRESTRESSED CONCRETE GIRDERS

LEVEL		VEHICLE	WEIGHT (W) (TONS)	CONTROLLING LOAD RATING	MINIMUM RATING FACTORS (RF)	TONS = W X RF	STRENGTH I LIMIT STATE											SERVICE III LIMIT STATE						COMMENT NUMBER
							LIVELOAD FACTORS	MOMENT					SHEAR					LIVELOAD FACTORS	MOMENT					
								DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)		DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	
DESIGN LOAD RATING		HL-93(Inv)	N/A	1	1.59	--	1.75	0.250	2.68	60'	EL	30.00	0.650	1.59	60'	EL	6.00	0.80	0.250	3.65	60'	EL	30.00	
DESIGN LOAD RATING		HL-93(Opr)	N/A	--	2.1	--	1.35	0.250	3.47	60'	EL	30.00	0.650	2.10	60'	EL	6.00	N/A	--	--	--	--	--	
DESIGN LOAD RATING		HS-20(Inv)	36.000	2	1.99	71.64	1.75	0.250	3.39	60'	EL	30.00	0.650	1.99	60'	EL	6.00	0.80	0.250	4.63	60'	EL	30.00	
DESIGN LOAD RATING		HS-20(Opr)	36.000	--	2.58	92.88	1.35	0.250	4.40	60'	EL	30.00	0.650	2.58	60'	EL	6.00	N/A	--	--	--	--	--	
LEGAL LOAD RATING	SV	SNSH	13.500	--	5.74	77.49	1.4	0.250	9.13	60'	EL	30.00	0.650	5.74	60'	EL	6.00	0.80	0.250	9.97	60'	EL	30.00	
LEGAL LOAD RATING	SV	SNGARBS2	20.000	--	4.13	82.60	1.4	0.250	6.99	60'	EL	30.00	0.650	4.13	60'	EL	6.00	0.80	0.250	7.63	60'	EL	30.00	
LEGAL LOAD RATING	SV	SNAGRIS2	22.000	--	3.86	84.92	1.4	0.250	6.70	60'	EL	30.00	0.650	3.86	60'	EL	54.00	0.80	0.250	7.32	60'	EL	30.00	
LEGAL LOAD RATING	SV	SNCOTTS3	27.250	--	2.87	78.21	1.4	0.250	4.55	60'	EL	30.00	0.650	2.87	60'	EL	54.00	0.80	0.250	4.97	60'	EL	30.00	
LEGAL LOAD RATING	SV	SNAGGRS4	34.925	--	2.42	84.52	1.4	0.250	3.87	60'	EL	30.00	0.650	2.42	60'	EL	6.00	0.80	0.250	4.23	60'	EL	30.00	
LEGAL LOAD RATING	SV	SNS5A	35.550	--	2.46	87.45	1.4	0.250	3.78	60'	EL	30.00	0.650	2.46	60'	EL	54.00	0.80	0.250	4.13	60'	EL	30.00	
LEGAL LOAD RATING	SV	SNS6A	39.950	--	2.26	90.29	1.4	0.250	3.50	60'	EL	30.00	0.650	2.26	60'	EL	6.00	0.80	0.250	3.82	60'	EL	30.00	
LEGAL LOAD RATING	SV	SNS7B	42.000	--	2.24	94.08	1.4	0.250	3.33	60'	EL	30.00	0.650	2.24	60'	EL	6.00	0.80	0.250	3.64	60'	EL	30.00	
LEGAL LOAD RATING	TTST	TNAGRIT3	33.000	--	2.67	88.11	1.4	0.250	4.28	60'	EL	30.00	0.650	2.67	60'	EL	6.00	0.80	0.250	4.67	60'	EL	30.00	
LEGAL LOAD RATING	TTST	TNT4A	33.075	--	2.6	86.00	1.4	0.250	4.30	60'	EL	30.00	0.650	2.60	60'	EL	6.00	0.80	0.250	4.70	60'	EL	30.00	
LEGAL LOAD RATING	TTST	TNT6A	41.600	--	2.44	101.50	1.4	0.250	3.55	60'	EL	30.00	0.650	2.44	60'	EL	6.00	0.80	0.250	3.88	60'	EL	30.00	
LEGAL LOAD RATING	TTST	TNT7A	42.000	--	2.32	97.44	1.4	0.250	3.58	60'	EL	30.00	0.650	2.32	60'	EL	54.00	0.80	0.250	3.91	60'	EL	30.00	
LEGAL LOAD RATING	TTST	TNT7B	42.000	--	2.17	91.14	1.4	0.250	3.74	60'	EL	30.00	0.650	2.17	60'	EL	6.00	0.80	0.250	4.09	60'	EL	30.00	
LEGAL LOAD RATING	TTST	TNAGRIT4	43.000	--	2.11	90.73	1.4	0.250	3.53	60'	EL	30.00	0.650	2.11	60'	EL	54.00	0.80	0.250	3.86	60'	EL	30.00	
LEGAL LOAD RATING	TTST	TNAGT5A	45.000	--	2.12	95.40	1.4	0.250	3.32	60'	EL	30.00	0.650	2.12	60'	EL	6.00	0.80	0.250	3.62	60'	EL	30.00	
LEGAL LOAD RATING	TTST	TNAGT5B	45.000	3	2	90.00	1.4	0.250	3.26	60'	EL	30.00	0.650	2.00	60'	EL	6.00	0.80	0.250	3.57	60'	EL	30.00	

LOAD FACTORS:

	LIMIT STATE	γ_{DC}	γ_{DW}
DESIGN LOAD RATING FACTORS	STRENGTH I	1.25	1.50
	SERVICE III	1.00	1.00

NOTES:

MINIMUM RATING FACTORS ARE BASED ON THE STRENGTH I AND SERVICE III LIMIT STATES.

ALLOWABLE STRESSES FOR SERVICE III LIMIT STATE ARE AS REQUIRED FOR DESIGN.

COMMENTS:

1.
2.
3.
4.

(#) CONTROLLING LOAD RATING

(1) DESIGN LOAD RATING (HL-93)

(2) DESIGN LOAD RATING (HS-20)

(3) LEGAL LOAD RATING **

** SEE CHART FOR VEHICLE TYPE

GIRDER LOCATION

I - INTERIOR GIRDER
EL - EXTERIOR LEFT GIRDER
ER - EXTERIOR RIGHT GIRDER

LRFR SUMMARY

FOR SPAN 'B'

PROJECT NO. B-5606

PERQUIMANS COUNTY

STATION: 16+99.00 -L-

NORTH CAROLINA PROFESSIONAL ENGINEER SEAL L. KEVIN AUSTIN 5/15/2018

DocuSigned by: L. Kevin Austin 72F7B372DE4D4B1...

PLANS PREPARED BY:

CALYX ENGINEERS + CONSULTANTS
6750 TRYON ROAD
CARY, NC 27518
phone: 919.851.1912
CALYXengineers.com
NC License # F-1333

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

LRFR SUMMARY FOR 60' CORED SLAB UNIT 60° SKEW
(NON-INTERSTATE TRAFFIC)

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-4
1			3			TOTAL SHEETS
2			4			24

DRAWN BY : W. B. ALLEN DATE : 7/17
CHECKED BY : Z. H. BROWN DATE : 7/17
DESIGN ENGINEER OF RECORD: L. K. AUSTIN DATE : 5/18

5/15/2018 3:21:7 PM R:\Structures\B5606_SMU_G04_7000.dgn