PROJECT REFERENCE NO.	SHEET NO.
R-5118	2

ROADWAY DESIGN ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 29134 ENGINEER PIERCE W. SCHULTZ — 11/2/10

PAVEMENT DESIGN ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 20134 ENGINEER ROBERT H. CRIS — 11/2/10

℄ -L- & -L-REV-



TYPICAL SECTION NO. 1

WIDENING
-L- STA. 10+20 TO -L-REV- STA. 45+60
SUPERELEVATED 0.06 FT/FT MAX.

* NOTE: BERM WIDTH VARIES
FROM -L- STA 13+50 TO 17+00 LT.
FROM -L- STA 25+40 TO 25+70 LT.
FROM -L-REV- STA. 40+75 TO 43+00 LT.
(SEE CROSS SECTIONS)

℄ -Y-



TYPICAL SECTION NO. 2

WIDENING
-Y- STA. 10+10 TO STA. 12+10
SUPERELEVATED 0.06 FT/FT MAX.

PAVEMENT SCHEDULE

C1	PROP. APPROX. 2" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 224 LBS. PER SQ. YD.
C2	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 2 " IN DEPTH.
E1	PROP. APPROX. 5" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 570 LBS. PER SQ. YD.
E2	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5½" IN DEPTH.
R1	2'-6" CONCRETE CURB AND GUTTER. (NCDOT STANDARD DRAWING 846.01)
T	EARTH MATERIAL.
U	EXISTING PAVEMENT.
W	VARIABLE DEPTH ASPHALT PAVEMENT (SEE WEDGING DETAIL FOR RESURFACING).
S	4" CONCRETE SIDEWALK



Wedging Detail For Resurfacing
Where Existing E.O.P. Controls

SYSTIME
DGN
USERNAME

PROJECT REFERENCE NO.	SHEET NO.
R-5118	4
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 26950 ENGINEER JEFFREY M. SCHLICH — 11/2/10

NORTH CAROLINA PROFESSIONAL SEAL 030453 ENGINEER JASON C. CARVER — 11/2/10

8/17/99

REVISIONS

DATUM DESCRIPTION

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY OTHERS FOR MONUMENT "BRYSON CP2" WITH NAD 1983/95 STATE PLANE GRID COORDINATES OF NORTHING: 675960.744(ft) EASTING: 639989.571(ft)
THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.99982875
THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "BRYSON CP2" TO -L- STATION 10+00.00 IS N 18° 30' 37.5" W 1,093.31'
ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
VERTICAL DATUM USED IS: NAVD 88

NAD 83

REMOVE EXISTING PAVEMENT

BRYSON WALK SR 1321

POT Sta. 10+00.00

TIE TO EXISTING PAVEMENT

BEGIN TIP PROJECT R-5118
-L- STA. 10+20

5+00.00 Off 32.16 LT
BL-1

10+16.40 25' (LT)

10+38.22 25' (LT)

BEGIN CURB & GUTTER
-L- STA 10+50

GRAVEL

PAVED SURFACE

11+37.98 25' (LT)

N 20° 46' 54" W

25' BST
SLOPE STREET

N 23° 32' 43.0" W

15" CMP

20' BST

WCR

CB

15"

F

10+38.22 19' (RT) 25' (RT) ISFD

10+90.00 19' (RT) 25' (RT)

+63.00

+04.57

21.00'

+26.13

RETAIN 18" CMP 1A CB

PDE

TIE TO EXISTING PAVEMENT

BEGIN CURB & GUTTER
-L- STA 10+25
SEE DETAIL 1

10+22.65 25' (RT)

10+16.22 @ EXIST. R/W

157.46'
S25°00'00"E

ISFD

PCSta. 10+38.22

PTSta. 11+37.98

BRYSON WALK SR 1321

18" CMP

20' BST

1 WARREN MICHAEL SMITH

2 WADE CHITTOM JR. and wife, PATSY JEAN CHITTOM

ISFR BUS

42.48' N51°46'30"E

32.56' N54°55'31"E

41.93' N65°13'38"E

N14°43'23"E 157.47'

PCSta. 11+98.24

18.83' N16°47'00"E

37.65' N32°21'13"E

12.54' N68°15'15"E

PTSta. 12+95.38

3' ROCK WALL

11+98.24 25' (LT)

12+95.38 25' (LT)

8+62.94 -L- 13+12.91 Off 42.15 LT
BL-2

REMOVE PAVEMENT

F EXISTING R/W

36' DR.

30' DR.

20' DR.

SR 1323

EXISTING R/W

N 23° 18' 42.1" W

SLOPE STREET 16' BST

CB 18" CB

WCR 12" CMP

+79.38

DO NOT DISTURB TREE

2SR

11+98.24 25' (RT)

+73.08

S 67°26'04" W 43.00'

12+37.05 @℄ 20' (RT)

12+37.12 @℄ 25' (RT)

+74.38

12+95.38 20.00' (RT) REMOVE DI PLUG AND ABANDON 15" CMP

+95.38

13+24.36 @℄ 20' (RT) @℄ 25' (RT)

21.00'

CONC

EXISTING R/W (MAINTAINED)

BRYSON AVE

EXISTING R/W

RETAIN DI PLUG AND ABANDON 12" CMP

ADJUST MANHOLE

3 FREDERICK E. BRYSON

4 PAWS: PLACING ANIMALS WITHIN SOCIETY, INC.

ISFR BUS

5 GARY L. ARVEY and KAREN E. ARVEY

ISFD

S 23°16'56" E 38.77'

S 23°16'57" E 88.66'

NOTCH SIDEWALK AROUND TREES

6 ROBERT L. LYDAY and wife, DOROTHY B. LYDAY

141.16'
S23°16'57"E

MATCHLINE -L- 14+50 SEE SHEET 5

DETAIL 1



DETAIL FOR TRANSITION AT END OF 2'-6" CONCRETE CURB & GUTTER

PI Sta 10+88.11
Δ = 2° 35' 53.8" (RT)
D = 2° 36' 15.7"
L = 99.77'
T = 49.89'
R = 2,200.00'
SE = 0.03
R0 = 63.00'

PI Sta 12+46.82
Δ = 2° 31' 47.9" (LT)
D = 2° 36' 15.7"
L = 97.14'
T = 48.58'
R = 2,200.00'
SE = 0.03
R0 = 63.00'

SEE SHEET 11 FOR PROFILE

SYSTIMES$$$$ CONG$$$$

PROJECT REFERENCE NO.	SHEET NO.
R-5118	5
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 25360 ENGINEER PEGGY M. SCHULER 10/25/10

NORTH CAROLINA PROFESSIONAL SEAL 030458 ENGINEER AARON C. CANVENDER 10/25/10

REMOVE EXISTING PAVEMENT

8/17/99 REVISIONS

81.57' N 03°10'08" W

NAD 83

3 FREDERICK E. BRYSON

15

20

7 VARNER PROPERTIES UNLIMITED, INC.

275.37' N69°49'52"E

PCSta. 15+70.29

PTSta. 17+89.82

PCSta. 19+44.79

SOIL RD.

BRYSON BRANCH

N 23°18'42"W

15+70.29 25' (LT)

16+00.00 25' (LT)

17+89.82 25' (LT)

17+70.00 45' (LT) 25' (LT)

18+00.00 45' (LT) 25' (LT)

18+50.00 25' (LT)

19+80.00 70' (LT)

19+70.00 60' (LT)

19+44.79 25' (LT)

PLACE 1 TON CLASS B RIP RAP 5 SY FILTER FABRIC

PROP. 2'-6" C & G

BM-1

TDE

PDE

MATCHLINE -L- 14+50 SEE SHEET 4

MATCHLINE -L- 20+00 SEE SHEET 6

16' DR.

20' DR.

24' DR.

15" CMP

18" CMP

REMOVE CMP

-L-

EXISTING R/W

INV 1737.74

PLUG AND ABANDON

INV= 1738.86 DI REMOVE DI

BL-3

SR 1323

SLOPE STREET

17' BST

N 35°53'23.7"W

CB 7

DI 6

6

ADJUST MANHOLE

WHEELER ST

SOIL RD.

126.81' S66°06'31"W

121.55' S66°06'31"W

EXISTING R/W

30.00'

CONVERT DI TO OPEN THROAT

ADJUST MANHOLE

PROP. 2'-6" C & G

15+00.00 25' (RT)

15+25.00 30' (RT)

15+70.29 25' (RT)

15+70.29 30' (RT)

17+89.82 30' (RT)

17+89.82 25' (RT)

19+00.00 30' (RT)

19+44.80 25' (RT)

20.61'

+44.18

+04.03

+56.15

+99.43

+61.75

PI Sta 16+80.50
△ = 12° 34' 41.7" (LT)
D = 5° 43' 46.5"
L = 219.53'
T = 110.21'
R = 1,000.00'
SE = 0.049
RO = 101.00'

6

ROBERT L. and wife, DOROTHY B. LYDAY

SEE SHEET 11 FOR PROFILE

$$SYSTIME$$
$$DGN$$
$$FILENAME$$

I:\TIMA\1490\ll_rwy_pnls_pls.dgn 10/25/2010 12:26:12 PM

PROJECT REFERENCE NO.	SHEET NO.
R-5118	6
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 15990 ENGINEER CHARLES M. SCHULER — 10/25/10

HYDRAULICS ENGINEER — NORTH CAROLINA PROFESSIONAL SEAL 030453 ENGINEER AARON C. CARVER — 10/25/10

REVISIONS 8/17/99

NAD 83

207.13'
N 41°57'07" W

56.89'
S 47°04'37" W

110.90'
S 47°04'38" W

205.19'
S47°44'35"W

37.80'
S47°04'39"W

7
VARNER PROPERTIES
UNLIMITED, INC.

9
MITCHELL A. JENKINS
ELIZABETH JENKINS

10
TRUSTEES OF:
NORTH CAROLINA WEST
DISTRICT OF THE
WESLEYAN CHURCH AND
BRYSON CITY CORNERSTONE
WESLEYAN CHURCH

PCSta. 23+65.57

PTSta. 22+05.83

PTSta. 24+84.52

PLACE 1 TON
CLASS B RIP RAP
5 SY FILTER FABRIC

BRYSON BRANCH

TAIL DITCH
DETAIL 2

TRAILER

MATCHLINE -L- 20+00 SEE SHEET 5

MATCHLINE -L- 25+00 SEE SHEET 7

-L-

N 41° 49' 30.2" W

20+15.00 25' (LT)
20+50.00 25' (LT)
21+00.00 30' (LT)
22+05.83 30' (LT)
22+05.83 25' (LT)
23+65.56 30' (LT)
25' (LT)
23+45.00 30' (LT)
25' (LT)
24+01.47 52' (LT)
24+01.71 30' (LT)
24+01.75 25' (LT)
24+22.00 55' (LT)
30' (LT)
25' (LT)
24+84.52 30' (LT)
25' (LT)

INV=1752.30
INV=1734.28
INV=1761.56

REMOVE
REMOVE DI
PLUG & ABANDON
CONST. PAVED SWALE GRADE TO DRAIN TO CB
PROP. 2'-6" C & G

24' DR.
EXISTING R/W
20' DR.
12' DR.
36' DR.
16' DR.
11' BST
SLOPE STREET
GRAVEL
PROPOSED DRIVEWAY GRADE 16%

EX. DRIVE EXCEEDS 20% GRADE. TIE IN CURB CUT WITH DRIVE.

EXTEND PIPE 5 FT

ADJUST 3 WATER VALVE BOXES

REGRADE CORNER OF DRIVEWAY

PLACE SIDEWALK 2FT BEHIND CURB TO ACCOMMODATE MAIL BOXES

DETAIL 2
STANDARD "V" DITCH
(Not to Scale)

Natural Ground — 2:1 — D — 2:1 — Natural Ground
Min. D= 1Ft.
DDE = 2 CY

STA. 24+07 TO 24+12

PI Sta 20+75.43
Δ = 5°56'06.4" (LT)
D = 2°16'25.1"
L = 261.04'
T = 130.64'
R = 2,520.00'
SE = 0.028
RO = 58.10'

6
ROBERT L. and wife,
DOROTHY B. LYDAY

N45°13'23"E 262.12'

8
MARK FORTNER

PI Sta 24+25.05
Δ = 1°52'20.6" (LT)
D = 1°34'26.6"
L = 118.95'
T = 59.48'
R = 3,640.00'
SE = 0.02
RO = 41.44'

S 38°32'39" W 94.06'

S 40°50'54" W 61.46'

SEE SHEET 11 & 12 FOR PROFILE

$$$$USERNAME$$$$ $$$$SYSTIME$$$$ $$$$DGN$$$$ $$$$USERPROFILE$$$$

\\PSHMAIN\PROJ\R_PRJ_RW.dgn 10/26/2010 12:10:58 PM

PROJECT REFERENCE NO.	SHEET NO.
R-5118	7
R/W SHEET NO.	

ROADWAY DESIGN ENGINEER — SEAL 28220 — ENGINEER — DEREK M. SCHRADER — 10/26/18

HYDRAULICS ENGINEER — SEAL 030453 — ENGINEER — MARION C. CARPER — 10/25/18

NAD 83

(10) TRUSTEES OF: NORTH CAROLINA WEST DISTRICT OF THE WESLEYAN CHURCH AND BRYSON CITY CORNERSTONE WESLEYAN CHURCH
D.B. 208 PG. 762

(13) MOUNTAIN MORTGAGE INVESTMENT COMPANY
D.B. 120 PG. 683

25

PCSta. 25+82.72

PTSta. 28+51.15

PCSta. 29+17.30

CHORD BEARING = N39°26'39"E
CHORD DISTANCE=194.47
RADIUS=950.00
ARC LENGTH=194.81

MATCHLINE -L- 25+00 SEE SHEET 6

MATCHLINE -L- STATION 30+00 SEE SHEET 8

WIDTH VARIES -L- STA 25+40 TO 25+70 LT.

25+82.72 30' (LT)

25+82.72 25' (LT)

POND

PAVED SURFACE

24" DR.

15"

SR 1323

N 43° 41' 50.8" W

14' DR.

30" DR.

SIGN

EXISTING R/W

CB

EIP

BL-5

N 64° 12' 12.6" W

28+76.00 40' (LT) 25' (LT)

28+95.00 40' (LT) 25' (LT)

28+51.15 30' (LT) 25' (LT)

PLACE 1 TON CLASS B RIP RAP 5 SY FILTER FABRIC

29+17.30 30' (LT)

29+17.30 25' (LT)

IS BUS

11" BST

15" CMP REMOVE

STEPS

16' DR.

TRAILER

36" DR.

42" CMP RETAIN

28+51.15 25' (RT)

28+51.15 30' (LT)

29+17.30 25' (RT)

29+17.30 30' (RT)

29+80.00 25' (RT)

29+80.00 30' (RT)

GRAVEL

(12) BEVERLY ROSS
D.B. 156 PG. 38

(11) BARBARA CATES McHAN
D.B. 200 PG. 649
D.B. 223 PG. 33

(14) MATTIE COLEMAN PATE
D.B. 86 PG. 48

(35) MARY H. BROWN
D.B. 211 PG. 328
D.B. 51 PG. 395

(36) CHARLES JENKINS
D.B. 301 PG. 303

(15) LESLIE POWELL
PEGGY PARRISH
D.B. 85 PG. 114

96.79' S33°45'50"E

82.80' S 49°24'29" E

61.96' N 32°12'46" W

R=222.55' ARC=15.55'

R=222.55' ARC=15.73'

R=65.33' ARC=29.42'

109.16' N 85°01'41" E

18.48' N39°36'41"E

164.91' N39°36'41"E

188.38' N35°44'47"E

197.99' N35°00'00"E

63.82' N27°37'05"E

46.61' S54°28'48"E

EASEMENT

INSTALL 300 LF OF 4" SHOULDER DRAIN & 30 LF OF 4" OUTLET PIPE. CONNECT TO EXIST. C.B. INSTALL 4' BEHIND BACK OF CURB PE NCDOT STD. 816.02

NOTCH SIDEWALK AROUND MANHOLE

PLACE SIDEWALK 2 FT BEHIND CURB TO ACCOMMODATE MAIL BOXES

SEE SHEETS 12 FOR PROFILE

8/17/98

#####USERNAME#####

#####FILENAME#####

#####DESIGN#####

#####STATUS#####

#####TIME#####

#####DATE#####

\\PGMAIN\1400\R_Proj_007 dgn 10/25/2018 12:44:14 PM

PROJECT REFERENCE NO.	SHEET NO.
R-5118	8
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

NORTH CAROLINA PROFESSIONAL SEAL 28650 ENGINEER DEREK M. SCHILLER — 11/2/10

NORTH CAROLINA PROFESSIONAL SEAL 030453 ENGINEER AARON C. CARVER — 11/2/10

8/17/99

REVISIONS

NAD 83

ADD CURB RAMP

MATCHLINE -L- STATION 30+00 SEE SHEET 7

MATCHLINE -L- STATION 35+00 SEE SHEET 9

PI Sta 33+86.13
Δ = 2° 58' 25.3" (LT)
D = 2° 50' 11.1"
L = 104.84'
T = 52.43'
R = 2,020.00'
SE = 0.033
RO = 68.01'

PI Sta 30+41.04
Δ = 8° 22' 30.8" (RT)
D = 3° 23' 25.0"
L = 247.04'
T = 123.74'
R = 1,690.00'
SE = 0.037
RO = 76.52'

PC Sta. 33+33.70

PT Sta. 31+64.34

PT Sta. 34+38.54

966.51'
N44°53'58"E

(13) MOUNTAIN MORTGAGE INVESTMENT COMPANY

(18) RALPH F. and wife, DONNA C. WOODARD

(20) VERNIE and wife, NINA COLE

(16) RICHARD POWELL

(17) RESSIE DEHART

(19) MARK FORTNER

PAVED SURFACE

4' CHAINLINK

SIGN

SLOPE STREET

SR 1323

36' DR.

16' DR.

-L-

N 55° 49' 41.8" W

N 58° 48' 07.1" W

EXISTING R/W

32+25.00 40' (LT) 25' (LT)

32+45.00 40' (LT) 25' (LT)

PLACE 1 TON CLASS B RIP RAP 5 SY FILTER FABRIC

31+64.34 30' (LT)

31+64.34 25' (LT) EIP

PDE

17B

17A CB

15"

BL-6

27+84.47 -L- 32+49.15 Offset 12.31' LT

+54.71

+56.58

PROP. 2'-6" C & G

33+33.70 25' (LT)

33+33.70 30' (LT)

34+00.00 40' (LT) 25' (LT)

GRAVEL

19B

34+10.00 40' (LT) 25' (LT)

34+38.54 25' (LT)

34+50.00 35' (LT)

+64.79

INV=1785.73

20.61'

16' DR.

18"

REMOVE EIP

CB

19A

17' BST

WCR

INV=1789.71

15"

R 40.00'

18

19

R 23.00'

+15.87

+42.66

SIGN INV= 1794.49

TIE TO EXISTING PAVEMENT

MORNING STAR DRIVE SR 1389

ISF

TRAILER

ASPHALT

RETAIN

15" CMP

INV= 1796.03

INV= 1798.71

INV=1803.83

EXISTING R/W

30+20.00 25' (RT) 30' (RT)

31+00.00 45' (RT) 30' (RT)

31+64.34 25' (RT)

31+70.00 45' (RT)

32+75.00 30' (RT)

33+00.00 25' (RT)

33+33.70 25' (RT)

34+38.54 25' (RT)

34+50.00 25' (RT)

+38.84

+47.15

110.25'
N35°00'00"E

103.27'
S35°00'00"W

98.54'
S35°00'00"W

137.00'
N 61°00'00" W

177.01'
N 56°12'56" W

141.57'
S49°04'18"W

94.83'
N58°26'16"W

50.00'
N 58°26'16" W

DETAIL 4
DRIVEWAY
-L- STA 30+85± TO STA 31+85± RT
(Not to Scale)

EXISTING DRIVEWAY

RELOCATED DRIVEWAY

15'

NOTE: MATCH EXISTING DRIVEWAY WIDTH, SLOPE, AND GRADE

SEE SHEET 12 AND 13 FOR PROFILE

$$SYSTIME$$ $$SYSTIME$$ $$SYSTIME$$ $