

SEE SHEET 3 FOR PLAN SHEET LAYOUT  
AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA  
DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-6055	1	23

CONTENTS

LINE	STATION	PLAN	PROFILE
-L-	12+00 - 14+10	4	N/A
-Y-	10+00 - 10+25	4	N/A
-Y1-	10+70 - 12+52	4	N/A
-Y2-	10+00 - 11+50	4	N/A
-Y3-	10+00 - 12+50	4	N/A
-Y4-	10+55 - 11+94	4	N/A

APPENDICES

APPENDIX	TITLE	SHEETS
A	LABORATORY TEST RESULTS	11-12
B	HAND AUGER/DCP LOGS	13-17
C	KESSLER DCP LOGS	18-20

ROADWAY  
SUBSURFACE INVESTIGATION

COUNTY HAYWOOD  
PROJECT DESCRIPTION INTERSECTION OF PISGAH DR  
(NC 110), HOLTZCLAW ST, AND LOCUST ST IN  
THE TOWN OF CANTON

INVENTORY

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
  - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

S. SAWYER, P.E.

D. KESTNER

M. BREWER, P.E.

INVESTIGATED BY ECS SOUTHEAST, LLP

DRAWN BY M. BREWER, P.E.

CHECKED BY M. WALKO, P.E.

SUBMITTED BY ECS SOUTHEAST, LLP

DATE SEPTEMBER 2018

Prepared in the Office of:



ECS SOUTHEAST, LLP  
1812 CENTER PARK DRIVE, SUITE D  
CHARLOTTE, NC 28217  
(704) 525-5152 [PHONE]  
(704) 357-0023 [FAX]  
NC REGISTERED  
ENGINEERING  
FIRM # F-1078



DocuSigned by:

*Michael J. Walko*

09589EECD3814D9

SIGNATURE

DATE

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

REFERENCE: U-6055

PROJECT: N/A

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
 DIVISION OF HIGHWAYS  
**GEOTECHNICAL ENGINEERING UNIT**

# SUBSURFACE INVESTIGATION


SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION	GRADATION	ROCK DESCRIPTION	TERMS AND DEFINITIONS																																																																																																																																																																																																																																																																																																																																																																																																																																									
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 298, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</p>	<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE.                  UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE.                  GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>	<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL, SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK.                  ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>	<p><b>ALLUVIUM (ALLUV.)</b> - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.  <b>AQUIFER</b> - A WATER BEARING FORMATION OR STRATA.  <b>ARENACEOUS</b> - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.  <b>ARGILLACEOUS</b> - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.  <b>ARTESIAN</b> - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.  <b>CALCAREOUS (CALC.)</b> - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.  <b>COLLUVIUM</b> - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.  <b>CORE RECOVERY (REC.)</b> - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.  <b>DIKE</b> - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.  <b>DIP</b> - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.  <b>DIP DIRECTION (DIP AZIMUTH)</b> - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.  <b>FAULT</b> - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.  <b>FISSILE</b> - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.  <b>FLOAT</b> - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL.  <b>FLOOD PLAIN (FP)</b> - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.  <b>FORMATION (FM)</b> - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.  <b>JOINT</b> - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.  <b>LEDGE</b> - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.  <b>LENS</b> - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.  <b>MOTTLED (MOT.)</b> - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.  <b>PERCHED WATER</b> - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.  <b>RESIDUAL (RES.) SOIL</b> - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.  <b>ROCK QUALITY DESIGNATION (RQD)</b> - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.  <b>SAPROLITE (SAP.)</b> - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.  <b>SILL</b> - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.  <b>SLICKENSIDE</b> - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.  <b>STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT)</b> - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.  <b>STRATA CORE RECOVERY (SREC.)</b> - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.  <b>STRATA ROCK QUALITY DESIGNATION (SROD)</b> - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.  <b>TOPSOIL (TS)</b> - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																																																																																																																																																																																																																																																																																																									
<p><b>SOIL LEGEND AND AASHTO CLASSIFICATION</b></p> <table border="1"> <thead> <tr> <th>GENERAL CLASS.</th> <th colspan="6">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="6">SILT-CLAY MATERIALS (&gt; 35% PASSING #200)</th> <th colspan="4">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th colspan="2">A-1</th> <th colspan="2">A-3</th> <th colspan="2">A-2</th> <th colspan="2">A-4</th> <th colspan="2">A-5</th> <th colspan="2">A-6</th> <th colspan="2">A-7</th> <th colspan="2">A-1, A-2</th> <th colspan="2">A-3</th> <th colspan="2">A-4, A-5</th> <th colspan="2">A-6, A-7</th> </tr> <tr> <th>SYMBOL</th> <th colspan="2">A-1-a</th> <th colspan="2">A-1-b</th> <th colspan="2">A-2-4</th> <th colspan="2">A-2-5</th> <th colspan="2">A-2-6</th> <th colspan="2">A-2-7</th> <th colspan="2">A-4</th> <th colspan="2">A-5</th> <th colspan="2">A-6</th> <th colspan="2">A-7</th> <th colspan="2">A-1, A-2</th> </tr> <tr> <th>% PASSING #10 #40 #200</th> <th colspan="2">50 MX 30 MX 15 MX</th> <th colspan="2">50 MX 10 MX</th> <th colspan="2">50 MX 10 MX</th> <th colspan="2">35 MX 35 MX</th> <th colspan="2">35 MX 35 MX</th> <th colspan="2">35 MX 35 MX</th> <th colspan="2">35 MX 35 MX</th> <th colspan="2">35 MN 36 MN</th> <th colspan="2">36 MN 36 MN</th> <th colspan="2">36 MN 36 MN</th> <th colspan="2">GRANULAR SOILS SILT-CLAY SOILS MUCK, PEAT</th> </tr> <tr> <th>MATERIAL PASSING #40 LL PI</th> <th colspan="2">-</th> <th colspan="2">-</th> <th colspan="2">40 MX 41 MN</th> <th colspan="2">40 MX 41 MN</th> <th colspan="2">40 MX 41 MN</th> <th colspan="2">40 MX 41 MN</th> <th colspan="2">40 MX 41 MN</th> <th colspan="2">40 MX 41 MN</th> <th colspan="2">40 MX 41 MN</th> <th colspan="2">40 MX 41 MN</th> <th colspan="2">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER HIGHLY ORGANIC SOILS</th> </tr> <tr> <th>GROUP INDEX</th> <th colspan="2">0</th> <th colspan="2">0</th> <th colspan="2">0</th> <th colspan="2">4 MX</th> <th colspan="2">8 MX</th> <th colspan="2">12 MX</th> <th colspan="2">16 MX</th> <th colspan="2">NO MX</th> <th colspan="2"></th> <th colspan="2"></th> <th colspan="2"></th> </tr> <tr> <th>USUAL TYPES OF MAJOR MATERIALS</th> <th colspan="2">STONE FRAGS. GRAVEL, AND SAND</th> <th colspan="2">FINE SAND</th> <th colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</th> <th colspan="2">SILTY SOILS</th> <th colspan="2">CLAYEY SOILS</th> <th colspan="2"></th> <th colspan="2"></th> <th colspan="2"></th> <th colspan="2"></th> <th colspan="2"></th> <th colspan="2"></th> </tr> <tr> <th>GEN. RATING AS SUBGRADE</th> <th colspan="6">EXCELLENT TO GOOD</th> <th colspan="6">FAIR TO POOR</th> <th colspan="2">FAIR TO POOR</th> <th colspan="2">POOR</th> <th colspan="2">UNSATURABLE</th> <th colspan="2"></th> </tr> <tr> <td colspan="23">                     PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS &gt; LL - 30                 </td> </tr> <tr> <td colspan="1"> <p><b>CONSISTENCY OR DENSENESS</b></p> <table border="1"> <thead> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> </thead> <tbody> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 &gt; 4</td> </tr> </tbody> </table> </td> <td colspan="1"> <p><b>MISCELLANEOUS SYMBOLS</b></p> </td> <td colspan="1"> <p><b>ROCK HARDNESS</b></p> <table border="1"> <thead> <tr> <th>VERY HARD</th> <th>HARD</th> <th>MODERATELY HARD</th> <th>MEDIUM HARD</th> <th>SOFT</th> <th>VERY SOFT</th> <th>COMPLETE</th> </tr> </thead> <tbody> <tr> <td>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</td> <td>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</td> <td>CAN BE SCRATCHED BY KNIFE OR PICK OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</td> <td>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</td> <td>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</td> <td>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</td> <td>ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</td> </tr> </tbody> </table> </td> <td colspan="1"> <p><b>RECOMMENDATION SYMBOLS</b></p> </td> <td colspan="1"> <p><b>ABBREVIATIONS</b></p> <table border="1"> <thead> <tr> <th>AR - AUGER REFUSAL</th> <th>BT - BORING TERMINATED</th> <th>CL - CLAY</th> <th>CPT - CONE PENETRATION TEST</th> <th>CSE - COARSE</th> <th>DMT - DILATOMETER TEST</th> <th>DPT - DYNAMIC PENETRATION TEST</th> <th>ø - VOID RATIO</th> <th>F - FINE</th> <th>FOSS. - FOSSILIFEROUS</th> <th>FRAC. - FRACTURED, FRACTURES</th> <th>FRAGS. - FRAGMENTS</th> <th>HI. - HIGHLY</th> <th>MED. - MEDIUM</th> <th>MICA. - MICACEOUS</th> <th>MOD. - MODERATELY</th> <th>NP - NON PLASTIC</th> <th>ORG. - ORGANIC</th> <th>PMT - PRESSUREMETER TEST</th> <th>SAP. - SAPROLITIC</th> <th>SD. - SAND, SANDY</th> <th>SL. - SILT, SILTY</th> <th>SLI. - SLIGHTLY</th> <th>TCR - TRICONE REFUSAL</th> <th>w - MOISTURE CONTENT</th> <th>V - VERY</th> <th>VST - VANE SHEAR TEST</th> <th>WEA. - WEATHERED</th> <th>γ<sub>u</sub> - UNIT WEIGHT</th> <th>γ<sub>d</sub> - DRY UNIT WEIGHT</th> <th>S - BULK</th> <th>SS - SPLIT SPOON</th> <th>ST - SHELBY TUBE</th> <th>RS - ROCK</th> <th>RT - RECOMPACTED TRIAXIAL</th> <th>CBR - CALIFORNIA BEARING RATIO</th> </tr> </thead> <tbody> <tr> <td>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td> <td>AR</td> <td>BT</td> <td>CL</td> <td>CPT</td> <td>CSE</td> <td>DMT</td> <td>DPT</td> <td>ø</td> <td>F</td> <td>FOSS.</td> <td>FRAC.</td> <td>FRAGS.</td> <td>HI.</td> <td>MED.</td> <td>MICA.</td> <td>MOD.</td> <td>NP</td> <td>ORG.</td> <td>PMT</td> <td>SAP.</td> <td>SD.</td> <td>SL.</td> <td>SLI.</td> <td>TCR</td> <td>w</td> <td>V</td> <td>VST</td> <td>WEA.</td> <td>γ<sub>u</sub></td> <td>γ<sub>d</sub></td> <td>S</td> <td>SS</td> <td>ST</td> <td>RS</td> <td>RT</td> <td>CBR</td> </tr> </tbody> </table> </td> <td colspan="1"> <p><b>EQUIPMENT USED ON SUBJECT PROJECT</b></p> <table border="1"> <thead> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> CME-450</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td rowspan="2">CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -H <input type="checkbox"/> -N</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td rowspan="3">HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input checked="" type="checkbox"/> KESSLER DCP <input checked="" type="checkbox"/> CORING MACHINE</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> w/ ADVANCER <input type="checkbox"/> TRICONE <input type="checkbox"/> *STEEL TEETH <input type="checkbox"/> TRICONE <input type="checkbox"/> *TUNG-CARB. <input type="checkbox"/> CORE BIT <input type="checkbox"/></td> </tr> </tbody> </table> </td> <td colspan="1"> <p><b>TEXTURE OR GRAIN SIZE</b></p> <table border="1"> <thead> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> </thead> <tbody> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F. SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>GRAIN SIZE MM 305 75 2.0 0.25 0.05 0.005</p> </td> <td colspan="1"> <p><b>SOIL MOISTURE - CORRELATION OF TERMS</b></p> <table border="1"> <thead> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>LL</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PLASTIC RANGE (PI)</td> <td>- WET - (W)</td> <td>SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td></td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>OM</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>SL</td> <td></td> <td></td> </tr> </tbody> </table> </td> <td colspan="1"> <p><b>PLASTICITY</b></p> <table border="1"> <thead> <tr> <th>NON PLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> </thead> <tbody> <tr> <td></td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </tbody> </table> </td> <td colspan="1"> <p><b>COLOR</b></p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p> </td> <td colspan="1"> <p><b>FRACATURE SPACING</b></p> <table border="1"> <thead> <tr> <th>TERM</th> <th>SPACING</th> </tr> </thead> <tbody> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </tbody> </table> </td> <td colspan="1"> <p><b>BEDDING</b></p> <table border="1"> <thead> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> </thead> <tbody> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </tbody> </table> </td> <td colspan="1"> <p><b>INDURATION</b></p> <table border="1"> <thead> <tr> <th>FRAGILE</th> <th>MODERATELY INDURATED</th> <th>INDURATED</th> <th>EXTREMELY INDURATED</th> </tr> </thead> <tbody> <tr> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </tbody> </table> </td> <td colspan="1"> <p><b>BENCH MARK:</b></p> <p>ELEVATION: FEET</p> </td> <td colspan="1"> <p><b>NOTES:</b></p> <p>SURVEY INFORMATION AND DESIGN FILES PROVIDED BY TGS ENGINEERS</p> </td> </tr> </thead></table>	GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)						SILT-CLAY MATERIALS (> 35% PASSING #200)						ORGANIC MATERIALS				GROUP CLASS.	A-1		A-3		A-2		A-4		A-5		A-6		A-7		A-1, A-2		A-3		A-4, A-5		A-6, A-7		SYMBOL	A-1-a		A-1-b		A-2-4		A-2-5		A-2-6		A-2-7		A-4		A-5		A-6		A-7		A-1, A-2		% PASSING #10 #40 #200	50 MX 30 MX 15 MX		50 MX 10 MX		50 MX 10 MX		35 MX 35 MX		35 MX 35 MX		35 MX 35 MX		35 MX 35 MX		35 MN 36 MN		36 MN 36 MN		36 MN 36 MN		GRANULAR SOILS SILT-CLAY SOILS MUCK, PEAT		MATERIAL PASSING #40 LL PI	-		-		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER HIGHLY ORGANIC SOILS		GROUP INDEX	0		0		0		4 MX		8 MX		12 MX		16 MX		NO MX								USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS														GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD						FAIR TO POOR						FAIR TO POOR		POOR		UNSATURABLE				PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30																							<p><b>CONSISTENCY OR DENSENESS</b></p> <table border="1"> <thead> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> </thead> <tbody> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 &gt; 4</td> </tr> </tbody> </table>	PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	<p><b>MISCELLANEOUS SYMBOLS</b></p>	<p><b>ROCK HARDNESS</b></p> <table border="1"> <thead> <tr> <th>VERY HARD</th> <th>HARD</th> <th>MODERATELY HARD</th> <th>MEDIUM HARD</th> <th>SOFT</th> <th>VERY SOFT</th> <th>COMPLETE</th> </tr> </thead> <tbody> <tr> <td>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</td> <td>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</td> <td>CAN BE SCRATCHED BY KNIFE OR PICK OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</td> <td>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</td> <td>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</td> <td>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</td> <td>ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</td> </tr> </tbody> </table>	VERY HARD	HARD	MODERATELY HARD	MEDIUM HARD	SOFT	VERY SOFT	COMPLETE	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	CAN BE SCRATCHED BY KNIFE OR PICK OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.	<p><b>RECOMMENDATION SYMBOLS</b></p>	<p><b>ABBREVIATIONS</b></p> <table border="1"> <thead> <tr> <th>AR - AUGER REFUSAL</th> <th>BT - BORING TERMINATED</th> <th>CL - CLAY</th> <th>CPT - CONE PENETRATION TEST</th> <th>CSE - COARSE</th> <th>DMT - DILATOMETER TEST</th> <th>DPT - DYNAMIC PENETRATION TEST</th> <th>ø - VOID RATIO</th> <th>F - FINE</th> <th>FOSS. - FOSSILIFEROUS</th> <th>FRAC. - FRACTURED, FRACTURES</th> <th>FRAGS. - FRAGMENTS</th> <th>HI. - HIGHLY</th> <th>MED. - MEDIUM</th> <th>MICA. - MICACEOUS</th> <th>MOD. - MODERATELY</th> <th>NP - NON PLASTIC</th> <th>ORG. - ORGANIC</th> <th>PMT - PRESSUREMETER TEST</th> <th>SAP. - SAPROLITIC</th> <th>SD. - SAND, SANDY</th> <th>SL. - SILT, SILTY</th> <th>SLI. - SLIGHTLY</th> <th>TCR - TRICONE REFUSAL</th> <th>w - MOISTURE CONTENT</th> <th>V - VERY</th> <th>VST - VANE SHEAR TEST</th> <th>WEA. - WEATHERED</th> <th>γ<sub>u</sub> - UNIT WEIGHT</th> <th>γ<sub>d</sub> - DRY UNIT WEIGHT</th> <th>S - BULK</th> <th>SS - SPLIT SPOON</th> <th>ST - SHELBY TUBE</th> <th>RS - ROCK</th> <th>RT - RECOMPACTED TRIAXIAL</th> <th>CBR - CALIFORNIA BEARING RATIO</th> </tr> </thead> <tbody> <tr> <td>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td> <td>AR</td> <td>BT</td> <td>CL</td> <td>CPT</td> <td>CSE</td> <td>DMT</td> <td>DPT</td> <td>ø</td> <td>F</td> <td>FOSS.</td> <td>FRAC.</td> <td>FRAGS.</td> <td>HI.</td> <td>MED.</td> <td>MICA.</td> <td>MOD.</td> <td>NP</td> <td>ORG.</td> <td>PMT</td> <td>SAP.</td> <td>SD.</td> <td>SL.</td> <td>SLI.</td> <td>TCR</td> <td>w</td> <td>V</td> <td>VST</td> <td>WEA.</td> <td>γ<sub>u</sub></td> <td>γ<sub>d</sub></td> <td>S</td> <td>SS</td> <td>ST</td> <td>RS</td> <td>RT</td> <td>CBR</td> </tr> </tbody> </table>	AR - AUGER REFUSAL	BT - BORING TERMINATED	CL - CLAY	CPT - CONE PENETRATION TEST	CSE - COARSE	DMT - DILATOMETER TEST	DPT - DYNAMIC PENETRATION TEST	ø - VOID RATIO	F - FINE	FOSS. - FOSSILIFEROUS	FRAC. - FRACTURED, FRACTURES	FRAGS. - FRAGMENTS	HI. - HIGHLY	MED. - MEDIUM	MICA. - MICACEOUS	MOD. - MODERATELY	NP - NON PLASTIC	ORG. - ORGANIC	PMT - PRESSUREMETER TEST	SAP. - SAPROLITIC	SD. - SAND, SANDY	SL. - SILT, SILTY	SLI. - SLIGHTLY	TCR - TRICONE REFUSAL	w - MOISTURE CONTENT	V - VERY	VST - VANE SHEAR TEST	WEA. - WEATHERED	γ <sub>u</sub> - UNIT WEIGHT	γ <sub>d</sub> - DRY UNIT WEIGHT	S - BULK	SS - SPLIT SPOON	ST - SHELBY TUBE	RS - ROCK	RT - RECOMPACTED TRIAXIAL	CBR - CALIFORNIA BEARING RATIO	UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE	UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL	UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK	AR	BT	CL	CPT	CSE	DMT	DPT	ø	F	FOSS.	FRAC.	FRAGS.	HI.	MED.	MICA.	MOD.	NP	ORG.	PMT	SAP.	SD.	SL.	SLI.	TCR	w	V	VST	WEA.	γ <sub>u</sub>	γ <sub>d</sub>	S	SS	ST	RS	RT	CBR	<p><b>EQUIPMENT USED ON SUBJECT PROJECT</b></p> <table border="1"> <thead> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> CME-450</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td rowspan="2">CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -H <input type="checkbox"/> -N</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td rowspan="3">HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input checked="" type="checkbox"/> KESSLER DCP <input checked="" type="checkbox"/> CORING MACHINE</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> w/ ADVANCER <input type="checkbox"/> TRICONE <input type="checkbox"/> *STEEL TEETH <input type="checkbox"/> TRICONE <input type="checkbox"/> *TUNG-CARB. <input type="checkbox"/> CORE BIT <input type="checkbox"/></td> </tr> </tbody> </table>	DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> CME-450	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -H <input type="checkbox"/> -N	<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input checked="" type="checkbox"/> KESSLER DCP <input checked="" type="checkbox"/> CORING MACHINE	<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	<input type="checkbox"/>	<input type="checkbox"/> CASING <input type="checkbox"/> w/ ADVANCER <input type="checkbox"/> TRICONE <input type="checkbox"/> *STEEL TEETH <input type="checkbox"/> TRICONE <input type="checkbox"/> *TUNG-CARB. <input type="checkbox"/> CORE BIT <input type="checkbox"/>	<p><b>TEXTURE OR GRAIN SIZE</b></p> <table border="1"> <thead> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> </thead> <tbody> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F. SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>GRAIN SIZE MM 305 75 2.0 0.25 0.05 0.005</p>	U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)								<p><b>SOIL MOISTURE - CORRELATION OF TERMS</b></p> <table border="1"> <thead> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>LL</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PLASTIC RANGE (PI)</td> <td>- WET - (W)</td> <td>SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td></td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>OM</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>SL</td> <td></td> <td></td> </tr> </tbody> </table>	SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PLASTIC RANGE (PI)	- WET - (W)	SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE		- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	OM	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	SL			<p><b>PLASTICITY</b></p> <table border="1"> <thead> <tr> <th>NON PLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> </thead> <tbody> <tr> <td></td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </tbody> </table>	NON PLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH		0-5	VERY LOW	SLIGHTLY PLASTIC	6-15	SLIGHT	MODERATELY PLASTIC	16-25	MEDIUM	HIGHLY PLASTIC	26 OR MORE	HIGH	<p><b>COLOR</b></p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>	<p><b>FRACATURE SPACING</b></p> <table border="1"> <thead> <tr> <th>TERM</th> <th>SPACING</th> </tr> </thead> <tbody> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </tbody> </table>	TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FOOT	VERY CLOSE	LESS THAN 0.16 FEET	<p><b>BEDDING</b></p> <table border="1"> <thead> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> </thead> <tbody> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </tbody> </table>	TERM	THICKNESS	VERY THICKLY BEDDED	4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET	<p><b>INDURATION</b></p> <table border="1"> <thead> <tr> <th>FRAGILE</th> <th>MODERATELY INDURATED</th> <th>INDURATED</th> <th>EXTREMELY INDURATED</th> </tr> </thead> <tbody> <tr> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </tbody> </table>	FRAGILE	MODERATELY INDURATED	INDURATED	EXTREMELY INDURATED	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	<p><b>BENCH MARK:</b></p> <p>ELEVATION: FEET</p>	<p><b>NOTES:</b></p> <p>SURVEY INFORMATION AND DESIGN FILES PROVIDED BY TGS ENGINEERS</p>
GENERAL CLASS.	GRANULAR MATERIALS (≤ 35% PASSING #200)						SILT-CLAY MATERIALS (> 35% PASSING #200)						ORGANIC MATERIALS																																																																																																																																																																																																																																																																																																																																																																																																																															
GROUP CLASS.	A-1		A-3		A-2		A-4		A-5		A-6		A-7		A-1, A-2		A-3		A-4, A-5		A-6, A-7																																																																																																																																																																																																																																																																																																																																																																																																																							
SYMBOL	A-1-a		A-1-b		A-2-4		A-2-5		A-2-6		A-2-7		A-4		A-5		A-6		A-7		A-1, A-2																																																																																																																																																																																																																																																																																																																																																																																																																							
% PASSING #10 #40 #200	50 MX 30 MX 15 MX		50 MX 10 MX		50 MX 10 MX		35 MX 35 MX		35 MX 35 MX		35 MX 35 MX		35 MX 35 MX		35 MN 36 MN		36 MN 36 MN		36 MN 36 MN		GRANULAR SOILS SILT-CLAY SOILS MUCK, PEAT																																																																																																																																																																																																																																																																																																																																																																																																																							
MATERIAL PASSING #40 LL PI	-		-		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		40 MX 41 MN		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER HIGHLY ORGANIC SOILS																																																																																																																																																																																																																																																																																																																																																																																																																							
GROUP INDEX	0		0		0		4 MX		8 MX		12 MX		16 MX		NO MX																																																																																																																																																																																																																																																																																																																																																																																																																													
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS																																																																																																																																																																																																																																																																																																																																																																																																																																			
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD						FAIR TO POOR						FAIR TO POOR		POOR		UNSATURABLE																																																																																																																																																																																																																																																																																																																																																																																																																											
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30																																																																																																																																																																																																																																																																																																																																																																																																																																												
<p><b>CONSISTENCY OR DENSENESS</b></p> <table border="1"> <thead> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> </thead> <tbody> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 &gt; 4</td> </tr> </tbody> </table>	PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	<p><b>MISCELLANEOUS SYMBOLS</b></p>	<p><b>ROCK HARDNESS</b></p> <table border="1"> <thead> <tr> <th>VERY HARD</th> <th>HARD</th> <th>MODERATELY HARD</th> <th>MEDIUM HARD</th> <th>SOFT</th> <th>VERY SOFT</th> <th>COMPLETE</th> </tr> </thead> <tbody> <tr> <td>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</td> <td>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</td> <td>CAN BE SCRATCHED BY KNIFE OR PICK OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</td> <td>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</td> <td>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</td> <td>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.</td> <td>ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</td> </tr> </tbody> </table>	VERY HARD	HARD	MODERATELY HARD	MEDIUM HARD	SOFT	VERY SOFT	COMPLETE	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	CAN BE SCRATCHED BY KNIFE OR PICK OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.	<p><b>RECOMMENDATION SYMBOLS</b></p>	<p><b>ABBREVIATIONS</b></p> <table border="1"> <thead> <tr> <th>AR - AUGER REFUSAL</th> <th>BT - BORING TERMINATED</th> <th>CL - CLAY</th> <th>CPT - CONE PENETRATION TEST</th> <th>CSE - COARSE</th> <th>DMT - DILATOMETER TEST</th> <th>DPT - DYNAMIC PENETRATION TEST</th> <th>ø - VOID RATIO</th> <th>F - FINE</th> <th>FOSS. - FOSSILIFEROUS</th> <th>FRAC. - FRACTURED, FRACTURES</th> <th>FRAGS. - FRAGMENTS</th> <th>HI. - HIGHLY</th> <th>MED. - MEDIUM</th> <th>MICA. - MICACEOUS</th> <th>MOD. - MODERATELY</th> <th>NP - NON PLASTIC</th> <th>ORG. - ORGANIC</th> <th>PMT - PRESSUREMETER TEST</th> <th>SAP. - SAPROLITIC</th> <th>SD. - SAND, SANDY</th> <th>SL. - SILT, SILTY</th> <th>SLI. - SLIGHTLY</th> <th>TCR - TRICONE REFUSAL</th> <th>w - MOISTURE CONTENT</th> <th>V - VERY</th> <th>VST - VANE SHEAR TEST</th> <th>WEA. - WEATHERED</th> <th>γ<sub>u</sub> - UNIT WEIGHT</th> <th>γ<sub>d</sub> - DRY UNIT WEIGHT</th> <th>S - BULK</th> <th>SS - SPLIT SPOON</th> <th>ST - SHELBY TUBE</th> <th>RS - ROCK</th> <th>RT - RECOMPACTED TRIAXIAL</th> <th>CBR - CALIFORNIA BEARING RATIO</th> </tr> </thead> <tbody> <tr> <td>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td> <td>AR</td> <td>BT</td> <td>CL</td> <td>CPT</td> <td>CSE</td> <td>DMT</td> <td>DPT</td> <td>ø</td> <td>F</td> <td>FOSS.</td> <td>FRAC.</td> <td>FRAGS.</td> <td>HI.</td> <td>MED.</td> <td>MICA.</td> <td>MOD.</td> <td>NP</td> <td>ORG.</td> <td>PMT</td> <td>SAP.</td> <td>SD.</td> <td>SL.</td> <td>SLI.</td> <td>TCR</td> <td>w</td> <td>V</td> <td>VST</td> <td>WEA.</td> <td>γ<sub>u</sub></td> <td>γ<sub>d</sub></td> <td>S</td> <td>SS</td> <td>ST</td> <td>RS</td> <td>RT</td> <td>CBR</td> </tr> </tbody> </table>	AR - AUGER REFUSAL	BT - BORING TERMINATED	CL - CLAY	CPT - CONE PENETRATION TEST	CSE - COARSE	DMT - DILATOMETER TEST	DPT - DYNAMIC PENETRATION TEST	ø - VOID RATIO	F - FINE	FOSS. - FOSSILIFEROUS	FRAC. - FRACTURED, FRACTURES	FRAGS. - FRAGMENTS	HI. - HIGHLY	MED. - MEDIUM	MICA. - MICACEOUS	MOD. - MODERATELY	NP - NON PLASTIC	ORG. - ORGANIC	PMT - PRESSUREMETER TEST	SAP. - SAPROLITIC	SD. - SAND, SANDY	SL. - SILT, SILTY	SLI. - SLIGHTLY	TCR - TRICONE REFUSAL	w - MOISTURE CONTENT	V - VERY	VST - VANE SHEAR TEST	WEA. - WEATHERED	γ <sub>u</sub> - UNIT WEIGHT	γ <sub>d</sub> - DRY UNIT WEIGHT	S - BULK	SS - SPLIT SPOON	ST - SHELBY TUBE	RS - ROCK	RT - RECOMPACTED TRIAXIAL	CBR - CALIFORNIA BEARING RATIO	UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE	UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL	UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK	AR	BT	CL	CPT	CSE	DMT	DPT	ø	F	FOSS.	FRAC.	FRAGS.	HI.	MED.	MICA.	MOD.	NP	ORG.	PMT	SAP.	SD.	SL.	SLI.	TCR	w	V	VST	WEA.	γ <sub>u</sub>	γ <sub>d</sub>	S	SS	ST	RS	RT	CBR	<p><b>EQUIPMENT USED ON SUBJECT PROJECT</b></p> <table border="1"> <thead> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> CME-450</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td rowspan="2">CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -H <input type="checkbox"/> -N</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td rowspan="3">HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input checked="" type="checkbox"/> KESSLER DCP <input checked="" type="checkbox"/> CORING MACHINE</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> w/ ADVANCER <input type="checkbox"/> TRICONE <input type="checkbox"/> *STEEL TEETH <input type="checkbox"/> TRICONE <input type="checkbox"/> *TUNG-CARB. <input type="checkbox"/> CORE BIT <input type="checkbox"/></td> </tr> </tbody> </table>	DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> CME-450	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -H <input type="checkbox"/> -N	<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input checked="" type="checkbox"/> KESSLER DCP <input checked="" type="checkbox"/> CORING MACHINE	<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	<input type="checkbox"/>	<input type="checkbox"/> CASING <input type="checkbox"/> w/ ADVANCER <input type="checkbox"/> TRICONE <input type="checkbox"/> *STEEL TEETH <input type="checkbox"/> TRICONE <input type="checkbox"/> *TUNG-CARB. <input type="checkbox"/> CORE BIT <input type="checkbox"/>	<p><b>TEXTURE OR GRAIN SIZE</b></p> <table border="1"> <thead> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> </thead> <tbody> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F. SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>GRAIN SIZE MM 305 75 2.0 0.25 0.05 0.005</p>	U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)								<p><b>SOIL MOISTURE - CORRELATION OF TERMS</b></p> <table border="1"> <thead> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>LL</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PLASTIC RANGE (PI)</td> <td>- WET - (W)</td> <td>SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td></td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>OM</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>SL</td> <td></td> <td></td> </tr> </tbody> </table>	SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PLASTIC RANGE (PI)	- WET - (W)	SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE		- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	OM	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	SL			<p><b>PLASTICITY</b></p> <table border="1"> <thead> <tr> <th>NON PLASTIC</th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> </thead> <tbody> <tr> <td></td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </tbody> </table>	NON PLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH		0-5	VERY LOW	SLIGHTLY PLASTIC	6-15	SLIGHT	MODERATELY PLASTIC	16-25	MEDIUM	HIGHLY PLASTIC	26 OR MORE	HIGH	<p><b>COLOR</b></p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>	<p><b>FRACATURE SPACING</b></p> <table border="1"> <thead> <tr> <th>TERM</th> <th>SPACING</th> </tr> </thead> <tbody> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </tbody> </table>	TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FOOT	VERY CLOSE	LESS THAN 0.16 FEET	<p><b>BEDDING</b></p> <table border="1"> <thead> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> </thead> <tbody> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </tbody> </table>	TERM	THICKNESS	VERY THICKLY BEDDED	4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET	<p><b>INDURATION</b></p> <table border="1"> <thead> <tr> <th>FRAGILE</th> <th>MODERATELY INDURATED</th> <th>INDURATED</th> <th>EXTREMELY INDURATED</th> </tr> </thead> <tbody> <tr> <td>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> <td>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> <td>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> <td>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </tbody> </table>	FRAGILE	MODERATELY INDURATED	INDURATED	EXTREMELY INDURATED	RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	<p><b>BENCH MARK:</b></p> <p>ELEVATION: FEET</p>	<p><b>NOTES:</b></p> <p>SURVEY INFORMATION AND DESIGN FILES PROVIDED BY TGS ENGINEERS</p>																																																																																																																																																																																																								
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )																																																																																																																																																																																																																																																																																																																																																																																																																																									
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																																																																																																																																																																																																																																																																																																									
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																																																																																																																																																																																																																																																																																																																																																									
VERY HARD	HARD	MODERATELY HARD	MEDIUM HARD	SOFT	VERY SOFT	COMPLETE																																																																																																																																																																																																																																																																																																																																																																																																																																						
CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	CAN BE SCRATCHED BY KNIFE OR PICK OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGER NAIL.	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.																																																																																																																																																																																																																																																																																																																																																																																																																																						
AR - AUGER REFUSAL	BT - BORING TERMINATED	CL - CLAY	CPT - CONE PENETRATION TEST	CSE - COARSE	DMT - DILATOMETER TEST	DPT - DYNAMIC PENETRATION TEST	ø - VOID RATIO	F - FINE	FOSS. - FOSSILIFEROUS	FRAC. - FRACTURED, FRACTURES	FRAGS. - FRAGMENTS	HI. - HIGHLY	MED. - MEDIUM	MICA. - MICACEOUS	MOD. - MODERATELY	NP - NON PLASTIC	ORG. - ORGANIC	PMT - PRESSUREMETER TEST	SAP. - SAPROLITIC	SD. - SAND, SANDY	SL. - SILT, SILTY	SLI. - SLIGHTLY	TCR - TRICONE REFUSAL	w - MOISTURE CONTENT	V - VERY	VST - VANE SHEAR TEST	WEA. - WEATHERED	γ <sub>u</sub> - UNIT WEIGHT	γ <sub>d</sub> - DRY UNIT WEIGHT	S - BULK	SS - SPLIT SPOON	ST - SHELBY TUBE	RS - ROCK	RT - RECOMPACTED TRIAXIAL	CBR - CALIFORNIA BEARING RATIO																																																																																																																																																																																																																																																																																																																																																																																																									
UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE	UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL	UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK	AR	BT	CL	CPT	CSE	DMT	DPT	ø	F	FOSS.	FRAC.	FRAGS.	HI.	MED.	MICA.	MOD.	NP	ORG.	PMT	SAP.	SD.	SL.	SLI.	TCR	w	V	VST	WEA.	γ <sub>u</sub>	γ <sub>d</sub>	S	SS	ST	RS	RT	CBR																																																																																																																																																																																																																																																																																																																																																																																																						
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																																																																																																																																																																																																																																																																																																																																																										
<input type="checkbox"/> CME-450	<input type="checkbox"/> CLAY BITS	<input type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																																																																																																																																																																																																																																																																																																																																										
<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE: <input type="checkbox"/> -B <input type="checkbox"/> -H <input type="checkbox"/> -N																																																																																																																																																																																																																																																																																																																																																																																																																																										
<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS																																																																																																																																																																																																																																																																																																																																																																																																																																											
<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	HAND TOOLS: <input type="checkbox"/> POST HOLE DIGGER <input checked="" type="checkbox"/> HAND AUGER <input type="checkbox"/> SOUNDING ROD <input checked="" type="checkbox"/> KESSLER DCP <input checked="" type="checkbox"/> CORING MACHINE																																																																																																																																																																																																																																																																																																																																																																																																																																										
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS																																																																																																																																																																																																																																																																																																																																																																																																																																											
<input type="checkbox"/>	<input type="checkbox"/> CASING <input type="checkbox"/> w/ ADVANCER <input type="checkbox"/> TRICONE <input type="checkbox"/> *STEEL TEETH <input type="checkbox"/> TRICONE <input type="checkbox"/> *TUNG-CARB. <input type="checkbox"/> CORE BIT <input type="checkbox"/>																																																																																																																																																																																																																																																																																																																																																																																																																																											
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																																																																																																																																																																																																																																																																																						
	4.75	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																																																																																																																																																																																																																																																																																						
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																																																																																																																																																																																																																																																																																						
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																																																																																																																																																																																																																																																																										
LL	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																																																																																																																																																																																																																																																																										
PLASTIC RANGE (PI)	- WET - (W)	SEMI-SOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																																																																																																																																																																																																																																																										
	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																																																																																																																																																																																																																																																																										
OM	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																																																																																																																																																																																																																																																																										
SL																																																																																																																																																																																																																																																																																																																																																																																																																																												
NON PLASTIC	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																																																																																																																																																																																																																																																																																										
	0-5	VERY LOW																																																																																																																																																																																																																																																																																																																																																																																																																																										
SLIGHTLY PLASTIC	6-15	SLIGHT																																																																																																																																																																																																																																																																																																																																																																																																																																										
MODERATELY PLASTIC	16-25	MEDIUM																																																																																																																																																																																																																																																																																																																																																																																																																																										
HIGHLY PLASTIC	26 OR MORE	HIGH																																																																																																																																																																																																																																																																																																																																																																																																																																										
TERM	SPACING																																																																																																																																																																																																																																																																																																																																																																																																																																											
VERY WIDE	MORE THAN 10 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																											
WIDE	3 TO 10 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																											
MODERATELY CLOSE	1 TO 3 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																											
CLOSE	0.16 TO 1 FOOT																																																																																																																																																																																																																																																																																																																																																																																																																																											
VERY CLOSE	LESS THAN 0.16 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																											
TERM	THICKNESS																																																																																																																																																																																																																																																																																																																																																																																																																																											
VERY THICKLY BEDDED	4 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																											
THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																											
THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																											
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																											
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																											
THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																																																																																																																																																																																																																																																																																											
FRAGILE	MODERATELY INDURATED	INDURATED	EXTREMELY INDURATED																																																																																																																																																																																																																																																																																																																																																																																																																																									
RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																																																																																																																																																																																																																																																																																																																																									

See Sheet 1A For Index of Sheets

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-6055	1	23
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
47166.1.1		PE	

**TIP PROJECT: U-6055**





STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

**HAYWOOD COUNTY**

**LOCATION: INTERSECTION OF PISGAH DR (NC 110), HOLTZCLAW ST, AND LOCUST ST IN THE TOWN OF CANTON**

**TYPE OF WORK: GRADING, PAVING, DRAINAGE, AND CURB & GUTTER**

**BEGIN TIP PROJECT U-6055**  
**-L- STA. 12 + 00.00**




CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II. THIS PROJECT IS WITHIN THE MUNICIPAL BOUNDARIES OF THE TOWN OF CANTON.

**INCOMPLETE PLANS**  
DO NOT USE FOR R/W ACQUISITION  
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

**CONTRACT:**

<p><b>GRAPHIC SCALES</b></p> <p>20 10 0 20 40 PLANS</p> <p>20 10 0 20 40 PROFILE (HORIZONTAL)</p> <p>4 2 0 4 8 PROFILE (VERTICAL)</p>	<p><b>DESIGN DATA</b></p> <p>ADT 2019 = 8,100 ADT 2040 = 9,980 V = 30 MPH</p> <p>FUNC CLASS = URBAN ARTERIAL REGIONAL TIER</p>	<p><b>PROJECT LENGTH</b></p> <p>LENGTH ROADWAY TIP PROJECT U-6055 = 0.150 MILES TOTAL LENGTH TIP PROJECT U-6055 = 0.150 MILES</p>	<p><b>NCDOT CONTACT:</b> STEVE WILLIAMS</p>	<p><b>HYDRAULICS ENGINEER</b></p>	
			<p><b>PLANS PREPARED BY:</b></p> <p><b>TGS ENGINEERS</b> 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH: (704) 476-0003 CORP. LICENSE NO. C-0275</p>	<p><b>PLANS PREPARED FOR:</b></p> <p>NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION 14 253 WEBSTER RD SYLVA, NC 28779</p>	<p><b>RIGHT OF WAY DATE:</b></p>
			<p><b>LETTING DATE:</b></p>	<p><b>SANDRA G. MELVIN</b> PROJECT DESIGN ENGINEER</p>	<p>SIGNATURE: _____ P.E.</p>



3/23/2017 X:\NCDOT\U-6055\Roadway\Proj\U-6055\_Rdy\_1.sh.dgn User:smelvin



## ECS Southeast, LLP

1812 Center Park Drive, Suite D  
Charlotte, NC 28217  
T 704.525.5152 | F 704.357.0023  
www.ecslimited.com

September 26, 2018

WBS NO: N/A  
TIP NO: U-6055  
F.A. NUMBER: N/A  
COUNTY: Haywood  
DESCRIPTION: Intersection of Pisgah Drive (NC 110), Holtzclaw Street, and Locus Street in the Town of Canton

**SUBJECT: Geotechnical Report – Inventory**

### Project Description

The project site is at the intersection of Pisgah Drive (NC 110), Holtzclaw Street, and Locus Street in Canton, North Carolina. We understand improvements to intersection will consist of the addition of a traffic circle with lane widening and associated sidewalk, curb, and gutter.

The project consists of the construction of a roundabout with various roadway improvements at the intersection of NC 110 and Pisgah Drive in Canton, North Carolina. The following roads are included as part of this exploration:

<u>Line</u>	<u>Road Name</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	NC 110/Pisgah Drive	12+00 to 14+10	LT to RT
-Y-	Johnston Street	10+00 to 10+25	LT to RT
-Y1-	NC 110/Pisgah Drive	10+70 to 12+52	LT to RT
-Y2-	Holtzclaw Street	10+00 to 11+50	LT to RT
-Y3-	Locust Street	10+00 to 12+50	LT to RT
-Y4-	Hillside Street	10+55 to 11+94	LT to RT

A geotechnical field investigation was performed by ECS on May 25 & 26, 2017. During this time period, a total of eleven (11) Hand Auger (HA) borings (4 pavement borings, 4 roadway borings, and 3 slope borings) were advanced with a hand auger. Hand auger DCP testing and Kessler DCP testing was performed in general accordance with applicable ASTM standards. Representative soil samples were collected for visual classification in the field and for analysis by ECS's testing laboratory.

A project slope along Hillside Street and Locust Street was encountered at the following locations:

<u>Location</u>	<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
Cut Slope	-Y3-	11+81 to 12+50	LT
Cut Slope	-Y4-	10+55 to 11+94	LT

### Site Description

The project corridor is comprised mainly of residential and commercial properties. The project is centered around the intersection of Pisgah Drive, Holtzclaw Street and Locust Street. At approximate Station 14+10 -L-, a roundabout will be constructed at the 4-way intersection. From the roundabout, intersection improvements will continue north along Locust Street and west along Hillside Street.

The road elevations along the various alignments are generally sloping and range from approximately 2,661 to 2,611 feet. Soils encountered in the proposed widened areas generally consisted of surficial organic materials underlain by roadway embankment and residual soils. Based on the Roadway Plans provided to us by TGS Engineers, a majority of the widening will occur along -L-, -Y1-, and -Y3-. Mass grading will generally be limited to the existing shoulders and new pavement areas with cut and fill depths on the order of approximately 4 feet or less. The existing slope on -Y3- and -Y4- will be re-graded with a cut of approximately 10 to 14 feet. The slope inclination will be decreased from 1H:1V (existing) to 1.5H:1V.

### Areas of Special Geotechnical Interest

- 1) Artificial Fill: The following areas encountered artificial fill. Artificial fill poses risks associated with undetected deleterious inclusions or soft zones within the fill and/or deleterious materials at the virgin ground/fill interface.

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	13+50 to 14+50	LT
-Y2-	10+50 to 11+00	RT

- 2) **Moderate to High Plasticity Soils:** The following areas contain moderate to high plasticity soils with plasticity indices (PI's) in excess of 25. These soils have the potential to cause subgrade problems during construction, embankment stability or long term settlement problems:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-Y2-	10+50 to 11+00	RT

- 3) **Wet or Saturated Soils:** The field exploration did not encounter soils with natural moisture contents in excess of the liquid limit or soils below the ground water table. During the field exploration, soils were labeled as wet at the following locations:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-Y2-	10+50 to 11+00	RT
-Y4-	11+25 to 11+75	LT

- 4) **Soft/Very Loose Soils:** The following areas contain relatively soft or very loose soils that have the potential for subgrade problems, embankment stability or long-term settlement problems during construction:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-Y2-	10+50 to 11+00	RT
-Y4-	10+55 11+94	LT

- 5) **Shallow Groundwater:** Shallow groundwater was not encountered within six feet of the proposed subgrade elevation at the locations explored on the project.
- 6) **Organic Soil:** Soils with little organic content with organic soil thicknesses in excess of 0.3 feet were not encountered at the locations explored on the project.

### **Physiography and Geology**

The site is located in the Coweeta Group of the Blue Ridge Physiographic Province of North Carolina. According the Geological Map of North Carolina, 1985, the Coweeta Group is in the Middle/Late Proterozoic geologic age consisting primarily of Biotite Gneiss (ZYbn) and amphibolite. The parent bedrock was not encountered at the locations and depths explored on the project. The virgin soils encountered are the residual product of in-place chemical weathering of rock that was similar to the rock presently underlying the site.

In general, the topography along a majority of the corridor is sloping. Soils encountered in the project corridor generally consisted of artificial fill soils underlain by residual soils.

### **Soil Properties**

The subsurface conditions discussed below represent the subsurface conditions based on interpretation of the boring data using normally accepted geotechnical engineering judgments. The transitions between different soil strata are usually less distinct than those shown on the Borelogs. Sometimes the relatively small sample obtained in the field is insufficient to definitively describe the origin of the subsurface material. Although individual soil test borings are representative of the subsurface conditions at the boring locations on the dates shown, they are not necessarily indicative of subsurface conditions at other locations or at other times.

Soils within the area of this project have been divided into two categories: artificial fill and residual soils.

**Artificial Fill:** Artificial fill (A.F.) soils were encountered along the following alignments and at the approximate stationing:

<u>Line</u>	<u>Station (±)</u>	<u>Offsets</u>
-L-	13+50 to 14+50	LT
-Y2-	10+50 to 11+00	RT

The artificial fill encountered generally consisted of loose, brown, moist, silty fine to coarse sand (A-2-4), and very soft to soft, brown, moist to wet, silty clay (A-7-6) and extends to depths of approximately 2.0 feet below existing grades. Laboratory testing indicated a PI of 27 for the A-7-6 soil.

**Residual Soils:** Residual soils throughout the project corridor are derived from the weathering of the underlying parent bedrock. A majority of the residual soils encountered generally consisted of orange-brown-red, wet, very soft to medium stiff, fine sandy clay (A-6), orange-brown-red, moist, very soft to very stiff, fine sandy, silt (A-4), or orange-brown, moist, loose to medium dense, silty fine sand (A-2-4). Laboratory testing indicated PI's ranging from 7 to 9 for the A-4 soils.

### **Groundwater Properties**

Groundwater levels were measured in the borings both immediately after augering and, where applicable, after a stabilization period of at least 24 hours. At the time of drilling, ground water was not encountered in any of the borings. For safety reasons, several of the borings located in or in close proximity to the roadway were backfilled immediately after augering making stabilized water readings unobtainable.

*No geotechnical cross sections or profiles will be included as part of this inventory report.*

Respectively submitted,



DocuSigned by:  
*D. Matthew Brewer*  
0EAF318632CF43A...  
D. Matthew Brewer, P.E.  
Senior Project Engineer

DocuSigned by:  
*Michael J. Walko* 09/26/18  
99589EECD3814D9...  
Michael J. Walko, P.E.  
Principal Engineer  
N.C. Registration No. 026917

-L- CURVE DATA	-Y1- CURVE DATA	-Y2- CURVE DATA
PI Sta 13+08.52 Δ = 22° 57' 33.0" (LT) D = 22' 55' 05.9" L = 100.18' T = 50.77' R = 250.00' SE = 02 DS = 25 MPH	PI Sta 10+87.53 Δ = 5° 15' 45.0" (RT) D = 3' 41' 47.4" L = 142.36' T = 71.23' R = 1550.00' SE = NC DS = 45 MPH	PI Sta 11+00.02 Δ = 14° 08' 54.6" (RT) D = 8' 11' 06.4" L = 172.86' T = 86.87' R = 700.00' SE = 03 DS = 40 MPH
① -L-PC 12+57.75 ② -L-PT 13+57.93		③ -Y2-PC 10+13.15

-Y3- CURVE DATA		-Y4- CURVE DATA	
PI Sta 11+44.84 Δ = 15° 17' 45.1" (RT) D = 22' 55' 05.9" L = 66.74' T = 33.57' R = 250.00' SE = 02 DS = 25 MPH	PI Sta 12+61.87 Δ = 73° 57' 13.4" (RT) D = 88' 08' 50.5" L = 83.90' T = 48.94' R = 65.00' SE = EXIST.	PI Sta 10+24.92 Δ = 14° 12' 20.8" (LT) D = 28' 38' 52.4" L = 49.59' T = 24.92' R = 200.00' SE = 03 DS = 20 MPH	PI Sta 11+40.70 Δ = 22° 41' 35.3" (RT) D = 57' 17' 44.8" L = 39.61' T = 20.07' R = 100.00' SE = 03 DS = 20 MPH

**BEGIN CONSTRUCTION**  
-Y1- STA. 10+70.00


**BEGIN CONSTRUCTION**  
-Y4- STA. 10+55.00



**BEGIN TIP**  
PROJECT U-6055  
-L- STA. 12+00.00

**END CONSTRUCTION**  
-Y- STA. 10+25.00

**END CONSTRUCTION**  
-Y2- STA. 11+50.00

**END TIP**  
PROJECT U-6055  
-Y3- STA. 12+50.00

PROJECT REFERENCE NO. <b>U-6055</b>	SHEET NO. <b>4</b>
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	
 TGS ENGINEERS 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH: (704) 476-0003 CORP. LICENSE NO.: C-0275	



FOR ROUNDABOUT LAYOUT SEE SHEET NO. 2B-1  
 FOR -L-, -Y1- & -Y2- PROFILES, SEE SHEET NO. 5  
 FOR -Y3- & -Y4- PROFILES, SEE SHEET NO. 6

REVISIONS  
 28-JUN-2017 18:39  
 15-DEC-2017 14:32  
 PROJECTS\12000-12999\12100\12175 - U-6055 Pisgah Drive Roadway Improvement Project\CA00.GEOTECH\PlanProf\U-6055\_geo\_psh\_04.dgn

# GEOTECHNICAL BORING REPORT

## BORE LOG

WBS N/A		TIP U-6055		COUNTY HAYWOOD		GEOLOGIST S. Sawyer										
SITE DESCRIPTION Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							GROUND WTR (ft)									
BORING NO. HA-1		STATION 10+66		OFFSET 28 ft LT		ALIGNMENT -Y4-										
COLLAR ELEV. 2,673.3 ft		TOTAL DEPTH 7.5 ft		NORTHING 669,045		EASTING 858,829										
DRILL RIG/HAMMER EFF./DATE N/A			DRILL METHOD Hand Auger			HAMMER TYPE Automatic										
DRILLER S. Sawyer		START DATE 05/25/17		COMP. DATE 05/25/17		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
2675														2,673.3	0.0	GROUND SURFACE
2670														2,669.3	4.0	RESIDUAL Very Soft to Medium Stiff, Wet, Orange-Brown, Fine Sandy CLAY (A-6), with trace organics.
														2,667.3	6.0	Stiff, Moist, Orange-Brown, Fine Sandy SILT (A-4).
														2,665.8	7.5	Medium Dense, Moist, Brown, Silty Fine to Coarse SAND (A-2-4). Boring Terminated at Elevation 2,665.8 ft In Residual Silty Fine to Coarse Sand (A-2-4)  - Hand Auger Refusal at 7.5 feet.

WBS N/A		TIP U-6055		COUNTY HAYWOOD		GEOLOGIST S. Sawyer										
SITE DESCRIPTION Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							GROUND WTR (ft)									
BORING NO. HA-2		STATION 11+11		OFFSET 41 ft LT		ALIGNMENT -Y4-										
COLLAR ELEV. 2,676.1 ft		TOTAL DEPTH 6.5 ft		NORTHING 669,050		EASTING 858,875										
DRILL RIG/HAMMER EFF./DATE N/A			DRILL METHOD Hand Auger			HAMMER TYPE Automatic										
DRILLER S. Sawyer		START DATE 05/25/17		COMP. DATE 05/25/17		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
2680														2,676.1	0.0	GROUND SURFACE
2675														2,673.1	3.0	RESIDUAL Very Soft to Soft, Wet, Orange-Brown, Fine Sandy SILT (A-4), with trace organics.
2670														2,669.6	6.5	Loose to Medium Dense, Moist, Orange-Brown, Silty Fine to Coarse SAND (A-2-4), with trace gravel-sized rock fragments. Boring Terminated at Elevation 2,669.6 ft In Residual Silty Fine to Coarse Sand (A-2-4)  - Hand Auger Refusal at 6.5 feet.

NCDOT BORE DOUBLE U-6055\_GEO\_BORELOGS.GPJ NC\_DOT.GDT 6/28/17



# GEOTECHNICAL BORING REPORT

## BORE LOG

WBS N/A		TIP U-6055		COUNTY HAYWOOD		GEOLOGIST S. Sawyer									
SITE DESCRIPTION Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							GROUND WTR (ft)								
BORING NO. HA-3		STATION 11+55		OFFSET 48 ft LT		ALIGNMENT -Y4-									
COLLAR ELEV. 2,671.4 ft		TOTAL DEPTH 7.0 ft		NORTHING 669,037		EASTING 858,934									
DRILL RIG/HAMMER EFF./DATE N/A			DRILL METHOD Hand Auger			HAMMER TYPE Automatic									
DRILLER S. Sawyer		START DATE 05/25/17		COMP. DATE 05/25/17		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG MOI	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
2675															
														2,671.4	GROUND SURFACE 0.0
2670														2,668.4	RESIDUAL Very Soft to Medium Stiff, Wet, Orange-Brown, Fine Sandy CLAY (A-6), with trace organics. 3.0
														2,666.4	Medium Stiff to Stiff, Moist, Orange-Brown, Fine Sandy SILT (A-4). 5.0
2665														2,664.4	Medium Dense, Moist, Brown, Silty Fine to Coarse SAND (A-2-4). 7.0
															Boring Terminated at Elevation 2,664.4 ft In Residual Silty Fine to Coarse Sand (A-2-4)  - Hand Auger Refusal at 7.0 feet.

WBS N/A		TIP U-6055		COUNTY HAYWOOD		GEOLOGIST S. Sawyer									
SITE DESCRIPTION Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							GROUND WTR (ft)								
BORING NO. HA-4		STATION 11+76		OFFSET 15 ft LT		ALIGNMENT -Y3-									
COLLAR ELEV. 2,648.5 ft		TOTAL DEPTH 6.0 ft		NORTHING 668,976		EASTING 858,925									
DRILL RIG/HAMMER EFF./DATE N/A			DRILL METHOD Hand Auger			HAMMER TYPE Automatic									
DRILLER S. Sawyer		START DATE 05/25/17		COMP. DATE 05/25/17		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG MOI	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
2650															
														2,648.5	GROUND SURFACE 0.0
2645														2,645.5	RESIDUAL Medium Stiff to Stiff, Moist, Red-Brown, Fine Sandy SILT (A-4(3)), with trace organics. 3.0
														2,642.5	Medium Dense, Moist, Brown, Silty Fine to Coarse SAND (A-2-4), with trace mica. 6.0
															Boring Terminated at Elevation 2,642.5 ft In Residual Silty Fine to Coarse Sand (A-2-4)

NCDOT BORE DOUBLE U-6055\_GEO\_BORELOGS.GPJ NC\_DOT.GDT 6/28/17

# GEOTECHNICAL BORING REPORT

## BORE LOG

WBS N/A		TIP U-6055		COUNTY HAYWOOD		GEOLOGIST S. Sawyer									
SITE DESCRIPTION Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							GROUND WTR (ft)								
BORING NO. HA-5		STATION 10+74		OFFSET 12 ft LT		ALIGNMENT -Y3-									
COLLAR ELEV. 2,630.6 ft		TOTAL DEPTH 6.0 ft		NORTHING 668,880		EASTING 858,889									
DRILL RIG/HAMMER EFF./DATE N/A			DRILL METHOD Hand Auger			HAMMER TYPE Automatic									
DRILLER S. Sawyer		START DATE 05/25/17		COMP. DATE 05/25/17		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG MOI	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
2635															
2630														2,630.6	0.0
														2,627.6	3.0
2625														2,624.6	6.0
Boring Terminated at Elevation 2,624.6 ft In Residual Silty Fine to Coarse Sand (A-2-4)															

WBS N/A		TIP U-6055		COUNTY HAYWOOD		GEOLOGIST S. Sawyer									
SITE DESCRIPTION Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							GROUND WTR (ft)								
BORING NO. HA-6		STATION 13+82		OFFSET 24 ft LT		ALIGNMENT -L-									
COLLAR ELEV. 2,623.0 ft		TOTAL DEPTH 7.0 ft		NORTHING 668,777		EASTING 858,855									
DRILL RIG/HAMMER EFF./DATE N/A			DRILL METHOD Hand Auger			HAMMER TYPE Automatic									
DRILLER S. Sawyer		START DATE 05/25/17		COMP. DATE 05/25/17		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG MOI	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100					
2625															
														2,623.0	0.0
														2,621.0	2.0
														2,617.0	6.0
														2,616.0	7.0
Boring Terminated at Elevation 2,616.0 ft In Residual Silty Fine to Coarse Sand (A-2-4)															

NCDOT BORE DOUBLE U-6055\_GEO\_BORELOGS.GPJ NC\_DOT.GDT 6/28/17

# GEOTECHNICAL BORING REPORT

## BORE LOG

WBS N/A		TIP U-6055		COUNTY HAYWOOD		GEOLOGIST S. Sawyer										
SITE DESCRIPTION Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							GROUND WTR (ft)									
BORING NO. HA-7		STATION 10+67		OFFSET 13 ft RT		ALIGNMENT -Y2-										
COLLAR ELEV. 2,626.9 ft		TOTAL DEPTH 6.0 ft		NORTHING 668,791		EASTING 858,944										
DRILL RIG/HAMMER EFF./DATE N/A			DRILL METHOD Hand Auger			HAMMER TYPE Automatic										
DRILLER S. Sawyer		START DATE 05/25/17		COMP. DATE 05/25/17		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
2630																
															2,626.9	0.0
															2,624.9	2.0
2625															2,622.9	4.0
															2,620.9	6.0

WBS N/A		TIP U-6055		COUNTY HAYWOOD		GEOLOGIST S. Sawyer										
SITE DESCRIPTION Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							GROUND WTR (ft)									
BORING NO. HA-8		STATION 11+44		OFFSET 2 ft RT		ALIGNMENT -Y1-										
COLLAR ELEV. 2,627.0 ft		TOTAL DEPTH 5.0 ft		NORTHING 668,845		EASTING 858,776										
DRILL RIG/HAMMER EFF./DATE N/A			DRILL METHOD Hand Auger			HAMMER TYPE Automatic										
DRILLER S. Sawyer		START DATE 05/26/17		COMP. DATE 05/26/17		SURFACE WATER DEPTH N/A										
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)	
			0.5ft	0.5ft	0.5ft	0	25	50	75	100						
2630																
															2,627.0	0.0
															2,625.8	1.2
2625															2,624.0	3.0
															2,622.0	5.0

NCDOT BORE DOUBLE U-6055\_GEO\_BORELOGS.GPJ NC\_DOT.GDT 6/28/17

# GEOTECHNICAL BORING REPORT

## BORE LOG

<b>WBS</b> N/A		<b>TIP</b> U-6055		<b>COUNTY</b> HAYWOOD		<b>GEOLOGIST</b> S. Sawyer											
<b>SITE DESCRIPTION</b> Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							<b>GROUND WTR (ft)</b>										
<b>BORING NO.</b> HA-9		<b>STATION</b> 12+22		<b>OFFSET</b> 5 ft LT		<b>ALIGNMENT</b> -Y3-											
<b>COLLAR ELEV.</b> 2,655.6 ft		<b>TOTAL DEPTH</b> 3.0 ft		<b>NORTHING</b> 669,012		<b>EASTING</b> 858,961											
<b>DRILL RIG/HAMMER EFF./DATE</b> N/A				<b>DRILL METHOD</b> Hand Auger		<b>HAMMER TYPE</b> Automatic											
<b>DRILLER</b> S. Sawyer		<b>START DATE</b> 05/26/17		<b>COMP. DATE</b> 05/26/17		<b>SURFACE WATER DEPTH</b> N/A											
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100							
2660																	
2655															2,655.6	GROUND SURFACE	0.0
															2,654.4	Asphalt (0.4) and ABC Stone (0.8')	1.2
															2,652.6	<b>RESIDUAL</b> Moist, Brown, Silty Fine SAND (A-2-4)	3.0
																Boring Terminated at Elevation 2,652.6 ft In Residual Silty Fine Sand (A-2-4)	
																	- Hand Auger Refusal at 3.0 feet.

<b>WBS</b> N/A		<b>TIP</b> U-6055		<b>COUNTY</b> HAYWOOD		<b>GEOLOGIST</b> S. Sawyer											
<b>SITE DESCRIPTION</b> Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							<b>GROUND WTR (ft)</b>										
<b>BORING NO.</b> HA-10		<b>STATION</b> 10+18		<b>OFFSET</b> 21 ft RT		<b>ALIGNMENT</b> -Y3-											
<b>COLLAR ELEV.</b> 2,625.9 ft		<b>TOTAL DEPTH</b> 5.0 ft		<b>NORTHING</b> 668,817		<b>EASTING</b> 858,903											
<b>DRILL RIG/HAMMER EFF./DATE</b> N/A				<b>DRILL METHOD</b> Hand Auger		<b>HAMMER TYPE</b> Automatic											
<b>DRILLER</b> S. Sawyer		<b>START DATE</b> 05/26/17		<b>COMP. DATE</b> 05/26/17		<b>SURFACE WATER DEPTH</b> N/A											
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION	DEPTH (ft)		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100							
2630																	
2625															2,625.9	GROUND SURFACE	0.0
															2,625.1	Asphalt (0.2') and ABC Stone (0.6')	0.8
																<b>RESIDUAL</b> Moist, Red-Brown, Fine Sandy CLAY (A-6)	5.0
															2,620.9	Boring Terminated at Elevation 2,620.9 ft In Residual Fine Sandy Clay (A-6)	

NCDOT BORE DOUBLE U-6055\_GEO\_BORELOGS.GPJ NC\_DOT.GDT 6/28/17

# GEOTECHNICAL BORING REPORT

## BORE LOG

WBS N/A		TIP U-6055		COUNTY HAYWOOD		GEOLOGIST S. Sawyer									
SITE DESCRIPTION Intersection of Pisgah Drive (NC 110), Holzclaw Street, & Locust Street in Town of Canton							GROUND WTR (ft)								
BORING NO. HA-11		STATION 12+82		OFFSET 12 ft RT		ALIGNMENT -L-	0 HR. Dry								
COLLAR ELEV. 2,615.7 ft		TOTAL DEPTH 5.0 ft		NORTHING 668,675		EASTING 858,881	24 HR. Dry								
DRILL RIG/HAMMER EFF./DATE N/A				DRILL METHOD Hand Auger		HAMMER TYPE Automatic									
DRILLER S. Sawyer		START DATE 05/26/17		COMP. DATE 05/26/17		SURFACE WATER DEPTH N/A									
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION		
			0.5ft	0.5ft	0.5ft	0	25	50	75	100			ELEV. (ft)	DEPTH (ft)	
2620															
2615														2,615.7	GROUND SURFACE 0.0
														2,614.2	Asphalt (0.5') and ABC Stone (1.0'). 1.5
														2,610.7	<b>RESIDUAL</b> Moist, Orange-Brown, Fine Sandy SILT (A-4). 5.0
															Boring Terminated at Elevation 2,610.7 ft In Residual Fine Sandy Silt (A-4)

NCDOT BORE DOUBLE U-6055\_GEO\_BORELOGS.GPJ NC\_DOT.GDT 6/28/17

PROJECT REFERENCE NO.	SHEET NO.
U-6055	11

*NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT*

---

***SUBSURFACE INVESTIGATION***

---

*APPENDIX A  
LABORATORY TEST RESULTS*

**REFERENCE: U-6055**

**PROJECT: N/A**

*Prepared in the Office of:*



**ECS SOUTHEAST, LLP**  
1900 HENDERSONVILLE ROAD #10  
ASHEVILLE, NC 28803  
(828) 665-2377 [PHONE]  
NC REGISTERED  
ENGINEERING  
FIRM # F-1078

## SOIL TEST RESULTS

BORING NO.	SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
								C. SAND	F. SAND	SILT	CLAY	10	40	200		
HA-4	S-1	15' LT	11+76 -Y3-	0.0 - 1.0'	A-4(3)	38	7	25.2	23.0	26.9	24.9	98.0	83.0	55.0	22.7	*
HA-6	S-2	24' LT	13+82 -L-	2.0 - 6.0'	A-4(2)	37	9	31.2	22.1	23.0	23.7	95.0	74.0	48.0	18.1	*
HA-7	S-3	13' RT	10+67 -Y2-	0.0 - 2.0'	A-7-6(14)	50	27	25.4	15.6	13.4	45.6	99.0	84.0	60.0	22.6	*

LAB TECHNICIAN: DILLON KESTNER

NCDOT CERTIFICATION NO. 135-01-0816

SIGNATURE: \_\_\_\_\_

PROJECT REFERENCE NO.	SHEET NO.
U-6055	13

*NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT*

---

***SUBSURFACE INVESTIGATION***

---

***APPENDIX B  
HAND AUGER / DCP LOGS***

**REFERENCE: U-6055**

**PROJECT: N/A**

*Prepared in the Office of:*



**ECS SOUTHEAST, LLP**  
1900 HENDERSONVILLE ROAD #10  
ASHEVILLE, NC 28803  
(828) 665-2377 [PHONE]  
NC REGISTERED  
ENGINEERING  
FIRM # F-1078




**ECS** ECS SOUTHEAST, LLP  
 1812 Center Park Drive Suite D  
 Charlotte, North Carolina 28217  
 (704)525.5152

**Client** TGS Engineers  
**Project** U-6055 - Pisgah Road  
**Location** Canton, North Carolina  
**Job No.** 12175  
**Boring** HA-1 **Alignment** Y4  
**Station** 10+66 **Offset** 28' LT

Depth*	Soil Description
0.5 ft	Surficial Organic Soils
0 - 4 ft	Residual: Very Soft to Soft, Wet, Orange-Brown, Fine Sandy CLAY (A-6), with trace organics.
4 - 6 ft	Stiff, Moist, Orange-Brown, Fine Sandy SILT (A-4).
6 - 7.5 ft	Medium Dense, Moist, Brown, Silty Fine to Coarse SAND (A-2-4).
Hand Auger Refusal at 7.5 feet	

\*Depths are measured below soil subgrade.  
 \*\*Groundwater not encountered.

Dyanmic Cone Penetrometer Measurements per Drive Increments				
Depth	0" to 2"	2" to 3.75"	3.75" to 5.5"	Average
0.0	2	1	2	1.0
-1.0	2	2	3	2.0
-2.0	3	3	3	3.0
-3.0	5	7	7	7.0
-4.0	11	12	11	11.0
-5.0	14	13	16	14.0
-6.0	17	19	24	21.0
-7.0	26	32	34	33.0




**ECS** ECS SOUTHEAST, LLP  
 1812 Center Park Drive Suite D  
 Charlotte, North Carolina 28217  
 (704)525.5152

**Client** TGS Engineers  
**Project** U-6055 - Pisgah Road  
**Location** Canton, North Carolina  
**Job No.** 12175  
**Boring** HA-2 **Alignment** Y4  
**Station** 11+11 **Offset** 41' LT

Depth*	Soil Description
0.5 ft	Surficial Organic Soils
0 - 3 ft	Residual: Very Soft to Soft, Wet, Orange-Brown, Fine Sandy SILT (A-4), with trace organics.
3 - 6.5 ft	Loose to Medium Dense, Moist, Orange-Brown, Silty Fine to Coarse SAND (A-2-4), with trace gravel-sized rock fragments.
Hand Auger Refusal at 6.5 feet	

\*Depths are measured below soil subgrade.  
 \*\*Groundwater not encountered.

Dyanmic Cone Penetrometer Measurements per Drive Increments				
Depth	0" to 2"	2" to 3.75"	3.75" to 5.5"	Average
0.0	2	1	2	1.0
-1.0	2	1	3	2.0
-2.0	2	3	2	2.0
-3.0	5	5	9	7.0
-4.0	12	22	19	20.0
-5.0	16	23	19	21.0
-6.0	18	26	28	27.0
-6.5	26	28	34	31.0




**ECS** ECS SOUTHEAST, LLP  
 1812 Center Park Drive Suite D  
 Charlotte, North Carolina 28217  
 (704)525.5152

**Client** TGS Engineers  
**Project** U-6055 - Pisgah Road  
**Location** Canton, North Carolina  
**Job No.** 12175  
**Boring** HA-3 **Alignment** Y4  
**Station** 11+55 **Offset** 48' LT

Depth*	Soil Description
0.5 ft	Surficial Organic Soils
0 - 3 ft	Residual: Very Soft to Medium Stiff, Wet, Orange-Brown, Fine Sandy CLAY (A-6), with trace organics.
3 - 5 ft	Medium Stiff to Stiff, Moist, Orange-Brown, Fine sandy SILT (A-4).
5 - 7 ft	Medium Dense, Moist, Brown, Silty Fine to Coarse SAND (A-2-4).
Hand Auger Refusal at 7.0 feet	

\*Depths are measured below soil subgrade.  
 \*\*Groundwater not encountered.

Dyanmic Cone Penetrometer Measurements per Drive Increments				
Depth	0" to 2"	2" to 3.75"	3.75" to 5.5"	Average
0.0	1	2	1	1.0
-1.0	2	3	3	3.0
-2.0	4	5	6	5.0
-3.0	4	6	6	6.0
-4.0	12	12	13	12.0
-5.0	10	13	12	12.0
-6.0	20	22	24	23.0
-7.0	20	28	29	28.0




**ECS** ECS SOUTHEAST, LLP  
 1812 Center Park Drive Suite D  
 Charlotte, North Carolina 28217  
 (704)525.5152

**Client** TGS Engineers  
**Project** U-6055 - Pisgah Road  
**Location** Canton, North Carolina  
**Job No.** 12175  
**Boring** HA-4 **Alignment** Y3  
**Station** 11+76 **Offset** 15' LT

Depth*	Soil Description
Asphalt	None
ABC Stone	None
0 - 3 ft	Residual: Medium Stiff to Stiff, Moist, Red-Brown, Fine Sandy SILT (A-4(3)), with trace organics.
3 - 6 ft	Medium Dense, Moist, Brown, Silty Fine to Coarse SAND (A-2-4), with trace mica.
Hand Auger Terminated at 6.0 feet	

\*Depths are measured below soil subgrade.  
 \*\*Groundwater not encountered.

Dyanmic Cone Penetrometer Measurements per Drive Increments				
Depth	0" to 2"	2" to 3.75"	3.75" to 5.5"	Average
0.0	4	5	11	8.0
-1.0	9	8	12	10.0
-2.0	10	12	17	14.0
-3.0	12	16	12	14.0
-4.0	15	17	18	17.0
-5.0	20	18	23	20.0
-6.0	21	26	24	25.0



**ECS** ECS SOUTHEAST, LLP  
 1812 Center Park Drive Suite D  
 Charlotte, North Carolina 28217  
 (704)525.5152


**Client** TGS Engineers  
**Project** U-6055 - Pisgah Road  
**Location** Canton, North Carolina  
**Job No.** 12175  
**Boring** HA-5 **Alignment** Y3  
**Station** 10+74 **Offset** 12' LT

Depth*	Soil Description
Asphalt	None
ABC Stone	None
0 - 3 ft	Residual: Medium Stiff to Stiff, Moist, Red-Brown, Fine Sandy SILT (A-4), with trace organics.
3 - 6 ft	Medium Dense, Moist, Brown, Silty Fine to Coarse SAND (A-2-4), with trace mica.
Hand Auger Terminated at 6.0 feet	

\*Depths are measured below soil subgrade.  
 \*\*Groundwater not encountered.

Dyanmic Cone Penetrometer Measurements per Drive Increments				
Depth	0" to 2"	2" to 3.75"	3.75" to 5.5"	Average
0.0	4	8	8	8.0
-1.0	10	9	11	10.0
-2.0	15	16	15	15.0
-3.0	17	14	14	14.0
-4.0	16	18	17	17.0
-5.0	22	26	24	25.0
-6.0	24	28	28	28.0

**Dynamic Cone Penetrometer**



**ECS** ECS SOUTHEAST, LLP  
 1812 Center Park Drive Suite D  
 Charlotte, North Carolina 28217  
 (704)525.5152


**Client** TGS Engineers  
**Project** U-6055 - Pisgah Road  
**Location** Canton, North Carolina  
**Job No.** 12175  
**Boring** HA-6 **Alignment** L  
**Station** 13+82 **Offset** 24' LT


Depth*	Soil Description
Asphalt	None
ABC Stone	None
0 - 2 ft	Artificial Fill: Loose, Moist, Brown, Silty Fine to Coarse SAND (A-2-4), with trace gravel.
2 - 6 ft	Residual: Medium Stiff to Stiff, Moist, Red-Orange-Brown, Fine Sandy SILT (A-4(2)), with trace mica.
6 - 7 ft	Medium Dense, Moist, Brown, Silty Fine to Coarse SAND (A-2-4), with trace mica.
Hand Auger Terminated at 7.0 feet	

\*Depths are measured below soil subgrade.  
 \*\*Groundwater not encountered.

Dyanmic Cone Penetrometer Measurements per Drive Increments				
Depth	0" to 2"	2" to 3.75"	3.75" to 5.5"	Average
0.0	10	10	8	9.0
-1.0	9	10	5	7.0
-2.0	7	8	7	7.0
-3.0	6	7	7	7.0
-4.0	14	12	14	13.0
-5.0	15	15	18	16.0
-6.0	21	20	21	20.0
-7.0	19	26	24	25.0

**Dynamic Cone Penetrometer**






**Client** TGS Engineers  
**Project** U-6055 - Pisgah Road  
**Location** Canton, North Carolina  
**Job No.** 12175  
**Boring** HA-7 **Alignment** Y2  
**Station** 10+67 **Offset** 13' RT

Depth*	Soil Description
Asphalt	None
ABC Stone	None
0 - 2 ft	Artificial Fill: Very Soft to Soft, Wet, Brown, Silty CLAY (A-7-6(14)).
2 - 4 ft	Residual: Stiff, Wet to Moist, Red-Brown, Fine Sandy CLAY (A-6).
4 - 6 ft	Very Stiff, Moist, Red-Brown, Fine Sandy SILT (A-4), with trace mica.
Hand Auger Terminated at 6.0 feet	

\*Depths are measured below soil subgrade.

\*\*Groundwater not encountered.

**Dynamic Cone Penetrometer**



Dyanmic Cone Penetrometer Measurements per Drive Increments				
Depth	0" to 2"	2" to 3.75"	3.75" to 5.5"	Average
0.0	1	0	1	0.0
-1.0	5	3	3	3.0
-2.0	7	12	15	13.0
-3.0	15	18	24	21.0
-4.0	19	26	29	27.0
-5.0	27	29	27	28.0
-6.0	27	31	33	32.0

PROJECT REFERENCE NO.	SHEET NO.
U-6055	18

*NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT*

---

---

***SUBSURFACE INVESTIGATION***

---

---

***APPENDIX C  
KESSLER DCP LOGS***

**REFERENCE: U-6055**

**PROJECT: N/A**

*Prepared in the Office of:*



**ECS SOUTHEAST, LLP**  
1812 CENTER PARK DRIVE, SUITE D  
CHARLOTTE, NC 28217  
(704) 525-5152 [PHONE]  
(704) 357-0023 [FAX]  
NC REGISTERED  
ENGINEERING  
FIRM # F-1078

