

**This electronic collection of documents is provided  
for the convenience of the user  
and is Not a Certified Document –**

**The documents contained herein were originally issued  
and sealed by the individuals whose names and license  
numbers appear on each page, on the dates appearing  
with their signature on that page.**

**This file or an individual page  
shall not be considered a certified document.**

09/08/99

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

**CARTERET COUNTY**



LOCATION: US 70 FROM 1000' WEST OF WILLIS RD EASTWARD  
TO BANKS STREET IN MOREHEAD CITY

TYPE OF WORK: GRADING, PAVING, WIDENING


STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	W5319	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
46142.1.1	HSIP-0070(137)	PE	
46142.2.1	HSIP-0070(137)	RW	
46142.3.2	HSIP-0070(137)	CONST	

TIP PROJECT: W5319

CONTRACT: DB00252



GRAPHIC SCALES



DESIGN DATA  
ADT 2014 = 22,000

PROJECT LENGTH

TOTAL LENGTH PROJECT W-5319 = 2.565 MILES

Prepared in the Office of:  
**DIVISION OF HIGHWAYS**  
1704 N. GREENE ST, GREENVILLE NC, 27834

2012 STANDARD SPECIFICATIONS


RIGHT OF WAY DATE:  
JULY 2015

LETTING DATE:  
FEBRUARY 2016

ED EATMON  
PROJECT ENGINEER


LANG JONES  
PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER




DocuSigned by:  
Ed Eatmon  
SIGNATURE: 10/12/2015 P.E.

ROADWAY DESIGN ENGINEER



DocuSigned by:  
Lang Jones  
SIGNATURE: 10/12/2015 P.E.



06-OCT-2015 14:47  
G:\PROJECTS\CARTERET\MHC SIGNALS\W5319-ps-hi.dgn  
\$\$\$\$\$USERNAME\$\$\$\$\$



12/05/11

Note: Not to Scale

\*S.U.E. = Subsurface Utility Engineering

# CONVENTIONAL PLAN SHEET SYMBOLS

## BOUNDARIES AND PROPERTY:

State Line	-----
County Line	-----
Township Line	-----
City Line	-----
Reservation Line	-----
Property Line	-----
Existing Iron Pin	○ EP
Property Corner	----->
Property Monument	□ ECM
Parcel/Sequence Number	⑫③
Existing Fence Line	-x-x-x-
Proposed Woven Wire Fence	○
Proposed Chain Link Fence	□
Proposed Barbed Wire Fence	◇
Existing Wetland Boundary	----- MLB
Proposed Wetland Boundary	----- MLB
Existing Endangered Animal Boundary	----- EAB
Existing Endangered Plant Boundary	----- EPB
Known Soil Contamination: Area or Site	☠
Potential Soil Contamination: Area or Site	☠?

## BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	○
Sign	○
Well	○ W
Small Mine	✕
Foundation	□
Area Outline	□
Cemetery	□
Building	□
School	□
Church	□
Dam	□

## HYDROLOGY:

Stream or Body of Water	-----
Hydro, Pool or Reservoir	□
Jurisdictional Stream	----- JS
Buffer Zone 1	----- BZ 1
Buffer Zone 2	----- BZ 2
Flow Arrow	←
Disappearing Stream	-----
Spring	○
Wetland	-----
Proposed Lateral, Tail, Head Ditch	-----
False Sump	-----

## RAILROADS:

Standard Gauge	-----
RR Signal Milepost	○ CSX TRANSPORTATION MILEPOST 35
Switch	□ SWITCH
RR Abandoned	-----
RR Dismantled	-----

## RIGHT OF WAY:

Baseline Control Point	◆
Existing Right of Way Marker	△
Existing Right of Way Line	-----
Proposed Right of Way Line	----- RW
Proposed Right of Way Line with Iron Pin and Cap Marker	----- RW ▲
Proposed Right of Way Line with Concrete or Granite RW Marker	----- RW ●
Proposed Control of Access Line with Concrete CA Marker	----- CA
Existing Control of Access	----- CA
Proposed Control of Access	----- CA
Existing Easement Line	----- E
Proposed Temporary Construction Easement	----- E
Proposed Temporary Drainage Easement	----- TDE
Proposed Permanent Drainage Easement	----- PDE
Proposed Permanent Drainage / Utility Easement	----- DUE
Proposed Permanent Utility Easement	----- PUE
Proposed Temporary Utility Easement	----- TUE
Proposed Aerial Utility Easement	----- AUE

## ROADS AND RELATED FEATURES:

Proposed Permanent Easement with Iron Pin and Cap Marker	◆
Existing Edge of Pavement	-----
Existing Curb	-----
Proposed Slope Stakes Cut	----- C
Proposed Slope Stakes Fill	----- F
Proposed Curb Ramp	○ CR
Existing Metal Guardrail	-----
Proposed Guardrail	-----
Existing Cable Guiderail	-----
Proposed Cable Guiderail	-----
Equality Symbol	⊕
Pavement Removal	-----

## VEGETATION:

Single Tree	☼
Single Shrub	☼
Hedge	-----
Woods Line	-----

Orchard	☼☼☼☼
Vineyard	□ Vineyard

## EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	----- CONC
Bridge Wing Wall, Head Wall and End Wall	----- CONC WW
MINOR:	
Head and End Wall	----- CONC HW
Pipe Culvert	-----
Footbridge	-----
Drainage Box: Catch Basin, DI or JB	□ CB
Paved Ditch Gutter	-----
Storm Sewer Manhole	○
Storm Sewer	----- S

## UTILITIES:

POWER:	
Existing Power Pole	●
Proposed Power Pole	○
Existing Joint Use Pole	●
Proposed Joint Use Pole	○
Power Manhole	⊕
Power Line Tower	⊗
Power Transformer	⊗
U/G Power Cable Hand Hole	□
H-Frame Pole	●
Recorded U/G Power Line	----- P
Designated U/G Power Line (S.U.E.*)	----- P

## TELEPHONE:

Existing Telephone Pole	●
Proposed Telephone Pole	○
Telephone Manhole	⊕
Telephone Booth	□
Telephone Pedestal	⊕
Telephone Cell Tower	⊕
U/G Telephone Cable Hand Hole	□
Recorded U/G Telephone Cable	----- T
Designated U/G Telephone Cable (S.U.E.*)	----- T
Recorded U/G Telephone Conduit	----- TC
Designated U/G Telephone Conduit (S.U.E.*)	----- TC
Recorded U/G Fiber Optics Cable	----- T FO
Designated U/G Fiber Optics Cable (S.U.E.*)	----- T FO

## WATER:

Water Manhole	⊕
Water Meter	○
Water Valve	⊗
Water Hydrant	⊕
Recorded U/G Water Line	----- W
Designated U/G Water Line (S.U.E.*)	----- W
Above Ground Water Line	----- A/G Water

## TV:

TV Satellite Dish	☼
TV Pedestal	□
TV Tower	⊗
U/G TV Cable Hand Hole	□
Recorded U/G TV Cable	----- TV
Designated U/G TV Cable (S.U.E.*)	----- TV
Recorded U/G Fiber Optic Cable	----- TV FO
Designated U/G Fiber Optic Cable (S.U.E.*)	----- TV FO

## GAS:

Gas Valve	◇
Gas Meter	⊕
Recorded U/G Gas Line	----- G
Designated U/G Gas Line (S.U.E.*)	----- G
Above Ground Gas Line	----- A/G Gas

## SANITARY SEWER:


Sanitary Sewer Manhole	⊕
Sanitary Sewer Cleanout	⊕
U/G Sanitary Sewer Line	----- SS
Above Ground Sanitary Sewer	----- A/G Sanitary Sewer
Recorded SS Forced Main Line	----- FSS
Designated SS Forced Main Line (S.U.E.*)	----- FSS

## MISCELLANEOUS:


Utility Pole	●
Utility Pole with Base	□
Utility Located Object	○
Utility Traffic Signal Box	⊕
Utility Unknown U/G Line	----- ?U/L
U/G Tank; Water, Gas, Oil	□
Underground Storage Tank, Approx. Loc.	⊕
A/G Tank; Water, Gas, Oil	□
Geoenvironmental Boring	⊕
U/G Test Hole (S.U.E.*)	⊕
Abandoned According to Utility Records	AATUR
End of Information	E.O.I.

C1	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ.YD. 1.5 INCHES IN EACH OF TWO LAYERS
D1	PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
E1	PROP. APPROX. 5" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 570 LBS. PER SQ. YD.
R1	PROP. 2'-6" CONCRETE CURB AND GUTTER
R2	1'-6" CONCRETE CURB AND GUTTER.
R3	4" CONCRETE ISLAND COVER.
S	EXISTING CONCRETE SIDEWALK.
T	EARTH MATERIAL.
U	EXISTING PAVEMENT.

NOTE: PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.



USE TYPICAL SECTION #1 (NTS)  
-L- STA 44+22.74 TO STA 45+55.21



USE TYPICAL SECTION #2 (NTS)  
-L- STA 49+83.87 TO STA 53+07.02

REVISIONS

8/17/99

06-OCT-2015 09:56  
S:\PROJECTS\W5319\_PSH.dgn  
S:\PROJECTS\W5319\_PSH.dgn

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS  
SUMMARY OF QUANTITIES



SECT	QUANTITY	UNIT	ITEM DESCRIPTION
800	1	LS	MOBILIZATION
801	1	LS	CONSTRUCTION SURVEYING
226	1	LS	GRADING
300	10	TON	FOUNDATION CONDITIONING MATERIAL, MINOR STRUCTURES
300	10	SY	FOUNDATION CONDITIONING GEOTEXTILE
310	24	LF	15' RC PIPE CULVERTS, CLASS III
610	270	TON	ASPHALT CONCRETE BASE COURSE, TYPE B25.0B
610	160	TON	ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B
610	125	TON	ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B
620	30	TON	ASPHALT BINDER FOR PLANT MIX, GRADE PG64-22
840	1	EA	MASONRY DRAINAGE STRUCTURES
840	1	EA	FRAME WITH GRATE & HOOD, STD 840.03, TYPE E
840	.5	CY	PIPE COLLARS
846	135	LF	1'-6" CONCRETE CURB & GUTTER
846	400	LF	2'-6" CONCRETE CURB & GUTTER
846	120	LF	CONCRETE VALLEY GUTTER
852	240	SY	4" CONCRETE ISLAND COVER
852	30	SY	5" MONOLITHIC CONCRETE ISLANDS (SURFACE MOUNTED)
858	4	EA	ADJUST WATER VALVE
858	2	EA	ADJUST MANHOLE LID
1620	150	LB	SEED FOR TEMPORARY SEEDING
1620	0.6	TON	FERTILIZER FOR TEMPORARY SEEDING
1632	4	EA	RESPONSE FOR EROSION CONTROL
1661	50	LB	SEED FOR REPAIR SEEDING
1661	.2	TON	FERTILIZER FOR REPAIR SEEDING
SP	1	ACRE	SEEDING AND MULCHING

REVISIONS

8/17/99


06-OCT-2015 09:56  
S:\PROJECTS\2015\09\56\REFR\REFR\MHC SIGNALS\W5319\_psh.dgn





*PI Sta 45+51.33*  
 $\Delta = 6^{\circ}19'13.8''$  (RT)  
 $D = 1^{\circ}06'06.6''$   
 $L = 573.63'$   
 $T = 287.11'$   
 $R = 5,200.00'$

DENOTES CONCRETE ISLAND REVOVAL  
 SEE SHEET 3A FOR DETAILS



**DATUM DESCRIPTION**

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "GPS-4" WITH NAD 83/NSRS 2007 STATE PLANE GRID COORDINATES OF NORTHING: 364701.915(±ft) EASTING: 2666320.124(±ft) ELEVATION: 8.81(±ft)

THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.999918970

THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "GPS-4" TO -L- STATION IS


ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES  
 VERTICAL DATUM USED IS NAVD 88

REVISIONS



8/17/99

06-0617-2015-09-05-56 PERET\MHC SIGNALS\W5319\_psh4.dgn





50



CONTROL POINT -BL- 6  
 N 366000.8234  
 E 2662429.1042  
 ELEV 22.01


**DATUM DESCRIPTION**

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "GPS-4" WITH NAD 83/NSRS 2007 STATE PLANE GRID COORDINATES OF NORTHING: 364701.915(±) EASTING: 2666320.124(±) ELEVATION: 8.81(±)

THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.999918970

THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "GPS-4" TO -L- STATION IS

ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES VERTICAL DATUM USED IS NAVD 88



REVISIONS

06-OCT-2015 09:56 PERET\MHC SIGNALS\W5319\_psh.dgn  
 8/17/99



DIVISION OF HIGHWAYS  
STATE OF NORTH CAROLINA


## CROSS-SECTION SUMMARY




IN CUBIC YARDS

NOTE: Approximate quantities only. Unclassified Excavation, Borrow Excavation, Fine Grading, Clearing and Grubbing, and Removal of Existing Pavement will be paid for at the contract Lump Sum price for "Grading".


LOCATION (-LREV-)	UNCLASSIFIED EXCAVATION	UNDERCUT	EMBANKMENT
44 + 25.02	0	0	0
44 + 50.00	11	0	0
45 + 00.00	30	0	0
45 + 50.00	16	0	0
45 + 59.86	1	0	0

LOCATION (-LREV-)	UNCLASSIFIED EXCAVATION	UNDERCUT	EMBANKMENT
50 + 00.00	0	0	0
50 + 50.00	42	0	0
51 + 00.00	58	0	0
51 + 50.00	60	0	0
52 + 00.00	60	0	0
52 + 50.00	49	0	0
53 + 00.00	26	0	0





PHASING DIAGRAM




PHASING DIAGRAM DETECTION LEGEND

- DETECTED MOVEMENT
- ← UNDETECTED MOVEMENT (OVERLAP)
- UNSIGNALIZED MOVEMENT
- ↔ PEDESTRIAN MOVEMENT

SIGNAL FACE	PHASE							
	01+6	02+5	02+6	03+7	03+8	04+7	04+8	FLASH
11,12	—	—	—	—	—	—	—	—
21,22	R	G	G	R	R	R	R	Y
31	—	—	—	—	—	—	—	—
41	R	R	R	R	R	G	G	R
51,52	—	—	—	—	—	—	—	—
61,62	G	G	R	R	R	R	R	Y
71	—	—	—	—	—	—	—	—
81,82	R	R	R	R	G	R	G	R

SIGNAL FACE I.D.



OASIS 2070 TIMING CHART

FEATURE	PHASE							
	1	2	3	4	5	6	7	8
Min Green 1*	7	12	7	7	7	12	7	7
Extension 1*	2.0	6.0	2.0	6.0	2.0	6.0	2.0	6.0
Max Green 1*	25	90	15	25	25	90	15	25
Yellow Clearance	3.0	4.5	3.0	4.6	3.0	4.5	3.0	4.6
Red Clearance	3.5	1.4	3.3	2.0	3.8	1.6	3.4	1.7
Walk 1*	-	-	-	-	-	-	-	-
Don't Walk 1	-	-	-	-	-	-	-	-
Seconds Per Actuation*	-	1.5	-	-	-	1.5	-	-
Max Variable Initial*	-	34	-	-	-	34	-	-
Time Before Reduction*	-	15	-	0	-	15	-	0
Time To Reduce*	-	30	-	15	-	30	-	15
Minimum Gap	-	3.0	-	3.0	-	3.0	-	3.0
Recall Mode	-	MIN RECALL	-	-	-	MIN RECALL	-	-
Vehicle Call Memory	-	YELLOW	-	-	-	YELLOW	-	-
Dual Entry	-	-	-	ON	-	-	-	ON
Simultaneous Gap	ON	ON	ON	ON	ON	ON	ON	ON

\* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.



7 Phase Fully Actuated  
US 70 Morehead City - CLS 3

NOTES

- Refer to "Roadway Standard Drawings NCDOT" dated January 2012 and "Standard Specifications for Roads and Structures" dated January 2012.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Phase 3 and/or phase 7 may be lagged.
- The order of phase 1+6 and phase 2+5 may be reversed.
- Set all detector units to presence mode.
- Maximum times shown in timing chart are for free-run timing operation only. Coordinated signal system timing values supersede these values.
- Closed loop system data: Master Asset #10213, Controller Asset #0423.

OASIS 2070 LOOP & DETECTOR INSTALLATION CHART

LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	DETECTOR PROGRAMMING									
				NEW LOOP	PHASE	CALLING	EXTENSION	STRETCH TIME	DELAY TIME	SYSTEM LOOP	NEW CARD		
1A	6X40	+5	2-4-2	Y	1	Y	Y	-	-	-	-	-	-
1B	6X40	+5	2-4-2	Y	1	Y	Y	-	-	-	-	-	-
2A	6X6	300	5	-	2	Y	Y	-	-	-	-	-	-
2B	6X6	300	5	-	2	Y	Y	-	-	-	-	-	-
3A	6X40	+5	2-4-2	-	3	Y	Y	-	-	-	-	-	-
4A	6X6	300	6	-	4	-	Y	-	-	-	-	-	-
4B	6X6	300	6	-	4	-	Y	-	-	-	-	-	-
4C	6X40	+5	2-4-2	-	4	Y	Y	Y	2.0	5.0	-	-	-
4D	6X40	+5	2-4-2	-	4	Y	Y	Y	2.0	5.0	-	-	-
5A	6X40	+5	2-4-2	-	5	Y	Y	-	-	-	-	-	-
5B	6X40	+5	2-4-2	-	5	Y	Y	-	-	-	-	-	-
5C	6X40	+5	2-4-2	-	5	Y	Y	-	-	-	-	-	-
6A	6X6	300	6	Y	6	Y	Y	-	-	-	-	-	-
6B	6X6	300	6	Y	6	Y	Y	-	-	-	-	-	-
7A	6X40	+5	2-4-2	-	7	Y	Y	-	-	-	-	-	-
8A	6X6	300	4	-	8	-	Y	-	-	-	-	-	-
8B	6X40	+5	2-4-2	-	8	Y	Y	Y	2.0	5.0	-	-	-
8C	6X40	+5	2-4-2	-	8	Y	Y	Y	2.0	5.0	-	-	-
S07	6X6	+135	4	-	-	-	-	-	-	-	Y	-	-
S08	6X6	+135	4	-	-	-	-	-	-	-	Y	-	-
S09	6X6	Ramp	4	-	-	-	-	-	-	-	Y	-	-



LEGEND

PROPOSED	EXISTING
○ Traffic Signal Head	● N/A
○ Modified Signal Head	○ N/A
○ Sign	○ N/A
○ Pedestrian Signal Head With Push Button & Sign	○ N/A
○ Signal Pole with Guy	○ N/A
○ Signal Pole with Sidewalk Guy	○ N/A
○ Metal Pole with Mastarm	○ N/A
○ Inductive Loop Detector	○ N/A
○ Controller & Cabinet	○ N/A
○ Junction Box	○ N/A
○ Over-sized Junction Box	○ N/A
○ 2-in Underground Conduit	○ N/A
○ Directional Drill	○ N/A
○ Right of Way	○ N/A
○ Directional Arrow	○ N/A
○ "YIELD" Sign (R1-2)	○ N/A
○ Right Arrow "ONLY" Sign (R3-5R)	○ N/A
○ "U-TURN YIELD TO RIGHT TURN" Sign (R10-16)	○ N/A
○ Combined Through and Right Arrow Sign (R3-6R)	○ N/A

Signal Upgrade

Prepared In the Offices of:  
TRANSPORTATION MOBILITY AND SAFETY SOLUTIONS  
A DIVISION OF NORTH CAROLINA PROFESSIONAL ENGINEERS AND SURVEYORS  
Signal Design Section  
750 N. Greenfield Pkwy, Garner, NC 27529

US 70 At NC 24/SR 1176 (Bridges Street)

Division 2 Carteret County Morehead City  
PLAN DATE: January 2015 REVIEWED BY: PLA  
PREPARED BY: JPG REVIEWED BY:


SCALE 1"=40'

SEAL  
NORTH CAROLINA PROFESSIONAL ENGINEERS AND SURVEYORS  
JASON P. GALLAGHER  
12/15/2015  
SIG. INVENTORY NO. 02-0423

15-065-2015 15-51 S:\MISC\5319\15-51\SIGNAL\Signal Design Section\Eastern Region\01-02\W-5319\en\l\020423\_51.dwg, 20150306.dgn

**EDI MODEL 2018ECL-NC CONFLICT MONITOR PROGRAMMING DETAIL**

(remove jumpers and set switches as shown)



**NOTES:**

1. Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
2. Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
3. Ensure that Red Enable is active at all times during normal operation.
4. Connect serial cable from conflict monitor to comm. port 1 of 2070 controller. Ensure conflict monitor communicates with 2070.

**NOTES**

1. To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
2. Program phases 4 and 8 for Dual Entry.
3. Enable Simultaneous Gap-Out for all phases.
4. Program phases 2 and 6 for Variable Initial.
5. Program phases 2, 4, 6 and 8 for Gap Reduction.
6. Program phases 2 and 6 for Start Up In Green.
7. Program phases 2 and 6 for Yellow Flash.
8. The cabinet and controller are part of the Morehead City Closed Loop System 3.

**SIGNAL HEAD HOOK-UP CHART**

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	11,12	21,22	NU	31	41,42	NU	42	51,52	61,62	NU	71	81,82	NU	NU	NU	NU	NU	NU
RED		128			101				134			107						
YELLOW		129			102				135			108						
GREEN		130			103				136			109						
RED ARROW	125				116				131			122						
YELLOW ARROW	126				117				132	132		123						
GREEN ARROW	127				118				133	133		124						

NU = Not Used

**EQUIPMENT INFORMATION**

CONTROLLER.....2070  
 CABINET.....332 /W/ AUX  
 SOFTWARE.....ECONOLITE OASIS  
 CABINET MOUNT.....BASE  
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE  
 LOAD SWITCHES USED.....S1,S2,S4,S5,S7,S8,S10,S11  
 PHASES USED.....1,2,3,4,5,6,7,8  
 OVERLAPS.....NONE

**PHASE SEQUENCE PROGRAMMING DETAIL**


(program controller as shown below)

FROM OASIS LOCAL CONTROLLER MAIN MENU  
 SELECT: 4 PHASE SEQUENCE  
 (8 - PHASE, W/ 1+ 5 CONFLICTING)

PHASE SEQUENCE: PAGE 1	NEXT: PAGES)					
RNG	LEAD	BARRIER 1	X-LAG	LEAD	BARRIER 2	X-LAG
1	:0	2	0	0	3	4
2	:0	6	0	5	7	8
3	:0	0	0	0	0	0
4	:0	0	0	0	0	0

**INPUT FILE POSITION LAYOUT**

(front view)




**INPUT FILE CONNECTION & PROGRAMMING CHART**

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	INPUT ASSIGNMENT NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND	FULL TIME DELAY	STRETCH TIME	DELAY TIME
1A	TB2-1,2	I1U	56	18	1	1	Y	Y			
1B	TB2-3,4	I1L	56	18	1	1	Y	Y			
2A	TB2-5,6	I2U	39	1	2	2	Y	Y			
2B	TB2-7,8	I2L	43	5	12	2	Y	Y			
3A	TB4-5,6	I5U	58	20	3	3	Y	Y			
4A	TB4-9,10	I6U	41	3	4	4		Y			
4B	TB4-11,12	I6L	45	7	14	4		Y			
4C	TB6-1,2	I7U	65	27	34	4	Y	Y	Y	2.0	5.0
4D	TB6-3,4	I7L	78	40	44	4	Y	Y	Y	2.0	5.0
*S07	TB6-9,10	I9U	60	22	11	SYS					
5A	TB3-1,2	J1U	55	17	5	5	Y	Y			
5B	TB3-5,6	J2U	40	2	6	5	Y	Y			
5C	TB3-7,8	J2L	44	6	16	5	Y	Y			
6A	TB3-9,10	J3U	64	26	36	6	Y	Y			
6B	TB3-11,12	J3L	77	39	46	6	Y	Y			
7A	TB5-5,6	J5U	57	19	7	7	Y	Y			
8A	TB5-9,10	J6U	42	4	8	8		Y			
8B	TB5-11,12	J6L	46	8	18	8	Y	Y	Y	2.0	5.0
8C	TB7-1,2	J7U	66	28	38	8	Y	Y	Y	2.0	5.0
*S08	TB7-9,10	J9U	59	21	15	SYS					
*S09	TB7-11,12	J9L	61	23	17	SYS					

\* SYSTEM DETECTOR ONLY. REMOVE THE VEHICLE PHASE ASSIGNED TO THIS DETECTOR IN THE DEFAULT PROGRAMMING.

INPUT FILE POSITION LEGEND: J2L



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 02-0423  
 DESIGNED: January 2015  
 SEALED: 12-15-15  
 REVISED: N/A

Electrical Detail

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Prepared in the Offices of:  
 TRANSPORTATION MOBILITY AND SAFETY DIVISION  
 NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
 Signal Management Section  
 750 N. Greenfield Pkwy, Garner, NC 27529

US 70 at NC 24/SR 1176 (Bridges Street)  
 Division 2 Carteret County Morehead City  
 PLAN DATE: December 2015 REVIEWED BY: DTJ  
 PREPARED BY: James Peterson REVIEWED BY:


REVISIONS INIT. DATE

DocuSigned by: Keith M. Mims 12/29/2015  
 SEAL 036880  
 ENGINEER KEITH M. MIMS  
 DATE  
 SIG. INVENTORY NO. 02-0423





**Design Loading for METAL POLE NO. 3**



Elevation View

**SPECIAL NOTE**

The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

**Elevation Data for Mast Arm Attachment (H1)**

Elevation Differences for:	Pole 1	Pole 2
Baseline reference point at $\phi$ Foundation @ ground level	0.0 ft.	0.0 ft.
Elevation difference at High point of roadway surface	-0.57 ft.	-0.22 ft.
Elevation difference at Edge of travelway or face of curb	+/-0.0 ft.	+/-0.0 ft.

**MAST ARM LOADING SCHEDULE**

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	66.0" W X 25.5" L	74 LBS
	SIGN RIGID MOUNTED	7.5 S.F.	30.0" W X 36.0" L	14 LBS
	STREET NAME SIGN RIGID MOUNTED	12.0 S.F.	18.0" W X 96.0" L	27 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-3 SECTION-WITH BACKPLATE	9.3 S.F.	25.5" W X 52.5" L	60 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-5 SECTION-WITH BACKPLATE	16.3 S.F.	42.0" W X 56.0" L	103 LBS


**NOTES**

**DESIGN REFERENCE MATERIAL**

- Design the traffic signal structure and foundation in accordance with:
  - The 5th Edition 2009 AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
  - The 2012 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
  - The 2012 NCDOT Roadway Standard Drawings.
  - The traffic signal project plans and special provisions.
  - The NCDOT "Metal Pole Standards" located at the following NCDOT website: <https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>


**DESIGN REQUIREMENTS**

- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using stress ratios that do not exceed 0.9.
- The camber design for the mast arm deflection should provide an appearance of a low pitched arch where the tip or the free end of the mast arm does not deflect below horizontal when fully loaded.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
  - Mast arm slope and deflection are not considered in determining the arm attachment height as they are assumed to offset each other.
  - Signal heads are rigidly mounted and vertically centered on the mast arm.
  - The roadway clearance height for design is as shown in the elevation views.
  - The top of the pole base plate is 0.75 feet above the ground elevation.
  - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
- The pole manufacturer will determine the total height (H2) of pole 4 using the greater of the following unless otherwise shown:
  - Mast arm attachment height (H1) plus 2 feet, or
  - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 773-2800.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The Department will provide soil penetration data (SPT) for foundation designs. Contact the Division Traffic Engineer at (919) 439-2800 for the reports.




POLE RADIAL ORIENTATION


**Design Loading for METAL POLE NO. 4**



Elevation View



8 BOLT BASE PLATE DETAIL





BASE PLATE TEMPLATE & ANCHOR BOLT LOCK PLATE DETAIL For 8 Bolt Base Plate

**NCDOT Wind Zone 2 (130 mph)**

	Prepared In the Offices of: <b>US 70 (Arendell Street)</b> At <b>NC 24/SR 1176 (Bridges Street)</b>		SEAL 
	Division 2 Carteret County Morehead City PLAN DATE: February 2015 REVIEWED BY: PLA PREPARED BY: JPG REVIEWED BY:	SCALE 0 N/A N/A	
SIG. INVENTORY NO. 02-0423			

02-11-2016 09:57  
 S:\ITS\5319\15\_Signal\Signal Design\Section\Eastern Region\01\1-02\W-5319\4\1-4\_20150209.dgn  
 J:\Calloway


**PHASING DIAGRAM**



**TABLE OF OPERATION**

SIGNAL FACE	PHASE					
	01+5	01+6	02+5	02+6	04+8	U-TURN
11	←	←	←	←	←	←
21,22	R	R	G	G	R	Y
41	R	R	R	R	G	R
42	R	R	R	R	G	R
51	←	←	←	←	←	←
61,62	R	G	R	G	R	Y
81	R	R	R	R	G	R
82	R	R	R	R	G	R

**SIGNAL FACE I.D.**




**OASIS 2070 LOOP & DETECTOR INSTALLATION**

LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	DETECTOR PROGRAMMING					SYSTEM LOOP	NEW CARD	
					PHASE	CALLING	EXTENSION	FULL TIME DELAY	STRETCH TIME			DELAY TIME
1A	6X60	+5	2-4-2	-	1	Y	Y	-	-	-	-	-
1B	6X60	+5	2-4-2	-	1	Y	Y	-	-	-	-	-
1C	6X15	+10	EXIST	-	1	Y	Y	-	-	15	-	-
2A	6X6	300	4	-	2	Y	Y	-	-	-	-	-
2B	6X6	300	4	-	2	Y	Y	-	-	-	-	-
2C	6X6	300	4	-	2	Y	Y	-	-	-	-	-
4A	6X40	0	2-4-2	-	4	Y	Y	-	-	-	-	-
5A	6X60	+5	2-4-2	-	5	Y	Y	-	-	-	-	-
5B	6X40	0	2-4-2	-	5	Y	Y	-	-	15	-	-
6A	6X6	300	4	-	6	Y	Y	-	-	-	-	-
6B	6X6	300	4	-	6	Y	Y	-	-	-	-	-
8A	6X60	+5	2-4-2	-	8	Y	Y	-	-	-	-	-
S10	6X6	+170	EXIST	-	-	-	-	-	-	-	Y	-
S11	6X6	+170	EXIST	-	-	-	-	-	-	-	Y	-
S12	6X6	+170	EXIST	-	-	-	-	-	-	-	Y	-
S13	6X6	+170	EXIST	-	-	-	-	-	-	-	Y	-

5 Phase Fully Actuated US 70 (Morehead City) - CLS 3

**NOTES**



- Refer to "Roadway Standard Drawings NCDOT" dated January 2012 and "Standard Specifications for Roads and Structures" dated January 2012.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Phase 1 or phase 5 may be lagged.
- Set all detector units to presence mode.
- Pavement markings are existing.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.
- Closed loop system data: Controller Asset #0249



**OASIS 2070 TIMING CHART**

FEATURE	PHASE					
	1	2	4	5	6	8
Min Green 1 *	4	12	7	4	12	7
Extension 1 *	4.0	6.0	2.0	1.0	6.0	2.0
Max Green 1 *	15	90	25	30	90	25
Yellow Clearance	3.0	4.5	3.8	3.0	4.5	3.8
Red Clearance	2.8	1.5	2.5	2.6	1.7	2.8
Walk 1 *	-	-	-	-	-	-
Don't Walk 1	-	-	-	-	-	-
Seconds Per Actuation *	-	1.8	-	-	1.8	-
Max Variable Initial *	-	34	-	-	34	-
Time Before Reduction *	-	15	-	-	15	-
Time To Reduce *	-	30	-	-	30	-
Minimum Gap	-	3.0	-	-	3.0	-
Recall Mode	-	MIN RECALL	-	-	MIN RECALL	-
Vehicle Call Memory	-	YELLOW	-	-	YELLOW	-
Dual Entry	-	-	ON	-	-	ON
Simultaneous Gap	ON	ON	ON	ON	ON	ON

\* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.



**Signal Upgrade**

Prepared In the Offices of:  
  
 TRANSPORTATION MOBILITY AND SAFETY SOLUTIONS, INC.  
 ENGINEERS OF TRANSPORTATION SIGNAL DESIGN SECTION  
 1750 N. Greenfield Pkwy, Garner, NC 27529

**US 70 (Arendell Street) at Rochelle Road**  
 Division 2 Carteret County Morehead City  
 PLAN DATE: January 2015 REVIEWED BY:  
 PREPARED BY: EM Minshew REVIEWED BY:


SEAL  
 JASON P. GALLAWAY  
 ENGINEER  
 029904  
 DATE: 12/15/2015  
 SIG. INVENTORY NO. 02-0249

SCALE: 1" = 40'

REVISIONS	INIT.	DATE

02-0249-2015-08-14  
 S:\Projects\5319\15\_Signal\Signal Design Section\Eastern Region\01-02\W-5319\en\updates\020249\_s.dwg, 20150306.dgn  
 J:\011000

**EDI MODEL 2018ECL-NC CONFLICT MONITOR**  
**PROGRAMMING DETAIL**  
*(remove jumpers and set switches as shown)*



- NOTES:**
- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
  - Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
  - Ensure that Red Enable is active at all times during normal operation.
  - Connect serial cable from conflict monitor to comm. port 1 of 2070 controller. Ensure conflict monitor communicates with 2070.

**NOTES**

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program phases 4 and 8 for Dual Entry.
- Enable Simultaneous Gap-Out for all phases.
- Program phases 2 and 6 for Variable Initial and Gap Reduction.
- Program phases 2 and 6 for Start Up In Green.
- Program phases 2 and 6 for Yellow Flash.
- The cabinet and controller are part of the US 70 (Morehead City) Closed Loop System 3.

**SIGNAL HEAD HOOK-UP CHART**

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12		
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16		
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED		
SIGNAL HEAD NO.	11	82	21,22	NU	NU	41,42	NU	42	51	61,62	NU	NU	81,82	NU
RED		128			101			134				107		
YELLOW		129			102			135				108		
GREEN		130			103			136				109		
RED ARROW	125							131						
YELLOW ARROW	126	126						132	132					
GREEN ARROW	127	127						133	133					


NU = Not Used

**EQUIPMENT INFORMATION**

CONTROLLER.....2070  
 CABINET.....332  
 SOFTWARE.....ECONOLITE OASIS  
 CABINET MOUNT.....BASE  
 OUTPUT FILE POSITIONS...12  
 LOAD SWITCHES USED.....S1,S2,S5,S7,S8,S11  
 PHASES USED.....1,2,4,5,6,8  
 OVERLAPS.....NONE

**INPUT FILE POSITION LAYOUT**

(front view)




EX.: 1A, 2A, ETC. = LOOP NO.'S  
 FS = FLASH SENSE  
 ST = STOP TIME

**INPUT FILE CONNECTION & PROGRAMMING CHART**

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	INPUT ASSIGNMENT NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND	FULL TIME DELAY	STRETCH TIME	DELAY TIME
1A	TB2-1,2	I1U	56	18	1	1	Y	Y			
1B,1C	TB2-5,6	I2U	39	1	2	1	Y	Y			15
2A	TB2-9,10	I3U	63	25	32	2	Y	Y			
2B	TB2-11,12	I3L	76	38	42	2	Y	Y			
2C	TB4-1,2	I4U	47	9	22	2	Y	Y			
4A	TB4-9,10	I6U	41	3	4	4	Y	Y			
* S10	TB6-9,10	I9U	60	22	11	SYS					
* S11	TB6-11,12	I9L	62	24	13	SYS					
5A	TB3-5,6	J2U	40	2	6	5	Y	Y			
5B	TB3-7,8	J2L	44	6	16	5	Y	Y			15
6A	TB3-9,10	J3U	64	26	36	6	Y	Y			
6B	TB3-11,12	J3L	77	39	46	6	Y	Y			
8A	TB5-9,10	J6U	42	4	8	8	Y	Y			
* S12	TB7-9,10	J9U	59	21	15	SYS					
* S13	TB7-11,12	J9L	61	23	17	SYS					

\* SYSTEM DETECTOR ONLY. REMOVE THE VEHICLE PHASE ASSIGNED TO THIS DETECTOR IN THE DEFAULT PROGRAMMING.



THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 02-0249  
 DESIGNED: January 2015  
 SEALED: 12-15-15  
 REVISED: N/A

Electrical Detail

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Prepared In the Offices of:  
  
 750 N. Greenfield Pkwy, Garner, NC 27529

US 70 (Arendell Street) at Rochelle Road

Division 2 Carteret County Morehead City

PLAN DATE: December 2015 REVIEWED BY: DTJ  
 PREPARED BY: James Peterson REVIEWED BY:


REVISIONS INIT. DATE

DocuSigned by:  
  
 Keith M. Mins 12/29/2015  
 2F807856C0D345 DATE

SIG. INVENTORY NO. 02-0249


02-0249-2015\_01739  
 S:\TCS\01739\Sig\01739\work\0249\smc\0249\_sm.ele...xxx.dgn  
 J.peterson

**Design Loading for METAL POLE NO. 1**



**Elevation View**

**Design Loading for METAL POLE NO. 2**




**Elevation View**

**SPECIAL NOTE**


The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

**Elevation Data for Mast Arm Attachment (H1)**


Elevation Differences for:	Pole 1	Pole 2
Baseline reference point at $\phi$ Foundation @ ground level	0.0 ft.	0.0 ft.
Elevation difference at High point of roadway surface	-0.08 ft.	-0.78 ft.
Elevation difference at Edge of travelway or face of curb	+/-0.0 ft.	+/-0.0 ft.



**POLE RADIAL ORIENTATION**



**8 BOLT BASE PLATE DETAIL**



**BASE PLATE TEMPLATE & ANCHOR BOLT LOCK PLATE DETAIL For 8 Bolt Base Plate**

**METAL POLE No. 1 and 2**

**MAST ARM LOADING SCHEDULE**

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	66.0" W X 25.5" L	74 LBS
	SIGN RIGID MOUNTED	7.5 S.F.	30.0" W X 36.0" L	14 LBS
	STREET NAME SIGN RIGID MOUNTED	12.0 S.F.	18.0" W X 96.0" L	27 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	25.5" W X 66.0" L	74 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-3 SECTION-WITH BACKPLATE	9.3 S.F.	25.5" W X 52.5" L	60 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-5 SECTION-WITH BACKPLATE	16.3 S.F.	42.0" W X 56.0" L	103 LBS

**NOTES**

**DESIGN REFERENCE MATERIAL**

- Design the traffic signal structure and foundation in accordance with:
  - The 5th Edition 2009 AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
  - The 2012 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
  - The 2012 NCDOT Roadway Standard Drawings.
  - The traffic signal project plans and special provisions.
  - The NCDOT "Metal Pole Standards" located at the following NCDOT website: <https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

**DESIGN REQUIREMENTS**


- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using stress ratios that do not exceed 0.9.
- The camber design for the mast arm deflection should provide an appearance of a low pitched arch where the tip or the free end of the mast arm does not deflect below horizontal when fully loaded.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
  - Mast arm slope and deflection are not considered in determining the arm attachment height as they are assumed to offset each other.
  - Signal heads are rigidly mounted and vertically centered on the mast arm.
  - The roadway clearance height for design is as shown in the elevation views.
  - The top of the pole base plate is 0.75 feet above the ground elevation.
  - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
- The pole manufacturer will determine the total height (H2) of each pole using the greater of the following:
  - Mast arm attachment height (H1) plus 2 feet, or
  - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 773-2800.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The Department will provide soil penetration data (SPT) for foundation designs. Contact the Division Traffic Engineer at (919) 439-2800 for the reports.

**NCDOT Wind Zone 2 (130 mph)**

	Prepared In the Offices of: <b>US 70 (Arendell Street) At Rochelle Road</b>		SEAL NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 029904 JASON P. GALLAWAY ENGINEER 12/31/2015
	Division 2 Carteret County Morehead City PLAN DATE: February 2015 REVIEWED BY: PLA PREPARED BY: JPG REVIEWED BY:	SCALE 0 N/A N/A	
REVISIONS INIT. DATE		SIGNATURE DATE SIG. INVENTORY NO. 02-0249	


30-066-2015-14501  
 S:\ITS\SIG\15\SIG\Signal\Design\Section\Eastern Region\01\1-02\W-5319\02-0249\020249\_s10\_r01-4\_20150209.dgn  
 Jpg11owcy

**Design Loading for METAL POLE NO. 3**



**Elevation View**

**Design Loading for METAL POLE NO. 4**




**Elevation View**

**SPECIAL NOTE**


The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

**Elevation Data for Mast Arm Attachment (H1)**


Elevation Differences for:	Pole 1	Pole 2
Baseline reference point at $\phi$ Foundation @ ground level	0.0 ft.	0.0 ft.
Elevation difference at High point of roadway surface	-0.38 ft.	-0.9 ft.
Elevation difference at Edge of travelway or face of curb	+/-0.0 ft.	+/-0.0 ft.



**POLE RADIAL ORIENTATION**



**8 BOLT BASE PLATE DETAIL**



**BASE PLATE TEMPLATE & ANCHOR BOLT LOCK PLATE DETAIL For 8 Bolt Base Plate**

**METAL POLE No. 3 and 4**

**MAST ARM LOADING SCHEDULE**

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	66.0" W X 25.5" L	74 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-5 SECTION-WITH BACKPLATE	14.6 S.F.	82.5" W X 25.5" L	93 LBS
	SIGN RIGID MOUNTED	7.5 S.F.	30.0" W X 36.0" L	14 LBS
	STREET NAME SIGN RIGID MOUNTED	12.0 S.F.	18.0" W X 96.0" L	27 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	25.5" W X 66.0" L	74 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-3 SECTION-WITH BACKPLATE	9.3 S.F.	25.5" W X 52.5" L	60 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-5 SECTION-WITH BACKPLATE	16.3 S.F.	42.0" W X 56.0" L	103 LBS

**NOTES**

**DESIGN REFERENCE MATERIAL**

- Design the traffic signal structure and foundation in accordance with:
  - The 5th Edition 2009 AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
  - The 2012 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
  - The 2012 NCDOT Roadway Standard Drawings.
  - The traffic signal project plans and special provisions.
  - The NCDOT "Metal Pole Standards" located at the following NCDOT website: <https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

**DESIGN REQUIREMENTS**


- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using stress ratios that do not exceed 0.9.
- The camber design for the mast arm deflection should provide an appearance of a low pitched arch where the tip or the free end of the mast arm does not deflect below horizontal when fully loaded.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
  - Mast arm slope and deflection are not considered in determining the arm attachment height as they are assumed to offset each other.
  - Signal heads are rigidly mounted and vertically centered on the mast arm.
  - The roadway clearance height for design is as shown in the elevation views.
  - The top of the pole base plate is 0.75 feet above the ground elevation.
  - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
- The pole manufacturer will determine the total height (H2) of each pole using the greater of the following:
  - Mast arm attachment height (H1) plus 2 feet, or
  - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 773-2800.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The Department will provide soil penetration data (SPT) for foundation designs. Contact the Division Traffic Engineer at (919) 439-2800 for the reports.

NCDOT Wind Zone 2 (130 mph)

<p>TRANSPORTATION MOBILITY AND SAFETY DIVISION SIGNAL DESIGN SECTION</p>	<p>US 70 (Arendell Street) At Rochelle Road</p>		
	<p>Division 2 Carteret County Morehead City</p> <p>PLAN DATE: February 2015 REVIEWED BY: PLA</p> <p>PREPARED BY: JPG REVIEWED BY:</p>	<p>REVISIONS</p> <p>INIT. DATE</p>	
<p>SCALE: 0 N/A</p>		<p>SIGNATURE: Jason P. Gallaway</p>	
<p>N/A</p>		<p>SIG. INVENTORY NO. 02-0249</p>	

30-065-2015-1452  
 S:\ITS\SIG\15\SIG\Signal Design\Section\Eastern Region\01\1-02\W-5319\02-0249\020249\_510.mpl-4\_20150209.dgn  
 Jpg:lloway

**PHASING DIAGRAM**




SIGNAL FACE	PHASE			
	01+6	02+6	04+8	FLASH
11	←	←	←	←
21	←	←	←	←
22,23	R	G	R	Y
41,42	R	R	G	R
61,62	G	G	R	Y
81	R	R	G	R
82	R	R	G	R

**SIGNAL FACE I.D.**

All Heads L.E.D.

All Heads Polycarbonate

\* Install Polycarbonate Backplates



OASIS 2070 LOOP & DETECTOR INSTALLATION CHART										
LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	DETECTOR PROGRAMMING				SYSTEM LOOP	NEW CARD
					PHASE	CALLING	EXTENSION	FULL TIME DELAY		
1A	6X60	+5	*	Y	1	Y	Y	-	20	-
2A	6X60	0	*	Y	2	Y	Y	-	-	-
2B	6X60	0	*	Y	2	Y	Y	-	-	-
2C	6X60	+5	*	Y	2	Y	Y	-	-	-
4A	6X50	+5	*	Y	4	Y	Y	-	3	-
4B	6X50	+5	*	Y	4	Y	Y	-	10	-
6A	6X60	0	*	Y	6	Y	Y	-	-	-
6B	6X60	0	*	Y	6	Y	Y	-	-	-
8A	6X50	+5	*	Y	8	Y	Y	-	-	-
8B	6X50	+10	*	Y	8	Y	Y	-	20	-
S14	6X6	+130	*	Y	-	-	-	-	-	Y
S15	6X6	+130	*	Y	-	-	-	-	-	Y

\* Multizone Microwave Detection Zone


**3 Phase Fully Actuated US 70 (Morehead City) - CLS 3**

**NOTES**

- Refer to "Roadway Standard Drawings NCDOT" dated January 2012 and "Standard Specifications for Roads and Structures" dated January 2012.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Set all detector units to presence mode.
- Phase 1 may be lagged.
- In the event of loop replacement, refer to the current ITS and Signals Design Manual and submit a Plan of Record to the Signal Design Section.
- Pavement markings are existing.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.
- Closed loop system data: Controller Asset # 0614.

**PHASING DIAGRAM DETECTION LEGEND**

- ← ● DETECTED MOVEMENT
- ← ○ UNDETECTED MOVEMENT (OVERLAP)
- ← - - - UNSIGNALIZED MOVEMENT
- ← - - - PEDESTRIAN MOVEMENT



**OASIS 2070 TIMING CHART**

FEATURE	PHASE				
	1	2	4	6	8
Min Green 1 *	7	10	7	10	7
Extension 1 *	1.0	3.0	1.0	3.0	1.0
Max Green 1 *	15	60	20	60	20
Yellow Clearance	3.0	3.8	3.0	3.8	3.8
Red Clearance	2.8	2.3	2.8	2.3	2.1
Walk 1 *	-	-	-	-	-
Don't Walk 1	-	-	-	-	-
Seconds Per Actuation *	-	-	-	-	-
Max Variable Initial *	-	-	-	-	-
Time Before Reduction *	-	-	-	-	-
Time To Reduce *	-	-	-	-	-
Minimum Gap	-	-	-	-	-
Recall Mode	-	MIN RECALL	-	MIN RECALL	-
Vehicle Call Memory	-	YELLOW	-	YELLOW	-
Dual Entry	-	-	ON	-	ON
Simultaneous Gap	ON	ON	ON	ON	ON

\* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

**LEGEND**

- | PROPOSED   | EXISTING  |
|--|-----------|
| ○ → Traffic Signal Head                          | ● → N/A   |
| ○ → Modified Signal Head                         | ○ → N/A   |
| ⊥ Sign   | ⊥ N/A     |
| ⊥ Pedestrian Signal Head With Push Button & Sign | ⊥ N/A     |
| ○ → Signal Pole with Guy                         | ○ → N/A   |
| ○ → Signal Pole with Sidewalk Guy                | ○ → N/A   |
| ▭ Inductive Loop Detector                        | ▭ N/A     |
| ▭ Multizone Microwave Detection                  | ▭ N/A     |
| ⊠ Controller & Cabinet                           | ⊠ N/A     |
| □ Junction Box                                   | □ N/A     |
| □ Over-sized Junction Box                        | □ N/A     |
| - - - Directional Drill                          | - - - N/A |
| - - - 2-in Underground Conduit                   | - - - N/A |
| - - - Right of Way                               | - - - N/A |
| → Directional Arrow                              | → N/A     |
| ⊠ Metal Pole with Mastarm                        | ⊠ N/A     |

**Signal Upgrade**

**US 70 (Arendell Street) at Mansfield Parkway**

Division 2 Carteret County Morehead City

PLAN DATE: January 2015 REVIEWED BY: JPG

PREPARED BY: Jeff Spence REVIEWED BY:

SEAL

JASON P. CALLAWAY

ENGINEER

029904

750 N. Greenfield Pkwy, Garner, NC 27529

SCALE 0 20 1"=20'


REVISIONS: \_\_\_\_\_ INIT. DATE

DocuSigned by: Jason P. Callaway 12/15/2015

SIG. INVENTORY NO. 02-0614

02-0614-2015-08-18  
 S:\ITS\SIG\15\SIG\02-0614-2015-08-18\02-0614-2015-08-18.dgn  
 7:00:11 AM

**EDI MODEL 2018ECL-NC CONFLICT MONITOR PROGRAMMING DETAIL**  
(remove jumpers and set switches as shown)



**NOTES:**

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Connect serial cable from conflict monitor to comm. port 1 of 2070 controller. Ensure conflict monitor communicates with 2070.

**NOTES**

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program phases 4 and 8 for Dual Entry.
- Enable Simultaneous Gap-Out for all phases.
- Program phases 2 and 6 for Start Up In Green.
- Program phases 2 and 6 for Yellow Flash, and overlap 1 as WAG Overlaps.
- The cabinet and controller are part of the US 70 (Morehead City) Closed Loop System 3.

**SIGNAL HEAD HOOK-UP CHART**


LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX A5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	11	82	22,23	NU	NU	41,42	NU	NU	61,62	NU	NU	81,82	NU	11	NU	NU	21	NU
RED	*	128			101			134			107							
YELLOW		129			102			135			108							
GREEN		130			103			136			109							
RED ARROW													A121				A114	
YELLOW ARROW		126											A122				A115	
FLASHING YELLOW ARROW													A123				A116	
GREEN ARROW	127	127																

NU = Not Used  
\* Denotes install load resistor. See load resistor installation detail this sheet.  
★ See pictorial of head wiring in detail below.

**EQUIPMENT INFORMATION**

CONTROLLER.....2070  
CABINET.....332 W/ AUX  
SOFTWARE.....ECONOLITE OASIS  
CABINET MOUNT.....BASE  
OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE  
LOAD SWITCHES USED.....S1,S2,S5,S8,S11,AUX S1,AUX S4  
PHASES USED.....1,2,4,6,8  
OVERLAP "A".....1+2  
OVERLAP "B".....NOT USED  
OVERLAP "C".....6  
OVERLAP "D".....NOT USED


**FYA SIGNAL WIRING DETAIL**  
(wire signal heads as shown)



**NOTE**


- The sequence display for signal head 11 requires special logic programming. See sheet 2 for programming instructions.

**INPUT FILE POSITION LAYOUT**  
(front view)



EX. : 1A, 2A, ETC. = LOOP NO.'S  
FS = FLASH SENSE  
ST = STOP TIME

**LOAD RESISTOR INSTALLATION DETAIL**  
(install resistors as shown below)



**SPECIAL DETECTOR NOTE**

Install a multizone microwave detection zone for vehicle detection. Perform installation according to manufacturer's directions and NCDOT engineer-approved mounting locations to accomplish the detection schemes shown on the Signal Design Plans.

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 02-0614  
DESIGNED: January 2015  
SEALED: 12-15-15  
REVISED: N/A

Electrical Detail - Sheet 1 of 2

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Prepared in the Offices of:  
TRANSPORTATION MOBILITY AND SAFETY DIVISION  
NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
Signal Management Section  
750 N. Greenfield Pkwy, Garner, NC 27529

US 70 (Arendell Street) at Mansfield Parkway

Division 2 Carteret County Morehead City  
PLAN DATE: December 2015 REVIEWED BY: DTJ  
PREPARED BY: James Peterson REVIEWED BY:

REVISIONS INIT. DATE


DocuSigned by:  
Keith M. Minus 12/29/2015  
SEAL  
NORTH CAROLINA PROFESSIONAL ENGINEER  
KEITH M. MINUS  
036880  
DATE  
SIG. INVENTORY NO. 02-0614

2015-01-15 09:14:11 C:\Users\jpeterson\Documents\020614\_sml.ele\_20150310.dgn T.peterson

## LOGICAL I/O PROCESSOR PROGRAMMING DETAIL TO PRODUCE SPECIAL FYA-PPLT SIGNAL SEQUENCE

(program controller as shown below)

- FROM MAIN MENU PRESS '2' (PHASE CONTROL), THEN '1' (PHASE CONTROL FUNCTIONS), SCROLL TO THE BOTTOM OF THE MENU AND ENABLE ACT LOGIC COMMANDS 1, 2 AND 3.
- FROM MAIN MENU PRESS '6' (OUTPUTS), THEN '3' (LOGICAL I/O PROCESSOR).



### OUTPUT REFERENCE SCHEDULE

OUTPUT 50 = Overlap A Red  
OUTPUT 51 = Overlap A Yellow  
OUTPUT 52 = Overlap A Green

## OVERLAP PROGRAMMING DETAIL

(program controller as shown below)

FROM MAIN MENU PRESS '8' (OVERLAPS), THEN '1' (VEHICLE OVERLAP SETTINGS).

PAGE 1: VEHICLE OVERLAP 'A' SETTINGS

PHASE: |12345678910111213141516

VEH OVL PARENTS: |XX

VEH OVL NOT VEH: |

VEH OVL NOT PED: |

VEH OVL GRN EXT: |

STARTUP COLOR: - RED - YELLOW - GREEN

FLASH COLORS: - RED - YELLOW X GREEN

SELECT VEHICLE OVERLAP OPTIONS: (Y/N)

FLASH YELLOW IN CONTROLLER FLASH?...Y

GREEN EXTENSION (0-255 SEC).....0

YELLOW CLEAR (0=PARENT,3-25.5 SEC)..0.0

RED CLEAR (0=PARENT,0.1-25.5 SEC)..0.0

OUTPUT AS PHASE # (0=NONE, 1-16)....0

PRESS '+' TWICE

PAGE 1: VEHICLE OVERLAP 'C' SETTINGS

PHASE: |12345678910111213141516

VEH OVL PARENTS: | X

VEH OVL NOT VEH: |

VEH OVL NOT PED: |

VEH OVL GRN EXT: |

STARTUP COLOR: - RED - YELLOW - GREEN

FLASH COLORS: - RED - YELLOW X GREEN

SELECT VEHICLE OVERLAP OPTIONS: (Y/N)

FLASH YELLOW IN CONTROLLER FLASH?...Y

GREEN EXTENSION (0-255 SEC).....0

YELLOW CLEAR (0=PARENT,3-25.5 SEC)..0.0

RED CLEAR (0=PARENT,0.1-25.5 SEC)..0.0



OUTPUT AS PHASE # (0=NONE, 1-16)....0

OVERLAP PROGRAMMING COMPLETE

THIS ELECTRICAL DETAIL IS FOR  
THE SIGNAL DESIGN: 02-0614  
DESIGNED: January 2015  
SEALED: 12-15-15  
REVISED: N/A


Electrical Detail - Sheet 2 of 2

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

<p>Prepared In the Offices of:</p>  <p>750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p><b>US 70 (Arendell Street) at Mansfield Parkway</b></p> <p>Division 2     Carteret County     Morehead City</p> <p>PLAN DATE: December 2015     REVIEWED BY: DTJ</p> <p>PREPARED BY: James Peterson     REVIEWED BY:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>REVISIONS</th> <th>INIT.</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>	REVISIONS	INIT.	DATE				<p>SEAL</p>  <p>DocuSigned by: Keith M. Mins     12/29/2015</p> <p>SIG. INVENTORY NO. 02-0614</p>
REVISIONS	INIT.	DATE						




**Design Loading for METAL POLE NO. 1, MAST ARM A**



**Elevation View @ 270°**

**Design Loading for METAL POLE NO. 1, MAST ARM B**




**Elevation View @ 0°**

**SPECIAL NOTE**


The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

**Elevation Data for Mast Arm Attachment (H1)**

Elevation Differences for:	Arm A	Arm B
Baseline reference point at $\odot$ Foundation @ ground level	0.0 ft.	0.0 ft.
Elevation difference at High point of roadway surface	+0.42 ft.	+0.16 ft.
Elevation difference at Edge of travelway or face of curb	+/-0.0 ft.	+/-0.0 ft.




**POLE RADIAL ORIENTATION**



**8 BOLT BASE PLATE DETAIL**

See Note 6



**BASE PLATE TEMPLATE & ANCHOR BOLT LOCK PLATE DETAIL For 8 Bolt Base Plate**

**METAL POLE No. 1**

PROJECT REFERENCE NO.	SHEET NO.
W-5319	Sig. 3.3

**MAST ARM LOADING SCHEDULE**

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	66.0" W X 25.5" L	74 LBS
	SIGN RIGID MOUNTED	7.5 S.F.	30.0" W X 36.0" L	14 LBS
	STREET NAME SIGN RIGID MOUNTED	12.0 S.F.	18.0" W X 96.0" L	27 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	25.5" W X 66.0" L	74 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-3 SECTION-WITH BACKPLATE	9.3 S.F.	25.5" W X 52.5" L	60 LBS

**NOTES**

**DESIGN REFERENCE MATERIAL**

- Design the traffic signal structure and foundation in accordance with:
  - The 5th Edition 2009 AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
  - The 2012 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
  - The 2012 NCDOT Roadway Standard Drawings.
  - The traffic signal project plans and special provisions.
  - The NCDOT "Metal Pole Standards" located at the following NCDOT website: <https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

**DESIGN REQUIREMENTS**


- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using stress ratios that do not exceed 0.9.
- The camber design for the mast arm deflection should provide an appearance of a low pitched arch where the tip or the free end of the mast arm does not deflect below horizontal when fully loaded.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements. This requires staggering the connections. Use elevation data for each arm to determine appropriate arm connection points.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
  - Mast arm slope and deflection are not considered in determining the arm attachment height as they are assumed to offset each other.
  - Signal heads are rigidly mounted and vertically centered on the mast arm.
  - The roadway clearance height for design is as shown in the elevation views.
  - The top of the pole base plate is 0.75 feet above the ground elevation.
  - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
- The pole manufacturer will determine the total height (H2) of each pole using the greater of the following:
  - Mast arm attachment height (H1) plus 2 feet, or
  - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 773-2800.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The Department will provide soil penetration data (SPT) for foundation designs. Contact the Division Traffic Engineer at (919) 439-2800 for the reports.

NCDOT Wind Zone 2 (130 mph)

<p>750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p>US 70 (Arendell Street) at Mansfield Parkway</p>		
	<p>Division 2 Carteret County Morehead City</p> <p>PLAN DATE: January 2015 REVIEWED BY: JPG</p> <p>PREPARED BY: Jeff Spence REVIEWED BY:</p>	<p>REVISIONS</p> <p>INIT. DATE</p>	


31-DEC-2015 08:46  
 S:\MTCAS\Signal Design\Section\Eastern Region\01-02\W-5319\02-0614\020614\_s10.mpl-2\_20150209.dgn  
 Jpg11owcy

**Design Loading for METAL POLE NO. 2, MAST ARM A**



**Elevation View @ 270°**

**Design Loading for METAL POLE NO. 2, MAST ARM B**




**Elevation View @ 0°**

**SPECIAL NOTE**


The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

**Elevation Data for Mast Arm Attachment (H1)**


Elevation Differences for:	Arm A	Arm B
Baseline reference point at $\phi$ Foundation @ ground level	0.0 ft.	0.0 ft.
Elevation difference at High point of roadway surface	+0.12 ft.	-0.56 ft.
Elevation difference at Edge of travelway or face of curb	+/-0.0 ft.	+/-0.0 ft.



**POLE RADIAL ORIENTATION**



**8 BOLT BASE PLATE DETAIL**



**BASE PLATE TEMPLATE & ANCHOR BOLT LOCK PLATE DETAIL**  
For 8 Bolt Base Plate

**METAL POLE No. 2**

PROJECT REFERENCE NO.	SHEET NO.
W-5319	Sig. 3.4

**MAST ARM LOADING SCHEDULE**

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	66.0" W X 25.5" L	74 LBS
	SIGN RIGID MOUNTED	7.5 S.F.	30.0" W X 36.0" L	14 LBS
	STREET NAME SIGN RIGID MOUNTED	12.0 S.F.	18.0" W X 96.0" L	27 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	25.5" W X 66.0" L	74 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-3 SECTION-WITH BACKPLATE	9.3 S.F.	25.5" W X 52.5" L	60 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-5 SECTION-WITH BACKPLATE	16.3 S.F.	42.0" W X 56.0" L	103 LBS

**NOTES**

**DESIGN REFERENCE MATERIAL**

- Design the traffic signal structure and foundation in accordance with:
  - The 5th Edition 2009 AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
  - The 2012 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
  - The 2012 NCDOT Roadway Standard Drawings.
  - The traffic signal project plans and special provisions.
  - The NCDOT "Metal Pole Standards" located at the following NCDOT website: <https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

**DESIGN REQUIREMENTS**


- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using stress ratios that do not exceed 0.9.
- The camber design for the mast arm deflection should provide an appearance of a low pitched arch where the tip or the free end of the mast arm does not deflect below horizontal when fully loaded.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements. This requires staggering the connections. Use elevation data for each arm to determine appropriate arm connection points.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
  - Mast arm slope and deflection are not considered in determining the arm attachment height as they are assumed to offset each other.
  - Signal heads are rigidly mounted and vertically centered on the mast arm.
  - The roadway clearance height for design is as shown in the elevation views.
  - The top of the pole base plate is 0.75 feet above the ground elevation.
  - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
- The pole manufacturer will determine the total height (H2) of each pole using the greater of the following:
  - Mast arm attachment height (H1) plus 2 feet, or
  - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 773-2800.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The Department will provide soil penetration data (SPT) for foundation designs. Contact the Division Traffic Engineer at (919) 439-2800 for the reports.

NCDOT Wind Zone 2 (130 mph)

<p>750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p>US 70 (Arendell Street) at Mansfield Parkway</p>		
	<p>Division 2 Carteret County Morehead City</p> <p>PLAN DATE: January 2015 REVIEWED BY: JPG</p> <p>PREPARED BY: Jeff Spence REVIEWED BY:</p>	<p>DocuSigned by: Jason P. Gallaway</p> <p>12/31/2015</p>	
<p>SCALE 0 N/A N/A</p>	<p>REVISIONS</p>	<p>INIT. DATE</p>	<p>SIGNATURE DATE</p>
<p>SIG. INVENTORY NO. 02-0614</p>			

31-100-2015-08-18  
 S:\ITS\ASST\ITS\_Signal\Signal Design\Section\Eastern Region\01\1-02\W-5319\02-0614\020614\_s10.mpl-2\_20150209.dgn  
 Jpg11owcy

**PHASING DIAGRAM**



**PHASING DIAGRAM DETECTION LEGEND**

- ←●→ DETECTED MOVEMENT
- ←○→ UNDETECTED MOVEMENT (OVERLAP)
- UNSIGNALIZED MOVEMENT
- ←- - -> PEDESTRIAN MOVEMENT

**TABLE OF OPERATION**





SIGNAL FACE	PHASE			
	Ø 2 + 5	Ø 2 + 6	Ø 4 + 8	FLASH
21,22	G	G	R	Y
41,42	R	R	G	R
51	-	F	R	Y
61	-	F	R	Y
62,63	R	G	R	Y
81,82	R	R	G	R

**SIGNAL FACE I.D.**

All Heads L.E.D.

All Heads Polycarbonate

\* Install Polycarbonate Backplates



**OASIS 2070 LOOP & DETECTOR INSTALLATION CHART**


LOOP	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	DETECTOR PROGRAMMING							
					PHASE	CALLING	EXTENSION	FULL TIME DELAY	STRETCH TIME	DELAY TIME	SYSTEM LOOP	NEW CARD
2A	6X60	0	*	Y	2	Y	Y	-	-	-	-	-
2B	6X60	0	*	Y	2	Y	Y	-	-	-	-	-
4A	6X60	+5	*	Y	4	Y	Y	-	-	3	-	-
4B	6X60	+5	*	Y	4	Y	Y	-	-	5	-	-
5A	6X60	+5	*	Y	5	Y	Y	-	-	10	-	-
6A	6X60	0	*	Y	6	Y	Y	-	-	-	-	-
6B	6X60	0	*	Y	6	Y	Y	-	-	-	-	-
8A	6X15	0	*	Y	8	Y	Y	-	-	10	-	-
S1	6X6	+90	*	Y	-	-	-	-	-	-	Y	-
S2	6X6	+90	*	Y	-	-	-	-	-	-	Y	-

\* Multizone Microwave Detection Zone

3 Phase Fully Actuated  
US 70 (Morehead City) - CLS 2

**NOTES**

- Refer to "Roadway Standard Drawings NCDOT" dated January 2012 and "Standard Specifications for Roads and Structures" dated January 2012.
- Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- Phase 5 may lag.
- Set all detector units to presence mode.
- In the event of loop replacement, refer to the current ITS and Signals Design Manual and submit a Plan of Record to the Signal Design Section.
- Pavement markings are existing.
- Maximum times shown in timing chart are for free-run operation only. Coordinated signal system timing values supersede these values.
- Closed loop system data: Controller Asset #0416.



Install New Cabinet and Controller on New Foundation  
Install New Underground Electrical Service with Combination Panel and Pedestal Extension


**OASIS 2070 TIMING CHART**

FEATURE	PHASE				
	2	4	5	6	8
Min Green 1 *	10	7	7	10	7
Extension 1 *	3.0	1.0	1.0	3.0	2.0
Max Green 1 *	60	25	25	60	25
Yellow Clearance	3.8	3.8	3.0	3.8	3.0
Red Clearance	1.5	1.6	2.1	1.6	2.8
Walk 1 *	-	-	-	-	-
Don't Walk 1	-	-	-	-	-
Seconds Per Actuation *	-	-	-	-	-
Max Variable Initial *	-	-	-	-	-
Time Before Reduction *	-	-	-	-	-
Time To Reduce *	-	-	-	-	-
Minimum Gap	-	-	-	-	-
Recall Mode	MIN RECALL	-	-	MIN RECALL	-
Vehicle Call Memory	YELLOW	-	-	YELLOW	-
Dual Entry	-	ON	-	-	ON
Simultaneous Gap	ON	ON	ON	ON	ON

\* These values may be field adjusted. Do not adjust Min Green and Extension times for phases 2 and 6 lower than what is shown. Min Green for all other phases should not be lower than 4 seconds.

**LEGEND**

- | PROPOSED   | EXISTING |
|--|----------|
| ○→ Traffic Signal Head                           | ●→       |
| ●→ Modified Signal Head                          | N/A      |
| ⊥ Sign   | ⊥        |
| ⊥ Pedestrian Signal Head With Push Button & Sign | ⊥        |
| ⊥ Signal Pole with Guy                           | ⊥        |
| ⊥ Signal Pole with Sidewalk Guy                  | ⊥        |
| ⊥ Metal Pole With Mastarm                        | ⊥        |
| ▭ Inductive Loop Detector                        | ▭        |
| ▭ Multizone Microwave Detection                  | ▭        |
| ⊠ Controller & Cabinet                           | ⊠        |
| □ Junction Box                                   | □        |
| □ Over-sized Junction Box                        | □        |
| - - - 2-in Underground Conduit                   | - - -    |
| - - - Directional Drill                          | N/A      |
| - - - Right of Way                               | - - -    |
| → Directional Arrow                              | →        |



**Signal Upgrade**

750 N. Greenfield Pkwy, Garner, NC 27529

**US 70 (Arendell Street) at SR 1605 (Friendly Road)**

Division 2 Carteret County Morehead City

PLAN DATE: January 2015 REVIEWED BY:

PREPARED BY: EM Minshew REVIEWED BY:

REVISIONS INIT. DATE

SEAL

**JASON P. GALLAWAY**

PROFESSIONAL ENGINEER

SEAL 029904


DocuSigned by: Jason P. Gallaway 12/15/2015

SIG. INVENTORY NO. 02-0416

07-065-2015\_08:16  
 S:\IT\GIS\115\Sig\Signal\Signal Design Section\Eastern Region\01\02\W-5319\01\on\updates\020416.sig.dsn.20150306.dgn  
 J:\gallaway



**EDI MODEL 2018ECL-NC CONFLICT MONITOR  
PROGRAMMING DETAIL**

(remove jumpers and set switches as shown)



**NOTES:**

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Connect serial cable from conflict monitor to comm. port 1 of 2070 controller. Ensure conflict monitor communicates with 2070.



■ = DENOTES POSITION OF SWITCH

**NOTES**

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program phases 4 and 8 for Dual Entry.
- Enable Simultaneous Gap-Out for all phases.
- Program phases 2 and 6 for Start Up In Green.
- Program phases 2 and 6 for Yellow Flash, and overlap 1 as WAG Overlaps.
- The cabinet and controller are part of the US 70 Morehead City Closed Loop System 2.

**EQUIPMENT INFORMATION**

CONTROLLER.....2070  
 CABINET.....332 /W/ AUX  
 SOFTWARE.....ECONOLITE OASIS  
 CABINET MOUNT.....BASE  
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE  
 LOAD SWITCHES USED.....S2,S5,S7,S8,S11,AUX S1,AUX S4.  
 PHASES USED.....2,4,5,6,8.  
 OVERLAP "A".....2  
 OVERLAP "B".....NOT USED  
 OVERLAP "C".....5+6  
 OVERLAP "D".....NOT USED

**SIGNAL HEAD HOOK-UP CHART**

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	NU	21,22	NU	NU	41,42	NU	51	62,63	NU	NU	81,82	NU	61	NU	NU	51	NU	NU
RED		128			101			134			107							
YELLOW		129			102		*	135			108							
GREEN		130			103			136			109							
RED ARROW													A121				A114	
YELLOW ARROW													A122				A115	
FLASHING YELLOW ARROW													A123				A116	
GREEN ARROW								133										


NU = Not Used

\* Denotes install load resistor. See load resistor installation detail this sheet.

★ See pictorial of head wiring in detail below.

**FYA SIGNAL WIRING DETAIL**

(wire signal heads as shown)




**NOTE**

- The sequence display for signal head 51 requires special logic programming. See sheet 2 for programming instructions.

**INPUT FILE POSITION LAYOUT**

(front view)




EX. : 1A, 2A, ETC. = LOOP NO.'S

FS = FLASH SENSE  
 ST = STOP TIME

**LOAD RESISTOR INSTALLATION DETAIL**

(install resistors as shown below)



**SPECIAL DETECTOR NOTE**

Install a multizone microwave detection zone for vehicle detection. Perform installation according to manufacturer's directions and NCDOT engineer-approved mounting locations to accomplish the detection schemes shown on the Signal Design Plans.

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 02-0416  
 DESIGNED: January 2015  
 SEALED: 12-15-15  
 REVISED: N/A

Electrical Detail - Sheet 1 OF 2


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Prepared In the Offices of: 750 N. Greenfield Pkwy, Garner, NC 27529	US 70 (Arendell Street) at SR 1605 (Friendly Road)		SEAL KEITH M. MIMS ENGINEER
	Division 2 PLAN DATE: December 2015 PREPARED BY: James Peterson	Carteret County Morehead City REVIEWED BY: DTJ REVIEWED BY:	

**LOGICAL I/O PROCESSOR PROGRAMMING DETAIL  
TO PRODUCE SPECIAL FYA-PPLT SIGNAL SEQUENCE**

(program controller as shown below)

1. FROM MAIN MENU PRESS '2' (PHASE CONTROL), THEN '1' (PHASE CONTROL FUNCTIONS), SCROLL TO THE BOTTOM OF THE MENU AND ENABLE ACT LOGIC COMMANDS 1, 2 AND 3.
2. FROM MAIN MENU PRESS '6' (OUTPUTS), THEN '3' (LOGICAL I/O PROCESSOR).



**OUTPUT REFERENCE SCHEDULE**

- OUTPUT 42 = Overlap C Red
- OUTPUT 43 = Overlap C Yellow
- OUTPUT 44 = Overlap C Green

**OVERLAP PROGRAMMING DETAIL**

(program controller as shown below)

FROM MAIN MENU PRESS '8' (OVERLAPS), THEN '1' (VEHICLE OVERLAP SETTINGS).

PAGE 1: VEHICLE OVERLAP 'A' SETTINGS  
 PHASE: 12345678910111213141516  
 VEH OVL PARENTS: X  
 VEH OVL NOT VEH:  
 VEH OVL NOT PED:  
 VEH OVL GRN EXT:  
 STARTUP COLOR: - RED - YELLOW - GREEN  
 FLASH COLORS: - RED - YELLOW X GREEN  
 SELECT VEHICLE OVERLAP OPTIONS: (Y/N)  
 FLASH YELLOW IN CONTROLLER FLASH?...Y  
 GREEN EXTENSION (0-255 SEC)...0.0  
 YELLOW CLEAR (0=PARENT,3-25.5 SEC)...0.0  
 RED CLEAR (0=PARENT,0.1-25.5 SEC)...0.0  
 OUTPUT AS PHASE # (0=NONE, 1-16)...0

← NOTICE GREEN FLASH

PRESS '+' TWICE

PAGE 1: VEHICLE OVERLAP 'C' SETTINGS  
 PHASE: 12345678910111213141516  
 VEH OVL PARENTS: XX  
 VEH OVL NOT VEH:  
 VEH OVL NOT PED:  
 VEH OVL GRN EXT:  
 STARTUP COLOR: - RED - YELLOW - GREEN  
 FLASH COLORS: - RED - YELLOW X GREEN  
 SELECT VEHICLE OVERLAP OPTIONS: (Y/N)  
 FLASH YELLOW IN CONTROLLER FLASH?...Y  
 GREEN EXTENSION (0-255 SEC)...0.0  
 YELLOW CLEAR (0=PARENT,3-25.5 SEC)...0.0  
 RED CLEAR (0=PARENT,0.1-25.5 SEC)...0.0  
 OUTPUT AS PHASE # (0=NONE, 1-16)...0

← NOTICE GREEN FLASH

OVERLAP PROGRAMMING COMPLETE

THIS ELECTRICAL DETAIL IS FOR  
 THE SIGNAL DESIGN: 02-0416  
 DESIGNED: January 2015  
 SEALED: 12-15-15  
 REVISED: N/A


Electrical Detail - Sheet 2 of 2

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

ELECTRICAL AND PROGRAMMING DETAILS FOR: Prepared in the Offices of: 	US 70 (Arendell Street) at SR 1605 (Friendly Road)		SEAL 
	Division 2 PLAN DATE: December 2015 PREPARED BY: James Peterson	Carteret County REVIEWED BY: DTJ REVIEWED BY:	
REVISIONS			DocuSigned by: Keith M. Mins DATE: 12/30/2015 DATE:
SIG. INVENTORY NO. 02-0416			DATE:


09-06-2015 08:39  
 C:\TCS\0175-Signal\work\output\sig\_Management\020416\_sml.ele\_20150310.dgn  
 J.peterson

**Design Loading for METAL POLE NO. 1, MAST ARM A**



**Elevation View @ 270°**

**Design Loading for METAL POLE NO. 1, MAST ARM B**




**Elevation View @ 0°**

**SPECIAL NOTE**


The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

**Elevation Data for Mast Arm Attachment (H1)**


Elevation Differences for:	Arm A	Arm B
Baseline reference point at Foundation @ ground level	0.0 ft.	0.0 ft.
Elevation difference at High point of roadway surface	+0.42 ft.	+0.16 ft.
Elevation difference at Edge of travelway or face of curb	+/-0.0 ft.	+/-0.0 ft.



**POLE RADIAL ORIENTATION**



**8 BOLT BASE PLATE DETAIL**



**BASE PLATE TEMPLATE & ANCHOR BOLT LOCK PLATE DETAIL For 8 Bolt Base Plate**

**METAL POLE No. 1**

PROJECT REFERENCE NO.	SHEET NO.
W-5319	Sig. 4.3

**MAST ARM LOADING SCHEDULE**

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	66.0" W X 25.5" L	74 LBS
	SIGN RIGID MOUNTED	7.5 S.F.	30.0" W X 36.0" L	14 LBS
	STREET NAME SIGN RIGID MOUNTED	12.0 S.F.	18.0" W X 96.0" L	27 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	25.5" W X 66.0" L	74 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-3 SECTION-WITH BACKPLATE	9.3 S.F.	25.5" W X 52.5" L	60 LBS

**NOTES**

**DESIGN REFERENCE MATERIAL**

- Design the traffic signal structure and foundation in accordance with:
  - The 5th Edition 2009 AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
  - The 2012 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
  - The 2012 NCDOT Roadway Standard Drawings.
  - The traffic signal project plans and special provisions.
  - The NCDOT "Metal Pole Standards" located at the following NCDOT website: <https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

**DESIGN REQUIREMENTS**


- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using stress ratios that do not exceed 0.9.
- The camber design for the mast arm deflection should provide an appearance of a low pitched arch where the tip or the free end of the mast arm does not deflect below horizontal when fully loaded.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements. This requires staggering the connections. Use elevation data for each arm to determine appropriate arm connection points.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
  - Mast arm slope and deflection are not considered in determining the arm attachment height as they are assumed to offset each other.
  - Signal heads are rigidly mounted and vertically centered on the mast arm.
  - The roadway clearance height for design is as shown in the elevation views.
  - The top of the pole base plate is 0.75 feet above the ground elevation.
  - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
- The pole manufacturer will determine the total height (H2) of each pole using the greater of the following:
  - Mast arm attachment height (H1) plus 2 feet, or
  - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 773-2800.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The Department will provide soil penetration data (SPT) for foundation designs. Contact the Division Traffic Engineer at (919) 439-2800 for the reports.

NCDOT Wind Zone 2 (130 mph)

<p>750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p>US 70 (Arendell Street) at SR 1605 (Friendly Road)</p>		
	<p>Division 2 Carteret County Morehead City</p> <p>PLAN DATE: January 2015 REVIEWED BY: JPG</p> <p>PREPARED BY: Jeff Spence REVIEWED BY:</p>	<p>SCALE: N/A</p> <p>REVISIONS: INIT. DATE</p> <p>SIGNATURE: Jason P. Gallaway DATE: 12/31/2015</p>	


3D-065-2015-14509  
 S:\ITS\SIG\15\SIG\Signal Design\Section\Eastern Region\01\1-02\W-5319\02-0416\020416\_s10\_m1-2\_20150209.dgn  
 Jpg11owcy

**Design Loading for METAL POLE NO. 2, MAST ARM A**



**Elevation View @ 270°**

**Design Loading for METAL POLE NO. 2, MAST ARM B**




**Elevation View @ 0°**

**SPECIAL NOTE**


The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

**Elevation Data for Mast Arm Attachment (H1)**

Elevation Differences for:	Arm A	Arm B
Baseline reference point at $\odot$ Foundation @ ground level	0.0 ft.	0.0 ft.
Elevation difference at High point of roadway surface	+0.12 ft.	-0.56 ft.
Elevation difference at Edge of travelway or face of curb	+/-0.0 ft.	+/-0.0 ft.




**POLE RADIAL ORIENTATION**



**8 BOLT BASE PLATE DETAIL**

See Note 6



**BASE PLATE TEMPLATE & ANCHOR BOLT LOCK PLATE DETAIL For 8 Bolt Base Plate**

**METAL POLE No. 2**

PROJECT REFERENCE NO.	SHEET NO.
W-5319	Sig. 4.4

**MAST ARM LOADING SCHEDULE**

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	66.0" W X 25.5" L	74 LBS
	SIGN RIGID MOUNTED	7.5 S.F.	30.0" W X 36.0" L	14 LBS
	STREET NAME SIGN RIGID MOUNTED	12.0 S.F.	18.0" W X 96.0" L	27 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	25.5" W X 66.0" L	74 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-3 SECTION-WITH BACKPLATE	9.3 S.F.	25.5" W X 52.5" L	60 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-5 SECTION-WITH BACKPLATE	16.3 S.F.	42.0" W X 56.0" L	103 LBS

**NOTES**

**DESIGN REFERENCE MATERIAL**

- Design the traffic signal structure and foundation in accordance with:
  - The 5th Edition 2009 AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
  - The 2012 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
  - The 2012 NCDOT Roadway Standard Drawings.
  - The traffic signal project plans and special provisions.
  - The NCDOT "Metal Pole Standards" located at the following NCDOT website: <https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

**DESIGN REQUIREMENTS**

- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using stress ratios that do not exceed 0.9.
- The camber design for the mast arm deflection should provide an appearance of a low pitched arch where the tip or the free end of the mast arm does not deflect below horizontal when fully loaded.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements. This requires staggering the connections. Use elevation data for each arm to determine appropriate arm connection points.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
  - Mast arm slope and deflection are not considered in determining the arm attachment height as they are assumed to offset each other.
  - Signal heads are rigidly mounted and vertically centered on the mast arm.
  - The roadway clearance height for design is as shown in the elevation views.
  - The top of the pole base plate is 0.75 feet above the ground elevation.
  - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
- The pole manufacturer will determine the total height (H2) of each pole using the greater of the following:
  - Mast arm attachment height (H1) plus 2 feet, or
  - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 773-2800.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The Department will provide soil penetration data (SPT) for foundation designs. Contact the Division Traffic Engineer at (919) 439-2800 for the reports.

NCDOT Wind Zone 2 (130 mph)

<p>Prepared in the Offices of: TRANSPORTATION MOBILITY AND SAFETY DIVISION SIGNAL DESIGN SECTION 750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p>US 70 (Arendell Street) at SR 1605 (Friendly Road)</p> <p>Division 2 Carteret County Morehead City</p>		<p>SEAL JASON P. GALLAWAY ENGINEER 12/31/2015</p>
	<p>PLAN DATE: January 2015</p> <p>PREPARED BY: Jeff Spence</p>	<p>REVIEWED BY: JPG</p> <p>REVISIONS</p>	
<p>SCALE: 0 N/A</p>	<p>SIGNATURE</p>		<p>DATE</p>
<p>SIG. INVENTORY NO. 02-0416</p>			<p>DATE</p>

30-000-2016-1410  
 S:\ITS\SS\115\_Signal\Signal Design\Section\Eastern Region\01\1-02\W-5319\02-0416\020416\_s10.mpl-2\_20150209.dgn  
 Jpg11owcy






**EDI MODEL 2018ECL-NC CONFLICT MONITOR PROGRAMMING DETAIL**

(remove jumpers and set switches as shown)

REMOVE DIODE JUMPERS 1-5, 1-6, 1-9, 1-11, 2-5, 2-6, 2-9, 2-11, 4-8, 4-14, 5-9, 5-11, 6-9, 6-11, 8-14 AND 9-11.



REMOVE JUMPERS AS SHOWN

**NOTES:**

- Card is provided with all diode jumpers in place. Removal of any jumper allows its channels to run concurrently.
- Ensure jumpers SEL2-SEL5 and SEL9 are present on the monitor board.
- Ensure that Red Enable is active at all times during normal operation.
- Connect serial cable from conflict monitor to comm. port 1 of 2070 controller. Ensure conflict monitor communicates with 2070.

■ = DENOTES POSITION OF SWITCH

**NOTES**

- To prevent "flash-conflict" problems, insert red flash program blocks for all unused vehicle load switches in the output file. The installer shall verify that signal heads flash in accordance with the Signal Plans.
- Program phases 4 and 8 for Dual Entry.
- Enable Simultaneous Gap-Out for all phases.
- Program phases 2 and 6 for Start Up In Green.
- Program phase 4 for 'STARTUP PED CALL'.
- Program phases 2 and 6 for Yellow Flash, and overlap 1 as Wag Overlaps.
- The cabinet and controller are part of the US 70 (Morehead City) - CLS 2.

**EQUIPMENT INFORMATION**

CONTROLLER.....2070  
 CABINET.....332 /W/ AUX  
 SOFTWARE.....ECONOLITE OASIS  
 CABINET MOUNT.....BASE  
 OUTPUT FILE POSITIONS...18 WITH AUX. OUTPUT FILE  
 LOAD SWITCHES USED.....S1,S2,S5,S6,S7,S8,S11,AUX S1,AUX S4.  
 PHASES USED.....1,2,4,5,6,8,4 PED  
 OVERLAP "A".....1+2  
 OVERLAP "B".....NOT USED  
 OVERLAP "C".....5+6  
 OVERLAP "D".....NOT USED

**SIGNAL HEAD HOOK-UP CHART**

LOAD SWITCH NO.	S1	S2	S3	S4	S5	S6	S7	S8	S9	S10	S11	S12	AUX S1	AUX S2	AUX S3	AUX S4	AUX S5	AUX S6
CMU CHANNEL NO.	1	2	13	3	4	14	5	6	15	7	8	16	9	10	17	11	12	18
PHASE	1	2	2 PED	3	4	4 PED	5	6	6 PED	7	8	8 PED	OLA	OLB	SPARE	OLC	OLD	SPARE
SIGNAL HEAD NO.	11	21,22	NU	NU	41,42	P41, P42	51	61,62	NU	NU	81,82	NU	11	NU	NU	51	NU	NU
RED		128			101			134			107							
YELLOW	*	129			102		*	135			108							
GREEN		130			103			136			109							
RED ARROW													A121			A114		
YELLOW ARROW													A122			A115		
FLASHING YELLOW ARROW													A123			A116		
GREEN ARROW	127							133										
Hand							104											
Walking							106											


NU = Not Used

\* Denotes install load resistor. See load resistor installation detail this sheet.

\* See pictorial of head wiring in detail below.

**INPUT FILE POSITION LAYOUT**

(front view)



EX.: 1A, 2A, ETC. = LOOP NO.'S


FS = FLASH SENSE  
 ST = STOP TIME

**INPUT FILE CONNECTION & PROGRAMMING CHART**

LOOP NO.	LOOP TERMINAL	INPUT FILE POS.	PIN NO.	INPUT ASSIGNMENT NO.	DETECTOR NO.	NEMA PHASE	CALL	EXTEND	FULL TIME DELAY	STRETCH TIME	DELAY TIME
PED PUSH BUTTONS											
P41,P42	TB8-5,6	I12L	69	31	PED 4	4 PED					


NOTE:  
 INSTALL DC ISOLATOR IN INPUT FILE SLOT 112.

INPUT FILE POSITION LEGEND: J2L



**4 SECTION FYA PPLT SIGNAL WIRING DETAIL**

(wire signal heads as shown)



**NOTE**

- The sequence display for this signal requires special logic programming. See sheet 2 for programming instructions.

THIS ELECTRICAL DETAIL IS FOR THE SIGNAL DESIGN: 02-0149  
 DESIGNED: January 2015  
 SEALED: 12-15-15  
 REVISED: N/A

**SPECIAL DETECTOR NOTE**

Install a multizone microwave detection zone for vehicle detection. Perform installation according to manufacturer's directions and NCDOT engineer-approved mounting locations to accomplish the detection schemes shown on the Signal Design Plans.


**COUNTDOWN PEDESTRIAN SIGNAL OPERATION**

Countdown Ped Signals are required to display timing only during Ped Clearance Interval. Consult Ped Signal Module user's manual for instructions on selecting this feature.

**LOAD RESISTOR INSTALLATION DETAIL**

(install resistors as shown below)

VALUE (ohms)	WATTAGE
1.5K - 1.9K	25W (min)
2.0K - 3.0K	10W (min)



ELECTRICAL DETAIL SHEET 1 OF 2

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Prepared in the Offices of:  
 Transpacific Mobility and Safety Solutions  
 NORTH CAROLINA PROFESSIONAL ENGINEER  
 KEITH M. MINS  
 SEAL 036880

US 70 (Arendell Street) at Savannah Avenue

Division 2 Carteret County Morehead City  
 PLAN DATE: December 2015 REVIEWED BY: DTJ  
 PREPARED BY: James Peterson REVIEWED BY:

REVISIONS INIT. DATE

DocuSigned by: Keith M. Mins 12/29/2015  
 252077856273466 DATE

750 N. Greenfield Pkwy, Garner, NC 27529  
 SIG. INVENTORY NO. 02-0149

## LOGICAL I/O PROCESSOR PROGRAMMING DETAIL TO PRODUCE SPECIAL FYA-PPLT SIGNAL SEQUENCE

(program controller as shown below)

1. FROM MAIN MENU PRESS '2' (PHASE CONTROL), THEN '1' (PHASE CONTROL FUNCTIONS). SCROLL TO THE BOTTOM OF THE MENU AND ENABLE ACT LOGIC COMMANDS 1, 2, 3, 4, 5 AND 6.
2. FROM MAIN MENU PRESS '6' (OUTPUTS), THEN '3' (LOGICAL I/O PROCESSOR).

LOGICAL I/O COMMAND #1 (+/-COMMAND#)  
IF ACTIVE PHASE #1 IS ON  
AND RED CLEAR ON PHASE #1 IS ON

↓  
SCROLL DOWN

THEN:  
SET OUTPUT ASSIGNMENT #50 ON  
SET OUTPUT ASSIGNMENT #51 OFF

PRESS '+'

NOTE: LOGIC FOR PHASE 1 RED CLEAR WHEN TRANSITIONING FROM PHASE 1 TO PHASE 2 (HEAD 11).

LOGICAL I/O COMMAND #2 (+/-COMMAND#)  
IF ACTIVE PHASE #1 IS ON

↓  
SCROLL DOWN

THEN:  
SET OUTPUT ASSIGNMENT #52 OFF

PRESS '+'

NOTE: LOGIC FOR SWITCHING FLASHING YELLOW ARROW "OFF" DURING PHASE 1 (HEAD 11).

LOGICAL I/O COMMAND #3 (+/-COMMAND#)  
IF YELLOW ON PHASE #1 IS ON

↓  
SCROLL DOWN

THEN:  
SET OUTPUT ASSIGNMENT #51 ON

PRESS '+'

NOTE: LOGIC FOR YELLOW ARROW CLEARANCE FROM PHASE 1 (HEAD 11).

LOGICAL I/O COMMAND #4 (+/-COMMAND#)  
IF ACTIVE PHASE #5 IS ON  
AND RED CLEAR ON PHASE #5 IS ON

↓  
SCROLL DOWN

THEN:  
SET OUTPUT ASSIGNMENT #42 ON  
SET OUTPUT ASSIGNMENT #43 OFF

PRESS '+'

NOTE: LOGIC FOR PHASE 5 RED CLEAR WHEN TRANSITIONING FROM PHASE 5 TO PHASE 6 (HEAD 51).

LOGICAL I/O COMMAND #5 (+/-COMMAND#)  
IF ACTIVE PHASE #5 IS ON

↓  
SCROLL DOWN

THEN:  
SET OUTPUT ASSIGNMENT #44 OFF

PRESS '+'

NOTE: LOGIC FOR SWITCHING FLASHING YELLOW ARROW "OFF" DURING PHASE 5 (HEAD 51).

LOGICAL I/O COMMAND #6 (+/-COMMAND#)  
IF YELLOW ON PHASE #5 IS ON

↓  
SCROLL DOWN

THEN:  
SET OUTPUT ASSIGNMENT #43 ON

PRESS '+'

NOTE: LOGIC FOR YELLOW ARROW CLEARANCE FROM PHASE 5 (HEAD 51).

LOGIC I/O PROCESSOR PROGRAMMING COMPLETE

OUTPUT REFERENCE SCHEDULE
OUTPUT 42 = Overlap C Red
OUTPUT 43 = Overlap C Yellow
OUTPUT 44 = Overlap C Green
OUTPUT 50 = Overlap A Red
OUTPUT 51 = Overlap A Yellow
OUTPUT 52 = Overlap A Green

## OVERLAP PROGRAMMING DETAIL

(program controller as shown below)

FROM MAIN MENU PRESS '8' (OVERLAPS), THEN '1' (VEHICLE OVERLAP SETTINGS).

PAGE 1: VEHICLE OVERLAP 'A' SETTINGS  
PHASE: 12345678910111213141516  
VEH OVL PARENTS: XX  
VEH OVL NOT VEH:  
VEH OVL NOT PED:  
VEH OVL GRN EXT:  
STARTUP COLOR: \_ RED \_ YELLOW \_ GREEN  
FLASH COLORS: \_ RED \_ YELLOW X GREEN  
SELECT VEHICLE OVERLAP OPTIONS: (Y/N)  
FLASH YELLOW IN CONTROLLER FLASH?...Y  
GREEN EXTENSION (0-255 SEC)...0.0  
YELLOW CLEAR (0=PARENT,3-25.5 SEC)...0.0  
RED CLEAR (0=PARENT,0.1-25.5 SEC)...0.0  
OUTPUT AS PHASE # (0=NONE, 1-16)...0

← NOTICE GREEN FLASH

PRESS '+' TWICE

PAGE 1: VEHICLE OVERLAP 'C' SETTINGS  
PHASE: 12345678910111213141516  
VEH OVL PARENTS: XX  
VEH OVL NOT VEH:  
VEH OVL NOT PED:  
VEH OVL GRN EXT:  
STARTUP COLOR: \_ RED \_ YELLOW \_ GREEN  
FLASH COLORS: \_ RED \_ YELLOW X GREEN  
SELECT VEHICLE OVERLAP OPTIONS: (Y/N)  
FLASH YELLOW IN CONTROLLER FLASH?...Y  
GREEN EXTENSION (0-255 SEC)...0.0  
YELLOW CLEAR (0=PARENT,3-25.5 SEC)...0.0  
RED CLEAR (0=PARENT,0.1-25.5 SEC)...0.0  
OUTPUT AS PHASE # (0=NONE, 1-16)...0



← NOTICE GREEN FLASH

OVERLAP PROGRAMMING COMPLETE

THIS ELECTRICAL DETAIL IS FOR  
THE SIGNAL DESIGN: 02-0149  
DESIGNED: January 2015  
SEALED: 12-15-15  
REVISED: N/A


ELECTRICAL DETAIL SHEET 2 OF 2

DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

<p>Prepared In the Offices of:</p>  <p>750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p><b>US 70 (Arendell Street) at Savannah Avenue</b></p> <p>Division 2 Carteret County Morehead City</p> <p>PLAN DATE: December 2015 REVIEWED BY: DTJ</p> <p>PREPARED BY: James Peterson REVIEWED BY:</p>	<p>SEAL</p>  <p>SEAL 036880 ENGINEER KEITH M. MIRAS</p>	<p>DocuSigned by:</p> <p>Keith M. Miras 12/29/2015</p> <p>SIG. INVENTORY NO. 02-0149</p>								
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>REVISIONS</th> <th>INIT.</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>		REVISIONS	INIT.	DATE				<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td> </td> <td> </td> </tr> </table>			
REVISIONS	INIT.	DATE									

02-0149-2015\_08-12  
S:\TSS\0149-TS\Sig\m\work\output\sig\_Mir\ Peterson\020149\_sml.ele...xxx.dgn  
J. Peterson

**Design Loading for METAL POLE NO. 1, MAST ARM A**



**Elevation View @ 270°**

**SPECIAL NOTE**

The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

**Elevation Data for Mast Arm Attachment (H1)**

Elevation Differences for:	Arm A	Arm B
Baseline reference point at $\phi$ Foundation @ ground level	0.0 ft.	0.0 ft.
Elevation difference at High point of roadway surface	-0.04 ft.	-0.24 ft.
Elevation difference at Edge of travelway or face of curb	+/-0.0 ft.	+/-0.0 ft.

**METAL POLE No. 1**

PROJECT REFERENCE NO.	SHEET NO.
W-5319	Sig. 5.3

**MAST ARM LOADING SCHEDULE**

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	66.0" W X 25.5" L	74 LBS
	SIGN RIGID MOUNTED	7.5 S.F.	30.0" W X 36.0" L	14 LBS
	STREET NAME SIGN RIGID MOUNTED	12.0 S.F.	18.0" W X 96.0" L	27 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	25.5" W X 66.0" L	74 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-3 SECTION-WITH BACKPLATE	9.3 S.F.	25.5" W X 52.5" L	60 LBS


**NOTES**

**DESIGN REFERENCE MATERIAL**


- Design the traffic signal structure and foundation in accordance with:
  - The 5th Edition 2009 AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
  - The 2012 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
  - The 2012 NCDOT Roadway Standard Drawings.
  - The traffic signal project plans and special provisions.
  - The NCDOT "Metal Pole Standards" located at the following NCDOT website: <https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

**DESIGN REQUIREMENTS**

- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using stress ratios that do not exceed 0.9.
- The camber design for the mast arm deflection should provide an appearance of a low pitched arch where the tip or the free end of the mast arm does not deflect below horizontal when fully loaded.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements. This requires staggering the connections. Use elevation data for each arm to determine appropriate arm connection points.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
  - Mast arm slope and deflection are not considered in determining the arm attachment height as they are assumed to offset each other.
  - Signal heads are rigidly mounted and vertically centered on the mast arm.
  - The roadway clearance height for design is as shown in the elevation views.
  - The top of the pole base plate is 0.75 feet above the ground elevation.
  - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
- The pole manufacturer will determine the total height (H2) of each pole using the greater of the following:
  - Mast arm attachment height (H1) plus 2 feet, or
  - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 773-2800.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The Department will provide soil penetration data (SPT) for foundation designs. Contact the Division Traffic Engineer at (919) 439-2800 for the reports.




**POLE RADIAL ORIENTATION**




**8 BOLT BASE PLATE DETAIL**

See Note 6



**BASE PLATE TEMPLATE & ANCHOR BOLT LOCK PLATE DETAIL**  
For 8 Bolt Base Plate

**Design Loading for METAL POLE NO. 1, MAST ARM B**




**Elevation View @ 0°**

**NCDOT Wind Zone 2 (130 mph)**

<p>Prepared in the Offices of: TRANSPORTATION MOBILITY AND SAFETY DIVISION SIGNAL DESIGN SECTION 750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p><b>US 70 (Arendell Street) at Savannah Avenue</b></p> <p>Division 2 Carteret County Morehead City</p>		
	<p>PLAN DATE: January 2015</p> <p>PREPARED BY: Jeff Spence</p>	<p>REVIEWED BY: JPG</p> <p>REVISIONS</p>	
<p>SCALE: N/A</p>	<p>SIG. INVENTORY NO. 02-0149</p>		

30-000-2015-13-53  
 S:\MTC\SS\115\SIGNAL\DESIGN\Region01\49\20149\_510.mpl-2\_20150209.dgn  
 Jpg11owcy

**Design Loading for METAL POLE NO. 2, MAST ARM A**



**Elevation View @ 270°**

**SPECIAL NOTE**

The contractor is responsible for verifying that the mast arm attachment height (H1) will provide the "Design Height" clearance from the roadway before submitting final shop drawings for approval. Verify elevation data below which was obtained by field measurement or from available project survey data.

**Elevation Data for Mast Arm Attachment (H1)**

Elevation Differences for:	Arm A	Arm B
Baseline reference point at $\phi$ Foundation @ ground level	0.0 ft.	0.0 ft.
Elevation difference at High point of roadway surface	-0.81 ft.	-1.29 ft.
Elevation difference at Edge of travelway or face of curb	+/-0.0 ft.	+/-0.0 ft.

**METAL POLE No. 2**

PROJECT REFERENCE NO.	SHEET NO.
W-5319	Sig. 5.4

**MAST ARM LOADING SCHEDULE**

LOADING SYMBOL	DESCRIPTION	AREA	SIZE	WEIGHT
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	66.0" W X 25.5" L	74 LBS
	SIGN RIGID MOUNTED	7.5 S.F.	30.0" W X 36.0" L	14 LBS
	STREET NAME SIGN RIGID MOUNTED	12.0 S.F.	18.0" W X 96.0" L	27 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-4 SECTION-WITH BACKPLATE	11.5 S.F.	25.5" W X 66.0" L	74 LBS
	RIGID MOUNTED SIGNAL HEAD 12"-3 SECTION-WITH BACKPLATE	9.3 S.F.	25.5" W X 52.5" L	60 LBS


**NOTES**

**DESIGN REFERENCE MATERIAL**

- Design the traffic signal structure and foundation in accordance with:
  - The 5th Edition 2009 AASHTO "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, including all of the latest interim revisions.
  - The 2012 NCDOT "Standard Specifications for Roads and Structures." The latest addenda to the specifications can be found in the traffic signal project special provisions.
  - The 2012 NCDOT Roadway Standard Drawings.
  - The traffic signal project plans and special provisions.
  - The NCDOT "Metal Pole Standards" located at the following NCDOT website: <https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>


**DESIGN REQUIREMENTS**

- Design the traffic signal structure using the loading conditions shown in the elevation views. These are anticipated worst case "design loads" and may not represent the actual loads that will be applied at the time of the installation. The contractor should refer to the traffic signal plans for the actual loads that will be applied at the time of the installation.
- Design all signal supports using stress ratios that do not exceed 0.9.
- The camber design for the mast arm deflection should provide an appearance of a low pitched arch where the tip or the free end of the mast arm does not deflect below horizontal when fully loaded.
- A clamp-type bolted mast arm-to-pole connection may be used instead of the welded ring stiffened box connection shown as long as the connection meets all of the design requirements. This requires staggering the connections. Use elevation data for each arm to determine appropriate arm connection points.
- Design base plate with 8 anchor bolt holes. Provide 2 inch x 60 inch anchor bolts.
- The mast arm attachment height (H1) shown is based on the following design assumptions:
  - Mast arm slope and deflection are not considered in determining the arm attachment height as they are assumed to offset each other.
  - Signal heads are rigidly mounted and vertically centered on the mast arm.
  - The roadway clearance height for design is as shown in the elevation views.
  - The top of the pole base plate is 0.75 feet above the ground elevation.
  - Refer to the Elevation Data Chart for the elevation differences between the proposed foundation ground level and the high point of the roadway.
- The pole manufacturer will determine the total height (H2) of each pole using the greater of the following:
  - Mast arm attachment height (H1) plus 2 feet, or
  - H1 plus 1/2 of the total height of the mast arm attachment assembly plus 1 foot.
- If pole location adjustments are required, the contractor must gain approval from the Engineer as this may affect the mast arm lengths and arm attachment heights. The contractor may contact the Signal Design Section Senior Structural Engineer for assistance at (919) 773-2800.
- The contractor is responsible for verifying that the mast arm length shown will allow proper positioning of the signal heads over the roadway.
- The Department will provide soil penetration data (SPT) for foundation designs. Contact the Division Traffic Engineer at (919) 439-2800 for the reports.




**POLE RADIAL ORIENTATION**


**Design Loading for METAL POLE NO. 2, MAST ARM B**



**Elevation View @ 0°**



**8 BOLT BASE PLATE DETAIL**



**BASE PLATE TEMPLATE & ANCHOR BOLT LOCK PLATE DETAIL For 8 Bolt Base Plate**

NCDOT Wind Zone 2 (130 mph)


<p>750 N. Greenfield Pkwy, Garner, NC 27529</p>	<p>US 70 (Arendell Street) at Savannah Avenue</p>		
	<p>Division 2 Carteret County Morehead City</p>	<p>PLAN DATE: January 2015 REVIEWED BY: JPG</p>	
<p>SCALE 0 N/A N/A</p>	<p>PREPARED BY: Jeff Spence REVIEWED BY:</p>	<p>REVISIONS</p>	<p>INIT. DATE</p>
<p>DocuSigned by: Jason P. Callaway 12/31/2015</p>			<p>SIG. INVENTORY NO. 02-0149</p>

30-000-2015-13-54  
 S:\MTC\5319\15\_Signal\Signal Design\Section\Eastern Region\01-02\W-5319\W-02-0149.dgn  
 7/20/15 10:02 AM

# STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

## STANDARD DRAWINGS FOR METAL POLES

**NCDOT METAL POLE STANDARDS**



<https://connect.ncdot.gov/resources/safety/Pages/ITS-Design-Resources.aspx>

Prepared In the Offices of:

750 N. Greenfield Pkwy, Garner, NC 27529

Designed in conformance with the latest 2012 Interim to the 5th Edition 2009 **AASHTO** Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals


INDEX OF PLANS	
DRAWING NUMBER	DESCRIPTION
M 1	Title Sheet
M 2	Fabrication Details - All Poles
M 3	Fabrication Details - Strain Poles
M 4,5	Fabrication Details - Mast Arm Poles
M 6	Construction Details - Strain Poles
M 7	Construction Details - Foundations
M 8,9	Standard Strain Pole Foundations

**NCDOT CONTACTS:**  
**MOBILITY AND SAFETY DIVISION - ITS AND SIGNALS UNIT**

**G. A. FULLER, P.E. - STATE ITS AND SIGNALS ENGINEER**  
**G. G. MURR, JR., P.E. - STATE SIGNALS ENGINEER**  
**D.C. SARKAR, P.E. - ITS AND SIGNALS SENIOR STRUCTURAL ENGINEER**  
**C.F. ANDREWS - ITS AND SIGNALS JOURNEY STRUCTURAL ENGINEER**


SEAL

Designed by: *Debesh C. Sarkar* 8/26/2014  
DATE



Note: Unless otherwise specified, locate Terminal Compartment 1 foot above the pole base plate at 180 degrees on the pole's radial index.

**Terminal Compartment Detail**



Construct Templates and Plates from 1/4 inch min. thick Steel. Galvanizing is not required.  
**Base Plate Template and Anchor Bolt Lock Plate Details**

MFG	_____	MFG. DATE: MM/YY
SHAFT	D/T/L/Y	_____
ARM-A	D/T/L/Y	_____
ARM-B	D/T/L/Y	_____
A.B. DIA./B.C./L/Y	_____	_____
NCDOT STANDARD	_____	_____

Shaft I.D. Tag  
(Provide on Strain Poles and Mast Arm Poles)


**Notes:**

- 1) D= Diameter, T= Thickness, L= Length, Y= Yield Strength
- 2) A.B. = Anchor Bolt
- 3) B.C. = Bolt Circle of Anchor Bolts
- 4) If Custom Design, use "NCDOT STANDARD" line for pole I.D. number and Signal Inv. Number.
- 5) See drawing M4 for mounting positions of I.D. tags.

**Identification Tag Details**


MFG	_____	MFG. DATE: MM/YY
SECTION	D/T/L/Y	_____
NCDOT STANDARD	_____	_____

Arm I.D. Tag  
(Provide on each section of a multi-section mast arm)



**Anchor Bolt Detail**

Note: See Strain Pole drawing M3 and Mast arm drawing M4 for base plate weld details.




**8 Bolt Base Plate Detail**


	Typical Fabrication Details Common To All Metal Poles		
	PLAN DATE: AUGUST 2013 PREPARED BY: N. BITTING	DESIGNED BY: C.F. ANDREWS REVIEWED BY: D.C. SARKAR	
SCALE: NONE	REVISIONS: _____	INIT. DATE: _____	DocuSign by: Dinesh C. Sarkar 8/26/2014 DATE: _____ SIG. INVENTORY NO. _____

06-AUG-2014 08:55  
 S:\IT\SS\115\_Signal\Signal Design\Section\Eastern Region\MM\_Sheets\2012\_M2\_Fab\_Details\_All\_Poles.dgn  
 Top | Lowy


**Fabrication Details – All Poles**




Cable Entrances at Top of Pole



Section B-B  
Pole Base Plate  
(See drawing M2)




Radial Orientation for Factory Installed  
Accessories at Top of Pole



Socket Connection Weld Detail

2 Cable Clamps designed for variable attachment heights from 1'-6" to 10' below the top of the pole.




Monotube Strain Pole  
(.14\"/>


	Typical Fabrication Details For Strain Poles		
	PLAN DATE: AUGUST 2013 PREPARED BY: N. BITTING	DESIGNED BY: C.F. ANDREWS REVIEWED BY: D.C. SARKAR	
SCALE: 0 NA NONE	REVISIONS: _____ INIT.: _____ DATE: _____	SIG. INVENTORY NO.	

06-AUG-2014 09:51  
 C:\TCS\Signal Design\Section\Eastern Region\M3\_Fab\_Details\Strain\_Poles.dgn  
 Top View


**Fabrication Details – Strain Poles**




Section A-A  
(See drawing M 2)  
**Pole Base Plate**




3/4" Factory Drilled Hole in Outboard Tube.  
Field Drill Inboard Tube.  
5/8" Galvanized Thru Stud with  
(2) Hex. Locknuts Each.



**Slip Fit Joint Detail for Mast Arm**




Monotube Mast Arm Pole  
(.14in./ft. taper)



Section B-B  
(Pole Attachment to Base Plate)

**Full-Penetration Groove Weld Detail**



**Mast Arm Radial Orientation**




	Typical Fabrication Details for Mast Arm Poles		
	PLAN DATE: AUGUST 2013 PREPARED BY: N. BITTING	DESIGNED BY: C.F. ANDREWS REVIEWED BY: D.C. SARKAR	
SCALE: 0 NA NONE	REVISIONS:	INIT. DATE:	SIG. INVENTORY NO.:

26-AUG-2014 08:50  
 S:\TDS\Signal Design\Section\Eastern Region\M\ Sheets\2012\_M4\_Fab\_Details\MastArms.dgn  
 T:\jll\cwy

**Fabrication Details – Mast Arm Poles**



# Welded Ring Stiffened Mast Arm Connection




**Full-Penetration Groove Weld Detail**

**Notes:**


1. Provide a permanent means of identification above the mast arm to indicate proper attachment orientation of the mast arm.
2. Designer will determine the size of all structural components, plates, fasteners, and welds shown unless they are already specified.
3. Designer is responsible for providing appropriate drainage points.

	<p>Prepared In the Offices of:</p> <p><b>Transporation, Mobility and Safety Solutions</b></p> <p>750 N. Greenfield Pkwy, Garner, NC 27529</p>		<p><b>Fabrication Details For Mast Arm Connection To Pole</b></p>		<p>SEAL</p> <p>PROFESSIONAL ENGINEER</p> <p>STATE OF NORTH CAROLINA</p> <p>028094</p> <p>D. C. SARKAR</p>
	<p>PLAN DATE: AUGUST 2013</p> <p>DESIGNED BY: C.F. ANDREWS</p> <p>PREPARED BY: N. BITTING</p> <p>REVIEWED BY: D.C. SARKAR</p>	<p>REVISIONS</p> <p>INIT.</p> <p>DATE</p>	<p>INIT.</p> <p>DATE</p>	<p>DocuSigned by:</p> <p>D. C. Sarkar</p> <p>8/26/2014</p> <p>44E8E32E147E4C4</p> <p>DATE</p>	




### Strain Pole Attachments

Note: Strap all signal cables to the side of the pole with 3/4" stainless steel straps when the distance between the spanwire attachment clamp and the weatherheads exceeds 36"






### Attachment of Cable to Intermediate Metal Pole



### Metal Pole Grounding Detail

	<b>Construction Details Strain Poles</b>		
	PLAN DATE: AUGUST 2013 PREPARED BY: N. BITTING	REVIEWED BY: C.F. ANDREWS REVIEWED BY: D.C. SARKAR	
SCALE: 0 NA NONE			

### Reinforcing Steel Bars




Typical "C" Bars

Shaft Dia (in.)	Conc. Volume (cu. yds.)	Bar Name	MIN.	Size	Type	Length
48"	.465 x L	V1	***	#8	STR.	**
		C	*	#4	CIR.	12'-6"


\* See Note No. 1  
\*\* See Note No. 3  
\*\*\* See Note No. 4

### Typical Foundation Anchor Bolt Details

(Reinforcing Cage Not Shown for Clarity)



### Typical Foundation Conduit Details



### Notes

- The number of C-bars is based on foundation depth and/or as required. For standard foundations, see sheets M 8 and M 9 for details.
- Circular tie reinforcing rings may be vertically adjusted by +/- 3" at a depth between 2'-0" and 3'-0" to facilitate the installation of electrical conduit entering in the cage.
- The length of V1-bars is based on foundation depth. For standard foundations, see sheets M 8 and M 9 for details. Vertical reinforcing bars (V1) may be horizontally adjusted by +/- 3" to facilitate the installation of electrical conduit entering into the cage.
- Provide vertical reinforcement as required per design. See sheets M 8 and M9 for details.

	<b>Construction Details Foundations</b>		
	PLAN DATE: AUGUST 2013 PREPARED BY: N. BITTING	DESIGNED BY: K.C. DURIGON REVIEWED BY: D.C. SARKAR	
SCALE: 0 NA NONE	REVISIONS:	INIT. DATE:	SIG. INVENTORY NO.:

# SATURATED SOIL CONDITION

		STANDARD STRAIN POLES						STANDARD FOUNDATIONS 48" Diameter Drilled Pier Length (L) - Feet							Reinforcement			
		Case No.	Pole Height (Ft.)	Base Plate BC (In.)	Reactions at the Pole Base			Clay				Sand			Longitudinal		Stirrups	
					Axial (kip)	Shear (kip)	Moment (ft-kip)	Medium N-Value 4-8	Stiff N-Value 9-15	Very Stiff N-Value 16-30	Hard N-Value >30	Loose N-Value 4-10	Medium N-Value 11-30	Dense N-Value >30	Bar Size (#)	Quantity	Bar Size (#)	Spacing (in.)
WIND ZONE 1	LIGHT	S26L3	26	25	2	11	270	19	13	9	8	17	14.5	12.5	8	13	4	12
		S30L3	30	25	2	11	300	20	13.5	9	8	17.5	15	13	8	14	4	12
		S35L3	35	25	3	11	320	20	13.5	9.5	8	17.5	15	13	8	15	4	12
	HEAVY	S30H3	30	29	3	16	450	24.5	17	13	11	21	17.5	15	8	18	4	12
		S35H3	35	29	4	16	515	26	17.5	12	8.5	22	18.5	16	8	20	4	12
WIND ZONE 2	LIGHT	S26L2	26	23	2	10	245	18	12.5	8.5	8	16.5	14	12	8	13	4	12
		S30L2	30	23	2	10	270	19	12.5	9	8	16.5	14	12.5	8	13	4	12
		S35L2	35	23	3	10	300	19.5	13	9	8	17	14.5	13	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	25.5	15.5	11	8	20	17	14.5	8	17	4	12
		S35H2	35	29	4	15	475	25	16.5	11.5	8	21	17.5	15.5	8	19	4	12
WIND ZONE 3	LIGHT	S26L2	26	23	2	10	245	18	12.5	8.5	8	16.5	14	12	8	13	4	12
		S30L2	30	23	2	10	270	19	12.5	9	8	16.5	14	12.5	8	13	4	12
		S35L2	35	23	3	10	300	19.5	13	9	8	17	14.5	13	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	25.5	15.5	11	8	20	17	14.5	8	17	4	12
		S35H2	35	29	4	15	475	25	16.5	11.5	8	21	17.5	15.5	8	19	4	12
WIND ZONE 4	LIGHT	S26L1	26	22	2	8	190	16	11	8	8	15	12.5	11	8	12	4	12
		S30L1	30	22	2	8	205	16.5	11.5	8	8	15	13	11.5	8	12	4	12
		S35L1	35	22	3	8	230	17	12	8	8	15.5	13.5	11.5	8	12	4	12
	HEAVY	S30H1	30	25	3	12	320	20.5	14	9.5	8	18	15	13.5	8	15	4	12
		S35H1	35	25	4	12	350	21	14.5	10	8	18.5	15.5	13.5	8	16	4	12
WIND ZONE 5	LIGHT	S26L2	26	23	2	10	245	18	12.5	8.5	8	16.5	14	12	8	13	4	12
		S30L2	30	23	2	10	270	19	12.5	9	8	16.5	14	12.5	8	13	4	12
		S35L2	35	23	3	10	300	19.5	13	9	8	17	14.5	13	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	25.5	15.5	11	8	20	17	14.5	8	17	4	12
		S35H2	35	29	4	15	475	25	16.5	11.5	8	21	17.5	15.5	8	19	4	12

**Fabrication Design Notes:**

1. Values shown in the "Reactions at the Pole Base" column represent the minimum acceptable capacity allowed for design using a design CSR of 1.00.
2. Min. base plate thickness (T) is 2.0 inches.

**Foundation Selection:**



1. Perform a standard penetration test at each proposed foundation site to determine "N" value.
2. Select the appropriate wind zone from M 1 drawing.
3. Select the soil type (Clay or Sand) that best describes the soil characteristics.
4. Get the appropriate standard pole case number from the plans or from the Engineer.
5. Select the appropriate column in the chart based on soil type and "N" value. Select the appropriate row based on the pole load case.  
The foundation depth is the value where the column and the row intersect.
6. Reference Drilled Shafts: Construction Procedures and Design Methods, FHWA -IF-99-025

- S30H1 - Hard Clay-Stirrup Spacing: 6 in. c/c
- S30H2 - Hard Clay-Stirrup Spacing: 6 in. c/c
- S30H3 - Hard Clay-Stirrup Spacing: 6 in. c/c
- Dense Sand-Stirrup Spacing: 6 in. c/c
- S35H1 - Hard Clay - Stirrup Spacing: 6 in. c/c
- S35H2 - Very Stiff Clay-Stirrup Spacing: 6 in. c/c
- Hard Clay- Stirrup Spacing: 6 in. c/c
- Dense Sand- Stirrup Spacing: 6 in. c/c
- S35H3 - Very Stiff Clay-Stirrup Spacing: 6 in. c/c
- Dense Sand-Stirrup Spacing: 6 in. c/c

48" Dia. Foundations Concrete Volume (cubic yards) = (0.465) x Foundation Depth

26-M8-2014-08-12  
S:\Projects\13-Signal\Signal Design Section\Eastern Region\MM\_Sheets\2012\_M8\_Standard Foundations\_Wet.dgn  
J.Li

Standard Strain Pole Foundation-Saturated Soil Condition

	<p><b>Standard Strain Pole Foundation for Saturated Soil Condition</b></p> <p>PLAN DATE: SEPTEMBER 2013    DESIGNED BY: C.B. COGDILL                  PREPARED BY: N. BITTING    REVIEWED BY: D. SARKAR</p>	
SCALE: 0 NA None	REVISIONS:    INIT.    DATE	DocuSigned by: Deborah C. Sarkar 8/26/2014 44EBE32E147E4C4...    DATE

# DRY SOIL CONDITION

		STANDARD STRAIN POLES						STANDARD FOUNDATIONS 48" Diameter Drilled Pier Length (L) - Feet						Reinforcement				
		Case No.	Pole Height (Ft.)	Base Plate BC (In.)	Reactions at the Pole Base			Clay				Sand			Longitudinal		Stirrups	
					Axial (kip)	Shear (kip)	Moment (ft-kip)	Medium N-Value 4-8	Stiff N-Value 9-15	Very Stiff N-Value 16-30	Hard N-Value >30	Loose N-Value 4-10	Medium N-Value 11-30	Dense N-Value >30	Bar Size (#)	Quantity	Bar Size (#)	Spacing (in.)
WIND ZONE 1	LIGHT	S26L3	26	25	2	11	270	18	12.5	9	8	14.5	11	10	8	13	4	12
		S30L3	30	25	2	11	300	18.5	13	9	8	15	11.5	10	8	14	4	12
		S35L3	35	25	3	11	320	19	13.5	9.5	8	15	11.5	10.5	8	15	4	12
	HEAVY	S30H3	30	29	3	16	450	23	16	11	8	17.5	13.5	11.5	8	18	4	12
		S35H3	35	29	4	16	515	24.5	16.5	12	8.5	18.5	14	12	8	20	4	12
WIND ZONE 2	LIGHT	S26L2	26	23	2	10	245	17	12	8.5	8	14	11	9.5	8	13	4	12
		S30L2	30	23	2	10	270	18	12.5	8.5	8	14.5	11	10	8	13	4	12
		S35L2	35	23	3	10	300	18.5	13	9	8	14.5	11.5	10	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	22	15	10.5	8	17	13	11.5	8	17	4	12
		S35H2	35	29	4	15	475	23.5	16	11.5	8	18	13.5	12	8	19	4	12
WIND ZONE 3	LIGHT	S26L2	26	23	2	10	245	17	12	8.5	8	14	11	9.5	8	13	4	12
		S30L2	30	23	2	10	270	18	12.5	8.5	8	14.5	11	10	8	13	4	12
		S35L2	35	23	3	10	300	18.5	13	9	8	14.5	11.5	10	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	22	15	10.5	8	17	13	11.5	8	17	4	12
		S35H2	35	29	4	15	475	23.5	16	11.5	8	18	13.5	12	8	19	4	12
WIND ZONE 4	LIGHT	S26L1	26	22	2	8	190	15.5	10.5	8	8	13	10	9	8	12	4	12
		S30L1	30	22	2	8	205	15.5	11	8	8	13	10	9	8	12	4	12
		S35L1	35	22	3	8	230	16.5	11.5	8	8	13.5	10.5	9	8	12	4	12
	HEAVY	S30H1	30	25	3	12	320	19.5	13.5	9.5	8	15	12	10.5	8	15	4	12
		S35H1	35	25	4	12	350	20	14	10	8	15.5	12	10.5	8	15	4	12
WIND ZONE 5	LIGHT	S26L2	26	23	2	10	245	17	12	8.5	8	14	11	9.5	8	13	4	12
		S30L2	30	23	2	10	270	18	12.5	8.5	8	14.5	11	10	8	13	4	12
		S35L2	35	23	3	10	300	18.5	13	9	8	14.5	11.5	10	8	14	4	12
	HEAVY	S30H2	30	29	3	15	415	22	15	10.5	8	17	13	11.5	8	17	4	12
		S35H2	35	29	4	15	475	23.5	16	11.5	8	18	13.5	12	8	19	4	12

### Fabrication Design Notes:



1. Values shown in the "Reactions at the Pole Base" column represent the minimum acceptable capacity allowed for design using a design CSR of 1.00.
2. Min. base plate thickness (T) is 2.0 inches.

### Foundation Selection:

1. Perform a standard penetration test at each proposed foundation site to determine "N" value.
2. Select the appropriate wind zone from M 1 drawing.
3. Select the soil type (Clay or Sand) that best describes the soil characteristics.
4. Get the appropriate standard pole case number from the plans or from the Engineer.
5. Select the appropriate column in the chart based on soil type and "N" value. Select the appropriate row based on the pole load case.  
The foundation depth is the value where the column and the row intersect.
6. Reference Drilled Shafts: Construction Procedures and Design Methods, FHWA -IF-99-025

- S30H1 - Hard Clay-Stirrup Spacing: 6 in. c/c  
- Dense Sand-Stirrup Spacing: 6 in. c/c
- S30H2 - Very Stiff Clay: Stirrup Spacing: 6 in. c/c  
- Hard Clay: Stirrup Spacing: 6 in. c/c  
- Medium Clay: Stirrup Spacing: 6 in. c/c  
- Dense Sand: Stirrup Spacing: 6 in. c/c
- S30H3 - Very Stiff Clay: Stirrup Spacing: 6 in. c/c  
- Hard Clay: Stirrup Spacing: 6 in. c/c  
- Medium Clay: Stirrup Spacing: 6 in. c/c  
- Dense Sand: Stirrup Spacing: 6 in. c/c
- S35H1 - Hard Clay: tirrup Spacing: 6 in. c/c  
- Dense Sand: Stirrup Spacing: 6 in. c/c
- S35H2 - Very Stiff Clay: Stirrup Spacing: 6 in. c/c  
- Hard Clay: Stirrup Spacing: 6 in. c/c  
- Medium Clay: Stirrup Spacing: 6 in. c/c  
- Dense Sand: Stirrup Spacing: 6 in. c/c
- S35H3 - Very Stiff Clay: Stirrup Spacing: 6 in. c/c  
- Hard Clay: Stirrup Spacing: 6 in. c/c  
- Medium Clay: Stirrup Spacing: 6 in. c/c  
- Dense Sand: Stirrup Spacing: 6 in. c/c

48" Dia. Foundations Concrete Volume (cubic yards) = (0.465) x Foundation Depth

	<p><b>Standard Strain Pole Foundation for Dry Soil Condition</b></p> <p>PLAN DATE: SEPTEMBER 2013    DESIGNED BY: C.B. COGDILL                  PREPARED BY: N. BITTING    REVIEWED BY: D. SARKAR</p>							
<p>SCALE: 0 NA</p> <p>None</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>REVISIONS</th> <th>INIT.</th> <th>DATE</th> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </table>	REVISIONS	INIT.	DATE				<p>DocuSigned by: Deborah C. Sarkar 2/26/2014</p> <p>44EBE32E147E4C4</p>
REVISIONS	INIT.	DATE						



STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

06-14



ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL

SHEET 1 OF 3  
**1705D01**

**PUSHBUTTON PLACEMENT**  
SEPARATE CURB RAMPS



**PUSHBUTTON PLACEMENT**  
SHARED CURB RAMP



- NOTES**
1. Pushbutton pedestals should not be located further than 10 feet from the edge of curb, shoulder, or pavement.
  2. The face of the pushbutton should be parallel to the applicable crosswalk.
  3. Separate pushbuttons used on the same corner should be separated by a distance of at least 10 feet.
  4. Pushbuttons shall be installed adjacent to a level surface with a maximum reach distance of 10 inches.
  5. Maintain 4 feet of clearance around pedestal if located in sidewalk.
  6. Refer to section 1705 of the 2012 NCDOT Roadway Standard Drawings for Pushbutton Assembly details.
  7. Refer to section 1743 of the 2012 NCDOT Roadway Standard Drawings for Pedestal details.
  8. Contact Division Traffic Engineer for pushbutton location approval prior to installation.
  9. Curb ramps are for symbolic use only and may not reflect actual design or field conditions.

PROPOSED	LEGEND
	Signal Pole
	Type I Pushbutton Post
	Type II Signal Pedestal
	Pushbutton & Sign
	Pedestrian Signal Head
	Curb Ramp
	Pushbutton Location Area

STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

06-14

ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL

SHEET 1 OF 3  
**1705D01**

See Plate for Title

Prepared in the Offices of:

750 N. Greenfield Parkway  
Garner, NC 27529

SEAL

DocuSigned by:  
*Robert J. Ziemba*  
18084828744604

SIGNATURE DATE

6/17/2014

06-AUG-2014 16:37  
 S:\ITS\ASU\ITS\_Signal\Signal Design\Section\Central\_Region\Rob's Files\Red Stds\Pushbutton Drawings\20140617.dgn  
 rz1emba


STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

06-14


ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL

SHEET 2 OF 3  
**1705D01**


TYPICAL PUSHBUTTON LOCATIONS (CASE I)  
SEPARATE CURB RAMPS W/ TYPE I PEDESTALS



BACK OF SIDEWALK IS WITHIN 10'  
OF CURB OR PAVEMENT/SHOULDER



GRASS STRIP PLACEMENT IF BACK  
OF SIDEWALK EXCEEDS 10' FROM  
CURB OR PAVEMENT/SHOULDER




PUSHBUTTON PLACEMENT  
IN WIDE SIDEWALK

**PROPOSED**


- Signal Pole
- Type I Pushbutton Post
- Type II Signal Pedestal
- Pushbutton & Sign
- Pedestrian Signal Head
- Curb Ramp
- Pushbutton Location Area

**LEGEND**


TYPICAL PUSHBUTTON LOCATIONS (CASE II)  
SEPARATE CURB RAMPS W/ TYPE II PEDESTALS



BACK OF SIDEWALK IS WITHIN 10'  
OF CURB OR PAVEMENT/SHOULDER




GRASS STRIP PLACEMENT IF BACK  
OF SIDEWALK EXCEEDS 10' FROM  
CURB OR PAVEMENT/SHOULDER



PUSHBUTTON PLACEMENT  
IN WIDE SIDEWALK

OPTIONAL PUSHBUTTON EXTENSION  
FACE OF PUSHBUTTON PARALLEL TO  
APPLICABLE CROSSWALK



STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

06-14

ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL

SHEET 2 OF 3  
**1705D01**

See Plate for Title

Prepared in the Offices of:

750 N. Greenfield Parkway  
Garner, NC 27529

SEAL

DocuSigned by:

1888488274464

SIGNATURE

6/17/2014  
DATE

06-1406-2014.r16.r38  
 S:\1705D01\SIGNAL Design Section\Central Region\Rob's Files\Red State\Pushbutton Drawings\Pushbutton Place Drawings\20140617.dgn  
 rz1emba

STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.

06-14

ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL

SHEET 3 OF 3  
**1705D01**

STATE OF NORTH CAROLINA  
DEPT. OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
RALEIGH, N.C.


06-14

ENGLISH DETAIL DRAWING FOR  
**PEDESTRIAN PUSHBUTTON LOCATIONS**  
PLACEMENT DETAIL


SHEET 3 OF 3  
**1705D01**

**TYPICAL PUSHBUTTON LOCATIONS (CASE III)**


SHARED CURB RAMPS




BACK OF SIDEWALK IS WITHIN 10' OF CURB OR PAVEMENT/SHOULDER



GRASS STRIP PLACEMENT IF BACK OF SIDEWALK EXCEEDS 10' FROM CURB OR PAVEMENT/SHOULDER




PUSHBUTTON PLACEMENT IN WIDE SIDEWALK (CORRESPONDING PUSHBUTTONS AND SIGNAL HEADS ON DIFFERENT PEDESTALS)




PUSHBUTTON PLACEMENT WITH SHARED TYPE II SIGNAL PEDESTAL AND TYPE I PUSHBUTTON POST

**TRAFFIC ISLAND PUSHBUTTON LOCATIONS**




PUSHBUTTON PLACEMENT IN LARGE "PORK CHOP ISLAND" WITH SEPARATE PEDESTALS




PUSHBUTTON PLACEMENT IN SMALL "PORK CHOP ISLAND" WITH SHARED PEDESTAL

**PUSHBUTTON PLACEMENT IN MEDIAN**

TYPE II PEDESTAL (FOR STAGED OR MULTI-PHASE CROSSING)



TYPE I PEDESTAL (FOR COMPLETE CROSSING CURB TO CURB WITH OPTIONAL REFUGE)



**PROPOSED**

- Signal Pole
- Type I Pushbutton Post
- Type II Signal Pedestal
- Pushbutton & Sign
- Pedestrian Signal Head
- Curb Ramp
- Pushbutton Location Area

**LEGEND**

06-AUG-2014 16:39  
 S:\ITS\ASU\ITS\_Signal\Signal\_Design\_Sections\Central\_Regional\Rob's Files\Red Stds\Pushbutton Drawings\Pushbutton Place Drawings\20140617.dgn  
 rz1emba

See Plate for Title

Prepared in the Offices of:

750 N. Greenfield Parkway  
Garner, NC 27529


SEAL

DocuSigned by:  
*Robert J. Ziemba*  
18084982744494

SIGNATURE

6/17/2014  
DATE





**NOTES FOR CCTV CAMERA INSTALLATION:**

- 1) REMOVE EXISTING CCTV CAMERA ASSEMBLY AND ASSOCIATED CCTV EQUIPMENT WITH THE EXCEPTION OF THE CELLULAR MODEM AND RETURN TO THE ENGINEER.
- 2) INSTALL NEW CAMERA CONTROL COMPONENTS IN THE SIGNAL CABINET. RELOCATE THE EXISTING CELLULAR MODEM TO THE NEW SIGNAL CABINET.
- 3) ATTACH NEW CCTV CAMERA ASSEMBLY A MINIMUM OF 5 FEET FROM THE TOP OF POLE.
- 4) INSTALL NEW "CCTV UNIFIED CABLE" BETWEEN THE CAMERA CONTROL COMPONENTS IN THE SIGNAL CABINET AND THE NEW CCTV CAMERA.

**NOTES FOR WIRELESS RADIO SYSTEM:**

- 1) REMOVE THE WIRELESS RADIO, LIGHTNING ARRESTOR, COAXIAL CABLE, ANTENNA MOUNTING HARDWARE, AND ANTENNAS.
- 2) RETURN WIRELESS RADIO, ANTENNAS, AND MOUNTING HARDWARE TO THE ENGINEER.
- 3) INSTALL NEW WIRELESS RADIO SYSTEM.
- 4) ENSURE THE NEW WIRELESS RADIO IS COMPATIBLE WITH THE EXISTING SYSTEM.

**LEGEND**

	EXISTING CCTV CAMERA
	PROPOSED CCTV CAMERA
	YAGI ANTENNA (SINGLE)
	EXISTING CONTROLLER AND CABINET
	EXISTING MASTER CONTROLLER AND CABINET
	SIGNAL INVENTORY NUMBER
	EXISTING WOOD POLE
	SIGNAL POLE
	METAL POLE W/MAST ARM


**NOTES FOR WIRELESS COMMUNICATIONS:**

1. INSTALL COAXIAL CABLE:
  - A. ON WOOD POLES, REQUIRING A NEW RIGID GALVANIZED STEEL RISER, INSTALL A 2" RISER WITH WEATHERHEAD AND ROUTE THE COAXIAL CABLE TO THE ANTENNA.
  - B. ON METAL POLES WITH MAST ARMS, RUN COAXIAL CABLE UP THROUGH THE POLE AND OUT THE MAST ARM; FIELD DRILL A 1/2" HOLE UP THROUGH THE BOTTOM OF MAST ARM FOR INSTALLATION OF THE COAXIAL CABLE TO THE ANTENNA.
  - C. ON METAL STRAIN POLES, RUN COAXIAL CABLE UP THROUGH THE POLE AND OUT THE WEATHERHEAD AND ROUTE THE COAXIAL CABLE TO THE ANTENNA.
  - D. BETWEEN THE POINT OF EXITING THE RISER, METAL POLE OR MAST ARM AND THE ANTENNA, SECURE THE COAXIAL CABLE TO THE STRUCTURE USING 3/4" STAINLESS STEEL STRAPS EVERY 12".
2. IF AN EXISTING 2" SPARE RIGID GALVANIZED STEEL RISER IS AVAILABLE, INSTALL THE COAXIAL CABLE IN THE SPARE RISER.
3. INSTALL WIRELESS ANTENNA ON POLE WITH RF WARNING SIGN.  
(NOTE: RF WARNING SIGN NOT REQUIRED WHEN ANTENNA IS INSTALLED ON AN NCDOT-OWNED POLE.)
4. MAINTAIN PROPER CLEARANCE FROM ALL UTILITIES PER THE NATIONAL ELECTRICAL SAFETY CODE.
5. INSTALL WIRELESS SERIAL RADIO MODEM WITH EXTERIOR DISCONNECT SWITCH LOCATED ON CABINET.  
(NOTE: RF ANTENNA DISCONNECT SWITCH AND DECAL ARE NOT REQUIRED WHEN THE ANTENNA IS INSTALLED ON AN NCDOT-OWNED POLE.)
6. REFERENCE "WIRELESS RADIO ANTENNA TYPICAL DETAILS."

THESE PLANS SUPERCEDE THE PLAN SEALED BY GREGORY A. FULLER, PE (SEAL # 023919) ON APRIL 28, 2015.


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

<p>750 N. Greenfield Pkwy., Garner, NC 27529</p>	<p>WIRELESS COMMUNICATION AND CCTV RELOCATION PLAN</p>		
	<p>DIVISION 2 CARTERET CO. MAREHEAD CITY</p> <p>PLAN DATE: DECEMBER 2015 REVIEWED BY: <i>H. T. Berggren</i></p> <p>PREPARED BY: H. T. BERGGREN REVIEWED BY: <i>Gregory A. Fuller</i></p>	<p>REVISIONS</p> <p>INIT. DATE</p>	



**NOTES FOR WIRELESS RADIO SYSTEM:**

- 1) REMOVE THE WIRELESS RADIO, LIGHTNING ARRESTOR, COAXIAL CABLE, ANTENNA MOUNTING HARDWARE, AND ANTENNA.
- 2) RETURN WIRELESS RADIO, ANTENNA, AND MOUNTING HARDWARE TO THE ENGINEER.
- 3) INSTALL NEW WIRELESS RADIO SYSTEM.
- 4) ENSURE THE NEW WIRELESS RADIO IS COMPATIBLE WITH THE EXISTING SYSTEM.




INSTALL 8.5 DB GAIN ANTENNA  
VERTICALLY POLARIZED

ATTACH ANTENNA 24" ABOVE  
HORIZONTAL SHAFT MEMBER

LEGEND	
	YAGI ANTENNA (SINGLE)
	EXISTING CONTROLLER AND CABINET
	EXISTING MASTER CONTROLLER AND CABINET
	SIGNAL INVENTORY NUMBER
	EXISTING WOOD POLE
	SIGNAL POLE
	METAL POLE W/MAST ARM

- NOTES FOR WIRELESS COMMUNICATIONS:**
1. INSTALL COAXIAL CABLE:
    - A. ON WOOD POLES, REQUIRING A NEW RIGID GALVANIZED STEEL RISER, INSTALL A 2" RISER WITH WEATHERHEAD AND ROUTE THE COAXIAL CABLE TO THE ANTENNA.
    - B. ON METAL POLES WITH MAST ARMS, RUN COAXIAL CABLE UP THROUGH THE POLE AND OUT THE MAST ARM; FIELD DRILL A 1/2" HOLE UP THROUGH THE BOTTOM OF MAST ARM FOR INSTALLATION OF THE COAXIAL CABLE TO THE ANTENNA.
    - C. ON METAL STRAIN POLES, RUN COAXIAL CABLE UP THROUGH THE POLE AND OUT THE WEATHERHEAD AND ROUTE THE COAXIAL CABLE TO THE ANTENNA.
    - D. BETWEEN THE POINT OF EXITING THE RISER, METAL POLE OR MAST ARM AND THE ANTENNA, SECURE THE COAXIAL CABLE TO THE STRUCTURE USING 3/4" STAINLESS STEEL STRAPS EVERY 12".
  2. IF AN EXISTING 2" SPARE RIGID GALVANIZED STEEL RISER IS AVAILABLE, INSTALL THE COAXIAL CABLE IN THE SPARE RISER.
  3. INSTALL WIRELESS ANTENNA ON POLE WITH RF WARNING SIGN.  
(NOTE: RF WARNING SIGN NOT REQUIRED WHEN ANTENNA IS INSTALLED ON AN NCDOT-OWNED POLE.)
  4. MAINTAIN PROPER CLEARANCE FROM ALL UTILITIES PER THE NATIONAL ELECTRICAL SAFETY CODE.
  5. INSTALL WIRELESS SERIAL RADIO MODEM WITH EXTERIOR DISCONNECT SWITCH LOCATED ON CABINET.  
(NOTE: RF ANTENNA DISCONNECT SWITCH AND DECAL ARE NOT REQUIRED WHEN THE ANTENNA IS INSTALLED ON AN NCDOT-OWNED POLE.)
  6. REFERENCE "WIRELESS RADIO ANTENNA TYPICAL DETAILS."

	<b>WIRELESS COMMUNICATION PLAN</b>	
	DIVISION 2 CARTERET CO. <u>MARBLEHEAD CITY</u> PLAN DATE: APRIL 2015 REVIEWED BY: <u>N. Berry</u> PREPARED BY: H. T. BERGGREN REVIEWED BY: <u>99F5094CBED0443</u>	SCALE: 0 
REVISIONS _____ _____	INIT. DATE _____ _____	SEAL NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 023919 GREGORY A. FULLER 4/28/2015 DATE



**NOTES FOR WIRELESS RADIO SYSTEM:**

- 1) REMOVE THE WIRELESS RADIO, LIGHTNING ARRESTOR, COAXIAL CABLE, ANTENNA MOUNTING HARDWARE, AND ANTENNA.
- 2) RETURN WIRELESS RADIO, ANTENNA, AND MOUNTING HARDWARE TO THE ENGINEER.
- 3) INSTALL NEW WIRELESS RADIO SYSTEM.
- 4) ENSURE THE NEW WIRELESS RADIO IS COMPATIBLE WITH THE EXISTING SYSTEM.

US 70 (ARENDELL STREET)

MANSFIELD PARKWAY

**NOTES FOR WIRELESS COMMUNICATIONS:**


1. INSTALL COAXIAL CABLE:
  - A. ON WOOD POLES, REQUIRING A NEW RIGID GALVANIZED STEEL RISER, INSTALL A 2" RISER WITH WEATHERHEAD AND ROUTE THE COAXIAL CABLE TO THE ANTENNA.
  - B. ON METAL POLES WITH MAST ARMS, RUN COAXIAL CABLE UP THROUGH THE POLE AND OUT THE MAST ARM; FIELD DRILL A 1/2" HOLE UP THROUGH THE BOTTOM OF MAST ARM FOR INSTALLATION OF THE COAXIAL CABLE TO THE ANTENNA.
  - C. ON METAL STRAIN POLES, RUN COAXIAL CABLE UP THROUGH THE POLE AND OUT THE WEATHERHEAD AND ROUTE THE COAXIAL CABLE TO THE ANTENNA.
  - D. BETWEEN THE POINT OF EXITING THE RISER, METAL POLE OR MAST ARM AND THE ANTENNA, SECURE THE COAXIAL CABLE TO THE STRUCTURE USING 3/4" STAINLESS STEEL STRAPS EVERY 12".
2. IF AN EXISTING 2" SPARE RIGID GALVANIZED STEEL RISER IS AVAILABLE, INSTALL THE COAXIAL CABLE IN THE SPARE RISER.
3. INSTALL WIRELESS ANTENNA ON POLE WITH RF WARNING SIGN.  
(NOTE: RF WARNING SIGN NOT REQUIRED WHEN ANTENNA IS INSTALLED ON AN NCDOT-OWNED POLE.)
4. MAINTAIN PROPER CLEARANCE FROM ALL UTILITIES PER THE NATIONAL ELECTRICAL SAFETY CODE.
5. INSTALL WIRELESS SERIAL RADIO MODEM WITH EXTERIOR DISCONNECT SWITCH LOCATED ON CABINET.  
(NOTE: RF ANTENNA DISCONNECT SWITCH AND DECAL ARE NOT REQUIRED WHEN THE ANTENNA IS INSTALLED ON AN NCDOT-OWNED POLE.)
6. REFERENCE "WIRELESS RADIO ANTENNA TYPICAL DETAILS."

LEGEND	
	YAGI ANTENNA (SINGLE)
	EXISTING CONTROLLER AND CABINET
	EXISTING MASTER CONTROLLER AND CABINET
	SIGNAL INVENTORY NUMBER
	EXISTING WOOD POLE
	SIGNAL POLE
	METAL POLE W/MAST ARM

<p>750 N. Greenfield Pkwy., Garner, NC 27529</p>	<b>WIRELESS COMMUNICATION PLAN</b>		
	DIVISION 2 CARTERET CO. <u>MARSHHEAD CITY</u> PLAN DATE: APRIL 2015 REVIEWED BY: <u>N. Berry</u> PREPARED BY: H. T. BERGGREN REVIEWED BY: <u>99F5094CBED3443</u>	REVISIONS _____ _____ _____	
	SCALE 	DocuSigned by: <u>Gregory A. Fuller</u> 4/28/2015 <small>7032CAGAE874FF DATE</small>	


INSTALL 8.5 DB GAIN ANTENNA VERTICALLY POLARIZED

ATTACH ANTENNA 12" ABOVE HORIZONTAL SHAFT MEMBER



NOTES FOR WIRELESS RADIO SYSTEM:

- 1) MAKE MODIFICATIONS TO THE MASTER RADIO PROGRAMMING AT SIN #02-0423 TO INCLUDE THIS INTERSECTION INTO THE EXISTING SYSTEM.
- 2) ENSURE THE NEW WIRELESS RADIO IS COMPATIBLE WITH THE EXISTING SYSTEM.



NOTES FOR WIRELESS COMMUNICATIONS:

1. INSTALL COAXIAL CABLE:
  - A. ON WOOD POLES, REQUIRING A NEW RIGID GALVANIZED STEEL RISER, INSTALL A 2" RISER WITH WEATHERHEAD AND ROUTE THE COAXIAL CABLE TO THE ANTENNA.
  - B. ON METAL POLES WITH MAST ARMS, RUN COAXIAL CABLE UP THROUGH THE POLE AND OUT THE MAST ARM; FIELD DRILL A 1/2" HOLE UP THROUGH THE BOTTOM OF MAST ARM FOR INSTALLATION OF THE COAXIAL CABLE TO THE ANTENNA.
  - C. ON METAL STRAIN POLES, RUN COAXIAL CABLE UP THROUGH THE POLE AND OUT THE WEATHERHEAD AND ROUTE THE COAXIAL CABLE TO THE ANTENNA.
  - D. BETWEEN THE POINT OF EXITING THE RISER, METAL POLE OR MAST ARM AND THE ANTENNA, SECURE THE COAXIAL CABLE TO THE STRUCTURE USING 3/4" STAINLESS STEEL STRAPS EVERY 12".
2. IF AN EXISTING 2" SPARE RIGID GALVANIZED STEEL RISER IS AVAILABLE, INSTALL THE COAXIAL CABLE IN THE SPARE RISER.
3. INSTALL WIRELESS ANTENNA ON POLE WITH RF WARNING SIGN.  
(NOTE: RF WARNING SIGN NOT REQUIRED WHEN ANTENNA IS INSTALLED ON AN NCDOT-OWNED POLE.)
4. MAINTAIN PROPER CLEARANCE FROM ALL UTILITIES PER THE NATIONAL ELECTRICAL SAFETY CODE.
5. INSTALL WIRELESS SERIAL RADIO MODEM WITH EXTERIOR DISCONNECT SWITCH LOCATED ON CABINET.  
(NOTE: RF ANTENNA DISCONNECT SWITCH AND DECAL ARE NOT REQUIRED WHEN THE ANTENNA IS INSTALLED ON AN NCDOT-OWNED POLE.)
6. REFERENCE "WIRELESS RADIO ANTENNA TYPICAL DETAILS."

**LEGEND**

	YAGI ANTENNA (SINGLE)
	EXISTING CONTROLLER AND CABINET
	EXISTING MASTER CONTROLLER AND CABINET
	SIGNAL INVENTORY NUMBER
	EXISTING WOOD POLE
	SIGNAL POLE
	METAL POLE W/MAST ARM

<p>750 N. Greenfield Pkwy., Garner, NC 27529</p>	<b>WIRELESS COMMUNICATION PLAN</b>		
	DIVISION 2 CARTERET CO. <u>MARHEAD CITY</u> PLAN DATE: APRIL 2015 REVIEWED BY: <u>J. N. Berry</u> PREPARED BY: <u>H. T. BERGGREN</u> REVIEWED BY: <u>99F5094C8ED3443</u>	REVISIONS _____ _____ _____	
	SCALE 		DocuSigned by: <u>Gregory A. Fuller</u> 4/28/2015 <small>7032CAGAE874FF DATE</small>

INSTALL 8.5 DB GAIN ANTENNA  
VERTICALLY POLARIZED


ATTACH ANTENNA 24" ABOVE  
HORIZONTAL SHAFT MEMBER

INSTALL 8.5 DB GAIN ANTENNA  
VERTICALLY POLARIZED

ATTACH ANTENNA 12" ABOVE  
HORIZONTAL SHAFT MEMBER

INSTALL COAXIAL CABLE  
SUITABLE FOR WET LOCATIONS

DIRECTIONAL DRILL 2" CONDUIT  
FOR COAXIAL CABLE INSTALLATION







NOTES FOR WIRELESS RADIO SYSTEM:

- 1) REMOVE THE WIRELESS RADIO, LIGHTNING ARRESTOR, COAXIAL CABLE, ANTENNA MOUNTING HARDWARE, AND ANTENNA.
- 2) RETURN WIRELESS RADIO, ANTENNA, AND MOUNTING HARDWARE TO THE ENGINEER.
- 3) INSTALL NEW WIRELESS RADIO SYSTEM.
- 4) ENSURE THE NEW WIRELESS RADIO IS COMPATIBLE WITH THE EXISTING SYSTEM.


- NOTES FOR WIRELESS COMMUNICATIONS:
1. INSTALL COAXIAL CABLE:
    - A. ON WOOD POLES, REQUIRING A NEW RIGID GALVANIZED STEEL RISER, INSTALL A 2" RISER WITH WEATHERHEAD AND ROUTE THE COAXIAL CABLE TO THE ANTENNA.
    - B. ON METAL POLES WITH MAST ARMS, RUN COAXIAL CABLE UP THROUGH THE POLE AND OUT THE MAST ARM; FIELD DRILL A 1/2" HOLE UP THROUGH THE BOTTOM OF MAST ARM FOR INSTALLATION OF THE COAXIAL CABLE TO THE ANTENNA.
    - C. ON METAL STRAIN POLES, RUN COAXIAL CABLE UP THROUGH THE POLE AND OUT THE WEATHERHEAD AND ROUTE THE COAXIAL CABLE TO THE ANTENNA.
    - D. BETWEEN THE POINT OF EXITING THE RISER, METAL POLE OR MAST ARM AND THE ANTENNA, SECURE THE COAXIAL CABLE TO THE STRUCTURE USING 3/4" STAINLESS STEEL STRAPS EVERY 12".
  2. IF AN EXISTING 2" SPARE RIGID GALVANIZED STEEL RISER IS AVAILABLE, INSTALL THE COAXIAL CABLE IN THE SPARE RISER.
  3. INSTALL WIRELESS ANTENNA ON POLE WITH RF WARNING SIGN.  
(NOTE: RF WARNING SIGN NOT REQUIRED WHEN ANTENNA IS INSTALLED ON AN NCDOT-OWNED POLE.)
  4. MAINTAIN PROPER CLEARANCE FROM ALL UTILITIES PER THE NATIONAL ELECTRICAL SAFETY CODE.
  5. INSTALL WIRELESS SERIAL RADIO MODEM WITH EXTERIOR DISCONNECT SWITCH LOCATED ON CABINET.  
(NOTE: RF ANTENNA DISCONNECT SWITCH AND DECAL ARE NOT REQUIRED WHEN THE ANTENNA IS INSTALLED ON AN NCDOT-OWNED POLE.)
  6. REFERENCE "WIRELESS RADIO ANTENNA TYPICAL DETAILS."

LEGEND	
	YAGI ANTENNA (SINGLE)
	EXISTING CONTROLLER AND CABINET
	EXISTING MASTER CONTROLLER AND CABINET
	SIGNAL INVENTORY NUMBER
	EXISTING WOOD POLE
	SIGNAL POLE
	METAL POLE W/MAST ARM

	<b>WIRELESS COMMUNICATION PLAN</b>		
	DIVISION 2 CARTERET CO. <small>DocuSign</small> MAREHEAD CITY		
750 N. Greenfield Pkwy., Garner, NC 27529 SCALE: 0	PLAN DATE: APRIL 2015 PREPARED BY: H. T. BERGGREN REVISIONS:	REVIEWED BY: <i>N. Avery</i> REVIEWED BY: 99F5094C8ED3443	SEAL 023919 ENGINEER GREGORY A. FULLER DATE: 4/28/2015



THESE PLANS SUPERCEDE THE PLAN SEALED BY GREGORY A. FULLER, PE (SEAL # 023919) ON APRIL 28, 2015.



- NOTES**
1. BOND 0.5 INCH DIAMETER, 28 STRAND (MINIMUM) CLASS II COPPER CONDUCTOR TO THE MAIN GROUND ROD BY AN EXOTHERMIC WELD METHOD.
  2. EXOTHERMICALLY WELD ALL CONNECTIONS TO GROUND RODS.
  3. BOND #4 AWG SOLID BARE COPPER WIRE TO REBAR CAGE AND THE MAIN GROUND ROD BY AN EXOTHERMIC WELD METHOD.
  4. ENSURE CAMERA HOUSING, CAMERA, AND PAN -TILT UNIT ARE BONDED TO POLE.
  5. REMOVE BONDING JUMPER BETWEEN EQUIPMENT CABINET GROUND BUSS AND NEUTRAL BUSS.
  6. THE CONTRACTOR MAY, UPON APPROVAL OF THE ENGINEER, INSTALL A 30-FOOT SECTIONAL GROUND ROD WHEN CONDITIONS WILL NOT ALLOW FOR THE INSTALLATION OF THE 3 - RADIAL GROUND RODS.
  7. INSTALL MARKER TAPE DIRECTLY ABOVE ALL GROUNDING ELECTRODES AND CONDUCTORS AT A DEPTH OF 12 INCHES.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	<p>CCTV CAMERA INSTALLATION FOR METAL POLE WITH UNDERGROUND ELECTRICAL SERVICE TYPICAL DETAIL</p>									
	<p>DIVISION 2 CARTERET CO. DOCKHEAD CITY</p> <p>PLAN DATE: DECEMBER 2015 REVIEWED BY: M. Kelly</p> <p>PREPARED BY: H. T. BERGGREN REVIEWED BY: 09F5084CBE0343</p>	<p>SCALE 0 N/A</p>		<p>REVISIONS</p> <table border="1"> <tr> <th>NO.</th> <th>DATE</th> <th>INIT.</th> <th>DATE</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>	NO.	DATE	INIT.	DATE		
NO.	DATE	INIT.	DATE							

DocuSigned by: Gregory A. Fuller 12/30/2015

CADD File name: