

REFERENCE: U-5788

PROJECT: 44360

SEE SHEET 3 FOR PLAN SHEET LAYOUT
AT TIME OF INVESTIGATION

CONTENTS

<u>LINE</u>	<u>STATION</u>	<u>PLAN</u>
-L-	15+27 to 16+85	4
-Y1-	10+00 to 17+90	4 - 5

CROSS SECTIONS

<u>LINE</u>	<u>STATION</u>	<u>SHEETS</u>
-L-	15+27 - 16+85	6 - 8
-Y1-	10+50 - 17+90	9 - 14

APPENDICES

<u>APPENDIX</u>	<u>TITLE</u>	<u>SHEETS</u>
A	LABORATORY TESTING SUMMARY	16

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

ROADWAY
SUBSURFACE INVESTIGATION

COUNTY BRUNSWICK
PROJECT DESCRIPTION REALIGNMENT OF WALL
STREET (NON-SYSTEM) AT US 17 BUSINESS
(MAIN STREET) AND SHALLOTTE AVENUE
(NON-SYSTEM) INTERSECTION

INVENTORY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-5788	1	16

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

ALEXANDER, M. J.

SCHLEMM, T. S.

TURNAGE, J. R.

COGAR, T. E.

STUDNICKY, R. T.

INVESTIGATED BY ALEXANDER, M. J.

DRAWN BY ALEXANDER, M. J.

DRAWN BY FIELDS, W. D.

CHECKED BY ALEXANDER, M. J.

SUBMITTED BY NASH, A. A.

DATE NOVEMBER 2018

Prepared in the Office of:

Terracon

Consulting Engineers and Scientists
2401 BRENTWOOD ROAD, SUITE 107
RALEIGH, NORTH CAROLINA 27604
NC REGISTERED ENGINEERING FIRM: F-0869
NC REGISTERED GEOLOGIC FIRM: C-367

For:



1223 Jones Franklin Rd.
Raleigh, N.C. 27606
License No. F-0377
Bus: 919 851 8077
Fax: 919 851 8107

TRANSPORTATION PLANNING/DESIGN - BRIDGE/STRUCTURE DESIGN
CIVIL/SITE DESIGN - GIS/GPS - CONSTRUCTION OBSERVATION



SIGNATURE _____ DATE _____

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT**

SUBSURFACE INVESTIGATION


SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																																																						
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 208, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i></p>										<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>										<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>										<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>																																																																																																																																																						
SOIL LEGEND AND AASHTO CLASSIFICATION										MINERALOGICAL COMPOSITION										WEATHERING										MISCELLANEOUS SYMBOLS																																																																																																																																																						
<p>GENERAL CLASS.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="5">GRANULAR MATERIALS (≤ 35% PASSING #200)</th> <th colspan="5">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="5">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-3</th> <th>A-2</th> <th>A-2</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th colspan="5"></th> </tr> <tr> <th>SYMBOL</th> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="5"></td> </tr> </thead> <tbody> <tr> <td>% PASSING #10</td> <td>50</td> <td>30</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td colspan="5"></td> </tr> <tr> <td>% PASSING #40</td> <td>25</td> <td>15</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td>10</td> <td colspan="5"></td> </tr> <tr> <td>% PASSING #200</td> <td>5</td> <td>5</td> <td>5</td> <td>5</td> <td>5</td> <td>5</td> <td>5</td> <td>5</td> <td>5</td> <td>5</td> <td>5</td> <td>5</td> <td colspan="5"></td> </tr> <tr> <td>MATERIAL PASSING #40</td> <td colspan="2">LL</td> <td colspan="2">PL</td> <td colspan="2">LL</td> <td colspan="2">PL</td> <td colspan="2">LL</td> <td colspan="2">PL</td> <td colspan="5"></td> </tr> <tr> <td>GROUP INDEX</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="5"></td> </tr> </tbody> </table>										GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS					GROUP CLASS.	A-1	A-3	A-2	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7						SYMBOL	○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○							% PASSING #10	50	30	10	10	10	10	10	10	10	10	10	10						% PASSING #40	25	15	10	10	10	10	10	10	10	10	10	10						% PASSING #200	5	5	5	5	5	5	5	5	5	5	5	5						MATERIAL PASSING #40	LL		PL		LL		PL		LL		PL							GROUP INDEX	0		0		0		0		0		0							<p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p>										<p>FRESH - ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE. VERY SLIGHT (IV SLI.) - ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE. SLIGHT (SLI.) - ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS. MODERATE (MOD.) - SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK. MODERATELY SEVERE (MOD. SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <i>IF TESTED, WOULD YIELD SPT REFUSAL</i> SEVERE (SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <i>IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF</i> VERY SEVERE (IV SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</i> COMPLETE - ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</p>										<p>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION SOIL SYMBOL ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT INFERRED SOIL BOUNDARY INFERRED ROCK LINE ALLUVIAL SOIL BOUNDARY</p>									
GRANULAR MATERIALS (≤ 35% PASSING #200)					SILT-CLAY MATERIALS (> 35% PASSING #200)					ORGANIC MATERIALS																																																																																																																																																																										
GROUP CLASS.	A-1	A-3	A-2	A-2	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																																																								
SYMBOL	○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○																																																																																																																																																																									
% PASSING #10	50	30	10	10	10	10	10	10	10	10	10	10																																																																																																																																																																								
% PASSING #40	25	15	10	10	10	10	10	10	10	10	10	10																																																																																																																																																																								
% PASSING #200	5	5	5	5	5	5	5	5	5	5	5	5																																																																																																																																																																								
MATERIAL PASSING #40	LL		PL		LL		PL		LL		PL																																																																																																																																																																									
GROUP INDEX	0		0		0		0		0		0																																																																																																																																																																									
CONSISTENCY OR DENSENESS										PERCENTAGE OF MATERIAL										GROUND WATER										RECOMMENDATION SYMBOLS																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> </thead> <tbody> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>< 4 4 TO 10 10 TO 30 30 TO 50 > 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30</td> <td>< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4</td> </tr> </tbody> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> </thead> <tbody> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE 1 - 10%</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE 10 - 20%</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME 20 - 35%</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>> 10%</td> <td>> 20%</td> <td>HIGHLY 35% AND ABOVE</td> </tr> </tbody> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE	<p>WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING STATIC WATER LEVEL AFTER 24 HOURS PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA SPRING OR SEEP</p>										<p>UNDERCUT SHALLOW UNDERCUT UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</p>																																																																																																																						
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																																																																																																	
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																																																	
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																																																																																																	
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																																																	
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE 1 - 10%																																																																																																																																																																																	
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE 10 - 20%																																																																																																																																																																																	
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME 20 - 35%																																																																																																																																																																																	
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY 35% AND ABOVE																																																																																																																																																																																	
TEXTURE OR GRAIN SIZE										ABBREVIATIONS										FRACTURE SPACING										BEDDING																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> </thead> <tbody> <tr> <td></td> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </tbody> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.75	2.00	0.42	0.25	0.075	0.053	<p>AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - CONE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS. - FOSSILIFEROUS FRAC. - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HI. - HIGHLY</p>										<p>VERY WIDE MORE THAN 10 FEET WIDE 3 TO 10 FEET MODERATELY CLOSE 1 TO 3 FEET CLOSE 0.16 TO 1 FOOT VERY CLOSE LESS THAN 0.16 FEET</p>										<p>VERY THICKLY BEDDED 4 FEET THICKLY BEDDED 1.5 - 4 FEET THINLY BEDDED 0.16 - 1.5 FEET VERY THINLY BEDDED 0.03 - 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED < 0.008 FEET</p>																																																																																																																																								
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																														
	4.75	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																														
SOIL MOISTURE - CORRELATION OF TERMS										EQUIPMENT USED ON SUBJECT PROJECT										INDURATION										NOTES:																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SHRINKAGE LIMIT</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </tbody> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p>DRILL UNITS: <input type="checkbox"/> CME-45C <input type="checkbox"/> CME-55 <input type="checkbox"/> CME-550 <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/> PORTABLE HOIST <input checked="" type="checkbox"/> GEOPROBE 6625 <input type="checkbox"/></p>										<p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE. MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER. EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p>FIAD - FILLED IMMEDIATELY AFTER DRILLING REPORT PREPARED USING PROVIDED PROJECT TIN FILE: U5788_Is.tbl.160222.tin</p>																																																																																																																																							
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																																		
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																																		
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																		
OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																																		
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																																		
PLASTICITY										FRACURE SPACING										INDURATION										NOTES:																																																																																																																																																						
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> </thead> <tbody> <tr> <td>NON PLASTIC</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </tbody> </table>										PLASTICITY INDEX (PI)		DRY STRENGTH	NON PLASTIC	0-5	VERY LOW	SLIGHTLY PLASTIC	6-15	SLIGHT	MODERATELY PLASTIC	16-25	MEDIUM	HIGHLY PLASTIC	26 OR MORE	HIGH	<p>DRILL UNITS: <input type="checkbox"/> CME-45C <input type="checkbox"/> CME-55 <input type="checkbox"/> CME-550 <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/> PORTABLE HOIST <input checked="" type="checkbox"/> GEOPROBE 6625 <input type="checkbox"/></p>										<p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE. MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER. EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p>FIAD - FILLED IMMEDIATELY AFTER DRILLING REPORT PREPARED USING PROVIDED PROJECT TIN FILE: U5788_Is.tbl.160222.tin</p>																																																																																																																																							
PLASTICITY INDEX (PI)		DRY STRENGTH																																																																																																																																																																																		
NON PLASTIC	0-5	VERY LOW																																																																																																																																																																																		
SLIGHTLY PLASTIC	6-15	SLIGHT																																																																																																																																																																																		
MODERATELY PLASTIC	16-25	MEDIUM																																																																																																																																																																																		
HIGHLY PLASTIC	26 OR MORE	HIGH																																																																																																																																																																																		
COLOR										FRACURE SPACING										INDURATION										NOTES:																																																																																																																																																						
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>										<p>DRILL UNITS: <input type="checkbox"/> CME-45C <input type="checkbox"/> CME-55 <input type="checkbox"/> CME-550 <input type="checkbox"/> VANE SHEAR TEST <input type="checkbox"/> PORTABLE HOIST <input checked="" type="checkbox"/> GEOPROBE 6625 <input type="checkbox"/></p>										<p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE. MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER. EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p>FIAD - FILLED IMMEDIATELY AFTER DRILLING REPORT PREPARED USING PROVIDED PROJECT TIN FILE: U5788_Is.tbl.160222.tin</p>																																																																																																																																																						

09/08/19

TIP PROJECT: U-5788

CONTRACT:




25% PLANS

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS
BRUNSWICK COUNTY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-5788	3	16
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
44360.1.1	N/A	PE, UTIL., R/W CONST.	


**LOCATION: REALIGNMENT OF WALL STREET (NON-SYSTEM)
AT US 17 BUSINESS (MAIN STREET)
AND SHALLOTTE AVENUE (NON-SYSTEM) INTERSECTION**

**TYPE OF WORK: GRADING, DRAINAGE, CURB & GUTTER, SIGNAL,
RESURFACING, & PAVING**



CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD III MODIFIED.
THIS PROJECT IS WITHIN THE MUNICIPAL BOUNDARIES OF THE TOWN OF SHALLOTTE.

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



DESIGN DATA

ADT 2019 =	1,500
ADT 2040 =	2,300
K =	12 %
D =	60 %
T =	3 % *
V =	40 MPH
* TTST =	1% DUAL = 2%
FUNC. CLASS =	URBAN LOCAL

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT U-5788	=	0.150 MILES
TOTAL LENGTH TIP PROJECT U-5788	=	0.150 MILES

NOTE: -Y1- USED FOR PROJECT LENGTH

Prepared in the Office of:
WETHERILL ENGINEERING
1223 Jones Franklin Rd.
Raleigh, N.C. 27606
License No. F-43377
Bus: 919 851 8077
Fax: 919 851 8107

2012 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE:
JULY 2, 2018

LETTING DATE:
AUGUST 15, 2019

NCDOT CONTACT:

Prepared for:
**DIVISION OF HIGHWAYS
DIVISION 3**
5501 Barbados Boulevard
Castle Hayne NC, 28249

EDWARD G. WETHERILL, PE
PROJECT ENGINEER

GREG S. PURVIS, PE
PROJECT DESIGN ENGINEER


DAVID LEONARD, PE
DIVISION 3 DDC ENGINEER

HYDRAULICS ENGINEER

SIGNATURE: _____ P.E.

ROADWAY DESIGN ENGINEER

SIGNATURE: _____ P.E.



Date: November 2018
 WBS Number: 44360.1.1
 TIP Number: U-5788
 County: Brunswick
 Description: Realignment of Wall Street (Non-System) at US 17 Business (Main Street) and Shallotte Avenue (Non-System) Intersection

Subject: Roadway Geotechnical Report - Inventory

Project Description

The project is located along the new alignment of Wall Street (-Y1-) at the existing intersection of US 17 Business / Main Street (-L-) and Shallotte Avenue in Shallotte, North Carolina. The project will consist of overlaying -L- near the intersection of Shallotte Avenue and realigned -Y1-. The realignment of -Y1- begins on -L- where Shallotte Avenue currently intersects and continues approximately 790 feet southeast to tie-in with existing Wall Street. Parking spaces and driveways will be provided for Town of Shallotte buildings along the north side of the -Y1- alignment including a fire station. The proposed realigned section of -Y1- will be one lane in each direction with left turn lanes at the intersection with -L- and planned driveways. There is a landscaped median planned to separate each direction on the realigned portion of -Y1-. The realigned section will tie-in to the existing two-lane section of Wall Street. The project corridor is in an urban setting.

A Roadway Geotechnical Inventory Report was provided in November 2016 describing the investigation previously performed for the realignment of Shallotte Avenue. During that investigation the pavement and subgrade of -L- were investigated. The geotechnical subsurface investigation of -L- was performed in September of 2016. The existing pavements at Station 16+00 and 17+00 -L- were cored with a truck mounted HILTI-DD200 electric coring machine using a 4-inch inside diameter, diamond impregnated, thin walled core barrel. The pavement subgrades and subsurface soils along the -L- alignment were evaluated with a dual-mass dynamic cone penetrometer (DCP). The results of the DCP testing and California Bearing Ratio (CBR) correlations were submitted under a separate cover. Soil samples were obtained during the pavement and subgrade investigation by advancing solid stem augers with a GeoProbe 6625CPT drill rig. Representative soil samples were collected in the field for visual classification and selected samples were submitted for analysis by Terracon’s soil testing laboratory. Laboratory testing was performed in accordance with the AASHTO Soil Classification System.

The geotechnical subsurface investigation of -Y1- was performed in September 2018. Soil samples were obtained using a hand auger. Representative soil samples were collected in the field for visual classification and selected samples were submitted for analysis by Terracon’s soil testing laboratory. Laboratory testing was performed in accordance with the AASHTO Soil Classification System. The site was revisited and offset borings were advanced near the locations of our September 2018 hand auger borings. These borings remained open for 24 hours for the specific purpose of obtaining 24 hour water levels.

The following alignments were investigated by soil testing and visual reconnaissance:

Alignment	Stations
-L-	15+27 to 16+85
-Y1-	10+00 to 17+90

Physiography and Geology

The site is located within the Inner Coastal Plain Physiographic and Geologic Province of North Carolina in Brunswick County. The Coastal Plain Province is characterized by flat, low-lying, subdued topographic features. The existing elevations along the investigated corridor range from approximately 23 feet to 12 feet. In general, the topography at this site slopes gently to the southeast toward the unnamed stream and surrounding wetland.

The project is located in the Coastal Plain Physiographic Province with geology consisting of a wedge of unconsolidated sands, silt, marl, and other clays interbedded with occasional limestone strata, which rests atop crystalline basement rocks. Based on previous mapping (N.C. Geologic Map 1985) and our knowledge of the local geology, the site falls within the Tertiary age Waccamaw Formation. However, based on our site visit and subsurface conditions encountered, the near surface soils appear to be recent Undivided Coastal Plain deposits of alluvial origin and are consistent with interbedded sands, clayey sands and clays. These near surface soils overlie the blue-gray to tan, loosely consolidated, fossiliferous sand with silt and clay of the Waccamaw Formation.

Soil Properties

Soils encountered during this investigation were artificial fill, roadway embankment, and Undivided Coastal Plain deposited soils.

Artificial fill is present at the surface on -Y1- near the proposed intersection with -L-. This material appears to be associated with development of the store and parking lot currently located on the south corner of Main Street and Wall Street. The artificial fill consists of loose, moist, silty fine sand (A-2-4).

Roadway embankment soils are present beneath the existing pavement on -L- and -Y1-. It appears the -L- alignment was undercut and replaced during construction of the existing roadway. Roadway embankment fill was placed to raise grades of existing Wall Street near the southeast end of the project. The roadway embankment soils can be generalized as loose to medium dense, moist, silty fine sand (A-2-4) that extends to 4 to 5 feet below existing site grades.

Undivided Coastal Plain deposits are present at the surface along most of the corridor. The Undivided Coastal Plain soils can be generalized as alternating layers of clay, silt, and sand extending to the boring termination depths of 4 to 6 feet below existing site grades. The soils along the -Y1- alignment consist of 1 to 4 feet of loose to medium dense, dry to saturated, silty fine sand (A-2-4), soft to medium stiff, moist to wet, fine sandy silt (A-4), and loose to medium dense, moist, clayey fine sand (A-2-6). A layer of medium



stiff, wet, sandy to silty clay (A-6 and A-7-5, respectively) was encountered beneath the near surface Undivided Coastal Plain sand and silts along a majority of the -Y1- alignment. Based on laboratory testing, the sandy clay is moderately plastic with indices ranging from 23 to 24.

Groundwater

In general, the site drains to the unnamed jurisdictional stream and wetlands just southeast of the corridor near the end of existing Wall Street. Groundwater was encountered at depths ranging from 1.5 to 4 feet below existing site grades in the hand augers performed along the -Y1- alignment. In our opinion, the groundwater encountered in the hand auger borings along -Y1- is perched. Water infiltrating the near surface sands likely becomes trapped over the less permeable clay underlying a majority of the corridor. Groundwater was not encountered along the -L- alignment above the 4.5 feet boring termination depths at the time of drilling. These borings were performed within existing pavement sections and were filled immediately after drilling (FIAD) and patched. The depth of groundwater, beneath the ground surface, will fluctuate with seasonal precipitation and may occur a higher levels at other times of the year above less permeable clayey soils.

Areas of Special Geotechnical Interest

- 1) Plastic Soils – Slightly to moderately plastic Undivided Coastal Plain soils with plastic indices (PI) of 16 and greater were encountered at the following locations:

<u>Alignment</u>	<u>Stations</u>
-Y1-	10+23 to 16+25±

A discussion of these plastic soils is located above in the section titled “Soil Properties.”

- 2) Artificial Fill - Artificial fill was encountered at the following locations:

<u>Alignment</u>	<u>Stations</u>
-Y1-	10+23 to 10+48±

A discussion of the artificial fill is located above in the section titled “Soil Properties.”

- 3) Shallow Groundwater - Shallow perched groundwater was encountered within 6 feet of proposed grades at the following locations:

<u>Alignment</u>	<u>Stations</u>
-Y1-	10+23 to 17+90±

A discussion of the shallow groundwater is located above in the section titled “Groundwater.”

BULK SAMPLES

No bulk samples were taken for this project.



Sincerely,
Terracon Consultants, Inc.



Matthew J. Alexander, PE
Senior Geotechnical Engineer

Andrew A. Nash, PE
Geotechnical Department Manager

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



ROADWAY EMBANKMENT

ROADWAY EMBANKMENT

US17-2

US17-1

ARTIFICIAL FILL

**END CONSTRUCTION
END MILLING
AND RESURFACING
-L- STA. 16+85.00**

**BEGIN TIP PROJECT U-5788
-Y1- POT STA. 10+00.00 =
-L- POT STA. 15+81.50**

-DRI- POT Sta. 11+50.00

**END CONSTRUCTION
-DRI- STA. 10+82.50**

-Y2- POT Sta. 11+50.00

UNDIVIDED COASTAL PLAIN

UNDIVIDED COASTAL PLAIN

UNDIVIDED COASTAL PLAIN



**BEGIN CONSTRUCTION
BEGIN MILLING AND RESURFACING
-L- STA. 15+27.00**


**-DRI- POT Sta. 10+00.00 =
-Y1- POT Sta. 13+32.17**

**-Y2- POT Sta. 10+87.58 =
-Y1- POT Sta. 14+62.78**


MATCHLINE STA. 15+00 -Y1- SEE SHEET 5


BRITT AND HEWETT INC DB 577 PG 1085
WILLIAM D MILLIGAN DB 1522 PG 800
EDWARD M & CAROLYN SWEATT DB 54 PG 649 DB 111 PG 123 DB 123 PG 224 DB 123 PG 224
TOWN OF SHALLOTTE DB 3656 PG 892 PB 90 PG 38
TOWN OF SHALLOTTE DB 3517 PG 1296 PB 83 PG 50
TOWN OF SHALLOTTE DB 513 PG 667 PB 02.5 PG 224
SHALLOTTE CITY HALL DB 408 PG 212 PB 02.5 PG 224
TOWN OF SHALLOTTE DB 2649 PG 897 PB 52 PG 54
TOWN OF SHALLOTTE DB 479 PG 785
TOWN OF SHALLOTTE DB 349 PG 68 PB 02.5 PG 224
TOWN OF SHALLOTTE DB 349 PG 82 PB 81 PG 96
GENE G & GRACIE EVANS DB 647 PG 328
GENE G & GRACIE EVANS DB 647 PG 332
SHALLOTTE ABC BOARD DB 1867 PG 53 PB 02.5 PG 224
TOWN OF SHALLOTTE DB 3605 PG 34 PB 2.5 PG 224







PROJ. REFERENCE NO.	SHEET NO.
U-5788	6






PROJ. REFERENCE NO.	SHEET NO.
U-5788	7





PROJ. REFERENCE NO.	SHEET NO.
U-5788	8



US17-2

17+00 -L-

CL

PAVEMENT

EXIST.
EOP

ROADWAY EMBANKMENT
DENSE, MOIST, SILTY

BROWN, GRAY, MEDIUM
FINE SAND (A-2-4)

UNDIVIDED COASTAL PLAIN, ORANGE, GRAY, BROWN, MEDIUM
STIFF, WET, MODERATELY PLASTIC SILTY CLAY (A-7-5)

BT

FIAD

09/16

16+85

PAVEMENT

EXIST.
EOP



4:1



ROADWAY EMBANKMENT, BROWN, GRAY,
MEDIUM DENSE, MOIST, SILTY FINE SAND (A-2-4)



UNDIVIDED COASTAL PLAIN, ORANGE, GRAY, BROWN, MEDIUM
STIFF, WET, MODERATELY PLASTIC SILTY CLAY (A-7-5)



16+75



-L-











17+50

17+00

16+50

-Y/-

DRIVEWAY

S-10

B-8

16+51 -Y1-

14' RT

BT

4:1
 ROADWAY EMBANKMENT, GRAY, LOOSE TO MEDIUM DENSE, MOIST, SILTY FINE SAND (A-2-4)
 ORANGE, GRAY, LOOSE TO MEDIUM DENSE, MOIST, SILTY FINE SAND (A-2-4)
 4:1


4:1
 ROADWAY EMBANKMENT, GRAY, LOOSE TO MEDIUM DENSE, MOIST, SILTY FINE SAND (A-2-4)
 ORANGE, GRAY, LOOSE TO MEDIUM DENSE, MOIST, SILTY FINE SAND (A-2-4)
 3:1

3:1
 ROADWAY EMBANKMENT, GRAY, LOOSE TO MEDIUM DENSE, MOIST, SILTY FINE SAND (A-2-4)
 ORANGE, GRAY, LOOSE TO MEDIUM DENSE, MOIST, SILTY FINE SAND (A-2-4)
 3:1

UNDIVIDED COASTAL PLAIN, DARK GRAY, SOFT TO MEDIUM STIFF, WET, FINE SANDY SILT (A-4)


UNDIVIDED COASTAL PLAIN, DARK GRAY, SOFT TO MEDIUM STIFF, WET, FINE SANDY SILT (A-4)

UNDIVIDED COASTAL PLAIN, DARK GRAY, SOFT TO MEDIUM STIFF, WET, FINE SANDY SILT (A-4)



PROJ. REFERENCE NO.	SHEET NO.
U-5788	14

75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	U-5788	15	16

REFERENCE: U-5788

PROJECT: 44360

APPENDIX A
LABORATORY TESTING SUMMARY

LABORATORY TESTING SUMMARY

PROJECT NUMBER: 44360.1.1

TIP: U-5788

COUNTY: Brunswick

DESCRIPTION: Realignment of Wall Street at US 17 Business (Main Street) and Shallotte Avenue

Sample No.	Alignment	Station	Offset (feet)	Depth Interval (feet)	AASHTO Class.	L.L.	P.I.	% by Weight				% Retained #4 Sieve	% Passing (sieves)			% Moisture	% Organic
								Coarse Sand	Fine Sand	Silt	Clay		#10	#40	#200		
S-3	-L-	16+00	15 RT	0.5 - 3.5	A-2-4 (0)	25	9	7.8	64.0	6.7	21.5	0	100	98	31	--	--
S-4	-Y1-	10+50	17 LT	2.0 - 3.0	A-2-6 (1)	33	17	1.7	67.1	4.6	26.6	0	100	100	33	--	--
S-5	-Y1-	12+40	24 LT	3.0 - 4.0	A-2-4 (0)	17	NP	3.9	80.1	7.9	8.1	0	100	99	20	--	--
S-6	-Y1-	14+02	15 RT	2.0 - 3.0	A-6 (6)	38	24	2.4	54.0	10.0	33.6	0	100	100	45	18.4	--
S-7	-Y1-	14+62	3 LT	2.0 - 3.0	A-6 (4)	38	23	2.4	60.8	8.1	28.7	0	100	99	40	20.9	--
S-8	-Y1-	15+29	21 RT	0.0 -1.0	A-4 (0)	24	NP	5.1	52.5	29.0	13.4	0	99	98	44	28.5	--
S-9	-Y1-	15+29	21 RT	2.0 - 3.0	A-2-4 (0)	14	NP	3.6	71.6	17.1	7.7	0	100	99	29	--	--
S-10	-Y1-	16+51	14 RT	3.0 - 4.0	A-4 (0)	22	5	5.1	56.6	18.4	19.9	0	100	98	40	30.0	--

Stephanie H. Huffman

 Certified Lab Technician Signature

 114-01-1203
 Certification Number