


09.08/19

2/22/2017
Q:\Rdy-psn-01.dgn
lisa.jamison

TIP PROJECT: R-4436CH

CONTRACT: 34625.2.66

See Sheet 1-A For Index of Sheets




VICINITY MAP

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS


BRUNSWICK COUNTY

LOCATION: NC 906 NORTH OF INTRACOASTAL WATERWAY

TYPE OF WORK: GRADING, STORM DRAINAGE, INFILTRATION BASIN, EROSION CONTROL,
AND SEEDING & MULCHING



STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-4436CH	1	10
STATE PROJ. NO.	F. A. PROJ. NO.	DESCRIPTION	
34625.2.66			



2/22/2017

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

GRAPHIC SCALES

SCALE VARIES
SEE PLANS



LETTING DATE:
MAY 18, 2017

Prepared by

AECOM

AECOM TECHNICAL SERVICES OF NORTH CAROLINA
Licensure Number F-0342
1600 Perimeter Park Drive
Morrisville, North Carolina 27560
TELEPHONE: (919) 461-1100 FAX: (919) 461-1415

JASON SITES, PE
PROJECT ENGINEER


PROJECT DESIGN ENGINEER

HYDRAULICS ENGINEER

SIGNATURE: _____ P.E.

NCDOT CONTACT
BRIAN LIPSCOMB, P.E.
HIGHWAY STORMWATER PROGRAM

DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA
HYDRAULICS UNIT
STORMWATER GROUP



PROJECT ENGINEER

8/17/99

INDEX OF SHEETS

SHEET NUMBER	SHEET DESCRIPTION
1	TITLE SHEET
1-A	INDEX OF SHEETS, GENERAL NOTES, AND LIST OF STANDARD DRAWINGS
1-B	CONVENTIONAL SYMBOLS
1-C	SURVEY CONTROL
2-A	BMP DETAILS 1 & PROFILE
2-B	BMP DETAILS 2
3B/3D	EARTHWORK, DRAINAGE & EROSION CONTROL SUMMARIES
4	PLAN SHEET
EC-1	EROSION CONTROL PLANS
TC-1	TRAFFIC CONTROL PLANS

CONSTRUCTION SEQUENCE NOTES

PROJECT REQUIRES A PRE-CONSTRUCTION CONFERENCE PRIOR TO INITIATING ANY EARTH DISTURBANCE ACTIVITIES.

1. INSTALL TEMPORARY SILT FENCE AND GRAVEL CONSTRUCTION ENTRANCE AS SHOWN ON PLANS.
2. CONSTRUCT INFILTRATION BASIN AND OTHER IMPROVEMENTS.
3. FOLLOW SEEDING/ MULCHING GUIDELINES ON THE PLANS TO STABILIZE ALL REMAINING DISTURBED SURFACES.
4. INSPECT OUTLETS FOR SEDIMENT AND REMOVE SEDIMENT AS REQUIRED.
5. REMOVE ALL REMAINING TEMPORARY EROSION CONTROL MEASURES AFTER PERMANENT PERENNIAL VEGETATION IS ESTABLISHED.

EROSION CONTROL NOTES

1. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH NCDOT STANDARDS, SPECIFICATIONS, AND DETAILS, LATEST VERSION.
2. CONTRACTOR SHALL MAINTAIN ALL EROSION CONTROL MEASURES DURING THE LIFE OF THE PROJECT UNLESS OTHERWISE INDICATED ON THE PLANS OR DIRECTED BY NCDOT INSPECTOR.
3. CONTRACTOR SHALL CONSTRUCT DIVERSION DITCHES AS NECESSARY TO ENSURE THAT ALL SEDIMENT IS DIRECTED INTO EROSION CONTROL MEASURES.
4. CUT AND FILL SLOPES SHALL BE STABILIZED WITHIN 14 DAYS OF ANY PHASE OF GRADING. SLOPES 3:1 OR STEEPER SHALL BE STABILIZED WITHIN 7 DAYS.
5. PROVIDE TEMPORARY EROSION CONTROL MEASURES AS NECESSARY TO PREVENT SEDIMENT FROM MIGRATING INTO BASIN BOTTOM OR SODDED AREAS.
6. ALL STREETS ADJACENT TO THIS PROJECT SHALL REMAIN CLEAN AT ALL TIMES OR A WASH STATION MAY BE REQUIRED.
7. IF USED, SILT FENCE SHALL BE MAINTAINED ON THE SITE UNTIL ALL SITE WORK IS COMPLETED AND THE FINAL SITE INSPECTION IS COMPLETE.
8. RESEED OF PERMANENT GROUND COVER WILL BE ESTABLISHED IN 15 WORKING DAYS OR 30 CALENDAR DAYS, WHICH EVER IS SHORTER.
9. EROSION CONTROL MATTING SHALL BE STRAW MATTING. USE STD. DWG. 1631.01 FOR MATTING INSTALLATION.
10. PROVIDE GRAVEL CONSTRUCTION ENTRANCE PER 1607.01 AS NEEDED TO PREVENT TRACKING OFFSITE.

SURVEY

LOCATIONS AND ELEVATIONS SHOULD BE FIELD VERIFIED. CONSULT WITH ENGINEER IF SIGNIFICANT DEVIATIONS FROM THE PLAN ARE REQUIRED.

UTILITIES

THE CONTRACTOR SHOULD MAKE HIS OWN INVESTIGATIONS AS TO THE LOCATION OF UTILITIES. EXISTING UTILITIES AND STRUCTURES (UNDERGROUND, SURFACE, OR OVERHEAD) ARE INDICATED ONLY TO THE THE EXTENT THAT SUCH INFORMATION WAS KNOWN, MADE AVAILABLE TO, OR DISCOVERED BY THE ENGINEER IN PREPARING THE DRAWINGS. THE LOCATIONS, CONFIGURATIONS, AND ELEVATIONS OF SUBSURFACE FACILITIES AND UTILITIES ARE APPROXIMATE, AND NOT ALL UTILITIES AND FACILITIES MAY BE INDICATED.

2012 ROADWAY ENGLISH STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" HIGHWAY DESIGN BRANCH - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., JANUARY, 2012 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED PART OF THESE PLANS.

STD.NO.	TITLE
DIVISION 2 - EARTHWORK	
200.02	METHOD OF CLEARING - METHOD II
DIVISION 11 - WORK ZONE TRAFFIC CONTROL	
1101.01	WORK ZONE ADVANCE WARNING SIGNS FOR FACILITIES ≤ 55 MPH
1101.02	TEMPORARY LANE CLOSURES - DIVIDED MULTI-LANE ROADWAY - 1 LANE CLOSED (FOR ROADWAYS < 60 MPH)
1101.04	TEMPORARY SHOULDER CLOSURES
DIVISION 16 - EROSION CONTROL AND ROADSIDE DEVELOPMENT	
1605.01	TEMPORARY SILT FENCE
1607.01	GRAVEL CONSTRUCTION ENTRANCE

GENERAL NOTES

GRADING:

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED OR FUTURE SURFACING AT GRADE POINTS SHOWN ON THE PLANS. GRADE LINES MAY BE ADJUSTED AT THEIR BEGINNING AND ENDING AND AT STRUCTURES AS DIRECTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.

TRAFFIC CONTROL:

USE APPROPRIATE STANDARDS PER DIVISION 11 AS REQUIRED TO COMPLETE WORK. COORDINATE TRAFFIC CONTROL WITH THE DIVISION.


SEEDBED PREPARATION

1. PREPARE AND SEED ONLY DISTURBED AREAS. DO NOT SPREAD SEED ON AREAS TO RECEIVE SOD, SEE SHEET 2-A FOR 3-D GEOTEXTILE & SOD INSTALLATION.
2. CHISEL COMPACTED AREAS AND SPREAD TOPSOIL 3 INCHES DEEP OVER ADVERSE SOIL CONDITIONS IF AVAILABLE.
3. RIP THE ENTIRE AREA TO 6 INCHES DEPTH.
4. REMOVE ALL LOOSE ROCK, ROOTS AND OTHER OBSTRUCTIONS LEAVING SURFACES REASONABLY SMOOTH AND UNIFORM.
5. APPLY AGRICULTURAL LIME, FERTILIZER, AND SUPERPHOSPHATE UNIFORMLY AND MIX WITH SOIL (SEE BELOW*).
6. CONTINUE TILLAGE UNTIL A WELL-PULVERIZED, FIRM, REASONABLY UNIFORM SEEDBED IS PREPARED 4 TO 6 INCHES DEEP.
7. SEED A FRESHLY PREPARED SEEDBED AND COVER SEED LIGHTLY WITH SEEDING EQUIPMENT OR CULTIPACK AFTER SEEDING.
8. MULCH IMMEDIATELY AFTER SEEDING AND ANCHOR MULCH.
9. INSPECT ALL SEEDED AREAS AND MAKE ALL NECESSARY REPAIRS OR RESEEDINGS WITHIN THE PLANTING SEASON, IF POSSIBLE. IF STAND SHOULD BE OVER 70% DAMAGED, REESTABLISH FOLLOWING ORIGINAL LIME, FERTILIZER AND SEEDING RATES.
10. CONSULT CONSERVATION INSPECTOR ON MAINTENANCE TREATMENT AND FERTILIZATION AFTER PERMANENT COVER IS ESTABLISHED.

*APPLY: AGRICULTURAL LIMESTONE - 2 TONS/ACRE (34 TONS/ACRE ON CLAY SOILS)
FERTILIZER - 1,000 LBS/ACRE - 10-10-10
SUPERPHOSPHATE - 500 LBS/ACRE - 20%
MULCH - 2 TONS/ACRE - SMALL GRAIN STRAW
ANCHOR - ASPHALT EMULSION @ 300 GAL. ACRE

MAINTENANCE PLAN

1. ALL EROSION AND SEDIMENTATION CONTROL PRACTICES WILL BE CHECKED FOR STABILITY AND OPERATION FOLLOWING EVERY RUNOFF-PRODUCING RAINFALL BUT IN NO CASE LESS THAN ONCE A WEEK. ANY NEEDED REPAIRS WILL BE MADE IMMEDIATELY TO MAINTAIN ALL PRACTICES AS DESIGNED.
2. SEDIMENT WILL BE REMOVED FROM BEHIND THE SILT FENCE WHEN IT BECOMES ABOUT 6-INCHES DEEP AT THE FENCE. THE SILT FENCE WILL BE REPAIRED AS NECESSARY TO MAINTAIN A BARRIER.
3. INLET PROTECTION DEVICES SHALL BE INSPECTED AFTER EVERY RAINFALL EVENT. DAMAGED SILT FENCE SHALL BE REPLACED AND GRAVEL SHALL BE CLEANED OR REPLACED WHEN INLET NO LONGER DRAINS PROPERLY.

























PROJECT REFERENCE NO.	SHEET NO.
R-4436CH	I-A
	HYDRAULICS ENGINEER  2/22/2017

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED












2/20/2017
01:14:08
J. Stiles
J. Stiles

CONVENTIONAL PLAN SHEET SYMBOLS












BOUNDARIES AND PROPERTY:

State Line	
County Line	
Township Line	
City Line	
Reservation Line	
Property Line	
Existing Iron Pin	
Computed Property Corner	
Property Monument	
Parcel/Sequence Number	
Existing Fence Line	
Proposed Woven Wire Fence	
Proposed Chain Link Fence	
Proposed Barbed Wire Fence	
Existing Wetland Boundary	
Proposed Wetland Boundary	
Existing Endangered Animal Boundary	
Existing Endangered Plant Boundary	
Existing Historic Property Boundary	
Known Contamination Area: Soil	
Potential Contamination Area: Soil	
Known Contamination Area: Water	
Potential Contamination Area: Water	
Contaminated Site: Known or Potential	




BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	
Sign	
Well	
Small Mine	
Foundation	
Area Outline	
Cemetery	
Building	
School	
Church	
Dam	























HYDROLOGY:

Stream or Body of Water	
Hydro, Pool or Reservoir	
Jurisdictional Stream	
Buffer Zone 1	
Buffer Zone 2	
Flow Arrow	
Disappearing Stream	
Spring	
Wetland	
Proposed Lateral, Tail, Head Ditch	
False Sump	












RAILROADS:

Standard Gauge	
RR Signal Milepost	
Switch	
RR Abandoned	
RR Dismantled	



RIGHT OF WAY & PROJECT CONTROL:

Secondary Horiz and Vert Control Point	
Primary Horiz Control Point	
Primary Horiz and Vert Control Point	
Exist Permanent Easment Pin and Cap	
New Permanent Easement Pin and Cap	
Vertical Benchmark	
Existing Right of Way Marker	
Existing Right of Way Line	
New Right of Way Line	
New Right of Way Line with Pin and Cap	
New Right of Way Line with Concrete or Granite R/W Marker	
New Control of Access Line with Concrete C/A Marker	
Existing Control of Access	
New Control of Access	
Existing Easement Line	
New Temporary Construction Easement	
New Temporary Drainage Easement	
New Permanent Drainage Easement	
New Permanent Drainage /Utility Easement	
New Permanent Utility Easement	
New Temporary Utility Easement	
New Aerial Utility Easement	





ROADS AND RELATED FEATURES:

Existing Edge of Pavement	
Existing Curb	
Proposed Slope Stakes Cut	
Proposed Slope Stakes Fill	
Proposed Curb Ramp	
Existing Metal Guardrail	
Proposed Guardrail	
Existing Cable Guiderail	
Proposed Cable Guiderail	
Equality Symbol	
Pavement Removal	










VEGETATION:

Single Tree	
Single Shrub	













*S.U.E. = Subsurface Utility Engineering

Hedge	
Woods Line	
Orchard	
Vineyard	
















EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	
Bridge Wing Wall, Head Wall and End Wall	
MINOR:	
Head and End Wall	
Pipe Culvert	
Footbridge	
Drainage Box: Catch Basin, DI or JB	
Paved Ditch Gutter	
Storm Sewer Manhole	
Storm Sewer	









UTILITIES:

POWER:	
Existing Power Pole	
Proposed Power Pole	
Existing Joint Use Pole	
Proposed Joint Use Pole	
Power Manhole	
Power Line Tower	
Power Transformer	
U/G Power Cable Hand Hole	
H-Frame Pole	
U/G Power Line LOS B (S.U.E.*)	
U/G Power Line LOS C (S.U.E.*)	
U/G Power Line LOS D (S.U.E.*)	










TELEPHONE:

Existing Telephone Pole	
Proposed Telephone Pole	
Telephone Manhole	
Telephone Pedestal	
Telephone Cell Tower	
U/G Telephone Cable Hand Hole	
U/G Telephone Cable LOS B (S.U.E.*)	
U/G Telephone Cable LOS C (S.U.E.*)	
U/G Telephone Cable LOS D (S.U.E.*)	
U/G Telephone Conduit LOS B (S.U.E.*)	
U/G Telephone Conduit LOS C (S.U.E.*)	
U/G Telephone Conduit LOS D (S.U.E.*)	
U/G Fiber Optics Cable LOS B (S.U.E.*)	
U/G Fiber Optics Cable LOS C (S.U.E.*)	
U/G Fiber Optics Cable LOS D (S.U.E.*)	







WATER:

Water Manhole	
Water Meter	
Water Valve	
Water Hydrant	
U/G Water Line LOS B (S.U.E.*)	
U/G Water Line LOS C (S.U.E.*)	
U/G Water Line LOS D (S.U.E.*)	
Above Ground Water Line	








TV:

TV Pedestal	
TV Tower	
U/G TV Cable Hand Hole	
U/G TV Cable LOS B (S.U.E.*)	
U/G TV Cable LOS C (S.U.E.*)	
U/G TV Cable LOS D (S.U.E.*)	
U/G Fiber Optic Cable LOS B (S.U.E.*)	
U/G Fiber Optic Cable LOS C (S.U.E.*)	
U/G Fiber Optic Cable LOS D (S.U.E.*)	











GAS:

Gas Valve	
Gas Meter	
U/G Gas Line LOS B (S.U.E.*)	
U/G Gas Line LOS C (S.U.E.*)	
U/G Gas Line LOS D (S.U.E.*)	
Above Ground Gas Line	

SANITARY SEWER:


Sanitary Sewer Manhole	
Sanitary Sewer Cleanout	
U/G Sanitary Sewer Line	
Above Ground Sanitary Sewer	
SS Forced Main Line LOS B (S.U.E.*)	
SS Forced Main Line LOS C (S.U.E.*)	
SS Forced Main Line LOS D (S.U.E.*)	

MISCELLANEOUS:

Utility Pole	
Utility Pole with Base	
Utility Located Object	
Utility Traffic Signal Box	
Utility Unknown U/G Line LOS B (S.U.E.*)	
U/G Tank; Water, Gas, Oil	
Underground Storage Tank, Approx. Loc.	
A/G Tank; Water, Gas, Oil	
Geoenvironmental Boring	
U/G Test Hole LOS A (S.U.E.*)	
Abandoned According to Utility Records	AATUR
End of Information	E.O.I.

GPS-1

NAD 83/2011

PROJECT REFERENCE NO.		SHEET NO.	
R-4436CH		I-C	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
			
		2/22/2017	
<p align="center">DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</p>			

POINT	NORTHING	EASTING	ELEVATION	DESCRIPTION
1	67165.866	2255366.092	33.665	GPS-1
2	66427.477	2255241.994	49.93	GPS-2

EXISTING CONDITIONS SURVEY

SITE COORDINATE CONTROL AND EXISTING CONDITIONS FOR PROJECT
ARE FROM A TOPOGRAPHIC SURVEY PERFORMED IN NOVEMBER 2016 BY:
AECOM

[illegible]

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT
IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY
OTHERS FOR MONUMENT "GPS-1"

WITH NAD 83/NSRS 2007 STATE PLANE GRID COORDINATES OF
NORTHING: 67165.866(+) EASTING: 2255366.092(+)
ELEVATION: 33.665(+)

THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT
(GROUND TO GRID) IS: 0.999778365

THE N.C. LAMBERT GRID BEARING AND
LOCALIZED HORIZONTAL GROUND DISTANCE FROM
"GPS-1" TO -L- STATION IS

ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
VERTICAL DATUM USED IS NAVD 88





8/17/99

REVISIONS

2/20/2017
01
J. H. CASH-02A.dgn
J. H. CASH

BMP DETAILS 1 & PROFILE




3-D GEOTEXTILE & SOD INSTALLATION
N.T.S.

TYPICAL SECTION – INFILTRATION BASIN
N.T.S.

NOTE:

1. PLACE BERMUDA SOD ON BASIN BOTTOMS, BERMS, AND SIDE SLOPES.
2. SEE SPECIAL PROVISIONS FOR 3-D GEOTEXTILE. ANCHOR ON SIDE SLOPES PER MANUFACTURE'S INSTRUCTIONS.
3. 3-D GEOTEXTILE & SOD INSTALLATION METHOD
 - a. LOOSEN SURFACE SOIL (TILL)
 - b. LAY 3-D GEOTEXTILE SO THAT LOOSENEED SOIL FILLS UNDERSIDE VOIDS
 - c. FEATHER SOIL ON TOP OF 3-D GEOTEXTILE TO FILL TOP VOIDS
 - d. ANCHOR PER MANUFACTURER'S RECOMMENDATION.
 - e. LAY SOD & WATER PER STD. SPECIFICATION 1664 UNLESS OTHERWISE NOTED ON THESE PLANS. DO NOT APPLY LIME OR FERTILIZER.
4. MAINTAIN EXISTING INFILTRATION RATE. NO HEAVY CONSTRUCTION EQUIPMENT PERMITTED ON BASIN BOTTOM. CONTACT ENGINEER IF CLAYEY SOILS ARE ENCOUNTERED DURING CONSTRUCTION.
5. CONTRACTOR SHALL CONDUCT HYDRAULIC CONDUCTIVITY TESTS AT 2 LOCATIONS IN THE BASIN BOTTOM PRIOR TO INSTALLATION OF GEOTEXTILE AND SOD. RESULTS SHALL BE REPORTED TO THE ENGINEER PRIOR TO INSTALLATION OF GEOTEXTILE AND SOD.



SECTION A-A – INFILTRATION BASIN
N.T.S.


PROJECT REFERENCE NO.	SHEET NO.
R-4436CH	2-A
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
	<div>SEAL 035946 ENGINEER JASON S. STES 2/22/2017</div>
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

8/17/99

REVISIONS

2/20/2017
J. H. C. dsh-02B.dgn
J. H. C. dsh-02B.dgn

BMP DETAILS 2




INFILTRATION BASIN FOREBAY

N.T.S.

- NOTE:
- DO NOT PLACE CLEAN SAND UNDERNEATH RIPRAP.
 - ELEVATIONS INDICATE TOP OF RIPRAP.


BASIN REF.	TOP TRANSITION BERM	BERM LENGTH	BOTTOM EL.	BASE LENGTH	LINING
1	42	5	39	15	CLASS B RIPRAP



INFILTRATION SPILLWAY OUTLET

N.T.S.

- NOTE:
- COMPACTED EMBANKMENT TO MEET SECTION 235 OF NCDOT STANDARD SPECIFICATIONS.



FALSE SUMP

N.T.S.

PROJECT REFERENCE NO. <i>R-4436CH</i>		SHEET NO. <i>2-B</i>
RW SHEET NO.		
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER	
	<div>SEAL 035946 ENGINEER JASON S. STEB 2/22/2017</div>	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		

8/17/99

2/20/2017
01_Rdy-psh-03.dgn
lisa.lamson

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

SUMMARY OF EARTHWORK *(for Stormwater BMP's)*


ITEM DESCRIPTION	UNIT	QUANTITY
		PROJECT TOTALS
UNCLASSIFIED EXCAVATION	CY	900
CLEARING AND GRUBBING	ACR	0.23
RIPRAP, CL. B	TON	160

DRAINAGE SUMMARY ***(for Stormwater BMP's)***

ITEM DESCRIPTION	UNIT	QUANTITY
		PROJECT TOTALS
GEOTEXTILE FOR DRAINAGE (TYPE 2, NON-WOVEN)	SY	275
3-D GEOTEXTILE	SY	575

SUMMARY FOR EROSION CONTROL ***(for Stormwater BMP's)***

ITEM DESCRIPTION	UNIT	QUANTITY
		PROJECT TOTALS
TEMP. SILT FENCE	LF	275
SEEDING & MULCHING	ACR	0.1
SODDING	SY	925
WATER	MG	20
EROSION CONTROL STONE CL. A	TON	26


PROJECT REFERENCE NO.	SHEET NO.
R-4436CH	3B / 3D
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
	
2/22/2017	
<p align="center">DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</p>	

8/17/99

REVISIONS

2/20/2017
01:14:05
J. J. Harrison
J. J. Harrison-04.dgn


PLAN VIEW



- NOTES:
- SEE SHEETS 2-A AND 2-B FOR PROFILE & DETAILS.
 - SOD WILL BE PLACED ON BASIN BOTTOM AND SIDES UNLESS OTHERWISE NOTED.



NAD 83/2011

PROJECT REFERENCE NO.		SHEET NO.
R-4436CH		4
RW SHEET NO.		
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER	
		
2/22/2017		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		


8/17/99


REVISIONS

2/20/2017
01:10:00
J:\Projects\2017\201702\20170201\20170201.dgn
J:\Projects\2017\201702\20170201\20170201.dgn

EROSION CONTROL PLAN

NAD 83/2011

PROJECT REFERENCE NO. <i>R-4436CH</i>		SHEET NO. <i>EC-1</i>
RW SHEET NO.		
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER	
		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED		




8/17/99

REVISIONS

2/20/2017
01:00 PM
TC-1.dgn
1101.04

TRAFFIC CONTROL PLAN

PROJECT REFERENCE NO. <i>R-4436CH</i>		SHEET NO. <i>TC-1</i>	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			


STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

1-12

ENGLISH STANDARD DRAWING FOR
WORK ZONE ADVANCE WARNING SIGNS FOR
FACILITIES \geq 55 MPH

SHEET 2 OF 3
1101.01

DETAIL A



GENERAL NOTES

- 1- USE FLUORESCENT ORANGE SHEETING (TYPE VII OR HIGHER) ON ALL ADVANCED WORK ZONE SIGNS.
- 2- DO NOT INSTALL ADVANCE WARNING SIGNS MORE THAN 3 DAYS PRIOR TO BEGINNING OF WORK UNLESS COVERED.
- 3- SIGNS SHOWN ARE REQUIRED FOR WORK ZONES THAT WILL REMAIN IN EFFECT OVERNIGHT. FOR SHORT-TERM DAILY MAINTENANCE TYPE OPERATIONS, THIS SIGNING APPLICATION IS OPTIONAL; MAY USE ONLY APPLICABLE ROADWAY STANDARD DRAWINGS INSTEAD. HOWEVER, IF THIS SIGNING APPLICATION IS USED, SIGNS MAY BE PORTABLE MOUNTED.
- 4- ALL SIGN SPACING DIMENSIONS ARE APPROXIMATE, FIELD ADJUST AS NECESSARY OR AS DIRECTED.
- 5- USE 3LB STEEL U-CHANNEL POST OR 4" X 4" WOOD POST FOR ALL WORK ZONE SIGNS. 3LB STEEL U-CHANNEL POSTS MUST MEET THE REQUIREMENTS OF STANDARD SPECIFICATION SECTION 1094-1(B), MAY BE GALVANIZED STEEL, OR MAY BE PAINTED GREEN BY THE POST MANUFACTURER. SQUARE STEEL TUBING POSTS HAVING EQUIVALENT STRENGTH OF THE 3 LB STEEL U-CHANNEL POST ARE ALSO ACCEPTABLE FOR USE. ERECT SIGNS PER ROADWAY STANDARD DRAWING 1110.01. PAYMENT FOR WOOD POSTS, 3LB STEEL U-CHANNEL AND SQUARE STEEL TUBING POSTS WITH SIGNS WILL BE MADE ACCORDING TO STANDARD SPECIFICATION "WORK ZONE SIGNS" SECTION 1110.
- 6- WHEN NECESSARY, USE SPLICING IN ACCORDANCE WITH ROADWAY STANDARD DRAWING NO. 1110.01.
- 7- DO NOT BACK BRACE SIGN SUPPORTS.
- 8- TWO-WAY UNDIVIDED ADVANCE WARNING SIGN CONFIGURATION MAY BE USED ON URBAN MULTI-LANE FACILITIES WHERE CONDITIONS LIMIT THE USE OF DUAL MOUNTED SIGNS AS DETERMINED BY THE ENGINEER.

LEGEND

- STATIONARY SIGN
- DIRECTION OF TRAFFIC FLOW


STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

1-12


ENGLISH STANDARD DRAWING FOR
WORK ZONE ADVANCE WARNING SIGNS FOR
FACILITIES \leq 55 MPH

SHEET 2 OF 3
1101.01


DETAIL B



DETAIL C



DETAIL D



GENERAL NOTES

- 1- IF NECESSARY, USE SPLICING IN ACCORDANCE WITH ROADWAY STANDARD DRAWING NO. 1110.01.
- 2- DO NOT BACK BRACE SIGN SUPPORTS.
- 3- TWO-WAY UNDIVIDED ADVANCE WARNING SIGN CONFIGURATION MAY BE USED ON URBAN MULTI-LANE FACILITIES WHERE CONDITIONS LIMIT THE USE OF DUAL MOUNTED SIGNS AS DETERMINED BY THE ENGINEER.

LEGEND

- STATIONARY SIGN
- DIRECTION OF TRAFFIC FLOW


STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

1-12


ENGLISH STANDARD DRAWING FOR
TEMPORARY SHOULDER CLOSURES

SHEET 1 OF 1
1101.04

SHOULDER CLOSURE ON CONTROLLED ACCESS FACILITIES - \geq 60 MPH




SHOULDER CLOSURE ON DIVIDED FACILITIES - \leq 55 MPH



SHOULDER CLOSURE ON UNDIVIDED ROADWAYS

(SEE NOTE 5)



GENERAL NOTES

- 1- PLACE SHOULDER CLOSURE SIGNS ON THE SAME SIDE AS THE SHOULDER THAT IS CLOSED.
- 2- PLACE DRUMS IN THE SHOULDER TAPER AT THE MAXIMUM SPACING EQUAL IN FEET TO THE POSTED SPEED LIMIT. THE MAXIMUM SPACING OF DRUMS ALONG THE WORK AREA IS EQUAL IN FEET TO 2 TIMES THE POSTED SPEED LIMIT.
- 3- USE STATIONARY SIGNS FOR LONG TERM OPERATIONS (LONGER THAN 3 DAYS).
- 4- REFER TO STD. 1101.11 FOR "L" DISTANCE AND SIGN SPACING.
- 5- THE TWO-LANE, TWO-WAY DRAWING MAY BE APPLIED TO UNDIVIDED, MULTI-LANE FACILITIES.

LEGEND

- DRUM
- STATIONARY OR PORTABLE SIGN
- DIRECTION OF TRAFFIC FLOW


STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

1-12


ENGLISH STANDARD DRAWING FOR
TEMPORARY LANE CLOSURES
DIVIDED MULTI-LANE ROADWAY-1 LANE CLOSED
(FOR ROADWAYS $<$ 60 MPH)

SHEET 3 OF 15
1101.02

LEFT LANE CLOSURE



RIGHT LANE CLOSURE



GENERAL NOTES

- 1- IF NECESSARY USE THIS STD. FOR ONE-WAY CITY TYPE STREETS WHERE SIGNS MAY BE MOUNTED ON BOTH SIDES OF THE ROADWAY.
- 2- PLACE ARROW BOARDS ON THE SHOULDER (PAVED OR UNPAVED). PLACE ARROW BOARDS WITHIN THE TAPER IF SHOULDERS DO NOT EXIST. MEET THE REQUIREMENTS FOR STOPPING SIGHT DISTANCE AT THE ARROW BOARD LOCATION. IF NEEDED, EXTEND LANE CLOSURES AT THE BUFFER SPACE, SUCH THAT STOPPING SIGHT DISTANCE TO THE ARROW BOARD IS MET (SEE STD. 1101.11 SHEET 2).
- 3- PLACE DRUMS IN TAPERS AT THE MAXIMUM SPACING EQUAL IN FEET TO THE POSTED SPEED LIMIT. PLACE DRUMS ALONG THE WORK AREA AT THE MAXIMUM SPACING EQUAL IN FEET TO 2 TIMES THE POSTED SPEED LIMIT.
- 4- REFER TO STD. 1101.11 FOR "L" DISTANCE, SIGN SPACING, AND BUFFER SPACE.
- 5- REFER TO STD. 1101.02 SHEETS 9 AND 10 FOR TREATMENT OF LANE CLOSURES THRU INTERCHANGES.
- 6- INSTALL LANE CLOSURES WITH THE TRAFFIC FLOW, BEGINNING WITH DEVICES ON THE UPSTREAM SIDE OF TRAFFIC. REMOVE LANE CLOSURES AGAINST THE TRAFFIC FLOW, BEGINNING WITH DEVICES ON THE DOWNSTREAM SIDE OF TRAFFIC.
- 7- POSITION THE TMA TO MAINTAIN A ROLL-AHEAD DISTANCE AS RECOMMENDED BY THE MANUFACTURER AND CONTINUOUSLY ADVANCE TMAS AS WORK PROGRESSES.
- 8- PLACE CHANGEABLE MESSAGE SIGN (CMS) ON THE OUTSIDE OF THE TRAVELWAY AS DIRECTED BY THE ENGINEER. PLACE CMS APPROXIMATELY 1 MILE IN ADVANCE OF THE W20-5 SIGNS. IF TRAFFIC BACKS UP TO WHERE THE CMS IS INITIALLY PLACED, RELOCATE CMS 1/2 MILE IN ADVANCE OF ANTICIPATED BACKUP. CONTINUE TO MONITOR TRAFFIC. MOVE CMS APPROXIMATELY 1/2 MILE IN ADVANCE OF ANTICIPATED BACKUP.
- 9- DO NOT EXCEED A 2 MILE LANE CLOSURE LENGTH UNLESS OTHERWISE SHOWN IN THE TMP OR AS DIRECTED BY THE ENGINEER.

LEGEND

- FLASHING ARROW BOARD (TYPE C)
- FLASHING ARROW BOARD, TYPE "C" (96"x48" MIN.) - CAUTION MODE
- TRUCK MOUNTED ATTENUATOR (TMA)
- CHANGEABLE MESSAGE SIGN (CMS)
- DRUM
- PORTABLE SIGN
- DIRECTION OF TRAFFIC FLOW