

**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**



**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**


**This file or an individual page
shall not be considered a certified document.**

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

SIGNING PLAN
GRANVILLE / VANCE COUNTIES

LOCATION: I-85 APPROX. 2880 FT NORTH OF EXIT 191
AND ENDS APPROX. 4350 FT SOUTH OF EXIT 209.

TIP NO.	SHEET NO.
I-5843	SIGN-1
APPROVED: 	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	



SUMMARY OF QUANTITIES

ITEM NO.		ITEM DESCRIPTION	QUANTITY	UNIT
DESC. NO.	SECT. NO.			
4110000000	904	SIGN ERECTION, TYPE A (GROUND MOUNTED)	32	EA.
4110000000	904	SIGN ERECTION, TYPE B (GROUND MOUNTED)	23	EA.
4096000000	904	SIGN ERECTION, TYPE D	7	EA.
4060000000	903	SUPPORTS, BREAKAWAY STEEL BEAM	24357	LB.
4054000000	902	PLAIN CONCRETE SIGN FOUNDATION	2	C.Y.
4048000000	902	REINFORCED CONCRETE SIGN FOUNDATION	29	C.Y.
4236000000	907	DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)	14	EA.
4238000000	907	DISPOSAL OF SIGN, D	4	EA.
4152000000	907	DISPOSAL OF SIGN SYSTEM, STEEL BEAM	23	EA.
4155000000	907	DISPOSAL OF SIGN SYSTEM, U-CHANNEL	1	EA.

ROADWAY STANDARD DRAWING

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2012 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
901.10	TYPE 'A' SIGNS
901.20	TYPE 'B' SIGNS
901.50	ARROWS AND SHIELDS
901.70	SIGN STRINGERS AND SUPPORT SPACING
901.80	SIGN MOUNTING DETAILS - FOR TYPE A AND TYPE B SIGNS
903.10	GROUND MOUNTED SIGN SUPPORTS
904.10	ORIENTATION OF GROUND MOUNTED SIGNS
904.20	SECONDARY SIGN MOUNTING
904.30	SUPPLEMENTAL SIGN MOUNTING
904.50	MOUNTING OF TYPE 'D', 'E' AND 'F' SIGNS ON 'U' CHANNEL POSTS

PLAN PREPARED BY: N.C.D.O.T. SIGNING AND DELINEATION UNIT

Renee Roach, PE SIGNING & DELINEATION REGIONAL ENGINEER
Ashley Kidd SIGNING & DELINEATION PROJECT DESIGN ENGINEER



GENERAL NOTES

- SIGNS FURNISHED BY STATE
- CONFIRM IN WRITING AT LEAST 4 MONTHS IN ADVANCE, THE ACTUAL DATE THE DEPARTMENT FURNISHED SIGNS WILL BE REQUIRED.
- ALL TYPE 'D' SIGNS SHALL BE MOUNTED ON TWO U-CHANNEL POSTS UNLESS OTHERWISE INDICATED ON THE PLANS.
- IF REMOVAL OR RELOCATION OF SIGNS ON PRIVATE STREET (NON-STATE MAINTAINED) IS REQUIRED DUE TO CONSTRUCTION, THE CONTRACTOR SHALL INFORM THE ENGINEER. THE WORK WILL BE COMPLETED BY OTHERS.
- WHEN NOT STATIONED OR DIMENSIONED ON PLANS, ALL 'E' AND 'F' SIGNS SHALL BE FIELD LOCATED BY THE ENGINEER
- ALL EXISTING SIGNS ON "U" CHANNEL POST WITHIN THE PROJECT LIMITS SHALL BE REMOVED AND DISPOSED OF UNLESS OTHERWISE NOTED ON PLANS.
- WHEN EXISTING SIGNS ARE REMOVED AND INSTALLED ON NEW SUPPORTS, THE RE-ERECTION SHALL IMMEDIATELY FOLLOW THE REMOVAL.
- THE BACKGROUND FOR TYPE E & F SIGNS SHALL BE TYPE C REFLECTIVE SHEETING.
- DO NOT BEGIN FABRICATION FOR TYPES A & B SIGNS MOUNTED ON OVERHEAD STRUCTURES OR STEEL SUPPORTS UNTIL "S" DIMENSIONS HAVE BEEN FIELD VERIFIED.
- SEE ROADWAY PLANS FOR GUARD/GUIDE RAIL DETAILS.

PROJECT NOTES

- DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- DISPOSAL OF SIGN, D
- INSTALL 20 FT BEHIND EXISTING SIGN
- INSTALL 10 FT BEHIND EXISTING SIGN
- INSTALL 100 FT IN FRONT OF EXISTING SIGN

INDEX



SHEET NO.	DESCRIPTION
SIGN-1	TITLE SHEET
SIGN-2-2B	SUPPORTS AND STANDARD DRAWINGS
SIGN-3-3J	SIGN DESIGNS
SIGN-4-18	SIGN DETAIL SHEETS

5/27/2016
S:\S&DU\Central\Ashley\I-5843\CADD\I-5843 Seed File.dgn
User:akidol


SIGN NO.	SIGN TYPE	SIGN SIZE (in. h		ROADWAY STATION	NO. OF SUP.	BEAM SECTION	SUPPORT TYPE BA or S	ATTACH METHOD	MOUNTING METHOD	HORIZ CLR. (ft.	LENGTH (ft)			LEFT SUPPORT (ft)			CENTER SUPPORT (ft)			RIGHT SUPPORT (ft)			FOOTING DIAMETER (ft.)	FOOTING DEPTH (ft.)	B/A SUPPORT WEIGHTS (lbs.)	SIMPLE SUPPORT WEIGHTS (lbs.)	REINF. FTGS. (c.y.)	PLAIN FTGS. (c.y.)	FIELD VERIFIED SEE NOTE 2 (mm/dd/yy)
		w	x								SNS HT H	MTG HT C	EMBED-MENT	S	L	TOTAL LENGTH	S	L	TOTAL LENGTH	S	L	TOTAL LENGTH							
101A	B	132	X30		2	W10x26	BA	1-R	N/A	30.00	11.50	7.00	6	3.70	22.20	28.20	0.00	0.00	0.00	4.50	23.00	29.00	2.5	6.5	1767.20	0.00	2.36	0.00	
101B	A	174	X138																										
102A	B	132	X30		2	W8x21	BA	1-R	N/A	30.00	11.50	7.20	6	2.60	21.30	27.30	0.00	0.00	0.00	-0.20	18.50	24.50	2.00	6.5	1233.80	0.00	1.51	0.00	
102B	A	174	X138																										
101A	B	132	X30		2	W10x26	BA	1-R	N/A	7.00	11.50	7.00	6	1.70	20.20	26.20	0.00	0.00	0.00	4.60	23.10	29.10	2.50	6.5	1717.80	0.00	2.36	0.00	
103B	A	174	X138																										
104A	B	132	X30		2	W8x21	BA	1-R	N/A	33.00	12.00	7.00	6	2.50	21.50	27.50	0.00	0.00	0.00	1.60	20.60	26.60	2.00	6.5	1282.10	0.00	1.51	0.00	
104B	A	174	X144																										
105A	B	132	X30		2	W10x26	BA	1-R	N/A	30.00	12.00	7.00	6	2.80	21.80	27.80	0.00	0.00	0.00	3.60	22.60	28.60	2.50	6.5	1746.40	0.00	2.36	0.00	
105B	A	174	X144																										
106A	B	132	X30		2	W8x21	BA	1-R	N/A	30.00	11.50	7.70	5.5	2.40	21.60	27.10	0.00	0.00	0.00	-0.70	18.50	24.00	2.00	6	1219.10	0.00	1.40	0.00	
106B	A	138	X138																										
107A	B	132	X30		2	W8x21	BA	1-R	N/A	7.00	11.50	7.00	6	1.60	20.10	26.10	0.00	0.00	0.00	3.30	21.80	27.80	2.00	6.5	1277.90	0.00	1.51	0.00	
107B	A	138	X138																										
108A	B	132	X30		2	W8x21	BA	1-R	N/A	32.00	14.00	7.00	5.5	3.30	24.30	29.80	0.00	0.00	0.00	2.30	23.30	28.80	2.00	6	1376.60	0.00	1.40	0.00	
108B	A	132	X138																										
109A	B	132	X30		2	W8x21	BA	1-R	N/A	7.00	11.50	7.00	6	1.40	19.90	25.90	0.00	0.00	0.00	3.20	21.70	27.70	2.00	6.5	1271.60	0.00	1.51	0.00	
109B	A	144	X138																										
110A	B	132	X30		2	W6x16	BA	1-R	N/A	7.00	9.00	7.00	5.5	1.40	17.40	22.90	0.00	0.00	0.00	3.20	19.20	24.70	1.50	6	855.60	0.00	0.79	0.00	
110B	A	138	X108																										
111A	B	132	X30		2	W8x18	BA	1-R	N/A	25.00	8.50	7.00	5.5	3.40	18.90	24.40	0.00	0.00	0.00	5.20	20.70	26.20	2.00	6	1050.80	0.00	1.40	0.00	
111B	A	138	X102																										
112A	B	132	X30		2	W8x21	BA	1-R	N/A	25.00	9.50	7.00	5.5	3.10	19.60	25.10	0.00	0.00	0.00	5.10	21.60	27.10	2.00	6	1242.20	0.00	1.40	0.00	
112B	A	138	X114																										
113A	B	132	X30		2	W6x16	BA	1-R	N/A	30.00	9.50	7.50	6	2.00	19.00	25.00	0.00	0.00	0.00	-0.50	16.50	22.50	1.50	6.5	854.00	0.00	0.85	0.00	
113B	A	138	X114																										
114A	B	132	X30		2	W8x21	BA	1-R	N/A	30.00	11.50	7.00	6	3.50	22.00	28.00	0.00	0.00	0.00	2.40	20.90	26.90	2.00	6.5	1298.90	0.00	1.51	0.00	
114B	A	168	X138																										
115A	B	132	X30		2	W10x22	BA	1-R	N/A	7.00	11.50	7.00	5.5	2.30	20.80	26.30	0.00	0.00	0.00	3.80	22.30	27.80	2.50	6	1428.20	0.00	2.18	0.00	
115B	A	168	X138																										
116A	B	132	X30		2	W10x26	BA	1-R	N/A	32.00	12.00	7.00	5.5	3.40	22.40	27.90	0.00	0.00	0.00	1.60	20.60	26.10	2.50	6	1684.00	0.00	2.18	0.00	
116B	A	168	X144																										
117A	B	132	X30		2	W8x18	BA	1-R	N/A	30.00	5.50	7.00	5.5	4.90	17.40	22.90	0.00	0.00	0.00	6.90	19.40	24.90	2.00	6	1000.40	0.00	1.40	0.00	
117B	A	216	X66																										
118A	B	132	X30		2	W6x16	BA	1-R	N/A	30.00	5.50	7.00	5.5	3.70	16.20	21.70	0.00	0.00	0.00	1.80	14.30	19.80	1.50	6	758.00	0.00	0.79	0.00	
118B	A	216	X66																										
125	A	96	X60		2	S3x5.7	BA	N/A	N/A	△	5.00	7.00	3.5	1.10	13.10	16.60	0.00	0.00	0.00	1.20	13.20	16.70	1.00	4	225.81	0.00	0.00	0.23	
126	A	96	X60		2	S4x7.7	BA	N/A	N/A	△	5.00	7.00	3.5	1.20	13.20	16.70	0.00	0.00	0.00	1.40	13.40	16.90	1.00	4	298.72	0.00	0.00	0.23	
130	A	96	X60		2	S3x5.7	BA	N/A	N/A	△	5.00	7.00	3.5	0.70	12.70	16.20	0.00	0.00	0.00	0.90	12.90	16.40	1.00	4	221.82	0.00	0.00	0.23	
131	A	96	X60		2	S3x5.7	BA	N/A	N/A	△	5.00	7.00	3.5	0.70	12.70	16.20	0.00	0.00	0.00	1.20	13.20	16.70	1.00	4	223.53	0.00	0.00	0.23	
132	B	108	X36		2	S4x7.7	BA	N/A	N/A	30.00	3.00	7.00	3.5	4.20	14.20	17.70	0.00	0.00	0.00	5.40	15.40	18.90	1.00	4	321.82	0.00	0.00	0.23	
* SIGN SUPPORT CENTERS SPACED AT 7' 7"																						TOTAL		TOTAL		TOTAL		TOTAL	
																						24356.30		0.00		28.42		1.16	
USE:																						24357		0		29		2	

NOTES

- DIMENSION "S" REPRESENTS AN INCREASE (+), OR A DECREASE (-) IN POLE LENGTH, RELATIVE TO THE ELEVATION OF THE EDGE OF TRAVEL LANE.
- FIELD VERIFICATIONS SHALL BE REQUIRED FOR ALL SUPPORTS, SEE (*) ARTICLE 903-3. FABRICATORS SHALL BE AISC CERTIFIED IN CATEGORY 1, SEE (*) ARTICLE 1072-1. (*) = N.C.D.O.T. STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES
- PLAN LOCATIONS FOR EXISTING UTILITIES ARE BASED ON THE BEST AVAILABLE INFORMATION AND, THEREFORE MAY NOT BE PRECISELY ACCURATE. THEREFORE, IT IS INCUMBENT UPON THE CONTRACTOR TO DETERMINE THE EXACT LOCATION OF UTILITIES BEFORE BEGINNING WORK IN A LOCATION.



TYPE "A" AND TYPE "B"
GROUND MOUNTED SIGNS



TIP NO. I-5843	SHEET NO. SIGN-2
Designed by: APPROVED: <i>Ronald W. King</i> 1367AF7B8AA4448	
DATE: 5/31/2016 5:24 AM PT	
SEAL 	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH DETAIL DRAWING FOR
GROUND MOUNTED SIGN SUPPORTS

SHEET 2 OF 3
903D10

	SLIP BASE PLATE DATA								KEEPER PLATE DATA							HINGE CONNECTION DATA										BREAK AWAY SUPPORT WEIGHT CONSTANT LBS.
BEAM SHAPE	BOLT SIZE	A ₁	B ₁	C ₁	D ₁	E ₁	T ₁	R ₁	A ₂	B ₂	C ₂	D ₂	E ₂	R ₂	T ₂	BOLT SIZE	F	G	H	I	J	K	L	R ₃	T ₃	
S3X5.7	½"DIA.X ¾"	7"	4"	1"	¾"	2½"	1"	⅝ ₃₂ "	7"	4"	1"	¾"	2½"	⅝ ₃₂ "	28 GAUGE	½"DIA.X1¾"	2¼"	3½"	4"	½"	1"	½"	2"	⅝ ₃₂ "	⅜"	18
S4X7.7	½"DIA.X ¾"	8"	4"	1"	¾"	2½"	1"	⅝ ₃₂ "	8"	4"	1"	¾"	2½"	⅝ ₃₂ "	28 GAUGE	½"DIA.X1¾"	2⅝"	3½"	4"	½"	1"	½"	2"	⅝ ₃₂ "	⅜"	20
W6X9	½"DIA.X ¾"	10"	5"	1"	¾"	3½"	1"	⅝ ₃₂ "	10"	5"	1"	¾"	3½"	⅝ ₃₂ "	28 GAUGE	½"DIA.X1¾"	4"	3½"	4"	¾"	1"	½"	2"	⅝ ₃₂ "	⅜"	32
W6X12	⅝" DIA.X 4"	11"	5"	1¼"	⅞"	3¼"	1¼"	1⅜ ₃₂ "	11"	5"	1¼"	⅞"	3¼"	1⅜ ₃₂ "	28 GAUGE	⅝" DIA.X 2"	4"	4"	4½"	¾"	1⅛"	⅝"	2¼"	1⅜ ₃₂ "	⅜"	39
W6X16	⅝" DIA.X 4½"	12"	6"	1¼"	⅞"	4¼"	1½"	1⅜ ₃₂ "	12"	6"	1¼"	⅞"	4¼"	1⅜ ₃₂ "	28 GAUGE	⅝" DIA.X2¼"	4"	4"	4½"	¾"	1⅛"	⅝"	2¼"	1⅜ ₃₂ "	½"	47
W8X18	⅝" DIA.X 4½"	13½"	6½"	1¼"	⅞"	4¾"	1½"	1⅜ ₃₂ "	13½"	6½"	1¼"	⅞"	4¾"	1⅜ ₃₂ "	28 GAUGE	⅝" DIA.X2¼"	5¼"	4"	4½"	1"	1⅛"	⅝"	2¼"	1⅜ ₃₂ "	½"	70
W8X21	¾" DIA.X 4½"	14"	7"	1½"	1"	5"	1½"	1⅜ ₃₂ "	14"	7"	1½"	1"	5"	1⅜ ₃₂ "	28 GAUGE	¾" DIA.X2½"	5¼"	6"	7"	1"	1¾"	¾"	3½"	1⅜ ₃₂ "	½"	73
W10X22	¾" DIA.X 4½"	16"	8"	1½"	1"	6"	1½"	1⅜ ₃₂ "	16"	8"	1½"	1"	6"	1⅜ ₃₂ "	28 GAUGE	¾" DIA.X2½"	5¾"	6"	7"	1"	1¾"	¾"	3½"	1⅜ ₃₂ "	½"	119
W10X26	¾" DIA.X 5½"	16½"	8"	1½"	1"	6"	1¾"	1⅜ ₃₂ "	16½"	8"	1½"	1"	6"	1⅜ ₃₂ "	28 GAUGE	¾" DIA.X2¾"	5¾"	6"	7"	1"	1¾"	¾"	3½"	1⅜ ₃₂ "	⅝"	140
W12X26	¾" DIA.X 5½"	18½"	9"	1½"	1"	7"	1¾"	1⅜ ₃₂ "	18½"	9"	1½"	1"	7"	1⅜ ₃₂ "	28 GAUGE	¾" DIA.X2¾"	6½"	6"	7"	1"	1¾"	¾"	3½"	1⅜ ₃₂ "	⅝"	176
W14X30	1" DIA.X 6"	22"	9"	2"	1½"	6"	2"	1⅜ ₃₂ "	22"	9"	2"	1½"	6"	1⅜ ₃₂ "	28 GAUGE	1" DIA.X 3"	6¾"	7"	8"	1¼"	2"	1"	4"	1⅜ ₃₂ "	⅝"	205
W16X31	1" DIA.X 6"	24"	9"	2"	1½"	6"	2"	1⅜ ₃₂ "	24"	9"	2"	1½"	6"	1⅜ ₃₂ "	28 GAUGE	1" DIA.X 3"	5½"	7"	8"	1¼"	2"	1"	4"	1⅜ ₃₂ "	¾"	223
W18X35	1" DIA.X 6"	25"	9"	2"	1½"	6"	2"	1⅜ ₃₂ "	25"	9"	2"	1½"	6"	1⅜ ₃₂ "	28 GAUGE	1" DIA.X 3"	6"	7"	8"	1¼"	2"	1"	4"	1⅜ ₃₂ "	¾"	243
W18X40	1" DIA.X 6½"	26"	9"	2"	1½"	6"	2¼"	1⅜ ₃₂ "	26"	9"	2"	1½"	6"	1⅜ ₃₂ "	28 GAUGE	1" DIA.X3½"	6"	7"	8"	1¼"	2"	1"	4"	1⅜ ₃₂ "	⅞"	278
W21X44	1" DIA.X 7"	29"	9"	2"	1½"	6"	2½"	1⅜ ₃₂ "	29"	9"	2"	1½"	6"	1⅜ ₃₂ "	28 GAUGE	1" DIA.X3½"	6½"	7"	8"	1¼"	2"	1"	4"	1⅜ ₃₂ "	⅞"	310



FOUNDATION DATA *		
FOOTING DIAMETER	REINFORCEMENT	SPIRAL BAR
1'-6"	8 # 6 BARS	#3 BAR, 6" PITCH
2'	8 # 7 BARS	#3 BAR, 6" PITCH
2'-6"	8 # 9 BARS	#3 BAR, 6" PITCH
3'	8 # 11 BARS	#3 BAR, 6" PITCH
3'-6"	8 # 12 BARS	#3 BAR, 6" PITCH
4'	8 # 14 BARS	#3 BAR, 6" PITCH

* FOUNDATION DIMENSIONS ARE SHOWN IN PLANS


STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH DETAIL DRAWING FOR
GROUND MOUNTED SIGN SUPPORTS


SHEET 2 OF 3
903D10

PROJECT REFERENCE NO.
I-5843

SHEET NO.
SIGN-2A

APPROVED: 

DATE: 4/25/16

SEAL


DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED








4/25/2016
I:\1-5843\1-5843 Seed File.dgn
0:00:00

STATE OF
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

1-12

ENGLISH STANDARD DRAWING FOR
GROUND MOUNTED SIGN SUPPORTS

SHEET 1 OF 3
903D10



SEE SHEET 2 OF 3 FOR
BASE CONNECTION DATA
HINGE CONNECTION DATA
& FOUNDATION DATA.
SEE SHEET 3 OF 3 FOR
GENERAL NOTES.

STATE OF
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.



1-12

ENGLISH STANDARD DRAWING FOR
GROUND MOUNTED SIGN SUPPORTS

SHEET 1 OF 3
903D10

PROJECT REFERENCE NO.	SHEET NO.
I-5843	SIGN-2B
APPROVED: <i>[Signature]</i>	
DATE: 4/27/16	
SEAL	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

REVISED SIGNING
ROADWAY STANDARD DRAWING

TIP NO.	SHEET NO.
I-5843	SIGN-3A
APPROVED: 	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

SIGN NUMBER: 1068 TYPE: A QUANTITY: 1 SIGN WIDTH: 11'-6" HEIGHT: 11'-6" TOTAL AREA: 132.3 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADIUS: 12" NO. Z BARS: 3 LENGTH: 130.0	BACKG COLOR: Green COPY COLOR: White SYMBOL M1_4 X 46.5 Y 88 WID 45 HT 36 MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 N/B Apr 20, 2016 DIV: 5
---	---	--

11'-6"

112"

14"

36"

12"

13.3"EM

12"

13.3"EM

13.3"

8"E

16.1"

11'-6"

112"

14"

36"

12"

13.3"EM

12"

13.3"EM

13.3"

8"E

16.1"

BORDER

R=12"

TH=2"

27.7"

82.6"

27.7"

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter											Series/Size
	O	x	f	a	r	d					Text Length
35.7	14	13.5	8.5	13.2	8.7	8.8	35.7				EM 2000
	R	o	x	b	o	r	o				66.7
27.7	13.2	12	14.8	11.7	13.2	8.7	9.1	27.7			EM 2000
	M	I	L	E	S						82.6
71.7	9.6	3.5	7.4	7.1	6.5	32.2					E 2000
	1		1/2								34.1
32.2	3.6	6	17.6	78.6							E 2000
											27.2

FILENAME: I-5843 NB Sign Designs

NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 1078 TYPE: A QUANTITY: 1 SIGN WIDTH: 12'-0" HEIGHT: 11'-6" TOTAL AREA: 138.0 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADIUS: 12" NO. Z BARS: 3 LENGTH: 136.0	BACKG COLOR: Green COPY COLOR: White SYMBOL M1_4 X 49.5 Y 88 WID 45 HT 36 MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 S/B Mar 09, 2016 DIV: 5
---	---	--

11'-6"

112"

14"

36"

12"

13.3"EM

12"

13.3"EM

13.3"

8"E

16.1"

11'-6"

112"

14"

36"

12"

13.3"EM

12"

13.3"EM

13.3"

8"E

16.1"

BORDER

R=12"

TH=2"

27.7"

82.6"

27.7"

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter											Series/Size
	O	x	f	a	r	d					Text Length
38.7	14	13.5	8.5	13.2	8.7	8.8	38.7				EM 2000
	R	o	x	b	o	r	o				66.7
30.7	13.2	12	14.8	11.7	13.2	8.7	9.1	30.7			EM 2000
	M	I	L	E	S						82.6
73.8	9.6	3.5	7.4	6	43.8						E 2000
	3/4										26.5
43.8	20	80.2									E 2000
											20

FILENAME: I-5843 Sign Designs

NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 1068 TYPE: A QUANTITY: 1 SIGN WIDTH: 11'-0" HEIGHT: 11'-6" TOTAL AREA: 126.5 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADIUS: 12" NO. Z BARS: 3 LENGTH: 124.0	BACKG COLOR: Green COPY COLOR: White SYMBOL M1_4 X 43.5 Y 91 WID 45 HT 36 AR_Type A 54.5 10 18.3 29.3 MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 N/B Apr 20, 2016 DIV: 5
---	--	--

11'-0"

112"

11"

36"

10"

13.3"EM

10"

13.3"EM

11.4"

23"

10"

11'-0"

112"

11"

36"

10"

13.3"EM

10"

13.3"EM

11.4"

23"

10"

BORDER

R=12"

TH=2"

24.7"

82.6"

24.7"

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter											Series/Size
	O	x	f	a	r	d					Text Length
32.7	14	13.5	8.5	13.2	8.7	8.8	32.7				EM 2000
	R	o	x	b	o	r	o				66.7
24.7	13.2	12	14.8	11.7	13.2	8.7	9.1	24.7			EM 2000
											82.6

FILENAME: I-5843 NB Sign Designs

NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 1098 TYPE: A QUANTITY: 1 SIGN WIDTH: 12'-0" HEIGHT: 11'-6" TOTAL AREA: 138.0 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADIUS: 12" NO. Z BARS: 3 LENGTH: 136.0	BACKG COLOR: Green COPY COLOR: White SYMBOL M1_4 X 49.5 Y 91 WID 45 HT 36 AR_Type A 60.5 10 18.3 29.3 MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 S/B Mar 09, 2016 DIV: 5
---	--	--

12'-0"

112"

11"

36"

10"

13.3"EM

10"

13.3"EM

11.4"

23"

10"

12'-0"

112"

11"

36"

10"

13.3"EM

10"

13.3"EM

11.4"

23"

10"

BORDER

R=12"

TH=2"

30.7"

82.6"

30.7"

Spacing Factor is 1 unless specified otherwise



LETTER POSITIONS

Letter spacings are to start of next letter											Series/Size
	O	x	f	a	r	d					Text Length
38.7	14	13.5	8.5	13.2	8.7	8.8	38.7				EM 2000
	R	o	x	b	o	r	o				66.7
30.7	13.2	12	14.8	11.7	13.2	8.7	9.1	30.7			EM 2000
											82.6


FILENAME: I-5843 Sign Designs

NORTH CAROLINA D.O.T. SIGN DETAIL

TYPE "A" SIGNS

TIP NO.	SHEET NO.
I-5843	SIGN-3B
APPROVED: 	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

SIGN NUMBER: 110B TYPE: A QUANTITY: 1 SIGN WIDTH: 11'-6" HEIGHT: 9'-0" TOTAL AREA: 103.5 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12" NO. Z BARS: 3 LENGTH: 130.0	BACKG COLOR: Green COPY COLOR: White SYMBOL X Y WID HT NC96 51 60 36 36 MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 N/B Apr 01, 2016 DIV: 5
---	---	--




Spacing Factor is 1 unless specified otherwise

Letter positions									
Letter spacings are to start of next letter									
	O	x	f	o	r	d		Series/Size	Text Length
35.7	14	13.5	8.5	13.2	8.7	8.8	35.7	EM 2000	66.7
	M	I	L	E				E 2000	26.5
62.6	9.6	3.5	7.4	6	49			E 2000	3.6
	1								
49	3.6	85.4							

FILENAME: I-5843 NB Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 111B TYPE: A QUANTITY: 1 SIGN WIDTH: 11'-6" HEIGHT: 8'-6" TOTAL AREA: 97.8 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12" NO. Z BARS: 3 LENGTH: 130.0	BACKG COLOR: Green COPY COLOR: White SYMBOL X Y WID HT NC96 51.6 55.1 36 36 MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 S/B Mar 21, 2016 DIV: 5
--	---	--




Spacing Factor is 1 unless specified otherwise

Letter positions									
Letter spacings are to start of next letter									
	O	x	f	o	r	d		Series/Size	Text Length
35.7	14	13.5	8.5	13.2	8.7	8.8	35.7	EM 2000	66.7
	M	I	L	E				E 2000	26.5
69.6	9.6	3.5	7.4	6	42			E 2000	17.6
	1/2								
42	17.6	78.5							

FILENAME: I-5843 Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 112B, 113B TYPE: A QUANTITY: 2 SIGN WIDTH: 11'-6" HEIGHT: 9'-6" TOTAL AREA: 109.3 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12" NO. Z BARS: 3 LENGTH: 130.0	BACKG COLOR: Green COPY COLOR: White SYMBOL X Y WID HT NC242 51 68.1 36 36 AR_Type A 57.5 10 18.3 29.3 MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 N/B & S/B Apr 15, 2016 DIV: 5
---	---	--




Spacing Factor is 1 unless specified otherwise

Letter positions									
Letter spacings are to start of next letter									
	O	x	f	o	r	d		Series/Size	Text Length
35.7	14	13.5	8.5	13.2	8.7	8.8	35.7	EM 2000	66.7

FILENAME: I-5843 NB Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 114B TYPE: A QUANTITY: 1 SIGN WIDTH: 14'-0" HEIGHT: 11'-6" TOTAL AREA: 161.0 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12" NO. Z BARS: 3 LENGTH: 160.0	BACKG COLOR: Green COPY COLOR: White SYMBOL X Y WID HT NC56 66 88 36 36 MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 S/B Mar 09, 2016 DIV: 5
--	---	--





Spacing Factor is 1 unless specified otherwise


Letter positions									
Letter spacings are to start of next letter									
	B	u	t	n	e	r		Series/Size	Text Length
48.5	14.5	12.8	11.2	12.9	12.9	6.7	48.4	EM 2000	71
	C	r	e	e	d	m	o	r	
28.3	14.5	8.7	11.7	11.7	14.1	18.8	12	13.2	6.7
	M	I	L	E	S				
77.4	9.6	3.5	7.4	7.1	6.5	56.5		E 2000	34.1
	2							E 2000	9.7
56.5	9.7	101.8							

FILENAME: I-5843 Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

TYPE "A" SIGNS

TIP NO.	SHEET NO.
I-5843	SIGN-3C
APPROVED:	
DATE:	4/27/16
SEAL	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

SIGN NUMBER: 1158 TYPE: A QUANTITY: 1 SIGN WIDTH: 14'-0" HEIGHT: 11'-6" TOTAL AREA: 161.0 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12" NO. Z BARS: 3 LENGTH: 160.0	BACKG COLOR: Green COPY COLOR: White SYMBOL X Y WID HT NCS6 66 88 36 36 MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 S/B Mar 09, 2016 DIV: 5
--	--	--




USE NOTES:
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.
3. Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum with Grade C reflective sheeting and demountable.

LETTER POSITIONS

Letter spacings are to start of next letter															Series/Size	
															Text Length	
B	u	t	n	e	r											EM 2000
48.5	14.5	12.8	11.2	12.9	6.7	48.4										71
C	r	e	e	d	m	o	o	r								EM 2000
28.3	14.5	8.7	11.7	11.7	14.1	18.8	12	13.2	6.7	28.3						111.4
M	I	L	E													E 2000
77.6	9.6	3.5	7.4	6	63.9											26.5
1																E 2000
64	3.6	100.4														3.6

FILENAME: I-5843 Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 1168 TYPE: A QUANTITY: 1 SIGN WIDTH: 14'-0" HEIGHT: 12'-0" TOTAL AREA: 168.0 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12" NO. Z BARS: 3 LENGTH: 160.0	BACKG COLOR: Green COPY COLOR: White SYMBOL X Y WID HT NCS6 66 88 36 36 AR_Type A 72.5 12.1 18.3 29.3 MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 S/B Mar 09, 2016 DIV: 5
--	---	--




USE NOTES:
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.
3. Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum with Grade C reflective sheeting and demountable.

LETTER POSITIONS

Letter spacings are to start of next letter															Series/Size	
															Text Length	
B	u	t	n	e	r											EM 2000
48.6	14.5	12.8	11.2	12.9	6.7	48.4										71
C	r	e	e	d	m	o	o	r								EM 2000
28.3	14.5	8.7	11.7	11.7	14.1	18.8	12	13.2	6.7	28.3						111.4
M	I	L	E													E 2000
77.6	9.6	3.5	7.4	6	63.9											26.5
1																E 2000
64	3.6	100.4														3.6

FILENAME: I-5843 Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 1178 TYPE: A QUANTITY: 1 SIGN WIDTH: 18'-0" HEIGHT: 5'-6" TOTAL AREA: 99.0 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 9" NO. Z BARS: 2 LENGTH: 208.0	BACKG COLOR: Green COPY COLOR: White SYMBOL X Y WID HT MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 N/B Apr 15, 2016 DIV: 5
---	--	--




USE NOTES:
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

LETTER POSITIONS

Letter spacings are to start of next letter															Series/Size	
															Text Length	
P	o	p	l	a	r											EM 2000
22.1	12.8	13.2	12.9	6.8	14.1	6.7	13.3	14.5	8.7	11.7	12.9	8.8	13.3	13.2	8.8	171.8
M	I	L	E													E 2000
101.6	9.6	3.5	7.4	6	88											26.5
1																E 2000
88	3.6	124.4														3.6

FILENAME: I-5843 NB Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 1188 TYPE: A QUANTITY: 1 SIGN WIDTH: 18'-0" HEIGHT: 5'-6" TOTAL AREA: 99.0 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 9" NO. Z BARS: 2 LENGTH: 208.0	BACKG COLOR: Green COPY COLOR: White SYMBOL X Y WID HT MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 W/B Apr 15, 2016 DIV: 5
---	--	--







USE NOTES:
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

LETTER POSITIONS

Letter spacings are to start of next letter															Series/Size	
															Text Length	
P	o	p	l	a	r											EM 2000
22.1	12.8	13.2	12.9	6.8	14.1	6.7	13.3	14.5	8.7	11.7	12.9	8.8	13.3	13.2	8.8	171.8
M	I	L	E													E 2000
100.8	9.6	3.5	7.4	7.1	6.5	81.1										34.1
2																E 2000
81.1	9.7	125.2														9.7

FILENAME: I-5843 WB Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

TYPE "A" SIGNS



TIP NO. I-5843
SHEET NO. SIGN-3D





APPROVED: *[Signature]*
DATE: 4/27/16

SEAL

SEAL
NORTH CAROLINA
PROFESSIONAL
ENGINEER
022959
DAVID W. KING


DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

TYPE "A" SIGNS




TIP NO.
I-5843

SHEET NO.
SIGN-3F

APPROVED: 

DATE: 4/27/16

SEAL


DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED


SIGN NUMBER: 128, 129
TYPE: A
QUANTITY: 2
SIGN WIDTH: 8'-0"
HEIGHT: 5'-0"
TOTAL AREA: 40.0 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 1.5"
RADIUS: 6"
NO. Z BARS: 2
LENGTH: 88.0

BACKG COLOR: Green
COPY COLOR: White
SYMBOL
AR_Type A
X
Y
WID
HT
67
6
18.3
29.3

MAT'L: 0.125" (3.2 mm) ALUMINUM

USE NOTES:
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.
3. Shields: A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum with Grade C reflective sheeting and demountable.

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B & S/B
Mar 08, 2016
DIV: 5



LETTER POSITIONS
Letter spacings are to start of next letter
Series/Size
Text Length
E 2000
25.8 12.8 15.8 6.8 9 25.8 44.4
2 0 4
7.4 17.6 17.6 16.9 36.4 52.2
FILENAME: I-5843 Sign Designs
NORTH CAROLINA D.O.T. SIGN DETAIL


SIGN NUMBER: 130, 131
TYPE: A
QUANTITY: 2
SIGN WIDTH: 8'-0"
HEIGHT: 5'-0"
TOTAL AREA: 40.0 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 1.5"
RADIUS: 6"
NO. Z BARS: 2
LENGTH: 88.0

BACKG COLOR: Green
COPY COLOR: White
SYMBOL
AR_Type A
X
Y
WID
HT
67
6
18.3
29.3

MAT'L: 0.125" (3.2 mm) ALUMINUM

USE NOTES:
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.
3. Shields: A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum with Grade C reflective sheeting and demountable.

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B & S/B
Mar 08, 2016
DIV: 5



LETTER POSITIONS
Letter spacings are to start of next letter
Series/Size
Text Length
E 2000
25.8 12.8 15.8 6.8 9 25.8 44.4
2 0 6
8.1 17.6 18.7 14.6 37 50.9
FILENAME: I-5843 Sign Designs
NORTH CAROLINA D.O.T. SIGN DETAIL


SIGN NUMBER: 114A, 115A, 116A
TYPE: B
QUANTITY: 3
SIGN WIDTH: 11'-0"
HEIGHT: 2'-6"
TOTAL AREA: 27.5 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 2"
RADIUS: 3"
NO. Z BARS: 2
LENGTH: 124.0

BACKG COLOR: Green
COPY COLOR: White
SYMBOL
X
Y
WID
HT
29.4
7.5
73.2
29.4

MAT'L: 0.125" (3.2 mm) ALUMINUM

USE NOTES:
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 S/B
Mar 09, 2016
DIV: 5



LETTER POSITIONS
Letter spacings are to start of next letter
Series/Size
Text Length
E 2000
29.4 9.2 11.1 3.8 7.5 71 31.6
1 9 1
75.9 7.5 14.7 4.5 29.4 26.7
FILENAME: I-5843 Sign Designs
NORTH CAROLINA D.O.T. SIGN DETAIL


SIGN NUMBER: 101A, 102A, 103A, 104A, 105A
TYPE: B
QUANTITY: 5
SIGN WIDTH: 11'-0"
HEIGHT: 2'-6"
TOTAL AREA: 27.5 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 2"
RADIUS: 3"
NO. Z BARS: 2
LENGTH: 124.0

BACKG COLOR: Green
COPY COLOR: White
SYMBOL
X
Y
WID
HT
21.7
31.6
88.5
21.75

MAT'L: 0.125" (3.2 mm) ALUMINUM

USE NOTES:
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B & S/B
Mar 09, 2016
DIV: 5



LETTER POSITIONS
Letter spacings are to start of next letter
Series/Size
Text Length
E 2000
21.7 9.2 11.1 3.8 7.5 78.6 31.6
2 0 2
68.3 14.7 15.1 12.2 21.7 42
FILENAME: I-5843 Sign Designs
NORTH CAROLINA D.O.T. SIGN DETAIL

TYPE "A" & "B" SIGNS

SIGN NUMBER:110A,111A,112A,113A
TYPE: B
QUANTITY: 4
SIGN WIDTH: 11'-0"
HEIGHT: 2'-6"
TOTAL AREA: 27.5 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 2"
RADII: 3"
NO. Z BARS: 2
LENGTH: 124.0

BACKG COLOR: Green
COPY COLOR: White
SYMBOL
X
Y
WID
HT
MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B & S/B
Mar 21, 2016
DIV: 5

11'-0"

2'-6"
10"
10"E
10"

7.5"
15"E
7.5"

21"90"21"

BORDER
R=3"
TH=2"

Spacing Factor is 1.2 for "EXIT"

LETTER POSITIONS
Letter spacings are to start of next letter
Series/Size
Text Length
E 2000
31.6
E 2000
43.5
NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER:106A,107A,108A,109A
TYPE: B
QUANTITY: 4
SIGN WIDTH: 11'-0"
HEIGHT: 2'-6"
TOTAL AREA: 27.5 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 2"
RADII: 3"
NO. Z BARS: 2
LENGTH: 124.0

BACKG COLOR: Green
COPY COLOR: White
SYMBOL
X
Y
WID
HT
MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B & S/B
Mar 09, 2016
DIV: 5

11'-0"

2'-6"
10"
10"E
10"

7.5"
15"E
7.5"

21.5"89"21.5"

BORDER
R=3"
TH=2"

Spacing Factor is 1.2 for "EXIT"

LETTER POSITIONS
Letter spacings are to start of next letter
Series/Size
Text Length
E 2000
31.6
E 2000
42.4
NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 117A,118A
TYPE: B
QUANTITY: 2
SIGN WIDTH: 11'-0"
HEIGHT: 2'-6"
TOTAL AREA: 27.5 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 2"
RADII: 3"
NO. Z BARS: 2
LENGTH: 124.0

BACKG COLOR: Green
COPY COLOR: White
SYMBOL
X
Y
WID
HT
MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B
Mar 21, 2016
DIV: 5

11'-0"

2'-6"
10"
10"E
10"

7.5"
15"E
7.5"

21.7"88.6"21.7"

BORDER
R=3"
TH=2"

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS
Letter spacings are to start of next letter
Series/Size
Text Length
E 2000
31.6
E 2000
42
NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 132
TYPE: B
QUANTITY: 1
SIGN WIDTH: 9'-0"
HEIGHT: 3'-0"
TOTAL AREA: 27.0 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 1"
RADII: 3"
NO. Z BARS: 2
LENGTH: 100.0

BACKG COLOR: Green
COPY COLOR: White
SYMBOL
X
Y
WID
HT
MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B
Mar 21, 2016
DIV: 5

9'-0"

3'-0"
7"
8"D
6"
8"D
7"

7"
8"D
6"
8"D
7"

8"92"8"

BORDER
R=3"
TH=1"

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS
Letter spacings are to start of next letter
Series/Size
Text Length
D 2000
49.4
D 2000
5.4
D 2000
49
D 2000
13.4
NORTH CAROLINA D.O.T. SIGN DETAIL

TIP NO. SHEET NO.
I-5843 SIGN-3G

APPROVED: [Signature]
DATE: 4/27/16
SEAL

SEAL
NORTH CAROLINA
PROFESSIONAL
ENGINEER
022959
RONALD W. KING

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

4/25/2016
I:\1-5843\1-5843 Sign Designs.dgn
RWR

TYPE "B" SIGNS

SIGN NUMBER: 133	BACKG COLOR: Green	DESIGN BY: A. Kidd	CHECKED BY: R. Roach
TYPE: B	COPY COLOR: White	PROJECT ID: I-5843	LOCATION: I-85 N/B
QUANTITY: 1			Mar 21, 2016 DIV: 5

SIGN WIDTH: 10'-6"
HEIGHT: 3'-0"

TOTAL AREA: 31.5 Sq.Ft.

BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 1"
RADIUS: 3"

NO. Z BARS: 2
LENGTH: 118.0

MAT'L: 0.125" (3.2 mm) ALUMINUM

USE NOTES:


- Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
- Background shall be Grade C reflective sheeting.

The diagram shows a rectangular sign with overall dimensions of 10'-6" wide by 3'-0" high. The sign features the text "Henderson Va State Line" in two lines. To the right of the text, the numbers "13" and "31" are displayed vertically. The sign has a 1" wide border. Dimensions for the text area are given as 8" D for the first line and 8" D for the second line. The total width of the sign is 110" and the total height is 36".

BORDER
R=3"
TH=1"


[illegible][illegible]

SIGN NUMBER: 136 TYPE: B QUANTITY: 1 SIGN WIDTH: 9'-0" HEIGHT: 3'-0" TOTAL AREA: 27.0 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 1" RADII: 3" NO. Z BARS: 2 LENGTH: 100.0	BACKG COLOR: Green COPY COLOR: White <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>SYMBOL</th> <th>X</th> <th>Y</th> <th>WID</th> <th>HT</th> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </table> MAT'L: 0.125" (3.2 mm) ALUMINUM	SYMBOL	X	Y	WID	HT																																														DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 S/B <div style="text-align: right;"> Mar 10, 2016 DIV: 5 </div> <div style="text-align: center;"> <p>Diagram showing a rectangular sign with overall dimensions of 9'-0" wide by 3'-0" high. The sign has a border of 8" on the left and right, and 7" on the top and bottom. The text "Durham" and "Burlington" are displayed in large, bold, sans-serif font. To the right of the text, the numbers "30" and "64" are displayed in a smaller font. The sign is mounted on a background with a spacing factor of 1 unless specified otherwise.</p> </div>																																																																																																						
SYMBOL	X	Y	WID	HT																																																																																																																																																						
USE NOTES: 1. Legend and border (except those that are colored black) shall be direct applied Grade C sheeting. 2. Background shall be Grade C reflective sheeting.																																																																																																																																																										
LETTER POSITIONS <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="15">Letter spacings are to start of next letter</th> <th>Series/Size Text Length</th> </tr> </thead> <tbody> <tr> <td></td><td>D</td><td>u</td><td>r</td><td>h</td><td>a</td><td>a</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>D 2000</td> </tr> <tr> <td>8</td><td>7</td><td>6.3</td><td>4</td><td>5.8</td><td>6.1</td><td>7.9</td><td>62.8</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>37.1</td> </tr> <tr> <td></td><td>3</td><td>0</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>D 2000</td> </tr> <tr> <td>87.3</td><td>7</td><td>5.7</td><td>8</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>12.7</td> </tr> <tr> <td></td><td>B</td><td>u</td><td>r</td><td>l</td><td>i</td><td>n</td><td>g</td><td>t</td><td>o</td><td>n</td><td></td><td></td><td></td><td></td><td></td><td>D 2000</td> </tr> <tr> <td>8</td><td>6.6</td><td>6.3</td><td>4</td><td>2.9</td><td>2.9</td><td>5.9</td><td>5.7</td><td>3.8</td><td>6.2</td><td>4.7</td><td>51.1</td><td></td><td></td><td></td><td></td><td>48.9</td> </tr> <tr> <td></td><td>6</td><td>4</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>D 2000</td> </tr> <tr> <td>87.6</td><td>6.4</td><td>6</td><td>8</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>12.4</td> </tr> </tbody> </table>			Letter spacings are to start of next letter															Series/Size Text Length		D	u	r	h	a	a										D 2000	8	7	6.3	4	5.8	6.1	7.9	62.8									37.1		3	0														D 2000	87.3	7	5.7	8													12.7		B	u	r	l	i	n	g	t	o	n						D 2000	8	6.6	6.3	4	2.9	2.9	5.9	5.7	3.8	6.2	4.7	51.1					48.9		6	4														D 2000	87.6	6.4	6	8													12.4
Letter spacings are to start of next letter															Series/Size Text Length																																																																																																																																											
	D	u	r	h	a	a										D 2000																																																																																																																																										
8	7	6.3	4	5.8	6.1	7.9	62.8									37.1																																																																																																																																										
	3	0														D 2000																																																																																																																																										
87.3	7	5.7	8													12.7																																																																																																																																										
	B	u	r	l	i	n	g	t	o	n						D 2000																																																																																																																																										
8	6.6	6.3	4	2.9	2.9	5.9	5.7	3.8	6.2	4.7	51.1					48.9																																																																																																																																										
	6	4														D 2000																																																																																																																																										
87.6	6.4	6	8													12.4																																																																																																																																										


TIP NO.	SHEET NO.
I-5843	SIGN-3H
APPROVED: <i>[Signature]</i> DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

TIP NO.
I-5843

SHEET NO.
SIGN-31

APPROVED: 

DATE: 4/27/16


SEAL


DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

SIGN NUMBER: 301
TYPE: D
QUANTITY: 1
SIGN WIDTH: 6'-0"
HEIGHT: 3'-6"
TOTAL AREA: 21.0 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 0.75"
RADII: 3"
NO. Z BARS:
LENGTH:

BACKG COLOR: Green
COPY COLOR: White
SYMBOL X Y WID HT
MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B
Mar 22, 2016
DIV: 5



USE NOTES: 1,2
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

LETTER POSITIONS
Letter spacings are to start of next letter

	W	E	L	C	O	M	E	T	O				
23.3	3.1	2.4	2.3	2.6	2.8	3.1	1.9	3	2.3	2.1	23.3		
	V	A	N	C	E		C	D					
15.5	4.9	6	5.4	5.4	3.7	6	5.3	4.3	15.5				
	L	E	A	V	I	N	G						
28	2.3	2.1	2.7	2.7	1.2	2.7	2	0.3	28				
	G	R	A	N	V	I	L	L	E		C	D	
7.4	5.4	4.6	6	5	5.5	2.4	4.6	4.6	3.7	6	5.3	4.3	7.3

Series/Size Text Length
D 2000 25.5
D 2000 41
D 2000 16.1
D 2000 57.3


Spacing Factor is 1 unless specified otherwise

FILENAME: I-5843 NB Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 302
TYPE: D
QUANTITY: 1
SIGN WIDTH: 8'-0"
HEIGHT: 3'-0"
TOTAL AREA: 24.0 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 1"
RADII: 3"
NO. Z BARS:
LENGTH:

BACKG COLOR: Green
COPY COLOR: White
SYMBOL X Y WID HT
MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B
Mar 23, 2016
DIV: 5



USE NOTES: 1,2
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

LETTER POSITIONS
Letter spacings are to start of next letter

	E	N	T	E	R	I	N	G							
33.8	3.8	3.9	3.7	3.8	4	1.8	4.2	3.2	33.8						
	T	a	r	-	P	a	m	i	c	o					
9	7.1	8.5	4	3	2.8	3	7.7	8.5	12	4.8	4.1	7	5.4	9	
	R	i	v	e	r		B	a	s	i	n				
11.2	8.6	3.9	7.8	7.8	4	8	8	7.6	7.8	4.8	5.3	11.2			

Series/Size Text Length
E 2000 28.4
EM 2000 77.9
EM 2000 73.5


Spacing Factor is 1 unless specified otherwise

FILENAME: I-5843 NB Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 303
TYPE: D
QUANTITY: 2
SIGN WIDTH: 6'-6"
HEIGHT: 3'-0"
TOTAL AREA: 19.5 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 1"
RADII: 3"
NO. Z BARS:
LENGTH:

BACKG COLOR: Green
COPY COLOR: White
SYMBOL X Y WID HT
MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B & S/B
Mar 23, 2016
DIV: 5



USE NOTES: 1,2
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

LETTER POSITIONS
Letter spacings are to start of next letter

	P	A	R	T		O	F		T	H	E				
18.2	3.6	4.8	3.7	3	4	4.3	3	4	3.7	4.3	3	0.3	18.2		
	T	a	r	-	P	a	m	i	c	o					
9	5.3	6.4	3	3	2.1	3	5.8	6.4	9	3.6	3.1	5.3	4.1	9	
	R	i	v	e	r		B	a	s	i	n				
11.4	6.5	2.9	5.8	5.8	3	6	6	5.7	5.8	3.6	4	11.4			

Series/Size Text Length
E 2000 41.6
EM 2000 59.9
EM 2000 55.1


Spacing Factor is 1 unless specified otherwise

FILENAME: I-5843 NB Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 304
TYPE: D
QUANTITY: 2
SIGN WIDTH: 6'-6"
HEIGHT: 1'-0"
TOTAL AREA: 6.5 Sq.Ft.
BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 1"
RADII: 3"
NO. Z BARS:
LENGTH:

BACKG COLOR: Green
COPY COLOR: White
SYMBOL X Y WID HT
MAT'L: 0.125" (3.2 mm) ALUMINUM

DESIGN BY: A. Kidd
PROJECT ID: I-5843
CHECKED BY: R. Roach
LOCATION: I-85 N/B & S/B
Mar 23, 2016
DIV: 5



USE NOTES: 1,2
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

LETTER POSITIONS
Letter spacings are to start of next letter

	T	a	r		R	i	v	e	r						
16.6	5.3	6.4	3	6	6.5	2.9	5.8	5.8	3	16.6					

Series/Size Text Length
EM 2000 44.8

Spacing Factor is 1 unless specified otherwise

FILENAME: I-5843 NB Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

TYPE "D" SIGNS

4/25/2016
U:\1-5843\1-5843 Sign Designs.dgn
User: rchrd

SIGN NUMBER: 305 TYPE: D QUANTITY: 1 SIGN WIDTH: 8'-0" HEIGHT: 3'-0" TOTAL AREA: 24.0 Sq.Ft. BORDER TYPE: FLUSH RECESS: 0" WIDTH: 1" RADIUS: 6" NO. 2 BARS LENGTH:	BACKG COLOR: Green COPY COLOR: White SYMBOL X Y WID HT MAT'L: 0.125" (3.2 mm) ALUMINUM	DESIGN BY: A. Kidd PROJECT ID: I-5843 CHECKED BY: R. Roach LOCATION: I-85 S/B Apr 11, 2016 DIV: 5
---	---	--

8'-0"

3'-0"

ENTERING
Neuse
River Basin

4"
4"
4"
4"
4"
4"
4"
4"

11.25"
73.5"
11.25"

BORDER
R=6"
TH=1"


USE NOTES: 1,2
1. Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
2. Background shall be Grade C reflective sheeting.

Spacing factor is 1 unless specified otherwise

LETTER POSITIONS												
Letter spacings are to start of next letter												
	E	N	T	E	R	I	N	G				
35.8	3.8	3.9	3.7	3.8	4	1.8	4.2	3.2	35.8			
	M	#	U	S	#							
29.9	8.5	7.8	7.8	7	5.3	28.9						
	R	I	V	E	R		B	A	S	I	N	
11.2	8.6	3.9	7.8	7.8	4	8	8	7.8	7.8	4.8	5.3	11.2

FILENAME: I-5843 08 Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

TIP NO. I-5843	SHEET NO. SIGN-3J
-------------------	----------------------


APPROVED: *R. Roach*
DATE: 4/27/16
SEAL

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

TYPE "D" SIGNS


4/26/2016
S:\S&D\Central\DIV 5 SIGN REQUEST\I-5843\NCADD\I-5843 SGN 4 Sign Details.dgn
User:rkidd

PROJECT NOTES


- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN




NAD 83/
NSRS 2007

TIP NO. I-5843	SHEET NO. SIGN-4
APPROVED: <i>RW77</i>	
DATE: <i>4/27/16</i>	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

SIGN DETAILS

TIP NO.	SHEET NO.
I-5843	SIGN-5
APPROVED:	<i>[Signature]</i>
DATE:	4/27/16
SEAL	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

NAD 83
NSRS 2007



PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN


SIGN DETAILS

4/26/2016
S:\S&G\Central\DIV 5 SIGN REQUEST\I-5843\CADD\I-5843 SGN 5 Sign Details.dgn
User:rkidd


4/26/2016
S:\S&B\Central\DIV 5 SIGN REQUEST\I-5843\CA00\I-5843 SGN 6 Sign Details.dgn
User:rkidd

PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN



NAD 83
NSRS 2007

TIP NO. I-5843	SHEET NO. SIGN-6
APPROVED: <i>R. King</i>	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

SIGN DETAILS


4/25/2016
S:\S&OU\Central\DIV 5 SIGN REQUEST\I-5843\ACADD\I-5843 SON 7 Sign Details.dgn
User: rakiidol

PROJECT NOTES



- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN




NAD 83
NSRS 2007

TIP NO. I-5843	SHEET NO. SIGN-7
APPROVED: <i>RW</i>	
DATE: 4/27/16	
SEAL 	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

SIGN DETAILS

TIP NO.	SHEET NO.
I-5843	SIGN-8
APPROVED: 	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	


NAD 83
NSRS 2007



PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN

SIGN DETAILS

TIP NO.	SHEET NO.
I-5843	SIGN-9
APPROVED: <i>[Signature]</i>	
DATE: 4/27/10	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	


NAD 83/
NSRS 2007



PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN

SIGN DETAILS

TIP NO.	SHEET NO.
I-5843	SIGN-10
APPROVED: <i>R. King</i>	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	


NAD 83/
NSRS 2007




PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN

SIGN DETAILS

TIP NO.	SHEET NO.
I-5843	SIGN-11
APPROVED: <i>RW</i>	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	


NAD 83
NSRS 2007



PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN

SIGN DETAILS

TIP NO.	SHEET NO.
I-5843	SIGN-12
APPROVED: <i>RWW</i>	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	


NAD 83
NSRS 2007




PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN

SIGN DETAILS

TIP NO.	SHEET NO.
I-5843	SIGN-13
APPROVED: <i>RW</i>	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

NAD 83
NSRS 2007



PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN

SIGN DETAILS


APPROVED:

DATE:

SEAL




**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**




PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
4 DISPOSAL OF SIGN, D
5 INSTALL 20 FT BEHIND EXISTING SIGN
6 INSTALL 10 FT BEHIND EXISTING SIGN
7 INSTALL 100 FT IN FRONT OF EXISTING SIGN

SIGN DETAILS

TIP NO.	SHEET NO.
I-5843	SIGN-15
APPROVED: <i>RK1W47</i>	
DATE: <i>4/27/16</i>	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	


NAD 83/
NSRS 2007



PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN

SIGN DETAILS

TIP NO.	SHEET NO.
I-5843	SIGN-16
APPROVED: <i>RW</i>	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

NAD 83
NSRS 2007



PROJECT NOTES


- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN

SIGN DETAILS


4/26/2016
S:\S&D\Centra\DIV 5 SIGN REQUEST\I-5843\CA000\I-5843 SGN I7 Sign Details.dgn
User:skiddl

PROJECT NOTES


- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN




NAD 83/
NSRS 2007

TIP NO. I-5843	SHEET NO. SIGN-17
APPROVED: <i>RW</i>	
DATE: <i>4/27/16</i>	
SEAL 	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

SIGN DETAILS

TIP NO.	SHEET NO.
I-5843	SIGN-18
APPROVED: <i>R.W.K.</i>	
DATE: 4/27/16	
SEAL	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	




PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN, A OR B (GROUND MOUNTED)
- 4 DISPOSAL OF SIGN, D
- 5 INSTALL 20 FT BEHIND EXISTING SIGN
- 6 INSTALL 10 FT BEHIND EXISTING SIGN
- 7 INSTALL 100 FT IN FRONT OF EXISTING SIGN

SIGN DETAILS

PROJECT: I-5843


CONTRACT NO.:




STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS
GRANVILLE COUNTY

LOCATION: BRIDGE #35 ON US 158 OVER I-85.
BRIDGE #44 ON NC 96 OVER I-85.
BRIDGE #50 ON SR 1127 OVER I-85.
BRIDGE #51 ON I-85 NBL OVER SR 1132.
BRIDGE #52 ON I-85 SBL OVER SR 1132.
BRIDGE #54 ON SR 1135 OVER I-85.
BRIDGE #55 ON I-85 NBL OVER TAR RIVER.
BRIDGE #56 ON I-85 SBL OVER TAR RIVER.
BRIDGE #57 ON SR 1192 OVER I-85.
BRIDGE #60 ON I-85 NBL OVER US 15.
BRIDGE #61 ON I-85 SBL OVER US 15.

BRIDGE PRESERVATION – SUBSTRUCTURE REPAIR, CLEANING AND PAINTING EXISTING BEARINGS,
INSTALLATION OF BEARING KEEPER ANGLES, JOINT HEADER REPAIRS, STRUCTURAL
STEEL REPAIRS, PAINTING STRUCTURAL STEEL, AND REPLACEMENT OF JOINT SEALS.



VICINITY MAP – GRANVILLE CO.



VICINITY MAP – GRANVILLE CO.

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	I-5843	1	45
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
53049.1.1	NHPP-0085(16)	PE	
53049.3.1		CONST	



DESIGN DATA	
#35 ADT 2012	= 7,900
#44 ADT 2012	= 9,900
#50 ADT 2012	= 1,100
#51 ADT 2012	= 14,000
#52 ADT 2012	= 14,000
#54 ADT 2012	= 720
#55 ADT 2012	= 14,000
#56 ADT 2012	= 14,000
#57 ADT 2012	= 680
#60 ADT 2012	= 14,000
#61 ADT 2012	= 14,000


PROJECT LENGTH	
BRIDGE #35	= 0.071 MILE
BRIDGE #44	= 0.050 MILE
BRIDGE #50	= 0.053 MILE
BRIDGE #51	= 0.026 MILE
BRIDGE #52	= 0.026 MILE
BRIDGE #54	= 0.068 MILE
BRIDGE #55	= 0.052 MILE
BRIDGE #56	= 0.052 MILE
BRIDGE #57	= 0.057 MILE
BRIDGE #60	= 0.069 MILE
BRIDGE #61	= 0.069 MILE

Prepared in the Office of:
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
STRUCTURES MANAGEMENT UNIT
1000 BIRCH RIDGE DR. RALEIGH, N.C. 27610

ERIC B. NELSON, P.E.
PROJECT ENGINEER


2012 STANDARD SPECIFICATIONS

LETTING DATE:
OCTOBER, 2016



TIMOTHY M. SHERRILL, P.E.
PROJECT DESIGN ENGINEER
9/12/2016

NOTES
FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.
FOR REPLACEMENT OF FOAM JOINT SEALS, SEE SPECIAL PROVISIONS.
FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.
FOR CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA, SEE SPECIAL PROVISIONS.



PLAN OF SPANS

(DIMENSIONS TYPICAL FOR BOTH BRIDGES)

TOTAL BILL OF MATERIAL

	EPOXY RESIN INJECTION	REPLACEMENT OF FOAM JOINT SEALS	EPOXY COATING	CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA BRIDGE NO. _	PAINTING CONTAINMENT FOR BRIDGE NO. _
	LF	LF	SF	EACH	LUMP SUM
380051	12	84	0	36	LUMP SUM
380052	0	84	85	36	LUMP SUM

CONSTRUCTION SEQUENCE:

- 1) - EPOXY INJECTION - 12' LONG CRACK IN APPROACH SLAB AT END BENT 1
- 2) - CLEAN AND PAINT EXISTING BEARINGS WITH HRCSA
- 3) - FOAM JOINT SEAL REPLACEMENT *
- 4) - EPOXY COATING OF END BENT CAPS **

DocuSign
T. M. SHERRILL
AD5081597748565C
ENGINEER
MOTIY M. SHERRILL
9/12/2016

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO.: 51 & 52

REVISIONS						SHEET NO. S-1
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			TOTAL SHEETS 42
2			4			

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

* QUANTITY INDICATED REPRESENTS ANTICIPATED REPLACEMENT OF TWO FOAM JOINT SEALS. ACTUAL QUANTITY SHALL BE FIELD VERIFIED BY CONTRACTOR AND ENGINEER.
** QUANTITY INDICATED REPRESENTS ANTICIPATED EPOXY COATING OF BRIDGE 52 END BENT 2 CAP. ACTUAL QUANTITY SHALL BE FIELD VERIFIED BY CONTRACTOR AND ENGINEER.





DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

NOTES

FOR REPLACEMENT OF FOAM JOINT SEALS, SEE SPECIAL PROVISIONS.

THE INSTALLED FOAM JOINT SEALS SHALL BE WATERTIGHT.

NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 2" AT BENTS AND 3 1/2" AT END BENTS FOR BRIDGE NO. 51 AND 4" AT END BENTS FOR BRIDGE NO. 52.




PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 51 & 52

DocuSign
T. M. SHERRILL
AD5081597748565C
ENGINEER
MOTRY M. SHERRILL
9/12/2016

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH						SHEET NO. S-2	
JOINT DETAILS						TOTAL SHEETS 42	
REVISIONS							
NO.	BY:	DATE:	NO.	BY:	DATE:		
1			3				
2			4				

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



PLAN OF SPANS
(DIMENSIONS TYP. FOR BOTH BRIDGES)

CONSTRUCTION SEQUENCE:

- 1) - CLEAN AND PAINT EXISTING BEARINGS WITH HRCSA
- 2) - ELASTOMERIC JOINT HEADER REPAIRS **
- 3) - FOAM JOINT SEAL REPLACEMENT *
- 4) - EPOXY COATING OF END BENT CAPS ***

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO.: 55 & 56

TOTAL BILL OF MATERIAL					
BRIDGE	REPLACEMENT OF FOAM JOINT SEALS	EPOXY COATING	CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA BRIDGE NO. _	ELASTOMERIC JOINT HEADER REPAIRS	PAINTING CONTAINMENT FOR BRIDGE NO. _
	LF	SF	EACH	SQ.FT.	LUMP SUM
380055	84	128	60	4	LUMP SUM
380056	84	64	60	0	LUMP SUM

NOTES:
FOR REPLACEMENT OF FOAM JOINT SEALS, SEE SPECIAL PROVISIONS.
FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.
FOR CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA, SEE SPECIAL PROVISIONS.
FOR ELASTOMETIC JOINT HEADER REPAIRS, SEE SPECIAL PROVISIONS.

ACCESS FOR REPAIRS TO ALL BRIDGE ELEMENTS OF BRIDGES 55 & 56 MUST BE STAGED FROM THE BRIDGE SUPERSTRUCTURE AND NOT FROM THE GROUND OR WATERWAY.

JURISDICTIONAL RESOURCES (WETLAND, STREAM AND REGULATED RIPARIAN BUFFER) ARE PRESENT AT BRIDGE 55 & 56. IMPACT TO THESE RESOURCES ARE NOT ALLOWED FROM ANY ACTIVITY ASSOCIATED WITH WORK AT THESE BRIDGES.

NO DISCHARGE OF WATER, CONCRETE DEBRIS, SLURRY, OR ANY REPAIR MATERIAL IS ALLOWED TO ENTER THE WATERCOARSE. THE CONTRACTOR SHALL COLLECT, CONTAIN AND REMOVE ALL DEBRIS RESULTING FROM REPAIR ACTIVITIES. A DETAILED PLAN FOR COLLECTION, CONTAINMENT AND DISPOSAL OF DEBRIS AS WELL AS STAGING THE EQUIPMENT, INCLUDING DRAWINGS, AND NARRATIVES MUST BE PROVIDED TO AND APPROVED BY THE ASSISTANT STATE STRUCTURES MANAGEMENT ENGINEER- OPERATIONS AND THE NCDOT DIVISION 5 ENVIRONMENTAL SUPERVISOR. THE SUBMITTAL SHALL BE MADE AT LEAST 30 DAYS PRIOR TO OCCURRENCE OF ANY ACTIVITY AT BRIDGES 55 & 56.





* QUANTITY INDICATED REPRESENTS ANTICIPATED REPLACEMENT OF FOAM JOINT SEALS. ACTUAL QUANTITY SHALL BE FIELD VERIFIED BY CONTRACTOR AND ENGINEER.
** QUANTITY INDICATED REPRESENTS ANTICIPATED REPAIRS OF JOINT HEADER. ACTUAL QUANTITY SHALL BE FIELD VERIFIED BY CONTRACTOR AND ENGINEER.
*** QUANTITY INDICATED REPRESENTS ANTICIPATED EPOXY COATING OF BRIDGE 55 END BENT 1 AND 2 CAPS AND BRIDGE 56 END BENT 1 CAP. ACTUAL QUANTITY SHALL BE FIELD VERIFIED BY CONTRACTOR AND ENGINEER.

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

DocuSign
NORTH CAROLINA
STATE ENGINEER
MOTONY M. SHERRILL
9/12/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
PLAN VIEW OF BRIDGE 55 & 56 ON I-85 OVER TAR RIVER					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
SHEET NO. S-3					TOTAL SHEETS 42



NOTES


FOR REPLACEMENT OF FOAM JOINT SEALS, SEE SPECIAL PROVISIONS.

THE INSTALLED FOAM JOINT SEALS SHALL BE WATERTIGHT.

NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 3" AT BENT 1 AND 2" AT BENT 2, 3, AND 4.

NOMINAL UNCOMPRESSED SEAL WIDTH OF FOAM JOINT SEAL SHALL BE 3 1/2" AT END BENTS FOR BRIDGE NO. 55 AND 4" AT END BENTS FOR BRIDGE NO. 56.

PROJECT NO. I-5843
GRANVILLE COUNTY
 BRIDGE NO. 55 & 56




9/12/2016

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH						SHEET NO. S-4	
JOINT DETAILS						TOTAL SHEETS 42	
REVISIONS							
NO.	BY:	DATE:	NO.	BY:	DATE:		
1			3				
2			4				

DRAWN BY : M.A.LEE DATE : 8/2016
 CHECKED BY : T.M.SHERILL DATE : 8/2016

09-SEP-2016 14:31
 R:\Structures\I-5843 Final\I-5843 FINAL.dgn
 malee7

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED



PLAN OF SPANS
(DIMENSIONS TYPICAL FOR BOTH BRIDGES)

NOTES:
FOR CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA, SEE SPECIAL PROVISIONS.
FOR BEAM REPAIR, SEE SPECIAL PROVISIONS.
BEAM REPAIRS SHALL BE COMPLETED BEFORE FINAL CLEANING AND PAINTING OF STRUCTUAL STEEL.

CONSTRUCTION SEQUENCE:
1) - CLEAN AND PAINT STRUCTURAL STEEL
2) - CLEAN AND PAINT EXISTING BEARINGS WITH HRCSA
3) - REPAIR STEEL BEAM ENDS, STIFFENERS

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO.: 60 & 61


TOTAL BILL OF MATERIAL					
BRIDGE	CLEANING & PAINTING OF BRIDGE NO..	PAINTING CONTAINMENT FOR BRIDGE NO..	POLLUTION CONTROL	BEAM REPAIR	CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA BRIDGE NO. .
	LUMP SUM	LUMP SUM	LUMP SUM	LBS	EACH
380060	LUMP SUM	LUMP SUM	LUMP SUM	328	48
380061	LUMP SUM	LUMP SUM	LUMP SUM	5	48

DocuSigned by
T. M. Sherrill
AD50E1D87748565...
NORTH CAROLINA
ENGINEER
MOTHSY M. SHERRILL
9/12/2016

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
PLAN VIEW OF BRIDGE 60 & 61 ON I-85 OVER US HWY 15					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
SHEET NO. S-5					TOTAL SHEETS 42

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016


DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



FRAMING PLANS

- KEY**
- ① BEAM NUMBER
 - Ⓟ PLATE REPAIR
 - Ⓢ STIFFENER REPAIR

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO.: 60 & 61



9/12/2016

DRAWN BY : D.V. JOYNER DATE : 8/2016
CHECKED BY : T.M. SHERRILL DATE : 8/2016

09-SEP-2016 14:33
R:\Structures\I-5843 Final\I-5843 FINAL.dgn
malee7

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-6
2			4			TOTAL SHEETS 42


NOTE
FOR REPAIR DETAILS, SEE "BEAM PLATING REPAIR DETAILS" SHEET.
FOR BEAM REPAIR, SEE SPECIAL PROVISIONS.

ANTICIPATED BEAM REPAIR LOCATIONS					
BRIDGE 380060					
SPAN	BEAM	LOCATION	DIM. "A"	DIM. "B"	COMMENTS
D	2	END BENT 2	7"	5"	STIFFENER \varnothing REPAIR
D	2	END BENT 2	7"	5"	STIFFENER \varnothing REPAIR
D	3	5'-6" FROM END BENT 2	6"	9'-0"	INTERMEDIATE PLATING REPAIR - WEB PLATE = $\frac{5}{16}$ "; FLANGE PLATE $\frac{5}{8}$ "

ANTICIPATED BEAM REPAIR LOCATIONS					
BRIDGE 380061					
SPAN	BEAM	LOCATION	DIM. "A"	DIM. "B"	COMMENTS
D	1	6' FROM END BENT 2	7"	6"	STIFFENER \varnothing REPAIR

BILL OF MATERIAL
BEAM REPAIR
333 LBS.


PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 60 & 61



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
BEAM END AND INTERMEDIATE REPAIR LOCATIONS					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					TOTAL SHEETS 42

DRAWN BY :	P.C. BREWER	DATE :	8-16
CHECKED BY :	T.M. SHERRILL	DATE :	8-16

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



PLAN

CONSTRUCTION SEQUENCE:

- 1) - SUBSTRUCTURE REPAIRS & EPOXY RESIN INJECTION
- 2) - REPAIR STEEL BEAM ENDS, STIFFENERS
- 3) - CLEAN AND PAINT STRUCTURAL STEEL
- 4) - CLEAN AND PAINT EXISTING BEARINGS WITH HRCSA
- 5) - INSTALL STEEL KEEPER ANGLE ASSEMBLY
- 6) - EPOXY COATING OF BENT CAPS


PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 35

NOTES:

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.
FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.
FOR CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA, SEE SPECIAL PROVISIONS.
FOR SHOTCRETE REPAIR, SEE SPECIAL PROVISIONS.
FOR BEAM REPAIR, SEE SPECIAL PROVISIONS.
FOR STEEL KEEPER ANGLE ASSEMBLY, SEE SPECIAL PROVISIONS.

TOTAL BILL OF MATERIAL

BRIDGE	SHOTCRETE REPAIR	EPOXY RESIN INJECTION	CLEANING & REPAINTING OF BRIDGE NO. 35	PAINTING CONTAINMENT FOR BRIDGE NO. 35	POLLUTION CONTROL	BEAM REPAIR	EPOXY COATING	STEEL KEEPER ANGLE ASSEMBLY	CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA BRIDGE NO. 35
	CF	LF	LUMP SUM	LUMP SUM	LUMP SUM	LBS	SF	EACH	EACH
380035	97	173	LUMP SUM	LUMP SUM	LUMP SUM	1,575	1,131	6	72




9/12/2016

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
PLAN VIEW OF BRIDGE 35 ON US 158 OVER I-85					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
TOTAL SHEETS					42

DRAWN BY : S. T. SANDOR/M. WELDON DATE : 08/2016
CHECKED BY : T. SHERRILL DATE : 08/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



FIX.

EXP. EXP.

FIX.

EXP. EXP.

FIX.

SPAN A

SPAN B

SPAN C

SPAN D

FRAMING PLAN


- KEY**
- ① BEAM NUMBER
 - ② PLATE REPAIR
 - ③ STIFFENER REPAIR
 - ④ STEEL KEEP ANGLE ASSEMBLY
 - ⑤ SHOTCRETE REPAIR ON UNDERSIDE OF DECK OVERHANG

NOTES:

SHOTCRETE REPAIRS ARE REQUIRED ON UNDERSIDE OF DECK AT LOCATIONS INDICATED. SEE SUBSTRUCTURE PLAN SHEETS FOR MORE INFORMATION ON LOCATION AND SIZE OF SHOTCRETE AREAS AND DETAILED INFORMATION FOR SHOTCRETE REPAIRS.

BEARINGS SHALL BE CLEANED AND BLASTED AS PART OF CLEANING AND BLASTING FOR STRUCTURAL STEEL BUT BEARINGS SHALL NOT BE PRIMED AND PAINTED WITH THE STRUCTURAL STEEL PAINT SYSTEM. AFTER BLASTING, BEARINGS SHALL BE PREPARED AND PAINTED AS REQUIRED BY THE HRCSA PAINT SYSTEM.

PROJECT NO. I-5843
GRANVILLE COUNTY
 BRIDGE NO.: 35



9/12/2016

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-9
2			4			TOTAL SHEETS
						42

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

DRAWN BY : D.V. JOYNER DATE : 7/2016
 CHECKED BY : W. SMITH DATE : 7/2016

NOTE
FOR REPAIR DETAILS, SEE "BEAM PLATING REPAIR DETAILS" SHEET.
FOR BEAM REPAIR, SEE SPECIAL PROVISIONS.

ANTICIPATED BEAM REPAIR LOCATIONS					
SPAN	BEAM	LOCATION	DIM. "A"	DIM. "B"	COMMENTS
A	1	BENT 1	10"	2'-0"	HAUNCH - WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{5}{16}"$
A	1	BENT 1	5"	6"	STIFFENER ℓ REPAIR
A	3	BENT 1	3"	2'-0"	HAUNCH - WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{5}{16}"$
A	4	BENT 1	4"	2'-0"	HAUNCH - WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{3}{8}"$
A	5	BENT 1	5"	2'-0"	HAUNCH - WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{5}{16}"$
A	6 STIFF.	BENT 1	5"	6"	STIFFENER ℓ REPAIR
A	7	BENT 1	4"	2'-0"	HAUNCH - WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{1}{2}"$
B	1	BENT 1	3"	1'-0"	GRIND SMOOTH "TEMPORARY" REPAIR WELD; $\frac{1}{4}" \ell$ EACH SIDE OF "RAT HOLE" IN WEB
B	1	8' FROM BENT 1	4"	12'-0"	INTERMEDIATE PLATING REPAIR - WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{1}{4}"$
B	2	BENT 1	4"	6'-0"	WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{1}{4}"$
B	3	BENT 1	4"	6'-0"	WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{1}{4}"$
B	4	BENT 1	5"	4'-0"	WEB $\ell = \frac{7}{16}"$; FLANGE $\ell = \frac{1}{4}"$
B	6	BENT 1	8"	7'-0"	WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{1}{4}"$
B	6 STIFF.	BENT 1	5"	6"	STIFFENER ℓ REPAIR
B	7 STIFF.	3' FROM BENT 1	4"	6"	STIFFENER ℓ REPAIR
B	8 STIFF.	3' FROM BENT 1	4"	6"	STIFFENER ℓ REPAIR
B	9	BENT 1	5"	11'-0"	WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{1}{4}"$
B	9 STIFF.	BENT 1	5"	6"	STIFFENER ℓ REPAIR
C	1	BENT 3	7"	6'-0"	WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{1}{4}"$
C	1 STIFF.	4' FROM BENT 3	5"	6"	STIFFENER ℓ REPAIR
C	3	BENT 3	7"	5'-0"	WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{1}{4}"$
C	6	BENT 3	4"	3'-0"	WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{1}{4}"$
C	7	BENT 3	3"	3'-0"	WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{1}{4}"$
D	1	BENT 3	1'-9"	2'-0"	HAUNCH - WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{5}{16}"$
D	8	BENT 3	3"	2'-0"	HAUNCH - WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{5}{16}"$
D	9	BENT 3	9"	2'-0"	HAUNCH - WEB $\ell = \frac{1}{4}"$; FLANGE $\ell = \frac{5}{16}"$

BILL OF MATERIAL
BEAM REPAIR
1,575 LBS.

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 35



9/12/2016

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
BEAM END AND INTERMEDIATE REPAIR LOCATIONS					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
TOTAL SHEETS					42


DRAWN BY :	P.C. BREWER	DATE :	7-16
CHECKED BY :	T.M. SHERRILL	DATE :	7-16

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

NOTE
FOR STEEL KEEPER ANGLE ASSEMBLY DETAILS, SEE "STEEL KEEPER ANGLE ASSEMBLY DETAILS" SHEET.
FOR STEEL KEEPER ANGLE ASSEMBLY, SEE SPECIAL PROVISIONS.

ANTICIPATED STEEL KEEPER ANGLE ASSEMBLY LOCATIONS		
SPAN	BEAM	LOCATION
C	1	BENT 3
C	2	BENT 3
C	3	BENT 3
C	5	BENT 3
C	7	BENT 3
C	9	BENT 3


PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 35




STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
STEEL KEEPER ANGLE ASSEMBLY REPAIR LOCATIONS					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
TOTAL SHEETS					42

DRAWN BY :	M.A.LEE	DATE :	9-16
CHECKED BY :	T.M. SHERRILL	DATE :	9-16


DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED




PLAN
END BENT 1



ELEVATION
END BENT 1



PLAN
END BENT 2



ELEVATION
END BENT 2

REPAIR QUANTITY TABLE

END BENT 1		QUANTITIES			
		ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS		AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)		0.0	0.0		
CAP (HORIZONTAL, CORNER)		0.0	0.0		
CONCRETE REPAIR		0.0	0.0		
EPOXY RESIN INJECTION			LN. FT		LN. FT
CAP			38.0		
EPOXY COATING		AREA SF			
CAP		174.0			
END BENT 2		QUANTITIES			
		ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS		AREA SF	VOLUME CF	AREA SF	
CAP (VERTICAL FACE)		0.0	0.0		
CAP (HORIZONTAL, CORNER)		0.0	0.0		
CONCRETE REPAIR		0.0	0.0		
EPOXY RESIN INJECTION			LN. FT		LN. FT
CAP			60.0		
EPOXY COATING		AREA SF			
CAP		174.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN, AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE AREA OF THE ORIGINAL CAP ONLY.

- SHOTCRETE REPAIRS
- ERI

EPOXY RESIN INJECTION


PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 35

DocuSigned by
Tina M. Sherrill
AD50E1D87740566...
9/12/2016


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
SUBSTRUCTURE
END BENT 1 & 2

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-12
2			4			TOTAL SHEETS 42



PLAN OF CAP
TOP




END VIEW
NORTH SIDE

ELEVATION
WEST SIDE



PLAN OF CAP
BOTTOM



END VIEW
SOUTH SIDE

ELEVATION
EAST SIDE

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE

BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	33.31	15.27		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	0.0	0.0		
UNDERDECK - SPAN 2, RIGHT OVERHANG, 3 FEET FROM BENT 1	4.0	1.83		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		5.0		
COLUMN		55.0		
EPOXY COATING	AREA SF			
CAP	261.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.

SHOTCRETE REPAIR

ERI EPOXY RESIN INJECTION

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 35



9/12/2016


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-13
2			4			TOTAL SHEETS 42

DRAWN BY : M.A.LEE DATE : 08/2016
CHECKED BY : T.M.SHERRILL DATE : 08/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



PLAN OF CAP
TOP




END VIEW
NORTH SIDE

ELEVATION
WEST SIDE



PLAN OF CAP
BOTTOM



END VIEW
SOUTH SIDE

ELEVATION
EAST SIDE

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE

BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	0.5	0.23		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0.0		
COLUMN		7.0		
EPOXY COATING	AREA SF			
CAP	261.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.

SHOTCRETE REPAIR

ERI EPOXY RESIN INJECTION

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 35



9/12/2016


STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE BENT 2					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
SHEET NO. S-14					TOTAL SHEETS 42

DRAWN BY : M.A.LEE DATE : 08/2016
CHECKED BY : T.M.SHERRILL DATE : 08/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



PLAN OF CAP
TOP




END VIEW
NORTH SIDE

ELEVATION
WEST SIDE



PLAN OF CAP
BOTTOM



END VIEW
SOUTH SIDE

ELEVATION
EAST SIDE

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP AND COLUMN REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

NO REPAIR NOTED DURING INSPECTION BY STRUCTURES MANAGEMENT UNIT. THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE

BENT 3	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.75	0.34		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	164.0	75.16		
UNDERDECK - SPAN 4, LEFT OVERHANG, 6 FEET FROM BENT 3	8.0	3.67		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		4.0		
COLUMN		4.0		
EPOXY COATING	AREA SF			
CAP	261.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.

SHOTCRETE REPAIR
ERI EPOXY RESIN INJECTION

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 35




9/12/2016

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

09-SEP-2016 14:42
R:\Structures\I-5843 Final\I-5843 FINAL.dgn
malee7

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-15
2			4			TOTAL SHEETS 42



PLAN

NOTES

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

FOR CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA, SEE SPECIAL PROVISIONS.

FOR SHOTCRETE REPAIR, SEE SPECIAL PROVISIONS.

FOR BEAM REPAIR, SEE SPECIAL PROVISIONS.

CONSTRUCTION SEQUENCE:


- 1) - SUBSTRUCTURE REPAIRS & EPOXY RESIN INJECTION
- 2) - REPAIR STEEL BEAM ENDS, STIFFENERS
- 3) - CLEAN AND PAINT STRUCTURAL STEEL
- 4) - CLEAN AND PAINT EXISTING BEARINGS WITH HRCSA
- 5) - EPOXY COATING OF BENT CAPS

PROJECT NO. I-5843

GRANVILLE COUNTY


BRIDGE NO. 44

TOTAL BILL OF MATERIAL								
BRIDGE	SHOTCRETE REPAIR	EPOXY RESIN INJECTION	CLEANING & REPAINTING OF BRIDGE NO. 44	PAINTING CONTAINMENT FOR BRIDGE NO. 44	POLLUTION CONTROL	BEAM REPAIR	EPOXY COATING	CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA BRIDGE NO. 44
	CF	LF	LUMP SUM	LUMP SUM	LUMP SUM	LBS	SF	EACH
380044	72	69	LUMP SUM	LUMP SUM	LUMP SUM	2,369	831	88



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
PLAN VIEW OF BRIDGE 44 ON NC 96 OVER I-85					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED					TOTAL SHEETS 42

DRAWN BY : S. T. SANDOR/M. WELDON DATE : 08/2016
CHECKED BY : T. SHERRILL DATE : 08/2016




FRAMING PLAN

NOTE:

BEARINGS SHALL BE CLEANED AND BLASTED AS PART OF CLEANING AND BLASTING FOR STRUCTURAL STEEL, BUT BEARINGS SHALL NOT BE PRIMED AND PAINTED WITH THE STRUCTURAL STEEL PAINT SYSTEM. AFTER BLASTING, BEARINGS SHALL BE PREPARED AND PAINTED AS REQUIRED BY THE HRCSA PAINT SYSTEM.

PROJECT NO. I-5843
GRANVILLE COUNTY
 BRIDGE NO.: 44



9/12/2016

DRAWN BY : D.V. JOYNER DATE : 7/2016
 CHECKED BY : W. SMITH DATE : 7/2016

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-17
2			4			TOTAL SHEETS 42

NOTE
FOR REPAIR DETAILS, SEE "BEAM PLATING REPAIR DETAILS" SHEET.
FOR BEAM REPAIR, SEE SPECIAL PROVISIONS.

ANTICIPATED BEAM REPAIR LOCATIONS					
SPAN	BEAM	LOCATION	DIM. ``A``	DIM. ``B``	COMMENTS
A	2	BENT 1	1'-0"	5'-0"	WEB $\ell = 1/4"$; NO FLANGE ℓ
A	6 STIFF.	BENT 1	5"	6"	STIFFENER ℓ REPAIR
A	6	BENT 1	8"	3'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 1/4"$
A	8	BENT 1	6"	3'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 1/4"$
A	10	BENT 1	7"	3'-0"	WEB $\ell = 5/16"$; FLANGE $\ell = 1/4"$
A	10 STIFF.	BENT 1	5"	6"	STIFFENER ℓ REPAIR
B	2	BENT 1	6"	8'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 1/4"$
B	5	BENT 1	3"	3'-0"	NO WEB ℓ ; FLANGE $\ell = 1/4"$
B	6	BENT 1	21"	3'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 1/4"$
B	7	BENT 1	11"	1'-0"	NO WEB ℓ ; FLANGE $\ell = 1/4"$
C	4	BENT 3	1'-1"	3'-0"	NO WEB ℓ ; FLANGE $\ell = 1/4"$
C	5	BENT 3	5"	4'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 1/4"$
C	5 STIFF.	BENT 3	4"	6"	STIFFENER ℓ REPAIR
C	5 STIFF.	BENT 3	4"	6"	STIFFENER ℓ REPAIR
C	6	BENT 3	1'-1"	3'-0"	WEB $\ell = 5/16"$; FLANGE $\ell = 5/16"$
C	7	BENT 3	8"	5'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 3/8"$
C	7 STIFF.	BENT 3	5"	6"	STIFFENER ℓ REPAIR
C	10	BENT 3	4"	5'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 3/8"$
C	10 STIFF.	BENT 3	5"	6"	STIFFENER ℓ REPAIR
D	1	BENT 3	5"	3'-0"	WEB $\ell = 1/4"$; NO FLANGE ℓ
D	2	BENT 3	5"	4'-0"	WEB $\ell = 5/16"$; FLANGE $\ell = 3/8"$
D	3	BENT 3	6"	4'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 3/8"$
D	4	BENT 3	6"	4'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 1/4"$
D	5	BENT 3	8"	5'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 3/8"$
D	5 STIFF.	BENT 3	5"	6"	STIFFENER ℓ REPAIR
D	7	BENT 3	6"	1'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 3/8"$
D	8	BENT 3	2'-0"	7'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 3/8"$
D	8 STIFF.	BENT 3	5"	6"	STIFFENER ℓ REPAIR
D	10	BENT 3	2'-0"	8'-0"	WEB $\ell = 1/4"$; FLANGE $\ell = 7/16"$
D	10 STIFF.	BENT 3	6"	6"	STIFFENER ℓ REPAIR

BILL OF MATERIAL
BEAM REPAIR
2,369


PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 44



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
BEAM END AND INTERMEDIATE REPAIR LOCATIONS					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
TOTAL SHEETS					42

DRAWN BY :	P.C. BREWER	DATE :	8-16
CHECKED BY :	T.M. SHERRILL	DATE :	8-16

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



DRAWN BY : M.ALEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

09-SEP-2016 14:45
R:\Structures\I-5843 Final\I-5843 FINAL.dgn
malee7

REPAIR QUANTITY TABLE				
END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL, CORNER)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		12.5		
EPOXY COATING	AREA SF			
CAP	132.0			
END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	
CAP (VERTICAL FACE)	20.0	9.17		
CAP (HORIZONTAL, CORNER)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		56.5		
EPOXY COATING	AREA SF			
CAP	132.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE AREA OF THE ORIGINAL CAP ONLY.

☒ SHOTCRETE REPAIR
ERI EPOXY RESIN INJECTION

PROJECT NO. I-5483
GRANVILLE COUNTY
BRIDGE NO. 44



9/12/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED


STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE END BENT 1 & 2					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
SHEET NO.					TOTAL SHEETS
S-19					42




PLAN OF CAP
TOP



END VIEW
WEST SIDE



ELEVATION
SOUTH SIDE



PLAN OF CAP
BOTTOM

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.


THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.



END VIEW
EAST SIDE



ELEVATION
NORTH SIDE

SHOTCRETE REPAIR
ERI EPOXY RESIN INJECTION

REPAIR QUANTITY TABLE

BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	21.0	9.63		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0.0		
COLUMN		0.0		
EPOXY COATING	AREA SF			
CAP	189.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 44




STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE BENT 1					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED					TOTAL SHEETS 42




PLAN OF CAP
TOP

NO REPAIRS NOTED DURING INSPECTION BY STRUCTURES
MANAGEMENT UNIT. THE CONTRACTOR AND ENGINEER
SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.




END VIEW
WEST SIDE




ELEVATION
SOUTH SIDE



END VIEW
EAST SIDE



ELEVATION
NORTH SIDE



PLAN OF CAP
BOTTOM

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.


THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE

BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0.0		
COLUMN		0.0		
EPOXY COATING	AREA SF			
CAP	189.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 44



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE BENT 2					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED					SHEET NO. S-21 TOTAL SHEETS 42

DRAWN BY : M.ALEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016



PLAN OF CAP
TOP

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.


FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE


BENT 3	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	24.25	11.11		
CAP (HORIZONTAL FACE)	63.0	28.87		
COLUMN (VERTICAL FACE)	27.0	12.38		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0.0		
COLUMN		0.0		
EPOXY COATING	AREA SF			
CAP	189.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.




END VIEW
WEST SIDE

ELEVATION
SOUTH SIDE



END VIEW
EAST SIDE

ELEVATION
NORTH SIDE



PLAN OF CAP
BOTTOM

SHOTCRETE REPAIR
ERI EPOXY RESIN INJECTION

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 44




9/12/2016

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE BENT 3					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
SHEET NO. S-22					TOTAL SHEETS 42

DRAWN BY : M.ALEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



PLAN

NOTES


- FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.
- FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.
- FOR CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA, SEE SPECIAL PROVISIONS.
- FOR SHOTCRETE REPAIR, SEE SPECIAL PROVISIONS.
- FOR BEAM REPAIR, SEE SPECIAL PROVISIONS.
- FOR STEEL KEEPER ANGLE ASSEMBLY, SEE SPECIAL PROVISIONS.

CONSTRUCTION SEQUENCE:

- 1) - SUBSTRUCTURE REPAIRS & EPOXY RESIN INJECTION
- 2) - CLEAN AND PAINT STRUCTURAL STEEL
- 3) - CLEAN AND PAINT EXISTING BEARINGS WITH HRCSA
- 4) - INSTALL STEEL KEEPER ANGLE ASSEMBLY
- 5) - EPOXY COATING OF BENT CAPS

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 57

TOTAL BILL OF MATERIAL								
BRIDGE	SHOTCRETE REPAIR	EPOXY RESIN INJECTION	CLEANING & REPAINTING OF BRIDGE NO. 57	PAINTING CONTAINMENT FOR BRIDGE NO. 57	POLLUTION CONTROL	EPOXY COATING	STEEL KEEPER ANGLE ASSEMBLY	CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA BRIDGE NO. 57
	CF	LF	LUMP SUM	LUMP SUM	LUMP SUM	SF	EACH	EACH
380057	41	34	LUMP SUM	LUMP SUM	LUMP SUM	455	5	48




9/12/2016

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
PLAN VIEW OF BRIDGE 57 ON SR 1192 OVER I-85					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
TOTAL SHEETS					42

DRAWN BY : S. T. SANDOR/M. WELDON DATE : 08/2016
CHECKED BY : T. SHERRILL DATE : 08/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



FIX

EXP. EXP.

FIX

EXP. EXP.

FIX

SPAN A

SPAN B

SPAN C


SPAN D

KEY
 ① BEAM NUMBER
 Ⓚ STEEL KEEPER ANGLE ASSEMBLY

FRAMING PLAN

PROJECT NO. I-5843
GRANVILLE COUNTY
 BRIDGE NO.: 57

NOTE:
 BEARINGS SHALL BE CLEANED AND BLASTED AS PART OF CLEANING AND BLASTING FOR STRUCTURAL STEEL, BUT BEARINGS SHALL NOT BE PRIMED AND PAINTED WITH THE STRUCTURAL STEEL PAINT SYSTEM. AFTER BLASTING, BEARINGS SHALL BE PREPARED AND PAINTED AS REQUIRED BY THE HRCSA PAINT SYSTEM.



9/12/2016

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-24
2			4			
TOTAL SHEETS						42


DRAWN BY : M. WELDON DATE : 7/2016
 CHECKED BY : W. SMITH DATE : 7/2016

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

NOTE
FOR STEEL KEEPER ANGLE ASSEMBLY DETAILS, SEE "STEEL KEEPER ANGLE ASSEMBLY DETAILS" SHEET.
FOR STEEL KEEPER ANGLE ASSEMBLY, SEE SPECIAL PROVISIONS.

ANTICIPATED STEEL KEEPER ANGLE ASSEMBLY LOCATIONS		
SPAN	BEAM	LOCATION
A	4	BENT 1
A	6	BENT 1
D	1	BENT 3
D	2	BENT 3
D	6	BENT 3


PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 57




STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
STEEL KEEPER ANGLE ASSEMBLY REPAIR LOCATIONS					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					TOTAL SHEETS 42

DRAWN BY :	M.A.LEE	DATE :	9-16
CHECKED BY :	T.M. SHERRILL	DATE :	9-16


DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED




PLAN
END BENT 1




ELEVATION
END BENT 1



PLAN
END BENT 2



ELEVATION
END BENT 2

-  SHOTCRETE REPAIR
- ERI EPOXY RESIN INJECTION


REPAIR QUANTITY TABLE				
END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	14.0	6.42		
CAP (HORIZONTAL, CORNER)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		3.0		
EPOXY COATING	AREA SF			
CAP	73.0			
END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL, CORNER)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		24.0		
EPOXY COATING	AREA SF			
CAP	73.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTES:

- REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER, THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.
- CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.
- CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.
- SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.
- FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.
- FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.
- FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.
- THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE AREA OF THE ORIGINAL CAP ONLY.

PROJECT NO. I-5483
GRANVILLE COUNTY
BRIDGE NO. 57

DocuSigned by

AD50E1D87748566

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE
END BENT 1 & 2

9/12/2016

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-26
2			4			TOTAL SHEETS 42

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

09-SEP-2016 14:51
R:\Structures\I-5843 Final\I-5843 FINAL.dgn
malee7

REPAIR, LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.


FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK
OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR
TO BEGINNING WORK.

BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	4.0	1.83		
CAP (HORIZONTAL FACE)	2.0	0.92		
COLUMN (VERTICAL FACE)	15.0	6.88		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0.0		
COLUMN		0.0		
EPOXY COATING	AREA SF			
CAP	103.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER
REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND
MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.



ERI EPOXY RESIN INJECTION

9/12/2016

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION

RALEIGH

SUBSTRUCTURE

BENT 1

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	<div style="font-size: 2em; font-weight: bold;">S-27</div> <div style="font-size: 1.2em; font-weight: bold;">TOTAL SHEETS</div> <div style="font-size: 2.5em; font-weight: bold;">42</div>
1			3			
2			4			

09-SEP-2016 14:51
R:\Structures\I-5843 Final\I-5843 FINAL.dgn
malee7

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE				
BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	2.5	1.15		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	1.25	0.57		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		2.5		
COLUMN		0.0		
EPOXY COATING	AREA SF			
CAP	103.0			


VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.



PLAN OF CAP
TOP



END VIEW
NORTH SIDE




ELEVATION
WEST SIDE



PLAN OF CAP
BOTTOM




END VIEW
SOUTH SIDE



ELEVATION
EAST SIDE

SHOTCRETE REPAIR
ERI EPOXY RESIN INJECTION

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 57



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE BENT 2					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED					TOTAL SHEETS 42

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.


THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE				
BENT 3	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	49.0	22.46		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0.0		
COLUMN		4.0		
EPOXY COATING	AREA SF			
CAP	103.0			


VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.




PLAN OF CAP
TOP




END VIEW
NORTH SIDE



ELEVATION
WEST SIDE



END VIEW
SOUTH SIDE



ELEVATION
EAST SIDE



PLAN OF CAP
BOTTOM

SHOTCRETE REPAIR
ERI EPOXY RESIN INJECTION


DocuSigned by
T.M. Sherrill
AD50B8D87749565
NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
ENGINEER
MOTY M. SHERRILL
9/12/2016

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 57


STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE BENT 3					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
TOTAL SHEETS					42

DRAWN BY : M.ALEE
CHECKED BY : T.M.SHERRILL
DATE : 8/2016
DATE : 8/2016


DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED




PLAN
END BENT 1



ELEVATION
END BENT 1



PLAN
END BENT 2



ELEVATION
END BENT 2

REPAIR QUANTITY TABLE

END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	15.0	6.88		
CAP (HORIZONTAL, CORNER)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		34.0		
EPOXY COATING	AREA SF			
CAP	70.0			
END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL, CORNER)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		19.0		
EPOXY COATING	AREA SF			
CAP	70.0			


VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTES:

- REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.
- CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.
- CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.
- SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.
- FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.
- FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.
- FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.
- THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE AREA OF THE ORIGINAL CAP ONLY.

- ☒ SHOTCRETE REPAIR
- ERI EPOXY RESIN INJECTION

PROJECT NO. I-5483
GRANVILLE COUNTY
BRIDGE NO. 54



9/12/2016

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE END BENT 1 & 2					
REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
SHEET NO. S-31					TOTAL SHEETS 42

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

+

+

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.


THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE				
BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		2.0		
COLUMN		14.0		
EPOXY COATING	AREA SF			
CAP	131.0			


VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.




PLAN OF CAP
TOP




END VIEW
NORTH SIDE




ELEVATION
WEST SIDE




END VIEW
SOUTH SIDE




ELEVATION
EAST SIDE



PLAN OF CAP
BOTTOM

 SHOTCRETE REPAIR
ERI EPOXY RESIN INJECTION



PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 54

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION

RALEIGH

SUBSTRUCTURE

BENT 1

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	TOTAL SHEETS 42
1			3			
2			4			

DRAWN BY : M.ALEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



PLAN OF CAP

TOP

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE


BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	9.0	4.13		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	3.5	1.61		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0.0		
COLUMN		48		
EPOXY COATING	AREA SF			
CAP	167.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.




END VIEW

NORTH SIDE




ELEVATION

WEST SIDE



END VIEW

SOUTH SIDE



ELEVATION

EAST SIDE



PLAN OF CAP

BOTTOM

SHOTCRETE REPAIR

ERI EPOXY RESIN INJECTION



9/12/2016

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 54

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE
BENT 2

REVISIONS

NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO.

S-33

TOTAL

SHEETS

42

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016



PLAN OF CAP

TOP

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE


BENT 3	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	22.1	10.13		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0.0		
COLUMN		37.0		
EPOXY COATING	AREA SF			
CAP	144.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.




END VIEW

NORTH SIDE




ELEVATION

WEST SIDE



END VIEW

SOUTH SIDE



ELEVATION

EAST SIDE

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 54

SHOTCRETE REPAIR

ERI EPOXY RESIN INJECTION




9/12/2016

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE BENT 3					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
TOTAL SHEETS					42

DRAWN BY : M.ALEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED



PLAN

NOTES

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

FOR CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA, SEE SPECIAL PROVISIONS.

FOR SHOTCRETE REPAIR, SEE SPECIAL PROVISIONS.


BEARINGS SHALL BE CLEANED AND BLASTED AS PART OF CLEANING AND BLASTING FOR STRUCTURAL STEEL, BUT BEARINGS SHALL NOT BE PRIMED AND PAINTED WITH THE STRUCTURAL STEEL PAINT SYSTEM. AFTER BLASTING, BEARINGS SHALL BE PREPARED AND PAINTED AS REQUIRED BY THE HRCSA PAINT SYSTEM.

CONSTRUCTION SEQUENCE:

- 1) - SUBSTRUCTURE REPAIRS & EPOXY RESIN INJECTION
- 2) - CLEAN AND PAINT STRUCTURAL STEEL
- 3) - CLEAN AND PAINT EXISTING BEARINGS WITH HRCSA
- 4) - EPOXY COATING OF BENT CAPS

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 50

TOTAL BILL OF MATERIAL							
BRIDGE	SHOTCRETE REPAIR	EPOXY RESIN INJECTION	CLEANING & REPAINTING OF BRIDGE NO. 50	PAINTING CONTAINMENT FOR BRIDGE NO. 50	POLLUTION CONTROL	EPOXY COATING	CLEANING AND PAINTING EXISTING BEARINGS WITH HRCSA BRIDGE NO. 50
	CF	LF	LUMP SUM	LUMP SUM	LUMP SUM	SF	EACH
380050	47	80	LUMP SUM	LUMP SUM	LUMP SUM	390	40




9/12/2016


STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
PLAN VIEW OF BRIDGE 50 ON SR 1127 OVER I-85					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
TOTAL SHEETS					42

DRAWN BY : S. T. SANDOR/M. WELDON DATE : 08/2016
CHECKED BY : T. SHERRILL DATE : 08/2016


DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED




PLAN
END BENT 1



ELEVATION
END BENT 1



PLAN
END BENT 2



ELEVATION
END BENT 2

REPAIR QUANTITY TABLE				
END BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL, CORNER)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		3.0		
EPOXY COATING	AREA SF			
CAP	60.0			
END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	
CAP (VERTICAL FACE)	10.0	4.58		
CAP (HORIZONTAL, CORNER)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		37.0		
EPOXY COATING	AREA SF			
CAP	60.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.

NOTES:

- REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.
- CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.
- CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.
- SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.
- FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.
- FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.
- FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.
- THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE AREA OF THE ORIGINAL CAP ONLY.

PROJECT NO. I-5483
GRANVILLE COUNTY
BRIDGE NO. 50



9/12/2016

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE END BENT 1 & 2					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
					TOTAL SHEETS 42

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

+

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.


THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE				
BENT 1	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL FACE)	7.5	3.44		
COLUMN (VERTICAL FACE)	28.0	12.83		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		3.0		
COLUMN		0.0		
EPOXY COATING	AREA SF			
CAP	90.0			


VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.




PLAN OF CAP
TOP




ELEVATION
WEST SIDE




END VIEW
SOUTH SIDE



ELEVATION
EAST SIDE



END VIEW
NORTH SIDE



PLAN OF CAP
BOTTOM

SHOTCRETE REPAIR

ERI EPOXY RESIN INJECTION

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 50



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE BENT 1					
REVISIONS					SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED					TOTAL SHEETS 42

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

+

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.

THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE				
BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	2.5	1.15		
CAP (HORIZONTAL FACE)	12.5	5.73		
COLUMN (VERTICAL FACE)	0.0	0.0		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0.0		
COLUMN		5.5		
EPOXY COATING	AREA SF			
CAP	90.0			


VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.




PLAN OF CAP
TOP




END VIEW
NORTH SIDE




ELEVATION
WEST SIDE




END VIEW
SOUTH SIDE




ELEVATION
EAST SIDE



PLAN OF CAP
BOTTOM

 SHOTCRETE REPAIR

 ERI EPOXY RESIN INJECTION



9/12/2016

I-5843
GRANVILLE COUNTY
BRIDGE NO. 50

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH						SHEET NO.	
SUBSTRUCTURE BENT 2						S-38	
REVISIONS						TOTAL SHEETS	
NO.	BY:	DATE:	NO.	BY:	DATE:	42	
1			3				
2			4				

DRAWN BY : M.ALEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

+

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.

CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR REPAIR DETAILS, SEE TYPICAL CAP, COLUMN AND DECK OVERHANG REPAIR DETAILS SHEET.

THE CONTRACTOR SHALL EPOXY COAT THE TOP SURFACE OF BENT CAPS AFTER ALL BEARING REPAIRS ARE COMPLETED, AS A FINAL FINISH.

FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL PROVISIONS.


THE CONTRACTOR AND ENGINEER SHALL INSPECT THE BENT PRIOR TO BEGINNING WORK.

REPAIR QUANTITY TABLE				
BENT 3	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF
CAP (VERTICAL FACE)	0.0	0.0		
CAP (HORIZONTAL FACE)	0.0	0.0		
COLUMN (VERTICAL FACE)	42.0	19.25		
CONCRETE REPAIR	0.0	0.0		
EPOXY RESIN INJECTION		LN. FT		LN. FT
CAP		0.0		
COLUMN		31.5		
EPOXY COATING	AREA SF			
CAP	90.0			

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2" CL TO SAWCUT. SEE REPAIR DETAILS.




PLAN OF CAP
TOP




END VIEW
NORTH SIDE

ELEVATION
WEST SIDE



END VIEW
SOUTH SIDE



ELEVATION
EAST SIDE



PLAN OF CAP
BOTTOM

SHOTCRETE REPAIR
ERI EPOXY RESIN INJECTION

DocuSigned by
T.M. Sherrill
AD50B8D8-7749-665
NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
ENGINEER
MOTY M. SHERRILL
9/12/2016

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 50

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION

RALEIGH

SUBSTRUCTURE

BENT 3

REVISIONS

NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO.

S-39


TOTAL SHEETS

42


DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

09-SEP-2016 15:01
R:\Structures\I-5843 Final\I-5843 FINAL.dgn
malee7


DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED




SECTION LOSS BEAM PLATING REPAIR




SECTION LOSS BEAM PLATING REPAIR




SECTION LOSS BEAM PLATING REPAIR




SECTION LOSS BEAM PLATING REPAIR



SECTION LOSS BEAM PLATING REPAIR




DETAIL "A"




VIEW I-I

NOTE: DETAIL INDICATES WEB AND FLANGE PLATING, BUT APPROPRIATE DETAILS ARE APPLICABLE FOR WEB PLATING OR FLANGE PLATING, ONLY.




SECTION LOSS INTERMEDIATE BEAM PLATING REPAIR




DETAIL "B"

NOTE: DETAIL INDICATES WEB PLATING, BUT GRINDING OF FILLET IS APPLICABLE FOR WEB PLATING, FLANGE PLATING, AND WEB AND FLANGE PLATING TOGETHER.




SECTION LOSS STIFFENER/CONN. REPAIR



SECTION LOSS STIFFENER/CONN. REPAIR SECTION

▲ FOR STIFFENERS, MILL TO BEAR AND DO NOT WELD



SECTION LOSS INTERMEDIATE BEAM PLATING REPAIR

BEAM REPAIR

ALL CONDITIONS AND DIMENSIONS SHALL BE FIELD VERIFIED PRIOR TO FABRICATION OR INSTALLATION OF ANY COMPONENTS.

REPAIR PLATES SHALL BE MINIMUM 36 KSI STEEL.

REPAIR SEQUENCE:

COORDINATE WITH MATERIALS AND TEST UNIT AT LEAST 4 DAYS PRIOR TO ANTICIPATED WORK.

REMOVE LIVE LOAD FROM REPAIR AREA BY EITHER CLOSING BRIDGE TO TRAFFIC OR SHIFTING TRAFFIC AWAY FROM REPAIR AREA.

IF NECESSARY, REMOVE EXISTING STIFFENER TO INSTALL WELDED PLATE REPAIR. REPLACE WITH A NEW STIFFENER PLATE OF SIMILAR SIZE.

IF BEAM DETERIORATION EXTENDS INTO THE CONCRETE DIAPHRAGM THEN CHIP AWAY CONCRETE TO DETERMINE THE EXTENT OF THE DAMAGE.

MECHANICALLY CLEAN RUST, SCALE, AND EXISTING PAINT TO AT LEAST 3" BEYOND REPAIR AREA.

PRIME ENTIRE REPAIR AREA AND REPAIR PLATES WITH AN ORGANIC ZINC PRIMER PRIOR TO WELDING NEW PLATES. REMOVE PRIMER IN WELD AREA.

ONE PLATE SHALL BE PLACED, AS INDICATED ON EACH SIDE OF THE BEAM WEB.

UNLESS NOTED OTHERWISE EACH PLATE SHALL BE APPROXIMATELY ONE- HALF THE ORIGINAL THICKNESS OF THE BEAM WEB, MINIMUM THICKNESS OF 1/4".

FULLY WELD ALONG TOP AND SIDES OF THE PLATES AS SHOWN.

ALL WELDING SHALL BE IN ACCORDANCE WITH CURRENT APPLICABLE AWS AND NCDOT STANDARD SPECIFICATIONS.

ALL WELDS SHALL BE INSPECTED AND TESTED BY THE NCDOT MATERIALS AND TEST UNIT IN ACCORDANCE WITH THE CURRENT AWS BRIDGE WELDING CODE AND STANDARD SPECIFICATIONS.

IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS, AFTER REPAIR, GRIND ALL WELDS FLUSH, THOROUGHLY CLEAN AREA TO REMOVE DEBRIS AND OILS FROM THE REPAIR PROCESS.


CLEANING AND PAINTING OF REPAIRED STRUCTURAL STEEL SHALL BE PERFORMED AS PART OF THE OVERALL CLEANING AND PAINTING CONTRACT.

FOR CLEANING AND PAINTING, SEE PAINTING EXISTING STRUCTURE SPECIAL PROVISIONS.

AFTER BEAMS ARE REPAIRED AND PAINTED, ANY CONCRETE REMOVED FROM THE BENT DIAPHRAGMS SHALL BE CAST BACK. ANY REINFORCING STEEL CUT DURING THE REMOVAL PROCESS SHALL BE SPLICED WITH A SIMILAR SIZE BAR WITH AT LEAST A ONE FOOT SPLICE TO THE EXISTING STEEL. NO SEPARATE PAYMENT SHALL BE MADE FOR CONCRETE AND REINFORCING STEEL AS THIS IS CONSIDERED INCIDENTAL TO THE PAY ITEM "BEAM REPAIR". FOR BEAM REPAIR, SEE SPECIAL PROVISIONS.

REMOVE ALL TRAFFIC CONTROL DEVICES.

PROJECT NO. I-5843
GRANVILLE COUNTY
 BRIDGE NO. 35, 44, 60, 61




9/12/2016


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-40
2			4			TOTAL SHEETS 42

DRAWN BY : M.ALEE DATE : 9/2016
 CHECKED BY : T.M.SHERRILL DATE : 9/2016



PLAN



PLAN

* LENGTH OF ANGLE SHALL MATCH WIDTH OF EXISTING MASONRY PLATE

STEEL KEEPER ANGLE ASSEMBLY DETAILS


NOTES

STRUCTURAL STEEL SHALL BE AASHTO GRADE 36 OR GREATER.


STRUCTURAL STEEL, ANCHOR BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

ANCHOR BOLTS SHALL MEET THE REQUIREMENTS OF ASTM A449. NUTS SHALL MEET THE REQUIREMENTS OF AASHTO M291-DH OR AASHTO M292-2H. WASHERS SHALL MEET THE REQUIREMENTS OF AASHTO M293. SHOP DRAWINGS ARE NOT REQUIRED FOR ANCHOR BOLTS, NUTS AND WASHERS. SHOP INSPECTION IS REQUIRED.

ANCHOR BOLTS MAY BE ADHESIVELY ANCHORED, SEE STANDARD SPECIFICATIONS. NO FIELD TESTING REQUIRED.




END ELEVATION



SECTION A-A
(LOCATION OF EXISTING ANCHOR BOLTS AS SHOWN IS FOR ILLUSTRATION ONLY)

PROJECT NO. I-5843
GRANVILLE COUNTY
 BRIDGE NO. 35 & 57



9/12/2016

DRAWN BY : M. WELDON DATE : 8/2013
 CHECKED BY : J. YANACCONI DATE : 8/2013

09-SEP-2016 15:03
 R:\Structures\I-5843 Final\I-5843 FINAL.dgn
 malee7

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	
1			3			S-41
2			4			TOTAL SHEETS
						42

NOTE

CONTRACTOR SHALL SAW CUT TO A NOMINAL DEPTH OF 1/2" BUT REINFORCING STEEL SHALL NOT BE DAMAGED.


CONTRACTOR SHALL REMOVE SURFACE CONCRETE TO VERIFY THAT SAWCUT DEPTH WILL NOT DAMAGE EXISTING REINFORCING STEEL.

CONTRACTOR SHALL SAW CUT THE REPAIR AREAS SO THAT THE CORNERS ARE SQUARE AS INDICATED ON THE DETAILS.


CONCRETE REPAIRS MAY BE SUBSTITUTED IN LIEU OF SHOTCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.


FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.



BENT CAP REPAIRS




PLAN OF COLUMN




SECTION THRU CAP
(EXAMPLE ONLY, ACTUAL REBAR SIZES & LOCATIONS MAY VARY)

CAP REPAIR




ELEVATION OF CAP

COLUMN REPAIR



TYPICAL SECTION

DAMAGED AREA REMOVE CONCRETE UNTIL SOUND
* CONCRETE IS FOUND
(MIN. 2" BEYOND EDGE OF SPALL)



SECTION E-E

OVERHANG DETAILS

PROJECT NO. I-5843
GRANVILLE COUNTY
BRIDGE NO. 35, 44, 50, 57, 54

DocuSigned by
T. M. SHERRILL
AD508150774856C
ENGINEER
MOTY M. SHERRILL
9/12/2016

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
SUBSTRUCTURE
TYPICAL CAP, COLUMN
AND DECK OVERHANG
REPAIR DETAILS

DRAWN BY : M.A.LEE DATE : 8/2016
CHECKED BY : T.M.SHERRILL DATE : 8/2016

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO.
S-42
TOTAL
SHEETS
42

STANDARD NOTES

DESIGN DATA:

SPECIFICATIONS	- - - - -	A.A.S.H.T.O. (CURRENT)
LIVE LOAD	- - - - -	SEE PLANS
IMPACT ALLOWANCE	- - - - -	SEE A.A.S.H.T.O.
STRESS IN EXTREME FIBER OF		
STRUCTURAL STEEL - AASHTO M270 GRADE 36	-	20,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50W	-	27,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50	-	27,000 LBS. PER SQ. IN.
REINFORCING STEEL IN TENSION		
GRADE 60	- -	24,000 LBS. PER SQ. IN.
CONCRETE IN COMPRESSION	- - - - -	1,200 LBS. PER SQ. IN.
CONCRETE IN SHEAR	- - - - -	SEE A.A.S.H.T.O.
STRUCTURAL TIMBER - TREATED OR		
UNTREATED - EXTREME FIBER STRESS	- - - - -	1,800 LBS. PER SQ. IN.
COMPRESSION PERPENDICULAR TO GRAIN OF TIMBER	- - - - -	375 LBS. PER SQ. IN.
EQUIVALENT FLUID PRESSURE OF EARTH	- - - - -	30 LBS. PER CU. FT.
		(MINIMUM)

MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2012 "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; AND CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP.

CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED 3/4" WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO 1-1/2" RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A 1/4" FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A 1/4" RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT, ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE. ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER. DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS. WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE 7/8"Ø SHEAR STUDS FOR THE 3/4"Ø STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - 7/8"Ø STUDS FOR 4 - 3/4"Ø STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF 7/8"Ø STUDS ALONG THE BEAM AS SHOWN FOR 3/4"Ø STUDS BASED ON THE RATIO OF 3 - 7/8"Ø STUDS FOR 4 - 3/4"Ø STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-0". EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST 5/16" IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2" OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED. WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES, ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY 1/16 INCH OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB. METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINIS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.

ENGLISH

JANUARY, 1990

STD. NO. SN