

**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**


**This file or an individual page
shall not be considered a certified document.**

09/08/19

PROJECT: 17BP.6.R.105

CONTRACT: DF00238

See Sheet I-A For Index of Sheets
See Sheet I-B For Conventional Symbols



VICINITY MAP


● ● ● DETOUR ROUTE N.T.S.

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS
ROBESON COUNTY

**LOCATION: REPLACE BRIDGE 770431 OVER JACOB SWAMP
ON SR 2305 (KITE ROAD)**


TYPE OF WORK: GRADING, DRAINAGE, PAVING AND STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.6.R.105	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
17BP.6.R.105	N/A	PE	
17BP.6.R.105	N/A	Row, Util.	
17BP.6.R.105	N/A	Construction	



DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

GRAPHIC SCALES



DESIGN DATA

ADT 2018 = 770 VPD
ADT 2040 = 1000 VPD
DHV = N/A
D = N/A
T = 7%
V = 55 MPH
FUNC CLASS =
LOCAL
SUB-REGIONAL TIER

PROJECT LENGTH

LENGTH ROADWAY PROJECT 17BP.6.R.105 = 0.064 MILES
LENGTH BRIDGE PROJECT 17BP.6.R.105 = 0.018 MILES
TOTAL LENGTH PROJECT 17BP.6.R.105 = 0.082 MILES

Prepared in the Office of:
CDM Smith
CDM Smith Inc.
5400 Glenwood Avenue
Suite 400
Raleigh, NC 27612-3228
NC CDA No. F-1255

FOR THE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
2018 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE:
JULY 30, 2018

LETTING DATE:
DECEMBER 19, 2018

DAVID J. CLODGO, PE
PROJECT ENGINEER

ADAM M. CONRAD, PE
PROJECT DESIGN ENGINEER


CHRISTY W. HUFF, PE
NCDOT CONTACT

HYDRAULICS ENGINEER

11/26/2018
SEAL 18533
ANDREW T. NOTTINGHAM
P.E.
SIGNATURE: Andrew T. Nottingham


ROADWAY DESIGN ENGINEER

11/26/2018
SEAL 035683
DAVID J. CLODGO
P.E.
SIGNATURE: David J. Clodgo



-SYSTEME:\PROJ\17BP.6.R.105_Rdy_1.sh.dgn
USER: CONRADAM

8/17/19



SHEET NUMBER	SHEET
1	TITLE SHEET
1-A	INDEX OF SHEETS, GENERAL NOTES AND STANDARD DRAWINGS
1-B	CONVENTIONAL SYMBOLS
1C-1	SURVEY CONTROL SHEET
1D-1	ALIGNMENT CONTROL SHEET
1E-1	RIGHT OF WAY CONTROL SHEET
2A-1 THRU 2A-2	PAVEMENT SCHEDULE AND TYPICAL SECTIONS
2C-1	DETAIL OF MODIFIED METHOD OF CLEARING II
3B-1	ROADWAY SUMMARIES
3D-1	DRAINAGE SUMMARIES
4	PLAN AND PROFILE SHEET
TMP-1 THRU TMP-3	TRANSPORTATION MANAGEMENT PLANS
PMP-1 THRU PMP-2	PAVEMENT MARKING PLANS
EC-1 THRU EC-5	EROSION CONTROL PLANS
UO-1 THRU UO-2	UTILITIES BY OTHERS PLANS
X-1 THRU X-4	CROSS-SECTION INDEX SHEET AND CROSS-SECTIONS
S-1 THRU S-19	STRUCTURE PLANS
SN	STANDARD NOTES

EFF. 01-16-2018
REV.

2018 ROADWAY ENGLISH STANDARD DRAWINGS

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch - N. C. Department of Transportation - Raleigh, N. C., Dated January, 2018 are applicable to this project and by reference hereby are considered a part of these plans:

STD.NO.	TITLE
DIVISION 2 - EARTHWORK	
200.02	Method of Clearing - Modified Method II (Use Detail in Lieu of Standard)
225.02	Guide for Grading Subgrade - Secondary and Local
225.04	Method of Obtaining Superelevation - Two Lane Pavement
DIVISION 3 - PIPE CULVERTS	
300.01	Method of Pipe Installation
310.10	Driveway Pipe Construction
DIVISION 4 - MAJOR STRUCTURES	
422.02	Bridge Approach Fills - Type II Modified Approach Fill
DIVISION 5 - SUBGRADE, BASES AND SHOULDERS	
560.01	Method of Shoulder Construction - High Side of Superelevated Curve - Method I
DIVISION 8 - INCIDENTALS	
840.29	Frames and Narrow Slot Flat Grates
840.35	Traffic Bearing Grated Drop Inlet - for Cast Iron Double Frame and Grates
846.01	Concrete Curb, Gutter and Curb & Gutter
846.04	Drop Inlet Installation in Shoulder Berm Gutter
862.01	Guardrail Placement
862.02	Guardrail Installation
862.03	Structure Anchor Units
876.02	Guide for Rip Rap at Pipe Outlets
876.04	Drainage Ditches with Class 'B' Rip Rap

GENERAL NOTES: 2018 SPECIFICATIONS
EFFECTIVE: 01-16-2018
REVISED:

GRADE LINE:
GRADING AND SURFACING:

THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. GRADE LINES MAY BE ADJUSTED AT THEIR BEGINNING AND ENDING AND AT STRUCTURES AS DIRECTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:

CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY MODIFIED METHOD II.

SUPERELEVATION:

ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNOFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:

ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01

GUARDRAIL:

THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

END BENTS:

THE ENGINEER SHALL CHECK THE STRUCTURE END BENT PLANS, DETAILS, AND CROSS-SECTION PRIOR TO SETTING OF THE SLOPE STAKES FOR THE EMBANKMENT OR EXCAVATION APPROACHING A BRIDGE.

UTILITIES:

UTILITY OWNERS ON THIS PROJECT ARE

DUKE ENERGY - POWER TRANSMISSION
LUMBEE RIVER ELECTRIC MEMBERSHIP CORP. - POWER DISTRIBUTION
ROBESON COUNTY PUBLIC UTILITIES - WATER DISTRIBUTION
AT&T - TELECOMMUNICATION
SPIRIT - TELECOMMUNICATION
CHARTER - TELECOMMUNICATION

RIGHT-OF-WAY MARKERS:

ALL RIGHT-OF-WAY MARKERS AND PERMANENT EASEMENT MARKERS ARE TO BE PLACED BY L&S. THE CONTRACT SURVEYOR WILL BE RESPONSIBLE FOR RESETTING ANY POINTS DISTURBED DURING CONSTRUCTION.

-SYSTEM: B:\105_Rdwy_psh_1A.dgn
DATE: 8/17/19 11:51:27 AM

STATE OF NORTH CAROLINA, DIVISION OF HIGHWAYS CONVENTIONAL PLAN SHEET SYMBOLS

12/2/2016

BOUNDARIES AND PROPERTY:

State Line	-----
County Line	-----
Township Line	-----
City Line	-----
Reservation Line	-----
Property Line	-----
Existing Iron Pin	○ EIP
Computed Property Corner	----->
Property Monument	□ ECM
Parcel/Sequence Number	⑫③
Existing Fence Line	-x-x-x-
Proposed Woven Wire Fence	○
Proposed Chain Link Fence	□
Proposed Barbed Wire Fence	◇
Existing Wetland Boundary	----- WLB
Proposed Wetland Boundary	----- WLB
Existing Endangered Animal Boundary	----- EAB
Existing Endangered Plant Boundary	----- EPB
Existing Historic Property Boundary	----- HPB
Known Contamination Area: Soil	☠-s-☠
Potential Contamination Area: Soil	??-s-??
Known Contamination Area: Water	☠-w-☠
Potential Contamination Area: Water	??-w-??
Contaminated Site: Known or Potential	☠??

BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	○
Sign	○ S
Well	○ W
Small Mine	✕
Foundation	□
Area Outline	□
Cemetery	□
Building	□
School	□
Church	□
Dam	□

HYDROLOGY:

Stream or Body of Water	-----
Hydro, Pool or Reservoir	□
Jurisdictional Stream	----- JS
Buffer Zone 1	----- BZ 1
Buffer Zone 2	----- BZ 2
Flow Arrow	←
Disappearing Stream	-----
Spring	○
Wetland	-----
Proposed Lateral, Tail, Head Ditch	-----
False Sump	-----

RAILROADS:

Standard Gauge	-----
RR Signal Milepost	○ MILEPOST 35
Switch	□ SWITCH
RR Abandoned	-----
RR Dismantled	-----

RIGHT OF WAY & PROJECT CONTROL:

Secondary Horiz and Vert Control Point	◆
Primary Horiz Control Point	○
Primary Horiz and Vert Control Point	◆
Exist Permanent Easement Pin and Cap	◇
New Permanent Easement Pin and Cap	◆
Vertical Benchmark	⊠
Existing Right of Way Marker	△
Existing Right of Way Line	-----
New Right of Way Line	-----
New Right of Way Line with Pin and Cap	-----
New Right of Way Line with Concrete or Granite RW Marker	-----
New Control of Access Line with Concrete C/A Marker	-----
Existing Control of Access	-----
New Control of Access	-----
Existing Easement Line	----- E
New Temporary Construction Easement	----- E
New Temporary Drainage Easement	----- TDE
New Permanent Drainage Easement	----- PDE
New Permanent Drainage / Utility Easement	----- DUE
New Permanent Utility Easement	----- PUE
New Temporary Utility Easement	----- TUE
New Aerial Utility Easement	----- AUE

ROADS AND RELATED FEATURES:

Existing Edge of Pavement	-----
Existing Curb	-----
Proposed Slope Stakes Cut	----- C
Proposed Slope Stakes Fill	----- F
Proposed Curb Ramp	----- CR
Existing Metal Guardrail	-----
Proposed Guardrail	-----
Existing Cable Guiderail	-----
Proposed Cable Guiderail	-----
Equality Symbol	⊕
Pavement Removal	-----

VEGETATION:

Single Tree	○
Single Shrub	○

Note: Not to Scale

*S.U.E. = Subsurface Utility Engineering

Hedge	-----
Woods Line	-----
Orchard	-----
Vineyard	-----

EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	----- CONC
Bridge Wing Wall, Head Wall and End Wall	----- CONC WW
MINOR:	
Head and End Wall	----- CONC HW
Pipe Culvert	-----
Footbridge	-----
Drainage Box: Catch Basin, DI or JB	□ CB
Paved Ditch Gutter	-----
Storm Sewer Manhole	○ S
Storm Sewer	----- S

UTILITIES:

POWER:	
Existing Power Pole	●
Proposed Power Pole	○
Existing Joint Use Pole	●
Proposed Joint Use Pole	○
Power Manhole	⊕
Power Line Tower	⊠
Power Transformer	⊠
U/G Power Cable Hand Hole	○
H-Frame Pole	●
U/G Power Line LOS B (S.U.E.*)	----- P
U/G Power Line LOS C (S.U.E.*)	----- P
U/G Power Line LOS D (S.U.E.*)	----- P

TELEPHONE:

Existing Telephone Pole	●
Proposed Telephone Pole	○
Telephone Manhole	⊕
Telephone Pedestal	⊠
Telephone Cell Tower	⊠
U/G Telephone Cable Hand Hole	○
U/G Telephone Cable LOS B (S.U.E.*)	----- T
U/G Telephone Cable LOS C (S.U.E.*)	----- T
U/G Telephone Cable LOS D (S.U.E.*)	----- T
U/G Telephone Conduit LOS B (S.U.E.*)	----- TC
U/G Telephone Conduit LOS C (S.U.E.*)	----- TC
U/G Telephone Conduit LOS D (S.U.E.*)	----- TC
U/G Fiber Optics Cable LOS B (S.U.E.*)	----- T FO
U/G Fiber Optics Cable LOS C (S.U.E.*)	----- T FO
U/G Fiber Optics Cable LOS D (S.U.E.*)	----- T FO

WATER:

Water Manhole	⊕
Water Meter	○
Water Valve	⊗
Water Hydrant	⊕
U/G Water Line LOS B (S.U.E.*)	-----
U/G Water Line LOS C (S.U.E.*)	-----
U/G Water Line LOS D (S.U.E.*)	-----
Above Ground Water Line	----- A/G Water

TV:

TV Pedestal	⊠
TV Tower	⊗
U/G TV Cable Hand Hole	○
U/G TV Cable LOS B (S.U.E.*)	----- TV
U/G TV Cable LOS C (S.U.E.*)	----- TV
U/G TV Cable LOS D (S.U.E.*)	----- TV
U/G Fiber Optic Cable LOS B (S.U.E.*)	----- TV FO
U/G Fiber Optic Cable LOS C (S.U.E.*)	----- TV FO
U/G Fiber Optic Cable LOS D (S.U.E.*)	----- TV FO

GAS:

Gas Valve	◇
Gas Meter	⊕
U/G Gas Line LOS B (S.U.E.*)	----- G
U/G Gas Line LOS C (S.U.E.*)	----- G
U/G Gas Line LOS D (S.U.E.*)	----- G
Above Ground Gas Line	----- A/G Gas

SANITARY SEWER:

Sanitary Sewer Manhole	⊕
Sanitary Sewer Cleanout	⊕
U/G Sanitary Sewer Line	----- SS
Above Ground Sanitary Sewer	----- A/G Sanitary Sewer
SS Forced Main Line LOS B (S.U.E.*)	----- FSS
SS Forced Main Line LOS C (S.U.E.*)	----- FSS
SS Forced Main Line LOS D (S.U.E.*)	----- FSS

MISCELLANEOUS:

Utility Pole	●
Utility Pole with Base	□
Utility Located Object	○
Utility Traffic Signal Box	⊠
Utility Unknown U/G Line LOS B (S.U.E.*)	----- 7UTL
U/G Tank; Water, Gas, Oil	□
Underground Storage Tank, Approx. Loc.	⊕
A/G Tank; Water, Gas, Oil	□
Geoenvironmental Boring	⊕
U/G Test Hole LOS A (S.U.E.*)	⊕
Abandoned According to Utility Records	AATUR
End of Information	E.O.I.

6/2/95

PROJECT REFERENCE NO.	SHEET NO.
17BP.6.R.105	1C-1
Location and Surveys	


SURVEY CONTROL SHEET 770431



BL	POINT	DESC.	NORTH	EAST	ELEVATION
1		BL-1	302294.7250	1999862.5142	111.60
2		BL-2	302310.9675	2000219.7773	112.02
3		BL-3	302259.6987	2000708.9531	109.13

 BM1 ELEVATION = 110.97
 N 302354 E 2000303
 L STATION 14+76.00 28 LEFT
 RR SPIKE SET IN 10" OAK TREE

REVISIONS



DATUM DESCRIPTION

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "BL-1"

WITH NAD 83/NA 2011 STATE PLANE GRID COORDINATES OF
 NORTHING: 302294.7250(±) EASTING: 1999862.5142(±)
 ELEVATION: 111.60(±)

THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.999940727

THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "BL-1" TO -L- STATION 10+00.00 IS
 S62°12'59.15"W 38.1174'

ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
 VERTICAL DATUM USED IS NAVD 88

NOTES:

1. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
2. THE SURVEY CONTROL DATA FOR THIS PROJECT HAS BEEN COMPILED FROM VARIOUS SOURCES. IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.

-SYTIME 77BP.6.R.105-1s-1C-1.dgn

PROPOSED ALIGNMENT CONTROL SHEET 770431

L

TYPE	STATION	NORTH	EAST
POT	10+00.00	302276.9572	1999828.7912
PC	11+75.69	302307.0091	2000001.8933
PT	18+23.68	302266.1166	2000642.5995
POT	18+60.77	302255.1784	2000678.0387

REVISIONS

-SYSTIME17BP.6.R.105.1s.1D-1.dgn
11/26/2014 10:11:16 AM

NOTES:

1. PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.
2. THE PROPOSED ALIGNMENT CONTROL DATA FOR THIS PROJECT HAS BEEN COMPILED FROM VARIOUS SOURCES. IF FURTHER INFORMATINO REGARDING PROJECT CONTROL IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.

6/2/95

RIGHT OF WAY CONTROL SHEET 770431

PROJECT REFERENCE NO.	SHEET NO.
17BP.6.R.105	1E-1
Location and Surveys	

PROJECT
SURVEYOR

ROW MARKER IRON PIN AND CAP-E

ALIGN	STATION	OFFSET	NORTH	EAST
L	13+60.00	-50.00	302376.2526	2000183.1600
L	15+15.00	-50.00	302373.2807	2000343.6838
L	13+75.00	30.00	302296.7851	2000200.8524
L	13+75.00	45.00	302281.7906	2000201.2565
L	13+60.00	-30.00	302356.2669	2000183.9168
L	15+15.00	45.00	302278.5469	2000336.5773
L	15+15.00	30.00	302293.5048	2000337.6994
L	15+15.00	-30.00	302353.3367	2000342.1877

REVISIONS

-SYTIME 770431.P.105.1s.1E-1.dgn
11:56:00 AM '95

NOTES:





- IF FURTHER INFORMATION REGARDING PROJECT CONTROL IS NEEDED, PLEASE CONTACT THE LOCATION AND SURVEYS UNIT.
- PROJECT CONTROL WAS ESTABLISHED USING GNSS, THE GLOBAL NAVIGATION SATELLITE SYSTEM.

6/2/99

PAVEMENT SCHEDULE <i>(FINAL PAVEMENT DESIGN)</i>	
C1	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
C2	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 110 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 1" IN DEPTH OR GREATER THAN 1 1/2" IN DEPTH.
E1	PROP. APPROX. 4" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
E2	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5 1/2" IN DEPTH.
R1	SHOULDER BERM GUTTER
T	EARTH MATERIAL.
U	EXISTING PAVEMENT.
V	INCIDENTAL MILLING
W	VARIABLE DEPTH ASPHALT PAVEMENT (SEE -L- WEDGING DETAIL)
Y	INCIDENTAL STONE


NOTE: ALL PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.

PROJECT REFERENCE NO. 17BP.6.R.105	SHEET NO. 2A-1
ROADWAY DESIGN ENGINEER	PAVEMENT DESIGN ENGINEER
CDM Smith CDM Smith Inc. 5400 Glenwood Avenue Suite 402 Raleigh, NC 27612-3228 NC CEA No. F-1255	NC DEPARTMENT OF TRANSPORTATION PAVEMENT MANAGEMENT UNIT 1503 MAIL SERVICE CENTER RALEIGH, NC 27699-1030
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	



6/2/19


PROJECT REFERENCE NO. 17BP.6.R.105	SHEET NO. 2A-2
ROADWAY DESIGN ENGINEER	PAVEMENT DESIGN ENGINEER
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	



TYPICAL SECTION NO. 2

USE TYPICAL SECTION NO. 2


-L- STA. 12+88.77 TO STA. 13+88.77 (BEGIN BRIDGE)
-L- STA. 14+81.23 (END BRIDGE) TO STA 15+81.23



DETAIL B

USE DETAIL B IN CONJUNCTION WITH TYPICAL SECTION NO. 2


-L- STA. 13+11.14 TO STA. 13+85.20 (LT)
-L- STA. 13+16.61 TO STA. 13+92.42 (RT)
-L- STA. 14+76.63 TO STA. 15+50.73 (LT)
-L- STA. 15+09.47 TO STA. 15+61.71 (RT)



TYPICAL BRIDGE SECTION

USE TYPICAL BRIDGE SECTION

-L- STA. 13+88.77 (BEGIN BRIDGE) TO STA. 14+81.23 (END BRIDGE)



DETAIL C

USE DETAIL C IN CONJUNCTION WITH TYPICAL SECTION NO. 2

-L- STA. 14+95.96 TO STA. 15+09.47 (RT)

PAVEMENT SCHEDULE (FINAL PAVEMENT DESIGN)	
C1	3" S9.5B
C2	VAR. S9.5B
E1	4" B25.0C
E2	VAR. B25.0C
R1	SHOULDER BERM GUTTER
T	EARTH MATERIAL
U	EXIST. PAVEMENT
V	INCIDENTAL MILLING
W	WEDGING
Y	INCIDENTAL STONE

PAVEMENT EDGESLOPES 1:1 UNLESS NOTED OTHERWISE

5/14/99

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.


ENGLISH DETAIL DRAWING FOR
METHOD OF CLEARING
MODIFIED METHOD - II

SHEET 1 OF 1
200d02

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ENGLISH DETAIL DRAWING FOR
METHOD OF CLEARING
MODIFIED METHOD - II


SHEET 1 OF 1
200d02




GENERAL NOTES:

1. REMOVE TREES OUTSIDE THE CLEARING LIMIT WHEN, IN THE OPINION OF THE ENGINEER, THE UTILITY OF A TREE WILL BE DESTROYED BY THE CONSTRUCTION OR THE CLEARING OPERATION.
2. CLEAR IN ACCORDANCE WITH THIS STANDARD EXCEPT WHERE ADDITIONAL CLEARING IS REQUIRED FOR SAFETY AS SHOWN ON THE PLANS.
3. FOR SECTIONS WITH WIDE MEDIANS WHERE TREES ARE TO REMAIN, CLEAR THE MEDIAN SIDE IN THE SAME MANNER AS ON THE OUTSIDE.
4. HAND CLEAR AS NEEDED TO 5' OUTSIDE THE SLOPE STAKE LINES FOR INSTALLATION OF EROSION CONTROL DEVICES.

CLEAR TO SLOPE STAKE LINE OR CONSTRUCTION LIMITS



11/20/2018




CONTRACT STANDARDS & DEVELOPMENT UNIT
STANDARDS AND SPECIAL DESIGN
Office 919-707-6950 FAX 919-250-4119

SEE TITLE BLOCK

ORIGINAL BY: rnbritt DATE: 05-02-11
 MODIFIED BY: DATE:
 CHECKED BY: DATE:
 FILE SPEC.: details/rnbritt/english/urban/u3615aconcretefume.dgn




DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

PROJECT REFERENCE NO. 17BP.6.R.105		SHEET NO. 4	
RW SHEET NO.		HYDRAULICS ENGINEER	
ROADWAY DESIGN ENGINEER		ENGINEER	
<p>CDM Smith Inc. 5420 Glenwood Avenue, Suite 100, Raleigh, NC 27609, No. CDM No. F-7252</p> <p>MI Engineering, PLLC 1011 Scharle Drive, Suite 100, Raleigh, NC 27609, No. CDM No. P-6671</p>			
<p>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</p>			



BRIDGE HYDRAULIC DATA



DESIGN DISCHARGE	= 360	CFS
DESIGN FREQUENCY	= 2	YRS
DESIGN HW ELEVATION	= 107.0	FT
BASE DISCHARGE	= 1940	CFS
BASE FREQUENCY	= 100	YRS
BASE HW ELEVATION	= 110.9	FT
OVERTOPPING DISCHARGE	= 490	CFS
OVERTOPPING FREQUENCY	= 5(-)	YRS
OVERTOPPING ELEVATION	= 108.1	FT
DATE OF SURVEY	= 4/3/2018	FT
W.S.ELEVATION AT DATE OF SURVEY	= 102.8	FT



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

TRANSPORTATION MANAGEMENT PLAN

ROBESON COUNTY




**LOCATION: REPLACE BRIDGE 770431 OVER JACOB SWAMP
ON SR 2305 (KITE ROAD)**

SHEET NO.	TITLE
TMP-1	TITLE SHEET, VICINITY MAP AND INDEX OF SHEETS
TMP-1A	LIST OF APPLICABLE ROADWAY STANDARD DRAWINGS, AND LEGEND
TMP-1B	TRANSPORTATION OPERATIONS PLAN: (MANAGEMENT STRATEGIES, GENERAL NOTES AND LOCAL NOTES)
TMP-2	OFF-SITE DETOUR
TMP-3	SIGN DESIGN

SHEET NO.
TMP-1

8/29/2018 R:\ncdot\17BP.6.R.105 (Robeson 431)\VOID-allcurrent files on PW\Traffic\TrafficControl\TCP\TRYING TO PRINT\17BP.6.R.105_TMP_TCOI.dgn User:GR00KJC




PLANS PREPARED BY:

ADAM CONRAD, P.E.
PROJECT ENGINEER
JONATHAN CROOK, E.I.
PROJECT DESIGN ENGINEER

NCDOT CONTACTS:

J. S. KITE, P.E.
PROJECT ENGINEER
MATTHEW SPRINGER, P.E.
PROJECT DESIGN ENGINEER



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

<p>CDM Smith Inc. 5400 Glenwood Avenue Suite 400 Raleigh, NC 27612-3228 NC COA No. F-1255</p>	<p>APPROVED: _____</p> <p>DATE: 11/20/2018</p>
	<p>SEAL</p>

PROJECT: 17BP.6.R.105

ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS SHOWN IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2018 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
1101.03	TEMPORARY ROAD CLOSURES
1101.11	TRAFFIC CONTROL DESIGN TABLES
1110.01	STATIONARY WORK ZONE SIGNS
1145.01	BARRICADES

LEGEND

GENERAL

- DIRECTION OF TRAFFIC FLOW
- DIRECTION OF PEDESTRIAN TRAFFIC FLOW
- EXIST. PVMT.
- NORTH ARROW
- PROPOSED PVMT.
- TEMP. SHORING (LOCATION PURPOSES ONLY)

SIGNALS

- EXISTING
- PROPOSED
- TEMPORARY

PAVEMENT MARKINGS

- EXISTING LINES
- TEMPORARY LINES

TRAFFIC CONTROL DEVICES

- BARRICADE (TYPE III)
- CONE
- DRUM
- SKINNY DRUM
- TUBULAR MARKER
- TEMPORARY CRASH CUSHION
- FLASHING ARROW BOARD
- FLAGGER
- LAW ENFORCEMENT
- TRUCK MOUNTED ATTENUATOR (TMA)
- CHANGEABLE MESSAGE SIGN

TEMPORARY SIGNING

- PORTABLE SIGN
- STATIONARY SIGN
- STATIONARY OR PORTABLE SIGN

PAVEMENT MARKERS


- CRYSTAL/CRYSTAL
- CRYSTAL/RED
- YELLOW/YELLOW


PAVEMENT MARKING SYMBOLS

- PAVEMENT MARKING SYMBOLS

8/29/2018 R:\ncdot\17BP.6.R.105 (Robeson 431)\VOID-allcurrent files on PW\Traffic\TrafficControl\TCP\TRYING TO PRINT\7BP.6.R.105_TMP_TCO1A.dgn User:GR00KJC

CDM Smith
 CDM Smith Inc.
 5400 Glenwood Avenue
 Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

APPROVED: _____
 DATE: 11/20/2018

 DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED



ROADWAY STANDARD DRAWINGS & LEGEND

MANAGEMENT STRATEGIES

- 1- CLOSE SR 2305 (KITE RD) TO TRAFFIC AND DETOR TRAFFIC OFF-SITE.
- 2- LOCAL ACCESS TO ALL RESIDENCES AND BUSINESSES WILL BE MAINTAINED BETWEEN CLOSURE POINTS AT ALL TIMES DURING CONSTRUCTION.

GENERAL NOTES

CHANGES MAY BE REQUIRED WHEN PHYSICAL DIMENSIONS IN THE DETAIL DRAWINGS, STANDARD DETAILS, AND ROADWAY DETAILS ARE NOT ATTAINABLE TO MEET FIELD CONDITIONS OR RESULT IN DUPLICATE OR UNDESIRED OVERLAPPING OF DEVICES. MODIFICATION MAY INCLUDE: MOVING, SUPPLEMENTING, COVERING, OR REMOVAL OF DEVICES AS DIRECTED BY THE ENGINEER.

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT EXCEPT WHEN OTHERWISE NOTED IN THE PLAN OR DIRECTED BY THE ENGINEER.

TRAFFIC PATTERN ALTERATIONS

- A) NOTIFY THE ENGINEER THIRTY (30) CALENDAR DAYS PRIOR TO ANY TRAFFIC PATTERN ALTERATION.

SIGNING

- B) INSTALL ADVANCE WORK ZONE WARNING SIGNS WHEN WORK IS WITHIN 40 FT FROM THE EDGE OF TRAVEL LANE AND NO MORE THAN THREE (3) DAYS PRIOR TO THE BEGINNING OF CONSTRUCTION.
- C) PROVIDE SIGNING AND DEVICES REQUIRED TO CLOSE THE ROAD ACCORDING TO THE ROADWAY STANDARD DRAWINGS AND TRAFFIC CONTROL PLANS.

PROVIDE SIGNING REQUIRED FOR THE OFF-SITE DETOUR ROUTE AS SHOWN IN THE TRAFFIC CONTROL PLANS.

- D) COVER OR REMOVE ALL SIGNS AND DEVICES REQUIRED TO CLOSE THE ROAD WHEN ROAD CLOSURE IS NOT IN OPERATION.

COVER OR REMOVE ALL SIGNS REQUIRED FOR THE OFF-SITE DETOUR WHEN THE DETOUR IS NOT IN OPERATION.

- E) ENSURE ALL NECESSARY SIGNING IS IN PLACE PRIOR TO ALTERING ANY TRAFFIC PATTERN.

TRAFFIC CONTROL DEVICES

- F) PLACE TYPE III BARRICADES, WITH "ROAD CLOSED" SIGN R11-2 ATTACHED, OF SUFFICIENT LENGTH TO CLOSE ENTIRE ROADWAY.

PHASING

- STEP 1: USING RSD 1101.03 (SHEET 1 OF 9), INSTALL DETOUR ROUTE SIGNING TO CLOSE SR 2305 (KITE RD) FROM STA. 12+00+/- TO STA. 16+35+/- -L-.
- STEP 2: AWAY FROM TRAFFIC, COMPLETE CONSTRUCTION OF PROPOSED BRIDGE AND ROADWAY APPROACHES, INCLUDING DRAINAGE, GUARDRAIL, FINAL PAVEMENT MARKINGS AND MARKERS ON PROPOSED -L- FROM STA. 12+00+/- TO STA. 16+35+/-.
- STEP 3: REMOVE TEMPORARY TRAFFIC CONTROL DEVICES AND OPEN -L- TO PROPOSED 2-LANE, 2-WAY TRAFFIC PATTERN.

LOCAL NOTES


- 1- NOTIFY ROBESON COUNTY EMERGENCY SERVICES AND PUBLIC SCHOOLS AT LEAST ONE MONTH PRIOR TO ROAD CLOSURE.

8/29/2018 R:\ncdot\17BP.6.R.105 (Robeson 431)\VOID-allcurrent files on PW\Traffic\TrafficControl\TCP\TRYING TO PRINT\7BP.6.R.105_TMP_TCOB.dgn User:RROOKJC




CDM Smith Inc.
5400 Glenwood Avenue
Suite 400
Raleigh, NC 27612-3228
NC COA No. F-1255








APPROVED: _____
DATE: 11/20/2018



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



TRANSPORTATION OPERATIONS PLAN




8/29/2018 R:\ncdot\17BP.6.R.105 (Robeson 431)\VOID-allocurrent files on PW\Traffic\TrafficControl\TCP\TRYING TO PRINT\17BP.6.R.105_TMP_TC02.dgn User:RROOKJC

CDM Smith
CDM Smith Inc.
5400 Glenwood Avenue
Suite 400
Raleigh, NC 27612-3228
NC COA No. F-1255

APPROVED: _____
DATE: 11/20/2018

Adam M. Conrad
REGISTERED PROFESSIONAL ENGINEER
ADAM M. CONRAD
200305739041

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



OFF-SITE DETOUR

SIGN NUMBER: name
TYPE: D
QUANTITY: 1

BACKG COLOR: Orange
COPY COLOR: Black

SYMBOL	X	Y	WID	HT

SIGN WIDTH: 2'-0"
HEIGHT: 1'-6"
TOTAL AREA: 3.0 Sq.Ft.

BORDER TYPE: FLUSH
RECESS: 0.38"
WIDTH: 0.63"
RADII: 1.5"

NO. Z BARS: MAT'L: 0.063" (1.6 mm) ALUMINUM
LENGTH:

DESIGN BY: JCC
PROJECT ID: 17BP.6.R.105

CHECKED BY: AMC
LOCATION: ROBESON

Sep 07, 2018
DIV: 6

USE NOTES:

- Legend and border(except those that are colored black) shall be direct applied Grade C sheeting.
- Background shall be Grade B reflective sheeting.
- Shields; A, B, and C type arrows shall be on 0.032" (0.8mm) aluminum with Grade C reflective sheeting and demountable.
- Bottom panel shall be yellow Grade C sheeting. Legend shall be direct applied black non-reflective sheeting. Arrow shall be on 0.032" aluminum, black non-reflective sheeting an demountable. Yellow panel is:

LETTER POSITIONS

Letter locations are panel edge to lower left corner

		Letter Locations					Series/Size
		K	i	t	e		Text Length
		7.6	11	12.1	14		D 2000 8.7
		6.3	9.5	12.4	15.3		D 2000 11.3

FILENAME: 17BP.6.R.105_TMP_TC03

NORTH CAROLINA D.O.T. SIGN DETAIL

Spacing Factor is 1 unless specified otherwise


09/07/18 D:\p\p\cdm\smi\th.com\FW_PLIN\Documents\17240\226510\10 Transport\atfon\04 Client\ Folder Structure\17BP.6.R.105\Traffic\Control\17BP.6.R.105_TMP_TC03.dgn User:CONRADAM

CDM Smith
CDM Smith Inc.
5400 Glenwood Avenue
Suite 400
Raleigh, NC 27612-3228
NC COA No. F-1255

APPROVED: _____
DATE: 11/20/2018

SEAL

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED





SIGN DESIGN

PROJECT: 17BP.6.R.105

**STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION**

**PAVEMENT MARKING PLAN
ROBESON COUNTY**

LOCATION: SR 2305 (KITE ROAD) OVER JACOB SWAMP

<small>TIP NO.</small> 17BP.6.R.105	<small>SHEET NO.</small> PMP-1
<small>APPROVED:</small> _____	
<small>DATE:</small> 11/20/2018	
	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
	

ROADWAY STANDARD DRAWING

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2018 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

<u>STD. NO.</u>	<u>TITLE</u>
1205.01	PAVEMENT MARKINGS - LINE TYPES AND OFFSETS
1205.02	PAVEMENT MARKINGS - TWO-LANE AND MULTILANE ROADWAYS
1205.12	PAVEMENT MARKINGS - BRIDGES
1250.01	RAISED PAVEMENT MARKERS - INSTALLATION SPACING
1251.01	RAISED PAVEMENT MARKERS - PERMANENT AND TEMPORARY
1261.01	GUARDRAIL AND BARRIER DELINEATORS - INSTALLATION SPACING
1261.02	GUARDRAIL AND BARRIER DELINEATORS - TYPES AND MOUNTING
1262.01	GUARDRAIL END DELINEATION

GENERAL NOTES

THE FOLLOWING GENERAL NOTES APPLY AT ALL TIMES FOR THE DURATION OF THE CONSTRUCTION PROJECT, EXCEPT WHEN OTHERWISE NOTED IN THE PLAN, OR DIRECTED BY THE ENGINEER.

- A) INSTALL PAVEMENT MARKINGS AND PAVEMENT MARKERS ON THE FINAL SURFACE AS FOLLOWS:

ROAD NAME	MARKING	MARKER
KITE ROAD	PAINT	PERMANENT RAISED
- B) PLACE TWO APPLICATIONS OF PAINT PAVEMENT MARKINGS ON THE FINAL WEARING SURFACE. PLACE THE SECOND APPLICATION OF PAINT UPON SUFFICIENT DRYING TIME OF THE FIRST.
- C) TIE PROPOSED PAVEMENT MARKING LINES TO EXISTING PAVEMENT MARKING LINES.
- D) REMOVE/REPLACE ANY CONFLICTING/DAMAGED PAVEMENT MARKINGS AND MARKERS.
- E) MARKERS SHALL BE INSTALLED ACCORDING TO THE NCDOT ROADWAY STANDARD DRAWING 1250.01.

SUMMARY OF QUANTITIES

ITEM NO.		ITEM DESCRIPTION	QUANTITY	UNIT
DESC. NO.	SECT. NO.			
4810000000	1205	PAINT PAVEMENT MARKING LINES (4")	3,480	L.F.
4900000000	1251	PERMANENT RAISED PAVEMENT MARKERS	10	EA.

INDEX

<u>SHEET NO.</u>	<u>DESCRIPTION</u>
PMP-1	PAVEMENT MARKING PLAN TITLE SHEET
PMP-2	PAVEMENT MARKING DETAIL

PLAN PREPARED BY: CDM SMITH, INC.


DAVID J. CLOGGO, PE PROJECT MANAGER
ADAM M. CONRAD, PE PROJECT DESIGN ENGINEER



CDM Smith Inc.
5400 Glenwood Avenue
Suite 400
Raleigh, NC 27612-3228
NC COA No. F-1255

PLAN REVIEWED BY: N.C.D.O.T. DIVISION 6


FRANK D. WEST, JR. DIVISION TRAFFIC ENGINEER
RANDY K. WISE, PE DIVISION CONSTRUCTION ENGINEER



TIP NO. 17BP.6.R.105	SHEET NO. PMP-2
APPROVED: _____	
DATE: 11/20/2018	
SEAL 	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
CDM Smith	CDM Smith Inc. 5400 Glenwood Avenue Suite 400 Raleigh, NC 27612-3228 NC COA No. F-1255

PAVEMENT MARKING SCHEDULE	
SYMBOL	DESCRIPTION
	PAINT (4")
PA	WHITE EDGELINE
PI	YELLOW DOUBLE CENTER
	PERMANENT RAISED PAVEMENT MARKERS
MA	YELLOW & YELLOW


NAD 83 NVA 2011



inv:\d\exp\p\1705_105_TMP_PMP02.dgn

PAVEMENT MARKING DETAIL

PROJECT: 17BP.6.R.105



VICINITY MAP


●—●—●—●—● DETOUR ROUTE N.T.S.

EROSION AND SEDIMENT CONTROL MEASURES

Std. #	Description	Symbol
1634.01	Temporary Rock Sediment Dam Type-A	
1634.02	Temporary Rock Sediment Dam Type-B	
1635.01	Rock Pipe Inlet Sediment Trap Type-A	
1635.02	Rock Pipe Inlet Sediment Trap Type-B	
1630.04	Stilling Basin	
1630.06	Special Stilling Basin	
Rock Inlet Sediment Trap:		
1632.01	Type A	
1632.02	Type B	
1632.03	Type C	
	Skimmer Basin	
	Tiered Skimmer Basin	
	Infiltration Basin	

THIS PROJECT CONTAINS EROSION CONTROL PLANS FOR CLEARING AND GRUBBING PHASE OF CONSTRUCTION.

GRAPHIC SCALE



THESE EROSION AND SEDIMENT CONTROL PLANS COMPLY WITH THE REGULATIONS SET FORTH BY THE NCG-010000 GENERAL CONSTRUCTION PERMIT EFFECTIVE AUGUST 1, 2016 AND ISSUED BY THE NORTH CAROLINA DEPARTMENT OF ENVIRONMENTAL QUALITY DIVISION OF WATER RESOURCES.


STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS
PLAN FOR PROPOSED
HIGHWAY EROSION CONTROL
ROBESON COUNTY

**LOCATION: REPLACE BRIDGE 770431 OVER JACOB SWAMP
ON SR 2305 (KITE ROAD)
TYPE OF WORK: GRADING, DRAINAGE, PAVING AND STRUCTURE**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.6.R.105	EC-1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	

EROSION AND SEDIMENT CONTROL MEASURES

Std. #	Description	Symbol
1630.03	Temporary Silt Ditch	
1630.05	Temporary Diversion	
1605.01	Temporary Silt Fence	
1606.01	Special Sediment Control Fence	
1622.01	Temporary Berms and Slope Drains	
1630.02	Silt Basin Type B	
1633.01	Temporary Rock Silt Check Type-A	
	Temporary Rock Silt Check Type-A with Matting and Polyacrylamide (PAM)	
1633.02	Temporary Rock Silt Check Type-B	
	Wattle / Coir Fiber Wattle	
	Wattle / Coir Fiber Wattle with Polyacrylamide (PAM)	



Prepared in the Office of:
MI ENGINEERING, PLLC
1011 SCHAUB DRIVE, SUITE 100
RALEIGH, NC 27606

Designed by:
KAREN HEFNER, PE 3428
NAME LEVEL III CERTIFICATION NO.

Reviewed in the Office of:
ROADSIDE ENVIRONMENTAL UNIT
1 South Wilmington St.
Raleigh, NC 27611

2018 STANDARD SPECIFICATIONS

Reviewed by:
MARK STALEY, CPESC, CPSWQ


Roadway Standard Drawings

The following roadway english standards as appear in "Roadway Standard Drawings"- Roadway Design Unit - N. C. Department of Transportation - Raleigh, N. C., dated January 2018 and the latest revision thereto are applicable to this project and by reference hereby are considered a part of these plans.

1604.01 Railroad Erosion Control Detail	1632.01 Rock Inlet Sediment Trap Type A
1605.01 Temporary Silt Fence	1632.02 Rock Inlet Sediment Trap Type B
1606.01 Special Sediment Control Fence	1632.03 Rock Inlet Sediment Trap Type C
1607.01 Gravel Construction Entrance	1633.01 Temporary Rock Silt Check Type A
1622.01 Temporary Berms and Slope Drains	1633.02 Temporary Rock Silt Check Type B
1630.01 Riser Basin	1634.01 Temporary Rock Sediment Dam Type A
1630.02 Silt Basin Type B	1634.02 Temporary Rock Sediment Dam Type B
1630.03 Temporary Silt Ditch	1635.01 Rock Pipe Inlet Sediment Trap Type A
1630.04 Stilling Basin	1635.02 Rock Pipe Inlet Sediment Trap Type B
1630.05 Temporary Diversion	1640.01 Coir Fiber Baffle
1630.06 Special Stilling Basin	1645.01 Temporary Stream Crossing
1631.01 Matting Installation	

PROJECT REFERENCE NO. 17BP.6.R.105	SHEET NO. EC-2
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

TEMPORARY ROCK SILT CHECK TYPE 'A' WITH EXCELSIOR MATTING AND POLYACRYLAMIDE (PAM)



PLAN


NOTES:

INSTALL TEMPORARY ROCK SILT CHECK TYPE A IN ACCORDANCE WITH ROADWAY STANDARD DRAWING NO. 1633.01.


USE EXCELSIOR FOR MATTING MATERIAL AND ANCHOR MATTING SECTION AT TOP AND BOTTOM WITH CLASS B STONE.

PRIOR TO POLYACRYLAMIDE (PAM) APPLICATION, OBTAIN A SOIL SAMPLE FROM PROJECT LOCATION, AND FROM OFFSITE MATERIAL, AND ANALYZE FOR APPROPRIATE PAM FLOCCULANT TO BE APPLIED TO EACH ROCK SILT CHECK.


INITIALLY APPLY 4 OUNCES OF POLYACRYLAMIDE (PAM) TO TOP OF MATTING SECTION AND AFTER EVERY RAINFALL EVENT THAT EQUALS OR EXCEEDS 0.50 INCHES.



INSET A



SECTION A-A




SECTION B-B


NOT TO SCALE

PROJECT REFERENCE NO. 17BP.6.R.105	SHEET NO. EC-2A
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

SILT FENCE WATTLE BREAK DETAIL



ISOMETRIC VIEW





VIEW FROM SLOPE

NOTES:

- USE MINIMUM 12 IN. DIAMETER EXCELSIOR WATTLE AND LENGTH OF 10 FT.
- EXCAVATE A 1 TO 2 INCH TRENCH FOR WATTLE TO BE PLACED.
- DO NOT PLACE WATTLE ON TOE OF SLOPE.
- USE 2 FT. WOODEN STAKES WITH A 2 IN. BY 2 IN. NOMINAL CROSS SECTION.
- INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO GROUND.
- PROVIDE STAPLES MADE OF 0.125 IN. DIAMETER STEEL WIRE FORMED INTO A U SHAPE NOT LESS THAN 12" IN LENGTH.
- INSTALL STAPLES APPROXIMATELY EVERY 1 LINEAR FOOT ON BOTH SIDES OF WATTLE AND AT EACH END TO SECURE IT TO THE SOIL.
- WATTLE INSTALLATION CAN BE ON OUTSIDE OF THE SILT FENCE AS DIRECTED.
- INSTALL TEMPORARY SILT FENCE IN ACCORDANCE WITH SECTION 1605 OF THE STANDARD SPECIFICATIONS.

INSET A



SIDE VIEW



DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA

PROJECT REFERENCE NO. <i>17BP.6.R.105</i>	SHEET NO. <i>EC-3</i>
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

SOIL STABILIZATION TIMEFRAMES




<i>SITE DESCRIPTION</i>	<i>STABILIZATION TIME</i>	<i>TIMEFRAME EXCEPTIONS</i>
PERIMETER DIKES, SWALES, DITCHES AND SLOPES	7 DAYS	NONE
HIGH QUALITY WATER (HQW) ZONES	7 DAYS	NONE
SLOPES STEEPER THAN 3:1	7 DAYS	IF SLOPES ARE 10' OR LESS IN LENGTH AND ARE NOT STEEPER THAN 2:1, 14 DAYS ARE ALLOWED.
SLOPES 3:1 OR FLATTER	14 DAYS	7 DAYS FOR SLOPES GREATER THAN 50' IN LENGTH.
ALL OTHER AREAS WITH SLOPES FLATTER THAN 4:1	14 DAYS	NONE, EXCEPT FOR PERIMETERS AND HQW ZONES.

PROJECT REFERENCE NO. 17BP.6.R.105	SHEET NO. EC-05/CONST.04
R/W SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
CDM Smith	ME Engineering, PLLC
NOTE: UTILIZE SPECIAL STILLING BASIN(S) WHERE APPLICABLE.	



-L-
 PI Sta 15+05.82
 $\Delta = 27^{\circ}00'05.4''$ (RT)
 $D = 4'10''01.1''$
 $L = 647.99'$
 $T = 330.13'$
 $R = 1,375.00'$
 $e = 0.04$
 $RO = 88'$
 $DS = 55$ mph


3
 JAMES G & MELINDA C. REVELS
 NAD 83/NA 2011



8/17/99
 REVISIONS
 TIME
 C
 1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526
 527
 528
 529
 530
 531
 532
 533
 534
 535
 536
 537
 538
 539
 540
 541
 542
 543
 544
 545
 546
 547
 548
 549
 550
 551
 552
 553
 554
 555
 556
 557
 558
 559
 560
 561
 562
 563
 564
 565
 566
 567
 568
 569
 570
 571
 572
 573
 574
 575
 576
 577
 578
 579
 580
 581
 582
 583
 584
 585
 586
 587
 588
 589
 590
 591
 592
 593
 594
 595
 596
 597
 598
 599
 600
 601
 602
 603
 604
 605
 606
 607
 608
 609
 610
 611
 612
 613
 614
 615
 616
 617
 618
 619
 620
 621
 622
 623
 624
 625
 626
 627
 628
 629
 630
 631
 632
 633
 634
 635
 636
 637
 638
 639
 640
 641
 642
 643
 644
 645
 646
 647
 648
 649
 650
 651
 652
 653
 654
 655
 656
 657
 658
 659
 660
 661
 662
 663
 664
 665
 666
 667
 668
 669
 670
 671
 672
 673
 674
 675
 676
 677
 678
 679
 680
 681
 682
 683
 684
 685
 686
 687
 688
 689
 690
 691
 692
 693
 694
 695
 696
 697
 698
 699
 700
 701
 702
 703
 704
 705
 706
 707
 708
 709
 710
 711
 712
 713
 714
 715
 716
 717
 718
 719
 720
 721
 722
 723
 724
 725
 726
 727
 728
 729
 730
 731
 732
 733
 734
 735
 736
 737
 738
 739
 740
 741
 742
 743
 744
 745
 746
 747
 748
 749
 750
 751
 752
 753
 754
 755
 756
 757
 758
 759
 760
 761
 762
 763
 764
 765
 766
 767
 768
 769
 770
 771
 772
 773
 774
 775
 776
 777
 778
 779
 780
 781
 782
 783
 784
 785
 786
 787
 788
 789
 790
 791
 792
 793
 794
 795
 796
 797
 798
 799
 800
 801
 802
 803
 804
 805
 806
 807
 808
 809
 810
 811
 812
 813
 814
 815
 816
 817
 818
 819
 820
 821
 822
 823
 824
 825
 826
 827
 828
 829
 830
 831
 832
 833
 834
 835
 836
 837
 838
 839
 840
 841
 842
 843
 844
 845
 846
 847
 848
 849
 850
 851
 852
 853
 854
 855
 856
 857
 858
 859
 860
 861
 862
 863
 864
 865
 866
 867
 868
 869
 870
 871
 872
 873
 874
 875
 876
 877
 878
 879
 880
 881
 882
 883
 884
 885
 886
 887
 888
 889
 890
 891
 892
 893
 894
 895
 896
 897
 898
 899
 900
 901
 902
 903
 904
 905
 906
 907
 908
 909
 910
 911
 912
 913
 914
 915
 916
 917
 918
 919
 920
 921
 922
 923
 924
 925
 926
 927
 928
 929
 930
 931
 932
 933
 934
 935
 936
 937
 938
 939
 940
 941
 942
 943
 944
 945
 946
 947
 948
 949
 950
 951
 952
 953
 954
 955
 956
 957
 958
 959
 960
 961
 962
 963
 964
 965
 966
 967
 968
 969
 970
 971
 972
 973
 974
 975
 976
 977
 978
 979
 980
 981
 982
 983
 984
 985
 986
 987
 988
 989
 990
 991
 992
 993
 994
 995
 996
 997
 998
 999
 1000

09, 08, 95

PROJECT: 17BP.6.R.105



VICINITY MAP
 ●—●—● DETOUR ROUTE N.T.S.

STATE OF NORTH CAROLINA
 DIVISION OF HIGHWAYS


UTILITIES BY OTHERS PLANS
ROBESON COUNTY

LOCATION: REPLACE BRIDGE 770431 OVER JACOB SWAMP
 ON SR 2305 (KITE ROAD)


TYPE OF WORK: POWER (DISTRIBUTION) AND COMMUNICATIONS

T.I.P. NO.	SHEET NO.
17BP.6.R.105	UO-1

NOTE:
 ALL UTILITY WORK SHOWN ON THIS SHEET WILL BE DONE BY OTHERS. NO PAYMENT WILL BE MADE TO THE CONTRACTOR FOR UTILITY WORK SHOWN ON THIS SHEET.



4



INDEX OF SHEETS

SHEET NO.:	DESCRIPTION:
UO-1	TITLE SHEET
UO-2	UBO PLAN SHEET

UTILITY OWNERS WITH CONFLICTS


(A) POWER (DISTRIBUTION) - LUMBEE RIVER EMC
 (B) COMMUNICATIONS - AT&T
 (C) COMMUNICATIONS - SPIRIT
 (D) COMMUNICATIONS - SPECTRUM

PREPARED IN THE OFFICE OF:

SO-DEEP | SAM NCTM

SO-DEEP | SAM NC, Inc.
 A SAM COMPANY
 2800-154 Sumner Boulevard, Raleigh, NC 27616 Tel 919-878-7466

Keith Garry UTILITY PROJECT MANAGER
 Doug Joyner PROJECT UTILITY COORDINATOR



DIVISION OF HIGHWAYS
 DIVISION 6
 DIV ADDRESS
 558 GILLESPIE ST.
 FAYETTEVILLE, NC 28301

Rick Handlin DIVISION CONTACT #1
 Randy Rogers DIVISION CONTACT #2

\$\$\$\$\$ SYSTEM \$\$\$\$\$\$
 \$\$\$ DGN \$\$\$
 \$\$\$ USERNAME \$\$\$

UTILITIES BY OTHERS



ALL PROPOSED UTILITY WORK SHOWN ON THIS SHEET WILL BE DONE BY OTHERS. NO PAYMENT WILL BE MADE TO THE CONTRACTOR FOR PROPOSED UTILITY WORK SHOWN ON THIS SHEET.

8/17/99

3

JAMES G & MELINDA C. REVELS

NAD 83NA 2011




REVISIONS

8/17/99
 17BP.6.R.105
 U0-2
 THIS SHEET CORRESPONDS TO RDY-4

CROSS SECTION SHEET INDEX

X-1 CROSS SECTION SHEET INDEX
X-2 THRU X-4 -L-

Note: Approximate quantities only. Unclassified Excavation, Borrow Excavation, Fine Grading, Clearing and Grubbing, and Removal of Existing Pavement will be paid for at the contract lump sum price for "Grading."



Note: Approximate quantities only. Unclassified Excavation, Borrow Excavation, Fine Grading, Clearing and Grubbing, and Removal of Existing Pavement will be paid for at the contract lump sum price for "Grading."

13 + 88.77
BEGIN BRIDGE STA. 13 + 88.77

PROPOSED DRIVEWAY

PROPOSED DRIVEWAY

13 + 50.00

PROPOSED DRIVEWAY

PROPOSED DRIVEWAY

13 + 00.00

12 + 50.00


12 + 00.00
BEGIN PROJECT STA. 12 + 00.00

11 + 50.00

EXIST

EXIST


6/23/16



-SYSTEME:\XSC\17BP\6.R.105\Fduj-XPL-L.dgn
USER:PROJ\JC

6/23/16


0 2.5 5	PROJ. REFERENCE NO.	SHEET NO.
	17BP.6.R.105	X-4



-SYSTEME:\XSS\17BP.6.R.105_Rdwy_XPL_L.dgn
USER:PROJ\JC

CONTRACT: DF00238 PROJECT: 17BP.6.R.105

STRUCTURE



VICINITY MAP

●●●● OFF-SITE DETOUR ROUTE



STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

ROBESON COUNTY

**LOCATION: REPLACE BRIDGE 431 OVER JACOB SWAMP
ON SR 2305 (KITE ROAD)**

TYPE OF WORK: GRADING, DRAINAGE, PAVING, AND STRUCTURE

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	17BP.6.R.105		19
STATE PROJ. NO.	F. A. PROJ. NO.	DESCRIPTION	
17BP.6.R.105	N/A	P.E.	
17BP.6.R.105	N/A	UTIL. & RW	
17BP.6.R.105	N/A	CONSTR.	



DESIGN DATA

ADT 2018	=	770 VPD
ADT 2038	=	1000 VPD
DHV	=	N/A %
D	=	N/A %
T	=	7 %
V	=	55 MPH
FUNC CLASS = LOCAL SUB-REGIONAL TIER		

PROJECT LENGTH

LENGTH ROADWAY PROJECT 17BP.6.R.105	=	0.065 MILES
LENGTH STRUCTURE PROJECT 17BP.6.R.105	=	0.017 MILES
TOTAL LENGTH OF PROJECT 17BP.6.R.105	=	0.082 MILES

Prepared in the Office of:

CDM Smith
CDM Smith Inc.
5400 Glenwood Avenue
Suite 400
Raleigh, NC 27612-3228
NC CDA No. F-1255

FOR THE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

2018 STANDARD SPECIFICATIONS

LETTING DATE : DECEMBER 19, 2018

DAVID J. CLODGO, P.E.
PROJECT ENGINEER


TING H. FANG, P.E.
PROJECT DESIGN ENGINEER

Professional Engineer Seal for Ting H. Fang, No. 16301, State of North Carolina.

11/8/2018

GRADE DATA -L-
PVI STA. = 13+45.00 -L-
PVI EL. = 112.50'
V.C. = 80'

GRADE DATA -L-
PVI STA. = 15+25.00 -L-
PVI EL. = 111.96'
V.C. = 80'





SECTION ALONG -L-
(SECTIONS AT END BENTS AND BENT ARE AT RIGHT ANGLES)

I HEREBY CERTIFY THESE PLANS ARE THE AS-BUILT PLANS

HORIZONTAL CURVE DATA -L-

PI STA. = 15+05.82
Δ = 27°-00'-05.4" (RT.)
D = 4°-10'-01.1"
L = 647.99'
T = 330.13'
R = 1,375.00'



PLAN
(PILES NOT SHOWN FOR CLARITY)


PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
STATION: 14+35.00 -L- POC

SHEET 1 OF 3 REPLACES BRIDGE NO. 431

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
GENERAL DRAWING
FOR BRIDGE OVER
JACOB SWAMP ON SR 2305
BETWEEN SR 2289 & NC 72

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


CDM Smith
CDM SMITH
5400 Glenwood Avenue, Suite 400
Raleigh, NC 27612-3228
NC COA No. F-1255
DRAWN BY: VDK DATE: 07/18
CHECKED BY: THF DATE: 07/18
DESIGN ENGINEER: VDK DATE: 07/18
DWG. No.



REVISIONS					
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

SHEET NO. S-01
TOTAL SHEETS 19

FILE: c:\pwworking\cdm\1783701_001_17BP6R105_S&U_G001_001.dgn
DATE: 10/2/2018 10:56:19 AM



FOUNDATION LAYOUT

DIMENSIONS LOCATING PILES ARE SHOWN TO THE CENTERLINE OF PILES. ALL PILES ARE VERTICAL.

NOTES

- FOR PILES, SEE SECTION 450 OF THE STANDARD SPECIFICATIONS.
- PILES AT END BENT 1 ARE DESIGNED FOR A FACTORED RESISTANCE OF 75 TONS PER PILE.
- PILES AT BENT 1 ARE DESIGNED FOR A FACTORED RESISTANCE OF 100 TONS PER PILE.
- PILES AT END BENT 2 ARE DESIGNED FOR A FACTORED RESISTANCE OF 55 TONS PER PILE.
- DRIVE PILES AT END BENT 1 TO A REQUIRED DRIVING RESISTANCE OF 125 TONS PER PILE.
- DRIVE PILES AT BENT 1 TO A REQUIRED DRIVING RESISTANCE OF 170 TONS PER PILE.
- DRIVE PILES AT END BENT 2 TO A REQUIRED DRIVING RESISTANCE OF 95 TONS PER PILE.
- THE SCOUR CRITICAL ELEVATION FOR BENT 1 IS ELEVATION 95 FT. SCOUR CRITICAL ELEVATIONS ARE USED TO MONITOR POSSIBLE SCOUR PROBLEM DURING THE LIFE OF THE STRUCTURE.
- TESTING PILES WITH THE PDA DURING DRIVING, RESTRIKING OR REDRIVING MAY BE REQUIRED. THE ENGINEER WILL DETERMINE THE NEED FOR PDA TESTING. FOR PDA TESTING, SEE SECTION 450 OF THE STANDARD SPECIFICATIONS.

PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
 STATION: 14+35.00 -L- POC
 SHEET 2 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

GENERAL DRAWING

FOR BRIDGE OVER
 JACOB SWAMP ON SR 2305
 BETWEEN SR 2289 & NC 72

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-02
1			3			TOTAL SHEETS
2			4			19

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

DRAWN BY : VDK DATE : 07/18
 CHECKED BY : THF DATE : 07/18
 DESIGN ENGINEER : VDK DATE : 07/18

DWG. No.

NORTH CAROLINA
 PROFESSIONAL
 SEAL
 04707
 ENGINEER
 VENKATA D.T. KOLLUPARA
 10/27/2018

FILE: c:\pwworking\cdm\17BP6R105_001_003_17BP6R105_SML_GDD2_002.dgn
 DATE: 10/22/18 10:56:30 AM

TOTAL BILL OF MATERIAL																			
	REMOVAL OF EXISTING STRUCTURE	ASBESTOS ASSESSMENT	PDA TESTING	UNCLASSIFIED STRUCTURE EXCAVATION	CLASS A CONCRETE	BRIDGE APPROACH SLABS	REINFORCING STEEL	PILE DRIVING EQUIPMENT SETUP FOR HP 12X53 STEEL PILES	PILE DRIVING EQUIPMENT SETUP FOR HP 14X73 GALVANIZED STEEL PILES	HP 12 X 53 STEEL PILES		HP 14 X 73 GALVANIZED STEEL PILES		VERTICAL CONCRETE BARRIER RAIL	RIP RAP CLASS II (2'-0" THICK)	GEOTEXTILE FOR DRAINAGE	ELASTOMERIC BEARINGS	3'-0" X 1'-9" PRESTRESSED CONCRETE CORED SLABS	
	LUMP SUM	LUMP SUM	EA.	LUMP SUM	CU. YDS.	LUMP SUM	LBS.	EA.	EA.	NO.	LIN. FT.	NO.	LIN. FT.	LIN. FT.	TON	SO. YD.	LUMP SUM	NO.	LIN. FT.
SUPERSTRUCTURE														180.26			LUMP SUM	22	990
END BENT 1				LUMP SUM	14.5		2,131	7		7	385.0				95	105			
BENT 1					11.3		2,127		8			8	480.0						
END BENT 2				LUMP SUM	14.5		2,131	7		7	350.0				70	75			
TOTAL	LUMP SUM	LUMP SUM	1	LUMP SUM	40.3	LUMP SUM	6,389	14	8	14	735.0	8	480.0	180.26	165	180	LUMP SUM	22	990

NOTES:

ASSUMED LIVE LOAD = HL-93 OR ALTERNATE LOADING.

THIS BRIDGE HAS BEEN DESIGNED IN ACCORDANCE WITH THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS

THIS BRIDGE IS LOCATED IN SEISMIC PERFORMANCE ZONE 1.

FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE SHEET SN.

FOR EROSION CONTROL MEASURES SEE EROSION CONTROL PLANS.

THIS STRUCTURE HAS BEEN DESIGNED IN ACCORDANCE WITH "HEC-18 EVALUATING SCOUR AT BRIDGES".

REMOVAL OF THE EXISTING BRIDGE SHALL BE PERFORMED SO AS NOT TO ALLOW DEBRIS TO FALL INTO THE WATER. THE CONTRACTOR SHALL REMOVE THE BRIDGE AND SUBMIT PLANS FOR DEMOLITION IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS.

THE SUBSTRUCTURE OF THE EXISTING BRIDGE INDICATED ON THE PLANS IS FROM THE BEST INFORMATION AVAILABLE. SINCE THIS INFORMATION IS SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR, THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT OF TRANSPORTATION FOR ANY DELAYS OR ADDITIONAL COST INCURRED BASED ON DIFFERENCES BETWEEN THE EXISTING BRIDGE SUBSTRUCTURE SHOWN ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

INASMUCH AS THE PAINT SYSTEM ON THE EXISTING STRUCTURAL STEEL CONTAINS LEAD, THE CONTRACTOR'S ATTENTION IS DIRECTED TO ARTICLE 107-1 OF THE STANDARD SPECIFICATIONS. ANY COSTS RESULTING FROM COMPLIANCE WITH APPLICABLE STATE OR FEDERAL REGULATIONS PERTAINING TO HANDLING OF MATERIALS CONTAINING LEAD BASED PAINT SHALL BE INCLUDED IN THE BID PRICE FOR "REMOVAL OF EXISTING STRUCTURE AT STATION 14+35.00 -L-".

FOR BENT 1, ONLY PARTIAL GALVANIZING OF THE PILES IS REQUIRED. SEE BENT 1 SHEET FOR REQUIRED GALVANIZED LENGTHS. PAYMENT FOR PARTIALLY GALVANIZED PILES WILL BE MADE UNDER THE CONTRACT UNIT PRICE FOR GALVANIZED STEEL PILES.

THE MATERIAL SHOWN IN THE CROSS-HATCHED AREA SHALL BE EXCAVATED FOR A DISTANCE OF 10 FT. LEFT SIDE, 30 FT. RIGHT SIDE, AT END BENTS 1 AND 27 FT. LEFT SIDE, 23 FT. RIGHT SIDE AT END BENT 2 OF CENTERLINE ROADWAY AS DIRECTED BY THE ENGINEER. THIS WORK WILL BE PAID FOR AT THE CONTRACT LUMP SUM PRICE FOR UNCLASSIFIED STRUCTURE EXCAVATION. SEE SECTION 412 OF THE STANDARD SPECIFICATIONS.

THE EXISTING STRUCTURE CONSISTING OF 2 SPANS: 1 @ 41'-0" AND 1 @ 40'-0" WITH CLEAR ROADWAY WIDTH OF 24'-0" AND STEEL PLANK FLOOR ON I-BEAMS, STD. BMD-10; SUBSTRUCTURE CONSISTING OF TIMBER CAPS ON TIMBER PILES AT END BENTS AND INTERIOR BENT EXCEPT RIGHT SIDE PILE AT INTERIOR BENT WHICH IS A CONCRETE ENCASED TIMBER PILE AND LOCATED AT THE SITE OF THE PROPOSED BRIDGE SHALL BE REMOVED. THE EXISTING BRIDGE IS PRESENTLY POSTED FOR LOAD LIMIT.

AT THE CONTRACTOR'S OPTION, PRESTRESSED CONCRETE END BENT AND BENT CAPS MAY BE SUBSTITUTED IN PLACE OF THE CAST-IN-PLACE CAPS. THE CONTRACTOR SHALL COORDINATE WITH THE RESIDENT ENGINEER TO RECEIVE REVISED PLANS AND DETAILS FROM THE STRUCTURES MANAGEMENT UNIT. THE REDESIGN AND ANY ADDITIONAL MATERIALS NEEDED WILL BE AT NO ADDITIONAL COST TO THE CONTRACTOR.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.


FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

FOR ASBESTOS ASSESSMENT FOR BRIDGE DEMOLITION AND RENOVATION ACTIVITIES, SEE SPECIAL PROVISIONS.

ASPHALT WEARING SURFACE IS INCLUDED IN ROADWAY QUANTITY ON ROADWAY PLANS.

B.M. #: 1 RR SPIKE IN 10" OAK 28.37' LEFT OF STA. 14+76.41 -L-, EL. 110.97



LOCATION SKETCH

HYDRAULIC DATA

DESIGN DISCHARGE	= 360 CFS
FREQUENCY OF DESIGN FLOOD	= 2 YR.
DESIGN HIGH WATER ELEVATION	= 107.0 FT.
DRAINAGE AREA	= 15.5 SQ. MI.
BASE DISCHARGE (Q100)	= 1940 CFS
BASE HIGH WATER ELEVATION	= 110.9 FT.
DESIGN MAINTAINS EXISTING LEVEL OF SERVICE	

OVERTOPPING FLOOD DATA

OVERTOPPING DISCHARGE	= 490 CFS
FREQUENCY OF OVERTOPPING FLOOD	= 5(-) YRS.
OVERTOPPING FLOOD ELEVATION	= 108.1 FT. *

* AT EXISTING SAG PT. APPROX. 2000 FT EAST OF BRIDGE

PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
 STATION: 14+35.00 -L- POC

SHEET 3 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

GENERAL DRAWING

FOR BRIDGE OVER
 JACOB SWAMP ON SR 2305
 BETWEEN SR 2289 & NC 72

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

CHECKED BY: VDK DATE: 07/18
 THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.

NORTH CAROLINA PROFESSIONAL SEAL 04707 ENGINEER VENKATA D.T. KOLLUPARA

10/27/2018

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-S-03
1			3			TOTAL SHEETS
2			4			19

LOAD AND RESISTANCE FACTOR RATING (LRFD) SUMMARY FOR PRESTRESSED CORED SLAB UNITS

LEVEL	VEHICLE	WEIGHT (W) (TONS)	CONTROLLING LOAD RATING	MINIMUM RATING FACTORS (RF)	TONS = W X RF	STRENGTH I LIMIT STATE								SERVICE III LIMIT STATE								COMMENT NUMBER		
						MOMENT				SHEAR				MOMENT										
						LIVELOAD FACTORS	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (ft)	LIVELOAD FACTORS	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION		DISTANCE FROM LEFT END OF SPAN (ft)	
DESIGN LOAD RATING	HL-93(Inv)	N/A	1	1.065	--	1.75	0.27	1.25	55'	EL	26.982	0.616	1.12	55'	EL	5.396	0.80	0.27	1.07	55'	EL	26.982		
	HL-93(Opr)	N/A	--	1.452	--	1.35	0.27	1.61	55'	EL	26.982	0.616	1.45	55'	EL	5.396	N/A	--	--	--	--	--		
	HS-20(Inv)	36.000	2	1.335	48.043	1.75	0.27	1.56	55'	EL	26.982	0.616	1.34	55'	EL	5.396	0.80	0.27	1.33	55'	EL	26.982		
	HS-20(Opr)	36.000	--	1.734	62.425	1.35	0.27	2.02	55'	EL	26.982	0.616	1.73	55'	EL	5.396	N/A	--	--	--	--	--		
LEGAL LOAD RATING	SV	SNSH	13.500	--	2.802	37.83	1.4	0.27	4.09	55'	EL	26.982	0.616	3.81	55'	EL	5.396	0.80	0.27	2.80	55'	EL	26.982	
		SNGARBS2	20.000	--	2.175	43.506	1.4	0.27	3.18	55'	EL	26.982	0.616	2.76	55'	EL	5.396	0.80	0.27	2.18	55'	EL	26.982	
		SNAGRIS2	22.000	--	2.099	46.173	1.4	0.27	3.07	55'	EL	26.982	0.616	2.58	55'	EL	5.396	0.80	0.27	2.10	55'	EL	26.982	
		SNCOTTS3	27.250	--	1.397	38.065	1.4	0.27	2.04	55'	EL	26.982	0.616	1.91	55'	EL	5.396	0.80	0.27	1.40	55'	EL	26.982	
		SNAGGRS4	34.925	--	1.2	41.922	1.4	0.27	1.75	55'	EL	26.982	0.616	1.62	55'	EL	5.396	0.80	0.27	1.20	55'	EL	26.982	
		SNS5A	35.550	--	1.172	41.648	1.4	0.27	1.71	55'	EL	26.982	0.616	1.66	55'	EL	5.396	0.80	0.27	1.17	55'	EL	26.982	
	TTST	SNS6A	39.950	--	1.089	43.514	1.4	0.27	1.59	55'	EL	26.982	0.616	1.53	55'	EL	5.396	0.80	0.27	1.09	55'	EL	26.982	
		SNS7B	42.000	--	1.038	43.587	1.4	0.27	1.52	55'	EL	26.982	0.616	1.53	55'	EL	5.396	0.80	0.27	1.04	55'	EL	26.982	
		TNAGRIT3	33.000	--	1.333	43.973	1.4	0.27	1.95	55'	EL	26.982	0.616	1.81	55'	EL	5.396	0.80	0.27	1.33	55'	EL	26.982	
		TNT4A	33.075	--	1.342	44.4	1.4	0.27	1.96	55'	EL	26.982	0.616	1.75	55'	EL	5.396	0.80	0.27	1.34	55'	EL	26.982	
		TNT6A	41.600	--	1.112	46.252	1.4	0.27	1.62	55'	EL	26.982	0.616	1.67	55'	EL	5.396	0.80	0.27	1.11	55'	EL	26.982	
		TNT7A	42.000	--	1.125	47.255	1.4	0.27	1.64	55'	EL	26.982	0.616	1.56	55'	EL	5.396	0.80	0.27	1.13	55'	EL	26.982	
		TNT7B	42.000	--	1.174	49.318	1.4	0.27	1.72	55'	EL	26.982	0.616	1.47	55'	EL	5.396	0.80	0.27	1.17	55'	EL	26.982	
		TNAGRIT4	43.000	--	1.111	47.786	1.4	0.27	1.62	55'	EL	26.982	0.616	1.42	55'	EL	5.396	0.80	0.27	1.11	55'	EL	26.982	
		TNAGT5A	45.000	--	1.041	46.851	1.4	0.27	1.52	55'	EL	26.982	0.616	1.44	55'	EL	5.396	0.80	0.27	1.04	55'	EL	26.982	
TNAGT5B	45.000	3	1.023	46.02	1.4	0.27	1.49	55'	EL	26.982	0.616	1.35	55'	EL	5.396	0.80	0.27	1.02	55'	EL	26.982			

LOAD FACTORS:

DESIGN LOAD RATING FACTORS	LIMIT STATE	γ_{DC}	γ_{DW}
	STRENGTH I	1.25	1.50
	SERVICE III	1.00	1.00

NOTES:

MINIMUM RATING FACTORS ARE BASED ON THE STRENGTH I AND SERVICE III LIMIT STATES.

ALLOWABLE STRESSES FOR SERVICE III LIMIT STATE ARE AS REQUIRED FOR DESIGN.

COMMENTS:

- 1.
- 2.
- 3.
- 4.

CONTROLLING LOAD RATING

1 DESIGN LOAD RATING (HL-93)


2 DESIGN LOAD RATING (HS-20)

3 LEGAL LOAD RATING **

** SEE CHART FOR VEHICLE TYPE

GIRDER LOCATION

I - INTERIOR GIRDER
EL - EXTERIOR LEFT GIRDER
ER - EXTERIOR RIGHT GIRDER



PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
STATION: 14+35.00 -L- POC

SHEET 1 OF 2

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

**LRFR SUMMARY FOR
55' CORED SLAB UNIT
75° SKEW, SPAN A
(NON-INTERSTATE TRAFFIC)**

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith

CDM SMITH
5400 Glenwood Avenue, Suite 400
Raleigh, NC 27612-3228
NC COA No. F-1255

DRAWN BY : VDK DATE : 07/18
CHECKED BY : THF DATE : 07/18
DESIGN ENGINEER : VDK DATE : 07/18

DWG. No.

STATE OF NORTH CAROLINA
PROFESSIONAL
SEAL
04707
ENGINEER
VENKATA D.T. KOLLUPARA

10/2/2018

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		
TOTAL SHEETS					S-04
19					

LOAD AND RESISTANCE FACTOR RATING (LRFD) SUMMARY FOR PRESTRESSED CORED SLAB UNITS

LEVEL	VEHICLE	WEIGHT (W) (TONS)	CONTROLLING LOAD RATING	MINIMUM RATING FACTORS (RF)	TONS = W X RF	STRENGTH I LIMIT STATE										SERVICE III LIMIT STATE					COMMENT NUMBER			
						MOMENT					SHEAR					MOMENT								
						LIVELOAD FACTORS	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (FT)	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN	GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (FT)	LIVELOAD FACTORS	DISTRIBUTION FACTORS (DF)	RATING FACTOR	SPAN		GIRDER LOCATION	DISTANCE FROM LEFT END OF SPAN (FT)	
DESIGN LOAD RATING	HL-93(Inv)	N/A	1	1.06	--	1.75	0.275	1.38	35'	EL	16.982	0.623	1.2	35'	EL	1.698	0.80	0.275	1.06	35'	EL	16.982		
	HL-93(0pr)	N/A	--	1.549	--	1.35	0.275	1.79	35'	EL	16.982	0.623	1.55	35'	EL	1.698	N/A	--	--	--	--	--		
	HS-20(Inv)	36.000	2	1.377	49.573	1.75	0.275	1.82	35'	EL	13.586	0.623	1.38	35'	EL	1.698	0.80	0.275	1.41	35'	EL	16.982		
	HS-20(0pr)	36.000	--	1.785	64.262	1.35	0.275	2.36	35'	EL	13.586	0.623	1.79	35'	EL	1.698	N/A	--	--	--	--	--		
LEGAL LOAD RATING	SV	SNSH	13.500	--	2.424	32.72	1.4	0.275	3.95	35'	EL	16.982	0.623	3.55	35'	EL	1.698	0.80	0.275	2.42	35'	EL	16.982	
		SNGARBS2	20.000	--	2.082	41.635	1.4	0.275	3.34	35'	EL	13.586	0.623	2.68	35'	EL	1.698	0.80	0.275	2.08	35'	EL	13.586	
		SNAGRIS2	22.000	--	2.076	45.668	1.4	0.275	3.31	35'	EL	13.586	0.623	2.56	35'	EL	1.698	0.80	0.275	2.08	35'	EL	13.586	
		SNCOTTS3	27.250	--	1.213	33.066	1.4	0.275	1.98	35'	EL	16.982	0.623	1.79	35'	EL	1.698	0.80	0.275	1.21	35'	EL	16.982	
		SNAGGRS4	34.925	--	1.123	39.207	1.4	0.275	1.83	35'	EL	16.982	0.623	1.6	35'	EL	1.698	0.80	0.275	1.12	35'	EL	16.982	
		SNS5A	35.550	--	1.09	38.739	1.4	0.275	1.77	35'	EL	16.982	0.623	1.69	35'	EL	1.698	0.80	0.275	1.09	35'	EL	16.982	
		SNS6A	39.950	--	1.052	42.014	1.4	0.275	1.71	35'	EL	16.982	0.623	1.58	35'	EL	1.698	0.80	0.275	1.05	35'	EL	16.982	
	TTST	SNS7B	42.000	3	1.004	42.153	1.4	0.275	1.63	35'	EL	16.982	0.623	1.62	35'	EL	1.698	0.80	0.275	1.00	35'	EL	16.982	
		TNAGRIT3	33.000	--	1.299	42.872	1.4	0.275	2.11	35'	EL	16.982	0.623	1.85	35'	EL	1.698	0.80	0.275	1.30	35'	EL	16.982	
		TNT4A	33.075	--	1.298	42.933	1.4	0.275	2.11	35'	EL	16.982	0.623	1.75	35'	EL	1.698	0.80	0.275	1.30	35'	EL	16.982	
		TNT6A	41.600	--	1.137	47.314	1.4	0.275	1.85	35'	EL	16.982	0.623	1.71	35'	EL	1.698	0.80	0.275	1.14	35'	EL	16.982	
		TNT7A	42.000	--	1.175	49.358	1.4	0.275	1.92	35'	EL	16.982	0.623	1.59	35'	EL	1.698	0.80	0.275	1.18	35'	EL	16.982	
		TNT7B	42.000	--	1.156	48.536	1.4	0.275	1.88	35'	EL	16.982	0.623	1.54	35'	EL	1.698	0.80	0.275	1.16	35'	EL	16.982	
		TNAGRIT4	43.000	--	1.17	50.308	1.4	0.275	1.89	35'	EL	13.586	0.623	1.48	35'	EL	1.698	0.80	0.275	1.17	35'	EL	16.982	
TNAGT5A	45.000	--	1.079	48.572	1.4	0.275	1.76	35'	EL	16.982	0.623	1.56	35'	EL	1.698	0.80	0.275	1.08	35'	EL	16.982			
TNAGT5B	45.000	--	1.041	46.853	1.4	0.275	1.69	35'	EL	16.982	0.623	1.4	35'	EL	1.698	0.80	0.275	1.04	35'	EL	16.982			

LOAD FACTORS:

DESIGN LOAD RATING FACTORS	LIMIT STATE	γ_{DC}	γ_{DW}
	STRENGTH I	1.25	1.50
	SERVICE III	1.00	1.00

NOTES:

MINIMUM RATING FACTORS ARE BASED ON THE STRENGTH I AND SERVICE III LIMIT STATES.
ALLOWABLE STRESSES FOR SERVICE III LIMIT STATE ARE AS REQUIRED FOR DESIGN.

COMMENTS:

- 1.
- 2.
- 3.
- 4.

CONTROLLING LOAD RATING

1 DESIGN LOAD RATING (HL-93)


2 DESIGN LOAD RATING (HS-20)

3 LEGAL LOAD RATING **

** SEE CHART FOR VEHICLE TYPE

GIRDER LOCATION

I - INTERIOR GIRDER
EL - EXTERIOR LEFT GIRDER
ER - EXTERIOR RIGHT GIRDER



PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
STATION: 14+35.00 -L- POC
SHEET 2 OF 2

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

**LRFR SUMMARY FOR
35' CORED SLAB UNIT
75° SKEW, SPAN B
(NON-INTERSTATE TRAFFIC)**

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

CDM Smith

CDM SMITH
5400 Glenwood Avenue, Suite 400
Raleigh, NC 27612-3228
NC COA No. F-1255

DRAWN BY : VDK DATE : 07/18

CHECKED BY : THF DATE : 07/18


DESIGN ENGINEER : VDK DATE : 07/18

DWG. No.

NORTH CAROLINA
PROFESSIONAL
SEAL
04707
ENGINEER
VENKATA D.T. KOLLUPARA


Witnessed by:
Venkata D. T. Kollupara
10/27/2018 10:58:55 AM

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-05
3			4			
TOTAL SHEETS						19




TYPICAL SECTION

* THE MAXIMUM BARRIER RAIL HEIGHT AND ASPHALT THICKNESS IS SHOWN. THE HEIGHT OF THE BARRIER RAIL AND ASPHALT THICKNESS VARIES WHILE THE TOP OF THE BARRIER RAIL FOLLOWS THE PROFILE OF THE GUTTERLINE. FOR RAIL HEIGHT DETAILS AND ASPHALT THICKNESS SEE THE "VERTICAL CONCRETE BARRIER RAIL SECTION" DETAIL.




SECTION AT END BENT

SECTION AT BENT 1




EXT. SLAB SECTION

(FOR PRESTRESSED STRAND LAYOUT, SEE INTERIOR SLAB SECTION.)




END ELEVATION

SHOWING PLACEMENT OF DOUBLE STIRRUPS AND LOCATION OF ANCHOR BOLT HOLES. (STRAND LAYOUT NOT SHOWN.) INTERIOR SLAB SECTION SHOWN-EXTERIOR SLAB SECTION SIMILAR EXCEPT SHEAR KEY LOCATION.




THREADED INSERT DETAIL



INTERIOR SLAB SECTION SPAN A (55' UNIT)

(19 STRANDS REQUIRED)




INTERIOR SLAB SECTION SPAN B (35' UNIT)

(9 STRANDS REQUIRED)

0.6" Ø LOW RELAXATION STRAND LAYOUT


- ▲ BOND SHALL BE BROKEN ON THESE STRANDS FOR A DISTANCE OF 6'-0" FROM END OF CORED SLAB UNIT. SEE STANDARD SPECIFICATIONS, ARTICLE 1078-7.
- BOND SHALL BE BROKEN ON THESE STRANDS FOR A DISTANCE OF 2'-0" FROM END OF CORED SLAB UNIT. SEE STANDARD SPECIFICATIONS, ARTICLE 1078-7.
- OPTIONAL FULL LENGTH DEBONDED STRANDS. THESE STRANDS ARE NOT REQUIRED. IF THE FABRICATOR CHOOSES TO INCLUDE THESE STRANDS IN THE CORED SLAB UNIT, THE STRANDS SHALL BE DEBONDED FOR THE FULL LENGTH OF THE UNIT AT NO ADDITIONAL COST. SEE STANDARD SPECIFICATIONS, ARTICLE 1078-7.

DEBONDING LEGEND




SHEAR KEY DETAIL


NOTE: OMIT SHEAR KEY ON OUTSIDE FACE OF EXTERIOR CORED SLABS.



GROUTED RECESS AT END OF POST-TENSIONED STRAND CORED SLABS



TYPICAL PLAN



SECTION A-A

PLATE DETAILS

BLOCKOUT DETAIL FOR ANCHOR BOLTS

PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
STATION: 14+35.00 -L- POC

SHEET 1 OF 5

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
3'-0" X 1'-9"
PRESTRESSED CONCRETE
CORED SLAB UNIT
75° SKEW
SPANS A & B

CDM Smith
4000 Glenwood Avenue, Suite 400
Raleigh, NC 27612-3228
NC COA No. F-1255

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

DRAWN BY: VDK DATE: 07/18
CHECKED BY: THF DATE: 07/18
DESIGN ENGINEER: VDK DATE: 07/18



DWG. No.

NORTH CAROLINA PROFESSIONAL SEAL 04707 ENGINEER VENKATA D. T. KOLLUPARA

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

TOTAL SHEETS: 19

FILE: c:\pwworking\1783701_01_17BP6R05_SML_CSI_006.dgn
DATE: 10/22/18 10:59:04 AM



DETAIL "A"
 (SIMILAR EACH END OF UNIT)
 NOTE: EXTERIOR UNIT SHOWN - INTERIOR UNIT SIMILAR EXCEPT OMIT #5 S3 BARS.

PLAN OF SPAN A

PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
 STATION: 14+35.00 -L- POC

SHEET 2 OF 5


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
PLAN OF 55' UNIT
30'-10" CLEAR ROADWAY
75° SKEW
SPAN A

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255



DRAWN BY: VDK DATE: 07/18
 CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.



REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-07
1			3			TOTAL SHEETS
2			4			19

FILE: c:\pwworking\cdm\17BP6R105\17BP6R105_SML_CSD_007.dgn
 DATE: 10/22/2018 10:59:17 AM



DETAIL "A"
 (SIMILAR EACH END OF UNIT)
 NOTE: EXTERIOR UNIT SHOWN - INTERIOR UNIT SIMILAR EXCEPT OMIT #5 S3 BARS.

PLAN OF SPAN B

PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
 STATION: 14+35.00 -L- POC
 SHEET 3 OF 5

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

**PLAN OF 35' UNIT
 30'-10" CLEAR ROADWAY
 75° SKEW
 SPAN B**


REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-08
1			3			TOTAL SHEETS
2			4			19

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

DRAWN BY: VDK DATE: 07/18
 CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.



FILE: c:\pwworking\cdm\17BP6R105\17BP6R105_SML_C33_008.dgn
 DATE: 10/22/18 10:59:19 AM


CONCRETE RELEASE STRENGTH	
UNIT	PSI
SPAN A (55' UNITS)	4900
SPAN B (35' UNITS)	4000

DEAD LOAD DEFLECTION AND CAMBER		
ALL UNITS, 0.6" Ø L.R. STRAND	SPAN A 55' - 21" CS UNIT	SPAN B 35' - 21" CS UNIT
CAMBER (SLAB ALONE IN PLACE)	1/2" ↑	1/4" ↑
DEFLECTION DUE TO SUPERIMPOSED DEAD LOAD **	3/8" ↓	1/8" ↓
FINAL CAMBER	1/8" ↑	1/8" ↑

** INCLUDES FUTURE WEARING SURFACE

GRADE 270 STRANDS	
	0.6" Ø L.R.
AREA (SQUARE INCHES)	0.217
ULTIMATE STRENGTH (LBS. PER STRAND)	58,600
APPLIED PRESTRESS (LBS. PER STRAND)	43,950


CORED SLABS REQUIRED			
SPAN A (55' UNITS)			
	NUMBER	LENGTH	TOTAL LENGTH
EXTERIOR C.S.	2	55'-0"	110'-0"
INTERIOR C.S.	9	55'-0"	495'-0"
TOTAL			605'-0"
SPAN B (35' UNITS)			
	NUMBER	LENGTH	TOTAL LENGTH
EXTERIOR C.S.	2	35'-0"	70'-0"
INTERIOR C.S.	9	35'-0"	315'-0"
TOTAL			385'-0"



FIXED END
(TYPE I - 44 REQ'D)

ELASTOMERIC BEARING DETAILS

ELASTOMER IN ALL BEARINGS SHALL BE 50 DUROMETER HARDNESS.



ALL BAR DIMENSIONS ARE OUT TO OUT

BILL OF MATERIAL FOR ONE CORED SLAB UNIT							
SPAN A (55' - 21" CORED SLAB UNIT)							
				EXTERIOR UNIT		INTERIOR UNIT	
BAR	NUMBER	SIZE	TYPE	LENGTH	WEIGHT	LENGTH	WEIGHT
B7	4	#4	STR	28'-3"	75	28'-3"	75
S1	8	#5	3	4'-3"	35	4'-3"	35
S2	128	#4	3	5'-4"	456	5'-4"	456
* S3	64	#5	1	5'-7"	373		
REINFORCING STEEL				LBS.	566	566	
* EPOXY COATED REINFORCING STEEL				LBS.	373		
6500 P.S.I. CONCRETE				CU. YDS.	7.9	7.9	
0.6" Ø L.R. STRANDS				No.	19	19	
SPAN B (35' - 21" CORED SLAB UNIT)							
				EXTERIOR UNIT		INTERIOR UNIT	
BAR	NUMBER	SIZE	TYPE	LENGTH	WEIGHT	LENGTH	WEIGHT
B3	4	#4	STR	18'-3"	49	18'-3"	49
S1	8	#5	3	4'-3"	35	4'-3"	35
S2	88	#4	3	5'-4"	314	5'-4"	314
* S3	44	#5	1	5'-7"	256		
REINFORCING STEEL				LBS.	398	398	
* EPOXY COATED REINFORCING STEEL				LBS.	256		
5000 P.S.I. CONCRETE				CU. YDS.	5.2	5.2	
0.6" Ø L.R. STRANDS				No.	9	9	

NOTES

ALL PRESTRESSING STRANDS SHALL BE 7-WIRE LOW RELAXATION GRADE 270 STRANDS AND SHALL CONFORM TO AASHTO M203 EXCEPT FOR SAMPLING REQUIREMENTS WHICH SHALL BE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS.

ALL REINFORCING STEEL CAST WITH THE CORED SLAB SECTIONS SHALL BE GRADE 60 AND SHALL BE INCLUDED IN THE UNIT PRICE BID FOR PRESTRESSED CONCRETE CORED SLABS.

RECESSES FOR TRANSVERSE STRANDS SHALL BE GROUTED AFTER THE TENSIONING OF THE STRANDS.

THE 2 1/2" Ø ANCHOR BOLT HOLES AT FIXED ENDS OF SLAB SECTIONS SHALL BE FILLED WITH NON-SHRINK GROUT.

THE BACKER RODS SHALL CONFORM TO THE REQUIREMENTS OF TYPE M BOND BREAKER, SEE SECTION 1028 OF THE STANDARD SPECIFICATIONS.

WHEN CORED SLABS ARE CAST, AN INTERNAL HOLD-DOWN SYSTEM SHALL BE EMPLOYED TO PREVENT VOIDS FROM RISING OR MOVING SIDEWAYS. AT LEAST SIX WEEKS PRIOR TO CASTING CORED SLABS, THE CONTRACTOR SHALL SUBMIT TO THE ENGINEER FOR REVIEW AND COMMENT, DETAILED DRAWINGS OF THE PROPOSED HOLD-DOWN SYSTEM. IN ADDITION TO STRUCTURAL DETAILS, LOCATION AND SPACING OF THE HOLD-DOWNS SHALL BE INDICATED.

ALL REINFORCING STEEL IN THE VERTICAL CONCRETE BARRIER RAIL SHALL BE EPOXY COATED.

PRESTRESSING STRANDS SHALL BE CUT FLUSH WITH THE CORED SLAB UNIT ENDS.

APPLY EPOXY PROTECTIVE COATING TO CORED SLAB UNIT ENDS.

GROOVED CONTRACTION JOINTS, 1/2" IN DEPTH, SHALL BE TOoled IN ALL EXPOSED FACES OF THE BARRIER RAIL AND IN ACCORDANCE WITH ARTICLE 825-10(B) OF THE STANDARD SPECIFICATIONS. A CONTRACTION JOINT SHALL BE LOCATED AT EACH THIRD POINT BETWEEN BARRIER RAIL EXPANSION JOINTS. ONLY ONE CONTRACTION JOINT IS REQUIRED AT MIDPOINT OF BARRIER RAIL SEGMENTS LESS THAN 20 FEET IN LENGTH AND NO CONTRACTION JOINTS ARE REQUIRED FOR THOSE SEGMENTS LESS THAN 10 FEET IN LENGTH.

FLAME CUTTING OF THE TRANSVERSE POST-TENSIONING STRAND IS NOT ALLOWED.

THE TRANSFER OF LOAD FROM THE ANCHORAGES TO THE CORED SLAB UNIT SHALL BE DONE WHEN THE CONCRETE HAS REACHED A COMPRESSIVE STRENGTH OF NOT LESS THAN THE REQUIRED STRENGTH SHOWN IN THE "CONCRETE RELEASE STRENGTH" TABLE.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

THE PERMITTED THREADED INSERTS ARE DETAILED AS AN OPTION FOR THE CONTRACTOR TO ATTACH FALSEWORK AND FORMWORK DURING CONSTRUCTION.

THE PERMITTED THREADED INSERTS IN THE EXTERIOR UNITS SHALL BE SIZED BY THE CONTRACTOR, SPACED AT 4'-0" CENTERS AND GALVANIZED IN ACCORDANCE WITH SECTION 1076 OF THE STANDARD SPECIFICATIONS. STAINLESS STEEL THREADED INSERTS MAY BE USED AS AN ALTERNATE.

THE PERMITTED THREADED INSERTS SHALL BE GROUTED BY THE CONTRACTOR IMMEDIATELY FOLLOWING REMOVAL OF THE FALSEWORK.

THE COST OF THE PERMITTED THREADED INSERTS SHALL BE INCLUDED IN THE PRICE BID FOR THE PRECAST UNITS.

ANCHOR BOLTS SHALL MEET THE REQUIREMENTS OF ASTM A449. NUTS SHALL MEET THE REQUIREMENTS OF AASHTO M291-DH OR AASHTO M292-2H. WASHERS SHALL MEET THE REQUIREMENTS OF AASHTO M293. SHOP DRAWINGS ARE NOT REQUIRED FOR ANCHOR BOLTS, NUTS, WASHERS AND PLATES. SHOP INSPECTION IS REQUIRED.

NUTS FOR ANCHOR BOLTS ARE TO BE TIGHTENED FINGER TIGHT AND THEN BACKED OFF 1/2 TURN. THE THREAD OF THE NUT AND BOLT SHALL THEN BE BURRED WITH A SHARP POINTED TOOL.

ANCHOR BOLTS, NUTS, WASHERS AND PLATES "P1" SHALL BE GALVANIZED IN ACCORDANCE WITH STANDARD SPECIFICATIONS.

PAYMENT FOR ANCHOR BOLTS, NUTS, WASHERS AND PLATES SHALL BE INCLUDED IN THE PRESTRESSED CONCRETE CORED SLAB UNITS PAY ITEM.

PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
 STATION: 14+35.00 -L- POC

SHEET 4 OF 5

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
3'-0" X 1'-9"
PRESTRESSED CONCRETE
CORED SLAB UNIT
75° SKEW
SPANS A & B

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

TOTAL SHEETS: 19


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255


DRAWN BY: VDK DATE: 07/18
 CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.

NORTH CAROLINA PROFESSIONAL SEAL
 04707
 ENGINEER
 VENKATA D. T. KOLLUPARA
 10/27/2018




VERTICAL CONCRETE BARRIER RAIL SECTION



ELEVATION AT EXPANSION JOINTS


BILL OF MATERIAL FOR VERTICAL CONCRETE BARRIER RAIL						
SPAN A (55' UNIT)						
BAR	BARS PER PAIR OF EXTERIOR UNITS	TOTAL NO.	SIZE	TYPE	LENGTH	WEIGHT
*B14	80	80	#5	STR	15'-5"	1286
*S4	128	128	#5	2	7'-2"	957
* EPOXY COATED REINFORCING STEEL				LBS.	2243	
CLASS AA CONCRETE				CU.YDS.	14.1	
TOTAL VERTICAL CONCRETE BARRIER RAIL				LN. FT.	110.13	
SPAN B (35' UNIT)						
BAR	BARS PER PAIR OF EXTERIOR UNITS	TOTAL NO.	SIZE	TYPE	LENGTH	WEIGHT
*B10	80	80	#5	STR	10'-5"	869
*S4	88	88	#5	2	7'-2"	658
* EPOXY COATED REINFORCING STEEL				LBS.	1527	
CLASS AA CONCRETE				CU.YDS.	9.0	
TOTAL VERTICAL CONCRETE BARRIER RAIL				LN. FT.	70.13	



ALL BAR DIMENSIONS ARE OUT TO OUT

TOTAL VERTICAL CONCRETE BARRIER RAIL FOR ENTIRE BRIDGE: 180.26 LN.FT.

GUTTERLINE ASPHALT THICKNESS & RAIL HEIGHT		
	ASPHALT OVERLAY THICKNESS	RAIL HEIGHT
	@ MID-SPAN	@ MID-SPAN
SPAN A (55' UNITS)	1 5/8"	3'-7 5/8"
SPAN B (35' UNITS)	2 5/8"	3'-8 5/8"



END OF RAIL DETAILS

PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
 STATION: 14+35.00 -L- POC

SHEET 5 OF 5

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

DRAWN BY: VDK DATE: 07/18
 CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.

NORTH CAROLINA PROFESSIONAL SEAL 04707 ENGINEER VENKATA D.T. KOLLUPARA


10/27/2018

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


3'-0" X 1'-9"
 PRESTRESSED CONCRETE
 CORED SLAB UNIT
 75° SKEW
 SPANS A & B

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
3					
4					


TOTAL SHEETS: 19



PLAN




ELEVATION



SECTION E-E

GUARDRAIL ANCHOR ASSEMBLY DETAILS

FOR LOCATION OF GUARDRAIL ANCHOR ASSEMBLY, SEE "PLAN" BELOW



PLAN

LOCATION OF ANCHORS FOR GUARDRAIL

END BENT 1 SHOWN, END BENT 2 SIMILAR.

NOTES

- THE GUARDRAIL ANCHOR ASSEMBLY SHALL CONSIST OF A 1/4" HOLD DOWN PLATE AND 7 - 1/8" Ø BOLTS WITH NUTS AND WASHERS.
- THE HOLD-DOWN PLATE SHALL CONFORM TO AASHTO M270 GRADE 36. AFTER FABRICATION, THE HOLD-DOWN PLATE SHALL BE HOT-DIP GALVANIZED IN ACCORDANCE WITH AASHTO M111.
- BOLTS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A307 AND NUTS SHALL CONFORM TO THE REQUIREMENTS OF AASHTO M291. BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED. (AT THE CONTRACTOR'S OPTION, STAINLESS STEEL BOLTS, NUTS AND WASHERS MAY BE USED AS AN ALTERNATE FOR THE 1/8" Ø GALVANIZED BOLTS, NUTS AND WASHERS. THEY SHALL CONFORM TO OR EXCEED THE MECHANICAL REQUIREMENTS OF ASTM A307. THE USE OF THIS ALTERNATE SHALL BE APPROVED BY THE ENGINEER.)
- THE GUARDRAIL ANCHOR ASSEMBLY IS REQUIRED AT ALL POINTS WHERE APPROACH GUARDRAIL IS TO BE ATTACHED TO THE END OF BARRIER RAIL. FOR POINTS OF ATTACHMENT, SEE SKETCH.
- AFTER INSTALLATION, THE EXPOSED THREAD OF THE BOLT SHALL BE BURRED WITH A SHARP POINTED TOOL.
- THE COST OF THE GUARDRAIL ANCHOR ASSEMBLY SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR VERTICAL CONCRETE BARRIER RAIL.
- THE VERTICAL REINFORCING BARS MAY BE SHIFTED SLIGHTLY IN THE VERTICAL CONCRETE BARRIER RAIL TO CLEAR ASSEMBLY BOLTS.
- THE 1/4" Ø HOLES SHALL BE FORMED OR DRILLED WITH A CORE BIT. IMPACT TOOLS WILL NOT BE PERMITTED. ANY CONCRETE DAMAGED BY THIS WORK SHALL BE REPAIRED TO THE SATISFACTION OF THE ENGINEER.



SKETCH SHOWING POINTS OF ATTACHMENT

* DENOTES GUARDRAIL ANCHOR ASSEMBLY

PROJECT NO. 17BP.6.R.105
 ROBESON COUNTY
 STATION: 14+35.00 -L- POC

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 STANDARD GUARDRAIL
 ANCHORAGE FOR
 VERTICAL CONCRETE
 BARRIER RAIL

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

DRAWN BY : VDK DATE : 07/18
 CHECKED BY : THF DATE : 07/18
 DESIGN ENGINEER : VDK DATE : 07/18

DWG. No.

NORTH CAROLINA
 PROFESSIONAL
 SEAL
 04707
 ENGINEER
 VENKATA D.T. KOLLUPARA

10/27/2018

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

TOTAL SHEETS: 19

NOTES


STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR ANCHOR BOLTS.

THE CONCRETE IN THE SHADED AREA OF THE WING SHALL BE POURED AFTER THE VERTICAL CONCRETE BARRIER RAIL IS CAST IF SLIP FORMING IS USED.

FOR PILE SPLICE DETAILS, SEE SHEET 4 OF 4.


FOR WING DETAILS, SEE SHEET 3 OF 4.

FOR ANCHOR BOLTS DETAILS, SEE SHEET S-06.



PLAN

TOP OF PILE ELEVATIONS	
①	109.49
②	109.26
③	109.02
④	108.78
⑤	108.55
⑥	108.31
⑦	108.07



ELEVATION

WINGS NOT SHOWN FOR CLARITY. FOR SECTION A-A, SEE SHEET 4 OF 4.
 CONCRETE COLLARS FOR STEEL PILES NOT SHOWN IN PLAN AND ELEVATION VIEWS FOR CLARITY. SEE "CORROSION PROTECTION FOR STEEL PILES DETAIL", SHEET 4 OF 4.

PROJECT NO. **17BP.6.R.105**
ROBESON COUNTY
 STATION: **14+35.00 -L- POC**

SHEET 1 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUBSTRUCTURE
END BENT 1

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

DRAWN BY: VDK DATE: 07/18
 CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.

NORTH CAROLINA
 PROFESSIONAL SEAL
 04707
 ENGINEER
 VENKATA D. T. KOLLUPARA
 10/27/2018

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

TOTAL SHEETS: 19

FILE: c:\pwworking\cdm\17BP6R105_001_023_17BP6R105_SML_ET_012.dgn
 DATE: 10/22/18 10:59:48 AM

NOTES


STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR ANCHOR BOLTS.

THE CONCRETE IN THE SHADED AREA OF THE WING SHALL BE POURED AFTER THE VERTICAL CONCRETE BARRIER RAIL IS CAST IF SLIP FORMING IS USED.


FOR PILE SPLICE DETAILS, SEE SHEET 4 OF 4.

FOR WING DETAILS, SEE SHEET 3 OF 4.

FOR ANCHOR BOLTS DETAILS, SEE SHEET S-06.



PLAN



ELEVATION

WINGS NOT SHOWN FOR CLARITY.
 FOR SECTION A-A, SEE SHEET 4 OF 4.
 CONCRETE COLLARS FOR STEEL PILES NOT SHOWN IN PLAN AND ELEVATION VIEWS FOR CLARITY.
 SEE "CORROSION PROTECTION FOR STEEL PILES DETAIL", SHEET 4 OF 4.

TOP OF PILE ELEVATIONS	
①	109.22
②	108.99
③	108.75
④	108.51
⑤	108.27
⑥	108.04
⑦	107.80

PROJECT NO. **17BP.6.R.105**
ROBESON COUNTY
 STATION: **14+35.00 -L- POC**

SHEET 2 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE

END BENT 2

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255


DRAWN BY: VDK DATE: 07/18
 CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.


NORTH CAROLINA
 PROFESSIONAL
 SEAL
 04707
 ENGINEER
 VENKATA D.T. KOLLUPARA
 10/27/2018

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-13
1			3			TOTAL SHEETS
2			4			19


FILE: c:\pwworking\cdm\17BP6R105\17BP6R105_SML_E2_013.dgn
 DATE: 10/27/2018 10:59:55 AM




PLAN OF WING (W1)




PLAN OF WING (W2)




SECTION X-X



SECTION Y-Y



ELEVATION OF WING (W1)



ELEVATION OF WING (W2)

WING DETAILS

PROJECT NO. 17BP.6.R.105
 ROBESON COUNTY
 STATION: 14+35.00 -L- POC

SHEET 3 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE

END BENTS 1 & 2
 WING DETAILS

REVISIONS			
NO.	BY:	DATE:	NO.
1			3
2			4

SHEET NO. S-14
 TOTAL SHEETS 19

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

DRAWN BY: VDK DATE: 07/18
 CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.

NORTH CAROLINA
 PROFESSIONAL SEAL
 04707
 ENGINEER
 VENKATA D. T. KOLLUPARA
 10/2/2018

FILE: c:\pwworking\cdm\17BP6R105_SML_E3_014.dgn
 DATE: 10/2/2018 11:00:03 AM




BAGGED STONE AND PIPE SHALL BE PLACED IMMEDIATELY AFTER COMPLETION OF END BENT EXCAVATION. PIPE MAY BE EITHER CONCRETE, CORRUGATED STEEL, CORRUGATED ALUMINUM ALLOY, OR CORRUGATED PLASTIC. PERFORATED PIPE WILL NOT BE ALLOWED.

BAGGED STONE SHALL REMAIN IN PLACE UNTIL THE ENGINEER DIRECTS THAT IT BE REMOVED. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF SILT ACCUMULATIONS AT BAGGED STONE WHEN SO DIRECTED BY THE ENGINEER. BAGS SHALL BE REMOVED AND REPLACED WHENEVER THE ENGINEER DETERMINES THAT THEY HAVE DETERIORATED AND LOST THEIR EFFECTIVENESS.


NO SEPARATE PAYMENT WILL BE MADE FOR THIS WORK AND THE ENTIRE COST OF THIS WORK SHALL BE INCLUDED IN THE UNIT CONTRACT PRICE BID FOR THE SEVERAL PAY ITEMS.

TEMPORARY DRAINAGE AT END BENT





PILE SPLICE DETAILS

BAR TYPES		BILL OF MATERIAL FOR ONE END BENT (2 REQUIRED)					
<p>1</p>	<p>2</p>	BAR NO.	SIZE	TYPE	LENGTH	WEIGHT	
<p>3</p>	<p>4</p>	B1	#8		42'-6"	1156	
<p>5</p>	<p>6</p>	B2	#4	STR	21'-4"	228	
		B3	#4	STR	2'-5"	16	
		H1	#6	#4	2	7'-7"	30
		H2	#6	#4	2	7'-9"	31
		H3	#6	#4	3	8'-0"	32
		H4	#6	#4	3	7'-10"	31
		K1	#4	STR	3'-1"	25	
		S1	#2	#4	4	7'-5"	258
		S2	#2	#4	5	3'-2"	110
		S3	#2	#4	6	6'-6"	61
		V1	#4	STR	4'-8"	153	
ALL BAR DIMENSIONS ARE OUT TO OUT.		REINFORCING STEEL					2131 LBS.
		CLASS A CONCRETE BREAKDOWN					
		POUR #1 CAP, LOWER PART OF WINGS & COLLARS					12.7 C.Y.
		POUR #2 UPPER PART OF WINGS					1.8 C.Y.
		TOTAL CLASS A CONCRETE					14.5 C.Y.
		7/8" Ø ANCHOR BOLTS					EA. 22
		EMBEDDED WASHERS, NUTS & PLATES					EA. 22
		FOR PAYMENT FOR ANCHOR BOLTS, NUTS, WASHERS AND PLATES, SEE NOTE ON SHEET S-09.					



CORROSION PROTECTION FOR STEEL PILES DETAIL

(END BENT 1 SHOWN, END BENT 2 SIMILAR BY ROTATION)



PROJECT NO. 17BP.6.R.105
 ROBESON COUNTY
 STATION: 14+35.00 -L- POC

SHEET 4 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUBSTRUCTURE
 END BENTS 1 & 2
 DETAILS

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

DRAWN BY: VDK DATE: 07/18
 CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.

NORTH CAROLINA
 PROFESSIONAL SEAL
 04707
 ENGINEER
 VENKATA D.T. KOLLUPARA




10/2/2018

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
3			19		
4			19		

FILE: c:\pwworking\cdm\17BP6R105_SMU_E4_015.dgn
 DATE: 10/2/2018 11:00:11 AM

NOTES

- STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR ANCHOR BOLTS.
- ★ INVERT ALTERNATE STIRRUPS.
- GALVANIZE THE TOP OF EACH INTERIOR BENT PILE A MINIMUM OF 25 FEET. GALVANIZE IN ACCORDANCE WITH SECTION 1076 OF THE STANDARD SPECIFICATIONS.
- FOR ANCHOR BOLTS DETAILS, SEE SHEET S-06.



TOP OF PILE ELEVATIONS	
①	109.28
②	109.09
③	108.91
④	108.72
⑤	108.53
⑥	108.34
⑦	108.16
⑧	107.97

PROJECT NO. 17BP.6.R.105
 ROBESON COUNTY
 STATION: 14+35.00 -L- POC

SHEET 1 OF 2

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUPERSTRUCTURE

BENT 1

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-16
1			3			TOTAL SHEETS 19
2			4			

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

DRAWN BY: VDK DATE: 07/18
 CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.


NORTH CAROLINA PROFESSIONAL SEAL 04707
 VENKATA D.T. KOLLUPARA
 10/27/2018

FILE: c:\pwworking\cdm\17BP6R105_SMU_BT_016.dgn
 DATE: 10/22/18 11:00:18 AM




SECTION A-A

FOR 7/8" Ø ANCHOR BOLTS DETAILS, SEE SHEET S-06.



△ POSITION OF PILE DURING WELDING.

PILE SPLICE DETAILS



ALL BAR DIMENSIONS ARE OUT TO OUT.

BILL OF MATERIAL

BENT 1

BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT
B1	4	#10	1	40'-0"	688
B2	4	#10	STR	37'-4"	643
B3	4	#5	STR	37'-4"	156
B4	8	#4	STR	19'-11"	106
B5	10	#4	STR	2'-11"	19
S1	39	#5	2	8'-1"	329
S2	16	#4	3	7'-7"	81
U1	4	#4	4	5'-10"	16
U2	6	#4	4	5'-0"	20
U3	2	#9	4	10'-1"	69

REINFORCING STEEL 2127 LBS

TOTAL CLASS A CONCRETE 11.3 C.Y.

HP 14 X 73 GALVANIZED STEEL PILES


No. 8 LIN. FT. 480

PILE DRIVING EQUIPMENT SETUP FOR HP 14 X 73 GALVANIZED STEEL PILES EA. 8

7/8" Ø ANCHOR BOLTS EA. 44

EMBEDDED WASHERS, NUTS & PLATES EA. 44

FOR PAYMENT FOR ANCHOR BOLTS, NUTS, WASHERS AND PLATES, SEE NOTE ON SHEET S-09.



END OF CAP VIEW

(TYPICAL BOTH ENDS)

PROJECT NO. 17BP.6.R.105
ROBESON COUNTY
 STATION: 14+35.00 -L- POC

SHEET 2 OF 2

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE

BENT 1

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255





DRAWN BY : VDK DATE : 07/18
 CHECKED BY : THF DATE : 07/18
 DESIGN ENGINEER : VDK DATE : 07/18

DWG. No.

NORTH CAROLINA PROFESSIONAL SEAL 04707
 VENKATA D.T. KOLLUPARA
 10/27/2018

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-17
1			3			TOTAL SHEETS 19
2			4			

ESTIMATED QUANTITIES		
BRIDGE @ STA. 14+35.00 -L-	RIP RAP CLASS II	GEOTEXTILE FOR DRAINAGE
	TONS	SQUARE YARDS
END BENT 1	95	105
END BENT 2	70	75
TOTAL	165	180



SECTION C-C
BERM RIP RAPPED

PROJECT NO. **17BP.6.R.105**
ROBESON COUNTY
 STATION: **14+35.00 -L- POC**

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

STANDARD

— RIP RAP DETAILS —

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-18
1			3			TOTAL SHEETS
2			4			19

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

DRAWN BY: VDK DATE: 07/18
 CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No.

NORTH CAROLINA
 PROFESSIONAL SEAL
 04707
 ENGINEER
 VENKATA D.T. KOLLUPARA

FILE: c:\pwworking\17188570\d01_035_17BP6R105_SML_R18.dgn
 DATE: 10/22/18 2:54:44 PM




AT END BENT 1 AT END BENT 2

PLAN

DIMENSIONS SHOWN ARE TYPICAL FOR BOTH APPROACH SLABS


NOTES

FOR BRIDGE APPROACH FILL INCLUDING GEOTEXTILE, 4" Ø DRAINAGE PIPE, AND SELECT MATERIAL BACKFILL, SEE ROADWAY PLANS.
 GEOTEXTILE SHALL BE TYPE 1 IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS SECTION 1056.
 SELECT MATERIAL BACKFILL (CLASS V OR CLASS VI) SHALL BE IN ACCORDANCE WITH STANDARD SPECIFICATIONS SECTION 1016.
 SELECT MATERIAL BACKFILL IS TO BE CONTINUOUS ALONG FILL FACE OF BACKWALL FROM OUTSIDE EDGE TO OUTSIDE EDGE OF APPROACH SLAB.
 FOR THE 4" Ø DRAINAGE PIPE OUTLET(S), SEE ROADWAY STANDARD DRAWINGS.
 AREA BETWEEN THE WINGWALL AND APPROACH SLAB SHALL BE GRADED TO DRAIN THE WATER AWAY FROM THE FILL FACE OF THE BRIDGE AND SHALL BE PAVED, SEE ROADWAY PLANS.
 APPROACH SLAB GROOVING IS NOT REQUIRED.



NOTE: IF THE APPROACH SLAB IS NOT CONSTRUCTED IMMEDIATELY AFTER THE BACKFILLING OF THE END BENT EXCAVATION, GRADE TO DRAIN TO THE BOTTOM OF THE SLOPE AND PROVIDE EROSION RESISTANT MATERIAL, SUCH AS FIBERGLASS ROVING OR AS DIRECTED BY THE ENGINEER TO PREVENT SOIL EROSION AND TO PROTECT THE AREA ADJACENT TO THE STRUCTURE. THE CONTRACTOR WILL BE REQUIRED TO REMOVE THESE MATERIALS PRIOR TO CONSTRUCTION OF THE APPROACH SLAB.

TEMPORARY DRAINAGE DETAIL




NOTE: IMMEDIATELY AFTER THE CONSTRUCTION OF THE APPROACH SLAB, THE CONTRACTOR SHALL PROVIDE TEMPORARY BERM AND SLOPE DRAIN. CONTRACTOR SHALL GRADE TO PIPE INLET AND PROVIDE EROSION RESISTANT MATERIAL AS SHOWN. THE EROSION RESISTANT MATERIAL SHALL BE EITHER 1) ASPHALT PLANT MIX, TYPE 1 OR TYPE 2, MIN. 2" DEPTH, 2) EROSION CONTROL MAT, OR 3) CONCRETE, AS DIRECTED BY THE ENGINEER. THE SLOPE DRAIN SHALL CONSIST OF A NON-PERFORATED TEMPORARY DRAINAGE PIPE, 12 INCHES IN DIAMETER.

PLAN VIEW


TEMPORARY BERM AND SLOPE DRAIN DETAILS

(TO BE USED WHEN SHOULDER BERM GUTTER IS REQUIRED)



SECTION THRU SLAB

(TYPE II - MODIFIED APPROACH FILL)



CURB DETAILS

PROJECT NO. 17BP.6.R.105
 ROBESON COUNTY
 STATION: 14+35.00 -L- POC

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 STANDARD
 BRIDGE APPROACH SLAB
 FOR PRESTRESSED CONCRETE
 CORED SLAB UNIT
 (SUB-REGIONAL TIER)
 75° SKEW

REVISIONS				SHEET NO.	
NO.	BY:	DATE:	NO.	BY:	DATE:
1			3		
2			4		

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CDM Smith
 CDM SMITH
 5400 Glenwood Avenue, Suite 400
 Raleigh, NC 27612-3228
 NC COA No. F-1255

CHECKED BY: THF DATE: 07/18
 DESIGN ENGINEER: VDK DATE: 07/18

DWG. No. _____

NORTH CAROLINA
 PROFESSIONAL
 SEAL
 04707
 ENGINEER
 VENKATA D.T. KOLLUPARA

FILE: c:\p\p\1\kollupara\17183701_401_037_17BP6R105_SMU_AS_019.dgn
 DATE: 10/22/18 11:00:40 AM

STANDARD NOTES

DESIGN DATA:

SPECIFICATIONS	-----	A.A.S.H.T.O. (CURRENT)
LIVE LOAD	-----	SEE PLANS
IMPACT ALLOWANCE	-----	SEE A.A.S.H.T.O.
STRESS IN EXTREME FIBER OF		
STRUCTURAL STEEL - AASHTO M270 GRADE 36	-	20,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50W	-	27,000 LBS. PER SQ. IN.
- AASHTO M270 GRADE 50	-	27,000 LBS. PER SQ. IN.
REINFORCING STEEL IN TENSION		
GRADE 60	--	24,000 LBS. PER SQ. IN.
CONCRETE IN COMPRESSION	-----	1,200 LBS. PER SQ. IN.
CONCRETE IN SHEAR	-----	SEE A.A.S.H.T.O.
STRUCTURAL TIMBER - TREATED OR		
UNTREATED - EXTREME FIBER STRESS	-----	1,800 LBS. PER SQ. IN.
COMPRESSION PERPENDICULAR TO GRAIN OF TIMBER	-----	375 LBS. PER SQ. IN.
EQUIVALENT FLUID PRESSURE OF EARTH	-----	30 LBS. PER CU. FT. (MINIMUM)

MATERIAL AND WORKMANSHIP:

EXCEPT AS MAY OTHERWISE BE SPECIFIED ON PLANS OR IN THE SPECIAL PROVISIONS, ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE 2018 "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES" OF THE N. C. DEPARTMENT OF TRANSPORTATION.

STEEL SHEET PILING FOR PERMANENT OR TEMPORARY APPLICATIONS SHALL BE HOT ROLLED.

CONCRETE:

UNLESS OTHERWISE REQUIRED ON PLANS, CLASS A CONCRETE SHALL BE USED FOR ALL PORTIONS OF ALL STRUCTURES WITH THE EXCEPTION THAT: CLASS AA CONCRETE SHALL BE USED IN BRIDGE SUPERSTRUCTURES, ABUTMENT BACKWALLS, AND APPROACH SLABS; AND CLASS B CONCRETE SHALL BE USED FOR SLOPE PROTECTION AND RIP RAP.

CONCRETE CHAMFERS:

UNLESS OTHERWISE NOTED ON THE PLANS, ALL EXPOSED CORNERS ON STRUCTURES SHALL BE CHAMFERED 3/4" WITH THE FOLLOWING EXCEPTIONS: TOP CORNERS OF CURBS MAY BE ROUNDED TO 1-1/2" RADIUS WHICH IS BUILT INTO CURB FORMS; CORNERS OF TRANSVERSE FLOOR EXPANSION JOINTS SHALL BE ROUNDED WITH A 1/4" FINISHING TOOL UNLESS OTHERWISE REQUIRED ON PLANS; AND CORNERS OF EXPANSION JOINTS IN THE ROADWAY FACES AND TOPS OF CURBS AND SIDEWALKS SHALL BE ROUNDED TO A 1/4" RADIUS WITH A FINISHING STONE OR TOOL UNLESS OTHERWISE REQUIRED ON PLANS.

DOWELS:

DOWELS WHEN INDICATED ON PLANS AS FOR CULVERT EXTENSIONS, SHALL BE EMBEDDED AT LEAST 12" INTO THE OLD CONCRETE AND GROUTED INTO PLACE WITH 1:2 CEMENT MORTAR.

ALLOWANCE FOR DEAD LOAD DEFLECTION, SETTLEMENT, ETC. IN CASTING SUPERSTRUCTURES:

BRIDGES SHALL BE BUILT ON THE GRADE OR VERTICAL CURVE SHOWN ON PLANS. SLABS, CURBS AND PARAPETS SHALL CONFORM TO THE GRADE OR CURVE.

ALL DIMENSIONS WHICH ARE GIVEN IN SECTION AND ARE AFFECTED BY DEAD LOAD DEFLECTIONS ARE DIMENSIONS AT CENTER LINE OF BEARING UNLESS OTHERWISE NOTED ON PLANS. IN SETTING FORMS FOR STEEL BEAM BRIDGES AND PRESTRESSED CONCRETE GIRDER BRIDGES, ADJUSTMENTS SHALL BE MADE DUE TO THE DEAD LOAD DEFLECTIONS FOR THE ELEVATIONS SHOWN. WHERE BLOCKS ARE SHOWN OVER BEAMS FOR BUILDING UP TO THE SLAB, THE VERTICAL DIMENSIONS OF THE BLOCKS SHALL BE ADJUSTED BETWEEN BEARINGS TO COMPENSATE FOR DEAD LOAD DEFLECTIONS, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER. WHERE BOTTOM OF SLAB IS IN LINE WITH BOTTOM OF TOP FLANGES, DEPTH OF SLAB BETWEEN BEARINGS SHALL BE ADJUSTED TO COMPENSATE FOR DEAD LOAD DEFLECTION, VERTICAL CURVE ORDINATE, AND ACTUAL BEAM CAMBER.

IN SETTING FALSEWORK AND FORMS FOR REINFORCED CONCRETE SPANS, AN ALLOWANCE SHALL BE MADE FOR DEAD LOAD DEFLECTIONS, SETTLEMENT OF FALSEWORK, AND PERMANENT CAMBER WHICH SHALL BE PROVIDED FOR IN ADDITION TO THE ELEVATIONS SHOWN. AFTER REMOVAL OF THE FALSEWORK, THE FINISHED STRUCTURES SHALL CONFORM TO THE PROFILE AND ELEVATIONS SHOWN ON THE PLANS AND CONSTRUCTION ELEVATIONS FURNISHED BY THE ENGINEER.

DETAILED DRAWINGS FOR FALSEWORK OR FORMS FOR BRIDGE SUPERSTRUCTURE AND ANY STRUCTURE OR PARTS OF A STRUCTURE AS NOTED ON THE PLANS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE CONSTRUCTION OF THE FALSEWORK OR FORMS IS STARTED.

REINFORCING STEEL:

ALL REINFORCING STEEL SHALL BE DEFORMED. DIMENSIONS RELATIVE TO PLACEMENT OF REINFORCING ARE TO CENTERS OF BARS UNLESS OTHERWISE INDICATED IN THE PLANS. DIMENSIONS ON BAR DETAILS ARE TO CENTERS OF BARS OR ARE OUT TO OUT AS INDICATED ON PLANS.

WIRE BAR SUPPORTS SHALL BE PROVIDED FOR REINFORCING STEEL WHERE INDICATED ON THE PLANS. WHEN BAR SUPPORT PIECES ARE PLACED IN CONTINUOUS LINES, THEY SHALL BE SO PLACED THAT THE ENDS OF THE SUPPORTING WIRES SHALL BE LAPPED TO LOCK LEGS ON ADJOINING PIECES.

STRUCTURAL STEEL:

AT THE CONTRACTOR'S OPTION, HE MAY SUBSTITUTE 7/8" Ø SHEAR STUDS FOR THE 3/4" Ø STUDS SPECIFIED ON THE PLANS. THIS SUBSTITUTION SHALL BE MADE AT THE RATE OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS, AND STUD SPACING CHANGES SHALL BE MADE AS NECESSARY TO PROVIDE THE SAME EQUIVALENT NUMBER OF 7/8" Ø STUDS ALONG THE BEAM AS SHOWN FOR 3/4" Ø STUDS BASED ON THE RATIO OF 3 - 7/8" Ø STUDS FOR 4 - 3/4" Ø STUDS. STUDS OF THE LENGTH SPECIFIED ON THE PLANS MUST BE PROVIDED. THE MAXIMUM SPACING SHALL BE 2'-0".

EXCEPT AT THE INTERIOR SUPPORTS OF CONTINUOUS BEAMS WHERE THE COVER PLATE IS IN CONTACT WITH BEARING PLATE, THE CONTRACTOR MAY, AT HIS OPTION, SUBSTITUTE FOR THE COVER PLATES DESIGNATED ON THE PLANS COVER PLATES OF THE EQUIVALENT AREA PROVIDED THESE PLATES ARE AT LEAST 5/16" IN THICKNESS AND DO NOT EXCEED A WIDTH EQUAL TO THE FLANGE WIDTH LESS 2" OR A THICKNESS EQUAL TO 2 TIMES THE FLANGE THICKNESS. THE SIZE OF FILLET WELDS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT ANSI/AASHTO/AWS "BRIDGE WELDING CODE". ELECTROSLAG WELDING WILL NOT BE PERMITTED.

WITH THE SOLE EXCEPTION OF EDGES AT SURFACES WHICH BEAR ON OTHER SURFACES, ALL SHARP EDGES AND ENDS OF SHAPES AND PLATES SHALL BE SLIGHTLY ROUNDED BY SUITABLE MEANS TO A RADIUS OF APPROXIMATELY 1/16 INCH OR EQUIVALENT FLAT SURFACE AT A SUITABLE ANGLE PRIOR TO PAINTING, GALVANIZING, OR METALLIZING.

HANDRAILS AND POSTS:

METAL STANDARDS AND FACES OF THE CONCRETE END POSTS FOR THE METAL RAIL SHALL BE SET NORMAL TO THE GRADE OF THE CURB, UNLESS OTHERWISE SHOWN ON PLANS. THE METAL RAIL AND TOPS OF CONCRETE POSTS USED WITH THE ALUMINUM RAIL SHALL BE BUILT PARALLEL TO THE GRADE OF THE CURB.

METAL HANDRAILS SHALL BE IN ACCORDANCE WITH THE PLANS. RAILS SHALL BE AS MANUFACTURED FOR BRIDGE RAILING. CASTINGS SHALL BE OF A UNIFORM APPEARANCE. FINIS AND OTHER DEFORMATIONS RESULTING FROM CASTING OR OTHERWISE SHALL BE REMOVED IN A MANNER SO THAT A UNIFORM COLORING OF THE COMPLETED CASTING SHALL BE OBTAINED. CASTINGS WITH DISCOLORATIONS OR OF NON-UNIFORM COLORING WILL NOT BE ACCEPTED. CERTIFIED MILL REPORTS ARE REQUIRED FOR METAL RAILS AND POSTS.

SPECIAL NOTES:

GENERALLY, IN CASE OF DISCREPANCY, THIS STANDARD SHEET OF NOTES SHALL GOVERN OVER THE SPECIFICATIONS, BUT THE REMAINDER OF THE PLANS SHALL GOVERN OVER NOTES HEREON, AND SPECIAL PROVISIONS SHALL GOVERN OVER ALL. SEE SPECIFICATIONS ARTICLE 105-4.

ENGLISH

JANUARY, 1990