

**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**

**This file or an individual page
shall not be considered a certified document.**

04/05/15

STATE OF NORTH CAROLINA, DIVISION OF HIGHWAYS CONVENTIONAL PLAN SHEET SYMBOLS

Note: Not to Scale *S.U.E. = Subsurface Utility Engineering

BOUNDARIES AND PROPERTY:

State Line	-----
County Line	-----
Township Line	-----
City Line	-----
Reservation Line	-----
Property Line	-----
Existing Iron Pin	○ EIP
Property Corner	-----
Property Monument	□ ECM
Parcel/Sequence Number	⑫③
Existing Fence Line	-x-x-x-
Proposed Woven Wire Fence	○
Proposed Chain Link Fence	□
Proposed Barbed Wire Fence	◇
Existing Wetland Boundary	----- WL.B
Proposed Wetland Boundary	----- WL.B
Existing Endangered Animal Boundary	----- EAB
Existing Endangered Plant Boundary	----- EPB
Existing Historic Property Boundary	----- HPB
Known Contamination Area: Soil	-----
Potential Contamination Area: Soil	-----
Known Contamination Area: Water	-----
Potential Contamination Area: Water	-----
Contaminated Site: Known or Potential	☠ ?

BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	○
Sign	○ S
Well	○ W
Small Mine	✕
Foundation	□
Area Outline	□
Cemetery	□
Building	□
School	□
Church	□
Dam	□

HYDROLOGY:

Stream or Body of Water	-----
Hydro, Pool or Reservoir	-----
Jurisdictional Stream	----- JS
Buffer Zone 1	----- BZ 1
Buffer Zone 2	----- BZ 2
Flow Arrow	←
Disappearing Stream	-----
Spring	○
Wetland	-----
Proposed Lateral, Tail, Head Ditch	-----
False Sump	-----

RAILROADS:

Standard Gauge	-----
RR Signal Milepost	○ CSX TRANSPORTATION MILEPOST 35
Switch	□ SWITCH
RR Abandoned	-----
RR Dismantled	-----

RIGHT OF WAY:

Baseline Control Point	◆
Existing Right of Way Marker	△
Existing Right of Way Line	-----
Proposed Right of Way Line	----- RW
Proposed Right of Way Line with Iron Pin and Cap Marker	△ RW
Proposed Right of Way Line with Concrete or Granite R/W Marker	△ RW
Proposed Control of Access Line with Concrete C/A Marker	△ C/A
Existing Control of Access	△ C/A
Proposed Control of Access	△ C/A
Existing Easement Line	----- E
Proposed Temporary Construction Easement	----- E
Proposed Temporary Drainage Easement	----- TDE
Proposed Permanent Drainage Easement	----- PDE
Proposed Permanent Drainage / Utility Easement	----- DUE
Proposed Permanent Utility Easement	----- PUE
Proposed Temporary Utility Easement	----- TUE
Proposed Aerial Utility Easement	----- AUE
Proposed Permanent Easement with Iron Pin and Cap Marker	◆

ROADS AND RELATED FEATURES:

Existing Edge of Pavement	-----
Existing Curb	-----
Proposed Slope Stakes Cut	----- C
Proposed Slope Stakes Fill	----- F
Proposed Curb Ramp	○ CR
Existing Metal Guardrail	-----
Proposed Guardrail	-----
Existing Cable Guiderail	-----
Proposed Cable Guiderail	-----
Equality Symbol	⊕
Pavement Removal	-----

VEGETATION:

Single Tree	☼
Single Shrub	☼
Hedge	-----
Woods Line	-----

Orchard	☼ ☼ ☼ ☼
Vineyard	□ Vineyard

EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	----- CONC
Bridge Wing Wall, Head Wall and End Wall	----- CONC WW
MINOR:	
Head and End Wall	----- CONC HW
Pipe Culvert	-----
Footbridge	-----
Drainage Box: Catch Basin, DI or JB	□ CB
Paved Ditch Gutter	-----
Storm Sewer Manhole	○ S
Storm Sewer	----- S

UTILITIES:

POWER:	
Existing Power Pole	●
Proposed Power Pole	○
Existing Joint Use Pole	●
Proposed Joint Use Pole	○
Power Manhole	⊕
Power Line Tower	⊠
Power Transformer	⊠
U/G Power Cable Hand Hole	○
H-Frame Pole	●
U/G Power Line LOS B (S.U.E.*)	----- P
U/G Power Line LOS C (S.U.E.*)	----- P
U/G Power Line LOS D (S.U.E.*)	----- P

TELEPHONE:

Existing Telephone Pole	●
Proposed Telephone Pole	○
Telephone Manhole	⊕
Telephone Pedestal	⊠
Telephone Cell Tower	⊠
U/G Telephone Cable Hand Hole	○
U/G Telephone Cable LOS B (S.U.E.*)	----- T
U/G Telephone Cable LOS C (S.U.E.*)	----- T
U/G Telephone Cable LOS D (S.U.E.*)	----- T
U/G Telephone Conduit LOS B (S.U.E.*)	----- TC
U/G Telephone Conduit LOS C (S.U.E.*)	----- TC
U/G Telephone Conduit LOS D (S.U.E.*)	----- TC
U/G Fiber Optics Cable LOS B (S.U.E.*)	----- T FO
U/G Fiber Optics Cable LOS C (S.U.E.*)	----- T FO
U/G Fiber Optics Cable LOS D (S.U.E.*)	----- T FO

WATER:

Water Manhole	⊕
Water Meter	○
Water Valve	⊗
Water Hydrant	⊕
U/G Water Line LOS B (S.U.E.*)	----- W
U/G Water Line LOS C (S.U.E.*)	----- W
U/G Water Line LOS D (S.U.E.*)	----- W
Above Ground Water Line	----- A/G Water

TV:

TV Pedestal	⊠
TV Tower	⊗
U/G TV Cable Hand Hole	⊠
U/G TV Cable LOS B (S.U.E.*)	----- TV
U/G TV Cable LOS C (S.U.E.*)	----- TV
U/G TV Cable LOS D (S.U.E.*)	----- TV
U/G Fiber Optic Cable LOS B (S.U.E.*)	----- TV FO
U/G Fiber Optic Cable LOS C (S.U.E.*)	----- TV FO
U/G Fiber Optic Cable LOS D (S.U.E.*)	----- TV FO

GAS:

Gas Valve	◇
Gas Meter	⊕
U/G Gas Line LOS B (S.U.E.*)	----- G
U/G Gas Line LOS C (S.U.E.*)	----- G
U/G Gas Line LOS D (S.U.E.*)	----- G
Above Ground Gas Line	----- A/G Gas

SANITARY SEWER:

Sanitary Sewer Manhole	⊕
Sanitary Sewer Cleanout	⊕
U/G Sanitary Sewer Line	----- SS
Above Ground Sanitary Sewer	----- A/G Sanitary Sewer
SS Forced Main Line LOS B (S.U.E.*)	----- FSS
SS Forced Main Line LOS C (S.U.E.*)	----- FSS
SS Forced Main Line LOS D (S.U.E.*)	----- FSS

MISCELLANEOUS:

Utility Pole	●
Utility Pole with Base	⊠
Utility Located Object	○
Utility Traffic Signal Box	⊠
Utility Unknown U/G Line LOS B (S.U.E.*)	----- ?UTL
U/G Tank; Water, Gas, Oil	□
Underground Storage Tank, Approx. Loc.	⊕
A/G Tank; Water, Gas, Oil	□
Geoenvironmental Boring	⊕
U/G Test Hole LOS A (S.U.E.*)	⊕
Abandoned According to Utility Records	AATUR
End of Information	E.O.I.

PAVEMENT SCHEDULE (PRELIMINARY PAVEMENT DESIGN)	
C1	PROP. APPROX. 1½" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD.
C2	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 2" IN DEPTH.
D1	PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
D2	PROP. VAR. DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH, TO BE PLACED IN LAYERS NOT LESS THAN 2½" IN DEPTH OR GREATER THAN 4" IN DEPTH.
E1	PROP. APPROX. 3" ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 342 LBS. PER SQ. YD.
E2	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0B, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5½" IN DEPTH.
T	EARTH MATERIAL.
U	EXISTING PAVEMENT.
W	VARIABLE DEPTH ASPHALT PAVEMENT (SEE STANDARD WEDGING DETAIL)

NOTE: PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.







PROJECT NOTES

- The Contractor shall not work on both sides of the road simultaneously within the same area.
- Ingress and egress shall be maintained to all businesses and dwellings on the project.
- At the end of each workday, the Contractor shall be required to backfill any area adjacent to existing travelway that has been graded leaving no more than a 2" drop-off.
- A minimum of two-way, two-lane traffic (plus all existing left and right turn lanes) shall be maintained during periods of construction inactivity.
- The Contractor shall not be allowed to stop traffic for more than 5 minutes at a time in any one direction.
- During periods of construction inactivity, the difference in elevation between lanes shall not exceed 1½ inch.
- During periods of construction inactivity, place cones/drums 3' from existing edge of pavement (travelway) as directed by the Engineer.
- Contractor to install Erosion Control devices as directed by the Engineer.
- Contractor shall coordinate with the Division Six Traffic Services Unit for placement of all pavement markings and signs.
- Removal of existing road signs is incidental to the project.
- Access to police and fire station, fire hydrants, and hospitals shall be maintained at all times.

MILLING AT PAVEMENT TIE-INS

NOTES TO CONTRACTOR

For surface mixes over 1" in thickness, mill the existing pavement in accordance with the following sketch as directed by the Engineer.
Locations shall include ties into existing concrete pavement, at bridge approaches where the bridge will not be resurfaced, and at the beginning and ending point of each resurfacing map.
Perform the work in accordance with Section 607 of the January 2012 North Carolina Department of Transportation Standard Specifications for Roads and Structures. Resurfacing will be accomplished at the same time as the milling operation.




SUMMARY OF EARTHWORK

IN CUBIC YARDS

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

STATION	STATION	EXCAVATION					EMBANKMENT				BORROW	WASTE			
		TOTAL UNCL. EXCAV.	ROCK	UNDER-CUT	UNSUIT. UNCLASS.	SUITABLE UNCLASS.	TOTAL	ROCK	EARTH	EMBANK. (+) 25%		ROCK	SUITABLE	UNSUIT.	TOTAL
12+00 (-L-)	32+00 (-L-)	832				832	1908		1908	2385	1553				
10+50 (-Y1-)	11+50 (-Y1-)	34				34	88		88	110	76				
TOTALS		866				866	1996		1996	2495	1629				
EST. 5% TO REPLACE SOIL ON BORROW PIT											81				
GRAND TOTALS						866	1996		1996	2495	1710				
SAY											1725				

Note: Approximate quantities only. Unclassified Excavation, Fine Grading and Clearing and Grubbing will be paid for at the contract lump sum price for "Grading" according to Standard Specifications Section 226.



-L-

PI Sta 11+35.56 Δ = 6° 52' 11.9" (RT) D = 2° 57' 00.0" L = 232.88' T = 116.58' R = 1,942.23' SE = SEE PLANS RO = SEE PLANS	PI Sta 14+05.09 Δ = 0° 16' 49.3" (RT) D = 1° 08' 45.3" L = 24.47' T = 12.23' R = 5,000.00' SE = SEE PLANS RO = SEE PLANS	PI Sta 21+50.12 Δ = 42° 20' 13.8" (RT) D = 6° 21' 58.3" L = 665.03' T = 348.52' R = 900.00' SE = SEE PLANS RO = SEE PLANS
---	---	--

-YI-

PI Sta 10+88.18 Δ = 34° 11' 46.9" (RT) D = 28° 38' 52.4" L = 119.37' T = 61.52' R = 200.00' SE = SEE PLANS RO = SEE PLANS
--

-BL- 1
N. 1985605.5193
E. 572677.2873
ELEV. 369.2361
-L- STA. 13 + 20.99
LT. 24.5541

-BL- 2
N. 1985430.2939
E. 573330.7567
ELEV. 346.8455
-L- STA. 19 + 89.90
LT. 42.8200

BEGIN TIP PROJECT W-5601AF
-L- STA. 12 + 07.00


DATUM DESCRIPTION
THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "W-5601AF-2" WITH NAD 83/NA 2011 STATE PLANE GRID COORDINATES OF NORTHING: 572204.3540(±ft) EASTING: 1985785.7990(±ft) ELEVATION: 383.1000(±ft) THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.999861669 THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "W-5601AF-2" TO -L- STATION 10+00.00 IS S 17° 38' 08" E 183.71 (±ft) ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES VERTICAL DATUM USED IS NAVD 88

6/8/16 - R/W REVISION: SLOPE STAKE LINE ADJUSTED AND PARCEL 6 REMOVED

8/17/99
21-JUL-2016 07:51
SR 1115 (Buffalo Lakes Rd)\Roadway\Proj\W-5601AF_Rdy.psh_4.dgn
SR 1115 (Buffalo Lakes Rd)\Roadway\Proj\W-5601AF_Rdy.psh_4.dgn

FOR PROFILE SEE SHEET 6

PROJECT REFERENCE NO.	SHEET NO.
W-5601AF	5
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER



DATUM DESCRIPTION

THE LOCALIZED COORDINATE SYSTEM DEVELOPED FOR THIS PROJECT IS BASED ON THE STATE PLANE COORDINATES ESTABLISHED BY NCDOT FOR MONUMENT "W-5601AF-2"

WITH NAD 83/NA 2011 STATE PLANE GRID COORDINATES OF
 NORTHING: 572204.3540(ft) EASTING: 1985785.7990(ft)
 ELEVATION: 383.1000(ft)

THE AVERAGE COMBINED GRID FACTOR USED ON THIS PROJECT (GROUND TO GRID) IS: 0.999861669


THE N.C. LAMBERT GRID BEARING AND LOCALIZED HORIZONTAL GROUND DISTANCE FROM "W-5601AF-2" TO -L- STATION 10+00.00 IS
 S 17°38'08" E 183.71 (ft)

ALL LINEAR DIMENSIONS ARE LOCALIZED HORIZONTAL DISTANCES
 VERTICAL DATUM USED IS NAVD 88

REVISIONS

8/17/99

21-Jul-2016 07:51 (C:\Users\lakes\Documents\Roadway\Proj\W-5601AF_Rdwy_psh_5.dgn SR 1115 (Buffalo Lakes Rd)\W-5601AF_838383.dwg)



-BL- 3
 N. 1985594.7579
 E. 573886.4483
 ELEV. 328.4275
 -L- STA. 25 + 59.72
 LT. 21.0155



-BL- 4
 N. 1985817.5860
 E. 574315.9081
 ELEV. 315.1370
 -L- STA. 30 + 43.54
 LT. 18.8574

-BM- 1
 N. 1985665.9634
 E. 573858.0054
 ELEV. 326.6800
 -L- STA. 25 + 66.93
 RT. 55.3211

END TIP PROJECT W-5601AF
-L- STA. 32 + 05.00

FOR PROFILE SEE SHEET 6

PROJECT REFERENCE NO. W-5601AF	SHEET NO. 6
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER




FOR PLAN SEE SHEETS 4 & 5


5/28/99
 21-JUL-2016 07:51
 SR 1115 (Buffalo Lakes Rd)\Roadway\Proj\W-5601AF_Rdy.plt.dgn

PROJECT REFERENCE NO. W-5601AF	SHEET NO. 7
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

-Y-




-Y1-



FOR PLAN SEE SHEET 4


-DRV2-





FOR PLAN SEE SHEET 4


5/28/99


21-Jul-2016 07:51:11 SR 1115 (Buffalo Lakes Rd)\Roadway\Proj\W-5601AF_Rdy.plt.dgn

































75 70 65 60 55 50 45 40 35 30 25 20 15 10 5 0 5 10 15 20 25 30 35 40 45 50 55 60 65 70 75



-DRV2-