

| STATE | STATE PROJECT REFERENCE NO. | SHEET NO. | TOTAL SHEETS |
|-------|-----------------------------|-----------|--------------|
| N.C. | 42608.1.JA9 (M-0423) | 1 | 8 |

**STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT**

**STRUCTURE
SUBSURFACE INVESTIGATION**

PROJ. REFERENCE NO. 42608.1.JA9 (M-0423) F.A. PROJ. NA

COUNTY FORSYTH

PROJECT DESCRIPTION ARRA BRIDGES - DIVISION 9

SITE DESCRIPTION BRIDGE NO.68 ON SR 2014 OVER
BRANCH OF BELEWS CREEK

CONTENTS

| <u>SHEET</u> | <u>DESCRIPTION</u> |
|--------------|--------------------|
| 1 | TITLE SHEET |
| 2-2A | LEGEND |
| 3 | SITE PLAN |
| 4-7 | FINAL BORING LOGS |

PERSONNEL

R. TOOTHMAN

J. ST CLAIR

D. HOWELL

L. STAFFORD

INVESTIGATED BY T. WELLS

CHECKED BY P. WEAVER

SUBMITTED BY P. WEAVER

DATE 3/02/10

CAUTION NOTICE


THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF PREPARING THE SCOPE OF WORK TO BE INCLUDED IN THE REQUEST FOR PROPOSAL. THE VARIOUS FIELD BORING LOGS, ROCK CORES, AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT 1919 250-4088. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES, AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

SOIL AND ROCK BOUNDARIES WITHIN A BOREHOLE ARE BASED ON GEOTECHNICAL INTERPRETATION UNLESS ENCOUNTERED IN A SAMPLE. INTERPRETED BOUNDARIES MAY NOT NECESSARILY REFLECT ACTUAL SUBSURFACE CONDITIONS BETWEEN SAMPLED STRATA, AND BOREHOLE INFORMATION MAY NOT NECESSARILY REFLECT ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS. THE LABORATORY SAMPLE DATA AND THE IN-SITU (ON-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION, AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

NOTE - THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS BEING ACCURATE NOR IS IT CONSIDERED TO BE PART OF THE PLANS, SPECIFICATIONS, OR CONTRACT FOR THE PROJECT.

NOTE - BY HAVING REQUESTED THIS INFORMATION THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.



DRAWN BY: DJH

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

| SOIL DESCRIPTION | | | | | | | | | | GRADATION | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| SOIL IS CONSIDERED TO BE THE UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER, AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO STANDARD PENETRATION TEST (AASHTO T206, ASTM D-1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY SHALL INCLUDE: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. EXAMPLE: <i>VERY STIFF, DARK SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LENSES, HIGHLY PLASTIC, A-7-6</i> | | | | | | | | | | WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORM - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. (ALSO POORLY GRADED) GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLES OF TWO OR MORE SIZES. | | | | | | | | | |
| | | | | | | | | | | SOIL LEGEND AND AASHTO CLASSIFICATION | | | | | | | | | |
| MINERALOGICAL COMPOSITION MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHENEVER THEY ARE CONSIDERED OF SIGNIFICANCE. | | | | | | | | | | COMPRESSIBILITY SLIGHTLY COMPRESSIBLE MODERATELY COMPRESSIBLE HIGHLY COMPRESSIBLE | | | | | | | | | |
| PERCENTAGE OF MATERIAL | | | | | | | | | | GROUND WATER WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING STATIC WATER LEVEL AFTER 24 HOURS PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA SPRING OR SEEP | | | | | | | | | |
| CONSISTENCY OR DENSENESS | | | | | | | | | | MISCELLANEOUS SYMBOLS | | | | | | | | | |
| TEXTURE OR GRAIN SIZE | | | | | | | | | | ABBREVIATIONS | | | | | | | | | |
| SOIL MOISTURE - CORRELATION OF TERMS | | | | | | | | | | EQUIPMENT USED ON SUBJECT PROJECT | | | | | | | | | |
| PLASTICITY | | | | | | | | | | COLOR | | | | | | | | | |
| DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE. | | | | | | | | | | | | | | | | | | | |

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

| ROCK DESCRIPTION | | TERMS AND DEFINITIONS | |
|--|--|---|--------------------------|
| <p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT IF TESTED, WOULD YIELD SPT REFUSAL, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p> | | <p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p> | |
| <p>WEATHERED ROCK (WR)</p>  | <p>NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.</p> | | |
| <p>CRYSTALLINE ROCK (CR)</p>  | <p>FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.</p> | | |
| <p>NON-CRYSTALLINE ROCK (NCR)</p>  | <p>FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.</p> | | |
| <p>COASTAL PLAIN SEDIMENTARY ROCK (CPI)</p>  | <p>COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.</p> | | |
| WEATHERING | | | |
| <p>FRESH</p> | <p>ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p> | | |
| <p>VERY SLIGHT (V SL.)</p> | <p>ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY, ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p> | | |
| <p>SLIGHT (SL.)</p> | <p>ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED, CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</p> | | |
| <p>MODERATE (MOD.)</p> | <p>SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</p> | | |
| <p>MODERATELY SEVERE (MOD. SEV.)</p> | <p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION, ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <u>IF TESTED, WOULD YIELD SPT REFUSAL</u></p> | | |
| <p>SEVERE (SEV.)</p> | <p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT, SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <u>IF TESTED, YIELDS SPT N VALUES > 100 BPF</u></p> | | |
| <p>VERY SEVERE (V SEV.)</p> | <p>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT THE MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE SUCH THAT ONLY MINOR VESTIGES OF THE ORIGINAL ROCK FABRIC REMAIN. <u>IF TESTED, YIELDS SPT N VALUES < 100 BPF</u></p> | | |
| <p>COMPLETE</p> | <p>ROCK REDUCED TO SOIL, ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS, SAPROLITE IS ALSO AN EXAMPLE.</p> | | |
| ROCK HARDNESS | | | |
| <p>VERY HARD</p> | <p>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK, BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</p> | | |
| <p>HARD</p> | <p>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY, HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</p> | | |
| <p>MODERATELY HARD</p> | <p>CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK, HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</p> | | |
| <p>MEDIUM HARD</p> | <p>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT, CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</p> | | |
| <p>SOFT</p> | <p>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK, CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT, SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</p> | | |
| <p>VERY SOFT</p> | <p>CAN BE CARVED WITH KNIFE, CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE, CAN BE SCRATCHED READILY BY FINGER NAIL.</p> | | |
| FRACTURE SPACING | | BEDDING | |
| <p>TERM</p> | <p>SPACING</p> | <p>TERM</p> | <p>THICKNESS</p> |
| <p>VERY WIDE</p> | <p>MORE THAN 10 FEET</p> | <p>VERY THICKLY BEDDED</p> | <p>> 4 FEET</p> |
| <p>WIDE</p> | <p>3 TO 10 FEET</p> | <p>THICKLY BEDDED</p> | <p>1.5 - 4 FEET</p> |
| <p>MODERATELY CLOSE</p> | <p>1 TO 3 FEET</p> | <p>THINLY BEDDED</p> | <p>0.16 - 1.5 FEET</p> |
| <p>CLOSE</p> | <p>0.16 TO 1 FEET</p> | <p>VERY THINLY BEDDED</p> | <p>0.03 - 0.16 FEET</p> |
| <p>VERY CLOSE</p> | <p>LESS THAN 0.16 FEET</p> | <p>THICKLY LAMINATED</p> | <p>0.008 - 0.03 FEET</p> |
| | | <p>THINLY LAMINATED</p> | <p>< 0.008 FEET</p> |
| INDURATION | | | |
| <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF THE MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> | | | |
| <p>FRIABLE</p> | <p>RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> | | |
| <p>MODERATELY INDURATED</p> | <p>GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> | | |
| <p>INDURATED</p> | <p>GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> | | |
| <p>EXTREMELY INDURATED</p> | <p>SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p> | | |
| | | <p>BENCH MARK: BL-2: NE CORNER OF BRIDGE</p> | |
| | | <p align="right">ELEVATION: 783.75 FT.</p> | |
| <p>NOTES: --</p> | | | |



EB1-A
 EB1-B EB2-A
 EB2-B

OFFICE LOCATION: GREENSBORO
 KLEINFELDER JOB NUMBER: 108877
 DRAWING NAME: 202005_1.dwg
 PLOT DATE: 03/03/2010



| | | | |
|-------------------------|--|----------------------|----------|
| PROJECT NO. 42608.1.JA9 | SITE PLAN | | 3 |
| DRAWN: 03/03/2010 | REPLACE BRIDGE NO.68 OVER BRANCH OF BELEWS CREEK ON SR 2014 | | |
| DRAWN BY: DJH | TIP NO. M-0423 | STRUCTURE NO. 340068 | |
| CHECKED BY: PW | FORSYTH COUNTY NORTH CAROLINA | | |
| SCALE: 1" = 100' | | | |

The information indicated on this graphic representation has been compiled from a variety of sources and is subject to change without notice. Kleinfelder makes no representations or warranties, expressed or implied, as to accuracy, completeness, timeliness, or quality in the use of such information. This document is not intended for use as a final survey product nor is it designed or intended to be a construction design document. The user of this information understands and agrees that the user of this graphic representation is at the sole risk of the party using or relying on the information.



NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

| | | | |
|--|--------------------------|-----------------------|---|
| PROJECT NO. 42608.1.JA9 | ID. M-0423 | COUNTY Forsyth | GEOLOGIST T. Wells |
| SITE DESCRIPTION Bridge 68 on SR 2014 over Branch of Belew's Creek | | | GROUND WTR (ft) 0 HR. Dry 24 HR. FIAD |
| BORING NO. EB1-A | STATION N/A | OFFSET N/A | |
| COLLAR ELEV. 784.2 ft | TOTAL DEPTH 36.3 ft | NORTHING 884,169 | EASTING 1,679,901 |
| DRILL MACHINE CME-55 | DRILL METHOD H.S. Augers | HAMMER TYPE Automatic | |
| DRILLER R. Toothman | START DATE 03/08/10 | COMP. DATE 03/08/10 | SURFACE WATER DEPTH N/A |

| ELEV (ft) | DRIVE ELEV (ft) | DEPTH (ft) | BLOW COUNT | | | BLOWS PER FOOT | | | | | SAMP. NO. | MOI | LOG | SOIL AND ROCK DESCRIPTION | | | | |
|-----------|-----------------|------------|------------|--------|-------|----------------|----|----|----|-----|-----------|-----|-----|---------------------------|------------|-----|--|--|
| | | | 0.5ft | 0.5ft | 0.5ft | 0 | 25 | 50 | 75 | 100 | | | | ELEV. (ft) | DEPTH (ft) | | | |
| 785 | | | | | | | | | | | | | | | 784.2 | 0.0 | GROUND SURFACE | |
| 780 | 780.7 | 3.5 | WOH | 1 | 1 | | | | | | | | | W | | | ROADWAY EMBANKMENT Soft, Brown, Coarse to Fine Sandy SILT | |
| 775 | 775.7 | 8.5 | | 3 | 5 | 4 | | | | | | | | W | | | ALLUVIAL Loose, Brown and Gray, Silty, Fine to Coarse SAND | |
| 770 | 770.7 | 13.5 | WOH | 2 | 5 | | | | | | | | | Sat. | | | RESIDUAL Medium Dense, Brown, Silty, Fine to Coarse SAND | |
| 765 | 765.7 | 18.5 | | 7 | 8 | 6 | | | | | | | | Sat. | | | | |
| 760 | 760.7 | 23.5 | | 5 | 10 | 19 | | | | | | | | W | | | WEATHERED ROCK Gray, White and Brown, Biotite Gneiss and Schist | |
| 755 | 755.7 | 28.5 | 60/0.2 | | | | | | | | | | | | | | | |
| 750 | 750.7 | 33.5 | 11 | 89/0.5 | | | | | | | | | | | | | | |
| | 748.2 | 36.0 | 100/0.3 | | | | | | | | | | | | | | | |
| 745 | | | | | | | | | | | | | | | | | | Boring Terminated at Elevation 747.9 ft in Weathered Rock: Biotite Gneiss and Schist |
| 740 | | | | | | | | | | | | | | | | | | |
| 735 | | | | | | | | | | | | | | | | | | |
| 730 | | | | | | | | | | | | | | | | | | |
| 725 | | | | | | | | | | | | | | | | | | |
| 720 | | | | | | | | | | | | | | | | | | |
| 715 | | | | | | | | | | | | | | | | | | |
| 710 | | | | | | | | | | | | | | | | | | |
| 705 | | | | | | | | | | | | | | | | | | |

NCDOT BORE SINGLE 109827.GPJ NC_DOT.GDT 3/19/10



NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

| | | | |
|--|--------------------------|-----------------------|-------------------------|
| PROJECT NO. 42608.1.JA9 | ID. M-0423 | COUNTY Forsyth | GEOLOGIST T. Wells |
| SITE DESCRIPTION Bridge 68 on SR 2014 over Branch of Belew's Creek | | | GROUND WTR (ft) |
| BORING NO. EB1-B | STATION N/A | OFFSET N/A | ALIGNMENT N/A |
| COLLAR ELEV. 784.3 ft | TOTAL DEPTH 39.0 ft | NORTHING 884,159 | EASTING 1,679,888 |
| DRILL MACHINE CME-55 | DRILL METHOD H.S. Augers | HAMMER TYPE Automatic | |
| DRILLER R. Toothman | START DATE 03/09/10 | COMP. DATE 03/09/10 | SURFACE WATER DEPTH N/A |

| ELEV (ft) | DRIVE ELEV (ft) | DEPTH (ft) | BLOW COUNT | | | BLOWS PER FOOT | | | | | SAMP. NO. | MOI | LOG | SOIL AND ROCK DESCRIPTION | DEPTH (ft) |
|-----------|-----------------|------------|------------|--------|--------|----------------|----|----|----|---------|-----------|-----|------|--|------------|
| | | | 0.5ft | 0.5ft | 0.5ft | 0 | 25 | 50 | 75 | 100 | | | | | |
| 785 | | | | | | | | | | | | | | GROUND SURFACE | 0.0 |
| 780 | 780.8 | 3.5 | 1 | 1 | 2 | | | | | | | | W | ROADWAY EMBANKMENT Very Loose, Brown, Silty, Coarse to Fine SAND | |
| 775 | 775.8 | 8.5 | 1 | 2 | 2 | | | | | | | | W | ALLUVIAL Soft to Medium Stiff, Gray, Coarse to Fine Sandy SILT with Trace of Organic Matter | 6.5 |
| 770 | 770.8 | 13.5 | 1 | 1 | 2 | | | | | | | | Sat. | Very Loose, Light Brown, Silty, Fine to Coarse SAND | 12.0 |
| 765 | 765.8 | 18.5 | 28 | 72/0.3 | | | | | | 100/0.6 | | | | WEATHERED ROCK Brown and Gray, Biotite Gneiss and Schist | 18.5 |
| 760 | 760.8 | 23.5 | 3 | 8 | 15 | | | | | | | | W | RESIDUAL Medium Dense, Brown, Silty, Coarse to Fine SAND | 21.5 |
| 755 | 755.8 | 28.5 | 5 | 48 | 52/0.1 | | | | | 100/0.6 | | | | WEATHERED ROCK Brown, Biotite Gneiss and Schist | 28.5 |
| 750 | 750.8 | 33.5 | 23 | 35 | 42 | | | | | 77 | | | W | RESIDUAL Very Dense, Gray and Brown, Silty, Coarse to Fine SAND | 33.0 |
| 745 | 745.8 | 38.5 | 100/0.5 | | | | | | | 100/0.5 | | | | WEATHERED ROCK Gray, Biotite Gneiss and Schist | 36.0 |
| 740 | | | | | | | | | | | | | | Boring Terminated at Elevation 745.3 ft in Weathered Rock: Biotite Gneiss and Schist | 39.0 |
| 735 | | | | | | | | | | | | | | | |
| 730 | | | | | | | | | | | | | | | |
| 725 | | | | | | | | | | | | | | | |
| 720 | | | | | | | | | | | | | | | |
| 715 | | | | | | | | | | | | | | | |
| 710 | | | | | | | | | | | | | | | |
| 705 | | | | | | | | | | | | | | | |

NCDOT BORE SINGLE 109827.GPJ NC_DOT_GDT 3/19/10



NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

| | | | |
|--|--------------------------|-----------------------|-------------------------|
| PROJECT NO. 42608.1.JA9 | ID. M-0423 | COUNTY Forsyth | GEOLOGIST T. Wells |
| SITE DESCRIPTION Bridge 68 on SR 2014 over Branch of Belew's Creek | | | GROUND WTR (ft) |
| BORING NO. EB2-B | STATION N/A | OFFSET N/A | 0 HR. Dry |
| COLLAR ELEV. 784.7 ft | TOTAL DEPTH 28.8 ft | NORTHING 884,145 | 24 HR. FIAD |
| DRILL MACHINE CME-55 | DRILL METHOD H.S. Augers | HAMMER TYPE Automatic | |
| DRILLER R. Toothman | START DATE 03/08/10 | COMP. DATE 03/08/10 | SURFACE WATER DEPTH N/A |

| ELEV (ft) | DRIVE ELEV (ft) | DEPTH (ft) | BLOW COUNT | | | BLOWS PER FOOT | | | | | SAMP. NO. | LOG | SOIL AND ROCK DESCRIPTION | DEPTH (ft) | | |
|-----------|-----------------|------------|------------|-------|-------|----------------|--------|----|----|---------|-----------|-----|---------------------------|------------|------------|--|
| | | | 0.5ft | 0.5ft | 0.5ft | 0 | 25 | 50 | 75 | 100 | | | | | ELEV. (ft) | |
| 785 | | | | | | | | | | | | | | 784.7 | 0.0 | GROUND SURFACE |
| 780 | 781.2 | 3.5 | | WOH | 1 | 2 | | | | | | | W | | | ROADWAY EMBANKMENT Soft, Brown, Coarse to Fine Sandy, Silty CLAY |
| 775 | 776.2 | 8.5 | | | 1 | 2 | 4 | | | | | | W | | 7.5 | ALLUVIAL Medium Stiff, Gray, Coarse to Fine Sandy SILT |
| 770 | 771.2 | 13.5 | | | 1 | 1 | 1 | | | | | | Sat. | | 12.0 | Very Loose, Gray, Silty, Coarse to Fine SAND |
| 765 | 766.2 | 18.5 | | | 11 | 46 | 54/0.2 | | | | | | | | 18.5 | WEATHERED ROCK Gray and Brown, Biotite Gneiss and Schist |
| 760 | 761.2 | 23.5 | | | 11 | 89/0.3 | | | | 100/0.7 | | | | | | |
| 755 | 756.2 | 28.5 | | | | | | | | 100/0.3 | | | | | 28.8 | Boring Terminated at Elevation 755.9 ft in Weathered Rock: Biotite Gneiss and Schist |
| 750 | | | | | | | | | | | | | | | | |
| 745 | | | | | | | | | | | | | | | | |
| 740 | | | | | | | | | | | | | | | | |
| 735 | | | | | | | | | | | | | | | | |
| 730 | | | | | | | | | | | | | | | | |
| 725 | | | | | | | | | | | | | | | | |
| 720 | | | | | | | | | | | | | | | | |
| 715 | | | | | | | | | | | | | | | | |
| 710 | | | | | | | | | | | | | | | | |
| 705 | | | | | | | | | | | | | | | | |

NCDOT BORE_SINGLE 109827.GPJ NC_DOT_GDT 3/19/10