



LATERAL CLEARANCE
 1 meter MINIMUM FROM TRAVEL LANE. PLACE SIGN BEYOND SHOULDER POINT IF IT CANNOT BE INSTALLED PLUMB. IF SIGN IS PLACED WITHIN A LANE CLOSURE OR ON THE TRAVELWAY, THE CLEARANCE APPLIES FROM THE OPEN LANE.

SEE STANDARD SPECIFICATIONS FOR APPROVED SIGN SUBSTRATE MATERIAL

MOUNTING HEIGHT DIMENSIONS

ROADWAY TO SIGN 0.3m MINIMUM. FOR INTERSTATE OR OTHER HIGH VOLUME ROADWAYS USE 1.5m MINIMUM.

IF SUPPLEMENTAL PANEL IS REQUIRED USE A 1.5m MINIMUM HEIGHT TO MAIN SIGN WITH A 1.2m MINIMUM HEIGHT TO PANEL

GENERAL NOTES

- 1- DIMENSIONS SHOWN ARE MINIMUM VALUES. MOUNT SIGNS SO THEY WILL BE CLEARLY VISIBLE TO APPROACHING TRAFFIC EVEN WHEN SIGNS ARE MOUNTED BEHIND TRAFFIC CONTROL DEVICES SUCH AS DRUMS, BARRIER, OR OTHER OBJECTS,
- 2- ALL PORTABLE SIGNS AND STANDS MUST MEET OR EXCEED THE REQUIREMENTS OF NCHRP 350 FOR WORK ZONE CATEGORY II DEVICES. USE PORTABLE WORK ZONE SIGNS AND STANDS SPECIFICALLY DESIGNED FOR ONE ANOTHER.
- 3- ALL PORTABLE WORK ZONE SIGNS AND STANDS MUST BE LISTED ON NORTH CAROLINA'S APPROVED PRODUCTS LIST OR ACCEPTED AS TRAFFIC QUALIFIED BY THE WORK ZONE TRAFFIC CONTROL UNIT.

NOTE:
 THIS DRAWING IS DIMENSIONED IN MILLIMETERS UNLESS OTHERWISE DEPICTED WITHIN THE DRAWING.