

## PAVEMENT SCHEDULE (continued)

6-1D

CODE LETTER	ITEM
A	Portland Cement Concrete Pavement
B	Open-Graded Asphalt Friction Course, Type FC
C	Asphalt Concrete Surface Course, Type S
D	Asphalt Concrete Intermediate Course, Type I
E	Asphalt Concrete Base Course, Type B
F	Asphalt Surface Treatment
G	Cement Treated Base Course
J	Aggregate Base Course
K	Stabilized Subgrade
L	Stabilizer Aggregate
M	Soil Type Base Course
N	Geotextile
P	Prime Coat
R	Combination Concrete Curb and Gutter Concrete Curb 5" Monolithic Concrete Island Concrete Island Cover
S	Concrete Sidewalk
T	Earth Material
U	Existing Pavement
V	As needed
W	Variable Depth Asphalt Pavement (See Standard Wedging Detail).
X	Permeable Asphalt Drainage Course, Type P
Y Z	As needed

REV. DATE 02/05/18  
REV. NO. 8

PAVEMENT SCHEDULE (continued)

6-1D

F-1

- E3 Prop. Var. Depth Asphalt Concrete Base Course, Type B \_\_\_\_\_, at an Average Rate of 114lbs. per sq. yd. per 1" depth, to be placed in layers not greater than \_\_\_\_\_" in depth or less than \_\_\_\_\_" in depth.
- F1 Asphalt Surface Treatment, Mat and Seal.
- F2 Asphalt Surface Treatment, \_\_\_\_\_
- G Prop. Approx. 8" Cement Treated Base Course (Plant Mixed)  
**or**  
 Prop. 8" ABC with the top 7" to be Cement Treated (Road Mixed).
- J1 Prop. 8" Aggregate Base Course
- J2 Prop. 10" Aggregate Base Course
- J3 Prop. Var. Depth Aggregate Base Course
- K1 Prop. 8" Chemical Stabilization (Soil-Cement Base/Lime-Treated Soil). Base treated with Cement at a Rate of 55 lbs. per sq. yard or Soil treated with Lime at a Rate of 20 lbs. per sq. yard.
- K2 Prop. 8" Class IV Subgrade Stabilization
- L Base to be stabilized with 200 to 400 lbs. per sq. yard of Stabilizer Aggregate mixed with the top 3" of subgrade soil at locations directed by the Engineer.
- M1 Prop. 8" Soil Type Base Course, Type A
- M2 Prop. 10" Soil Type Base Course, Type \_\_\_\_\_
- N1 Geotextile for Pavement Stabilization
- N2 Geotextile for Soil Stabilization**
- P1 Prime Coat at the rate of .35 gal. per sq. yard.
- P2 Prime Coat at the rate of .50 gal. per sq. yard.