Goodan

State of North Carolina DEPARTMENT OF TRANSPORTATION

DAVID MCCOY SECRETARY

JASON MOORE

T. HUFFMAN
S. PRIDGEN
TT III

T IR

J. MORRISON
D. RICHARDSON
W. STEINBROOK
B. WEDEKING
CYNTHIA PERRY
D. GARDNER

J. jorinson J. gaddy

TT II

MEMOTO:

Roadway Design Project Engineers

For

FROM:

John Alford, PE D. J. Likes

DATE:

April 25, 2000

SUBJECT:

Intermediate Guiderail Anchors

This is to address plan incongruity with Intermediate Guiderail Anchors. These anchors have sometimes but not always been shown on our plans. Intermediate Guiderail Anchors are used at 2000 feet maximum intervals in continuous guiderail. The anchors overlap and there is no actual break in the guiderail. A sketch is attached.

It is not necessary nor desired to show these anchors since the provisions dictate their placement. We need only calculate them similar to fence post calculation and show in the guardrail summary. In the interest of plan uniformity, do not show these Intermediate Anchors in the plan view of your cable guiderail.

Thank you for you help in this matter.

JEA/dls

Attachment

cc: Dewayne Sykes, PE
Jay Bennett, PE
Jimmy Norris
Ross McDowell
Bob Brown, PE
Charlie Casey, PE