1 2	SECTION 1006 AGGREGATE QUALITY CONTROL/QUALITY ASSURANCE
3 4 5 6 7 8 9	The Aggregate QC/QA Program is designed to give aggregate producers more responsibility for controlling the quality of material they produce and to use the quality control information they provide in the acceptance process by the Department. It requires aggregate producers to perform quality control sampling, testing and record keeping on aggregates they ship for use by the Department. It requires the Department to perform quality assurance sampling, testing and record keeping confirming the performance of the producers' control plan. The program is described in the <i>Aggregate QC/QA Program Manual</i> .
10 11	Participation in this program does not relieve the producer of the responsibility of complying with all requirements of the Department's <i>Standard Specifications</i> .
12	SECTION 1008
13	AGGREGATE FOR STABILIZATION
14	1008-1 AGGREGATE STABILIZATION
15	(A) General
16 17	Aggregates consist of crushed stone, crushed gravel, uncrushed gravel or other similar material having hard, strong, durable particles free of adherent coatings.
18 19 20 21 22 23	Supply aggregates from approved sources participating in the Department's Aggregate QC/QA Program in accordance with Sections 1005 and 1006. Sources will not be approved unless the material has satisfactory soundness and satisfactory resistance to abrasion. Satisfactory soundness will be a loss in weight of not greater than 15% when subject to 5 alternations of the soundness test. Satisfactory resistance to abrasion will be a percentage of wear of not greater than 55%.
24	(B) Sampling and Acceptance
25 26 27	Sampling and acceptance for the determination of gradation, LL and PI will be performed as described in the <i>Aggregate QC/QA Program Manual</i> and the <i>Aggregate Sampling Manual</i> using the versions in effect at the time material is shipped.
28	SECTION 1010
29	AGGREGATE FOR NON-ASPHALT TYPE BASES
30	1010-1 AGGREGATE BASE COURSE
31	(A) General Requirements
32 33 34	Aggregate base course material consists of crushed stone, crushed gravel, uncrushed gravel or other similar material having hard, strong, durable particles free of adheren coatings.
35 36 37 38 39 40	Provide aggregates from approved sources participating in the Department's Aggregate QC/QA Program in accordance with Sections 1005 and 1006. Sources will not be approved unless the material has satisfactory soundness and resistance to abrasion Satisfactory soundness will be a weighted average loss of not greater than 15% wher subjected to 5 alternations of the soundness test. Satisfactory resistance to abrasion will be a percentage of wear of not greater than 55%.
41	(B) Sampling and Acceptance
42 43 44	Sampling and acceptance for the determination of gradation, LL and PI will be performed as described in the <i>Aggregate QC/QA Program Manual</i> and the <i>Aggregate Sampling Manual</i> using the versions in effect at the time material is shipped.