

| <b>TABLE 1070-2</b>                                 |             |                     |                      |
|---|-------------|---------------------|----------------------|
| <b>SPIRAL COLUMN REINFORCEMENT STEEL PROPERTIES</b> |             |                     |                      |
| <b>Material</b>                                     | <b>Size</b> | <b>Area, sq.in.</b> | <b>Weight, lb/ft</b> |
| Plain Cold Drawn Wire                               | W 20        | 0.20                | 0.668                |
|   | W 31        | 0.31                | 1.043                |
| Deformed Cold Drawn Wire                            | D-20        | 0.20                | 0.680                |
|   | D-31        | 0.31                | 1.054                |
| Plain or Deformed Bar                               | #4          | 0.20                | 0.668                |
|   | #5          | 0.31                | 1.043                |

1 Use cold drawn wire conforming to AASHTO M 32. Use plain or deformed bars conforming  
2 to AASHTO M 31 for Grade 60. Use deformed cold drawn wire conforming to  
3 AASHTO M 225.

4 The diameter of the spiral reinforcing steel is the outside to outside measurement of the bars  
5 or wire, with an allowance of 1/2" more or 1/2" less than the specified diameter as shown in  
6 the plans.

7 Furnish spirals with 1.5 extra turns at top and at bottom of the completed spiral cage. Where  
8 splicing of the spirals is necessary other than those shown in the plans, provide a minimum  
9 lap splice of 3 ft.

10 Do not weld on the spiral reinforcing steel.

11 When required by the plans, use epoxy coated spiral column reinforcing steel including  
12 spacers in accordance with Article 1070-7.

13 Use the minimum number of spiral spacers as shown in the plans. Ensure a minimum section  
14 modulus per spiral spacer of 0.030 cu.in.

#### 15 **1070-9 MECHANICAL BUTT SPLICES**

16 When called for by the contract or when directed by the Engineer, use a mechanical butt  
17 reinforcing steel splice from an approved source. Use a standard metal filled sleeve, cement  
18 mortar filled sleeve, threaded steel couplings, forged steel sleeve or cold-forged sleeve.  
19 An exothermic process whereby molten filler metal, contained by a high strength steel sleeve  
20 of larger inside diameter than the bars, is introduced into the annular space between the bars  
21 and the sleeve and between the ends of the bars may be used. Provide a splice that is capable  
22 of transferring at least 125% of the yield strength of the bars from one bar to the other by the  
23 mechanical strength of the splice components.

24 For splices not on the approved list, before use and as a condition of approval, assemble 3 test  
25 splices in the presence of the Engineer for each size of bar which is proposed for use on the  
26 project. Forward the test splices to the Materials and Tests Unit in Raleigh, NC for testing  
27 and approval.

## 28 **SECTION 1072**

### 29 **STRUCTURAL STEEL**

#### 30 **1072-1 GENERAL**

31 Furnish and fabricate all structural steel and related incidental materials including sign  
32 supports and high mount lighting standards and use materials in accordance with this section.

#### 33 **(A) Fabricator Qualification**

34 Use steel fabricators on the Department's Approved Structural Steel Fabricators List for  
35 the type work being performed. The list is available from the Materials and Tests Unit or  
36 on the Department's website.

## Section 1072

1       Employ fabricators of high mount lighting standards in excess of 80 ft in length,  
2       structural steel components of fender systems, retaining walls and noise walls, sign  
3       supports, sign structures, pot and expansion bearings, simple span rolled beams,  
4       including those requiring cover plates, solar array platforms and modular expansion joints  
5       that are AISC certified in Simple Steel Bridges. Employ fabricators of heat curved rolled  
6       beams, rolled beams for continuous spans and plate girders that are AISC certified in  
7       Major Steel Bridges. Employ fabricators of fracture critical bridge beams and girders  
8       that have a Fracture Critical Members Endorsement from AISC. Ensure that fabricators,  
9       applying over 1,500 sf of coating for each project, have a Sophisticated Paint System  
10       Endorsement from AISC or a Quality Procedure 3 Certification from the Society of  
11       Protective Coatings.

12       When AISC certification is required, submit proof of registration and certification of the  
13       plant or shop under the AISC program to the State Materials Engineer before beginning  
14       fabrication and on an annual basis. The same requirements apply to fabricators  
15       subcontracting work from the fabricator directly employed by the Contractor.

### 16       **(B) Office**

17       Ensure that fabricators of main structural steel components of bridges provide an office  
18       area with an approximate floor space of 100 sf, a desk or drafting table, 2 chairs,  
19       telephone, facilities for proper heating and cooling, telephone, separate dial-up or faster  
20       internet access and adequate lighting and located at the plant site for the exclusive use of  
21       the Engineer. Ensure fabricators of other structural steel items furnish reasonable work  
22       areas for the Engineer.

### 23       **1072-2 SHAPES, PLATES, BARS AND SHEETS**

24       Use shapes, plates, bars and sheets meeting AASHTO M 270 Grade 36 unless otherwise  
25       required by the contract. For painted beams or girders, use sheet material of 1/32" in  
26       thickness meeting ASTM A1008 or A1011, and sheet material of 1/16" through 5/32"  
27       thickness meeting ASTM A1011 for Grades 36, 40 or 45. For unpainted beams or girders,  
28       use sheet material less than 3/16" thickness meeting ASTM A606 for Type 4.

### 29       **1072-3 BEARING PLATE ASSEMBLIES**

30       Unless otherwise shown in the plans, galvanize steel bearing assemblies for both structural  
31       steel beams and girders and prestressed concrete girders. Galvanize anchor bolts, nuts and  
32       washers in accordance with AASHTO M 232. Cut pipe sleeves and collars from Schedule 40  
33       PVC pipe meeting ASTM D1785.

34       Except for attachments of bearing plates to beams, fabricate and weld bearing plate  
35       assemblies before galvanizing the steel. Seal all joints of welded parts with weld material.  
36       After the fabrication of the bearing plate assembly is complete, galvanize the assembly in  
37       accordance with AASHTO M 111. For prestressed concrete girders, clean welds made for  
38       attaching bearing plates to beams or girders and give them 2 coats of organic zinc repair paint  
39       having a minimum total coating thickness of 3 dry mils. For steel beams and girders, clean  
40       and paint in accordance with Article 442-10.

41       Repair galvanized surfaces that are abraded or damaged at any time after the application of  
42       the zinc coating by thoroughly wire brushing the damaged areas and removing all loose and  
43       cracked coating, after which give the cleaned area 2 coats of organic zinc repair paint having  
44       a minimum total coating thickness of 3 dry mils.

45       Use zinc rich paint meeting Article 1080-9.

### 46       **1072-4 ANCHOR BOLTS**

47       Unless otherwise stated herein, use anchor bolts meeting ASTM A307 for Grade A.

48       Provide anchor bolts for bearing plate assemblies meeting ASTM A449.

1 Swedge anchor bolts for a distance equal to the embedment length minus 3" measured from  
2 the embedded end.

3 Hot-dip galvanize anchor bolts, nuts and washers in accordance with AASHTO M 232.

4 **1072-5 HIGH STRENGTH BOLTS, NUTS AND WASHERS**

5 **(A) General**

6 Furnish all high-strength bolts, nuts and washers, including direct tension indicators, in  
7 accordance with the appropriate AASHTO or ASTM materials specifications as amended  
8 and revised herein.

9 Furnish the Engineer a copy of the manufacturer's test report for each component.  
10 Ensure the report indicates the testing date, the city and state where the components were  
11 manufactured, the lot number of the material represented, the rotational capacity tests lot  
12 number and the source identification marking used by the manufacturer of each  
13 component. On test reports for direct tension indicators, include the tension load at  
14 which indicators are tested, gap clearance, nominal size and coating thickness.

15 Produce each permanent fastener component installed in a structure from domestically  
16 processed material containing the grade identification markings required by the  
17 applicable reference specification and the manufacturer's source identification marking.  
18 A copy of the source identification marking used by each manufacturer is on file with the  
19 Department's Materials and Tests Unit.

20 Obtaining permanent bolts, nuts and washers in any one structure from different  
21 manufacturers is allowed provided:

22 (1) All bolts are produced by only one manufacturer.

23 (2) All nuts are produced by only one manufacturer.

24 (3) All washers are produced by only one manufacturer.

25 Have all fasteners used in a structure furnished by the fabricator of the steel. Require the  
26 fabricator to submit the fasteners for sampling and testing at least 5 weeks before delivery  
27 to the project site. Sample and test each diameter and length of bolt, nut and washer  
28 assembly in accordance with Table 1072-1.

| <b>TABLE 1072-1</b>                          |                          |
|--|--------------------------|
| <b>SAMPLING REQUIREMENTS FOR</b>             |                          |
| <b>HIGH STRENGTH BOLTS, NUTS AND WASHERS</b> |                          |
| <b>Lot Quantity</b>                          | <b>Number of Samples</b> |
| 0-800  | 3 Assemblies             |
| 801-8000                                     | 6 Assemblies             |
| > 8000                                       | 9 Assemblies             |

29 Ship only those fasteners to the project that are sampled, tested and approved. Protect the  
30 material from moisture during storage such that it does not contain any indication of rust  
31 at the time of installation. Ensure that each component contains a thin coat of lubricant at  
32 the time of installation.

33 When galvanized high strength bolts are required, use bolts, nuts and washers meeting  
34 Subarticle 1072-5(F).

35 When corrosion resistant structural steel is required by the plans, provide fasteners with  
36 atmospheric corrosion resistance and weathering characteristics comparable to that of the  
37 structural steel.

38 **(B) Specifications**

39 Ensure that all bolts meet ASTM A325.

## Section 1072

1 Ensure that all nuts meet ASTM A194 as applicable or ASTM A563. Completely coat  
2 each nut with a wax lubricant.

3 Ensure that all washers meet ASTM F436.

4 Ensure that all direct tension indicators meet ASTM F959.

### 5 (C) Manufacturing

#### 6 (1) Bolts

7 Hardness for bolt diameters 1/2" to 1" inclusive shall be 248 to 311 Brinell hardness  
8 and 24 to 33 Rockwell C hardness.

#### 9 (2) Nuts

10 (a) Heat treat galvanized nuts to Grades 2H, DH or DH3.

11 (b) Use plain (ungalvanized) nuts of Grades 2, C, D or C3 with a minimum  
12 Rockwell hardness of 89 HRB or Brinell hardness of 180 HB, or heat treat to  
13 Grades 2H, DH or DH3. The hardness requirements for Grades 2, C, D and C3  
14 exceed the current AASHTO/ASTM requirements.

15 (c) Tap oversize galvanized nuts the minimum amount required by ASTM A563.  
16 Overtap the nut such that the nut assembles freely on the bolt in the coated  
17 condition and meets mechanical requirements of ASTM A563 and the  
18 rotational-capacity test herein.

19 (3) Mark all bolts, nuts and washers in accordance with the appropriate  
20 AASHTO/ASTM Specifications.

#### 21 (4) Direct Tension Indicators

22 (a) For Type 3 high strength bolts, mechanically galvanize direct tension indicators  
23 to ASTM B695, Class 55, and then apply baked epoxy to a thickness of 1 mil  
24 minimum. Direct tension indicators need not be mechanically galvanized or  
25 epoxy coated if they are made from material conforming to ASTM A325,  
26 Type 3 bolts.

27 (b) For plain Type 1 high strength bolts, provide direct tension indicators that are  
28 plain or mechanically galvanized to ASTM B695, Class 55.

29 (c) For galvanized Type 1 high strength bolts, mechanically galvanize direct tension  
30 indicators to ASTM B695, Class 55.

### 31 (D) Testing

#### 32 (1) Bolts

33 (a) Proof load tests in accordance with ASTM F606, Method 1, are required at the  
34 minimum frequency as specified in AASHTO M 164, Paragraph 9.2.4.

35 (b) Wedge tests on full size bolts in accordance with ASTM F606, Paragraph 3.5,  
36 are required. If bolts are galvanized, perform the tests after galvanizing. Test at  
37 a minimum frequency as specified in AASHTO M 164, Paragraph 9.2.4.

38 (c) If galvanized bolts are supplied, measure the thickness of the zinc coating. Take  
39 measurements on the wrench flats or top of bolt head.

#### 40 (2) Nuts

41 (a) Proof load tests in accordance with ASTM F606, Paragraph 4.2, are required at  
42 the minimum frequency of as specified in ASTM A563 and ASTM A194. If  
43 nuts are galvanized, perform the tests after galvanizing, overlapping and  
44 lubricating.

- 1 (b) If galvanized nuts are supplied, measure the thickness of the zinc coating. Take  
2 measurements on the wrench flats.
- 3 (3) Washers
- 4 (a) If galvanized washers are supplied, perform hardness testing after galvanizing.
- 5 (b) Remove the coating before taking hardness measurements.
- 6 (c) If galvanized washers are supplied, measure the thickness of the zinc coating.
- 7 (d) Test direct tension indicators in accordance with ASTM F959.
- 8 (4) Assemblies
- 9 Rotational-capacity tests are required. Ensure the manufacturer or distributor  
10 perform such tests on all black or galvanized (after galvanizing) bolt, nut and washer  
11 assemblies before shipping. Washers are required as part of the test.
- 12 The following applies:
- 13 (a) Except as modified herein, perform the rotational-capacity test in accordance  
14 with ASTM A325.
- 15 (b) Test each combination of bolt production lot, nut lot and washer lot as  
16 an assembly. Where washers are not required by the installation procedures,  
17 do not include in the lot identification.
- 18 (c) Assign a rotational-capacity lot number to each combination of lots tested.
- 19 (d) The minimum frequency of testing is 2 assemblies per rotational-capacity lot.
- 20 (e) Assemble the bolt, nut and washer assembly in a Skidmore-Wilhelm Calibrator  
21 or an acceptable equivalent device (This requirement supersedes the current  
22 ASTM A325 requirement to perform the test in a steel joint). For short bolts  
23 that are too short for assembly in the Skidmore-Wilhelm Calibrator, see  
24 Subarticle 1072-5(D)(4)(i).
- 25 (f) The minimum rotation, from a snug tight condition (10% of the specified proof  
26 load), is: 240° (2/3 turn) for bolt lengths less than 4 diameters; 360° (1 turn) for  
27 bolt lengths greater than 4 diameters and less than 8 diameters; 480° (1 1/3 turn)  
28 for bolt lengths greater than 8 diameters.
- 29 (g) These values differ from the AASHTO M 164 Table 8 specifications.
- 30 (h) Achieve tension at the above rotation equal to or greater than 1.15 times the  
31 required installation tension. The installation tension and the tension for the turn  
32 test are shown in Table 1072-2.

| <b>Diameter, inch</b>           | <b>1/2"</b> | <b>5/8"</b> | <b>3/4"</b> | <b>7/8"</b> | <b>1"</b> | <b>1 1/8"</b> | <b>1 1/4"</b> | <b>1 3/8"</b> | <b>1 1/2"</b> |
|---------------------------------|-------------|-------------|-------------|-------------|-----------|---------------|---------------|---------------|---------------|
| Req. Installation Tension, kips | 12          | 19          | 27          | 39          | 51        | 56            | 71            | 85            | 103           |
| Turn Test Tension, kips         | 14          | 22          | 32          | 45          | 59        | 64            | 82            | 98            | 118           |

## Section 1072

- 1 (i) After the required installation tension listed in Table 1072-2 is exceeded, one  
2 reading of tension and torque is taken and recorded. The torque value shall  
3 conform to the following equation:

$$\text{Torque} \leq 0.25(P \times D)$$

Where:

**Torque** = measured torque in foot-pounds  
**P** = measured bolt tension in pounds  
**D** = bolt diameter in feet

- 4 For bolts that are too short to test in a Skidmore-Wilhelm Calibrator, test in  
5 a steel joint. The tension requirement of Subarticle 1072-5(D)(4)(h) is  
6 computed using a value of **P** equal to the turn test tension shown in the  
7 Table 1072-2.

### 8 (5) Reporting

- 9 (a) Record the results of all tests, including zinc coating thickness, required herein  
10 and in the appropriate AASHTO specifications on the appropriate document.  
11 (b) Report the location where tests are performed and date of tests on the  
12 appropriate document.

### 13 (6) Witnessing

- 14 Witness of the test by an inspection agency is not required; however, ensure the  
15 manufacturer or distributor performing the tests certifies that the recorded results are  
16 accurate.

### 17 (7) Documentation

#### 18 (a) Mill Test Report(s)

- 19 (i) Furnish Mill Test Report(s) for all mill steel used in the manufacture of the  
20 bolts, nuts or washers.  
21 (ii) Indicate in the Mill Test Report the place where the material was melted  
22 and manufactured, the lot number of the material represented and the source  
23 identification used by the manufacturer.

#### 24 (b) Manufacturer Certified Test Report(s)


- 25 (i) Have the manufacturer of the bolts, nuts and washers furnish Manufacturer  
26 Certified Test Report(s) for the item furnished.  
27 (ii) Include in each Manufacturer Certified Test Report the relevant information  
28 required in accordance with Subarticle 1072-5(D)(5).  
29 (iii) Have the manufacturer performing the rotational-capacity test include on  
30 the Manufacturer Certified Test Report:  
31 A) The lot number of each of the items tested.  
32 B) The rotational-capacity lot number as required in  
33 Subarticle 1072-5(D)(4)(c).  
34 C) The results of the tests required in Subarticle 1072-5(D)(4).  
35 D) The pertinent information required in Subarticle 1072-5(D)(5)(b).  
36 E) A statement that the Manufacturer Certified Test Report for the items  
37 are in conformance to the *Standard Specifications* and the appropriate  
38 AASHTO specifications.  
39 F) The location where the bolt assembly components were manufactured.

- 1 (c) Distributor Certified Test Report(s)
- 2 (i) Ensure that the Distributor Certified Test Report(s) includes Manufacturer
- 3 Certified Test Reports above for the various bolt assembly components.
- 4 (ii) Ensure the rotational-capacity test is performed by a distributor or
- 5 a manufacturer and reported on the Distributor Certified Test Report.
- 6 (iii) Include in the Distributor Certified Test Report the results of the tests
- 7 required in Subarticle 1072-5(D)(4).
- 8 (iv) Include in the Distributor Certified Test Report the pertinent information
- 9 required in Subarticle 1072-5(D)(5)
- 10 (v) Include in the Distributor Certified Test Report the rotational-capacity lot
- 11 number as required in Subarticle 1072-5(D)(4)(c).
- 12 (vi) Ensure that the Distributor Certified Test Report certifies that the
- 13 Manufacturer Certified Test Reports are in conformance to this *Standard*
- 14 *Specifications* and the appropriate AASHTO specifications.

15 **(E) Shipping**

- 16 (1) Ship bolts, nuts and washers, where required, from each rotational-capacity lot in the
- 17 same container. If there is only one production lot number for each size of nut and
- 18 washer, shipping of the nuts and washers in separate containers is allowed.
- 19 Permanently mark each container on the side with the rotational-capacity lot number
- 20 such that identification is possible at any stage before installation.
- 21 (2) Provide the appropriate MTR and MCTR or DCTR to the contractor or owner as
- 22 required by the contract.

Section 1072



1 **Figure 1072-1. Bolt and nut description.** Bolt and nut marking varies. Refer to  
 2 Subarticle 1072-5(B). **F** is the width across the flats of the bolt. **H** is the height of the bolt or  
 3 nut. Nuts may be washer facing as in (a) or double chamfered as in (b). **D** is the bolt  
 4 diameter and nominal bolt size. **W** is the width across the flats of the nut.

| <b>TABLE 1072-3<br/>HIGH STRENGTH BOLTS<br/>BOLT AND NUT DIMENSIONS</b> |   |               |                          |   |               |
|---|---|---------------|--------------------------|---|---------------|
| <b>Nominal Bolt<br/>Size, inch</b>                                      | <b>Heavy Hexagon Structural Bolt<br/>Dimensions, inch</b> |               |                          | <b>Semi-Finished Heavy<br/>Hexagon Nut<br/>Dimensions, inch</b> |               |
|   | <b>Width Across<br/>Flats</b>                             | <b>Height</b> | <b>Thread<br/>Length</b> | <b>Width<br/>Across Flats</b>                                   | <b>Height</b> |
| <i>(D)</i>  | <i>(F)</i>  | <i>(H)</i>    | <i>(Thread)</i>          | <i>(W)</i>  | <i>(H)</i>    |
| 1/2   | 7/8   | 5/16          | 1                        | 7/8   | 31/64         |
| 5/8   | 1 1/16  | 25/64         | 1 1/4                    | 1 1/16  | 39/64         |
| 3/4   | 1 1/4   | 15/32         | 1 3/8                    | 1 1/4   | 47/64         |
| 7/8   | 1 7/16  | 35/64         | 1 1/2                    | 1 7/16  | 55/64         |
| 1   | 1 5/8   | 39/64         | 1 3/4                    | 1 5/8   | 63/64         |
| 1 1/8   | 1 13/16   | 11/16         | 2                        | 1 13/16   | 1 7/64        |
| 1 1/4   | 2   | 25/32         | 2                        | 2   | 1 7/32        |
| 1 3/8   | 2 3/16  | 27/32         | 2 1/4                    | 2 3/16  | 1 11/32       |
| 1 1/2   | 2 3/8   | 15/16         | 2 1/4                    | 2 3/8   | 1 15/32       |



| TABLE 1072-4<br>HIGH STRENGTH BOLTS WASHER DIMENSIONS |                                   |                          |                   |                  |   |                |                             |
|---|-----------------------------------|--------------------------|-------------------|------------------|---|----------------|-----------------------------|
| Bolt Size D, inch                                     | Circular Washers Dimensions, inch |                          |                   |                  | Square or Rectangular Beveled Washers Dimensions for American Standard Beams and Channels, inch |                |                             |
|   | Nominal Outside Diameter          | Nominal Diameter of Hole | Thickness Min.    | Thickness Max.   | Minimum Side Dimension  | Mean Thickness | Slope of Taper in Thickness |
| 1/2   | 1 1/16                            | 17/32                    | .097              | .177             | 1 3/4   | 5/16           | 1:6                         |
| 5/8   | 1 5/16                            | 11/16                    | .122              | .177             | 1 3/4   | 5/16           | 1:6                         |
| 3/4   | 1 15/32                           | 13/16                    | .122              | .177             | 1 3/4   | 5/16           | 1:6                         |
| 7/8   | 1 3/4                             | 15/16                    | .136              | .177             | 1 3/4   | 5/16           | 1:6                         |
| 1   | 2                                 | 1 1/8                    | .136              | .177             | 1 3/4   | 5/16           | 1:6                         |
| 1 1/8   | 2 1/4                             | 1 1/4                    | .136              | .177             | 2 1/4   | 5/16           | 1:6                         |
| 1 1/4   | 2 1/2                             | 1 3/8                    | .136              | .177             | 2 1/4   | 5/16           | 1:6                         |
| 1 3/8   | 2 3/4                             | 1 1/2                    | .136              | .177             | 2 1/4   | 5/16           | 1:6                         |
| 1 1/2   | 3                                 | 1 5/8                    | .136              | .177             | 2 1/4   | 5/16           | 1:6                         |
| 1 3/4   | 3 3/8                             | 1 7/8                    | .178 <sup>A</sup> | .28 <sup>A</sup> | -   | -              | -                           |
| 2   | 3-3/4                             | 2-1/8                    | .178 <sup>A</sup> | .28 <sup>A</sup> | -   | -              | -                           |
| Over 2 to 4 Incl.                                     | 2D-1/2                            | D+1/8                    | .24 <sup>B</sup>  | .34 <sup>B</sup> | -   | -              | -                           |

1       A. 3/16" nominal

2       B. 1/4" nominal

### 3       (F) Galvanized High Strength Bolts, Nuts and Washers

4       Use galvanized high strength bolts, nuts and washers meeting all other requirements of  
5       this subarticle except as follows:

6       (1) Use Type 1 bolts.

7       (2) Quench and temper washers.

8       (3) Mechanically galvanize in accordance with ASTM B695, Class 55.

9       (4) Ship galvanized bolts and nuts in the same container.

10      (5) Use organic zinc repair paint for touch-up of galvanized surfaces meeting  
11      Article 1080-9.

12      (6) Include in manufacturer's test reports results of the zinc coating thickness  
13      measurements.

14      (7) Have each galvanized nut coated with a wax lubricant with a color contrast to that of  
15      the zinc coating.

### 16      1072-6 WELDED STUD SHEAR CONNECTORS

17      Use Type B shear studs in accordance with the Bridge Welding Code as defined in  
18      Article 1072-18.

19      Use and install welded stud shear connectors meeting Article 1072-18. Ensure that shear  
20      studs and the areas of beams, girders or other structural steel to which the studs are welded are  
21      free of rust, rust pits, oil, grease, moisture, paint, galvanizing, loose mill scale or other  
22      deleterious matter which adversely affects the welding operation. Apply shear studs on steel  
23      with tightly adhering mill scale as determined by the Engineer provided acceptable results are  
24      achieved and the installed studs meet the Bridge Welding Code.

## Section 1072

### 1 1072-7 INSPECTION

#### 2 (A) General

3 Give the Materials and Tests Unit 72 hours notice for in-state producers and 192 hours  
4 notice for producers out-of-state before beginning work in the shop. Do not manufacture  
5 or fabricate any material, other than stock items, before the Materials and Tests Unit is  
6 notified and the final shop drawings are reviewed, accepted and returned to the fabricator.

7 The contractor/fabricator shall be responsible for and shall be required to perform all  
8 quality control procedures and nondestructive testing in accordance with the Bridge  
9 Welding Code as defined in Article 1072-18 and as required by the contract. Perform all  
10 quality control procedures and nondestructive testing in the presence of the Department's  
11 inspector unless otherwise approved by the Department's inspector. Obtain approval for  
12 all quality control inspectors from the Department's inspector and ensure their  
13 qualification in accordance with the Bridge Welding Code. Maintain all QC reports as  
14 required by the Bridge Welding Code, including, but not limited to, visual and  
15 nondestructive testing reports and all phases of coating application inspection. Provide  
16 copies of all QC reports, including all radiographic films, to the Department inspector  
17 upon request. These copies become the property of the Department. No separate  
18 payment is made for this inspection and testing. The entire cost of this work is included  
19 in the unit contract price for the structural steel items involved.

20 Furnish facilities for the inspection of material and work in the mill and shop, and allow  
21 the inspectors free access to the necessary parts of the mill or shop. Do not ship any  
22 member or component of the structural steel from the shop to the job site before approval  
23 by the Department's inspector. Such approval is stamped on the member or appropriate  
24 container by the Department's inspector.

25 Furnish the Engineer with as many copies of mill orders and shipping statements as  
26 directed. The acceptance of any material or finished member by the Department's  
27 inspector is not a bar to their subsequent rejection, if found defective. Replace rejected  
28 material and correct rejected work promptly and satisfactorily.

#### 29 (B) Shop and Mill Inspection

30 Shop inspection is performed on all structural steel used on any project. Mill inspection  
31 of structural steel is performed when so noted in the plans or in the Specifications.  
32 Furnish complete certified mill test reports for all structural steel used except  
33 a Type 6 material certification in accordance with Article 106-3 as to the grade of steel  
34 used is acceptable for small amounts of structural steel items which are furnished from  
35 the supplier's stock and which are difficult to identify on any mill test report.

36 Show in the supplier's certification the items fabricated from stock material and the  
37 pounds of steel required for each item. A supplier's certification represents only anchor  
38 bolts, pipe sleeves, masonry plates, sole plates, diaphragm tees, connector plates and web  
39 stiffener plates. Represent all other items required for a structure by certified mill test  
40 reports as specified above.

41 Indicate in the complete certified mill test reports the pounds of steel and the item or  
42 items they represent and show heat number of steel, mechanical tests, chemical analyses,  
43 Department's project number, station number, the ASTM or AASHTO specification to  
44 which the material conforms and a signed statement certifying where the steel was melted  
45 and manufactured.

46 Forward to the Materials and Tests Unit a letter which states by station the items and  
47 pounds of steel that are represented by a supplier's certification and those represented by  
48 the certified mill test reports identifying the beam and/or plate material for each main  
49 member.

1 The Department reserves the right to select any item for test. Bear any expense of  
2 obtaining the sample. The tests are performed at the Department's expense.

3 **(C) Sampling Structural Steel**

4 Furnish samples of structural steel at the beginning of fabrication when random sampling  
5 is required.

6 Furnish one 2 1/2" x 24" sample for each grade of steel used on a project per  
7 1,000,000 lb. No more than 2 are required per project.

8 Take all samples at the location and in the manner directed by an authorized  
9 representative of the Engineer. Furnish the necessary personnel and equipment for  
10 obtaining samples and be responsible for providing a smooth finish to the areas from  
11 which the samples are taken.

12 **(D) Charpy V-Notch Tests**

13 Furnish all structural steel for girders, beams and diaphragm components connecting  
14 horizontally curved members meeting the longitudinal Charpy V-Notch Tests specified in  
15 the supplementary requirements in AASHTO M 270 for Zone 1. Unless otherwise noted  
16 in the plans, mark and test the materials as non-fracture critical. Sample and test in  
17 accordance with AASHTO T 243 and use the (H) frequency of heat testing. Use the  
18 grade or grades of structural steel required in the plans. Obtain and submit certified mill  
19 test reports to the Materials and Tests Unit to show the results of each test required by the  
20 *Standard Specifications*.

21 **1072-8 WORKING DRAWINGS**

22 Submit prints of checked structural steel shop drawings and changes thereto, including  
23 shipping diagrams for review, comments, acceptance and distribution as follows:

24 **(A)** Submit 2 sets for review, comments and acceptance on all steel structures. After review,  
25 comments and acceptance, submit 7 sets for distribution.

26 **(B)** Submit 5 sets for review, comments and acceptance for all bridges carrying railroad  
27 traffic, and after acceptance, submit 9 sets for distribution.

28 **(C)** Furnish any additional sets requested by the Engineer or for his use, review, comments,  
29 acceptance and/or distribution.

30 Shop drawings are not checked by the Engineer except to ascertain general compliance with  
31 the design and the *Standard Specifications*. Thoroughly check all shop drawings in all  
32 respects. Review, comments and acceptance of shop drawings by the Engineer is not  
33 considered as relieving the Contractor of his responsibility for the accuracy of his drawings,  
34 or for the fit of all shop and field connections and anchors.

35 The maximum size of prints for shop drawings is 22" x 36", including borders which are at  
36 least 1" at the left edge of the sheet. Provide shop drawings on any medium provided they are  
37 legible and are reproducible. Upon completion of the project, furnish to the Engineer one  
38 complete set of reproducible shop drawings that represent the as-built condition of the  
39 structural steel including all approved changes if any. Supply drawings that are 22" x 36".  
40 These drawings will become the property of the Department.

41 Changes on shop drawings after acceptance or distribution are subject to the approval of the  
42 Engineer. Furnish a record of such changes.

43 Make substitution of sections different from those on the structure plans only when approved  
44 in writing.

## Section 1072

### 1 1072-9 HANDLING AND STORING MATERIALS

- 2 Load, transport, unload and store structural material so the metal is kept clean and free from  
3 damage. Repair any coating damage. Do not use chains, cables or hooks that damage or scar  
4 the material. Repair all materials which are scarred or damaged and inspect at the fabricators  
5 expense as deemed necessary by the Engineer.
- 6 Use lifting equipment and rigging equipment with adequate capacity to handle the material at  
7 all times. Do not bend, twist, damage or excessively stress any materials. Do not perform  
8 hammering which injures or distorts the members. Operate and maintain all lifting equipment  
9 in a safe manner and in accordance with the manufacturer's directions.
- 10 When lifting main structural steel members, use spreader bars. Do not use one point pick-ups  
11 on members over 50 ft in length. Use 2 point pick-ups so the amount of overhang and the  
12 distance between hooks does not exceed the distances as noted in Table 1072-5.

| Property                       | Beam Size   |        |        |               |
|--------------------------------|-------------|--------|--------|---------------|
|                                | 30" or Less | 33" WF | 36" WF | Plate Girders |
| Maximum Distance Between Hooks | 74 lf       | 80 lf  | 85 lf  | 100 lf        |
| Maximum Overhang               | 25 lf       | 28 lf  | 30 lf  | 35 lf         |

- 13 Store structural material, either plain or fabricated, above the ground upon platforms, skids or  
14 other supports. Keep free from dirt, grease, vegetation and other foreign matter, and protect  
15 as far as practicable from corrosion.
- 16 Keep material clean and properly drained. Transport and store girders and beams with the  
17 web in the vertical plane and the top flange up. Request permission in writing and await  
18 approval to invert haunched girders and beams for transport for safety reasons. Use extreme  
19 care in turn-over operations to prevent excessive bending stresses in the edge of flanges.  
20 Support long members on blocking placed near enough together to prevent damage from  
21 deflection.
- 22 Do not use any beam, girder, diaphragm, cross frame or other material, in any stage of  
23 fabrication that will be permanently incorporated into the finished structure as a workbench,  
24 lifting device, dunnage or for any purpose for which it was not specifically intended.

### 25 1072-10 STRAIGHTNESS, CAMBER AND DIMENSIONAL TOLERANCES

#### 26 (A) General

- 27 Ensure that rolled material, before being laid out or fabricated, is straight.  
28 If straightening is necessary, use methods that do not damage the metal. Kinks or sharp  
29 bends are cause for rejection of the material.
- 30 Ensure that heat straightened or heat cambered parts are substantially free from external  
31 forces, except those resulting from mechanical means used in conjunction with the  
32 application of heat.
- 33 After heating, allow the metal to cool, without artificial cooling, down to 600°F. Below  
34 600°F, only dry compressed air is permitted to artificially cool steels having minimum  
35 yield strength greater than 36,000 psi as indicated by a Type 1 material certification in  
36 accordance with Article 106-3.

#### 37 (B) Straightening

- 38 Straighten distorted members and bent material by mechanical means or, if approved, by  
39 the carefully planned and supervised application of a limited amount of localized heat.  
40 Do not allow the temperature of the heated area to exceed 1,200°F as controlled by  
41 temperature indicating crayons or other approved methods.

1 Following the straightening of a bend or buckle, free the surface of the metal from  
 2 evidence of fracture as indicated by visual inspection or, if directed, by appropriate  
 3 nondestructive testing.

4 Shop straighten the bottom flanges of steel beams or girders at bearings as necessary to  
 5 provide uniform contact between the flanges and the bearings.

6 **(C) Camber**

7 Show the required camber on the drawings.

8 Make adequate provision in the fabrication of structural members to compensate for  
 9 change of camber due to welding of the shear connectors and other fabrication work.

10 Fabricate camber into the members on built-up plate girders and trusses. Where camber  
 11 is required on rolled sections, induce it by heat cambering, except that for rolled sections  
 12 within the depth, length and camber ordinate range shown in Table 1072-6, induce  
 13 camber by cold cambering or "gagging" at the mill or in the shop provided approval  
 14 procedures for cold cambering are employed.

15 Attach cover plates on rolled sections after cambering.

16 Where reverse curvature is required in a single rolled shape, induce it by heat cambering.

17 Show camber diagrams showing the required offset at each tenth point of the span and at  
 18 any web splice or field splice location and blocking diagrams on the shop drawings.  
 19 Show additional points if desired by the fabricator. Ensure that the beams, girders or  
 20 other members with field splices meet all of the blocking ordinates without inducing  
 21 stress into the members.

22 Following cambering or camber correction, correct evidence of fracture indicated by  
 23 visual inspection or, if directed, by appropriate nondestructive testing.

24 Show camber and blocking diagrams on the shop drawings. Shop assemble continuous  
 25 beams meeting all the blocking ordinates without inducing stress into the members.

| <b>TABLE 1072-6</b>                               |  |                              |
|---|--|------------------------------|
| <b>ACCEPTABLE COLD CAMBER FOR ROLLED SECTIONS</b> |  |                              |
| <b>Beam Length, feet</b>                          | <b>Section Designation and Nominal Depth</b>                       |                              |
|   | <b>W-Shapes 14" to 21"<br/>Inclusive<br/>S-Shapes 12" and Over</b> | <b>W-Shapes 24" and Over</b> |
| Over 30 through 42                                | 3/4" to 2 1/2" inclusive   | 1" to 2" inclusive           |
| Over 42 through 52                                | 1" to 3" inclusive   | 1" to 3" inclusive           |
| Over 52 through 65                                | 2" to 4" inclusive   | 2" to 4" inclusive           |
| Over 65 through 85                                | 2 1/2" to 5" inclusive   | 3" to 5" inclusive           |
| Over 85 through 100                               | As directed by the Engineer  | 3" to 6" inclusive           |

26 **(D) Heat Cambering of Rolled Beams and Welded Plate Girders**

27 (1) General

28 Where heat cambering is used, only V-type heating is permitted. Perform V-type  
 29 heating by the carefully planned and supervised application of a limited amount of  
 30 localized heat.

31 When minor corrections in camber are required, use small localized heats limited to  
 32 the flange material. Perform major corrections in camber by V-type heating to  
 33 prevent web distortion.

## Section 1072

1           Begin heating at the apex of the heating pattern and progress slowly towards the base  
2           of the pattern as each area is brought up to temperature as stated in  
3           Subarticle 1072-10(D)(5). Do not progress the heating torches toward the base of  
4           the heating pattern until the apex of the pattern is brought up to the specified  
5           temperature. Do not return the heating torch toward the apex of the heating triangle  
6           after heating has progressed towards the base. Continue heating to successive areas  
7           until the base of the triangular heating pattern is brought up to the required  
8           temperature across the full width of the flange.

### 9           (2) Heat Cambering of Rolled Beams

10           Heat cambering of rolled beams is allowed to provide the required vertical curvature.  
11           Space triangular heating patterns throughout the length of the member to provide the  
12           required curvature. Locate the apex of the heating triangle at a point not less  
13           than 75% of the depth of the member measured from the flange that is concave after  
14           cambering. Limit the total included angle of the heating pattern to 20°.

15           Weld all detail material such as connection plates, bearing stiffeners and gusset  
16           plates attached to the member to the rolled beam after the beam is cambered as  
17           required.

### 18           (3) Heat Cambering of Welded Plate Girders

19           Heat cambering of welded plate girders is only permitted when approved in writing  
20           as a necessary repair procedure for plate girders rejected for camber deviation.

21           When it is necessary to correct camber deviation in welded plate girders, heating is  
22           permitted in V-type heating patterns centered on intermediate stiffeners and  
23           connection plates. Where necessary, add stiffeners for this purpose if approved.  
24           Locate the apex of the heating pattern not less than 3/4 of the depth of the member  
25           from the flange that is shortened after cooling. The maximum included angle of the  
26           heating pattern is 10°. The maximum width of the base of the heating pattern is 10".  
27           Where shallow members or thin webs prescribe heating patterns with a width  
28           substantially less than 10" at the junction of the web to flange, extend the heating  
29           pattern in the flange at that location beyond the limits of the heating pattern in the  
30           web by no more than 1" provided the total width of pattern in the flange does not  
31           exceed the 10" limit stated above.

### 32           (4) Support of Members for Heat Cambering

33           Heat camber members with the web vertical and supports spaced to take the  
34           maximum advantage of dead load in the member before applying heat. Ensure all  
35           supports are approved by the Department's inspector before beginning work.

36           Do not place any combination of support system or external load on the member that  
37           causes a compressive stress in the flange to exceed 20,000 psi before heating for  
38           AASHTO M 270 Grades 36, 50 and 50W steels.

### 39           (5) Heating Process and Equipment

40           Heat using large, approximately 1" diameter, multi-orifice (rosebud) heating torches  
41           operating on approximately 25 psi thermal gas and 125 psi oxygen.

42           The torches and tips used are subject to approval. Choose torches and tips that  
43           promote heating efficiency and prevent unnecessary distortion.

44           Confine heating to the patterns described herein and conduct to bring the steel within  
45           the planned pattern to a temperature between 1,100°F and 1,200°F as rapidly as  
46           possible without overheating the steel.

1 Any heating procedure which causes a portion of the steel to exceed a temperature  
2 greater than 1,200°F is destructive heating and is automatically cause for rejection of  
3 the steel. Steel rejected for destructive heating is investigated for re-acceptance,  
4 repair or replacement if allowed by the Engineer. Bear the cost of such tests and any  
5 necessary repair or replacement.

6 (6) Heat Measurement

7 Specified temperatures are checked using portable digital pyrometers.

8 **(E) Heat Curving Girders**

9 (1) Type of Heating

10 With approval, use continuous or V-type heating methods to curve girders. For the  
11 continuous method, simultaneously heat a strip along the edge of the top and bottom  
12 flanges that is of sufficient width and temperature to obtain the required curvature.  
13 For V-type heating, heat the top and bottom flanges simultaneously in truncated  
14 triangular or wedge-shaped areas. Position the areas with their base along the flange  
15 edge and spaced at regular intervals along each flange. Set the spacing and  
16 temperatures to approximate the required curvature by a series of short chords. Heat  
17 along the top and bottom flanges at approximately the same rate.

18 For V-type heating, terminate the apex of the truncated triangular area applied to the  
19 inside flange surface just before the juncture of the web and flange. To avoid web  
20 distortion, make certain that heat is not applied directly to the web when heating the  
21 inside flange surfaces (the surfaces that intersect the web). Extend the apex of the  
22 truncated triangular heating pattern applied to the outside flange surface to the  
23 juncture of the flange and web. Use an included angle of approximately 15° to 30°  
24 in the truncated triangular pattern, but do not allow the base of the triangle to  
25 exceed 10". Vary the patterns prescribed above only with the Engineer's approval.

26 For both types of heating, heat the flange edges that will be on the inside of the  
27 horizontal curve after cooling. Concurrently heat both inside and outside flange  
28 surfaces for flange thicknesses of 1.25" and greater. Adhere to the temperature  
29 requirements presented below.

30 (2) Temperature

31 Conduct the heat curving operation so the temperature of the steel never exceeds  
32 1,150°F as measured by temperature indicating crayons or other suitable means. Do  
33 not artificially cool the girder until it naturally cools to 600°F. Below 600°F, use dry  
34 compressed air to artificially cool the girder.

35 (3) Position for Heating

36 Heat-curving the girder with the web in either a vertical or horizontal position is  
37 permitted. When curved in the vertical position, brace or support the girder so the  
38 tendency of the girder to deflect laterally during the heat-curving process does not  
39 cause the girder to overturn.

40 When curved in the horizontal position, support the girder near its ends and at  
41 intermediate points, if required, to obtain a uniform curvature. Do not allow the  
42 bending stress in the flanges to exceed 27,000 psi. To prevent a sudden sag due to  
43 plastic flange buckling when the girder is positioned horizontally for heating, place  
44 intermediate safety catch blocks at the midlength of the girder within 2" of the  
45 flanges at all times during the heating process.

## Section 1072

### (4) Sequence of Operations

Conduct the heat-curving operation either before or after completing all the required welding of transverse intermediate stiffeners to the web. However, unless provisions are made for shrinkage, position and attach connection plates and bearing stiffeners after heat-curving. In any event, weld the stiffeners, connection plates, and bearing stiffeners to the girder flanges after the member is curved. If longitudinal stiffeners are required, heat-curve or oxygen-cut these stiffeners separately before welding to the curved girder.

### (5) Camber and Curvature

Camber the girders before heat-curving. Cut the web to the prescribed camber allowing for shrinkage due to cutting welding and heat-curving. If approved, a carefully supervised application of heat is permitted to correct moderate deviations from the specified camber.

Horizontal curvature and vertical camber is measured for final acceptance after all welding and heating operations are complete and the flanges have cooled to a uniform temperature. Horizontal curvature is checked with the web in the vertical position by measuring offsets from a string line or wire attached to both flanges or by using other suitable means. Camber is checked with the web in the horizontal position. Camber the girder so it meets the horizontal and vertical curvature ordinates without inducing stress into the girders by mechanical force.

Compensate for loss of camber in the heat-curved girders as residual stresses dissipate during service life of the structure. Compute this anticipated loss of camber in accordance with the *AASHTO LRFD Bridge Design Specifications*.

### (6) Procedure Specification and Shop Drawings

Submit structural steel shop drawings, including a detailed written procedure specification for heat curving the girders, supplemented by calculations and sketches, for review, comments and acceptance. On the shop drawings, indicate the type, location and spacing of heat sectors, if used, supports and catch blocking for each field section of girders. Include suitable blocking diagrams for measuring horizontal curvature similar to those usually prepared for camber and vertical curvature.

## (F) Camber Measurement

At the time of acceptance at the shop and after erection, ensure that all stringers and girders for bridges meet the required camber values within the tolerances specified in Subarticle 1072-10(G). Follow the procedure for measuring camber as outlined below:

(1) Assemble the member at the shop as specified in Article 1072-19 and measure with the member lying on its side.

(2) Camber repairs are only allowed when approved by the Engineer. Camber deviation is judged irreparable if corrective measures in the shop produce web buckling in excess of the specified tolerance, in which case the member is rejected.

(3) The final camber measurement is made by the Engineer in the field after erection. At the time of this measurement, ensure that the members have all of the specified camber less the dead load deflection of the steel as specified in Subarticle 1072-10(G).

## (G) Dimensional Tolerances

Ensure that dimensions of all material covered by Section 1072 conform to ASTM A6 when received at the fabrication shop. Fabricate member dimensions conforming to this subarticle whether designated to be straight, cambered or curved and regardless of whether curvature is heat-induced (when so permitted). Dimensional tolerances not listed



1 in this subarticle shall be as specified by the Bridge Welding Code as defined in  
 2 Article 1072-18 and applied to rolled shapes where applicable as well as to welded  
 3 members.

4 Place welded butt joints no further than 1/2" from the point detailed. Intermediate  
 5 stiffeners varying  $\pm 1/2"$  from the point detailed are allowed. Connector plates for field  
 6 connections varying  $\pm 1/8"$  from the point detailed are allowed. Ensure that the actual  
 7 centerline of bearing lies within the thickness of the bearing stiffener.

8 Members with end milled for bearing and members with faced end connection angles  
 9 deviating from the detailed length by  $-0, +1/32"$  are acceptable. All other members  
 10 varying from detailed length by  $\pm 1/8"$  are acceptable.

11 Align to within  $\pm 1/8"$  from the location shown on the approved shop drawings all steel  
 12 requiring shop assembly for reaming, drilling from the solid or weld joint preparation.

13 Deviation from specified camber of fabricated members before shipment from the  
 14 fabrication shop is limited to:

15 -0;

16  $\frac{+3/32" \times \text{No. of ft from nearest bearing}}{10}$ , up to 3/4" maximum.  
 17

18 Deviation from specified camber of erected steel bridge superstructures measured when  
 19 the steel work is complete and the superstructure is subject to steel dead load stresses only  
 20 is limited to:

21 -0;

22  $\frac{+1/8" \times \text{No. of ft from nearest bearing}}{10}$ , up to 1" maximum.  
 23

24 If the plans do not require shop induced camber, provide an actual member that is straight  
 25 or one of the following:

26 (1) If natural camber "turned up" is required, the maximum plus camber is the algebraic  
 27 sum of the allowable deviation, dead load deflection, vertical curve ordinate and  
 28 superelevation ordinate;

29 (2) If natural camber "turned down" is required, the maximum negative camber is equal  
 30 to the algebraic sum of the dead load deflection, vertical curve ordinate and  
 31 superelevation ordinate.

32 Do not exceed 1/8" per 10 ft length for the actual deviation from curvature shown in the  
 33 plans.

#### 34 **1072-11 OXYGEN CUTTING**

35 Oxygen cutting of structural steel is allowed, provided a smooth surface free from cracks and  
 36 notches is secured and an accurate profile is secured by the use of a mechanical guide. Hand  
 37 cut only where approved and grind smooth leaving no burnt edges.

38 In all oxygen cutting, adjust and manipulate the cutting agent to avoid cutting beyond (inside)  
 39 the prescribed lines. Provide oxygen cut surfaces meeting the ANSI surface roughness rating  
 40 value of 1,000 except ensure that oxygen cut surfaces of members not subject to calculated  
 41 stress meet the surface roughness value of 2,000. Round corners of oxygen cut surfaces of  
 42 members carrying calculated stress to a 1/16" radius, or an equivalent flat surface at a suitable  
 43 angle, by grinding after oxygen cutting.

44 Fillet re-entrant cuts to a radius of not less than 1".

## Section 1072

1 Remove surface roughness exceeding the above values and occasional notches, gouges and  
2 cracks not more than 1/16" deep on otherwise satisfactory oxygen cut surfaces by chipping or  
3 grinding. Flair corrections of the defects with the surface of the cut on a bevel of one to 6 or  
4 flatter.

5 Repair occasional gouges of oxygen cut edges more than 3/16" deep, but not more than  
6 7/16" deep, by welding with low hydrogen electrodes not exceeding 5/32" in diameter and  
7 with a minimum preheat of 250°F. Grind the completed weld smooth and flush with the  
8 adjacent surface. Radiographically test any gouge over 1/8" deep after the repair.

### 9 **1072-12 EDGE PLANING**

10 Plane sheared edges of plates more than 5/8" in thickness that carry calculated stress to  
11 a depth of 1/4". Fillet re-entrant cuts before cutting. Round all edges of plates and shapes  
12 parallel to calculated stress and all free edges of plates and shapes intended for coating or  
13 galvanizing to 1/16" radius or provide an equivalent flat surface at a suitable angle. Grind  
14 edges of all other plates and shapes to remove burrs, slag or shear lip. The ends of all steel  
15 piles, intended for coating or galvanizing, are not required to be radiused, but remove all  
16 burrs, slag and shear lip.

### 17 **1072-13 FACING OR BEARING SURFACES**

18 Provide a surface finish of bearing and base plates and other bearing surfaces that come in  
19 contact with each other or with concrete that meet Table 1072-7 following ANSI surface  
20 roughness requirements as defined in ANSI B46.1.

| <b>Item</b>  | <b>ANSI Surface Roughness</b> |
|--|-------------------------------|
| Steel slabs  | ANSI 2,000                    |
| Heavy plates in contact in shoes to be welded  | ANSI 1,000                    |
| Milled ends of compression members, milled<br>or ground ends of stiffeners and fillers | ANSI 500                      |
| Bridge rollers and rockers   | ANSI 250                      |
| Pins and pin holes   | ANSI 125                      |
| Sliding bearings   | ANSI 125                      |

### 21 **1072-14 ABUTTING JOINTS**

22 Face and bring to an even bearing abutting joints in compression members, girder flanges and  
23 tension members where so indicated on the drawings. Where joints are not faced, do not  
24 exceed an opening of 1/4".

### 25 **1072-15 BENT PLATES**

26 Provide cold-bent, load carrying rolled-steel plates conforming to the following:

27 **(A)** Take from the stock plates so the bendline is at right angles to the direction of rolling.

28 **(B)** Use a radius of bends such that no cracking of the plate occurs. Use minimum bend radii,  
29 measured to the concave face of the metal, as shown in Table 1072-8.

30 If a shorter radius is essential, bend the plates hot at a temperature not greater than  
31 1,200°F and air cool slowly down to a temperature of 600°F. Below 600°F, use only dry  
32 compressed air to artificially cool steels having a minimum yield strength greater than  
33 36,000 psi. Use hot bent plates conforming to Subarticle 1072-15(A) above.

34 **(C)** Before bending, round the corners of the plates to a radius of 1/16" throughout the  
35 portion of the plate at which bending occurs.

**TABLE 1072-8  
MINIMUM BEND RADII**

| Plate Thickness (t)   | Minimum Bend Radii,<br>Ratio of Thickness |
|-----------------------|---|
| Up to 1/2"            | 2t  |
| Over 1/2" to 1"       | 2 1/2t                                    |
| Over 1" to 1 1/2"     | 3t  |
| Over 1 1/2" to 2 1/2" | 3 1/2t                                    |
| Over 2 1/2" to 4"     | 4t  |

1 Hot bend low alloy steel in thicknesses over 1/2" for small radii, if required.

2 **1072-16 HOLES FOR BOLTS AND OTHER FASTENERS**

3 **(A) General**

4 Punch or drill all holes and remove any burrs. Punching material forming parts of  
5 a member composed of not more than 5 thickness of metal 1/16" larger than the nominal  
6 diameter of the fastener is allowed whenever the thickness of the material is not greater  
7 than 3/4" for structural steel, 5/8" for high-strength steel or 1/2" for quenched and  
8 tempered alloy steel, unless subpunching and reaming is required by  
9 Subarticle 1072-16(D).

10 When there are more than 5 thicknesses or when any of the main material is thicker than  
11 3/4" for structural steel, 5/8" for high-strength steel or 1/2" for quenched and tempered  
12 alloy steel, either subdrill and ream or drill all holes full size.

13 When required by Subarticle 1072-16(D), subpunch or subdrill all holes (subdrill if  
14 thickness limitation governs) 1/4" smaller and, after assembling, ream 1/16" larger or  
15 drill full size to 1/16" larger than the nominal diameter of the fastener.

16 **(B) Punched Holes**

17 Do not use a diameter of the die exceeding the diameter of the punch by more than 1/16".  
18 If any holes require enlargement to admit the fasteners, ream such holes. Clean cut holes  
19 without torn or ragged edges. Poor matching of holes is cause for rejection. Grind all  
20 burrs smooth.

21 **(C) Reamed or Drilled Holes**

22 Make reamed or drilled holes cylindrical and perpendicular to the member complying  
23 with the size requirements of Subarticle 1072-16(A). Where practicable, direct reamers  
24 by mechanical means. Grind all burrs smooth. Poor matching of holes is cause for  
25 rejection. Ream and drill with twist drills. If required, take assembled parts apart for  
26 removal of burrs caused by drilling. Assemble connecting parts requiring reamed or  
27 drilled holes, securely hold while reaming or drilling and match mark before  
28 disassembling.

29 **(D) Subpunching and Reaming of Field Connections**

30 Subpunch or subdrill, if required according to Subarticle 1072-16(A), holes in all field  
31 connections and field splices of main members of trusses, arches, continuous beam spans,  
32 bents, towers (each face), plate girders, and rigid frames. Subsequently ream while  
33 assembled as required by Article 1072-19. Subpunch and ream to a steel template or  
34 ream while assembled all holes for floor beam and stringer field end connections. Ream  
35 or drill full size field connection holes through a steel template after the template is  
36 located with utmost care as to position and angle and firmly bolted in place. Use  
37 templates for reaming matching members, or the opposite faces of a single member that  
38 are exact duplicates. Accurately locate templates used for connections on like parts of  
39 members such that the parts or members are duplicates and require no match-marking.

## Section 1072

### 1 (E) Accuracy of Punched and Subdrilled Holes

2 Accurately punch or subdrill all holes punched full size, subpunched or subdrilled such  
3 that after assembling, and before any reaming is done, a cylindrical pin 1/8" smaller in  
4 diameter than the nominal size of the hole enters perpendicular to the face of the member,  
5 without drifting, in at least 75% of the contiguous holes in the same plane. If the  
6 requirement is not fulfilled, the badly punched pieces are rejected. If any hole does not  
7 pass a pin 3/16" smaller in diameter than the nominal size of the hole, this is cause for  
8 rejection.

### 9 (F) Accuracy of Reamed and Drilled Holes

10 When holes are reamed or drilled, ensure that 85% of the holes in any contiguous group,  
11 after reaming or drilling, show no offset greater than 1/32" between adjacent thicknesses  
12 of metal.

13 Use all steel templates with hardened steel bushings in holes accurately dimensioned  
14 from the centerlines of the connection as inscribed on the template. Use the centerlines in  
15 locating accurately by the template from the milled or scribed ends of the members.

### 16 (G) Alternate Methods

17 As an option, make the fastener holes by procedures other than those described in  
18 Subarticles 1072-16(A) through 1072-16(F) provided that the requirements for quality  
19 and for dimensional accuracy are met. Wherever an alternate method is employed,  
20 demonstrate the ability of each alternate method to produce holes and connections  
21 consistently meeting all requirements for quality and dimensional accuracy for the type of  
22 joint fabricated. When such ability of an alternate method is previously demonstrated on  
23 similar work for the Department, continue its use by certifying, on each subsequent  
24 project, that the procedure and equipment are the same as the method previously  
25 qualified, and that the equipment involved is in good repair and adjustment. Failure of  
26 joints to meet the quality and accuracy requirements is cause for rejection. In the case of  
27 repeated failures revise and/or requalify the method or discontinue its use.

28 At the time of qualification of an alternate method, submit for approval a written  
29 procedure specification describing the procedures and equipment and giving upper and  
30 lower value limits and tolerances for all pertinent variables. Accurately reflect the actual  
31 procedures, equipment and values used in the qualification tests. In addition to the  
32 certification on each subsequent project, the Engineer may request copies of the approved  
33 procedure specification.

### 34 (H) Oversize, Short-Slotted, and Long-Slotted Holes

35 Where shown in the plans or permitted in writing, use oversize, short-slotted and long-  
36 slotted holes with high strength bolts 5/8" and larger in diameter. Do not allow the  
37 distance between edges of adjacent holes or edges of holes and edges of members to be  
38 less than permitted under the AASHTO specification. Oversize, short-slotted and long-  
39 slotted holes are defined as follows:

40 (1) Oversize holes are 3/16" larger than bolts 7/8" and less in diameter, 1/4" larger than  
41 bolts 1" in diameter, and 5/16" larger than bolts 1 1/8" and greater in diameter.  
42 When oversized holes are permitted, they are allowed in any or all plies of friction  
43 type connections. Install hardened washers over exposed oversize holes.

44 (2) Short-slotted holes are 1/16" wider than the bolt diameter and have a length that does  
45 not exceed the oversize diameter requirements of Subarticle 1072-16(H)(1) by more  
46 than 1/16". When short-slotted holes are permitted, they are allowed in any or all  
47 plies of friction-type or bearing-type connection. Locate holes without regard to  
48 direction of loading in friction-type connections, but orient normal to the direction of  
49 the load in bearing-type connections. Install hardened washers over exposed short-  
50 slotted holes.

1 (3) Long-slotted holes are 1/16" wider than the bolt diameter and have a length more  
 2 than allowed in Sub-paragraph 2 but not more than 2 1/2 times the bolt diameter.  
 3 Structural plate washers or a continuous bar not less than 5/16" in thickness are  
 4 required to cover long slots that are the outer plies of joints. Ensure that these  
 5 washers have a size sufficient to completely cover the slot after installation. When  
 6 long-slotted holes are permitted, they are allowed in only one of the connected parts  
 7 of either a friction-type or bearing-type connection at an individual faying surface.

8 When used in friction-type connections, locate holes without regard to direction of  
 9 loading if one-third more bolts are provided than needed to satisfy the allowable unit  
 10 stresses except as herein restricted.

11 When used in bearing-type connections, orient the long diameter of the slot normal to the  
 12 direction of loading. No increase in the number of bolts over those necessary for the  
 13 allowable unit stress is required.

#### 14 (I) Misfits

15 When misfits occur for any reason, enlargement of the holes by reaming is limited to  
 16 1/16" over the nominal size hole called for unless otherwise permitted in writing.

#### 17 (J) Erection Bolt Holes

18 At field welded connections where erection bolts are used, provide holes 3/16" larger  
 19 than the nominal erection bolt diameter.

### 20 1072-17 INSTALLING BOLTS

21 Install high strength bolts in accordance with Article 440-8.

### 22 1072-18 WELDING

#### 23 (A) Definition

24 The Bridge Welding Code referred to herein is the edition of the  
 25 ANSI/AWS/AASHTO Bridge Welding Code D 1.5 and any applicable interim that is  
 26 current on the date of advertisement for the project, and as modified by the *Standard*  
 27 *Specifications*.

#### 28 (B) General

29 Commercially blast clean all steel used in girders, beams and connecting members to  
 30 SSPC-SP 6 before welding.

31 Weld all steel in the shop or in the field for bridges, whether permanent or temporary, and  
 32 perform all other work related to welding including, but not limited to, testing and  
 33 inspection of welds, preparation of material, oxygen cutting, electrodes, shielding and  
 34 shear studs, meeting the Bridge Welding Code. Weld other steel items in accordance  
 35 with AWS Welding Code.

36 Weld only where shown in the plans or where called for in the *Standard Specifications*  
 37 unless requesting and receiving written approval for additional welding.

38 Show all permanent and all temporary welds on the shop drawings. For groove welds,  
 39 indicate on the shop drawings the particular detail and process to be employed in  
 40 production of the work. For prequalified joints, use of the Bridge Welding Code letter  
 41 classification designation of the joint (B-L2b-S etc.) along with the appropriate symbol  
 42 satisfies this requirement. Tack welds that become part of a permanent weld are not  
 43 required on the shop drawings.

## Section 1072

1 Provide fillet welds, including seal welds, at least the minimum size allowed by the  
2 Bridge Welding Code for the thickness of material welded or the size called for in the  
3 plans, whichever is larger. For exposed, bare, unpainted applications of steel, the basic  
4 requirements for weld filler metal with atmospheric corrosion resistance and coloring  
5 characteristics similar to that of the base metal are mandatory. The variations from these  
6 basic requirements listed in the Bridge Welding Code for single pass welds are not  
7 permitted.

8 Use only Department approved electrodes for welding. The Department maintains a list  
9 of approved brands of electrodes for which satisfactory reports of tests made within one  
10 year are previously submitted. This list is available from the State Materials Engineer.  
11 Designate an appropriate storage area for all welding consumables in accordance with the  
12 Bridge Welding Code.

### 13 (C) Qualification of Personnel

14 Ensure that each welder, welding operator and tacker is qualified in accordance with the  
15 Bridge Welding Code or other applicable AWS Welding Code as determined by the  
16 Engineer. Employ welders that are qualified by the Department. Welders shall be  
17 requalified by the Department every 5 years. Contact the Materials and Tests Unit to  
18 schedule qualification tests. Permanent in-shop welders employed by a fabricator who  
19 passed the appropriate welding tests and whose weldments are radiographically tested  
20 with regularly acceptable results are exempt from additional testing when approved by  
21 the Engineer. Ensure a representative of the testing agency witness all phases of the  
22 qualification tests including preparation of the test plates and placing of welds. As  
23 evidence of such qualification, furnish a satisfactory certificate, or a copy thereof, issued  
24 by a testing agency which is approved by the Engineer, for each welder, welder operator  
25 and tacker employed on the work. Submit certification for each welder, welding operator  
26 or tacker, and for each project, stating the name and Social Security number of the  
27 welder, welding operator or tacker; the name and title of the person who conducted the  
28 examination; the kind of specimens; the position of welds; the AWS electrode  
29 classification used; the results of the tests; and the date of the examination. Such  
30 certifications are required for all persons performing shop or field welds of any kind on  
31 the work, whether permanent or temporary. Ensure each welder provides a picture ID  
32 upon request or other form of positive identification as required by the Engineer.

### 33 (D) Qualification of Welds and Procedures

34 Use welds, except as otherwise provided below, that are prequalified in accordance with  
35 the details, limitations and procedures prescribed by the Bridge Welding Code or other  
36 AWS Welding Code as determined by the Engineer. Substitute other such prequalified  
37 welds for those shown in the plans, subject to the approval of the Engineer.

38 For all prequalified field welds, submit Welding Procedure Specifications (WPS) for each  
39 joint configuration for approval at least 30 days before performing any welding. Instead  
40 of this, use the WPS provided and preapproved by the Department. These preapproved  
41 WPS are available from the Materials and Tests Unit. Use non-prequalified welds only if  
42 approved by the Engineer. Submit WPS for all non-prequalified welds to the Engineer  
43 for approval. At no cost to the Department, demonstrate their adequacy in accordance  
44 with the Bridge Welding Code.

45 Include in procedure specifications, upper and lower value limits of all variables listed for  
46 procedure qualification in the Bridge Welding Code for the process or processes used.  
47 Written welding procedure specifications are required for prequalified welds also.

48 On all welding, include in the welding procedure continuous visual inspection by  
49 welders, welding operator, tackers, welding supervisors and all personnel involved in  
50 preparation of the material for welding.

1 Approval by the Engineer of the procedure specifications does not relieve the Contractor  
2 of his responsibility to develop a welding procedure that produces weldments meeting the  
3 required quality and dimensions.

4 If non-prequalified joints procedures are previously found acceptable to the Engineer on  
5 another project, furnish the inspector with a copy of the joint details and procedure  
6 specification approved at the time of qualification. Such documentation is required from  
7 each fabricator employing a non-prequalified joint or procedure on the work. Failure to  
8 produce such documentation results in the fabricator being required to requalify the joint  
9 or procedure or to use prequalified joints, procedures, and procedure specifications.

10 On weldments where geometric shape prevents compliance with requirements to weld  
11 a particular position, alternate procedures are considered for approval. Previously  
12 qualified alternate procedures are considered for approval without further procedure  
13 qualification tests. No separate payment is made for developing, demonstrating and  
14 documenting for future use such alternate procedures, as such work is incidental to the  
15 work of welding.

#### 16 **(E) Requirements for Testing and Inspection**

17 Require the fabricator to make provisions for convenient access to the work for  
18 inspection and cooperate with the inspector during the required inspection and testing.

19 Inspect welds in the presence of the Department's inspector unless otherwise approved by  
20 the Department's inspector, using visual inspection and the nondestructive tests herein  
21 prescribed in addition to the test requirements of the Bridge Welding Code and the  
22 contract. Employ quality control inspectors and NDT technicians qualified in accordance  
23 with the Bridge Welding Code and preapproved by the Engineer before the start of any  
24 fabrication. Supply the appropriate certifications as required by the Bridge Welding  
25 Code to the Department's inspector for all inspectors. Individuals assigned to production  
26 welding activities or processes and their supervisors are not acceptable for performing  
27 quality control testing. Ensure a qualified welding inspector presents any time welding is  
28 in progress. No separate payment is made for inspection and testing. The entire cost of  
29 this work is included in the unit contract price for the structural steel items involved.

30 Retest welds requiring repairs or replacement in the presence of the Department's  
31 inspector after the repairs or replacements are made.

32 If the Engineer finds that acceptable repair to defective work is not feasible; the entire  
33 piece is rejected.

34 Payment at the contract prices for the various items in the contract which include the  
35 work of welding is full compensation for all costs resulting from the required  
36 nondestructive testing of welds and from the required inspection of welds.

#### 37 **(F) Nondestructive Test Required**

38 The extent of nondestructive testing required is as prescribed in the Bridge Welding Code  
39 and by the contract except radiograph all flange splices for their full length. The term  
40 "main members" in this regard means girders, beams, floor beams, stringers, truss  
41 members, high strength bolts, columns, bearing stiffeners, bearing shoes, high mount  
42 lighting standards and components of main member carrying stress, including the end  
43 connections for such members. Nondestructive testing of other complete welds or weld  
44 passes is required when so noted in the plans or deemed necessary by the Engineer. Tests  
45 other than those prescribed are also required when deemed necessary by the Engineer.  
46 Perform all radiographic testing in accordance with procedures established by the  
47 Engineer. Copies of these procedures are available from the State Materials Engineer.

48 Use edge blocks when radiographing butt welds greater than 1/2" in thickness. Use edge  
49 blocks with a length sufficient to extend beyond each side of the weld centerline for  
50 a minimum distance equal to the weld thickness, but not less than 2" and with a thickness

## Section 1072

1 equal to or greater than the thickness of the weld. Use edge blocks with a minimum  
2 width equal to half the weld thickness, but not less than 1". Center the edge blocks on the  
3 weld with a snug fit against the plate being radiographed allowing no more than  
4 1/16" gap. Produce edge blocks from radiographically clean steel and provide a surface  
5 finish of ANSI 125 or smoother.

6 High mount lighting standards longitudinal groove welds and fillet welds are  
7 radiographically tested as specified by the contract. Other nondestructive test methods  
8 are sometimes deemed necessary by the Engineer to determine the quality of the welds.  
9 No separate payment is made for inspection and testing. The entire cost of this work is  
10 included in the unit contract price involved.

### 11 (G) Welded Structural Shapes

12 Produce butt welds of flanges and webs, and fillet welds of web to flanges of plate  
13 girders and haunched beams using the submerged arc process. Produce other structural  
14 shapes built up from plates and bars using the submerged arc process unless another  
15 process is qualified for these joints in accordance with the Bridge Welding Code and is  
16 subject to the approval of the Engineer.

17 After all shop welded splices in the flanges and webs for the full length of the field  
18 section are made, tested and approved, fit the flange plates tight and square against the  
19 web to leave no gap and to not bow the web. Brace one side of each flange against the  
20 web with gussets or struts and tack weld securely to the web at the stiffener locations.  
21 Upon removal of the welds, grind any nicks or gouges, preheat, weld and test or  
22 incorporate into the stiffener fillet weld.

23 Connect the flanges to the web by starting the fillet weld at one end of the girder and  
24 proceeding to the other ends.

25 As an option, make adjacent welds simultaneously.

26 The sequence for making the flange to web fillet welds is subject only to the provisions  
27 for control of shrinkage and distortion and to the position requirements of the Bridge  
28 Welding Code.

29 After flange to web welds are complete, shift bracing gussets or struts if necessary, then  
30 remove all temporary gussets or struts. Remove tack welds by grinding flush with parent  
31 metal.

32 Straighten any transverse warpage of the flanges if necessary by heating along the  
33 centerline of the outside face.

34 Fit tight, square and tack weld stiffeners securely to the web. With the girder in the flat  
35 position (web horizontal), weld the stiffeners to the web. Do not weld or tack weld  
36 stiffeners to the flanges except where noted in the plans.

37 After all parts are welded into place, trim the girder to detail length with adjustments for  
38 slope and end rotation exceeding 1/4" net.

### 39 1072-19 SHOP ASSEMBLING

#### 40 (A) General

41 Assemble the field connections of main members of continuous beam spans, plate girders  
42 and rigid frames in the shop with milled ends of compressing members in full bearing,  
43 and then ream their sub-size holes to specified size while the connections are assembled.  
44 Assembly shall be either Full Girder Assembly or Progressive Girder Assembly unless  
45 Full Girder Assembly or Special Complete Structure Assembly is required by the  
46 contract.



1 Furnish a camber diagram to the Engineer showing the camber at each panel point of  
 2 each continuous beam line, plate girder or rigid frame. When the shop assembly is Full  
 3 Girder Assembly or Special Complete Structure Assembly, ensure the camber diagram  
 4 shows the camber measured in assembly. When any of the other methods of shop  
 5 assembly is used, show the calculated camber in the camber design.

6 Clean surfaces of metal in contact before assembling. Assemble the parts of a member,  
 7 pin well and firmly draw together with bolts before reaming. Take assembled pieces  
 8 apart, if necessary, for removal of burrs and shavings produced by the reaming operation.  
 9 Ensure that the member is free from twists, bends and other deformation.

10 Drift during assembling only to bring the parts into position, and not sufficient to enlarge  
 11 the holes or distort the metal. If any holes are enlarged to admit the fasteners, ream them.

12 Match-mark those connecting parts assembled in the shop for the purpose of reaming  
 13 holes in field connections and provide a diagram showing marks furnished by the  
 14 Engineer.

15 **(B) Full Girder Assembly**

16 Full Girder Assembly consists of assembling all members of each continuous beam line,  
 17 plate girder or rigid frame at one time.

18 **(C) Progressive Girder Assembly**

19 Progressive Girder Assembly consists of assembling initially for each continuous beam  
 20 line or plate girder at least 2 contiguous shop sections or all members in at least  
 21 2 contiguous shop panels but not less than the number of panels associated with  
 22 3 contiguous section lengths (i.e., length between field splices) and not less than 150 ft in  
 23 the case of structures longer than 150 ft. Add at least one shop section at the advancing  
 24 end of the assembly before removing any member from the rearward end, so the  
 25 assembled portion of the structure is never less than the specified above.

26 **(D) Special Complete Structure Assembly**

27 Special Complete Structure Assembly consists of assembling the entire structure,  
 28 including the floor system.

29 Ensure each assembly, including camber, alignment, accuracy of holes and fit of milled  
 30 joints, is approved by the Engineer before reaming.

31 **1072-20 PAINTING AND OTHER PROTECTIVE COATINGS**

32 Shop paint in accordance with Section 442.

33 Repair galvanized surfaces that are abraded or damaged in accordance with Article 1076-7.


34 **1072-21 MARKING AND SHIPPING**

35 Paint or mark each member with an erection mark for identification and furnish an erection  
 36 diagram with erection marks shown thereon.


37 Furnish to the Engineer as many copies of material orders, shipping statements and erection  
 38 diagrams as the Engineer directs. Show the weights of the individual members on the  
 39 statement. Mark the weights on members weighing more than 3 tons. Load structural  
 40 members on trucks or cars in such a manner that they are transported, unloaded and stored at  
 41 their destination without being excessively stressed, deformed or otherwise damaged.

42 Load and ship steel beams and girders in accordance with the Figures 1072-2 and 1072-3 and  
 43 Table 1072-9 for all types of transportation. When the contractor wishes to place members on  
 44 trucks not in accordance with these limits, to ship by rail, to attach shipping restraints to the  
 45 members, to ship horizontally curved steel members, or to invert members, he shall submit  
 46 a shipping plan before shipping. Refer to Article 1072-9.

Section 1072



**Figure 1072-2.** Truck loading diagram for when the length past the last support, *C*, is 15 ft or less.



1

2 **Figure 1072-3.** Truck loading diagram for when the length past the last support, *C*, is  
3 between 15 ft and 30 ft.

4 For truck loading with the length of the last support between 15 ft and 30 ft in Figure 1072-3,  
5 use the following formulas to calculate truck loading limits or use the values given in  
6 Table 1072-9:

7

$$B = 0.4C$$

8

$$C = 0.2L \text{ to } 0.3L, \text{ up to } 30 \text{ ft}$$

9 Where **B** is the length of the member past a required additional restraint, **C** is the length of the  
10 member extending past the last support and **L** is the length of the member.

| <b>TABLE 1072-9</b>                                    |  |  |  |
|--|--|--|--|
| <b>LIMITS FOR PLACEMENT OF STEEL BEAMS AND GIRDERS</b> |  |  |  |
| <b>DURING SHIPMENT</b>                                 |  |  |  |
| Length of Member,<br>feet                              | Minimum Length<br>Past Last Support,<br>feet | Maximum Length<br>Past Last Support,<br>feet | Maximum Length<br>Past Additional<br>Restraint, feet |
| <i>(L)</i>   | <i>(C)</i>                                   | <i>(C)</i>                                   | <i>(B)</i>   |
| 75   | 15   | 22.5   | 9  |
| 80   | 16   | 24   | 9.6  |
| 85   | 17   | 25.5   | 10.2   |
| 90   | 18   | 27   | 10.8   |
| 95   | 19   | 28.5   | 11.4   |
| 100  | 20   | 30   | 12   |
| 105  | 21   | 30   | 12   |
| 110  | 22   | 30   | 12   |
| 115  | 23   | 30   | 12   |
| 120  | 24   | 30   | 12   |
| 125  | 25   | 30   | 12   |
| 130  | 26   | 30   | 12   |
| 135  | 27   | 30   | 12   |

1 Restrain overhanging ends of beams or girders both vertically and horizontally to prevent  
 2 excess movement. Chains are permitted to secure beams and girders during shipping only  
 3 when adequate measures are taken to prevent damage to the material by the use of approved  
 4 protective material. If necessary, use adequate bracing to prevent bending of the top flange.

5 Pack bolts of one length and diameter and loose nuts or washers of each size separately. Ship  
 6 pins, small parts and packages of bolts, washers and nuts in boxes, crates, kegs or barrels, but  
 7 do not allow the gross weight of any package to exceed 300 lb. Plainly mark a list and  
 8 description of the contained material on the outside of each shipping container.

9 Steel die stamped fabricator's identity, station number, girder number and span number of  
 10 main members into an unpainted area (if available) near the end of the member. Die stamp  
 11 members with painted ends outside the painted area but as close to the end as possible.

12 Ship anchor bolts, washers and other anchorage or grillage materials, in time to be  
 13 incorporated into the masonry portion of the structure.

## 14 SECTION 1074

### 15 MISCELLANEOUS METALS AND HARDWARE

#### 16 1074-1 WELDING

17 Certify all welders performing any welding on any metals in accordance with the applicable  
 18 AWS welding code in the position and process required as approved by the Engineer.

#### 19 1074-2 EXPANSION ANCHORS

20 Unless otherwise shown in the plans, provide expansion anchors consisting of 2 or more units  
 21 with a minimum of 2 hard metal conical ring wedges and 2 expandable lead sleeves of  
 22 an equally effective design that is approved by the Engineer. Use anchors providing  
 23 a minimum safe holding power of 3,000 lb for 3/4" bolts and 2,000 lb for 5/8" bolts, based  
 24 upon 1/4 of the actual holding power of the anchor in 3,000 psi concrete. Furnish satisfactory  
 25 evidence, based upon actual tests performed by a commercial testing laboratory, which  
 26 indicate that the anchors develop the minimum required safe holding power.

27 When it is proposed to use anchors that are previously accepted as meeting the above  
 28 requirements, the anchors are accepted on the basis of a certified statement indicating the  
 29 prior acceptance of the furnished anchors.

#### 30 1074-3 PLAIN STEEL BARS WITH THREADED ENDS

31 Provide plain steel bars with threaded ends meeting ASTM A307, Grade A.

#### 32 1074-4 HARDWARE FOR TIMBER STRUCTURES

33 Use machine bolts, drift-bolts and dowels that are either wrought iron or medium steel. Use  
 34 washers that are cast iron ogee, malleable iron castings or cut from medium steel or wrought  
 35 iron plate.

36 Use machine bolts with square heads and nuts. Use nails that are cut or round wire of  
 37 standard form. Use spikes that are cut, wire spikes or boat spikes.

38 Use black or galvanized nails, spikes, bolts, dowels, washers and lag screws for untreated  
 39 timber.

40 Galvanize or cadmium plate all hardware for treated timber bridges, except malleable iron  
 41 connectors.