

Appendix B

Comprehensive Transportation Plan Definitions

This appendix contains descriptive information and definitions for the designations depicted on the CTP maps shown in Figure 1.

Highway Map

The "[NCDOT Facility Type –Control of Access Definitions](#)" document provides a visual depiction of facility types for the following CTP classification.

Facility Type Definitions

❖ **Freeways**

- Functional purpose – high mobility, high volume, high speed
- Posted speed – 55 mph or greater
- Cross section – minimum four lanes with continuous median
- Multi-modal elements – High Occupancy Vehicles (HOV)/High Occupancy Transit (HOT) lanes, busways, truck lanes, park-and-ride facilities at/near interchanges, adjacent shared use paths (separate from roadway and outside ROW)
- Type of access control – full control of access
- Access management – interchange spacing (urban – one mile; non-urban – three miles); at interchanges on the intersecting roadway, full control of access for 1,000ft or for 350ft plus 650ft island or median; use of frontage roads, rear service roads
- Intersecting facilities – interchange or grade separation (no signals or at-grade intersections)
- Driveways – not allowed

❖ **Expressways**

- Functional purpose – high mobility, high volume, medium-high speed
- Posted speed – 45 to 60 mph
- Cross section – minimum four lanes with median
- Multi-modal elements – HOV lanes, busways, very wide paved shoulders (rural), shared use paths (separate from roadway but within ROW)
- Type of access control – limited or partial control of access;
- Access management – minimum interchange/intersection spacing 2,000ft; median breaks only at intersections with minor roadways or to permit U-turns; use of frontage roads, rear service roads; driveways limited in location and number; use of acceleration/deceleration or right turning lanes
- Intersecting facilities – interchange; at-grade intersection for minor roadways; right-in/right-out and/or left-over or grade separation (no signalization for through traffic)
- Driveways – right-in/right-out only; direct driveway access via service roads or other alternate connections

❖ **Boulevards**

- Functional purpose – moderate mobility; moderate access, moderate volume, medium speed
- Posted speed – 30 to 55 mph
- Cross section – two or more lanes with median (median breaks allowed for U-turns per current NCDOT *Driveway Manual*)
- Multi-modal elements – bus stops, bike lanes (urban) or wide paved shoulders (rural), sidewalks (urban - local government option)
- Type of access control – limited control of access, partial control of access, or no control of access
- Access management – two lane facilities may have medians with crossovers, medians with turning pockets or turning lanes; use of acceleration/deceleration or right turning lanes is optional; for abutting properties, use of shared driveways, internal out parcel access and cross-connectivity between adjacent properties is strongly encouraged
- Intersecting facilities – at grade intersections and driveways; interchanges at special locations with high volumes
- Driveways – primarily right-in/right-out, some right-in/right-out in combination with median leftovers; major driveways may be full movement when access is not possible using an alternate roadway

❖ **Other Major Thoroughfares**

- Functional purpose – balanced mobility and access, moderate volume, low to medium speed
- Posted speed – 25 to 55 mph
- Cross section – four or more lanes without median (*US and NC routes may have less than four lanes*)
- Multi-modal elements – bus stops, bike lanes/wide outer lane (urban) or wide paved shoulder (rural), sidewalks (urban)
- Type of access control – no control of access
- Access management – continuous left turn lanes; for abutting properties, use of shared driveways, internal out parcel access and cross-connectivity between adjacent properties is strongly encouraged
- Intersecting facilities – intersections and driveways
- Driveways – full movement on two lane roadway with center turn lane as permitted by the current NCDOT *Driveway Manual*

❖ **Minor Thoroughfares**

- Functional purpose – balanced mobility and access, moderate volume, low to medium speed
- Posted speed – 25 to 55 mph
- Cross section – ultimately three lanes (no more than one lane per direction) or less without median
- Multi-modal elements – bus stops, bike lanes/wide outer lane (urban) or wide paved shoulder (rural), sidewalks (urban)
- ROW – no control of access

- Access management – continuous left turn lanes; for abutting properties, use of shared driveways, internal out parcel access and cross-connectivity between adjacent properties is strongly encouraged
- Intersecting facilities – intersections and driveways
- Driveways – full movement on two lane with center turn lane as permitted by the current NCDOT *Driveway Manual*

Other Highway Map Definitions

- ❖ **Existing** – Roadway facilities that are not recommended to be improved.
- ❖ **Needs Improvement** – Roadway facilities that need to be improved for capacity, safety, operations, or system continuity. The improvement to the facility may be widening, increasing the level of access control along the facility, operational strategies (including but not limited to traffic control and enforcement, incident and emergency management, and deployment of Intelligent Transportation Systems (ITS) technologies), or a combination of improvements and strategies. “Needs improvement” does not refer to the maintenance needs of existing facilities or the replacement or rehab of structures.
- ❖ **Recommended** – Roadway facilities on new location that are needed in the future.
- ❖ **Interchange** – Through movement on intersecting roads is separated by a structure. Turning movement area accommodated by on/off ramps and loops.
- ❖ **Grade Separation** – Through movement on intersecting roads is separated by a structure. There is no direct access between the facilities.
- ❖ **Full Control of Access** – Connections to a facility provided only via ramps at interchanges. No private driveway connections allowed.
- ❖ **Limited Control of Access** – Connections to a facility provided only via ramps at interchanges (major crossings) and at-grade intersections (minor crossings and service roads). No private driveway connections allowed.
- ❖ **Partial Control of Access** – Connections to a facility provided via ramps at interchanges, at-grade intersections, and private driveways. Private driveway connections shall be defined as a maximum of one connection per parcel. One connection is defined as one ingress and one egress point. These may be combined to form a two-way driveway (most common) or separated to allow for better traffic flow through the parcel. The use of shared or consolidated connections is highly encouraged.
- ❖ **No Control of Access** – Connections to a facility provided via ramps at interchanges, at-grade intersections, and private driveways.

Public Transportation and Rail Map

- ❖ **Bus Routes** – The primary fixed route bus system for the area. Does not include demand response systems.
- ❖ **Fixed Guideway** – Any transit service that uses exclusive or controlled rights-of-way or rails, entirely or in part. The term includes heavy rail, commuter rail, light rail,

monorail, trolleybus, aerial tramway, included plane, cable car, automated guideway transit, and ferryboats.

- ❖ **Operational Strategies** – Plans geared toward the non-single occupant vehicle. This includes but is not limited to HOV lanes or express bus service.
- ❖ **Rail Corridor** – Locations of railroad tracks that are either active or inactive tracks. These tracks were used for either freight or passenger service.
 - Active – rail service is currently provided in the corridor; may include freight and/or passenger service
 - Inactive – right of way exists; however, there is no service currently provided; tracks may or may not exist
 - Recommended – It is desirable for future rail to be considered to serve an area.
- ❖ **High Speed Rail Corridor** – Corridor designated by the U.S. Department of Transportation as a potential high speed rail corridor.
 - Existing – Corridor where higher-speed rail service (over 79 mph) is provided or a corridor that is officially designated by FRA to run higher speed trains in the future. There is currently one federally designated high-speed rail corridor in North Carolina - The Southeast High Speed Rail Corridor.
 - Recommended – Proposed corridor for higher speed rail service.
- ❖ **Rail Stop** – A railroad station or stop along the railroad tracks.
- ❖ **Multimodal Connector** - A location where more than one mode of transportation meet such as where light rail and a bus route come together in one location. (NOTE- intermodal refers to two or more modes that transfer the same cargo unit-like 40' shipping container from ship to train or truck); multimodal is the transfer of people/cargo between two or more modes and in NC is used in public transit settings i.e. Charlotte Multimodal Station)
- ❖ **Park and Ride Lot** – A strategically located parking lot that provides commuters connections to transit or carpools.
- ❖ **Existing Grade Separation** – Locations where existing rail facilities are physically separated from existing highways or other transportation facilities. These may be bridges, culverts, or other structures.
- ❖ **Proposed Grade Separation** – Locations where rail facilities are recommended to be physically separated from existing or recommended highways or other transportation facilities. These may be bridges, culverts, or other structures.

Bicycle Map

- ❖ **On Road-Existing** – Conditions for bicycling on the highway facility are adequate to safely accommodate cyclists.
- ❖ **On Road-Needs Improvement** – At the systems level, it is desirable for an existing highway facility to accommodate bicycle transportation; however, highway improvements are necessary to create safe travel conditions for the cyclists.

- ❖ **On Road-Recommended** – At the systems level, it is desirable for a **recommended** highway facility to accommodate bicycle transportation. The highway should be designed and built to safely accommodate cyclists.
- ❖ **Off Road-Existing** – A facility that accommodates only bicycle transportation and is physically separated from a highway facility either within the right-of-way or within an independent right-of-way.
- ❖ **Off Road-Needs Improvement** – A facility that accommodates only bicycle transportation and is physically separated from a highway facility either within the right-of-way or within an independent right-of-way that will not adequately serve future bicycle needs. Improvements may include but are not limited to, widening, paving (not re-paving or other maintenance activities), and improved horizontal or vertical alignment.
- ❖ **Off Road-Recommended** – A facility needed to accommodate only bicycle transportation and is physically separated from a highway facility either within the right-of-way or within an independent right-of-way.
- ❖ **Multi-use Path-Existing** – An existing facility physically separated from motor vehicle traffic that is either within the highway right-of-way or on an independent right-of-way that serves bicycle and pedestrian traffic. Sidewalks should not be designated as a multi-use path.
- ❖ **Multi-use Path-Needs Improvement** – An existing facility physically separated from motor vehicle traffic that is either within the highway right-of-way or on an independent right-of-way that serves bicycle and pedestrian traffic that will not adequately serve future needs. Improvements may include but are not limited to, widening, paving (not re-paving or other maintenance activities), and improved horizontal or vertical alignment. Sidewalks should not be designated as a multi-use path.
- ❖ **Multi-use Path-Recommended** – A facility physically separated from motor vehicle traffic that is either within the highway right-of-way or on an independent right-of-way that is needed to serve bicycle and pedestrian traffic. Sidewalks should not be designated as a multi-use path.
- ❖ **Existing Grade Separation** – Locations where existing “Off Road” facilities and “Multi-use Paths” are physically separated from existing highways, railroads, or other transportation facilities. These may be bridges, culverts, or other structures.
- ❖ **Proposed Grade Separation** – Locations where “Off Road” facilities and “Multi-use Paths” are recommended to be physically separated from existing or recommended highways, railroads, or other transportation facilities. These may be bridges, culverts, or other structures.

Pedestrian Map

- ❖ **Sidewalk-Existing** – Paved paths (including but not limited to concrete, asphalt, brick, stone, or wood) on both sides of a highway facility and within the highway right-of-way that are adequate to safely accommodate pedestrian traffic.
- ❖ **Sidewalk-Needs Improvement** – Improvements are needed to provide paved paths on both sides of a highway facility. The highway facility may or may not need improvements. Improvements do not include re-paving or other maintenance activities but may include: filling in gaps, widening sidewalks, or meeting ADA (Americans with Disabilities Act) requirements.
- ❖ **Sidewalk-Recommended** – At the systems level, it is desirable for a recommended highway facility to accommodate pedestrian transportation **or** to add sidewalks on an existing facility where no sidewalks currently exist. The highway should be designed and built to safely accommodate pedestrian traffic.
- ❖ **Off Road-Existing** – A facility that accommodates only pedestrian traffic and is physically separated from a highway facility usually within an independent right-of-way.
- ❖ **Off Road-Needs Improvement** – A facility that accommodates only pedestrian traffic and is physically separated from a highway facility usually within an independent right-of-way that will not adequately serve future pedestrian needs. Improvements may include but are not limited to, widening, paving (not re-paving or other maintenance activities), improved horizontal or vertical alignment, and meeting ADA requirements.
- ❖ **Off Road-Recommended** – A facility needed to accommodate only pedestrian traffic and is physically separated from a highway facility usually within an independent right-of-way.
- ❖ **Multi-use Path-Existing** – An existing facility physically separated from motor vehicle traffic that is either within the highway right-of-way or on an independent right-of-way that serves bicycle and pedestrian traffic. Sidewalks should not be designated as a multi-use path.
- ❖ **Multi-use Path-Needs Improvement** – An existing facility physically separated from motor vehicle traffic that is either within the highway right-of-way or on an independent right-of-way that serves bicycle and pedestrian traffic that will not adequately serve future needs. Improvements may include but are not limited to, widening, paving (not re-paving or other maintenance activities), and improved horizontal or vertical alignment. Sidewalks should not be designated as a multi-use path.
- ❖ **Multi-use Path-Recommended** – A facility physically separated from motor vehicle traffic that is either within the highway right-of-way or on an independent right-of-way that is needed to serve bicycle and pedestrian traffic. Sidewalks should not be designated as a multi-use path.

- ❖ **Existing Grade Separation** – Locations where existing “Off Road” facilities and “Multi-use Paths” are physically separated from existing highways, railroads, or other transportation facilities. These may be bridges, culverts, or other structures.
- ❖ **Proposed Grade Separation** – Locations where “Off Road” facilities and “Multi-use Paths” are recommended to be physically separated from existing or recommended highways, railroads, or other transportation facilities. These may be bridges, culverts, or other structures.