

Description	Range of Values	Points Project 1	Points Project 2	Points Project 3	Points Project 4	Points Project 5
PCR	Zero pts for PCR less than 65, 10 points if 65 to 75, 20 if 75 to 90, zero if above 90.					
Length (miles)	1 pt if less than 1 mile, 2 pts if 1 to 3 miles, and 5 pts if longer than 3 miles.					
AADT	1 pt if less than 1000, 5 pts if 1000 to 10000, and 10 pts if greater than 10000.					
Funds Leveraged	1 pt if less than 10% from other sources, 5 pts if 10 to 50%, 10 pts if more than 50%.					
Division Priority	1 pt if more than third priority, 5 points if second or third priority, and 10 points for top priority within division.					
Total P&I						

Table A: Form for Preservation and Impact calculation for 5 projects.

Distress	Range	Points Project 1	Points Project 2	Points Project 3	Points Project 4	Points Project 5
# Shattered Slabs per mile	No points if more than 10, 5 pts if 5 to 9, and 10 points if greater than zero and less than 5.					
# Corner Breaks per mile	No points if more than 10, 5 points if 5 to 9 and 10 points if 1 to 5.					
Faulting	No points if more than 0.5", 5 pts if 0.25 to 0.5", and 10 points if faulting is more than 0.1 but less than 0.25".					
Joint Condition	No points if good, 2 points if fair, and 5 points if poor.					
Spalling (% of slabs needing repair)	No points if more than 20%, 2 points if 10 to 20%, and 5 points if 1 to 10%.					
Slab leveling (total # of slabs needing treat.)	1 Point if more than 20 slabs, 2 pts if 10 to 20 slabs, and 5 points if 1 to 9 slabs.					
Sub slab Stabilization	1 Point if more than 20 slabs, 2 pts if 10 to 20 slabs, and 5 points if 1 to 9 slabs.					
Total Rigid Pavement Technical Points:						

Table B: form for concrete pavement technical scoring.

Distress	Range	Points Project 1	Points Project 2	Points Project 3	Points Project 4	Points Project 5
Alligator Cracking	Zero points if more than 40% low or moderate or more than 10% severe. 5 points if 30 to 40% low or moderate or 10% severe. 10 points if less than 30% low or moderate cracking.					
Rutting	Zero points if greater than 0.75"; 5 points if 0.5 to 0.75", and 10 points >0.1 but less than 0.5".					
Transverse or Reflection Cracking	1 point if greater than 1" wide, 5 points if 0.5 to 1.0" wide, and ten points if 0.25" to 0.5" wide.					
Ride Quality or IRI	2 points if very rough, 5 points if rough and 10 points if good but could be improved.					
Surface Issues	5 points if less than 5% of surface area is affected, 2 points if 5 to 10%, and 1 point if more than 10%.					
Oxidation	Zero points if none or new; 3 points if intermediate; 5 points if severe.					
Total Flexible Pavement Technical Points						

Table C: Form for comparing technical scores for five proposed flexible pavements.