

UNIT 4 - PAVEMENT MARKERS

ASSIGNMENT

Study 1250.01 thru 1253.01 of the Roadway Standard Drawings. Answer review questions. Take and pass the written test.

KEY POINTS

Markers are generally not required along edge lines. When used, they shall be spaced 20 feet apart and offset two inches from the edge line on the traffic side.

Pavement markers shall not be placed directly on pavement marking lines.

Pavement markers are not required along mini-skip lines in tapers.

For raised pavement markers, the minimum area of each reflective lens shall be two square inches.

REVIEW QUESTIONS

1) Are pavement markers required along edge lines?

YES NO

2) Pavement markers shall be placed directly on pavement marking lines.

TRUE FALSE

3) Are pavement markers required along mini-skip lines in tapers?

YES NO

4) What is the minimum area of each reflective lens?

_____ square inches

5) When the speed limit is greater than 45 mph, what is the typical spacing along tangent sections of highway?

_____ feet

6) What is the typical spacing along gore lines?

_____ feet

7) Should the typical spacing be reduced because of ambient light?

YES NO

ANSWERS TO REVIEW QUESTIONS

- 1) No (1250.01, sheet 1 of 3 of the Roadway Standard Drawings)
- 2) False (1250.01, sheet 1 of 3 of the Roadway Standard Drawings)
- 3) No (1250.01, sheet 1 of 3 of the Roadway Standard Drawings)
- 4) Two square inches (1251.01, sheet 1 of 1 of the Roadway Standard Drawings)
- 5) 80 feet (1250.01, sheet 1 of 3 of the Roadway Standard Drawings)
- 6) 20 feet (1250.01, sheet 1 of 3 of the Roadway Standard Drawings)
- 7) Yes (1250.01, sheet 1 of 3 of the Roadway Standard Drawings)