



# SlurryPro® CDP™

## Physical Data:

Appearance: Opaque to White free flowing granular solid  
 Odor: Odorless.  
 pH: NA  
 Freeze Point: NA  
 Specific Gravity: 1.00-1.01 (Water = 1.0)

## Description & Function:

The SlurryPro® CDP™ system is designed for preparation of viscous earth-stabilizing fluids or slurries to stabilize even the most challenging soil environments in a variety of excavation techniques including drilling, trenching, tunneling and diaphragm wall applications in the geoconstruction industry.

## General Application Instructions:

KB recommends CDP initially be mixed at a around a rate of 0.75 to 1.25 kg/m<sup>3</sup> of fresh water or water pretreated with ProTek™ 100. For larger projects this should be done in a properly designed mixing tank, please see KB's "Mix Tank Diagram" for specifics. Many contractors find they can start with lower dosages and adjust as required for stability. On smaller projects or highly mobile projects, such as power lines, CDP may be applied at the point of excavation. Typical product consumption rates are suggested to be as follows, again many contractors find less is acceptable:

Formation Type	Suggested SlurryPro CDP Initial Dosage			Typical Marsh Funnel Visc.
	lbs/yd <sup>3</sup>	lbs/1000 gals	kg/m <sup>3</sup>	
Clay & Shale	1.687-2.109	8.345-10.432	1.0-1.25+	60-75±
Silt & Fine to Medium Sand	1.687-2.531	8.345-12.518	1.0-1.5+	65-100±
Coarse Sand to Pea Gravel	2.025-3.037	10.014-15.022	1.2-1.8+	75-100±
Gravel to Cobbles	2.109-3.375	10.432-16.691	1.25-2.0+	85-100+

Formation Type	Suggested SlurryPro CDP Refreshment Dosage			Typical Marsh Funnel Visc.
	lbs/yd <sup>3</sup>	lbs/1000 gals	kg/m <sup>3</sup>	
Clay & Shale	1.012-1.519	5.007-7.511	0.6-0.9+	60-75±
Silt & Fine to Medium Sand	1.181-1.687	5.842-8.345	0.7-1.0+	65-100±
Coarse Sand to Pea Gravel	1.266-2.025	6.259-10.014	0.75-1.2+	75-100±
Gravel to Cobbles	1.266-2.109	6.259-10.432	0.75-1.25+	85-100+

Additional CDP may also be introduced at the point of excavation through a KB Eductor or into the mix tank or agitated slurry storage tanks. The addition of small quantities of CDP at the hole provides the following benefits: rapid increase in viscosity to stabilize highly permeable soils and immediate intervention in case of emergencies or other atypical situations. When adding SlurryPro CDP at the point of excavation, please pour CDP slowly into a KB Eductor feeding into an adequately flowing stream of slurry emptying into the excavation. SlurryPro CDP may also be added directly to the stream of fluid flowing into a pile while the excavation tool is one meter (3 feet) below the surface of the slurry and rotating to form a vortex within the slurry column. Avoid clumping the dry CDP into "white gel balls" in the slurry by slowly sifting product into the fluid stream. Feeding CDP too quickly with lack of proper agitation causes balling of the polymer particles into "fish eyes" and larger polymer masses wasting CDP. After adding CDP to the any excavation, raise and lower the excavation tool from the top of the hole to the bottom to assist in proper distribution of the product throughout the slurry column. The slurry viscosity within the excavation should never be allowed to drop below 55 seconds per quart regardless of what type of soil is being excavated.

be done in the mixing tank and not at the point of slurry entrance into the next excavation. At least one sedimentation tank is always recommended for recaptured slurry to pass through prior to the mix tank and the re-addition of CDP. The dosage rate of the SlurryPro CDP synthetic polymer in the initial make-up water should err on the side of caution and use the higher levels recommended in the dosage chart. Only after the slurry has been established and a secure dosage and viscosity obtained should the dosage be reduced.

When excavating in more challenging formations, appropriate slurry Additives are recommended in combination with a SlurryPro system to increase slurry stabilization performance. The more challenging the formation type the more benefit will be realized from various SlurryPro Specialty Additives. Unusual site conditions may arise during actual excavation, in which case the recommendations from KB technical personnel must always be followed.

## Special Operational Precautions and Instructions:

It is suggested from experience, the specific gravity of a SlurryPro CDP fluid should not exceed 1.04 under normal operating conditions. If low hydrostatic conditions are encountered where the water table is less than 3 meters or 10 feet beneath the slurry level, the specific gravity of the slurry should be increased as required using WeightIt to raise the slurry S.G. accordingly.

Due to the unique characteristics of a KB Earth Stabilization System as compared to bentonite, several key operational procedures are recommended to be modified from bentonite systems. These modifications will have a major impact on the overall effectiveness and successful use of KB International's Earth Stabilization Systems. For smaller projects, please consult KB International's "General Operating, Product Addition, and Testing Procedures." For larger or more complicated projects, please contact KB International for specific project planning.

## Packaging:

10 kilo / 22 lb. resealable plastic pails & 25 kilo / 55 lb. poly bags

## Availability:

SlurryPro CDP is available out of KB International's Charleston, SC warehouse and various other regional warehouses. Please check for availability in your area.



**KB International LLC • 735 Broad Street, Suite 209 • Chattanooga, TN 37402**  
**Phone: 1 (423) 266-6964 • Fax: 1 (832) 201-9196 • email: info@kbtech.com • www.kbtech.com**

The information in this document is given in good faith and is accurate to the best of our knowledge. Because we can neither anticipate nor control the different conditions under which this information and our products are used, we make no warranty of performance or this estimate expressed or implied. Typical properties given herein are not specifications. Our policy is to continually review historical site data, product formulations and manufacturing to assure technical suitability and cost-effectiveness. Product characteristics are subject to change without notice. Users of our products are responsible for compliance with government regulations and patent laws. The Synthetic Slurry Systems and Products are covered by the following US Patent's, 5,407,909; 5,663,123; 6,248,697; and 6,897,186 and various corresponding International patents. Other U.S. and International patents pending. All users should discuss the product with an appropriate representative of KB International, LLC before utilizing the product. SlurrySMART®, HydroCUT®, SlurryShield®, SlurryPro®, HydroCUT®, EnhancIT®, SeaDrill®, SandSeal®, and InstaFreeze® are all registered trademarks of KB International LLC.