

# Hanes Geogrid

Geogrid and Direction (MD, CD)	Polymer (PET, HDPE, PP)	Aperture Size (inches)	T <sub>ult</sub> <sup>1</sup> (lb/ft)	T <sub>2%</sub> <sup>1</sup> (lb/ft)	T <sub>5%</sub> <sup>1</sup> (lb/ft)	X <sub>jave</sub> <sup>1</sup> (lb)	J <sup>1</sup> (m-N/deg)	RF <sub>CR</sub>			RF <sub>D</sub>
								3-yr	75-yr	100-yr	
EGRID2020 (MDxCD)	PP	1.6x1.6	1370x1370	520x520	1045x1045	1300x1300					
Geogrid and Direction (MD, CD)	<b>Borrow (<math>\phi = 30^\circ</math>)</b>										
	RF <sub>ID</sub>	RF			T <sub>al</sub> (lb/ft)			C <sub>i</sub>	F*	C <sub>ds</sub>	$\rho$ (deg)
		3-yr	75-yr	100-yr	3-yr	75-yr	100-yr				
EGRID2020 (MDxCD)							0.67	0.38	0.67	21	
Geogrid and Direction (MD, CD)	<b>Fine Aggregate (<math>\phi = 34^\circ</math>)</b>										
	RF <sub>ID</sub>	RF			T <sub>al</sub> (lb/ft)			C <sub>i</sub>	F*	C <sub>ds</sub>	$\rho$ (deg)
		3-yr	75-yr	100-yr	3-yr	75-yr	100-yr				
EGRID2020 (MDxCD)							0.67	0.45	0.67	24	
Geogrid and Direction (MD, CD)	<b>Coarse Aggregate (<math>\phi = 38^\circ</math>)</b>										
	RF <sub>ID</sub>	RF			T <sub>al</sub> (lb/ft)			C <sub>i</sub>	F*	C <sub>ds</sub>	$\rho$ (deg)
		3-yr	75-yr	100-yr	3-yr	75-yr	100-yr				
EGRID2020 (MDxCD)							0.67	0.52	0.67	27	

<sup>1</sup> “Minimum Average Roll Values” (MARV) in accordance with ASTM D4439

Where,

T<sub>ult</sub> = wide width tensile strength @ ultimate (lb/ft),

T<sub>2%</sub> = wide width tensile strength @ 2% strain (lb/ft),

T<sub>5%</sub> = wide width tensile strength @ 5% strain (lb/ft),

X<sub>jave</sub> = average junction strength per rib (lb),

J = aperture stability modulus (m-N/deg),

RF<sub>CR</sub> = creep reduction factor for 3, 75 and 100-yr design life,

RF<sub>D</sub> = durability (degradation) reduction factor,

RF<sub>ID</sub> = installation damage reduction factor,

RF = (RF<sub>CR</sub> × RF<sub>ID</sub>) for 3-yr design life or (RF<sub>CR</sub> × RF<sub>D</sub> × RF<sub>ID</sub>) for 75 and 100-yr design life,

T<sub>al</sub> = short-term design strength for 3-yr design life or LTDS for 75 and 100-yr design life (lb/ft) = T<sub>ult</sub> / RF,

C<sub>i</sub> = coefficient of interaction,

F\* = pullout resistance factor = C<sub>i</sub> tan  $\phi$  ,

C<sub>ds</sub> = coefficient of direct sliding and

tan  $\rho$  = soil-geogrid friction angle (deg) = C<sub>ds</sub> tan  $\phi$  .