

SAMPLE REQUIREMENTS

Category	Sub-Category	Sample Quantity
Asphalt	Anti-Strip Additives	One half quart of raw product, one quart raw PG64-22 binder with COA, two quarts blended binder dosed at 0.5% and 0.75% sent to NCDOT. Three TSR pills of blended at 0.25%/0.5%/0.75% made with same source of the one quart PG64-22 sent to accredited 3 rd party lab with results submitted to PEP.
Asphalt	Binder Grade Modifiers	One half quart of raw product, two quarts raw PG64-22 binder, two quarts blended binder
Asphalt	Emulsion Additives	One gallon
Asphalt	Non-Tracking Tack Coats	One gallon
Asphalt	Patching	5 pounds
Asphalt	Polymer Additives	One half quart of raw product, two quarts raw PG64-22 binder, two quarts blended binder
Asphalt	Prime Coats	One gallon
Asphalt	Rejuvenator Additives	One half quart of raw product, two quarts raw PG64-22 binder, two quarts blended binder
Asphalt	Warm Mix Asphalt Additives	One half quart of raw product, one quart raw PG64-22 binder with COA, two quarts blended binder dosed at 0.5% and 0.75%
Admixtures	Latex Modifier	1 gallon
Admixtures	Fiber Additives	6 feet of fiber chord
Concrete and Concrete Patching Materials	Concrete and Concrete Patching Materials	1 bag
Grouts - Packaged	Type 1, 2, 3, 4 & Other	1 package (min. 20 lbs, not to exceed 100 lbs)
Grouts - Packaged	Type 5	Enough to make 6 – 6x12 inch cylinders
Epoxies	All Epoxy Sub-Categories	See Epoxy Checklist
Paints	All Paint Sub-Categories	Minimum 1 quart of each component
Curing Compounds	All Curing Compound Sub-Categories	See Curing Compound Checklist