NOTES


THE BARRIER RAIL IN EACH SPAN SHALL NOT BE CAST UNTIL ALL SLAB CONCRETE IN THAT SPAN HAS BEEN CAST AND HAS REACHED A MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI.

WHEN FOAM JOINT SEAL IS REQUIRED, THE JOINT IN THE DECK SHALL BE SAWED PRIOR TO THE CASTING OF VERTICAL CONCRETE BARRIER RAIL.

ALL REINFORCING STEEL IN BARRIER RAILS SHALL BE EPOXY COATED.

THE #5 S3 & S4 BARS SHALL BE INSTALLED, USING AN ADHESIVE ANCHORING SYSTEM, AFTER SAWING THE JOINT. THE YIELD LOAD FOR THE #5 S3 & S4 BARS IS 18.6 KIPS. FIELD TESTING FOR THE ADHESIVE BONDING SYSTEM IS NOT REQUIRED.

GROOVED CONTRACTION JOINTS, $\frac{1}{2}$ " IN DEPTH, SHALL BE TOOLED IN ALL EXPOSED FACES OF THE BARRIER RAIL AND IN ACCORDANCE WITH ARTICLE 825-10(B) OF THE STANDARD SPECIFICATIONS. THE CONTRACTION JOINT SHALL BE LOCATED AT EACH THIRD POINT BETWEEN BARRIER RAIL EXPANSION JOINTS. ONLY ONE CONTRACTION JOINT IS REQUIRED AT MIDPOINT OF BARRIER RAIL SEGMENTS LESS THAN 20 FEET IN LENGTH AND NO CONTRACTION JOINTS ARE REQUIRED FOR THOSE SEGMENTS LESS THAN 10 FEET IN LENGTH.



BAR TYPES 10" (1)2


ALL BAR DIMENSIONS ARE OUT TO OUT

BILL OF MATERIAL FOR VERTICAL CONCRETE BARRIER RAIL ONLY BAR NO. SIZE TYPE LENGTH WEIGHT * B1 #5 STR * S1 #5 | 1 * S2 #5 2 7'-2" * S3 #5 STR 4'-0" #5 STR 3'-6" * S4

* EPOXY COATED

REINFORCING STEEL CLASS AA CONCRETE CU. YDS CONCRETE BARRIER RAIL LIN. FT

SECTION THRU RAIL



ELEVATION AT EXPANSION JOINTS

BARRIER RAIL DETAILS

PROJECT NO. COUNTY STATION:_

> STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH

> > STANDARD

VERTICAL CONCRETE BARRIER RAIL

	REVISIONS						SHEET NO.
DOCUMENT NOT CONSIDERED	NO.	BY:	DATE:	NO.	BY:	DATE:	
FINAL UNLESS ALL	1			3			TOTAL SHEETS
SIGNATURES COMPLETED	2			4			

END OF RAIL DETAILS

FOR ADHESIVE ANCHORING AT SAWED JOINTS

ASSEMBLED BY : CHECKED BY : DATE : MAA/GM MAA/THC MAA/THC DRAWN BY: MAA 5/10 CHECKED BY: GM 5/10

11/28/2023 \\DOT\DFSRoo+01\Groups-SDCC\Share\Structures Standards\Standards English 2024\2024 DGN\CBR2.dgn BBARODAWALA

STD. CBR2